VS Code for table-image-icl

A one-screen cheat sheet. Keys are for a Mac: `⌘` command, `⌥` option, `⇧` shift, `^` control, `fn` the key bottom-left.

> **The F-keys on a MacBook.** The top row controls brightness and volume unless you hold `fn`, so "F12" means `fn F12`. Two ways around it: *System Settings → Keyboard → Keyboard Shortcuts → Function Keys → "Use F1, F2, etc. keys as standard function keys"* makes them plain F-keys; or skip them entirely, every F-key below has a non-F alternative on the same line.

Open things

`⌘P`	Quick open a file by name. Then `@` a symbol in that file, `:` a line number, `#` a symbol anywhere in the repo
`⇧⌘O`	Symbols in the current file (classes and functions); start typing to filter
`⌘T`	Symbols across the repo: type `LabelRead` from anywhere
`⇧⌘F`	Search text in every file; `⌘F` in the current one
`⌘B`	Hide and show the sidebar; `⌘J` the bottom panel (terminal, problems, output)
`^\``	Terminal; `⌘\` splits the editor; `^Tab` cycles open tabs
`⇧⌘P`	Command palette: every command by name ("CodeTour: Start Tour", "Toggle Editor Sticky Scroll")

Jump around code (Pylance)

`fn F12` or `⌘ click`	Go to definition. Works into torch and tabicl too
`⌥ fn F12` or right-click → Peek Definition	Peek the definition in a box without leaving the file; Escape closes it
`⇧ fn F12` or right-click → Go to References	Every place the name is used
`^−` / `^⇧−`	Back to where you were / forward again. The key after a jump
`⇧⌥H`	Call hierarchy: who calls this, what it calls
`⇧⌘.`	Focus the breadcrumb bar above the editor; arrows walk the file's symbols
`^⌥` held	Hide the grey inlay hints (types, argument names) while pressed
`fn F8` or `⇧⌘M`	Next problem / the Problems panel. Error Lens already prints each one at the end of its line
hover any name	Its signature and docstring; with jaxtyping, the tensor shapes

Edit

`⌘D`	Select the next occurrence of the word under the cursor (repeat to multi-edit)
`⌥↑` / `⌥↓`	Move the line up or down; `⇧⌥↓` copies it
`⌘/`	Comment or uncomment the selection
`⇧⌥F`	Format the file with Ruff; saving sorts the imports
`fn F2`	Rename the symbol everywhere it is used
`⌘K ⌘0` / `⌘K ⌘J`	Fold everything / unfold everything; `⌘⌥[` folds the block at the cursor
`⌘Z` / `⇧⌘Z`	Undo / redo

Tests and the debugger

Testing sidebar (flask icon)	The 131 tests by file. Hover one: ▸ runs it, the bug icon debugs it with `justMyCode` off
click left of a line number	Set a breakpoint (a red dot). Right-click it for a condition such as `b == 1`
`fn F5` or Run → Start Debugging	Run the config chosen in the Run and Debug sidebar (`⇧⌘D`): debug tests, `train.py` for a few CPU steps, or the tour server
`fn F10` / `fn F11` / `⇧ fn F11`	Step over / step into (torch included) / step out; `fn F5` continues
Debug Console	Type `x.shape`, `tokens[0, 0, :4]`, `y_context` while stopped at a breakpoint
Variables pane	Every local with its value; tensors show dtype and shape, click to expand

Notebooks (Jupyter, Data Wrangler)

⇧⏎ / ^⏎	Run the cell and move on / run it in place
Esc then A / B	New cell above / below; M makes it Markdown, Y code, DD deletes it
Variables button (toolbar)	Every array and tensor with its shape. A DataFrame opens in Data Wrangler: a spreadsheet with filters and column stats
Run by Line (toolbar)	Steps through one cell line by line, like a debugger

The tour, inside the editor (CodeTour)

CodeTour icon in the sidebar	The ten tours, one per file, `01 table_image_icl/model.py` first. Click ▸ to start
⌘→ / ⌘←	Next / previous step: the editor scrolls to the lines and shows the note with its source links and test names
Esc	Leave the tour; “Resume Tour” in the panel picks it up where you stopped
the last step	Offers the next file’s tour, so you can walk the whole repo in order

History (GitLens)

end of the current line	Faint text: the commit that last touched the line; hover for the message, which says why
GitLens sidebar → File History	How this file changed over the commits; click one to see the diff
Source Control (^⇧G)	Stage, commit, push; the Graph view shows the branch

Worth knowing

- `.vscode/settings.json` turns on pytest discovery, sticky scroll, breadcrumbs, inlay hints and Ruff for this repo only; `.vscode/launch.json` holds the three debug configs; `.vscode/extensions.json` lists the eight recommended extensions, so a fresh VS Code offers to install them.
- The website tour: `python tour/app.py`, then http://127.0.0.1:8899. The same notes as the CodeTour files, plus the upstream diffs, the shapes and the runnable proofs.
- Pylance’s “standard” type checking flags real mistakes but not every missing annotation; the jaxtyping shapes in model.py are checked at runtime by beartype, so a wrong shape fails on the first call with a message that names the dimension.
- Single-click opens a file in a preview tab that gets replaced by the next one; double-click or ⏎ in Quick Open pins it.
- Print this: ⌘K ⌘R in VS Code opens the official keyboard reference for your platform.