Thesis -> Paper

Benedikt Löw

Abstract

This thesis is being transformed into a paper

1 Introduction

1.1 Motivation and Research Context

The mean-variance framework introduced by Markowitz [1952] has shaped capital allocation for over seven decades, yet its core assumptions of stable correlations and reliable parameter estimates break down in exactly the conditions where diversification is meant to help. During market declines, correlations among S&P 500 constituents rise well above their upside levels, an asymmetry that erodes the diversification the framework is built to deliver precisely when protection matters most [Ang and Chen 2002].

2 Research Question

To what extent do classical and machine learning portfolio construction approaches deliver risk-adjusted outperformance and drawdown resilience across crisis episodes, and can regime detection improve them?

Sub questions:
1. How do MVO, HRP, XGB, RF and LSTM perform against market-cap weighted benchmarks, over the full sample and within crisis episodes?
2. Are the results robust to monthly, quarterly and yearly rebalancing?
3. How accurately and how early do changepoint, HMM and clustering detectors identify crisis episodes?
4. Does moving to T-bills in detected crises improve each approach, and is any gain due to timing rather than lower average equity exposure?
5. Does a regime-switched combination (ML in calm, HRP in crisis) outperform each approach alone and a static mix of both?

3 Methodology

3.1 Time Frame

- 28 years, January 1998 untill December 2025

3.2 Rebalancing

- Rebalancing Schedule 3x, monthly, quarterly, yearly - if non trading day, next day in the month/year

3.3 Weight Constraints

- 1% min and 10% maximum allocation per stock per rebalancing date. - Intra rebalancing drift can exceed 10%

3.4 Lookback Windows

- 60 month calculation window for HRP and MVO - Fixed 60 month lookback window for all Machine Learning models | 24 month validation | + 1, 3, 12 month embargo

3.5 Coverage and Missing Data

- price data of min. 50% given, otherwise excluded - 5 days forward filled, otherwise missing values

3.6 Transaction Cost

- 0bps, 10bps, 20bps calculated. 10bps standard transaction cost - Turnover is getting calculated and reported

3.7 Point-in-Time

- Everything is point in time only

3.8 Features

-

4 Regime Implementation

4.1 Changepoint Detection

4.1.1 Step 1

- daily VIX log changes - k-means clustering and mood rank test. is the spread of teh data after k different from before k? -> keeps the largest test statistic - if that maximum exceeds a threshold, it raises an alarm on day t (detection date). the k with the largest statistic becomes teh estimated break date t, search restarts from there - ARL0 = 10000 - Mood test uses ranks, it assumes no distribution and it reacts to changes in volatility

4.1.2 Step 2

- estimate teh volatility once - each detection day t, an EWMA (λ = 0.95) of squared S&P 500 returns from t det to t gives the new regime's annualised volatility o. Always SPY returns, because 20% annual volatility is from there - Freeze it. o stays constant until the new detection. That is why your chart has steps and late exits: calm returns only after a new break is detected and the new segment's vol is below 20%. - Map it to a score: $p_{\text{crisis}} = \Phi((\sigma - 0.20)/0.05)$, where Φ is the standard normal CDF. So o = 15% gives 0.16, 20% gives 0.50, 25% gives 0.84 and etc. - shift by one day. the value on day d uses data only through d-1, which mathces the paper's one day implementation delay

4.2 Hidden Markov Model

4.2.1 Step 1

- daily log return of S&P 500 - states follow a markov chain. false L holds the probabilities of staying in each state - never the state, only returns. the model infers the state from how well each day's return fits each state's distribution - crisis is defined as teh state with teh hgher o.

4.2.2 Step 2

- on the first 260 days, the parameters mu, o, false L are estimated by maximum likelihood

4.2.3 Step 3

- update parameters daily - Each new return moves the parameters one small step toward what fits recent data best. - Older days are down-weighted by $\lambda = 1 - 1/260$, which gives about a one-year memory. - So σ_{calm} and σ_{crisis} drift over time. "Crisis" means high volatility relative to the last year or so, not above a fixed 20%.

4.2.4 Step 4

- $\alpha_t \propto \alpha_{t-1} \cdot \Gamma \cdot P(r_t)$. This is Bayes' rule: - Prior: yesterday's state probabilities, pushed through Γ (regimes tend to persist). - Times the likelihood: how probable today's return is under each state's normal density. - Example: a −3% day is about 4.3 standard deviations under calm but only 1.9 under crisis. That makes it roughly 900 times more likely under crisis, so the probability jumps toward crisis. One quiet day after that barely moves it back, because Γ says crises persist.

4.2.5 Step 5

- $P(S_{t+1}) = \alpha_t \cdot \Gamma$. forecast = p_{crisis} - It is made at the close of d−1 and stored on day d, the same one-day delay as the changepoint files. - MVO and HRP switch to min-variance when it exceeds 0.5. ML uses the value directly.

4.3 Clustering (Wasserstein K-Means)

Wasserstein k-means compares whole monthly return distributions. It sorts past months into two groups by shape, then asks which group the latest month looks more like. p_{crisis} is a relative distance to the two group centres, so it is a score, not a model probability.

4.3.1 Step 1

- turn each month into a point clodu - a window of 21 daily returns becomes a cloud of 21 points. In the main run each point is (S&P log return, VIX log change) - each series is divided by its expanding standard deviation up to the day before the window starts. Without this, VIX changes about 4x as volatile would dominate. Only past data is used - The cloud captures the whole joint distribution: spread, fat tails, skew and how the S&P 500 and VIX move together. A single volatility number captures only the first of these

4.3.2 Step 2

- measure how different the two months are - The wasserstein distnace W2 mathces each point of one cloud to one point of the other so that the total squared distance is as small as possible (hungarian algorithm). $W_2^2 = \frac{1}{21} \min_\pi \sum_i \|X_i - Y_{\pi(i)}\|^2$. Two calm months are close. A calm and a crisis month are far apart becasue the crisis cloud is spread wider.

4.3.3 Step 3

- On the first trading day of each month, k-means with K=2 runs on all windows that end before that day. Windows slide by 1 day, and the history expands - Each cluster's centre is a medoid: the actual window with the smalles total distance to the other windows in its cluster. - it starts with k-means ++ (10 restarts), then alternates assigning windows to the nearest centre and updating the medoids until the asignments stop changing. - the crisis cluster is the one whose windows have the higher average S&P variance

4.3.4 Step 4

- score each day - on day d, the window ending d-1 is compared with both centres: $p_{\text{crisis}} = W_2(\text{calm})^2/(W_2(\text{calm})^2 + W_2(\text{crisis})^2)$ - example: if the distance to calm is 2 and to crisis is 1, $p_{\text{crisis}} = 4/(4+1) = 0.8$ - $p_{\text{crisis}} > 0.5$ exactly when the window is closer to the crisis centre, which is the paper's nearest centroid rule. So MVO and HRP switch exactly as the paper would classify - it uses data through d-1 only, teh same timing as teh other two detectors.

5 Regime Interpretation

5.1 MVO

- it reads teh detector's daily csv and takes teh value for rebalance date d, which uses data through d-1 - before the detector's first value, p_{crisis} is set to 0.5, meaning no information - with `DETECTOR = "none"`, p_{crisis} is 0, every model is its normal version

5.2 MVO

- on each rebalance date d, `in_crisis(d)` checks $p_{\text{crisis}}(d) > 0.5$ - if yes, the weights are minimum-variance, if no, max-sharpe - the choice is held until the next rebalance date. - it doesnt matter if it is 0.51 or 0.99, same effect

5.3 HRP

- on each rebalance date d, `in_crisis(d)` checks $p_{\text{crisis}}(d) > 0.5$ - if yes, the weights are minimum-variance, if no, max-sharpe - the choice is held until the next rebalance date. - it doesnt matter if it is 0.51 or 0.99, same effect

5.4 XGB and RF

-

6 Regimes

6.1 Changepoint Detection

Methodology and calculation 1:1 to the paper

6.2 Monthly Crisis Probability




Figure 1: Monthly crisis probability p_{crisis} of the three regime detectors: changepoint detection (VIX, top), clustering (Wasserstein k-means, S&P 500 and VIX, middle) and Hidden Markov Model (S&P 500, bottom). Value on the first trading day of each month, held until the next month, as read by the monthly rebalanced portfolios; it uses data up to the previous day. Dashed: 0.5 threshold, above which the portfolios switch to their crisis allocation. Grey shading: crisis periods from the S&P 500 peak until it is back at the peak; vertical lines: peak, trough and recovery.

7 Portfolio Performance

Table 1: Crisis overview: duration and maximum drawdown (%) within each crisis; baselines, monthly rebalancing. Trading Days: S&P 500 trading days from the peak to the trough. Maximum drawdown: from the S&P 500 peak until the S&P 500 is back at that peak. GSPC: S&P 500 price index.

	Asian Crisis	**Dotcom Crisis**	**Financial Crisis**	**Monetary Policy Shock**	**COVID-19 Crisis**	**Inflation & Rate Hikes**	**Trade Policy Shock**
Trading Days	31	637	355	65	23	195	34
Strategy	**Maximum Drawdown**						
GSPC	-19.3%	-49.1%	-56.8%	-19.8%	-33.9%	-25.4%	-18.9%
MCap	-17.0%	-48.6%	-50.4%	-20.2%	-29.0%	-32.4%	-22.4%
1/N	-17.0%	-39.3%	-55.6%	-16.7%	-30.8%	-29.1%	-18.7%
HRP	-15.6%	-34.3%	-45.6%	-14.5%	-29.6%	-23.8%	-15.1%
MVO	-17.5%	-54.1%	-44.6%	-19.9%	-31.6%	-28.7%	-19.2%
LSTM	-17.8%	-42.2%	-61.5%	-16.3%	-32.1%	-33.8%	-17.1%
RF	-19.9%	-39.6%	-61.0%	-17.8%	-34.1%	-33.8%	-19.7%
XGB	-19.6%	-38.6%	-61.6%	-18.3%	-32.3%	-32.9%	-18.9%

Table 2: Full-period performance 1998–2025; baselines, monthly rebalancing. Sharpe ratio on excess returns over the 3-month T-bill, annualised. CAGR: compound annual growth rate. Cum. return: cumulative return over the period. Ulcer index: root mean square drawdown from the running high. Turnover p.a.: average annual turnover, without the initial purchase. GSPC: S&P 500 price index (without dividends), held buy & hold; the portfolios are total-return series.

Strategy	**Sharpe Ratio**	**CAGR**	**Cum. Return**	**Annual Volatility**	**Max. Drawdown**	**Ulcer Index**	**Turnover p.a.**
GSPC	0.25	7.25%	607%	19.4%	-56.8%	17.7%	0%
MCap	0.39	10.49%	1523%	20.3%	-52.3%	18.5%	16%
1/N	0.38	10.07%	1360%	19.7%	-55.6%	14.4%	77%
HRP	0.40	9.41%	1134%	17.2%	-45.6%	10.5%	130%
MVO	0.38	9.84%	1277%	19.4%	-54.1%	20.2%	209%
LSTM	0.37	10.66%	1595%	21.8%	-61.5%	16.7%	336%
RF	0.36	10.51%	1534%	21.9%	-61.0%	16.0%	483%
XGB	0.36	10.37%	1477%	21.7%	-61.6%	15.5%	549%

Table 3: Average crisis performance: equal-weighted average over the seven crises; baselines, monthly rebalancing. Fixed S&P 500 windows: full crisis from the S&P 500 peak until it is back at that peak, peak to trough, and trough to recovery (back at the peak). Max. drawdown and Ulcer index over the full crisis; cumulative return over each of the three windows. Recovery: trading days from the portfolio's own trough until it is back at its value on the S&P 500 peak date, searched up to the next crisis peak; ≥: not recovered in at least one crisis (counted up to that cut-off, a lower bound); MCap and MVO did not recover from the Dotcom Crisis before the peak of the Financial Crisis (2007-10-09), so their Dotcom Crisis recovery is counted up to that date. GSPC: S&P 500 price index; its full-crisis return is about zero by construction of the windows.

				Cumulative Return		
Strategy	**Max. Drawdown**	**Ulcer Index**	**Recovery (days)**	**Full Crisis**	**Peak to Trough**	**Trough to Recovery**
GSPC	-31.9%	15.0%	400	0.3%	-31.9%	55.5%
MCap	-31.4%	15.1%	≥377	3.1%	-31.0%	54.0%
1/N	-29.6%	13.0%	357	5.0%	-29.2%	54.8%
HRP	-25.5%	10.2%	229	9.6%	-24.3%	49.6%
MVO	-30.8%	15.0%	≥323	3.8%	-30.3%	54.0%
LSTM	-31.5%	14.2%	333	6.1%	-31.0%	62.6%
RF	-32.3%	14.6%	359	4.9%	-31.9%	61.7%
XGB	-31.7%	14.2%	353	4.5%	-31.4%	61.0%

Table 4: Regime detectors: changepoint (VIX), Hidden Markov Model (S&P 500) and clustering (Wasserstein k-means, S&P 500 and VIX), 1998–2025. Daily: the detector's own daily state. Monthly, quarterly, yearly: the state on the first trading day of the month, quarter or year, held until the next one, as the portfolios hold it. Episodes: number of switches into the crisis state; duration: their average length in trading days. Defensive: share of trading days in the crisis state. Entry lag: trading days from the S&P 500 peak to the first crisis day (negative: already in the crisis state at the peak), over the crises entered before the trough. Exit lag: trading days from the S&P 500 trough to the first calm day, over the crises in which the detector switches back. In brackets: number of the seven crises behind the average lag. Recall and precision per day against the crisis label S&P 500 peak to trough.

Detector	Episodes	Duration (days)	Defensive	Entry Lag (days)	Exit Lag (days)	Recall	Precision
Daily							
Changepoint	10	343	48.7%	-74.3 (6)	258.4 (5)	66.6%	26.0%
HMM	156	10	23.2%	7.7 (7)	23.0 (7)	56.1%	45.9%
Clustering	110	26	41.1%	-3.6 (7)	73.9 (7)	75.4%	34.9%
Monthly							
Changepoint	9	381	48.7%	-133.0 (4)	240.7 (3)	66.6%	26.0%
HMM	32	49	22.3%	33.8 (6)	48.0 (6)	46.9%	40.1%
Clustering	41	68	39.7%	0.0 (7)	113.7 (7)	73.4%	35.2%
Quarterly							
Changepoint	9	384	49.1%	-118.0 (5)	176.8 (4)	67.2%	26.0%
HMM	15	101	21.5%	87.5 (4)	48.2 (4)	41.3%	36.6%
Clustering	21	144	42.9%	-20.2 (5)	181.2 (5)	65.6%	29.1%
Yearly							
Changepoint	6	628	53.5%	-6.5 (4)	611.0 (3)	72.2%	25.7%
HMM	5	251	17.8%	14.5 (2)	-43.0 (1)	21.4%	22.9%
Clustering	8	345	39.2%	18.4 (5)	165.5 (4)	60.1%	29.1%

7.1 Crisis Excess Returns: Peak to Trough vs. Trough to Recovery




Figure 2: Average crisis excess return over the benchmark per model: peak to trough (x) vs. trough to recovery (y). The dotted line marks $x + y = 0$: models above it gain over the whole crisis (peak to recovery), models below lose. The line is approximate, since the two phases compound, $(1 + x)(1 + y) - 1 \neq x + y$, rather than add.

7.2 Detection Quality

8 References

Nystup Peter, Madsen Hendrik, Lindström Erik, 2017. Dynamic portfolio optimization across hidden market regimes.
Used for:
- Transaction costs 10bps
- Hidden Markov Model