

Que: why do we need array?

problem: marks of 30 students for 1 subject are given as an input. You have to find average. will you need array? No

Sum
count
++
Sum / (double) count

problem^{II}: marks of 30 students for 1 subject are given as an input. You have to find difference between marks of each student and average. (deviate)

✓ 30 - 18 = 12
✓ 12 - 18 = -6
✓ 18 - 18 = 0
✓ 12 - 18 = -6

one step of
standard deviation

✓ → Ascending order
→ Descending "

program III: Sort given 5 numbers.

arr

2	3	4	6	9
---	---	---	---	---



✓
selection sort

6	2	9	1	3
---	---	---	---	---

0 1 2 3 4

↑

arr[3] = arr[0]

#include <stdio.h>

int main() {

int n, i, j;
scanf("%d", &n);

int arr[n];

for(i=0; i<n; i++)
scanf("%d", &arr[i]);

for(i=0; i<n-1; i++){

int min_index = i;

for(j=i+1; j<n; j++)

if(arr[j] < arr[min_index])
min_index = j;

int temp = arr[i];

arr[i] = arr[min_index];

arr[min_index] = temp;

}


for(i=0; i<n; i++)

printf("%d", arr[i]);

return 0;

}

(n)



} finding index
of min value
in unsorted
portion

} exchanging.