

# *Sebastian, Basti, Wastl?!*

## Recognizing Named Entities in Bavarian Dialectal Data

Siyao Peng, Zihang Sun, Huangyan Shan, Marie Kolm,  
Verena Blaschke, Ekaterina Artemova, Barbara Plank

MaiNLP & MCML, LMU Munich, Germany

LREC-COLING 2024  
May 22, 2024



## Named Entity Recognition (NER) is a fundamental task.

*Problem: Lack of high-quality annotations on non-standard language varieties.*

*WikiAnn (Pan et al., 2017) silver annotations on 282 languages/dialects, including Bavarian, but on unnatural texts.*

bar · 300 rows

Search this dataset

tokens  
sequence

[ "", "", "Mongolei", "", "" ]
[ "Dieter", "Hildebrandt", "(", "seit", "2005", ")" ]
[ "", "", "Heiliges", "Remisches", "Reich", "", "" ]
[ "Weiterleitung", "Josua", "(", "Buach", ")" ]
[ "***", "", "", "Ortenberg", "", "" ]
[ "", "", "Kina", "", "" ]
[ "Israel", "Kamakawiwo'ole", "-", "Wejdbekannta", "Sānga" ]
[ "Clark", "County", ",", "Indiana" ]
[ "**", "Rudolph", "Moshammer", ",", "1940-2005" ]
[ "***", "", "", "Holland", "", "" ]
[ "WEITERLEITUNG", "Gila", "County", ",", "Arizona" ]
[ "X", "Japan", "(", "1997", "aufgelöst", ",", "2007", "/", "08", "wiedavaeinigt", ")" ]
[ "**", "", "", "Toskana", "", "" ]
[ "Weiterleitung", "Johannes", "XXIII", "." ]

## Named Entity Recognition   Dialects   Bavarian German

- The first dialectal NER dataset for German, BARNER;
- 161K tokens annotated on Bavarian Wikipedia articles (*bar-wiki*) and tweets (*bar-tweet*);
- Comparing lexical distribution, syntactic construction, and entity information with 3 German NER datasets on *wiki*, *tweet* and *news*;
- Incorporating German datasets to improve BARNER parsing;
- Multi-task learning with Bavarian-German Dialect Identification.

# BARNER

First manually annotated NER dataset  
on a German dialect – Bavarian

Annotations and guidelines available:  
<https://github.com/mainlp/BarNER>

## CoNLL06 style (Tjong Kim Sang and De Meulder, 2003)

- PERSON, LOCATION, ORGANIZATION, MISCELLANEOUS;

## GermEval 2014/NoSta-D style (Benikova et al., 2014)

- -deriv/-part for nominal derivation and compounding;
- *Italienroas*<sub>LOCpart</sub> 'tour of Italy';
- *eiropäischn*<sub>LOCderiv</sub> 'European';

## Others


- LANGUAGE, RELIGION, EVENT, work-of-art (WOA);
- Only flat and named entities, excluding common nouns, pronouns, overlapping, or nested NEs.

**Tagset normalized to CoNLL06 for analyses and experiments.**

## Wikipedia articles

- Carefully written and consistently updated;
- <https://bar.wikipedia.org/wiki/Wikipedia:Hoamseitn>.

## Twitter (X) tweets

- noisier, less formal, and more dynamic;
- Snowballed from a list of 17 Bavarian ‘seed users’ (<http://indigenoustweets.com/bar/>) to their friends;
- Manually classified into *bar/de/other/NA* and only kept *bar*-items;
- Hashtags ([#*minga*]<sub>LOC</sub>) and emojis ([LOC) are annotated.

# BARNER – Inter-Annotator Agreement (IAA)

- Three graduate students took five months to annotate BARNER;
- 53% of BARNER are **double annotated** for disagreement studies;
- 85+ typed span F1s;
- Entity span detection is harder for tweets but entity typing is easier.

- Both *bar-wiki* and *bar-tweet* reach 75K+ tokens;
- *bar-tweet* has much fewer entities due to informality and length.

Corpus	#Toks	#Sents	#Ents	Ents/Tok (in %)
<i>bar-wiki</i>	75.7k	3.6k	4.2k	5.5
<i>bar-tweet</i>	86.1k	7.5k	2.5k	2.9



# *Named Entities Diverge*

*Bavarian vs. German*

>

*Wikipedia vs. Tweets vs. News*

# Comparisons – Five German & Bavarian Datasets


	Bavarian	German
<i>wiki</i>	<i>bar-wiki</i>	<i>de-wiki</i> the wiki portion of NoSta-D (Benikova et al., 2014)
<i>tweet</i>	<i>bar-tweet</i>	<i>de-tweet</i> MobIE transportation tweets (Hennig et al., 2021)
<i>news</i>	/	<i>de-news</i> CoNLL 2006 news (Tjong Kim Sang and De Meulder, 2003)

We use **Jaccard Similarity (JS)**:

- $\frac{\text{shared (i.e., intersection) tokens}}{\text{concatenated (i.e., union) tokens}}$  between datasets;
- Compare surface strings to preserve variations;
- German *wiki* × *news* highest 0.417 – formality and well-editedness;
- Similar between tweets and other same-dialect genres:
  - DE *tweet* × *news* 0.229;
  - DE *tweet* × *wiki* 0.195;
  - BAR *tweet* × *wiki* 0.181.

# Comparisons – Entity Type Distributions

- Frequencies of NE types per 1K tokens (log-scaled);
- *bar-wiki* and *de-wiki*: similar type distributions;
- *de-tweet*: extreme LOC outlier (105.2) – many routes/streets/cities;
- *bar-tweet*: least entities, esp. ORG; PER > LOC – personal chats.



# Comparisons – Top Entities

- Shared entities: *Deutschland* or *Deutschland* 'Germany';
- Most common city names differ between dialects: *Minga* 'Munich' in Bavarian vs. *Berlin* and *Frankfurt* in German;
- *bar-wiki*: document titles;
- *de-wiki*: city and country names;
- *bar-tweet*: tweet friends' names;
- *de-tweet*: railway lines, #S3, S3;
- *de-news*: currency *Mark* and political parties *SPD* or *CDU*.



bar-wiki



de-wiki



bar-tweet



de-tweet



de-news

## Person entities:

- Family names come before given names, e.g., *Dreßen* is the family name in *Dreßen Thomas*;
- Shortened given names with diminutive suffixes (e.g., *-l*), *Sebastian* becomes *Basti* or *Wastl*;
- Given names are typically preceded by definite articles, e.g., *d'Maria* and *da Michel*.

## Possessive constructions:

the genitive determiner in German is replaced by combining preposition *vo* 'from' with a dative determiner:

- 'Association of National Olympic Committees' in English
- *Vaeinigung vo de Nationoin Olympischn Komitees* in Bavarian
- *Vereinigung der Nationalen Olympischen Komitees* in German

*NER results on Bavarian*

*Cross-domain, sequential, and joint  
training with German*

*Multi-task learning with  
dialect identification*

- MaChAmp (van der Goot et al., 2021) with masked CRF decoder;
- Datasets: five tag-normalized German and Bavarian datasets;
- German GBERT (Chan et al., 2020)  
<https://huggingface.co/deepset/gbert-large>;
- Multilingual XLM (Conneau et al., 2020)  
<https://huggingface.co/xlm-roberta-large>;
- 3-run average on Span F1.



# Experiments – In-domain

- More difficult on **bar-wiki**, **bar-tweet**, and **de-tweet** – smaller datasets and non-mainstream variations (Bavarian and/or tweet);
- XLM-R for later experiments – higher F1s on BAR.

In-domain	<b>bar-wiki</b>	<b>bar-tweet</b>	<i>de-wiki</i>	<b>de-tweet</b>	<i>de-news</i>
-----------	-----------------	------------------	----------------	-----------------	----------------

## Corpus Statistics

#TrainToks	61.4K	71.8K	232.4K	47.0K	207.0K
#TrainEnts	2.7K	1.6K	12.9K	7.3K	10.0K

## In-domain Results

<b>XLM-R</b>	<b>72.91</b>	<b>77.55</b>	85.67	77.14	88.35
GBERT	72.17	73.30	<b>86.68</b>	<b>79.75</b>	<b>90.23</b>

# Experiments – Out-of-domain (OOD)

- Models trained on the larger *de-wiki* and *de-news* perform badly on *bar-wiki*, *bar-tweet*, and *de-tweet*;
- Models trained on smaller but in-domain Bavarian data are better;
- However, cross-genre degradations between *de-wiki* and *de-news* are relatively small.

# Experiments – Sequential

**Motivation:** *bar-wiki/tweet* suffer from smaller training size.

**Sequential:** train on another dataset → train+evaluate on target.

- Improved performances on all five datasets;
- *de-wiki* → *bar-wiki* – same genre but more data;
- *bar-wiki* → *bar-tweet* – same dialect but denser entities;
- *de-tweet* → *de-wiki* & *de-news* – topic-heavy entities;
- All other BAR/DE datasets → *de-news* – more diverse data.

Another\Target	<i>bar-wiki</i>	<i>bar-tweet</i>	<i>de-wiki</i>	<i>de-tweet</i>	<i>de-news</i>
<i>bar-wiki</i>	—	<b>79.27</b>	-	<b>77.26</b>	+
<i>bar-tweet</i>	-	—	-	-	+
<i>de-wiki</i>	<b>73.67</b>	+	—	-	+
<i>de-tweet</i>	-	-	<b>86.08</b>	—	<b>88.89</b>
<i>de-news</i>	-	+	-	-	—
In-domain	72.91	77.55	85.67	77.14	88.35

# Experiments – Joint

**Joint:** train on all five → dev/test on target.

**Joint+seq:** train on five → train on target → dev/test on target.

- Joint improves vastly on *bar-wiki* 8.82 ↑ & mildly on *bar-tweet* 0.62 ↑;
- Joint+seq improves *bar-wiki* by another 2.36 ↑.

	<i>bar-wiki</i>	<i>bar-tweet</i>	<i>de-wiki</i>	<i>de-tweet</i>	<i>de-news</i>
joint	<b>81.73</b>	<b>78.17</b>	<b>85.89</b>	-	-
joint+seq	<b>84.09</b>	+	-	-	<b>88.67</b>
In-domain	72.91	77.55	85.67	77.14	88.35

# Experiments – Multi-Task Learning (MTL)

**Dialect Identification (DID):** Classifying *tweet* and *wiki* as BAR or DE.

**MTL with 5 NER and 2 DID tasks:** Vastly improve *bar-wiki* 11.26 ↑.

**Overall best results:**

- *bar-wiki* by multi-task and other four by sequential;
- Still, Bavarian and tweets are more difficult.

	<i>bar-wiki</i>	<i>bar-tweet</i>	<i>de-wiki</i>	<i>de-tweet</i>	<i>de-news</i>
In-domain	72.91	77.55	85.67	77.14	88.35
Best model	multi-task	seq-bar-wiki	seq-de-tweet	seq-bar-wiki	seq-de-tweet
Improvement	11.26↑	1.72↑	0.41↑	0.12↑	0.54↑
Final result	84.17	79.27	86.08	77.26	88.89

# Conclusion & Future Work

## Conclusion

- BARNER – manually annotated named entity corpus for Bavarian;
- Lexical and entity-level distinctions between DE and BAR;
- SOTA results from sequential training and multi-task learning;
- Diversity – genres, topics, and dialects – helps BAR and DE.

## Future Work

- Alignments between mainstream languages and dialects;
- More fine-grained sub-dialectal (sub-regional) variations;
- Translation- vs. transfer-based approaches in dialectal NLP;
- Call for more dialectal datasets.

*More Bavarian at LREC-COLING 2024:*

*Now @ Poster I: Slot Intent Detection (Winkler et al., 2024)*

*Fri 11am @ Poster I: Universal Dependencies (Blaschke et al., 2024)*

Questions?  
Comments?



Paper

Siyao Logan Peng  
MaiNLP & MCML, LMU Munich  
[siyaopeng@cis.lmu.de](mailto:siyaopeng@cis.lmu.de)

This project is supported by ERC Consolidator Grant DIALECT 101043235.

# References I

- Darina Benikova, Chris Biemann, and Marc Reznicek. 2014. NoSta-D Named Entity Annotation for German: Guidelines and Dataset. *LREC* (2014).
- Verena Blaschke, Barbara Kovačić, Siyao Peng, Hinrich Schütze, and Barbara Plank. 2024. MaiBaam: A Multi-Dialectal Bavarian Universal Dependency Treebank. arXiv:2403.10293 [cs.CL]
- Branden Chan, Stefan Schweter, and Timo Möller. 2020. German's Next Language Model. In *Proceedings of the 28th International Conference on Computational Linguistics*, Donia Scott, Nuria Bel, and Chengqing Zong (Eds.). International Committee on Computational Linguistics, Barcelona, Spain (Online), 6788–6796. <https://doi.org/10.18653/v1/2020.coling-main.598>
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Unsupervised Cross-lingual Representation Learning at Scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault (Eds.). Association for Computational Linguistics, Online, 8440–8451. <https://doi.org/10.18653/v1/2020.acl-main.747>
- Leonhard Hennig, Phuc Tran Truong, and Aleksandra Gabryszak. 2021. MobIE: A German Dataset for Named Entity Recognition, Entity Linking and Relation Extraction in the Mobility Domain. In *Proceedings of the 17th Conference on Natural Language Processing (KONVENS 2021)*. KONVENS 2021 Organizers, Düsseldorf, Germany, 223–227. <https://aclanthology.org/2021.konvens-1.22>



# References II

- Xiaoman Pan, Boliang Zhang, Jonathan May, Joel Nothman, Kevin Knight, and Heng Ji. 2017. Cross-lingual Name Tagging and Linking for 282 Languages. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, Vancouver, Canada, 1946–1958.  
<https://doi.org/10.18653/v1/P17-1178>
- Erik F. Tjong Kim Sang and Fien De Meulder. 2003. Introduction to the CoNLL-2003 Shared Task: Language-Independent Named Entity Recognition. In *Proceedings of the Seventh Conference on Natural Language Learning at HLT-NAACL 2003*. 142–147.  
<https://aclanthology.org/W03-0419>
- Rob van der Goot, Ahmet Üstün, Alan Ramponi, Ibrahim Sharaf, and Barbara Plank. 2021. Massive Choice, Ample Tasks (MaChAmp): A Toolkit for Multi-task Learning in NLP. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: System Demonstrations*. Association for Computational Linguistics, Online, 176–197. <https://doi.org/10.18653/v1/2021.eacl-demos.22>
- Miriam Winkler, Virginija Juozapaityte, Rob van der Goot, and Barbara Plank. 2024. Slot and Intent Detection Resources for Bavarian and Lithuanian: Assessing Translations vs Natural Queries to Digital Assistants. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation*.