

Stacey Armstrong's ListNode class.

```
public class ListNode implements Linkable
{
    private Comparable listNodeValue;
    private ListNode nextListNode;

    public ListNode()
    {
        listNodeValue = null;
        nextListNode = null;
    }

    public ListNode(Comparable value, ListNode next)
    {
        listNodeValue=value;
        nextListNode=next;
    }

    public Comparable getValue()
    {
        return listNodeValue;
    }

    public ListNode getNext()
    {
        return nextListNode;
    }

    public void setValue(Comparable value)
    {
        listNodeValue = value;
    }

    public void setNext(Linkable next)
    {
        nextListNode = (ListNode)next;
    }
}

public interface Linkable
{
    Comparable getValue();
    Linkable getNext();
    void setNext(Linkable next);
    void setValue(Comparable value);
}
```

John Spicer's ListNode inner class.

It was inside of his LinkedList class, which means the methods they were implementing could access the private variables of each ListNode object.

```
private class ListNode
{
    private T value;
    private ListNode next;

    public ListNode(T initValue, ListNode initNext) {
        value = initValue;
        next = initNext;
    }

    public String toString() {
        return value.toString();
    }
}
```

Tom Halbert's ListNode class:

```
public class Node<T>
{
    private T value;
    private Node<T> next;

    public Node(){}

    public Node(T v, Node<T> n)
    {
        value = v;
        next = n;
    }

    public void setValue(T v) { value = v; }
    public void setNext(Node<T> n) { next = n; }

    public T getValue() { return value; }
    public Node<T> getNext() { return next; }
}
```