



MarzPay

Merchant API Integration Guide

Africa-focused payments platform — collections, disbursements,
bank transfers, bills, airtime, webhooks, and more.

Live: Uganda · Kenya · Rwanda · DRC · Zambia · Cameroon · Benin · Côte d'Ivoire ·
Gabon · Congo-Brazzaville · Senegal · Sierra Leone

Version 1.0 | September 20, 2026

Online documentation: <https://wallet.wearemarz.com/documentation>

Table of Contents

- 1.** [Introduction](#)
- 2.** [Getting Started](#)
- 3.** [Authentication & Security](#)
- 4.** [API Fundamentals](#)
- 5.** [Collections \(Mobile Money\)](#)
- 6.** [Card Payments](#)
- 7.** [Send Money & Bank Transfer](#)
- 8.** [Bill Payments, Airtime, Phone Verification & Payment Links](#)
- 9.** [Mobile App, WhatsApp & USSD](#)
- 10.** [Balance, Transactions & Services](#)
- 11.** [Webhooks & Callbacks](#)
- 12.** [Error Handling](#)
- 13.** [Sandbox Testing & Go-Live Checklist](#)
- 14.** [Resources & Support](#)

1. Introduction

MarzPay is an **Africa-focused** payment platform that enables businesses to collect and disburse funds across the continent. The platform supports mobile money, card payments, bank transfers, utility bills, airtime/data bundles, phone verification — through the merchant REST API documented in this guide.

Regional availability: MarzPay is built for Africa. **Uganda (UG / UGX)** — MTN & Airtel mobile money, card, bills, bank transfer, airtime. **Kenya (KE / KES)** — M-Pesa collect and send money (same `/collect-money` and `/send-money` endpoints). **Rwanda (RW / RWF)** — MTN & Airtel. **DRC (CD / CDF & USD)** — Vodacom, Airtel & Orange with dual wallets. **Zambia (ZM / ZMW)** — MTN, Airtel & Zamtel. **Cameroon (CM / XAF)** — MTN & Orange. **Benin (BJ / XOF)** — MTN & Moov. **Côte d'Ivoire (CI / XOF)** — MTN & Orange. **Gabon (GA / XAF)** — Airtel. **Congo-Brazzaville (CG / XAF)** — MTN & Airtel. **Senegal (SN / XOF)** — Orange & Free. **Sierra Leone (SL / SLE)** — Orange. Always send `country` on money-movement requests. For DRC also send `currency`. Check `GET /collect-money/services` and `GET /services` for your account's enabled countries. Guides: <https://wallet.wearemarz.com/documentation/kenya> · <https://wallet.wearemarz.com/documentation/rwanda> · <https://wallet.wearemarz.com/documentation/drc> · <https://wallet.wearemarz.com/documentation/zambia> · <https://wallet.wearemarz.com/documentation/cameroon> · <https://wallet.wearemarz.com/documentation/west-africa>

This guide walks you through integrating the merchant API from account setup to production go-live, covering every product available today.

Product overview

Product	Endpoint	IP whitelist
Collections (mobile money)	POST <code>/collect-money</code>	No
Card payments	POST <code>/collect-money</code> (method: card)	No

Send money	POST /send-money	Yes
Bank transfer	POST /bank-transfer	Yes
Bill payments	POST /bill-payment	Yes (POST)
Airtime & data	POST /airtime-data	Yes (POST)
Phone verification	POST /phone-verification/verify	No
Balance	GET /balance	Yes
Transactions	GET /transactions	No
Webhooks	POST /webhooks	No
Payment links	POST /payment-links	Business setting

MarzPay is also available on **mobile app**, **WhatsApp**, and **USSD** for businesses and customers — see Section 9. Those channels are not part of the merchant API in this guide.

Before you integrate: Subscribe to each product in the MarzPay dashboard service marketplace. Some endpoints also require IP whitelisting and disbursement permissions.

2. Getting Started

2.1 Account setup

1. Create a business account at <https://wallet.wearemarz.com>
2. Verify your email and complete your business profile
3. Upload required business documents for verification
4. Subscribe to the payment services you need (Collections, Send Money, etc.)

2.2 API credentials

1. Log in to the dashboard and navigate to **API Keys**
2. Click **Generate New API Key** and provide a descriptive name
3. Copy your API key and secret immediately — the secret is shown only once
4. Store credentials securely (environment variables, secrets manager)

2.3 Sandbox mode

New accounts start in **sandbox mode**. In sandbox, API calls return simulated responses without processing real money. Test your full integration flow before requesting live mode activation.

Important: Never commit API keys to source control. Use `.env` files and keep production credentials separate from development.

3. Authentication & Security

3.1 HTTP Basic authentication

Every API request must include an Authorization header with your API key and secret:

```
Authorization: Basic base64(api_key:api_secret)
Accept: application/json
Content-Type: application/json
```

Example: if your key is `mk_live_abc` and secret is `sk_live_xyz` :

```
Authorization: Basic bWtfbGl2ZV9hYmM6c2tfbGl2ZV94eXo=
```

3.2 IP whitelisting

The following endpoints require your server IP to be whitelisted in the dashboard:

- GET /balance
- POST /send-money
- POST /bank-transfer
- POST /bill-payment
- POST /airtime-data

3.3 Disbursement permission

Send money and bank transfer require **API disbursement** to be enabled on your business account. Contact support or enable this in your dashboard settings.

3.4 Recommended environment variables

```
MARZPAY_API_BASE=https://wallet.wearemarz.com/api/v1
MARZPAY_API_KEY=your_api_key
MARZPAY_API_SECRET=your_api_secret
MARZPAY_CALLBACK_URL=https://your-app.com/webhooks/marzpay
```

4. API Fundamentals

4.1 Base URL

```
https://wallet.wearemarz.com/api/v1
```

All paths in this guide are relative to this base URL.

4.2 Request format

- Send JSON bodies with `Content-Type: application/json`
- Some collection endpoints also accept `multipart/form-data`
- **Live markets:** Uganda (`UG`), Kenya (`KE`), Rwanda (`RW`), DRC (`CD`), Zambia (`ZM`), Cameroon (`CM`), Benin (`BJ`), Côte d'Ivoire (`CI`), Gabon (`GA`), Congo-Brazzaville (`CG`), Senegal (`SN`), Sierra Leone (`SL`)
- Phone numbers use E.164 — Uganda `+256...` , Kenya `+254...` , Rwanda `+250...` , DRC `+243...` , Zambia `+260...` , Cameroon `+237...` , Benin `+229...` , Côte d'Ivoire `+225...` , Gabon `+241...` , Congo-Brazzaville `+242...` , Senegal `+221...` , Sierra Leone `+232...`
- Optional request `metadata` (merchant array) is echoed on create as `data.collection.metadata` and on webhooks as top-level `metadata` . Do not confuse with `data.metadata` on some API responses (response diagnostics only).
- Always check services endpoints for your account's enabled countries and products

4.3 Success response envelope

```
{
  "status": "success",
  "message": "Optional human message",
  "data": { ... }
}
```

Money values are almost always objects: `{ "formatted": "5,000.00", "raw": 5000, "currency": "UGX" }`. Use `raw` for calculations; show `formatted` + `currency` in UI.

Exceptions: phone verification uses "success": true (boolean). Direct callback_url payloads start with event_type (no outer status / data). Dashboard webhooks wrap the same body under data .

4.4 Wallets

Every business has wallets **per country** (UG , KE , RW , CD , ZM , CM , BJ , CI , GA , CG , SN , SL). DRC has separate CDF and USD wallets.

Wallet	wallet_source	Funded by
Main wallet	main (default)	Mobile money collections
Card wallet	card	Card payment collections

5. Collections (Mobile Money)

Collect payments from customers via mobile money. **Uganda:** MTN or Airtel (auto-detected from phone). **Kenya:** M-Pesa — same endpoint with `country: "KE"` , `+254...` phones, and KES amounts.

5.1 Endpoints

Method	Path	Description
POST	/collect-money	Initiate collection
GET	/collect-money/services	Available countries/providers
GET	/collect-money/{uuid}	Transaction status

5.2 Create collection — request

```
{
  "amount": 5000,
  "phone_number": "+256712345678",
  "reference": "c97fae8b-9b7f-4192-9f72-6f0859d33e67",
  "country": "UG",
  "description": "Order #1042",
  "callback_url": "https://your-app.com/webhooks/marzpay",
  "metadata": [
    { "orderId": "ORD-123456789" },
    { "customerId": "customer@email.com", "isPII": true }
  ]
}
```

5.3 Field requirements

Field	Required	Rules
amount	Yes	500 – 10,000,000 UGX (Kenya: KES limits)
reference	Yes	UUID v4, unique per API collection

country	Yes	UG, KE, RW, CD, ZM, CM, BJ, CI, GA, CG, SN, or SL
phone_number	Yes	E.164 format (+256... / +254...)
description	No	Max 255 characters
callback_url	No	HTTPS webhook URL
metadata	No	Array max 10; each item one field + value, optional isPII. Echoed on create and webhooks

5.3b Kenya M-Pesa example

```
{
  "amount": 100,
  "phone_number": "+254710000000",
  "reference": "123e4567-e89b-12d3-a456-426614174000",
  "country": "KE",
  "description": "Payment for services",
  "callback_url": "https://your-app.com/webhooks/marzipay",
  "metadata": [
    { "orderId": "ORD-123456789" },
    { "customerId": "customer@email.com", "isPII": true }
  ]
}
```

Subscribe to M-Pesa Collection. Webhook `provider` is `mpesa`.

Reference rules: Every API collection must use a new UUID v4 reference. Reusing a reference returns `DUPLICATE_REFERENCE`. Payment links auto-generate references; API collections do not.

5.4 Integration flow

1. Generate a new UUID v4 reference for each collection
2. POST `/collect-money` with customer phone and amount
3. Customer receives USSD/SMS prompt on their phone
4. Wait for webhook callback or poll GET `/collect-money/{uuid}`

5. Mark order paid only on **completed/successful** status

Note: `provider_reference` is often null on create. Use `collection.provider_transaction_id` from webhook payloads for provider IDs.

5.5 Success response — mobile money (HTTP 201)

```
{
  "status": "success",
  "message": "Collection initiated successfully.",
  "data": {
    "transaction": {
      "uuid": "4e7fb3fa-c13a-4b05-8acd-cf60ff68cb94",
      "reference": "c97fae8b-9b7f-4192-9f72-6f0859d33e67",
      "status": "processing",
      "provider_reference": null
    },
    "collection": {
      "amount": { "formatted": "5,000.00", "raw": 5000, "currency": "UGX" },
      "provider": "mtn",
      "phone_number": "+256712345678",
      "mode": "live"
    },
    "timeline": {
      "initiated_at": "2024-01-20 14:30:00",
      "estimated_settlement": "2024-01-20 14:35:00"
    }
  }
}
```

Do not mark the order paid on create. Wait for webhook or confirmed GET status.

6. Card Payments

Use the same `POST /collect-money` endpoint with `"method": "card"`. Omit `phone_number`.

```
{
  "amount": 5000,
  "method": "card",
  "reference": "123e4567-e89b-12d3-a456-426614174000",
  "country": "UG",
  "description": "Order payment",
  "callback_url": "https://your-app.com/thank-you"
}
```

The response includes `data.redirect_url` — redirect the customer to that URL to complete payment on the card gateway. Card funds settle in the **card wallet**.

```
{
  "status": "success",
  "message": "Card collection initiated. Redirect the customer to redirect_url.",
  "data": {
    "transaction": {
      "uuid": "a799c628-f52a-4540-8b77-43509f2775d3",
      "reference": "b59d3d6d-5827-41ee-b455-18dd20ef1c8a",
      "status": "pending"
    },
    "redirect_url": "https://wallet.wearemarz.com/pay/card-gateway?reference=b59d3d6d-5827-41ee-b455-18dd20ef1c8a"
  }
}
```

7. Send Money & Bank Transfer

7.1 Send money (mobile money disbursement)

Send funds to a customer's mobile money wallet. Uganda: MTN or Airtel (auto-detected). Kenya: M-Pesa with `country: "KE"`.

Method	Path	Description
POST	/send-money	Disburse to phone
GET	/send-money/services	Limits and allowed phones
GET	/send-money/{uuid}	Transaction status

POST /send-money (Uganda)

```
{
  "amount": 10000,
  "phone_number": "+256712345678",
  "reference": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "country": "UG",
  "description": "Salary payment",
  "callback_url": "https://your-app.com/webhooks/marzpay",
  "metadata": [
    { "orderId": "ORD-123456789" },
    { "customerId": "customer@email.com", "isPII": true }
  ]
}
```

POST /send-money (Kenya M-Pesa)

```
{
  "amount": 100,
  "phone_number": "+254710000000",
  "reference": "123e4567-e89b-12d3-a456-426614174001",
  "country": "KE",
  "description": "Payout to customer",
  "callback_url": "https://your-app.com/webhooks/marzpay",
  "metadata": [
    { "orderId": "ORD-123456789" },
    { "customerId": "customer@email.com", "isPII": true }
  ]
}
```

Optional `metadata` is echoed on create as `data.withdrawal.metadata` and on webhooks as top-level `metadata`.

Requires: IP whitelist, API disbursement permission, disbursement service subscription (M-Pesa Disbursement for Kenya), sufficient **country** main-wallet balance. Some businesses restrict payouts to pre-registered withdrawal numbers. Always check `GET /balance` first.

7.1.1 Success response — live send-money (HTTP 201)

Live create uses key `withdrawal` . Callbacks use key `disbursement` . `data.transaction.reference` is the system UUID; `data.transaction.provider_reference` is **your** submitted reference.

```
{
  "status": "success",
  "message": "Withdrawal request submitted successfully! Amount: UGX 10,000 ...",
  "data": {
    "transaction": {
      "uuid": "4e7fb3fa-c13a-4b05-8acd-cf60ff68cb94",
      "reference": "<system-generated-uuid>",
      "provider_reference": "alb2c3d4-e5f6-7890-abcd-ef1234567890",
      "status": "pending"
    },
    "withdrawal": {
      "amount": { "formatted": "10,000.00", "raw": 10000, "currency": "UGX" },
      "charge": { "formatted": "500.00", "raw": 500, "currency": "UGX" },
      "total_deduction": { "formatted": "10,500.00", "raw": 10500, "currency": "UGX" },
      "provider": "mtn",
      "phone_number": "+256712345678"
    },
    "account": {
      "uuid": "8f6cdf42-44e1-4f9f-a359-09721bb32111",
      "balance_before": { "formatted": "100,000.00", "raw": 100000, "currency": "UGX" },
      "balance_after": { "formatted": "89,500.00", "raw": 89500, "currency": "UGX" }
    }
  }
}
```

7.2 Bank transfer

Push funds from your MarzPay wallet to a supported bank account. Available in the current Uganda rollout; designed to extend to additional African banking networks as markets launch.

Method	Path	Description
POST	/bank-transfer/validate	Validate account before sending (recommended)
POST	/bank-transfer	Create bank transfer
GET	/bank-transfer/banks	List supported banks
GET	/bank-transfer/services	Limits and tiered pricing
GET	/bank-transfer/{reference}	Transfer status

Step 1 — Validate account

```
POST /bank-transfer/validate
{
  "bank_name": "Equity Bank",
  "account_number": "60001256421"
}
```

Step 2 — Create transfer

```
POST /bank-transfer
{
  "amount": 100000,
  "description": "Vendor payment",
  "bank_name": "Equity Bank",
  "bank_account_number": "60001256421",
  "bank_account_name": "John Doe",
  "bank_branch": "Kampala",
  "wallet_source": "main"
}
```

Important: You pay *amount* + *tiered charge*; the recipient receives the stated amount. Minimum transfer is approximately 2,500 UGX (confirm via `GET /bank-transfer/services`). Balance is debited immediately; failed transfers are refunded. Poll `GET /bank-`

transfer/{reference} for final status. Use `wallet_source: main|card` to debit the main or card wallet.

Requires: IP whitelist, API disbursement permission, Bank Transfer service subscription.

8. Bill Payments, Airtime & Phone Verification

8.1 Bill payments

Pay utility and subscription bills in the current Uganda market: electricity (LIGHT/UMEME), water (NWSC), and TV (DSTV, GOTV).

Method	Path	Description
POST	/bill-payment/verify	Verify meter or account
POST	/bill-payment	Pay bill
GET	/bill-payment	List transactions
GET	/bill-payment/services	Utility requirements
GET	/bill-payment/nwsc/areas	NWSC service areas
GET	/bill-payment/dstv/bouquet-codes	DSTV packages and prices
GET	/bill-payment/gotv/bouquet-codes	GOTV packages and prices
GET	/bill-payment/{reference}	Payment status

Verify before paying

```
LIGHT: { "utility_code": "LIGHT", "meter_number": "12345678901" }
NWSC:  { "utility_code": "NWSC", "meter_number": "12345678901", "area": "Kampala" }
DSTV:  { "utility_code": "DSTV", "meter_number": "7039132763" }
```

Pay bill (LIGHT example)

```
POST /bill-payment
{
  "reference": "550e8400-e29b-41d4-a716-446655440000",
  "utility_code": "LIGHT",
  "meter_number": "12345678901",
  "phone_number": "+2567000000000",
  "amount": 10000,
```

```
"customer_name": "John Doe",
"email": "john@example.com",
"callback_url": "https://your-app.com/webhooks/marzipay"
}
```

NWSC: include `area` from `/bill-payment/nwsc/areas`. **DSTV/GOTV:** include `bouquet_code` from `bouquet-codes` endpoint; amount must exactly match bouquet price. Wallet debited for amount + bill payment charge (~1,500 UGX). Auto-refund on failure.

8.2 Airtime & data

Purchase MTN, Airtel, or Lyca airtime and data bundles. **No merchant webhooks** — poll status endpoint for final delivery (especially Airtel data bundles).

Method	Path	Description
GET	<code>/airtime-data/catalog</code>	Bundles by network
GET	<code>/airtime-data/detect-network</code>	Preview network from MSISDN
POST	<code>/airtime-data</code>	Purchase airtime or bundle
GET	<code>/airtime-data</code>	List purchases
GET	<code>/airtime-data/{reference}</code>	Purchase status

Network	Airtime	Data bundles	Delivery
MTN	Yes	Yes	Immediate
Airtel	Yes	Yes	Data may be async (pending)
Lyca	Yes	No	Immediate

```
POST /airtime-data (airtime)
{
  "reference": "550e8400-e29b-41d4-a716-446655440000",
  "purchase_type": "airtime",
  "msisdn": "256771234567",
  "amount": 5000
}
```

```
}
```

Network is auto-detected from MSISDN — do not send a separate network field. Use a unique UUID reference per purchase.

8.3 Phone verification

Verify mobile numbers and retrieve registered subscriber name (KYC) before onboarding customers.

Method	Path	Description
POST	/phone-verification/verify	Lookup subscriber details

```
POST /phone-verification/verify
{
  "phone_number": "+256712345678"
}
```

Currently supports Uganda mobile numbers. Additional African markets will be added as verification providers are connected per country.

8.4 Payment links

Create hosted payment pages with `POST /payment-links` (API key auth), or from the MarzPay dashboard. Share `https://wallet.wearemarz.com/pay/{uuid}` with customers. Configure `callback_url` and `redirect_url` on the link. `collection_methods` is optional; omit it to enable all subscribed collection services for that country and currency.

9. Mobile App, WhatsApp & USSD

In addition to the merchant API in this guide, MarzPay is available on **mobile app**, **WhatsApp**, and **USSD**. These are ready-made channels for businesses and their customers — you do not integrate them via the API endpoints in sections 5–8.

9.1 Mobile app (iOS & Android)

Download the MarzPay app to check balances, send money, buy airtime, manage payments, and run your business on the go. Sign in with the same account you use on the web dashboard.

- **App Store (iOS):** <https://apps.apple.com/us/app/marzipay/id6769404051>
- **Google Play (Android):**
<https://play.google.com/store/apps/details?id=com.marzipay.marzipay&pli=1>
- **Download page:** <https://wallet.wearemarz.com/download>

9.2 WhatsApp

MarzPay on WhatsApp lets businesses and customers collect, pay, check balance, and complete everyday payments through chat. To enable WhatsApp for your business or learn your business WhatsApp number, contact MarzPay support.

9.3 USSD

MarzPay on USSD lets customers and businesses access key payment services from any mobile phone by dialling a short code (e.g. *XXX#). To provision USSD for your business, contact MarzPay support.

For API integrators: This PDF covers the merchant REST API only. App, WhatsApp, and USSD are separate products — use the store links above for the app, or contact support for WhatsApp and USSD access.

10. Balance, Transactions & Services

10.1 Balance

```
GET /balance
GET /balance/history
```

Requires IP whitelist. Pass `country` (`UG` , `KE` , `RW` , `CD`). For DRC also pass `currency=CDF` (default) or `currency=USD` . `data.wallets` lists every currency wallet for that country.

How to read balances

Field	Use for
<code>account.available_balance.raw</code>	Spendable main wallet (preferred for send-money / bills / airtime)
<code>account.balance.raw</code>	Same main available balance (legacy-friendly alias)
<code>account.total_balance.raw</code>	Total main wallet figure
<code>account.card_balance.raw</code>	Card wallet — use when <code>wallet_source</code> is card
<code>account.limits.*</code>	Business min/max deposit & withdrawal
<code>metadata.country_code</code>	Which country wallet this response is for
<code>metadata.currency</code>	Wallet currency (CDF or USD for DRC)
<code>data.wallets</code>	All currency wallets for that country (DRC: CDF + USD)

10.1.1 Example — GET /balance

```
{
  "status": "success",
  "data": {
    "account": {
      "uuid": "8f6cdf42-44e1-4f9f-a359-09721bb32111",
      "business_name": "MarzPay Business",
      "balance": { "formatted": "2,503,899.02", "raw": 2503899.02, "currency": "UGX" },
      "available_balance": { "formatted": "2,503,899.02", "raw": 2503899.02, "currency":
"UGX" },
```

```

    "total_balance": { "formatted": "2,503,899.02", "raw": 2503899.02, "currency":
"UGX" },
    "card_balance": {
      "formatted": "125,000.00",
      "raw": 125000,
      "currency": "UGX",
      "description": "Card wallet balance"
    },
    "status": {
      "mode": "live",
      "account_status": "active",
      "is_frozen": false,
      "freeze_reason": null
    },
    "limits": {
      "withdrawal": { "minimum": 1000, "maximum": 5000000 },
      "deposit": { "minimum": 500, "maximum": 10000000 }
    }
  },
  "summary": {
    "monthly": { "credits": "50,000.00", "debits": "25,000.00", "net_change":
"25,000.00", "transaction_count": 15 },
    "weekly": { "credits": "10,000.00", "debits": "4,000.00", "net_change":
"6,000.00", "transaction_count": 4 },
    "daily": { "credits": "2,000.00", "debits": "500.00", "net_change": "1,500.00",
"transaction_count": 2, "period": "yesterday" }
  },
  "metadata": {
    "country_code": "UG",
    "last_updated": "2026-08-04 12:00:00",
    "response_timestamp": "2026-08-04 12:00:01"
  }
}

```

10.1.2 Example — GET /balance/history

Query params: `page`, `per_page` (max 100), `operation` (credit|debit), `start_date`, `end_date`.

```

{
  "status": "success",
  "data": {
    "account": {
      "uuid": "8f6cdf42-44e1-4f9f-a359-09721bb32111",
      "current_balance": { "formatted": "2,503,899.02", "raw": 2503899.02, "currency":
"UGX" }
    },
    "history": [
      {
        "uuid": "bh-uuid",
        "amount": { "formatted": "5,000.00", "raw": 5000 },
        "operation": "collection",
        "type": "credit",
        "description": "Collection credit - Reference: ...",
        "balance_before": 2498899.02,
        "balance_after": 2503899.02,
        "timestamp": "2026-08-04 11:55:00"
      }
    ],
    "pagination": {
      "current_page": 1,
      "last_page": 1,
      "per_page": 25,
      "total": 1,
      "from": 1,
      "to": 1
    },
    "metadata": { "country_code": "UG", "response_timestamp": "2026-08-04 12:00:01" }
  }
}

```

10.2 Transactions

```

GET /transactions?per_page=25&type=collection&status=successful
GET /transactions/{uuid}

```

Filter by type, status, provider, date range, and reference. Use as fallback when webhooks are delayed. `GET /transactions/{uuid}` returns a callback-shaped body (starts with `event_type`).

10.3 Services

```
GET /services
GET /services/{uuid}
```

Check which products your business is subscribed to before building integration UIs.

11. Webhooks & Callbacks

11.1 Per-request `callback_url`

Pass `callback_url` on `collect-money`, `send-money`, `bill-payment`, and similar endpoints. MarzPay POSTs JSON to your URL when the transaction reaches a final status.

11.2 Dashboard webhooks (API-managed)

Method	Path	Description
GET	<code>/webhooks</code>	List webhooks
POST	<code>/webhooks</code>	Create webhook
GET	<code>/webhooks/{uuid}</code>	Get details
PUT	<code>/webhooks/{uuid}</code>	Update
DELETE	<code>/webhooks/{uuid}</code>	Delete

Event types include `collection.completed|failed|cancelled` , `disbursement.completed|failed|cancelled` , `bill_payment.completed|failed|cancelled` , plus legacy `success / failure` .

Registered webhooks wrap the payload: `{ "event_type", "webhook_id", "business_id", "timestamp", "data": { /* same as direct */ } }` . Direct `callback_url` POSTs have no wrapper.

11.3 Webhook handler checklist

1. Accept POST requests and return **HTTP 200** quickly
2. Process asynchronously if needed (queue the work)
3. Make handlers **idempotent** — the same reference may be delivered more than once
4. Update your database by `reference` or transaction UUID
5. Collections: map `collection.provider_transaction_id` (not create `provider_reference`)
6. Disbursements: map `disbursement.provider_transaction_id` ; your ref is `transaction.provider_reference`
7. Handle both direct payload and dashboard `{ data: ... }` wrapper

8. Use HTTPS endpoints in production
9. Optionally verify HMAC signatures if enabled in dashboard (`X-MarzPay-Timestamp` , `X-MarzPay-Signature`)

11.4 Optional metadata on callbacks

If you sent `metadata` on `POST /collect-money` or `POST /send-money` , the same array is included as top-level `metadata` on direct `callback_url` POSTs and dashboard webhooks (success and failure). If you omitted it on create, the key is absent.

11.5 Example webhook payload (collection completed)

```
{
  "event_type": "collection.completed",
  "transaction": {
    "uuid": "transaction-uuid",
    "reference": "c97fae8b-9b7f-4192-9f72-6f0859d33e67",
    "status": "completed",
    "amount": { "formatted": "10,000.00", "raw": 10000, "currency": "UGX" },
    "provider": "mtn",
    "phone_number": "+256712345678",
    "description": "Order payment",
    "created_at": "2025-08-20T15:18:48.000000Z",
    "updated_at": "2025-08-20T15:18:48.000000Z"
  },
  "collection": {
    "provider": "mtn",
    "phone_number": "+256712345678",
    "amount": { "formatted": "10,000.00", "raw": 10000, "currency": "UGX" },
    "mode": "mtnuganda",
    "provider_transaction_id": "148769164724"
  },
  "metadata": [
    { "orderId": "ORD-123456789" },
    { "customerId": "customer@email.com", "isPII": true }
  ]
}
```

Kenya collections use `provider: "mpesa"` , currency `KES` , and `+254...` phones. Failed events use `collection.failed` .

11.6 Example webhook payload (disbursement completed)

```
{
  "event_type": "disbursement.completed",
  "transaction": {
    "uuid": "transaction-uuid",
    "reference": "system-generated-uuid",
    "provider_reference": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
    "status": "completed",
    "amount": { "formatted": "1,000.00", "raw": 1000, "currency": "UGX" },
    "provider": "airtel",
    "phone_number": "+256759983853",
    "recipient_name": "Katende Nicholas",
    "description": "Send Money",
    "created_at": "2025-12-07T05:41:28.000000Z",
    "updated_at": "2025-12-07T05:42:05.000000Z"
  },
  "disbursement": {
    "provider": "airtel",
    "phone_number": "+256759983853",
    "amount": { "formatted": "1,000.00", "raw": 1000, "currency": "UGX" },
    "mode": "airteluganda",
    "provider_reference": null,
    "recipient_name": "Katende Nicholas",
    "provider_transaction_id": "AIRTEL_MONEY_ID"
  },
  "metadata": [
    { "orderId": "ORD-123456789" },
    { "customerId": "customer@email.com", "isPII": true }
  ]
}
```

11.7 Example webhook payload (bill payment completed)

```
{
  "event_type": "bill_payment.completed",
  "transaction": {
    "uuid": "transaction-uuid",
    "reference": "550e8400-e29b-41d4-a716-446655440000",
    "status": "completed",
    "amount": { "formatted": "10,000.00", "raw": 10000, "currency": "UGX" },
    "phone_number": "+256700000000",
    "description": "LIGHT bill payment",
    "created_at": "2026-02-11T14:30:00.000000Z",
    "updated_at": "2026-02-11T14:30:05.000000Z"
  },
  "bill_payment": {
    "provider": "pegpay",
    "utility_code": "LIGHT",
    "meter_number": "12345678901",
    "area": null,
    "bouquet_code": null,
    "phone_number": "+256700000000",
    "amount": { "formatted": "10,000.00", "raw": 10000, "currency": "UGX" },
    "provider_reference": "32686091830930101535"
  }
}
```

See the online Webhooks guide for signed-callback details and more provider examples.

12. Error Handling

12.1 Error response format

```
{
  "status": "error",
  "message": "Human-readable explanation",
  "error_code": "VALIDATION_ERROR",
  "errors": { "field": ["message"] }
}
```

12.2 Common error codes

error_code	Meaning	Action
VALIDATION_ERROR	Invalid input	Fix fields in errors object
DUPLICATE_REFERENCE	Reference reused	Generate new UUID
INSUFFICIENT_BALANCE	Low wallet balance	Top up or reduce amount
SERVICE_NOT_SUBSCRIBED	Missing subscription	Subscribe in dashboard
UNAUTHORIZED	Bad credentials	Check API key/secret
FORBIDDEN	Permission denied	Check IP whitelist / permissions
NOT_FOUND	Resource missing	Verify UUID/reference
ACCOUNT_FROZEN	Account frozen	Contact support
PENDING_WITHDRAWAL_EXISTS	Another send-money in flight	Wait / show pending ref (often HTTP 409)
SERVER_ERROR	Internal error	Retry with exponential backoff

12.3 HTTP status codes

Code	Meaning
------	---------

200 / 201	Success
400	Bad request
401	Unauthorized — invalid credentials
403	Forbidden — IP or permission issue
404	Not found
422	Validation error
500	Server error — retry later

13. Sandbox Testing & Go-Live Checklist

13.1 Sandbox testing

- Confirm account is in sandbox mode
- Test collection create → webhook → status update flow
- Test duplicate reference rejection
- Test error responses (invalid phone, missing fields)
- Use the online API playground: <https://wallet.wearemarz.com/documentation/api-playground>

13.2 Go-live checklist

Business verification completed

Live mode activated on account

Subscribed to all required services

Production API keys generated and stored securely

Server IPs whitelisted for balance/disbursements

Disbursement permission enabled (if sending money)

Webhook endpoint live on HTTPS with idempotent handler

Callback URLs use production domains (not localhost)

Logging and monitoring in place for failed transactions

Customer support process for failed payments defined

13.3 Implementation best practices

1. Generate a **new UUID v4** for every collection and airtime/data reference
2. Never mark an order paid on the create response alone — wait for webhook or confirmed GET status
3. Store credentials in environment variables only
4. Validate meters and bank accounts before initiating payments

5. Use the correct `wallet_source` for bank transfers
6. Poll airtime/data status when response is pending

14. Resources & Support

Resource	URL
Documentation home	https://wallet.wearemarz.com/documentation
Getting started	https://wallet.wearemarz.com/documentation/getting-started
API reference	https://wallet.wearemarz.com/documentation/api
API playground	https://wallet.wearemarz.com/documentation/api-playground
Integration tools (OpenAPI, Postman, AI skill)	https://wallet.wearemarz.com/documentation/ai-integration
Collections guide	https://wallet.wearemarz.com/documentation/collections
Send money guide	https://wallet.wearemarz.com/documentation/send-money
Bank transfer guide	https://wallet.wearemarz.com/documentation/bank-transfer
Bill payments guide	https://wallet.wearemarz.com/documentation/bill-payments
Airtime & data guide	https://wallet.wearemarz.com/documentation/airtime-data
Phone verification guide	https://wallet.wearemarz.com/documentation/phone-verification
Webhooks guide	https://wallet.wearemarz.com/documentation/webhooks
API base URL	https://wallet.wearemarz.com/api/v1

Code example (PHP / Laravel)

```
use Illuminate\Support\Facades\Http;  
use Illuminate\Support\Str;  
  
$response = Http::withBasicAuth(
```

```
    config('services.marzpay.key'),
    config('services.marzpay.secret')
  )->post(config('services.marzpay.base_url').'/collect-money', [
    'amount'      => 5000,
    'phone_number' => '+256712345678',
    'reference'    => (string) Str::uuid(),
    'country'      => 'UG',
    'callback_url' => config('services.marzpay.callback_url'),
  ]);
```

Code example (Node.js)

```
const auth =
Buffer.from(`${process.env.MARZPAY_API_KEY}:${process.env.MARZPAY_API_SECRET}`).toString(
  'base64');

const res = await fetch(`${process.env.MARZPAY_API_BASE}/collect-money`, {
  method: 'POST',
  headers: { Authorization: `Basic ${auth}`, 'Content-Type': 'application/json' },
  body: JSON.stringify({
    amount: 5000, phone_number: '+256712345678',
    reference: crypto.randomUUID(), country: 'UG',
    callback_url: process.env.MARZPAY_CALLBACK_URL,
  }),
});
```

For the latest endpoint details, request/response schemas, and product-specific guides, always refer to the online documentation at <https://wallet.wearemarz.com/documentation>. Download OpenAPI and Postman files from the Integration Tools page.