

SteelStag

TECHNICAL SPECIFICATION PACKAGE · PREMIUM SOLID TEES · SS2026

1. BRAND & ORDER DETAILS

Brand: SteelStag
Contact: hello@steelstag.in
Buyer: Anjan Mishra | anjanimishrait@gmail.com | +36 70 198 3287
Approval Address: 1139 Budapest, Rozsnyay utca 14-16, B lph, 1 em, 104 ajto, Hungary
Season: SS2026 — Initial Launch Run
Styles: ST-RN-001 (Round Neck) | ST-DS-002 (Deep Scoop) | ST-VN-003 (V-Neck)
Sizes: S / M / L / XL
Size Split: S 15% | M 35% | L 35% | XL 15%
Destination: India — Direct to Consumer (DTC)

2. FABRIC SPECIFICATION

Fabric: 100% Combed Cotton — Single Jersey
Yarn Count: 30s Combed Ring Spun
GSM: 125 GSM (tolerance ± 5 GSM)
Construction: Single Jersey
Dyeing: Reactive Dyed
Finish: Light enzyme wash (no heavy silicone finish)
Pre-treatment: Pre-washed, pre-shrunk fabric
Shrinkage: Max $\pm 3\%$ after wash (no twisting)

3. COLOR PALETTE

All colors to be approved on pre-production lab dip before bulk. Pantone TCX references below.

#	Color Name	Pantone TCX	Style Code	Notes
01	Jet Black	19-0303 TCX	All styles	Priority — must have
02	Bright White	11-0601 TCX	All styles	Priority — must have
03	Seaport Teal	17-5126 TCX	All styles	Priority — hero color
04	Wild Ginger	15-1157 TCX	All styles	Priority — hero color
05	Brown Sugar	18-1048 TCX	All styles	

Note: 5 colors across all 3 styles. Provide lab dips for all colors. Priority colors (01–04) to be sampled first.

4. CONSTRUCTION & STITCH SPECIFICATION

GENERAL

Stitch Density: 12–14 SPI (stitches per inch)

Thread: Self-colour polyester thread to match each colourway

Seam Type: Overlock (serger) — all body seams

Side Seam: Clean overlock — no twisting

NECK FINISH

All styles: Clean-bound neck finish — no rib band. Self-fabric tape, folded and stitched flat. Single needle topstitch 1/8" from edge, self-colour thread. Neck must lie flat against body without rolling or gaping. Reference: white tee reference image provided.

Style	Neck Construction	Detail
ST-RN-001 Round Neck	Clean-bound / self-fabric tape	No rib band — folded self-fabric, single needle topstitch 1/8" from edge, lies flat
ST-DS-002 Deep Scoop	Clean-bound / self-fabric tape	No rib band — folded self-fabric, single needle topstitch 1/8" from edge, lies flat
ST-VN-003 V-Neck	Clean-bound / self-fabric tape	No rib band — mitered V-point, folded self-fabric, single needle topstitch 1/8" from edge

SLEEVE FINISH

Style	Sleeve Stitch	Detail
ST-RN-001 Round Neck	Clean flat hem	Twin needle, 1/4" hem, self-colour
ST-DS-002 Deep Scoop	Clean flat hem	Twin needle, 1/4" hem, self-colour
ST-VN-003 V-Neck	Clean flat hem	Twin needle, 1/4" hem, self-colour

HEM

Bottom Hem: Single needle, 1" hem, self-colour thread

Tolerance: ±0.5" on all measurements

5. BODY MEASUREMENTS (inches)

All measurements in inches. Tolerance ±0.5" unless stated.

Point of Measure	S	M	L	XL
HPS Length	26¾	27½	28¾	29
CB Length (from seam)	25¾	26½	27¾	28
Shoulder to Shoulder	17	17½	18	18½
½ Chest (1" below AH)	19¾	19¾	20¾	20¾
½ Waist	19¾	19¾	20¾	20¾
½ Sweep (Straight)	19¾	19¾	20¾	20¾
Armhole Drop from HPS	10½	10¾	11	11¼
½ Sleeve Opening	6	6¼	6½	6¾

6. NECK MEASUREMENTS (inches)

ROUND NECK — ST-RN-001

Point of Measure	S	M	L	XL
Neck Width	7	7¼	7½	7¾
Front Neck Drop	2⅞	3	3⅞	3¼
Back Neck Drop	1	1	1	1
Collar Band Ht	NA	NA	NA	NA

DEEP SCOOP — ST-DS-002

Point of Measure	S	M	L	XL
Neck Width	8	8½	8¾	9
Front Neck Drop	4¼	4½	4⅝	4¾
Back Neck Drop	1	1	1	1

Collar Band Ht	NA	NA	NA	NA
----------------	----	----	----	----

V-NECK — ST-VN-003

Point of Measure	S	M	L	XL
Neck Width	6¾	7	7¼	7½
Front Neck Drop	3½	3¾	4	4¼
Back Neck Drop	1	1	1	1
V-Point Depth	3½	3¾	4	4¼
Collar Band Ht	NA	NA	NA	NA

7. LABEL & BRANDING PLACEMENT

Label	Type	Position	Notes
Neck Label	Woven / printed	Centre back, 1" below collar seam	Per size: S / M / L / XL — files attached
Wash Care Label	Woven / printed	Left side seam, 3" from bottom hem	File attached
Brand Tag	Hang tag	Attached to left side seam with thread	Front + Back — files attached
Size Sticker	Printed sticker	On polybag outside	Per size — files attached

All label artwork files (.png, 300 DPI) attached separately. Do not substitute fonts or colors.

8. PACKAGING

PRIMARY PACKAGING — KRAFT PAPER STANDUP POUCH

- Type:** Kraft paper standup pouch with zipper seal
- Size:** 32cm × 40cm (fits folded tee — standard retail fold)
- Material:** Kraft paper laminated, food-grade inner layer not required
- Design:** Two-tone: top 65% natural kraft (#C8A96E), bottom 35% matte black (#1A1A1A)
- Logo Print:** "STEELSTAG" centered on kraft section — large, black ink, serif or brand font
- Tagline:** "Color. Nothing else." below brand name — smaller, black ink
- URL:** "steelstag.in" printed small on dark top band — gold/kraft ink
- Closure:** Zipper reseal at top — allows customer to reuse pouch
- Finish:** Matte throughout — no gloss lamination
- Reference:** Similar to Finn Design (finn-design.de) packaging style

FOLDING & PACKING

- Folding:** Standard retail fold — tee folded to approx 28cm × 20cm before pouching
- Insert:** Size sticker (provided) affixed on outside of pouch — bottom right corner
- Tissue:** Optional: single sheet natural kraft tissue wrap inside pouch

SHIPPING CARTON

- Carton:** Export carton — size-wise packing per color
- Carton Label:** Brand: SteelStag | Style Code | Color | Size | Qty | PO No.

9. SAMPLING & APPROVAL PROCESS

Stage	Requirement	Approval
Lab Dip	All 5 colors — reactive dyed on approved 125 GSM combed cotton	Written approval required before bulk

Fit Sample	1 pc per style in size M (Seaport Teal or Bright White)	Measurement + visual sign-off
Pre-Production	1 pc per style × all 5 colors	Final approval before cutting
Top of Production	2 pcs per style × per color from first bulk roll	Retained as bulk standard

Sample Shipment: All approval samples (lab dips, fit, pre-production) to be shipped to buyer address via DHL or FedEx express. Share AWB tracking number on dispatch. Buyer will provide written sign-off within 5 working days of receipt.

10. QUALITY & COMPLIANCE

Shrinkage: Max ±3% (length & width) after 3 washes at 30°C

Color Fastness: Min Grade 4 — washing, rubbing, perspiration

Pilling: Min Grade 3–4 after 1000 cycles

GSM Tolerance: ±5 GSM from approved standard

AQL: 2.5 — inline and final inspection

Certification: OCS / BCI certificate for cotton preferred — provide mill test report with sample

Shade Consistency: Shade variation within the same dye lot not to exceed Grade 4 on the Grey Scale (ISO 105-A02). Each dye lot to be accompanied by a shade band (lightest and darkest acceptable piece). Pieces outside the shade band to be rejected.