

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor $g[i]$, which is the minimum size of a cookie that the child will be content with; and each cookie j has a size $s[j]$. If $s[j] \geq g[i]$, we can assign the cookie j to the child i , and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

```
3
1 2 3
2
1 1
```

Output:

```
1
```

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

$1 \leq g.length \leq 3 * 10^4$

$0 \leq s.length \leq 3 * 10^4$

$1 \leq g[i], s[j] \leq 2^{31} - 1$

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 #include <stdlib.h>
3
4 int compare(const void *a, const void *b)
5 {
6     return (*(int *)a - *(int *)b);
7 }
8
9 int main()
10 {
11     int n, m;
12
13     scanf("%d", &n);
14
15     int g[n];
16
17     for (int i = 0; i < n; i++)
18     {
19         scanf("%d", &g[i]);
20     }
21
22     scanf("%d", &m);
23
24     int s[m];
25
26     for (int i = 0; i < m; i++)
27     {
28         scanf("%d", &s[i]);
29     }
30
31     qsort(g, n, sizeof(int), compare);
32     qsort(s, m, sizeof(int), compare);
33
34     int i = 0;
35     int j = 0;
36     int count = 0;
37
38     while (i < n && j < m)
39     {
```

```

40     if (s[j] >= g[i])
41     {
42         count++;
43         i++;
44         j++;
45     }
46     else
47     {
48         j++;
49     }
50 }
51
52 printf("%d", count);
53
54 return 0;
55 }

```

	Input	Expected	Got	
✓	2	2	2	✓
	1 2			
	3			
	1 2 3			

Passed all tests! ✓