

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```
1  #include <stdio.h>
2
3  int main()
4  {
5      int n;
6      scanf("%d", &n);
7
8      int a[n], b[n];
9
10     for (int i = 0; i < n; i++)
11     {
12         scanf("%d", &a[i]);
13     }
14
15     for (int i = 0; i < n; i++)
16     {
17         scanf("%d", &b[i]);
18     }
19
20
21     for (int i = 0; i < n - 1; i++)
22     {
23         for (int j = i + 1; j < n; j++)
24         {
25             if (a[i] > a[j])
26             {
27                 int temp = a[i];
28                 a[i] = a[j];
29                 a[j] = temp;
30             }
31         }
32     }
33
34
35     for (int i = 0; i < n - 1; i++)
36     {
```

```
37     for (int j = i + 1; j < n; j++)
38     {
39         if (b[i] < b[j])
40         {
41             int temp = b[i];
42             b[i] = b[j];
43             b[j] = temp;
44         }
45     }
46 }
47
48 long long sum = 0;
49
50 for (int i = 0; i < n; i++)
51 {
52     sum = sum + (long long)a[i] * b[i];
53 }
54
55 printf("%lld", sum);
56
57 return 0;
58 }
```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓