



Comment	Description	Designator	Footprint	LibRef	Quantity
CTAL_ABS06		*1	XTAL-ABS06	XTAL_ABS06	
Reed_MK24	Ceramic Chip	*2	Reed MK24-B-3	Reed_MK24	
22.5pF	Capacitor - Standard	C1, C2	0402	C0402	
I.OuF	Ceramic Chip Capacitor - Standard	C3, C10, C11	0402	C0402	
10nF	Ceramic Chip Capacitor - Standard	C4, C12	0402	C0402	
).1uF	Ceramic Chip Capacitor - Standard	C5, C6, C7, C20	0402	C0402	
17uF	capacitor - Standard	C7	Tant0805	Tant0805	
).1 uF	Ceramic Chip Capacitor - Standard	C8, C9	0402	C0402	
0603	Ceramic Chip	C13, C16, C21	0603	C0603	
luF	Capacitor - Standard	C14, C15	Tant0805	Tant0805	
	Ceramic Chip				
100nF	Capacitor - Standard	C17, C19	0402	C0402	
l0uF		C18	Tant0805	Tant0805	
Shottky		D1	DFLS130	DFLS130	
ED_0603 800Ohm	Ferrite 25mOhm@DC, 60	D3, D4 L1	Diode0603 0805 (M2125) Ferrite	LED_0603 Ferrite 0805(M2125) 3A	
	Ohm@100MHz				
17uH		L2	Inductor KLZ1608AHR	Inductor KLZ1608	
I00uH		L3	Inductor_NLV32T	Inductor_NLV32T	
?7uH		L4	Inductor MLZ2012M220WT000	Inductor MLZ2012M220WT000	
2.2uH		L5	Inductor KLZ1608AHR	Inductor KLZ1608	
nicroSD	 	P1	Molex microSD	microSD Molex tiny	
1x2 1.27mm		P2	Header1x2 1.27mm	Header 1x2 1.27mm	
PIEZO		P3	PIEZO	PIEZO	
Cortex Debug		P4	Header_2x5_50mil	CortexDebug	
IDR_4x1_2mm		P5	Hdr_4x1_2mm	HDR_4x1_2mm	
HDR_2x1_2mm		P6	HDR_2x1_2mm	HDR_2x1_2mm	
PMF250XN,115	N-Channel Trench MOSFET, 30 V, 0.9 A, - 55 to 150 degC, 3-Pin SOT323, Tape and Reel	Ω1	NXP-SOT323_N	PMF250XN,115	
10K	Precision Thick Film Chip Resistor, 10 Ohm to 1M Ohm Range, 1% and 0.5% Tolerance, 0603 Size, 0.063 W	R1	3-0603	ERJ3RK	
100k	Precision Thick Film Chip Resistor, 10 Ohm to 1M Ohm Range, 1% and 0.5% Tolerance, 0603 Size, 0.063 W	R2, R3	3-0603	ERJ3RK	
Do not place	Precision Thick Film Chip Resistor, 10 Ohm to 1M Ohm Range, 1% and 0.5% Tolerance, 0603 Size, 0.063 W	R4	3-0603	ERJ3RK	
2k	Precision Thick Film Chip Resistor, 10 Ohm to 1M Ohm Range, 1% and 0.5% Tolerance, 0603 Size, 0.063 W	R5	3-0603	ERJ3RK	
330X	Precision Thick Film Chip Resistor, 10 Ohm to 1M Ohm Range, 1% and 0.5% Tolerance, 0603 Size, 0.063 W	R6, R7	3-0603	ERJ3RK	
1.7k	Precision Thick Film Chip Resistor, 10 Ohm to 1M Ohm Range, 1% and 0.5% Tolerance, 0603 Size, 0.063 W	R8, R9	3-0603	ERJ3RK	
ATSAMD21GA-MUT		U1	QFN127P600-8N	ATSAMD21G18	
.P3985IM5-3.3	Micropower, 150mA Low-Noise Ultra Low- Dropout CMOS	U2, U4	MF05A_N	LP3985IM5-3.3	
	Voltage Regulator, 5- pin SOT-23			1	
PS62740	piii 3U1-23	U5	TPS6274x	TPS6274x	
VICP73831T-2DCI/OT	Miniature Single- Cell, Fully Integrated Li-lon, Li-Polymer Charge Management Controller, 4.2V, 5- Pin SOT-23, Industrial Temperature, Tape and Reel	U6	SOT-23-OT5_N	MCP73831T-2DCI/OT	
					I.
ICADC12	and Reel	117	ICA 12	LICADCIA	
		U7	LGA-12	LIS2DS12	
LIS2DS12 Level Shifter	Voltage level translator	U7 U8, U9	LGA-12 DHVQFN14	LIS2DS12 NTB0104	