



MINEW BeaconPlus Frame Definition

Version: V004

Date: 8/24/2022

- Apple iBeacon				
Offset	Length	Type	Data	Details
0	1	Data Length	0x02	/
1	1	Flag data type	0x01	/
2	1	Flag data	0x06	/
3	1	Data Length	0x1A	/
4	1	Manufacture Data	0xFF	/
5	2	Company ID	0x4C00	(little-endian) 0x004C
7	1	Beacon Type	0x02	(big-endian)0x02
8	1	Data Len	0x15	Beacon Adv data len
9	16	UUID	0x0112233445566778 899AABBCCDDEEFF0	(big-endian) 0x011223344556677889 9AABBCCDDEEFF0
25	2	Major	0x03E8	(big-endian)0x03E8
27	2	Minor	0x07D0	(big-endian)0x07D0
29	1	RSSI at 1m	0xC5	-59dBm

- Eddystone UID				
Offset	Length	Type	Data	Details
0	1	Data Length	0x02	/
1	1	Flag data type	0x01	/
2	1	Flag data	0x06	/
3	1	Data Length	0x03	/
4	1	Complete list of 16-bit Service UUIDs	0x03	/
5	2	UUID data	0xAAFE	(little-endian) 0xFEAA
7	1	Data Length	0x15	/
8	1	Service data	0x16	/
9	2	UUID data	0xAAFE	(little-endian) 0xFEAA
11	1	Frame Type	0x00	/
12	1	Ranging Data	0x00	Calibrated txpwr at 0m
13	10	Namespace	0x0112233445566778 8990	(big-endian) 0x0112233...
23	6	Instance ID	0xaabbccdde00	(big-endian) 0xaabbccdde00

- Eddystone URL				
Offset	Length	Type	Data	Details
0	1	Data Length	0x02	/
1	1	Flag data type	0x01	/
2	1	Flag data	0x06	/
3	1	Data Length	0x03	/
4	1	Complete list of 16-bit Service UUIDs	0x03	/
5	2	UUID data	0xAAFE	(little-endian) 0xFEAA
7	1	Data Length	0x10	0x07 + sizeof(Encoded URL)
8	1	Service data	0x16	/
9	2	UUID data	0xAAFE	(little-endian) 0xFEAA
11	1	Frame Type	0x10	/
12	1	Ranging Data	0x00	Calibrated txpwr at 0m
13	1	URL Scheme Prefix	0x00	http://www.
14	1-16	Encoded URL	"minewtech"	/
15+	1	HTTP URL encoding	0x00	.com/

- Eddystone TLM				
Offset	Length	Type	Data	Details
0	1	Data Length	0x02	/
1	1	Flag data type	0x01	/
2	1	Flag data	0x06	/
3	1	Data Length	0x03	/
4	1	Complete list of 16-bit Service UUIDs	0x03	/
5	2	UUID data	0xAAFE	(little-endian) 0xFEAA
7	1	Data Length	0x11	/
8	1	Service data	0x16	/
9	2	UUID data	0xAAFE	(little-endian) 0xFEAA
11	1	Frame Type	0x20	/
12	1	Version	0x00	/
13	2	Battery Voltage	0x0BB8	(big-endian) 3000mV
15	2	Temperature	0x1973	(8.8 fixed-point) 25.44°C
17	4	Adv Count	0x000003E8	(big-endian) 1000 times
21	4	Seconds Count	0x00000258	(big-endian)60 senconds

- Minew Device Info				
Offset	Length	Type	Data	Details
0	1	Data Length	0x02	/
1	1	Flag data type	0x01	/
2	1	Flag data	0x06	/
3	1	Data Length	0x03	/
4	1	Complete list of 16-bit Service UUIDs	0x03	/
5	2	UUID data	0xE1FF	(little-endian) 0xFFE1
7	1	Data Length	/	0x0C + sizeof(name)
8	1	Service data	0x16	/
9	2	UUID data	0xE1FF	(little-endian) 0xFFE1
11	1	Frame Type	0xA1	0xA1
12	1	Version Number	0x08	/
13	1	Battery level	0x64	Battery level is 100%
14	6	Mac address	0x009078563412	(little-endian) 12:34:56:78:90:00
20	n	Name	"YLWL"(default)	/

- Configuration Advertising				
Offset	Length	Type	Data	Details
0	1	Data Length	0x02	/
1	1	Flag data type	0x01	/
2	1	Flag data	0x06	/
3	1	Data Length	0x03	/
4	1	Complete list of 16-bit Service UUIDs	0x03	/
5	2	UUID data	0xAAFF	(little-endian) 0xFFAA
7	1	Data Length	0x11	/
8	1	Complete list of 128-bit Service UUIDs	0x07	/
9	16	UUID data	0x9ECADC240EE5A9E093F304820100287 F	(little-endian)