

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LINUX SHELL SCRIPTING

SIIC IIT KANPUR

www.oranelabs.com

SIIC IIT KANPUR

www.oranelabs.com

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

Scripting Languages Versus Compiled

ORANE LABS

ORANE LABS

ORANE LABS

- Most medium and large-scale programs are written in a compiled language, such as Fortran, Ada, Pascal, C, C++, or Java.

• The benefit of compiled languages is that they're efficient.

- Their disadvantage is that they usually work at a low level, dealing with bytes, integers, floating-point numbers, and other machine-level kinds of objects.

• For example, it's difficult in C++ to say something simple like "**copy all the files in this directory to that directory over there**".

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

- So-called scripting languages are usually interpreted.

ORANE LABS

The advantage to scripting languages is that they often work at a higher level than compiled languages, being able to deal more easily with objects such as files and directories.

- Examples of scripting languages include awk,

Perl, Python, Ruby, and the shell.

ORANE LABS

ORANE LABS

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

reasons to use a shell script

ORANE LABS

ORANE LABS

ORANE LABS

- **Simplicity**

— The shell is a high-level language; you can express

complex operations clearly and simply using it.

- **Portability**

— By using just POSIX-specified features, you have a

good chance of being able to move your script, unchanged, to different kinds of systems.

- **Ease of development**

— You can often write a powerful, useful script in little time.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

A Simple Script

ORANE LABS

- Let's start with a simple script. Suppose that you'd like to know how many users are currently logged in. The who command tells you who is logged in:

SIIC IIT KANPUR

\$ who

george pts/2
betsy pts/3

SIIC IIT KANPUR

Dec 31 16:39 (valley-forge.example.com)
Dec 27 11:07 (flags-r-us.example.com)

SIIC IIT KANPUR

- On a large multiuser system, the listing can scroll off the screen before you can count all the users, and doing that every time is painful anyway.
- This is a perfect opportunity for automation.

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

- What's missing is a way to count the number of users. For that, we use the wc (word count) program.

SIIC IIT KANPUR

\$ who | wc -l

SIIC IIT KANPUR

Count users

SIIC IIT KANPUR

- The next step is to make this pipeline into a separate command. You do this by entering the commands into a regular file, and then making the file executable, with chmod, like so:

ORANE

```
$ cat > nusers
who | wc -l
^D
$ chmod +x nusers
$ ./nusers
```

SIIC IIT K

www.orane

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

Create the file, copy terminal input with cat
 Program text
 Ctrl-D is end-of-file
 Make it executable
 Do a test run
 Output is what we expect

ORANE LABS

ORANE LABS

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

- You have already seen how we can view and

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

- You have already seen how we can view and

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

Environment variables

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

- You have already seen how we can view and

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

- You can also use them in your scripts.

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

```
$ cat test2  
#!/bin/bash  
# display user information from the system.  
echo "User info for userid: $USER"  
echo UID: $UID  
echo HOME: $HOME  
$
```

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

• Look at this Example:

• \$ echo "The cost of the item

• The cost of the item is 5

• The correct technique:

• \$ echo "The cost of the item

• The cost of the item is \$15

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

An Example
ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

```
# display user information from the system.  
echo "User info for userid: $USER"  
echo UID: $UID  
echo HOME: $HOME  
$
```

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

A Drawback
ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

• Look at this Example:

• \$ echo "The cost of the item

• The cost of the item is 5

• The correct technique:

• \$ echo "The cost of the item

• The cost of the item is \$15

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

- User variables can be any text string of up to 20 letters, digits, or an underscore character.

User variables are case sensitive.

- Here are a few examples of assigning values to user variables:

— var1=10

— var2=-57

— var3=testing

— var4="still more testing"

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

SII C IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

SII C IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

SII C IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

SII C IIT KANPUR

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC \$ cat test3

#!/bin/bash

testing variables

days=10

SIIC guest="Katie"

echo "\$guest checked in \$days days ago"

days=5

ORANE LABS guest="Jessica"

SIIC echo "\$guest checked in \$days days ago"

\$

ORANE LABS

SIIC IIT KANPUR

SII C IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

SII C IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

SII C IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

SII C IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

SII C IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC \$

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SII C IIT KANPUR

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

www.oranelabs.com

Using backtick

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

Performing Maths

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

Operator	Description	
C ARG1 ARG2	Return ARG1 if neither argument is null or zero; otherwise, return ARG2.	S
S ARG1 & ARG2	Return ARG1 if neither argument is null or zero; otherwise, return 0.	
S ARG1 < ARG2	Return 1 if ARG1 is less than ARG2; otherwise, return 0.	R
W ARG1 <= ARG2	Return 1 if ARG1 is less than or equal to ARG2; otherwise, return 0.	m
W ARG1 = ARG2	Return 1 if ARG1 is equal to ARG2; otherwise, return 0.	
C ARG1 != ARG2	Return 1 if ARG1 is not equal to ARG2; otherwise, return 0.	S
S ARG1 >= ARG2	Return 1 if ARG1 is greater than or equal to ARG2; otherwise, return 0.	
S ARG1 > ARG2	Return 1 if ARG1 is greater than ARG2; otherwise, return 0.	R
W ARG1 + ARG2	Return the arithmetic sum of ARG1 and ARG2.	m
ARG1 - ARG2	Return the arithmetic difference of ARG1 and ARG2.	
C ARG1 * ARG2	Return the arithmetic product of ARG1 and ARG2.	S
S ARG1 / ARG2	Return the arithmetic quotient of ARG1 divided by ARG2.	R
S ARG1 % ARG2	Return the arithmetic remainder of ARG1 divided by ARG2.	

ORANE LABS

ORANE LABS
ORANE INFOSYSTEM PVT. LTD.

ORANE LABS

ORANE LABS

Example
ORANE LABS

ORANE LABS

- To assign the result of a mathematical equation to a variable, you have to use the backtick character to extract the output from the expr command

ORANE LABS

ORANE LABS
ORANE INFOSYSTEM PVT. LTD.

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR • Using brackets

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com \$ var1=\$[1 + 5]

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR 6

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com \$ var2 = \$\$var1 * 2

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

12

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com \$

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR #!/bin/bash

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com var1=100

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR var2=50

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com var3=45

www.oranelabs.com

www.oranelabs.com

echo The final result is \$var4

echo The final result is \$var4

echo The final result is \$var4

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR \$

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

ORANE INFOSYSTEM PVT. LTD.

ORANE INFOSYSTEM PVT. LTD.

Commenting and Documenting Scripts

- In Unix shells, comment lines begin with a hashmark character (#). Anything that comes after the hashmark is taken to be a comment and is not interpreted as a command.

Here is a comment that spans multiple lines.

- In addition, a hashmark can be inserted into the middle of a line, and everything to the right of it will be considered a comment:
- ```
some_command # This is a comment explaining the
command
```

**ORANE LABS**

**ORANE LABS**  
ORANE INFOSYSTEM PVT. LTD.

**ORANE LABS**

## Invoking the Shell

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

- Before you add anything else to your script, you need to alert the system that a shell script is being started. This is done using the **shebang construct**. For example,

- `#!/bin/bash`
- tells the system that the commands that follow are to be executed by the bash shell.

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

## Performing Floating Calculations

ORANE LABS

ORANE LABS

ORANE LABS

- Floating point calculations can be performed using the bc command.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

- Example:

ORANE LABS

ORANE LABS

ORANE LABS

```
— echo "4 * 0.56" | bc
```

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

- Specifying decimal precision (scale): In the following example the scale=2 parameter sets the number of decimal places to 2. Hence the output of bc will contain a number with two decimal places:

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

```
— echo "scale=2;3/8" | bc
```

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

## Special Variables

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

| Variable | Function                                                                                                                                                                                  |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| w        | The previous command's exit status.                                                                                                                                                       |
| C        | The PID of the current shell process.                                                                                                                                                     |
| S        | Options invoked at start-up of the current shell.                                                                                                                                         |
| !        | The PID of the last command that was run in the background.                                                                                                                               |
| W        | The filename of the current script.                                                                                                                                                       |
| 1-9      | The first through ninth command-line arguments given when the current script was invoked: \$1 is the value of the first command-line argument, \$2 the value of the second, and so forth. |
| #        | The last argument given to the most recently invoked command before this one.                                                                                                             |

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

\$# Represents the Number of Command Line Arguments

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

- The \$?variable represents the exit status of the previous command.
- Exit status is a numerical value returned by every command upon its completion.
- As a rule, most commands return an exit status of 0 if they were successful, and 1 if they were unsuccessful.

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

\$ date

Sat Sep 29 10:01:30 EDT 2007

**ORANE LABS**

SIIC IIT KANPUR

\$ echo \$?

0

www.oranelabs.com

\$

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**Exit Status  
ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**  
ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

**Example  
ORANE LABS**

SIIC IIT KANPUR

\$ date

Sat Sep 29 10:01:30 EDT 2007

**ORANE LABS**

SIIC IIT KANPUR

\$ echo \$?

0

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**



www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

## The exit command

ORANE LABS

ORANE LABS

ORANE LABS

- You can change that to return your own exit status code. The exit command allows you to specify an exit status when your script ends:

ORANE LABS

ORANE LABS

ORANE LABS

#!/bin/bash  
# testing the exit status

SIIC IIT KANPUR  
var1=10

SIIC IIT KANPUR  
var1=10

SIIC IIT KANPUR  
var1=10

var2=30  
var3=\$[ \$var1 + var2 ]

echo The answer is \$var3  
exit 5

echo The answer is \$var3  
exit 5

echo The answer is \$var3  
exit 5

ORANE LABS

ORANE LABS

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

## Variables can also be used with exit

ORANE LABS

ORANE LABS

ORANE LABS

#!/bin/bash

# testing the exit status

var1=10

var2=30

var3=\$[ \$var1 + var2 ]

exit \$var3

\$

www.oranelabs.com

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

**ORANE LABS**

SIIC IIT #!/bin/bash  
# testing the exit status  
www.oranelabs.com  
var1=10

**ORANE LABS**

var2=30

www.oranelabs.com

**Limitations**  
**ORANE LABS**

SIIC IIT KANPUR  
echo The value is \$var3  
www.oranelabs.com  
exit \$var3

**ORANE LABS**

\$

**ORANE LABS**

**exit codes can go up to 255.**

SIIC IIT KANPUR  
**If the code exceeds this number, the result will be the  
code modulo 256**

**ORANE LABS**

**ORANE LABS**

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR  
www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR  
www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR  
www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

SIIC IIT KANPUR  
• The default for standard input, standard  
output, and standard error is the terminal.

This can be seen with cat:

SIIC IIT KANPUR  
\$ cat  
WW now is the time  
now is the time  
for all good men

SIIC IIT KANPUR  
With no arguments, read standard input, write standard output  
Typed by the user  
Echoed back by cat

SIIC IIT KANPUR

**ORANE LABS**

SIIC IIT KANPUR  
m

5

SIIC IIT KANPUR  
www.oranelabs.com

SIIC IIT KANPUR  
www.oranelabs.com

SIIC IIT KANPUR  
www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

ORANE INFOSYSTEM PVT. LTD.

**ORANE LABS**

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

## Redirection and pipelines

ORANE LABS

ORANE LABS

ORANE LABS

- Change standard input with <

- Use program < file to make program's standard input be file:

• tr -d '\r' < dos-file.txt ...

- Change standard output with >

- Use program > file to make program's standard output be file:

• tr -d '\r' < dos-file.txt > unix-file.txt

- The > redirector creates the destination file if it doesn't exist. However, if the file does exist, then it is truncated; all existing contents are lost.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

- Append to a file with >>

- Use program >> file to send program's standard output to the end of file.

- Like >, the >> operator creates the destination file if it doesn't exist.

- However, if it already exists, instead of truncating the file, any new data generated by the running program is appended to the end of the file:

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

- Create pipelines with |
  - Use program1 | program2 to make the standard output of program1 become the standard input of program2.

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

- Putting everything together:
  - tr -d '\r' < dos-file.txt | sort > unix-file.txt

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

## Basic Command Searching

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

- The shell searches for commands along the search path, **\$PATH**.

www.oranelabs.com

www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

- This is a colon-separated list of directories in which commands are found.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

• The default path varies from system to system.

It will contain at least /bin and /usr/bin.

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

ORANE INFOSYSTEM PVT. LTD.

- The term “bin” for directories that hold executables is short for binary.
- When you write your own scripts, it would be nice to have your own bin in which to place them, and have the shell find them automatically. For Example:

SIIC IIT KANPUR  
\$ cd  
\$ mkdir bin  
\$ mv nusers bin  
\$ PATH=\$PATH:\$HOME/bin  
\$ nusers

SIIC IIT KANPUR  
6

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

Change to home directory  
Make a personal “bin” directory  
Put our script there  
Append our bin directory to PATH  
Test it out

The shell finds it

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

.bs.com  
Put our script there  
Append our bin directory to PATH  
Test it out

The shell finds it

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

## Simple Execution Tracing

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

- One way to get some idea of what your program is doing is to turn on execution tracing.
- This causes the shell to print out each command as it’s executed, preceded by “+”— that is, a plus sign followed by a space.

\$ sh -x nusers  
+ who  
+ wc -l

7

Run with tracing on  
Traced commands

Actual output

KANPUR

ielabs.com

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

- The bash calculator allows you to enter floating-point expressions at a command line, then interprets the expressions, calculates them, and returns the result. The bash calculator recognizes:

- Numbers (both integer and floating point)
- Variables (both simple variables and arrays)
- Comments (lines starting with a pound sign or the C language /\* \*/ pair)
- Expressions
- Programming statements (such as if-then statements)
- Functions

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

**ORANE LABS**

**Using Scale**  
**ORANE LABS**

**ORANE LABS**

- The floating-point arithmetic is controlled by a built-in variable called scale.

– \$ bc -q  
ORANE LABS – 3.44 / 5

**ORANE LABS**

**ORANE LABS**

– 0  
www.oranelabs.com – scale=4  
ORANE LABS – 3.44 / 5  
– .6880

SIIC IIT KANPUR

SIIC IIT KANPUR

– quit  
www.oranelabs.com – \$

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

- Besides normal numbers, the bash calculator also understands variables:

www.oranelabs.com

\$ bc -q

**ORANE LABS**

var1=10

var1 \* 4

40

var2 = var1 / 5

print var2

2

quit

\$

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

Variables in bc

**ORANE LABS**

SIIC IIT KANPUR

40

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

**ORANE LABS**

Variables in bc

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

Using bc in scripts

**ORANE LABS**

SIIC IIT KANPUR

• The basic format to use is:

— variable= echo "options; expression" | bc

**ORANE LABS**

SIIC IIT KANPUR

• The first portion, options, allows us to set variables.

SIIC IIT KANPUR

• If you need to set more than one variable, separate

them using the semicolon.

SIIC IIT KANPUR

• The expression parameter defines the mathematical

expression to evaluate using bc.

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

`#!/bin/bash`

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

`$`

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

`#!/bin/bash`

var1=100

**ORANE LABS**

`var2=45`

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

`$`

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**Example**  
**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

**Example**  
**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

`$`

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

`$`

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

| SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

- And of course, once a value is assigned to a variable, that variable can be used in yet another calculation:

**ORANE LABS**

```
#!/bin/bash
```

SIIC IIT KANPUR

var1=20

SIIC IIT KANPUR

var2=3.14159

**ORANE LABS**

```
#!/bin/bash
```

SIIC IIT KANPUR

```
var3=`echo "scale=4; $var1 * $var1"
var4=`echo "scale=4; $var3 * $var2"
```

SIIC IIT KANPUR

echo The final result is \$var4

SIIC IIT KANPUR

\$

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

```
| bc`
| bc`
```

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

## Another Technique

**ORANE LABS**

#!/bin/bash

var1=10.46

var2=43.67

var3=33.2

var4=71

var5=`bc << EOF

SIIC IIT KANPUR

scale = 4

a1 = ( \$var1 \* \$var2)

b1 = (\$var3 \* \$var4)

a1 + b1

EOF

,

SIIC IIT KANPUR

echo The final answer for this mess is \$var5

\$

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

ORANE INFOSYSTEM PVT. LTD.

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

**Flow Control  
ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

**ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

ORANE INFOSYSTEM PVT. LTD.

SIIC IIT KANPUR

www.oranelabs.com

**ORANE LABS**

**ORANE LABS**

ORANE INFOSYSTEM PVT. LTD.

**ORANE LABS**

## The if-then Statement

**ORANE LABS**

**ORANE LABS**

**ORANE LABS**

- The heart of conditional flow control is the if-then statement. In general terms, an if-then statement looks like this:
- ```

if some_condition
then
    something happens
fi

```

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

#!/bin/bash

testing the if statement

ORANE LABS

ORANE LABS

if date

then

SIIC IIT KANPUR

echo "it worked"

ORANE LABS

ORANE LABS

fi

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

ORANE LABS

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

#!/bin/bash

ORANE LABS ORANE LABS

echo "Guess the secret color"

LABS

read COLOR

if [\$COLOR="purple"]

then

ORANE LABS

echo "You are correct."

SIIC IIT KANPUR

fi

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

SIIC IIT KANPUR

• You're not limited to just one command in the

then section.

ORANE LABS

#!/bin/bash

SIIC IIT KANPUR

testing multiple commands in the then section

SIIC IIT KANPUR

testuser=ankur

SIIC IIT KANPUR

if grep \$testuser /etc/passwd

SIIC IIT KANPUR

then

ORANE LABS

echo The bash files for user \$testuser are:

SIIC IIT KANPUR

ls -a /home/\$testuser/.b*

SIIC IIT KANPUR

fi

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

The if-then-else Statement

ORANE LABS

ORANE LABS

ORANE LABS

- The if-then-else statement provides another group of commands in the statement:

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR
commands

SIIC IIT KANPUR
www.oranelabs.com

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS
commands

ORANE LABS

ORANE LABS

SIIC IIT KANPUR
fi

SIIC IIT KANPUR
www.oranelabs.com

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

Adding an else

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR
#!/bin/bash

SIIC IIT KANPUR
echo "Guess the secret color"

SIIC IIT KANPUR

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR
read COLOR

SIIC IIT KANPUR
if [\$COLOR="purple"]

SIIC IIT KANPUR

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR
then

SIIC IIT KANPUR
echo "You are correct."

SIIC IIT KANPUR

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

fi

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC #!/bin/bash
testing the else section
www.oranelabs.com testuser=badtest

ORANE LABS if grep \$testuser /etc/passwd
then
SIIC IIT KANPUR SIIC IIT KANPUR echo The files for user \$testuser are:
www.oranelabs.com ls -a /home/\$testuser/.b*

ORANE LABS else
echo "The user name \$testuser doesn't exist on this
SIIC IIT KANPUR system"
fi
www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR • The elif continues an else section with another
www.oranelabs.com if-then statement:

ORANE LABS if command1
then
SIIC IIT KANPUR commands
www.oranelabs.com elif command2

ORANE LABS

SIIC IIT KANPUR then
more commands
www.oranelabs.com fi

ORANE LABS

ORANE LABS

SIIC IIT KANPUR # testing the else section
www.oranelabs.com testuser=badtest

ORANE LABS if grep \$testuser /etc/passwd
then
SIIC IIT KANPUR SIIC IIT KANPUR echo The files for user \$testuser are:
www.oranelabs.com ls -a /home/\$testuser/.b*

ORANE LABS else
echo "The user name \$testuser doesn't exist on this
SIIC IIT KANPUR system"
fi
www.oranelabs.com

ORANE LABS

www.oranelabs.com

Nesting ifs ORANE LABS

SIIC IIT KANPUR • The elif continues an else section with another
www.oranelabs.com if-then statement:

ORANE LABS if command1
then
SIIC IIT KANPUR commands
www.oranelabs.com elif command2

ORANE LABS

SIIC IIT KANPUR then
more commands
www.oranelabs.com fi

ORANE LABS

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

Using elif to specify another condition

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

echo "Guess the secret color"

www.oranelabs.com

www.oranelabs.com

read COLOR

if [\$COLOR="purple"]

then

SIIC IIT KANPUR

echo "You are correct."

www.oranelabs.com

elif [\$COLOR="blue"]

echo "You're close."

else

SIIC IIT KANPUR

echo "Your guess was incorrect."

www.oranelabs.com

fi

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

The test Command

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

• The test command is used to evaluate

conditions.

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

• For example, the preceding script could have

been written:

– if (test \$COLOR="purple")

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

fi

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

Syntax

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

**Three Classes
ORANE LABS**

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

- There are three classes of conditions the test command can evaluate:

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

#!/bin/bash

using numeric test comparisons

www.oranelabs.com

val1=10

val2=11

ORANE LABS

if [\$val1 -gt 5]

then

echo "The test value \$val1 is greater than 5"

fi

if [\$val1 -eq \$val2]

then

echo "The values are equal"

else

echo "The values are different"

fi

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

val1=10

val2=11

ORANE LABS

if [\$val1 -gt 5]

then

echo "The test value \$val1 is greater than 5"

fi

if [\$val1 -eq \$val2]

then

echo "The values are equal"

else

echo "The values are different"

fi

www.oranelabs.com

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

The test Numeric Comparisons

ORANE LABS **ORANE LABS** **ORANE LABS**

S	Comparison	Description	PUR
W	<code>n1 -eq n2</code>	Check if <code>n1</code> is equal to <code>n2</code> .	.com
	<code>n1 -ge n2</code>	Check if <code>n1</code> is greater than or equal to <code>n2</code> .	
C	<code>n1 -gt n2</code>	Check if <code>n1</code> is greater than <code>n2</code> .	BS
S	<code>n1 -le n2</code>	Check if <code>n1</code> is less than or equal to <code>n2</code> .	PUR
	<code>n1 -lt n2</code>	Check if <code>n1</code> is less than <code>n2</code> .	
W	<code>n1 -ne n2</code>	Check if <code>n1</code> is not equal to <code>n2</code> .	.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

Comparison Operators

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

if[\$COLOR != "purple"]

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

The test Command String Comparisons

Comparison	Description
<code>str1 = str2</code>	Check if <code>str1</code> is the same as string <code>str2</code> .
<code>str1 != str2</code>	Check if <code>str1</code> is not the same as <code>str2</code> .
<code>str1 < str2</code>	Check if <code>str1</code> is less than <code>str2</code> .
<code>str1 > str2</code>	Check if <code>str1</code> is greater than <code>str2</code> .
<code>-n str1</code>	Check if <code>str1</code> has a length greater than zero.
<code>-z str1</code>	Check if <code>str1</code> has a length of zero.

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

Example
ORANE LABS

\$ cat test8

SIIC IIT KANPUR

#!/bin/bash

www.oranelabs.com

testing string equality

ORANE LABS

testuser=baduser

if [\$USER != \$testuser]

SIIC IIT KANPUR

then

www.oranelabs.com

echo "This isn't \$testuser"

ORANE LABS

else

SIIC IIT KANPUR

echo "Welcome \$testuser"

fi

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS
ORANE INFOSYSTEM PVT. LTD.

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

String order

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

This will not run

ORANE LABS

SIIC IIT KANPUR

mis-using string comparisons

val1=baseball

val2=hockey

if [\$val1 > \$val2]

then

echo "\$val1 is greater than \$val2"

else

echo "\$val1 is less than \$val2"

fi

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

```
#!/bin/bash  
# mis-using string comparisons  
val1=baseball
```

ORANE LABS

```
val2=hockey  
if [ $val1 > $val2 ]  
then  
echo "$val1 is greater than $val2"  
else  
echo "$val1 is less than $val2"  
fi
```

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

```
$ cat test10  
#!/bin/bash  
# testing string length  
val1=testing  
val2=""
```

www.oranelabs.com

ORANE LABS

```
if [ -n $val1 ]  
then  
echo "The string '$val1' is not empty"  
else  
echo "The string '$val1' is empty"  
fi
```

www.oranelabs.com

ORANE LABS

```
if [ -z $val2 ]  
then  
echo "The string '$val2' is empty"  
else
```

www.oranelabs.com

ORANE LABS

```
echo "The string '$val2' is not empty"  
fi
```

www.oranelabs.com

**Correct
ORANE LABS**

```
SIIC IIT KANPUR  
# mis-using string comparisons  
val1=baseball
```

ORANE LABS

```
val2=hockey  
if [ $val1 > $val2 ]  
then  
echo "$val1 is greater than $val2"
```

ORANE LABS

```
echo "$val1 is less than $val2"  
fi
```

www.oranelabs.com

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

**String size
ORANE LABS**

```
SIIC IIT KANPUR  
# testing string length  
val1=testing  
val2=""
```

www.oranelabs.com

ORANE LABS

```
if [ -n $val1 ]  
then  
echo "The string '$val1' is not empty"  
else  
echo "The string '$val1' is empty"  
fi
```

www.oranelabs.com

ORANE LABS

```
if [ -z $val2 ]  
then  
echo "The string '$val2' is empty"  
else
```

www.oranelabs.com

ORANE LABS

```
echo "The string '$val2' is not empty"  
fi
```

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

test command File Comparision

ORANE LABS

Comparison	Description
<code>-d file</code>	Check if <i>file</i> exists and is a directory.
<code>-e file</code>	Checks if <i>file</i> exists.
<code>-f file</code>	Checks if <i>file</i> exists and is a file.
<code>-r file</code>	Checks if <i>file</i> exists and is readable.
<code>-s file</code>	Checks if <i>file</i> exists and is not empty.
<code>-w file</code>	Checks if <i>file</i> exists and is writable.
<code>-x file</code>	Checks if <i>file</i> exists and is executable.
<code>-O file</code>	Checks if <i>file</i> exists and is owned by the current user.
<code>-G file</code>	Checks if <i>file</i> exists and the default group is the same as the current user.
<code>file1 -nt file2</code>	Checks if <i>file1</i> is newer than <i>file2</i> .
<code>file1 -ot file2</code>	Checks if <i>file1</i> is older than <i>file2</i> .

ORANE INFOSYSTEM PVT. LTD.

File comparisons

ORANE LABS

- Checking directories
 - The `-d` test checks if a specified filename exists as a directory on the system

```

ORANE LABS #!/bin/bash ORANE LABS ORANE LABS
# look before you leap

```

```

SIIC IIT KANPUR if [ -d $HOME ] SIIC IIT KANPUR SIIC IIT KANPUR
then
  echo "Your HOME directory exists"
  cd $HOME

```

```

ORANE LABS ls -a ORANE LABS ORANE LABS
else

```

```

SIIC IIT KANPUR echo "There's a problem with your HOME directory"
fi

```

```

www.oranelabs.com www.oranelabs.com www.oranelabs.com

```

```

ORANE LABS ORANE LABS ORANE LABS

```

ORANE INFOSYSTEM PVT. LTD.

Checking if an object exists

ORANE LABS

- The `-e` comparison allows you to check if a file or directory object exists before you attempt to use it in your script:

ORANE LABS

```
if [ -e $HOME ]
```

ORANE LABS

```
then
```

SIIC IIT KANPUR

```
echo "OK on the directory, now let's check the file"
```

www.oranelabs.com

```
# checking if a file exists
```

ORANE LABS

```
if [ -e $HOME/testing ]
```

ORANE LABS

```
then # the file exists, append data to it
```

SIIC IIT KANPUR

```
echo "Appending date to existing file"
```

www.oranelabs.com

```
date >> $HOME/testing
```

ORANE LABS

ORANE LABS

www.oranelabs.com

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

ORANE LABS

ORANE LABS

www.oranelabs.com

Checking file date

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

```
#!/bin/bash
```

SIIC IIT KANPUR

```
# testing file dates
```

www.oranelabs.com

```
if [ ./test19 -nt ./test18 ]
```

ORANE LABS

```
then echo "The test19 file is newer than test18"
```

SIIC IIT KANPUR

```
else echo "The test18 file is newer than test19"
```

www.oranelabs.com

```
fi
```

ORANE LABS

```
if [ ./test17 -ot ./test19 ]
```

ORANE LABS

```
then
```

SIIC IIT KANPUR

```
echo "The test17 file is older than the test19 file"
```

www.oranelabs.com

```
fi
```

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

Can you read it

ORANE LABS

ORANE LABS

ORANE LABS

```
#!/bin/bash
# testing if you can read a file
pwfile=/etc/shadow
# first, test if the file exists, and is a file
if [ -f $pwfile ]
then
# now test if you can read it
if [ -r $pwfile ]
then
tail $pwfile
else
echo "Sorry, I'm unable to read the $pwfile file"
fi
else
echo "Sorry, the file $file doesn't exist"
fi
```

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

Checking ownership

ORANE LABS

ORANE LABS

ORANE LABS

```
#!/bin/bash
# check file ownership
if [ -O /etc/passwd ]
then
echo "You're the owner of the /etc/passwd file"
else
echo "Sorry, you're not the owner of the
/etc/passwd file"
fi
```

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
if [condition1]
then

ORANE LABS

SIIC IIT KANPUR
then
some action

ORANE LABS

SIIC IIT KANPUR
fi
www.oranelabs.com

ORANE LABS

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
• Or you could simplify it by using a logical and operator (&&):
www.oranelabs.com if [condition1 && condition2]

ORANE LABS

then
some action
SIIC IIT KANPUR
fi

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com if [condition1 && condition2]

ORANE LABS

SIIC IIT KANPUR
SIIC IIT KANPUR

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com if [condition1 && condition2]

ORANE LABS

SIIC IIT KANPUR
SIIC IIT KANPUR

ORANE LABS

• There is also a logical or operator (||):
www.oranelabs.com if [condition1 || condition2]

ORANE LABS

then
some action
SIIC IIT KANPUR
fi
www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com if [condition1 || condition2]

ORANE LABS

SIIC IIT KANPUR
www.oranelabs.com if [condition1 || condition2]

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

`#!/bin/bash`

www.oranelabs.com

`# testing compound comparisons`

SIIC IIT KANPUR

`if [-d $HOME] && [-w $HOME/testing]`

SIIC IIT KANPUR

`then`

www.oranelabs.com

`echo "The file exists and you can write to it"`

SIIC IIT KANPUR

`else`

www.oranelabs.com

`echo "I can't write to the file"`

`fi`

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

`#!/bin/bash`

`# testing compound comparisons`

`if [-d $HOME] && [-w $HOME/testing]`

SIIC IIT KANPUR

`then`

SIIC IIT KANPUR

`echo "The file exists and you can write to it"`

`else`

SIIC IIT KANPUR

`echo "I can't write to the file"`

`fi`

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

`#!/bin/bash`

`# testing compound comparisons`

`if [-d $HOME] && [-w $HOME/testing]`

SIIC IIT KANPUR

`then`

SIIC IIT KANPUR

`echo "The file exists and you can write to it"`

`else`

SIIC IIT KANPUR

`echo "I can't write to the file"`

`fi`

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

Advanced if-then Features

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

• There are two relatively recent additions to

the bash shell that provide advanced features

that you can use in if-then statements:

— Double parentheses for mathematical expressions

— Double square brackets for advanced string

handling functions

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

Using double parentheses

ORANE LABS

ORANE LABS

ORANE LABS

- The double parentheses command allows you to incorporate advanced mathematical formulas in your comparisons.

- The format of the double parentheses command is:

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

Example
ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

#! /bin/bash

www.oranelabs.com

www.oranelabs.com

using double parenthesis

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

val1=10

www.oranelabs.com

www.oranelabs.com

if ((\$val1 ** 2 > 90))

www.oranelabs.com

www.oranelabs.com

then

www.oranelabs.com

www.oranelabs.com

((val2 = \$val1 ** 2))

www.oranelabs.com

www.oranelabs.com

echo "The square of \$val1 is \$val2"

www.oranelabs.com

www.oranelabs.com

fi

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

www.oranelabs.com

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

The Double Parentheses Command

ORANE LABS

ORANE LABS

ORANE LABS

Symbol	Description	NPUR bs.com
<code>val++</code>	post-increment	
<code>val--</code>	post-decrement	
<code>++val</code>	pre-increment	.LABS
<code>--val</code>	pre-decrement	
<code>!</code>	logical negation	NPUR
<code>~</code>	bitwise negation	bs.com
<code>**</code>	exponentiation	
<code><<</code>	left bitwise shift	.LABS
<code>>></code>	right bitwise shift	
<code>&</code>	bitwise Boolean AND	NPUR
<code> </code>	bitwise Boolean OR	bs.com
<code>&&</code>	logical AND	
<code> </code>	logical OR	.LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com www.oranelabs.com www.oranelabs.com

Using double brackets

ORANE LABS

ORANE LABS

ORANE LABS

- The double bracket command provides advanced features for string comparisons. The double bracket command format is:

SIIC IIT KANPUR SIIC IIT KANPUR SIIC IIT KANPUR
www.oranelabs.com www.oranelabs.com www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR SIIC IIT KANPUR SIIC IIT KANPUR
www.oranelabs.com www.oranelabs.com www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

`#!/bin/bash`

`# using pattern matching`

`if [[$USER == r*]]`

`then`

`echo "Hello $USER"`

`else`

`echo "Sorry, I don't know you"`

`fi`

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

`case expression in`

`pattern1)`

`action1`

`ORANE LABS`

SIIC IIT KANPUR

`pattern2)`

`action2`

www.oranelabs.com

`pattern3)`

`action3`

SIIC IIT KANPUR

`esac`

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

`www.oranelabs.com`

`www.oranelabs.com`

`if [[$USER == r*]]`

`then`

`SIIC IIT KANPUR`

`echo "Hello $USER"`

`else`

`ORANE LABS`

`echo "Sorry, I don't know you"`

`fi`

www.oranelabs.com

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

SIIC IIT KANPUR

`case expression in`

`pattern1)`

`action1`

`ORANE LABS`

SIIC IIT KANPUR

`pattern2)`

`action2`

www.oranelabs.com

`pattern3)`

`action3`

SIIC IIT KANPUR

`esac`

www.oranelabs.com

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

`www.oranelabs.com`

ORANE LABS

SIIC IIT KANPUR

`www.oranelabs.com`

ORANE LABS

SIIC IIT KANPUR

`www.oranelabs.com`

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

SIIC IIT KANPUR

`case expression in`

`pattern1)`

`action1`

`ORANE LABS`

SIIC IIT KANPUR

`pattern2)`

`action2`

www.oranelabs.com

`pattern3)`

`action3`

SIIC IIT KANPUR

`esac`

www.oranelabs.com

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

ORANE LABS

```
#!/bin/bash
# using the case command
case $USER in
    ankur | root)
        echo "Welcome, $USER"
        echo "Please enjoy your visit";;
        testing)
        echo "Special testing account";;
        jessica)
        echo "Don't forget to log off when you're done";;
        *)
        echo "Sorry, you're not allowed here";;
esac
```

ORANE LABS

www.oranelabs.com

ORANE LABS

```
case `date +%-a` in
    "Mon")
        BACKUP=/home/myproject/data0
        TAPE=/dev/rft0
        # Note the use of the double semi-colon to end each option
        ;;
        # Note the use of the "|" to mean "or"
        "Tue" | "Thu")
        BACKUP=/home/myproject/data1
        TAPE=/dev/rft1
        www.oranelabs.com
        "Wed" | "Fri")
        BACKUP=/home/myproject/data2
        TAPE=/dev/rft2
        ;;
        # Don't do backups on the weekend.
        *)
        BACKUP="none"
        TAPE=/dev/null
        ;;
esac
```

ORANE LABS

www.oranelabs.com

**Example
ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

**Example
ORANE LABS**

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

SIIC IIT KANPUR

www.oranelabs.com

ORANE LABS

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

Some Examples

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

- Identifying the current shell:

- Display the currently used shell as follows:

ORANE LABS

ORANE LABS

ORANE LABS

— echo \$SHELL

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

Check for super user

ORANE LABS

ORANE LABS

ORANE LABS

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

- UID is an important environment variable that can be used to check whether the current script has been run as root user or regular user. For example:

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

— else

ORANE LABS

ORANE LABS

ORANE LABS

— echo "Root user"

SIIC IIT KANPUR

SIIC IIT KANPUR

SIIC IIT KANPUR

www.oranelabs.com

www.oranelabs.com

www.oranelabs.com

- The UID for the root user is 0.

ORANE LABS

ORANE LABS

ORANE LABS

ORANE INFOSYSTEM PVT. LTD.