Chapter 6

(R/W) Approach

There are few levels of *Avoidance* based on the *remaining time to collision.* These levels are summarized in (fig. 6.1).

Figure 6.1: Avoidance levels based on reaction time.

This work will focus on handling *Event Avoidance* and *Reactive Avoidance* and the *Avoidance Path* will be calculated using *Reach set Based Methods.*

The *Preemptive Avoidance* is trying to remove any possible threat prior the flight. The risk mitigation is tedious and its done only when necessary. Even the best *preemptive* avoidance could fail.

The *Reactive Avoidance* is solving most urgent situations with very short reaction opportunity. This work focus on physical obstacles and terrain. Non cooperative intruders are considered partially. The adversary behaviour was omitted.

The *Event Avoidance* has more opportunity to react. Some threats are know prior the flight (geo-fenced areas, ...). The future UTM implementation is also considered as *Event Avoidance*, due the time horizon and authority enforcement.

Basic Idea: Create deterministic finite-time *Reactive Avoidance* based on *Reach sets* to assure *trajectory feasibility.* Enhance method with set of the rules to enable handling more complex situations.

The *Discretization* is the key to assure calculation in finite time. Finite *partition* of *operational space (Known World)* and finite representation of *Reach set* guarantees finite count of calculation steps. Aircraft conflict prediction mentioned in [1].

6.1 (R) Overview

The *Overview* is based on *Existing* Emergency avoidance framework [2] (fig. **??**). To achieve goals defined in *Problem Definition* (sec. **??**, **??**) following *Avoidance Framework Concept* (fig. 6.2) is proposed:


Figure 6.2: Avoidance Framework Concept.

Structure of Avoidance Framework:

1. *Unmanned Aircraft System* (UAS) (Role: Controlled Plant) - the *UAS* is controlled via *interface* implemented as *Movement Automaton*. The model used is described in (sec. **??**).

2. *Movement Automaton* (Role: Control Interface/Predictor) - consumes *Discrete Command Chain* to generate discrete *reference trajectory*, it can be also used as a predictor of *future UAS states* (sec. **??**). The movement Automaton used in this work is given in (sec. **??**).

3. *Sensor Field* (Role: Surveillance Providers), following sensors were considered in this work:

   a. *LiDAR* (Static obstacle detection) - detection of physical obstacles (sec. **??**)

   b. *ADS-B* (Intruder UAS/Plane detection) - detection of intruders whom are broadcasting their position and heading sometimes with future plans and additional parameters. The *intersection models* are given in (sec. **??**, **??**, **??**, **??**).

4. *Information Sources* (Role: Known World Information Enhancers):

   a. *Obstacle Map* (Static Restriction Source) - imposing static soft/hard constraints on *Known Word/Operational Space*. Static constraints are given in (sec. **??**).

b. *Weather Information* (Static/Dynamic Restriction Source) - imposing static/moving soft/hard constraints on *Known World/Operational Space*. Moving constraints are given in (sec. **??**).

c. *Other Airspace Restrictions* - like restricted airspace, geo-fencing and other future constraint sources, all of them are covered by *Static/Dynamic Constraints* for now.

5. *Data Fusion* (Role: Sensor Input Interface) - is the unifying interface to asses *Operational State Properties* mainly *Obstacle Rating, Visibility, Map Obstacle Rating, Intruder Rating* for portion of the space. The partial *ratings* are proposed in related sections. The data fusion procedure with *defuzzyfication* and final assessment into space sets is outlined in (sec. **??**)

6. *Reach Set Approximation* (Role: Reachability Estimator) - as *data fusion* is providing the situation assessment, the *Reach set* is providing maneuvering capability assessment. The introduction is given in (sec. **??**), the properties are defined in (sec. **??**), the approximation methods with constrained expansion are outlined in (sec. **??, ??, ??, ??**). The reach set estimation is main contribution of this work.

7. *Grids: Navigation/Avoidance* (Role: Operation Space Segmentation & Situation Evaluation) - space discretization in polar coordinates grid, different reach sets are used for different grid type, defined in (sec. **??**).

8. *Avoidance loop* (Role: Short Term Decision Maker) - using data from *Sensor fusion* in *Avoidance/Navigation Grid* trimming *Reachable Space* approximated by *Reach Set* generating feasible *Avoidance Path*. *Avoidance Path* is fed to controlling *Movement Automaton*. The Goal is given by *Navigation Loop*. Avoidance loop is given in (sec. **??**).

9. *Navigation loop* (Role: Long Term Decision Maker) - using data from *Avoidance Loop, Mission plan* and *UTM* directives defines the current long term navigation goal. Details given in (sec. **??**).

10. *Command and Control Communication Link* (C2 Link) (Role: Communication Link) - standard communication link with sufficient reliability.

11. *UAS Traffic Management* (UTM) (Controlled Airspace Authority) - checking possible collisions and enforces counter-measurements. Details given in (sec. **??**).

Communication in Avoidance Framework:

1. *UAS ↔ Movement Automaton* - sharing *actual system state*, commanding the UAS platform.

2. *Reach Set ↔ Movement Automaton* - predicting set of feasible trajectories for given situation.

3. *Reach Set ↔ Grids* - providing trajectory set depending on active mode (Navigation/Emergency Avoidance).

4. *Avoidance Loop ↔ Data Fusion* - assessing the situation in *operational space* based on sensor readings/information sources.

5. *Avoidance Loop $\leftrightarrow$ Navigation Loop* - determining long term goal based on situation assessment and UTM directives.

6. *Avoidance Loop $\rightarrow$ Grids* - feeding assessment data and constraints into selected operational space Grid.

7. *Grids $\rightarrow$ Avoidance Loop* - returning feasible and *cost effective* avoidance path after situation assessment and *Reach set* pruning.

8. *Avoidance Loop $\rightarrow$ Movement Automaton* - issuing and monitoring movement commands based on actual *avoidance strategy*.

9. *Navigation Loop $\leftrightarrow$ C2 Link $\leftrightarrow$ UTM* - communication to receive directives and send fulfillment.

Bibliography

[1] Maria Prandini and Jianghai Hu. Application of reachability analysis for stochastic hybrid systems to aircraft conflict prediction. In *Decision and Control, 2008. CDC 2008. 47th IEEE Conference on*, pages 4036–4041. IEEE, 2008.

[2] Alojz Gomola, João Borges de Sousa, Fernando Lobo Pereira, and Pavel Klang. Obstacle avoidance framework based on reach sets. In *Iberian Robotics conference*, pages 768–779. Springer, 2017.