6.2. UAS Model and Control

The key feature of *Movement Automaton* is to interface the *UAS system* as the *discrete command chain*. Following topics are introduced in this section:

1. *Movement Automaton Applications* (sec. 6.2.1) - the listing of related work and similar approaches to ours.
2. *UAS Model* (sec. 6.2.2) - a simple plane model used in this work as the *controlled plant*.
3. *UAS Movement Automaton* (sec. 6.2.3) - movement automaton for *UAS Nonlinear Model* constructed from scratch.

6.2.1. Movement Automaton Applications

Movement Automaton is a basic interface approach for discretization of *trajectory evolution* or *control input* for any *continuous or discrete system model*.

Main function of *Movement Automaton is* for system given by equation $\dot{state} = f(time, state, input)$ with initial state $state_0$ to generate *reference trajectory* $\hat{state}(t)$ or *control signal input*(t).

Using *Movement Automaton* as *Control Proxy* will provide us with *discrete command chain* interface. This will reduce the *non-deterministic* element from *Evasive trajectory* generation, by reducing infinite maneuver set to finite *movement set*.

Non-determinism of *Avoidance Maneuver* has been discussed as an issue in following works:

1. Newton gradient method for evasive car maneuvers [1].
2. Non-holistic methods for trajectory generation [2].
3. Stochastic approach to elliptic trajectories generation [3].

Examples of *Movement Automaton Implementation* as *Control Element* can be mentioned as follows:

1. Control of traffic flow [4].
2. Complex air traffic collision situation resolution system [5, 6].
3. SAA/DAA capable avoidance system [7].

6.2.2. UAS Model

Motivation: Simplified rigid body kinematic model will be used. This model has decoupled roll, yaw and pitch angles. The focus is on *reach set approximation methods*; therefore the *UAS model* is simplified.

State Vector (eq. 6.1) defined as a positional state in euclidean position in right-hand euclidean space, where *x, y, z* can be abstracted as latitude, longitude, altitude.

$$state = [x, y, z, roll, pitch, yaw]^T \tag{6.1}$$

Input Vector (eq. 6.2) is defined as the linear velocity of UAS v and angular speed of rigid body $\omega_{roll}, \omega_{pitch}, \omega_{yaw}$.

$$input = \left[v, \omega_{roll}, \omega_{pitch}, \omega_{yaw}\right]^T \tag{6.2}$$

Velocity vector function (eq. 6.3) is defined through the standard rotation matrix and linear velocity v, oriented velocity $[v_x, v_y, v_z]$ given by (eq. 6.4).

$$\begin{bmatrix} v_x \\ v_y \\ v_z \end{bmatrix} = \begin{bmatrix} v.\cos(pitch)\cos(yaw) \\ v.\cos(pitch)\sin(yaw) \\ -v.\sin(pitch) \end{bmatrix} \tag{6.3}$$

UAS Nonlinear Model (eq. 6.4) is given by *first order equations:*

$$\begin{aligned} \frac{\mathrm{d}x}{\mathrm{d}time} &= v.\cos(pitch)\cos(yaw); & \frac{\mathrm{d}roll}{\mathrm{d}time} &= \omega_{roll}; \\ \frac{\mathrm{d}y}{\mathrm{d}time} &= v.\cos(pitch)\sin(yaw); & \frac{\mathrm{d}pitch}{\mathrm{d}time} &= \omega_{pitch}; \\ \frac{\mathrm{d}z}{\mathrm{d}time} &= -v.\sin(pitch); & \frac{\mathrm{d}yaw}{\mathrm{d}time} &= \omega_{yaw}; \end{aligned} \tag{6.4}$$

Discretization for *fixed step k* we start with discretization of the model:
The *linear velocity* in text step is given:

$$v(k+1) = v(k) + \delta v(k) \tag{6.5}$$

The *roll, pitch, yaw* for next step are given

$$\begin{aligned} roll(k+1) &= roll(k) + \delta roll(k) \\ pitch(k+1) &= pitch(k) + \delta pitch(k) \\ yaw(k+1) &= yaw(k) + \delta yaw(k) \end{aligned} \tag{6.6}$$

The $\delta v(k)$ is *velocity change*, $\delta roll(k)$, $\delta pitch(k)$, $\delta yaw(k)$, are *orientation changes* for current discrete step k. If the duration of *transition* is 0s (as. 1) then 3D trajectory evolution in discrete time is given as:

$$\begin{aligned} x(k+1) &= x(k) + v(k+1)\cos(pitch(k+1))\cos(yaw(k+1)) &&= \delta x(k) \\ y(k+1) &= y(k) + v(k+1)\cos(pitch(k+1))\sin(yaw(k+1)) &&= \delta y(k) \\ z(k+1) &= z(k) - v(k+1)\sin(pitch(k+1)) &&= \delta z(k) \\ time(k+1) &= time(k) + 1 &&= \delta time(k) \end{aligned} \tag{6.7}$$

The $\delta x(k)$, $\delta y(k)$, $\delta z(k)$ are positional differences depending on *input vector* for given discrete time k:

$$input(k) = \begin{bmatrix} \delta x(k), \delta y(k), \delta z(k), \delta v(k), \\ \delta roll(k), \delta pitch(k), \delta yaw(k), \delta time(k) \end{bmatrix}^T \tag{6.8}$$

The *state vector* for discrete time is given:

$$state(k) = \begin{bmatrix} x(k), y(k), z(k), v(k), \\ roll(k), pitch(k), yaw(k), time(k) \end{bmatrix}^T \tag{6.9}$$

6.2.3. UAS Movement Automaton

Motivation: An *UAS Nonlinear Model* (eq. 6.4) can be modeled by *Movement Automaton* (def. **??**).

Movement Primitives by (def. **??**) are given as (eq. **??**). Each movement primitive will last for fixed duration 1*s*.

Assumption 1. *Let assume that* transition time *of* roll, pitch, yaw, and the linear velocity *is* 0*s.*

Under the assumption (as. 1) the *movement transitions* (def. **??**) have zero duration. Therefore movement primitives can be considered as movements.

Note. The assumption (as. 1) can be relaxed under the condition that *path tracking controller exists*.

Movements satisfying (def. **??**), for the nonlinear model (eq. 6.4) reduced to *discrete model* (eq. 6.10), are given by *apply movements* function (eq. 6.5, 6.6, 6.7).

$$state(k+1) = applyMovement(state(k), input(k)) \tag{6.10}$$

Movement Set for the discrete model (eq. 6.10) is defined as a set of unitary movements on main axes (tab. 6.1) and diagonal axes (tab. 6.2).

The maneuvering capability of several commercial small fixed-wing UAS was abstracted together. The turning rate on horizontal/vertical is defined as 15°.

The deltas are posed in *UAS body-fixed coordinate frame* (ap. **??**) for discrete time *k*.

Parameter	Movement				
	Straight	Down	Up	Left	Right
$\delta x(k)[m]$	1.00	0.98	0.98	0.98	0.98
$\delta y(k)[m]$	0	0	0	0.13	-0.13
$\delta z(k)[m]$	0	-0.13	0.13	0	0
$\delta roll(k)[^\circ]$	0	0	0	0	0
$\delta pitch(k)[^\circ]$	0	15°	-15°	0	0
$\delta yaw(k)[^\circ]$	0	0	0	15°	-15°

Table 6.1: Input values for main axes movements.

Parameter	Movement			
	Down-Left	Down-Right	Up-Left	Up-Right
$\delta x(k)[m]$	0.76	0.76	0.76	0.76
$\delta y(k)[m]$	-0.13	0.13	0.13	-0.13
$\delta z(k)[m]$	-0.13	-0.13	0.13	0.13
$\delta roll(k)[^\circ]$	0	0	0	0
$\delta pitch(k)[^\circ]$	-15°	-15°	15°	15°
$\delta yaw(k)[^\circ]$	15°	-15°	15°	-15°

Table 6.2: Input values for diagonal axes movements.

Note. The *movement set* in shortened form is given as:

$$MovementSet = \left\{ \begin{matrix} Straight, Left, Right, Up, Down, \\ DownLeft, DownRight, UpLeft, UpRight \end{matrix} \right\} \tag{6.11}$$

The *implemented movement set example* (fig. 6.1) shows the movement used as basic building blocs of the trajectory for fixed-wing UAS:

1. *Initial position* (red plane) - the initial position, before any movement execution.
2. *Straight movement application* (blue plane) - the *neutral movement application* brings plane forward.
3. *Main axes movements* (cyan planes) - the application of movements from (tab. 6.1) {*Up*, *Down*, *Left*, *Right*}.
4. *Diagonal axes movements* (magenta planes) - the application of movements from (tab. 6.2) {*DownLeft*, *DownRight*, *UpLeft*, *UpRight*}.



Figure 6.1: Implemented movement set example.

Trajectory by (def. **??**) for initial time *time* = 0 , initial state *state*(0) and *Movement Buffer* (from def. **??**):

$$Buffer = \left\{ movement(j) : \begin{array}{l} movement(j) \in MovementSet(eq.6.11), \\ j \in 1 \ldots n, n \in N^{+} \end{array} \right\} \tag{6.12}$$

Assumption 2. *The buffer is always non-empty, ordered, finite list of* movements*.*

Note. The buffer has finite count *n* of movements stored. The buffer is the planning instrument used by higher level navigation/avoidance algorithm to control UAS (Control/Command interface) (fig. **??**).

The discrete trajectory (eq. 6.13) is ordered set of states bounded to discrete time $0 \ldots n$, where *n* is movement count of *Buffer*. Trajectory set has *n*+1 members defined like the following:

$$\begin{array}{l} Trajectory(state(0), Buffer) = \\ \left\{ \begin{array}{l} state(0) = state(0), \\ state(1) = applyMovement\,(state(0), movement(1))\,, \\ state(2) = applyMovement\,(state(1), movement(2))\,, \\ \qquad \vdots = \vdots \\ state(n-1) = applyMovement\,(state(n-2), movement(n-1))\,, \\ state(n) = applyMovement\,(state(n-1), movement(n)) \end{array} \right\} \end{array} \tag{6.13}$$

The movement(*k*) vector is selected from movement tables (tab. 6.1, 6.2).

Note. Parameter movement(·) (eq. 6.13) is a movement order index in buffer (eq. 6.12).

Bibliography

[1] Ondřej Šantin and Vladimir Havlena. Combined partial conjugate gradient and gradient projection solver for mpc. In *Control Applications (CCA), 2011 IEEE International Conference on*, pages 1270–1275. IEEE, 2011.

[2] Frangois G Pin and Hubert A Vasseur. Autonomous trajectory generation for mobile robots with non-holonomic and steering angle constraints. Technical report, Oak Ridge National Lab., 1990.

[3] Ralph G Andrzejak, G Widman, K Lehnertz, C Rieke, P David, and CE Elger. The epileptic process as nonlinear deterministic dynamics in a stochastic environment: an evaluation on mesial temporal lobe epilepsy. *Epilepsy research*, 44(2-3):129–140, 2001.

[4] Yoshiaki Kuwata, Justin Teo, Gaston Fiore, Sertac Karaman, Emilio Frazzoli, and Jonathan P How. Real-time motion planning with applications to autonomous urban driving. *IEEE Transactions on Control Systems Technology*, 17(5):1105–1118, 2009.

[5] Emilio Frazzoli. *Robust hybrid control for autonomous vehicle motion planning*. PhD thesis, Massachusetts Institute of Technology, 2001.

[6] Emilio Frazzoli, Munther A Dahleh, and Eric Feron. Trajectory tracking control design for autonomous helicopters using a backstepping algorithm. In *American Control Conference, 2000. Proceedings of the 2000*, volume 6, pages 4102–4107. IEEE, 2000.

[7] Alojz Gomola, João Borges de Sousa, Fernando Lobo Pereira, and Pavel Klang. Obstacle avoidance framework based on reach sets. In *Iberian Robotics conference*, pages 768–779. Springer, 2017.