

# Implementing a Capability Machine model into Iris

**Aïna Linn Georges**

Alix Trieu

Lars Birkedal

Aarhus University

*ageorges@cs.au.dk*

January 1, 2020

# Introduction

- ▶ Capability machines allow for fine grained control over pointer permissions
- ▶ Good target for secure compilation
- ▶ In particular: we are interested in enforcing certain higher level abstractions such as *local state encapsulation* as *well-bracketed control flow* at the lowest level of the machine
- ▶ We need tools to reason about these subtle properties in a language that does not enforce them
- ▶ These tools are elaborate and complex: we want to mechanize them, and facilitate the process of using them

# Introduction

- ▶ Capability machines allow for fine grained control over pointer permissions
- ▶ **Good target for secure compilation**
- ▶ In particular: we are interested in enforcing certain higher level abstractions such as *local state encapsulation* as *well-bracketed control flow* at the lowest level of the machine
- ▶ We need tools to reason about these subtle properties in a language that does not enforce them
- ▶ These tools are elaborate and complex: we want to mechanize them, and facilitate the process of using them

# Introduction

- ▶ Capability machines allow for fine grained control over pointer permissions
- ▶ Good target for secure compilation
- ▶ In particular: we are interested in enforcing certain higher level abstractions such as *local state encapsulation* as *well-bracketed control flow* at the lowest level of the machine
- ▶ We need tools to reason about these subtle properties in a language that does not enforce them
- ▶ These tools are elaborate and complex: we want to mechanize them, and facilitate the process of using them

# Introduction

- ▶ Capability machines allow for fine grained control over pointer permissions
- ▶ Good target for secure compilation
- ▶ In particular: we are interested in enforcing certain higher level abstractions such as *local state encapsulation* as *well-bracketed control flow* at the lowest level of the machine
- ▶ We need tools to reason about these subtle properties in a language that does not enforce them
- ▶ These tools are elaborate and complex: we want to mechanize them, and facilitate the process of using them

# Introduction

- ▶ Capability machines allow for fine grained control over pointer permissions
- ▶ Good target for secure compilation
- ▶ In particular: we are interested in enforcing certain higher level abstractions such as *local state encapsulation* as *well-bracketed control flow* at the lowest level of the machine
- ▶ We need tools to reason about these subtle properties in a language that does not enforce them
- ▶ These tools are elaborate and complex: we want to mechanize them, and facilitate the process of using them

# Overview

Capability Machines

Reasoning about Capability Safety

Program Logic

A Unary Logical Relation for Reasoning about Semantic Properties  
of an Untyped Language

The Fundamental Theorem of Logical Relations

Reasoning about Unknown Code

# Capability Machines




# Capability Machine

**Capability:** An unforgeable token of authority




# Capability Machine

**Capability:** An unforgeable token of authority





# Capability Machine

**Capability:** An unforgeable token of authority





# Capability Machine

**Capability:** An unforgeable token of authority




# Capability Machine

**Capability:** An unforgeable token of authority




## Enforcing Local Stack Encapsulation using Capabilities

## Local State Encapsulation



```
1 push r_stk 1
2 scall r
3 pop r_stk r_1
4 assert r_1 1
5 halt
```


## Local State Encapsulation



```
1 push r_stk 1
2 scall r
3 pop r_stk r_1
4 assert r_1 1
5 halt
```




## Local State Encapsulation



```
1 push r_stk 1
2 scall r
3 pop r_stk r_1
4 assert r_1 1
5 halt
```


## Enforcing Well Bracketed Control Flow using Capabilities

## Well Bracketed Control Flow




```
1 push r_stk 1
2 scall r
3 pop r_stk r_1
4 assert r_1 1
5 push r_stk 2
6 scall r
7 halt
```

## Well Bracketed Control Flow




```
1 push r_stk 1
2 scall r
3 pop r_stk r_1
4 assert r_1 1
5 push r_stk 2
6 scall r
7 halt
```

## Well Bracketed Control Flow




```
1 push r_stk 1
2 scall r
3 pop r_stk r_1
4 assert r_1 1
5 push r_stk 2
6 scall r
7 halt
```

## Well Bracketed Control Flow




```
1 push r_stk 1
2 scall r
3 pop r_stk r_1
4 assert r_1 1
5 push r_stk 2
6 scall r
7 halt
```

## Well Bracketed Control Flow



```
1 push r_stk 1
2 scall r
3 pop r_stk r_1
4 assert r_1 1
5 push r_stk 2
6 scall r
7 halt
```

## Well Bracketed Control Flow




```
1 push r_stk 1
2 scall r
3 pop r_stk r_1
4 assert r_1 1
5 push r_stk 2
6 scall r
7 halt
```



## Local Capabilities

# Local Capabilities

(p, **Local**, b, e, a)



well-bracketed


(p, **Global**, b, e, a)



not well-bracketed


# Local Capabilities

(p, **Local**, b, e, a)



well-bracketed


(p, **Global**, b, e, a)



not well-bracketed


# Local Capabilities

(p, **Local**, b, e, a)




well-bracketed

(p, **Global**, b, e, a)




not well-bracketed

# Calling Convention



r_stk	$(RWLX, Local, b, e, a)$
-------	--------------------------

# Calling Convention



<code>r_stk</code>	$(RWLX, Local, b, e, a)$
--------------------	--------------------------

## Reasoning about Capability Safety

# Expressing Capability Safety

- ▶ using a Program Logic
- ▶ using a logical relation to capture invariants on the type system
- ▶ using a logical relation on an untyped (or uni-typed) language to capture semantic properties of the language



# Expressing Capability Safety

- ▶ using a Program Logic
- ▶ using a logical relation to capture invariants on the type system
- ▶ using a logical relation on an untyped (or uni-typed) language to capture semantic properties of the language

# Expressing Capability Safety

- ▶ using a Program Logic
- ▶ using a logical relation to capture invariants on the type system
- ▶ using a logical relation on an untyped (or uni-typed) language to capture semantic properties of the language

- ▶ using a Program Logic
- ▶ using a logical relation to capture invariants on the type system
- ▶ **using a logical relation on an untyped (or uni-typed) language to capture semantic properties of the language**

# Step-indexed Kripke Logical Relation

$$\mathcal{V}(W) \triangleq \{\textcolor{red}{n}, (RW, g, b, e, a) | \dots\} \cup \dots$$

- ▶ World-circularity problem
  - ▶ *Step indexing*
- ▶ The world may evolve: we need future world relation
  - ▶ Local capabilities are revoked whereas Global capabilities are not, *the relation needs to model this distinction:*

$\sqsubseteq_{pub}$       *and*       $\sqsubseteq_{priv}$

# Step-indexed Kripke Logical Relation

$$\mathcal{V}(W) \triangleq \{\textcolor{red}{n}, (RW, g, b, e, a) | \dots\} \cup \dots$$

- ▶ World-circularity problem
  - ▶ *Step indexing*
- ▶ The world may evolve: we need future world relation
  - ▶ Local capabilities are revoked whereas Global capabilities are not, *the relation needs to model this distinction:*

$\sqsubseteq_{pub}$       *and*       $\sqsubseteq_{priv}$

# Step-indexed Kripke Logical Relation

$$\mathcal{V}(W) \triangleq \{ \textcolor{red}{n}, (RW, g, b, e, a) | \exists r, W(r) = \iota_{[b,e]} \} \cup \dots$$

- ▶ World-circularity problem
  - ▶ *Step indexing*
- ▶ The world may evolve: we need future world relation
  - ▶ Local capabilities are revoked whereas Global capabilities are not, *the relation needs to model this distinction:*

$\sqsubseteq_{pub}$       *and*       $\sqsubseteq_{priv}$

# Step-indexed Kripke Logical Relation

$$\mathcal{V}(W) \triangleq \{ \textcolor{red}{n}, (RW, g, b, e, a) | \exists r, W(r) = \iota_{[b,e]} \} \cup \dots$$

- ▶ World-circularity problem
  - ▶ **Step indexing**
- ▶ The world may evolve: we need future world relation
  - ▶ Local capabilities are revoked whereas Global capabilities are not, *the relation needs to model this distinction:*

$\sqsubseteq_{pub}$       *and*       $\sqsubseteq_{priv}$

# Step-indexed Kripke Logical Relation

$$\mathcal{V}(W) \triangleq \{ \textcolor{red}{n}, (RW, g, b, e, a) | \exists r, W(r) \stackrel{\textcolor{red}{n}}{=} \iota_{[b,e]} \} \cup \dots$$

- ▶ World-circularity problem
  - ▶ **Step indexing**
- ▶ The world may evolve: we need future world relation
  - ▶ Local capabilities are revoked whereas Global capabilities are not, *the relation needs to model this distinction*:

$\sqsubseteq_{pub}$       *and*       $\sqsubseteq_{priv}$



# Step-indexed Kripke Logical Relation

$$\mathcal{V}(W) \triangleq \{ \textcolor{red}{n}, (RW, g, b, e, a) | \exists r, W(r) \stackrel{\textcolor{red}{n}}{=} \iota_{[b,e]} \} \cup \dots$$

- ▶ World-circularity problem
  - ▶ **Step indexing**
- ▶ The world may evolve: we need future world relation
  - ▶ Local capabilities are revoked whereas Global capabilities are not, *the relation needs to model this distinction*:

$\sqsubseteq_{pub}$       *and*       $\sqsubseteq_{priv}$

# Step-indexed Kripke Logical Relation

$$\mathcal{V}(W) \triangleq \{ \textcolor{red}{n}, (RW, g, b, e, a) | \exists r, W(r) \stackrel{\textcolor{red}{n}}{=} \iota_{[b,e]} \} \cup \dots$$

- ▶ World-circularity problem
  - ▶ **Step indexing**
- ▶ The world may evolve: we need future world relation
  - ▶ Local capabilities are revoked whereas Global capabilities are not, *the relation needs to model this distinction*:

$$\sqsubseteq_{pub} \qquad \text{and} \qquad \sqsubseteq_{priv}$$

# Expressing Capability Safety in Iris - an Iris primer

## **Iris:** Higher-order Concurrent Separation Logic Framework

- ▶ Foundational
- ▶ Implemented in Coq – equipped with an interactive proof mode
- ▶ Framework – embed any language and its operational semantics into Iris
- ▶ Comes equipped with:
  - ▶ Invariants
  - ▶ Ghost state
  - ▶ Always and Later Modalities

We can take advantage of Iris' step-indexed model and invariants to mechanize step-indexed Kripke logical relations with recursive worlds in a succinct and elegant way.

# Expressing Capability Safety in Iris - an Iris primer

## **Iris:** Higher-order Concurrent Separation Logic Framework

- ▶ Foundational
- ▶ Implemented in Coq – equipped with an interactive proof mode
- ▶ Framework – embed any language and its operational semantics into Iris
- ▶ Comes equipped with:
  - ▶ Invariants
  - ▶ Ghost state
  - ▶ Always and Later Modalities

We can take advantage of Iris' step-indexed model and invariants to mechanize step-indexed Kripke logical relations with recursive worlds in a succinct and elegant way.

# Expressing Capability Safety in Iris - an Iris primer

**Iris:** Higher-order Concurrent Separation Logic Framework

- ▶ Foundational
- ▶ Implemented in Coq – equipped with an interactive proof mode
- ▶ Framework – embed any language and its operational semantics into Iris
- ▶ Comes equipped with:
  - ▶ Invariants
  - ▶ Ghost state
  - ▶ Always and Later Modalities

We can take advantage of Iris' step-indexed model and invariants to mechanize step-indexed Kripke logical relations with recursive worlds in a succinct and elegant way.

# Expressing Capability Safety in Iris - an Iris primer

**Iris:** Higher-order Concurrent Separation Logic Framework

- ▶ Foundational
- ▶ Implemented in Coq – equipped with an interactive proof mode
- ▶ Framework – embed any language and its operational semantics into Iris
- ▶ Comes equipped with:
  - ▶ Invariants
  - ▶ Ghost state
  - ▶ Always and Later Modalities

We can take advantage of Iris' step-indexed model and invariants to mechanize step-indexed Kripke logical relations with recursive worlds in a succinct and elegant way.

# Expressing Capability Safety in Iris - an Iris primer

**Iris:** Higher-order Concurrent Separation Logic Framework

- ▶ Foundational
- ▶ Implemented in Coq – equipped with an interactive proof mode
- ▶ Framework – embed any language and its operational semantics into Iris
- ▶ Comes equipped with:
  - ▶ Invariants
  - ▶ Ghost state
  - ▶ Always and Later Modalities

We can take advantage of Iris' step-indexed model and invariants to mechanize step-indexed Kripke logical relations with recursive worlds in a succinct and elegant way.

# Expressing Capability Safety in Iris - an Iris primer

**Iris:** Higher-order Concurrent Separation Logic Framework

- ▶ Foundational
- ▶ Implemented in Coq – equipped with an interactive proof mode
- ▶ Framework – embed any language and its operational semantics into Iris
- ▶ Comes equipped with:
  - ▶ Invariants
  - ▶ Ghost state
  - ▶ Always and Later Modalities

We can take advantage of Iris' step-indexed model and invariants to mechanize step-indexed Kripke logical relations with recursive worlds in a succinct and elegant way.



# Expressing Capability Safety in Iris - an Iris primer

**Iris:** Higher-order Concurrent Separation Logic Framework

- ▶ Foundational
- ▶ Implemented in Coq – equipped with an interactive proof mode
- ▶ Framework – embed any language and its operational semantics into Iris
- ▶ Comes equipped with:
  - ▶ Invariants
  - ▶ Ghost state
  - ▶ Always and Later Modalities

We can take advantage of Iris' step-indexed model and invariants to mechanize step-indexed Kripke logical relations with recursive worlds in a succinct and elegant way.

# Expressing Capability Safety in Iris - an Iris primer

**Iris:** Higher-order Concurrent Separation Logic Framework

- ▶ Foundational
- ▶ Implemented in Coq – equipped with an interactive proof mode
- ▶ Framework – embed any language and its operational semantics into Iris
- ▶ Comes equipped with:
  - ▶ Invariants
  - ▶ Ghost state
  - ▶ Always and Later Modalities

We can take advantage of Iris' step-indexed model and invariants to mechanize step-indexed Kripke logical relations with recursive worlds in a succinct and elegant way.

# Expressing Capability Safety in Iris - Challenges

- ▶ Region invariants: Iris invariants
- ▶ Future world relation: frame preserving updates and world satisfaction
- ▶ Step indexing: later modality

## Challenges

- ▶ Iris was designed with more high level languages in mind, how do we embed a low level machine language into Iris
- ▶ Iris abstracts away certain details we want to reason about directly
- ▶ There is only one frame preserving update, we need to distinguish between two future world relations

# Expressing Capability Safety in Iris - Challenges

- ▶ Region invariants: Iris invariants
- ▶ Future world relation: frame preserving updates and world satisfaction
- ▶ Step indexing: later modality

## Challenges

- ▶ Iris was designed with more high level languages in mind, how do we embed a low level machine language into Iris
- ▶ Iris abstracts away certain details we want to reason about directly
- ▶ There is only one frame preserving update, we need to distinguish between two future world relations

# Expressing Capability Safety in Iris - Challenges

- ▶ Region invariants: Iris invariants
- ▶ Future world relation: frame preserving updates and world satisfaction
- ▶ Step indexing: later modality

## Challenges

- ▶ Iris was designed with more high level languages in mind, how do we embed a low level machine language into Iris
- ▶ Iris abstracts away certain details we want to reason about directly
- ▶ There is only one frame preserving update, we need to distinguish between two future world relations

# Expressing Capability Safety in Iris - Challenges

- ▶ Region invariants: Iris invariants
- ▶ Future world relation: frame preserving updates and world satisfaction
- ▶ Step indexing: later modality

## Challenges

- ▶ Iris was designed with more high level languages in mind, how do we embed a low level machine language into Iris
- ▶ Iris abstracts away certain details we want to reason about directly
- ▶ There is only one frame preserving update, we need to distinguish between two future world relations

## Roadmap

- ▶ embed the language into Iris
- ▶ define a program logic by proving Hoare Triples
- ▶ define the logical relation – using Iris tools to solve the world circularity problem
- ▶ prove the fundamental theorem of logical relations
- ▶ use the logical relation to prove examples that rely on local state encapsulation and well-bracketed control flow with calls to unknown adversary

## Roadmap

- ▶ embed the language into Iris
- ▶ define a program logic by proving Hoare Triples
- ▶ define the logical relation – using Iris tools to solve the world circularity problem
- ▶ prove the fundamental theorem of logical relations
- ▶ use the logical relation to prove examples that rely on local state encapsulation and well-bracketed control flow with calls to unknown adversary



## Roadmap

- ▶ embed the language into Iris
- ▶ **define a program logic by proving Hoare Triples**
- ▶ define the logical relation – using Iris tools to solve the world circularity problem
- ▶ prove the fundamental theorem of logical relations
- ▶ use the logical relation to prove examples that rely on local state encapsulation and well-bracketed control flow with calls to unknown adversary

## Roadmap

- ▶ embed the language into Iris
- ▶ define a program logic by proving Hoare Triples
- ▶ **define the logical relation – using Iris tools to solve the world circularity problem**
- ▶ prove the fundamental theorem of logical relations
- ▶ use the logical relation to prove examples that rely on local state encapsulation and well-bracketed control flow with calls to unknown adversary

## Roadmap

- ▶ embed the language into Iris
- ▶ define a program logic by proving Hoare Triples
- ▶ define the logical relation – using Iris tools to solve the world circularity problem
- ▶ **prove the fundamental theorem of logical relations**
- ▶ use the logical relation to prove examples that rely on local state encapsulation and well-bracketed control flow with calls to unknown adversary

## Roadmap

- ▶ embed the language into Iris
- ▶ define a program logic by proving Hoare Triples
- ▶ define the logical relation – using Iris tools to solve the world circularity problem
- ▶ prove the fundamental theorem of logical relations
- ▶ use the logical relation to prove examples that rely on local state encapsulation and well-bracketed control flow with calls to unknown adversary

## Program Logic

# Abstract Instructions

$$(reg, mem) \rightarrow (reg', mem')$$

- ▶ Instr Executable
- ▶ Instr Halted  $\rightarrow$  HaltedV
- ▶ Instr Failed  $\rightarrow$  FailedV

$$(reg, mem) \rightarrow (reg', mem')$$

- ▶ Instr Executable
- ▶ Instr Halted  $\rightarrow$  HaltedV
- ▶ Instr Failed  $\rightarrow$  FailedV

# Abstract Instructions

$$(reg, mem) \rightarrow (reg', mem')$$

- ▶ Instr Executable
- ▶ Instr Halted  $\rightarrow$  HaltedV
- ▶ Instr Failed  $\rightarrow$  FailedV



# Abstract Instructions

$$(reg, mem) \rightarrow (reg', mem')$$

- ▶ Instr Executable
- ▶ Instr Halted  $\rightarrow$  HaltedV
- ▶ Instr Failed  $\rightarrow$  FailedV

# Abstract Instructions

$$(reg, mem) \rightarrow (reg', mem')$$

- ▶ Instr Executable
- ▶ Instr Halted  $\rightarrow$  HaltedV
- ▶ Instr Failed  $\rightarrow$  FailedV

## A Capability Points-to Predicate

# Points-to Predicate with Permissions

$$a \mapsto_a [RWL]w$$

# Points-to Predicate with Permissions

$$a \mapsto_a [RWL]_w \Longrightarrow^* a \mapsto_a [RWL]((p, Local), b, e, l)$$

# Points-to Predicate with Permissions

$$\begin{aligned} a \mapsto_a [RWL]_w &\Longrightarrow^* a \mapsto_a [RWL]((p, Local), b, e, l) \\ &\Longrightarrow^* a \mapsto_a [RW]((p, Local), b, e, l) \end{aligned}$$

# Points-to Predicate with Permissions

$$\begin{aligned} a \mapsto_a [RWL]_w &\Longrightarrow^* a \mapsto_a [RWL]((p, Local), b, e, l) \\ &\Longrightarrow^* a \mapsto_a [RW]((p, Local), b, e, l) \\ &\not\Longrightarrow^* a \mapsto_a [RW]((p', Local), b', e', l') \end{aligned}$$

# A Unary Logical Relation for Reasoning about Semantic Properties of an Untyped Language



## The Value Relation

## A unary logical relation of an un-typed language

$$\mathcal{V} : \text{Word} \rightarrow iProp \Sigma$$

**Challenge:** distinguish between Local and Global capabilities:

- ▶ At the level of the value relation
- ▶ Model revocation

**STS:** A collection of state transition systems

$$\mathcal{V}((\text{RW}, g), b, e, a) \triangleq \bigstar_{a \in [b, e]} \boxed{\exists w, a \mapsto_a [RW]w \multimap \mathcal{V}(w)}$$

# The Value Relation

## A unary logical relation of an un-typed language

$$\mathcal{V} : \text{Word} \rightarrow iProp \Sigma$$

**Challenge:** distinguish between Local and Global capabilities:

- ▶ At the level of the value relation
- ▶ Model revocation

**STS:** A collection of state transition systems

$$\mathcal{V}((_{RW}, g), b, e, a) \triangleq \bigstar_{a \in [b, e]} \boxed{\exists w, a \mapsto_a [RW]w \multimap \mathcal{V}(w)}$$

# The Value Relation

## A unary logical relation of an un-typed language

$$\mathcal{V} : \text{Word} \rightarrow iProp \Sigma$$

**Challenge:** distinguish between Local and Global capabilities:

- ▶ At the level of the value relation
- ▶ Model revocation

**STS:** A collection of state transition systems

$$\mathcal{V}((_{RW}, g), b, e, a) \triangleq \bigstar_{a \in [b, e]} \boxed{\exists w, a \mapsto_a [RW]w \multimap \mathcal{V}(w)}$$

## A unary logical relation of an un-typed language

$$\mathcal{V} : \text{Word} \rightarrow iProp \Sigma$$

**Challenge:** distinguish between Local and Global capabilities:

- ▶ At the level of the value relation
- ▶ Model revocation

STS: A collection of state transition systems

$$\mathcal{V}((_{RW}, g), b, e, a) \triangleq \bigstar_{a \in [b, e]} \boxed{\exists w, a \mapsto_a [RW]w \multimap \mathcal{V}(w)}$$

# The Value Relation

## A unary logical relation of an un-typed language

$$\mathcal{V} : \text{Word} \rightarrow iProp \Sigma$$

**Challenge:** distinguish between Local and Global capabilities:

- ▶ At the level of the value relation
- ▶ Model revocation

STS: A collection of state transition systems

$$\mathcal{V}((_{RW}, g), b, e, a) \triangleq \bigstar_{a \in [b, e]} \boxed{\exists w, a \mapsto_a [RW]_w \multimap \mathcal{V}(W)(w)}$$

# The Value Relation

## A unary logical relation of an un-typed language

$$\mathcal{V} : \textcolor{red}{STS} \rightarrow \textit{Word} \rightarrow \textit{iProp} \Sigma$$

**Challenge:** distinguish between Local and Global capabilities:

- ▶ At the level of the value relation
- ▶ Model revocation

**STS:** A collection of state transition systems

$$\mathcal{V}(\textcolor{red}{W})((\textcolor{blue}{r}_W, g), b, e, a) \triangleq \bigstar_{a \in [b, e]} \boxed{\exists w, a \mapsto_a [RW]w \textcolor{blue}{*} \mathcal{V}(\textcolor{red}{W})(w)}$$

## The Execute Condition



# The Execute Condition

$$\text{exec\_cond}(W)(p,g,b,e) \triangleq \begin{cases} \forall a \in [b \ e], W' \sqsubseteq_{pub} W. \\ \quad \triangleright \mathcal{E}(W')(((p, g), b, e, a)) \quad g = Local \\ \\ \forall a \in [b \ e], W' \sqsubseteq_{priv} W. \\ \quad \triangleright \mathcal{E}(W')(((p, g), b, e, a)) \quad g = Global \end{cases}$$

## The Expression Relation

# The Expression Relation

$$\begin{aligned}\mathcal{E}(W)(pc) &\triangleq \forall r, \mathcal{R}(W)(r) * \text{context}(W)(r[\text{PC} := pc]) \\ &\quad \rightarrow * \text{WP Seq (Instr Executable)} \\ &\quad \{v, v = \text{Halted}V \implies \exists W' r', W' \sqsubseteq_{\text{priv}} W \\ &\quad * \text{context}(W')(r')\}\end{aligned}$$

# The Expression Relation

$$\begin{aligned}\mathcal{E}(W)(pc) &\triangleq \forall r, \mathcal{R}(W)(r) * \text{context}(W)(r[\text{PC} := pc]) \\ &\quad \rightarrow * \text{WP Seq (Instr Executable)} \\ &\quad \{v, v = \text{HaltedV} \implies \exists W' r', W' \sqsubseteq_{\text{priv}} W \\ &\quad * \text{context}(W')(r')\}\end{aligned}$$

$$\text{context}(W)(r) = ?$$

# The Expression Relation

$$\begin{aligned}\mathcal{E}(W)(pc) &\triangleq \forall r, \mathcal{R}(W)(r) * \text{context}(W)(r[\text{PC} := pc]) \\ &\quad * \text{WP Seq (Instr Executable)} \\ &\quad \{v, v = \text{HaltedV} \implies \exists W' r', W' \sqsubseteq_{\text{priv}} W \\ &\quad * \text{context}(W')(r')\}\end{aligned}$$

$$\text{context}(W)(r) = \left( \bigstar_{r_i \mapsto w \in r} r_i \mapsto_r w \right) \wedge \text{full\_map } r$$

# The Expression Relation

$$\begin{aligned}\mathcal{E}(W)(pc) &\triangleq \forall r, \mathcal{R}(W)(r) * \text{context}(W)(r[PC := pc]) \\ &\quad * \text{WP Seq (Instr Executable)} \\ &\quad \{v, v = \text{HaltedV} \implies \exists W' r', W' \sqsubseteq_{\text{priv}} W \\ &\quad * \text{context}(W')(r')\}\end{aligned}$$

$$\begin{aligned}\text{context}(W)(r) = & \left( \bigstar_{r_i \mapsto w \in r} r_i \mapsto_r w \right) \wedge \text{full\_map } r \\ & * \text{na\_inv } \gamma_{na} \top\end{aligned}$$

# The Expression Relation

$$\begin{aligned}\mathcal{E}(W)(pc) &\triangleq \forall r, \mathcal{R}(W)(r) * \text{context}(W)(r[PC := pc]) \\ &\quad * \text{WP Seq (Instr Executable)} \\ &\quad \{v, v = \text{HaltedV} \implies \exists W' r', W' \sqsubseteq_{\text{priv}} W \\ &\quad * \text{context}(W')(r')\}\end{aligned}$$

$$\begin{aligned}\text{context}(W)(r) = & \left( \bigstar_{r_i \mapsto w \in r} r_i \mapsto_r w \right) \wedge \text{full\_map } r \\ & * \text{na\_inv } \gamma_{na} \top \\ & * \text{sts\_full } W\end{aligned}$$

# The Expression Relation

$$\begin{aligned}\mathcal{E}(W)(pc) &\triangleq \forall r, \mathcal{R}(W)(r) * \text{context}(W)(r[PC := pc]) \\ &\quad * \text{WP Seq (Instr Executable)} \\ &\quad \{v, v = \text{HaltedV} \implies \exists W' r', W' \sqsubseteq_{\text{priv}} W \\ &\quad * \text{context}(W')(r')\}\end{aligned}$$

$$\begin{aligned}\text{context}(W)(r) = & \left( \bigstar_{r_i \mapsto w \in r} r_i \mapsto_r w \right) \wedge \text{full\_map } r \\ & * \text{na\_inv } \gamma_{\text{na}} \top \\ & * \text{sts\_full } W \\ & * \text{region } W\end{aligned}$$



# The Fundamental Theorem of Logical Relations

# The Fundamental Theorem of logical relations

If we can read a region, and every word in that region is safe, then  
we can safely execute it

- ▶ "If we can read a region" :  $p = \text{RX} \vee p = \text{RWX} \vee p = \text{RWLX}$
- ▶ "and every word in that region is safe":  
 $\text{read\_write\_cond}(p, b, e)$
- ▶ "then we can safely execute it":  $\mathcal{E}(W)((p, g), b, e, a)$

$$(p = \text{RX} \vee p = \text{RWX} \vee p = \text{RWLX}) \implies \\ \text{read\_write\_cond}(p, b, e) \implies \mathcal{E}(W)((p, g), b, e, a)$$

- ▶ "If we can read a region" :  $p = \text{RX} \vee p = \text{RWX} \vee p = \text{RWLX}$
- ▶ "and every word in that region is safe":  
 $\text{read\_write\_cond}(p, b, e)$
- ▶ "then we can safely execute it":  $\mathcal{E}(W)((p, g), b, e, a)$

$$(p = \text{RX} \vee p = \text{RWX} \vee p = \text{RWLX}) \implies$$

$$\text{read\_write\_cond}(p, b, e) \implies \mathcal{E}(W)((p, g), b, e, a)$$

- ▶ "If we can read a region" :  $p = \text{RX} \vee p = \text{RWX} \vee p = \text{RWLX}$
- ▶ "and every word in that region is safe":  
 $\text{read\_write\_cond}(p, b, e)$
- ▶ "then we can safely execute it":  $\mathcal{E}(W)((p, g), b, e, a)$

$$(p = \text{RX} \vee p = \text{RWX} \vee p = \text{RWLX}) \implies$$

$$\text{read\_write\_cond}(p, b, e) \implies \mathcal{E}(W)((p, g), b, e, a)$$

- ▶ "If we can read a region" :  $p = \text{RX} \vee p = \text{RWX} \vee p = \text{RWLX}$
- ▶ "and every word in that region is safe":  
 $\text{read\_write\_cond}(p, b, e)$
- ▶ "then we can safely execute it":  $\mathcal{E}(W)((p, g), b, e, a)$


$$(p = \text{RX} \vee p = \text{RWX} \vee p = \text{RWLX}) \implies$$

$$\text{read\_write\_cond}(p, b, e) \implies \mathcal{E}(W)((p, g), b, e, a)$$

## Reasoning about Unknown Code

# Reasoning about Unknown Code

**We use the fundamental theorem to reason about calls to an unknown adversary**



```
1 push r_stk 1
2 scall r
3 pop r_stk r_1
4 assert r_1 1
5 halt
```

$$\mathcal{E}(W)(pc) \triangleq \forall r, \mathcal{R}(W)(r) * \text{context}(W)(r[PC := pc])$$

\* WP Seq (Instr Executable)

$$\{v, v = \text{HaltedV} \implies \exists W' r', W' \sqsubseteq_{\text{priv}} W$$

\* context( $W'$ )( $r'$ )\}



# Conclusion

- ▶ Embed a capability machine into Iris
- ▶ Define its program logic
- ▶ Mechanize a unary logical relation for an untyped capability machine language
- ▶ Prove the fundamental theorem of logical relations
- ▶ Reason about examples that rely on Local Stack  
Encapsulation and Well-Bracketed Control Flow with calls to an unknown adversary

# References



Lau Skorstengaard, Dominique Devriese, and Lars Birkedal (2018)  
Reasoning About a Machine with Local Capabilities  
*ESOP Programming Languages and Systems* 475–501.



Derek Dreyer, Georg Neis, Lars Birkedal (2012)  
The impact of higher-order state and control effects on local relational reasoning  
*Journal of Functional Programming* 22(4-5) 477–528.



Derek Dreyer, Amal Ahmed, Lars Birkedal (2011)  
Logical Step-Indexed Logical Relations  
*LMCS* 7(2:16).