

ARTIFICIAL INTELLIGENCE FUTURE FRONTIERS OF GENERATIVE AI IN ENGINEERING



Editors

Abdulkadir ŞEKER
Ahmet Gürkan YÜKSEK

Engineering Sciences



ARTIFICIAL INTELLIGENCE FUTURE FRONTIERS OF GENERATIVE AI IN ENGINEERING

Editors

Abdulkadir ŞEKER

Ahmet Gürkan YÜKSEK



LIVRE DE LYON

Lyon 2025

ARTIFICIAL INTELLIGENCE FUTURE FRONTIERS OF GENERATIVE AI IN ENGINEERING

Editors

Abdulkadir ŞEKER

Ahmet Gürkan YÜKSEK



LIVRE DE LYON

Lyon 2025

Artificial Intelligence Future Frontiers of Generative AI in Engineering

Editors • Asst. Prof. Abdulkadir ŞEKER • Orcid: 0000-0002-4552-2676
• Assoc. Prof. Ahmet Gürkan YÜKSEK • Orcid: 0000-0001-7709-6360

Cover Design • Motion Graphics

Book Layout • Motion Graphics

First Published • October 2025, Lyon

e-ISBN: 978-2-38236-948-7

DOI: 10.5281/zenodo.17449635

copyright © 2025 by Livre de Lyon

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the Publisher. The author or authors of the relevant section are responsible for any copyright infringement that may occur due to the images and graphics used in the book. The editor or publisher does not assume responsibility in this regard.



Publisher • Livre de Lyon

Address • 37 rue marietton, 69009, Lyon France

website • <http://www.livredelyon.com>

e-mail • livredelyon@gmail.com



LIVRE DE LYON

PREFACE

The rapid evolution of Generative Artificial Intelligence (GenAI) has triggered a paradigm shift, profoundly transforming how engineers, scientists, and professionals design, simulate, and innovate. Once largely confined to creative domains, generative models now permeate nearly every discipline—from the intricate virtual replicas of digital twin systems and automated software design to the discovery of novel solar cell materials, advanced cancer research diagnostics, and complex environmental modeling. The convergence of hard engineering principles with generative intelligence has unlocked frontiers where machines not only analyze data but also create, hypothesize, and optimize solutions at a scale and speed previously beyond human imagination.

This new era presents both immense opportunities and significant challenges, necessitating a comprehensive guide. This book, *Artificial Intelligence: Future Frontiers of Generative AI in Engineering*, serves as a critical chronicle of this transformation. It brings together leading-edge, interdisciplinary contributions that explore both the foundational theories and the disruptive real-world applications of GenAI.

What sets this volume apart is its ambitious scope. The chapters navigate a spectrum that stretches from the deep theoretical underpinnings of Kolmogorov complexity and conversational AI architectures to urgent, practical implementations in law, digital commerce, and particle physics. Crucially, this book also addresses the technology's dual-use nature, tackling vital issues of deepfake detection, cyber attacks, and security challenges.

By bridging the gap between academia and industry, this work highlights the transformative potential of GenAI for predictive maintenance, intelligent design, and the future of human-AI collaboration. This book has been coordinated under the auspices of the **Sivas Cumhuriyet University**

Artificial Intelligence and Data Science Application and Research Center, reflecting the center's ongoing commitment to fostering innovative, ethical, and interdisciplinary research in the rapidly advancing fields of artificial intelligence and engineering.

Asst. Prof. Abdulkadir ŞEKER
Assoc. Prof. Ahmet Gürkan YÜKSEK
Editors

Asst. Prof. Abdulkadir ŞEKER, Kyrgyz-Turkish Manas University,
Assoc. Prof. Ahmet Gürkan YÜKSEK, Sivas Cumhuriyet, University,

CONTENTS

PREFACE	I
CHAPTER I. FOUNDATION AND EVOLUTION OF GENERATIVE ARTIFICIAL INTELLIGENCE	1
<i>Ferhan DEMİRKOPARAN & Metin ZONTUL</i>	
CHAPTER II. FROM COMPRESSION TO CREATIVITY: KOLMOGOROV COMPLEXITY IN GENERATIVE AI	19
<i>Saliha YEŞİLYURT & Zehra BİLİCİ & Doğa NALCI</i>	
CHAPTER III. CONVERSATIONAL AI AND QUESTION ANSWERING SYSTEMS: ARCHITECTURES, TRAINING CHALLENGES AND SOLUTIONS	47
<i>Ramazan KATIRCI & Hilal ÇELİK & Taha OĞUZ</i>	
CHAPTER IV. SOFTWARE DEVELOPMENT SUPPORTED BY GENERATIVE ARTIFICIAL INTELLIGENCE	69
<i>Hakan KEKÜL</i>	
CHAPTER V. DIGITAL TWIN-DRIVEN PREDICTIVE MAINTENANCE IN INDUSTRY 4.0: EFFECTS OF CONDITIONAL GAN DATA AUGMENTATION ON SVM PERFORMANCE	85
<i>Ahmet Gürkan YÜKSEK</i>	
CHAPTER VI. LARGE LANGUAGE MODELS IN MATERIALS SCIENCE: APPLICATIONS AND FUTURE DIRECTIONS	107
<i>Nida KATI & Ferhat UÇAR</i>	
CHAPTER VII. LARGE LANGUAGE MODELS FOR SYSTEMATIC LITERATURE ANALYSIS IN SOLAR CELL MATERIALS RESEARCH: A PRACTICAL FRAMEWORK	121
<i>Nida KATI & Ferhat UÇAR</i>	
CHAPTER VIII. GENERATIVE AI-ENHANCED APPROACHES FOR PARTICLE PHYSICS APPLICATIONS	149
<i>Mehmet Uğur TÜRKDAMAR, & Celal ÖZTÜRK</i>	
CHAPTER IX. EMERGING TRENDS IN IOT-DRIVEN GENERATIVE ARTIFICIAL INTELLIGENCE APPLICATIONS FOR AGRICULTURAL ENTERPRISES	177
<i>Şükrü Mustafa KAYA</i>	

CHAPTER X.	Q-LEARNING APPLICATIONS IN DIGITAL COMMERCE	191
	<i>Havva ABUKAN & Yunus EROĞLU & Selen Yücesoy KAHRAMAN</i>	
CHAPTER XI.	GENERATIVE ARTIFICIAL INTELLIGENCE (GenAI) SUPPORTED DIGITAL MARKETING AND CONTENT STRATEGIES	207
	<i>Murat Fatih TUNA & Yunus Emre IŞIK</i>	
CHAPTER XII.	GENERATIVE ARTIFICIAL INTELLIGENCE IN EDUCATIONAL TECHNOLOGIES	233
	<i>Mehmet Ali DEVECİ & Yasin GÖRMEZ & Sait BARDAKÇI</i>	
CHAPTER XIII.	A BIBLIOMETRIC ANALYSIS OF CANCER RESEARCH UTILIZING GENERATIVE ARTIFICIAL INTELLIGENCE METHODS BETWEEN 2022 AND 2024	263
	<i>Mustafa TEMİZ & Burcu BAKIR-GUNGOR</i>	
CHAPTER XIV.	GENERATIVE ARTIFICIAL INTELLIGENCE APPLICATIONS IN LAW	275
	<i>Fatma Betül ŞEKER & Berna DÖNEK</i>	
CHAPTER XV.	GENERATIVE AI IN MEDIA, COMMUNICATION AND VISUAL ARTS	295
	<i>Oğuz KAYNAR & Murat Fatih TUNA</i>	
CHAPTER XVI.	DEEFAKE DETECTION, FAKE CONTENT VERIFICATION, AND CYBER ATTACK SCENARIOS: METHODS, CHALLENGES AND MITIGATION STRATEGIES	327
	<i>Saadin OYUCU & Ahmet AKSÖZ</i>	
CHAPTER XVII.	SUSTAINABILITY AND ENVIRONMENTAL MODELING WITH GENERATIVE ARTIFICIAL INTELLIGENCE	341
	<i>Emre ÜNSAL & Ahmet Fırat YELKUVAN</i>	

CHAPTER I

FOUNDATION AND EVOLUTION OF GENERATIVE ARTIFICIAL INTELLIGENCE

Ferhan DEMİRKOPARAN¹ & Metin ZONTUL²

¹(Res. Assist.) Sivas Cumhuriyet University, Sivas, TURKEY

E-mail: fdemirkoparan@cumhuriyet.edu.tr

Orcid-Id: 0009-0001-5913-0411

²(Prof. Dr.) Sivas University of Science and Technology, Sivas, TURKEY

E-mail: metinzontul@sivas.edu.tr

Orcid-Id: 0000-0002-7557-2981

1. Introduction

Humanity has come a long way since Alan Turing asked in 1950, “Can a machine think?” The concept of artificial intelligence has already become a part of our lives. Efforts to enable machines to perform tasks requiring intelligence have led to unprecedented achievements in tasks such as perception, learning, reasoning, decision-making, and natural language processing. Machine learning algorithms allow machines to automatically learn from data, uncovering hidden patterns. With the development of deep learning, large amounts of complex data can be processed using multilayered neural networks to produce high-level representations of this data.

These methods are discriminative models that learn the structure of the data to perform classification, prediction, personalized recommendations, and assist in the decision-making process. Generative AI models, on the other hand, have the ability to produce new, original, never-before-seen, coherent, and logical content (Feuerriegel, et. al. 2014; Rios-Campos, et. al. 2023). Although discriminative methods have a degree of stochasticity rooted in their initial randomness, their results are deterministic. This means that significantly different results cannot be obtained with the same dataset. Generative models are stochastic (probabilistic). Even when given the exact same input, they can

produce different results each time. For example, different answers may be received for the same prompt written to ChatGPT at different times. However, all these responses may be plausible and logical enough to be accepted as a proper answer to the question (Banh & Strobel, 2023). The reason for this is not only the probabilistic nature of generative models but also the use of semi-supervised learning. Semi-supervised learning involves using both labeled and unlabeled data together, especially in situations where labeled data is scarce. This approach helps to increase the model's generalization capability (Van Engelen & Hoos, 2020).

Generative AI (GAI) applications have permeated every aspect of our lives, particularly over the last decade. They are now being used across numerous sectors, including customer relations, education, healthcare, marketing, art, music, and entertainment.

2. Historical Background and Evolution

The current state of AI is the product of decades of cumulative work. The evolution of AI can be traced back to 1950s. After Turing asked the famous question, in 1957 Rosenblatt introduced Perceptron which is a single unit neural network and can be used as a binary classifier today (Rosenblatt, 1957). In 1980s, a crucial tool to train neural networks emerged and artificial intelligence era was officially started.

Data sequences such as text, time series or speech began to be processed with Recurrent Neural Networks (RNN) and used in natural language processing, time series prediction, speech recognition and neural machine translation applications. While it suffered from vanishing gradient problem and had limitations to capture long term dependencies in the data so Long-Short Term Memory (LSTM) was proposed to handle them. It was used in natural language processing tasks successfully (Hochreiter & Schmidhuber, 1997).

Alexnet's victory in the Imagenet competition in 2012 created a breakthrough in the field of deep learning (Krizhevsky, 2012). With the development of GPU technology and distributed computing, large amounts of data can be processed using large-scale deep networks. This has led to an increase in the number of studies in the field of deep learning.

A significant milestone came with the introduction of *Generative Adversarial Networks (GANs)* by Goodfellow et al. in 2014 and around the same time Variational Autoencoders was introduced (Goodfellow et al., 2014; Kingma & Welling, 2013). They initiated a new era of realistic data generation.

The emerge of transformer-based architecture, which enabled context-aware sequence modeling, marked the beginning of modern generative artificial intelligence period (Vaswani et al., 2017). Large-scale models such as Generative Pretrained Transformer (GPT), BERT and Stable Diffusion were adopted from Transformer (Alec, et. al, 2018; Devlin, et. al., 2019). In recent years, Large Language Models (LLMs) has expanded generative AI beyond text to include image, audio, and video synthesis.

3. Generative Architectures

In recent years, a lot of generative approaches have developed which are able to learn data distributions and synthesis new content. Although these methods are based on different mathematical foundations, their common goal is to capture the underlying patterns in the training data and produce new examples that are similar but original. The four main approaches most widely used today are Generative Adversarial Networks (GAN), Variational Autoencoders (VAE), Diffusion Models and Transformer-based generative models (Goodfellow et al., 2014; Kingma & Welling, 2013; Ho et al., 2020; Vaswani et al., 2017).

3.1. Variational Autoencoder (VAE)

Originally, traditional autoencoder (AE) is designed for tasks such as dimensionality reduction, anomaly detection, image denoising, image compression (Bengesi, et. al., 2014), because it is an encoder-decoder architecture which maps input data into a lower dimensional space.




Figure 1. The inference process of VAE

Variational Autoencoder is a generative model consisting of two networks like classical autoencoder first of which maps the input data to a lower dimensional latent space by eliminating unnecessary information and noise and second of which uses these latent representations to reconstruct by minimizing the loss function. VAE is trained by two loss functions, one of which is reconstruction loss that makes input data compatible with samples decoded. The other one is regularization loss which learns reconstructed latent space by approximating normal distribution as much as possible. The main difference between AE and VAE comes from VAE learning probability distribution rather than data points. This way, the model can capture the diversity in the training data and generate new, consistent examples. VAEs are often preferred for modeling complex data structures and data synthesis. There are a lot of VAE applications in the literature, considered state-of-the-art. On the other hand, VAE models which are used for image generation tasks, especially those with face images, may output blurry images (Foster, 2022), because decoder samples from latent vector and create outputs by using mean value of corresponding probability distribution. So, this causes sharp edges to become blurry. The inference process of a VAE can be seen in Figure 1(Kingma, 2017).

3.2. Generative Adversarial Network (GAN)

Generative Adversarial Network consists of two networks with opposing goals which are a generator and a discriminator. They are trained together with a zero-sum game (Goodfellow, et. al., 2014). While generator aims to generate realistic samples using random noise, discriminator aims to separate the outputs of the generator as real and fake by using both fake and real data as inputs. The training process stops when an equilibrium state is reached where discriminator can no longer distinguish between generated and real data (He, et. al., 2025). The input of generator is a noise vector which is created from multivariate standard normal distribution. Discriminator is trained with fake and real data and makes a binary classification which labels fake data as 0 and real data 1 (Foster, 2022). GANs have achieved groundbreaking successes, particularly in tasks such as image generation, facial synthesis, and style transfer. The whole generation process of a GAN can be seen in Figure 2 (Rios-Campos, et. al., 2023).

On the other hand, it has its own challenges and limitations:

Mode Collapse: this occurs when generator learns only a small part of data distribution and generates same or very similar outputs. It can happen when discriminator learns quickly and overfits and generator cannot keep up with it.

Training instability: In training process, loss values oscillate and collapse before it reaches an equilibrium. Model cannot learn and gradients vanish.

Evaluation difficulty: It is hard to evaluate the quality and diversity of generated data with an objective metric. Besides, since loss values of both networks changes relative to each other it does not always mean that low loss values cause high quality outputs.

Hyperparameters: GANs are highly sensitive to hyperparameter changes.




Figure 2. Generation process of GAN

To deal with these challenges a lot of variations of GAN are developed. One of them is Wasserstein GAN (WGAN) (Arjovsky, et. al., 2017). In this method a different loss function which is called Wasserstein distance is used. It makes gradients smoother, training more robust and outputs more diverse (Sengar, et. al., 2025). Least Squares GAN (LSGAN) uses least square loss function, Self-attention GAN uses self-attention mechanism to generate more robust outputs (Mao, et. al., 2017; Zhang, et. al., 2019). Odena showed that GANs can be used not only for data generation but also for semi-supervised learning tasks with limited labeled data, extending the discriminator network to perform both real and fake detection and class prediction (Odena, 2016). In another study of Odena, it was shown that it is possible to perform conditional image generation and create higher quality, controllable samples using class information with the Auxiliary Classifier GAN (AC-GAN) method (Odena, et. al., 2017). In the study of Mirza and Osindero, Conditional Generative Adversarial Networks (cGAN) were proposed, which can produce data samples with certain properties using conditional inputs (Mirza & Osindero, 2014). Deep convolutional GANs (DCGANs) were used for unsupervised representation learning, demonstrating that GAN-based models can generate images in a stable and effective manner (Radford, et. al., 2015).

3.3. Transformer

Transformer introduced by Vaswani et al. is a method that processes text data in an auto-regressive manner (Vaswani et al., 2017). Instead of processing data sequentially like traditional methods, the Transformer architecture utilizes a self-attention mechanism that assigns a weight value to words based on their importance (Rao, et al., 2025). This allows the model to extract long-range dependencies within the data. Through Multi-Head Attention and parallel processing, different types of data in the various subspaces and more detailed representations are learned simultaneously without details being lost. With positional encoding, location information is added to input sequence so sequential and relative relationships in data can be learned. The architecture of a Transformer model can be seen in Figure 3 (Vaswani, et. al., 2017).

Transformer models also form the foundation of large language models (LLMs) and have become one of the most powerful tools in generative artificial intelligence due to their ability to generate context-aware meaning.




Figure 3. The transformer model architecture

3.4. Diffusion Model

A diffusion model employs a two-way process: first, it gradually converts the input data into noise, which is called the forward process, and then, a clean output is reconstructed from the noisy data, which is known as the reverse process. A diffusion model is typically designed as a neural network (such as a U-Net) and learns to generate meaningful samples from noise. The noise is iteratively attempted to be approximated towards the target distribution.

Diffusion model is successfully used in zero-shot generative tasks and generation of scenes that do not exist in real world environments, but it is computationally expensive (He, et. al., 2025). Besides, it handles the instability and mode collapse problem of GANs and can create high quality, high resolution and diverse samples (Bengesi, et.al., 2024).

The original mathematical framework that forms the foundation of diffusion models is called Denoising Diffusion Probabilistic Models (DDPM). Since classical DDPM is computationally heavy, some methods have been developed to decrease the cost. Song et. al. decreased the number of steps by using deterministic sampling (Song, et. al., 2020). Rombach et. al. proposed Latent Diffusion Model (LDM) which applies diffusion on a lower dimension latent space (Rombach, et. al., 2022). This forms the scientific foundation of Stable Diffusion. The architectural structure of a text-to-image diffusion model used by Stable Diffusion (Rombach, et. al., 2022) which is an open source LLM can be seen in Figure 4 (Rahmatulloh, 2025).




Figure 4. Architectural structure of a text-to-image diffusion model

3.2. Large Language Models (LLMs)

Large Language Models (LLMs) are sub-branch of generative AI developed for NLP tasks such as text generation, question answering, natural translation. LLMs require them to be trained with large-scale datasets that consist of a large amount of unstructured, unlabeled data. They can be internet sources such as books, papers, websites or libraries. Even if LLMs were originally designed for text domains, after they become popular a lot of applications in various domains have emerged. They have the ability to create semantically consistent, coherent, realistic text, story, script, advertisement, audio, image, video, speech that cannot be separated from human created content. According to modality LLMs can be classified into two categories: unimodal models which generate same kinds of data as inputs, multimodal models which can operate with data

from various domains. These models are defined as x-to-modality (Bahn & Strobel, 2023). Unimodal models could be image-to-image or text-to-text while multimodal models could be text-to-image, text-to-video etc.

General purpose LLMs are initially pretrained with large scale datasets with billions or trillions of numbers of parameters and can be used in multiple domains for many different interdisciplinary tasks. After training process is completed, it can be made domain-specific by fine tuning and additional domain-specific data. This phenomenon is attributable to the principles of transfer learning. It is feasible to develop novel models by leveraging transfer learning in conjunction with open-source LLMs. To specialize in a Large Language Model (LLM) for a particular task, human evaluation can be employed to select sufficient high-quality responses. This process effectively serves to guide the system toward a desired behavioral trajectory in the target domain, which is crucial for fine-tuning or reinforcement learning from human feedback (RLHF) (Christiano, et. al., 2017).

On the other hand, the prompts given to LLM system directly affect the quality and direction of generated outputs. So, prompt engineering is crucial for GAI system to adopt certain problems (He, et. al, 2025).

The emergence of GPT by OpenAI in 2018 marked the rapid entry of LLMs into mainstream discourse and applications, profoundly impacting various sectors (Radford, et. al., 2018). Generative Pre-trained Transformer (GPT) is a transformer based LLM which employs decoder architecture. Bidirectional Encoder Representation from Transformers (BERT) is released by Google concurrently, which also depends on Transformer. But it adopts a different approach and rather than predicting the next word in the sentence like GPT, it predicts some masked words in the sentence and learns bidirectional semantic context (Devlin, et. al., 2019). Developed as a competitor to ChatGPT in 2023, Gemini (formerly Bard) is based on the Pathways architecture created by Google DeepMind (DeepMind, 2023). It can create not only text, but also audio, video, image and code content. Large Language Model Meta AI (LLaMA) is one of the most important open-source LLMs designed by Meta. The core importance of Llama is rooted in its open-source nature, thereby providing both researchers and developers with direct, unencumbered access to the model's parameters and architectural blueprints. Open accessibility has led to the development of numerous derivative models such as Alpaca, Vicuna, Mistral, primarily driven by collective community contributions. T5 is Google's sequence-to-sequence transformer-based model. It approaches all tasks as a text-to-text problem. There are a lot of different LLMs in various domains. Some of them are Meta's

Make-a-video (Singer, et.al., 2022) for video, Github’s CoPilot (Github, 2023) for code, JukeBox (Dhariwal, et. al., 2020) for music generation. It can be found a summary of major milestones of LLMs in Table 1 and a comprehensive comparison of some LLMs according to accuracy and complexity in Figure 5 (Jovanovic & Campbell, 2022).




Figure 5. Accuracy and complexity comparison of LLMs

Table1. A summary of major milestones of LLMs

Date	Model	Key Features	Significance
2017	Transformer (Vaswani et al.)	Introduced the self-attention mechanism and positional encoding	Established the foundation for scalable sequence modeling and parallel training
2018	GPT (Radford et al.)	Unsupervised pretraining using transformer decoder blocks	Demonstrated transfer learning for natural language understanding
2019	BERT (Devlin et al.)	Bidirectional encoding with masked language modeling	Enabled deep contextual comprehension in NLP tasks
2019–2020	GPT-2, RoBERTa, XLNet, T5	Larger datasets, refined training objectives	Marked a transition to general-purpose language understanding
2020	GPT-3 (Brown et al.)	175 billion parameters; few-shot learning	Enabled coherent open-domain text generation and reasoning
2022	InstructGPT / ChatGPT	Reinforcement Learning from Human Feedback (RLHF)	Introduced alignment with human intent and safer dialogue generation
2022	Stable Diffusion (Stability AI, LMU Munich, Runway)	Latent Diffusion Model (LDM)	Enabled high-quality, open-access text-to-image generation using latent space denoising; marked a major step in democratizing generative image synthesis.
2023	Gemini 1 (Google DeepMind)	Multimodal (text, vision, audio, code) reasoning	Integrated multiple modalities into a unified transformer framework
2023	GitHub Copilot (OpenAI + GitHub)	Fine-tuned transformer for software development	Popularized AI-assisted programming and code completion
2024	GPT-4 / GPT-4o (OpenAI)	Multimodal input (text, image, audio) with improved reasoning	Unified perception and reasoning across modalities

2024	Claude 3 (Anthropic)	Constitutional AI for safety and ethical alignment	Advanced transparency and user intent understanding
2024	LLaMA 3 (Meta)	Open-weight, high-efficiency model family	Democratized access to powerful open-source LLMs
2024	Mistral 7B / Mixtral 8x7B	Sparse mixture-of-experts (MoE) design	Enhanced efficiency without compromising accuracy
2025	Gemini 1.5 / Gemini 2 (Google DeepMind)	Long-context, multimodal reasoning, code understanding	Extended context memory and improved symbolic reasoning
2025	Claude 3.5 (Anthropic)	Real-time reasoning and factual consistency	Enhanced step-by-step reasoning and chain-of-thought reliability
2025	OpenAI o1 (Reasoning Model)	Specialized reasoning model with self-verification	Represents the frontier in structured logical problem-solving
2025	DeepSeek (Hangzhou DeepSeek AI)	Mixture-of-Experts (MoE) with Multi-head Latent Attention (MLA)	Combines efficient large-scale training and open-weight transparency; competitive with GPT-4-level models while maintaining lower computational costs.

4. Ethical Concerns, Limitations, Opportunities and Future Directions

Generative AI has quickly become one of the most exciting areas in artificial intelligence, allowing computers to create original and meaningful content. It raised opportunities for human interact with machines and explored many ways of creativity in many different areas such as industry, science, design, architecture, entertainment, art, literature etc. But this comes with ethical concerns, copyright and originality issues. In creativity matters, it is highly vague where generation of users start and where generation of GAI ends. So, this may raise concerns about artists, designers or writers taking credit for their AI assisted works.

Despite the remarkable progress in Generative AI, numerous challenges remain regarding ethical concerns, transparency, misuse or misinformation.

Since general purpose, multimodal GAIs require large scale datasets to learn language patterns, they are also highly dependent on the data. Most of data used in GAI are extracted from Internet sources so, the bias, discriminative content and controversial issues in data are directly carried out to model. The bias descended from data is called training bias. Sometimes, even if training data is clean, bias may occur in GAI system which is called algorithmic bias. GAI model being overfitted during training and not be able to learn data distribution appropriately cause algorithmic bias (Koehler, 2024).

The deployment of Generative AI (GAI) across the healthcare and education sectors holds the potential to yield substantive and immense benefits. The generation of personalized educational material provides significant advantages for students, teachers, individuals with learning disabilities, and adult learners. Similarly, in the healthcare sector, GAI will become one of the most important tools for improving individuals' quality of life through its capabilities such as drug design, personalized health monitoring, and customized diagnosis and treatment (Takale, et. al. 2024). Furthermore, given that the dataset holds a critical role in the training of GAI models, and acquiring sufficient, high-quality data is challenging in healthcare and numerous other sectors, the capacity for synthesizing novel data will specifically accelerate academic and scientific studies.

On the other hand, GAI applications being unexpensive, accessible and easy to use facilitate malicious use and abuse. Especially with deep fake applications users make highly realistic images, videos or even speeches which can be used for manipulating, deceive or blackmailing people. It can easily ruin an individual's reputation or impersonate them. This is why the transparency and interpretability of GAI are becoming crucial. Being able to interpret the system's underlying decision-making process and understand the reasons behind them both encourages responsible use by preventing manipulation and helps users be more aware of inaccurate, incomplete, or fabricated content created by GAI. To use GAI correctly and properly, user awareness must be increased, and training should be offered as needed (Kılınç & Keçecioğlu, 2024).

Interest in Generative AI among scientists and academics has been steadily rising, in parallel with its popularization and permanent integration into daily life, particularly over the last decade. The widespread adoption of open-source GAI models is critical for the advancement of this domain. However, due to the substantial requirements for processing power, storage capacity, and specialized hardware, GAI remains significantly more expensive than what an ordinary researcher can afford. For instance, the estimated computational cost for a single training run of GPT-3 (trained with 175 billion parameters on 300 billion tokens)

is approximately \$5 million (Corchado, et. al. 2023). So, it is highly expensive to research as an individual.

Conversely, the apprehension that GAI will lead to job displacement by eliminating certain occupations is among the escalating societal concerns. Nevertheless, while GAI's capability to automate specific tasks may indeed suppress some job roles, it concurrently gives rise to numerous novel job categories, such as prompt engineering. Furthermore, the automated handling of mundane, repetitive, and low-creativity tasks frees up employees in many professions, including software development and accounting, from burdensome chores, allowing them to dedicate more time to higher-level, large-scale, and creativity-intensive assignments.

5. Conclusion

The evolution of generative artificial intelligence has redefined the boundaries between human creativity and machine capability. What started as a question about whether machines could think has now become a reality where they can not only process and understand data but also create new, meaningful, and original content. From the foundational architectures such as Autoencoders and Recurrent Neural Networks to the revolutionary Transformer-based models, the progress in generative AI represents one of the most remarkable technological achievements of the modern era.

Generative models such as GANs, VAEs, Diffusion Models, and Transformer-based LLMs have each contributed unique mechanisms to learn data distributions and synthesize new content. These models have demonstrated extraordinary success across various modalities, including text, image, audio, and video generation. Their influence extends far beyond the field of computer science, impacting disciplines as diverse as healthcare, education, art, entertainment, and creative design. The multimodal nature of modern architectures such as GPT-4, Gemini, and LLaMA exemplifies the convergence of language, vision, and reasoning within a unified framework of intelligence.

Besides numerous benefits of deployment generative AI, ethical, social, and technical challenges remain. Concerns related to bias, misinformation, authenticity, and intellectual property have become increasingly important. The same systems capable of artistic and scientific breakthroughs can also be misused for manipulation or deception if not governed responsibly. Ensuring transparency, fairness, and interpretability within these systems remains one of the central goals of future AI research. Consequently, policymakers, engineers,

ethicists, and philosophers must collaborate to establish the necessary regulatory frameworks that ensure these principles are upheld. In the future, the responsible and transparent use of generative AI will be essential to ensure that it supports human progress, creativity, and ethical innovation.

References

- Feuerriegel, S., Hartmann, J., Janiesch, C., & Zschech, P. (2024). Generative ai. *Business & Information Systems Engineering*, 66(1), 111-126.
- Rios-Campos, C., Viteri, J. D. C. L., Batalla, E. A. P., Castro, J. F. C., Núñez, J. B., Calderón, E. V., ... & Tello, M. Y. P. (2023). Generative artificial intelligence. *South Florida Journal of Development*, 4(6), 2305-2320.
- Banh, L., & Strobel, G. (2023). Generative artificial intelligence. *Electronic Markets*, 33(1), 63.
- Van Engelen, J. E., & Hoos, H. H. (2020). A survey on semi-supervised learning. *Machine learning*, 109(2), 373-440.
- Rosenblatt, F. (1957). The perceptron, a perceiving and recognizing automaton project para, report: cornell aeronautical laboratory, cornell aeronautical laboratory. URL: <https://books.google.pl/books>.
- Hochreiter, S., & Schmidhuber, J. (1997). Long short-term memory. *Neural computation*, 9(8), 1735-1780.
- Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25.
- Alec, R., Karthik, N., Tim, S., & Ilya, S. (2018). Improving language understanding with unsupervised learning. *Citado*, 17, 1-12.
- Devlin, J., Chang, M. W., Lee, K., & Toutanova, K. (2019, June). Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)* (pp. 4171-4186).
- Goodfellow, I. J., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., ... & Bengio, Y. (2014). Generative adversarial nets. *Advances in neural information processing systems*, 27.
- Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., ... & Polosukhin, I. (2017). Attention is all you need. *Advances in neural information processing systems*, 30.

Kingma, D. P., & Welling, M. (2013). Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*.

Ho, J., Jain, A., & Abbeel, P. (2020). Denoising diffusion probabilistic models. *Advances in neural information processing systems*, 33, 6840-6851.

Bengesi, S., El-Sayed, H., Sarker, M. K., Houkpati, Y., Irungu, J., & Oladunni, T. (2024). Advancements in generative AI: A comprehensive review of GANs, GPT, autoencoders, diffusion model, and transformers. *IEEE Access*, 12, 69812-69837.

Foster, D. (2022). *Generative deep learning*. “O’Reilly Media, Inc.”.

He, R., Cao, J., & Tan, T. (2025). Generative artificial intelligence: a historical perspective. *National Science Review*, 12(5), nwaf050.

Arjovsky, M., Chintala, S., & Bottou, L. (2017, July). Wasserstein generative adversarial networks. In *International conference on machine learning* (pp. 214-223). PMLR.

Sengar, S. S., Hasan, A. B., Kumar, S., & Carroll, F. (2025). Generative artificial intelligence: a systematic review and applications. *Multimedia Tools and Applications*, 84(21), 23661-23700.

Mao, X., Li, Q., Xie, H., Lau, R. Y., Wang, Z., & Paul Smolley, S. (2017). Least squares generative adversarial networks. In *Proceedings of the IEEE international conference on computer vision* (pp. 2794-2802).

Zhang, H., Goodfellow, I., Metaxas, D., & Odena, A. (2019, May). Self-attention generative adversarial networks. In *International conference on machine learning* (pp. 7354-7363). PMLR.

Odena A (2016) Semi-supervised learning with generative adversarial networks.

Odena A, Olah C, Shlens J (2017) Conditional image synthesis with auxiliary classifier gans.

Mirza, M., & Osindero, S. (2014). Conditional generative adversarial nets. *arXiv preprint arXiv:1411.1784*.

Radford, A., Metz, L., & Chintala, S. (2015). Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*.

Srinivasa Rao, T., Mandava, S. K., Madathala, H., Durgaraju, S., & Dalal, A. (2025). Generative AI. *Sarath Krishna and Madathala, Harikrishna and Madathala, Harikrishna and Durgaraju, Sairam and Durgaraju, Sairam and Dalal, Aryendra, Generative AI (January 01, 2025)*.

Song, J., Meng, C., & Ermon, S. (2020). Denoising diffusion implicit models. *arXiv preprint arXiv:2010.02502*.

Rombach, R., Blattmann, A., Lorenz, D., Esser, P., & Ommer, B. (2022). High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition* (pp. 10684-10695).

Christiano, P. F., Leike, J., Brown, T., Martic, M., Legg, S., & Amodei, D. (2017). Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30.

Devlin, J., Chang, M. W., Lee, K., & Toutanova, K. (2019, June). Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)* (pp. 4171-4186).

DeepMind. (2023). *Gemini: A new generation of multimodal AI models*. Google DeepMind. <https://deepmind.google/technologies/gemini/>

Singer, U., Polyak, A., Hayes, T., Yin, X., An, J., Zhang, S., ... & Taigman, Y. (2022). Make-a-video: Text-to-video generation without text-video data. *arXiv preprint arXiv:2209.14792*.

GitHub. (2023). *GitHub Copilot documentation*. GitHub. <https://docs.github.com/en/copilot>

Dhariwal, P., Jun, H., Payne, C., Kim, J. W., Radford, A., & Sutskever, I. (2020). Jukebox: A generative model for music. *arXiv preprint arXiv:2005.00341*.

Jovanovic, M., & Campbell, M. (2022). Generative artificial intelligence: Trends and prospects. *Computer*, 55(10), 107-112.

Koehler, D. (2024). Large Scale Architectures: A Review of the Architecture of Generative AI. *Technology| Architecture+ Design*, 8(2), 394-399.

Takale, D. G., Mahalle, P. N., & Sule, B. (2024). Advancements and applications of generative artificial intelligence. *Journal of Information Technology and Sciences*, 10(1), 20-27.

Kılınç, H. K., & Keçecioglu, Ö. F. (2024). Generative Artificial intelligence: a historical and future perspective. *Academic Platform Journal of Engineering and Smart Systems*, 12(2), 47-58.

Corchado, J. M., López, S., Garcia, R., & Chamoso, P. (2023). Generative artificial intelligence: Fundamentals. *ADCAIJ: advances in distributed computing and artificial intelligence journal*, 12, e31704-e31704.

Rombach, R., Blattmann, A., Lorenz, D., Esser, P., & Ommer, B. (2022). High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition* (pp. 10684-10695).

Rahmatulloh, A. (2025). Custom concept text-to-image using stable diffusion Model in generative artificial intelligence. *JICO: International Journal of Informatics and Computing*, 1(1), 1-11.

CHAPTER II

FROM COMPRESSION TO CREATIVITY: KOLMOGOROV COMPLEXITY IN GENERATIVE AI

Saliha YEŞİLYURT¹ & Zehra BİLİCİ² & Doğa NALCI³

*¹ Sivas Cumhuriyet University & Gebze Technical University,
Computer Engineering Department, Sivas, Türkiye,
Email: salihayesilyurt@cumhuriyet.edu.tr,
ORCID: 0000-0003-2154-8932*

*² Gebze Technical University, Computer Engineering
Department, Kocaeli, Türkiye,
Email: zbilici@gtu.edu.tr,
ORCID: 0000-0002-5417-428X*

*³ Gebze Technical University, Computer Engineering Department &
Cybersecurity Vocational School, Kocaeli, Türkiye,
Email: doganalci@gtu.edu.tr,
ORCID: 0009-0005-0539-2562*

1. Introduction

The relationship between compression and prediction lies at the heart of modern artificial intelligence. Every learning system, whether biological or artificial, must discover patterns that allow it to represent the world concisely and predict future observations effectively. This equivalence between understanding and compression is formalized through information theory and, more rigorously, through algorithmic information theory (AIT) and Kolmogorov Complexity (KC). Within this framework, intelligence can be interpreted as the capacity to generate short, efficient descriptions of data—programs that summarize experience in its most compact form.

Formally, prediction and lossless coding are equivalent processes. Under an optimal code, the expected code length matches the negative log-likelihood of a model’s predictions. This equivalence explains why information theory and machine learning are “two sides of the same coin” (Dai et al., 2024). Any predictive model can be transformed into a compressor through arithmetic coding, while a compressor can be interpreted as a probabilistic predictor based on code lengths. This conceptual unity defines what is now known as the Prediction–Compression Equivalence, summarized in Figure 1.




Figure 1. The diagram illustrates the bidirectional relationship between prediction and compression. (a) In the forward direction, probabilistic predictions are encoded into bitstreams by an arithmetic coder. (b) In the reverse direction, code lengths define predictive distributions. Together, they show that minimizing predictive loss is mathematically identical to minimizing expected code length.

When these models learn statistical regularities in data, they effectively perform compression. They replace redundant structure with a compact set of generative rules. The Solomonoff–Hutter theory of universal induction formalizes this insight by proving that optimal prediction and optimal compression coincide up to a constant (Hutter, 2006; Solomonoff, 1964). Thus, inference and compression are not separate endeavours but different views of the same process—one reconstructs data, the other explains it.

Kolmogorov Complexity gives this intuition mathematical precision. For an object x , $K(x)$ is defined as the length of the shortest program on a fixed universal Turing machine that outputs x and halts (Kolmogorov A, 1965; Li & Vitányi, 2008). $K(x)$ therefore, represents the absolute information content of

x : the minimal description from which it can be regenerated. Importantly, $K(x)$ sets a lower bound on all achievable compression; no algorithm can encode x in fewer bits beyond an additive constant (Chaitin, 1966). However, this quantity is incomputable, as determining it exactly would solve the halting problem (Turing, 1937). Consequently, practical compression methods can only approximate $K(x)$ through computable upper bounds or heuristics (Vitányi, 2006).




Figure 2. Adjusted compression rates combine output code length with model size. The resulting curve shows a trade-off: larger models reduce per-token loss but can worsen total compression beyond an optimal point (Delétang et al., 2023).

In artificial intelligence, this limitation has deep implications. Every model strives to approximate the shortest effective description of its training data, yet the true minimum—the Kolmogorov complexity—is unreachable. The challenge, then, is to develop architectures that approach this ideal within finite resources. Recent advances such as transformer-based LLMs have made remarkable progress. When viewed as compressors, they achieve competitive lossless compression rates not only on text but across modalities. For example, the Chinchilla-70B model compresses ImageNet patches to 43.4% and LibriSpeech audio to 16.4% of raw size, outperforming traditional codecs like PNG (58.5%) and FLAC (30.3%) (Delétang et al., 2023). These results demonstrate that abstractions learned in one modality (text) can generalize to others—a key signature of genuine compression-based understanding.

Tokenization also plays a critical role in this process. It acts as a pre-compression step that defines the model’s alphabet and determines which regularities are captured by preprocessing versus learned during training. Choices in tokenization thus shape achievable bit-rates, model generalization,

and ultimately, compression efficiency (Delétang et al., 2023). As shown in Figure 2, even model scaling laws can be interpreted through the lens of compression. As parameter size increases, predictive loss decreases but total description length (including model size) may rise, revealing an optimal balance between capacity and parsimony.

Although contemporary generative models only approximate the ideal envisioned by Kolmogorov, they nonetheless operate within the same theoretical framework. In the universal coding limit, replacing code length with $K(x)$ yields the Solomonoff predictor, where shorter programs correspond to higher prior probability. Hence, better compression implies better modeling of reality. This convergence of predictive and descriptive efficiency provides a unifying foundation for understanding not only learning but also creativity. A creative system, in this light, is one that generates new data by recombining compressed representations—discovering short programs that capture both structure and novelty (Schmidhuber, 2008).

The subsequent sections expand upon this foundation. Section 2 traces the historical development of information theory leading to Kolmogorov’s algorithmic approach. Section 3 examines how the prediction–compression equivalence manifests in modern AI systems. Section 4 introduces recent Kolmogorov-based benchmarks that operationalize intelligence as compression, while Sections 5 and 6 explore recursive compression frameworks and their implications for creativity. Finally, Sections 7 and 8 discuss open challenges, future directions, and a concluding synthesis.

2. Historical Foundations

The idea that knowledge is compression has deep historical roots. Before Kolmogorov formalized algorithmic information, scientists had already explored different ways of quantifying information—combinatorial, probabilistic, and algorithmic. Each approach reflects a distinct philosophical view of what it means to “measure” information and how this measurement relates to learning and prediction.

2.1. Combinatorial and Probabilistic Views

In his 1965 essay, Andrey Kolmogorov identified three principal approaches to the quantitative definition of information (Kolmogorov A, 1965). The combinatorial approach measures information by counting possibilities. Fixing a variable $x = a$ within a set of N possible outcomes provide $H(x) = \log_2 N$

bits of information. This perspective is purely discrete; information is treated as reduction in uncertainty when one element is selected from a finite set. It applies well to deterministic systems such as codes, games, or logical puzzles, where probabilities are unnecessary.

The probabilistic approach, developed most notably by Claude Shannon (1948), introduced entropy as the expected information content of a random variable. Here, information depends on the probability distribution $p(x)$:

$$H(X) = -\sum_x p(x) \log_2 p(x)$$

This framework enabled engineering breakthroughs such as channel capacity, rate–distortion theory, and source coding theorems. However, it presupposes an ensemble of outcomes—an assumption that becomes artificial when analysing individual objects, such as a particular novel or scientific dataset. These conceptual limitations inspired Kolmogorov to seek a third, more general definition.

2.2. The Algorithmic Turn

Kolmogorov’s algorithmic approach addressed the problem of measuring the information content of a single object without assuming any underlying probability distribution. The Kolmogorov complexity $K(x)$ of a finite string x is defined as the length of the shortest program that produces x and halts on a fixed optimal universal Turing machine (Li & Vitányi, 2008). This definition provides an absolute measure of information that applies to any data type—numeric, textual, or visual—because any computable description can be represented as a program.

The algorithmic view unites description and prediction. According to the Algorithmic Coding Theorem,

$$K(x) = -\log m(x) + O(1)$$

where $m(x)$ denotes the universal distribution or algorithmic probability (Solomonoff, 1964). This equation links complexity and probability, objects generated by shorter programs have higher prior probability. The result encapsulates the intuition that simpler explanations are more likely—a mathematical expression of Occam’s razor.

Building on this foundation, Levin (1984) introduced resource-bounded variants such as $K_t(x)$, which add runtime penalties to favor both short and

efficient programs. These forms bridge the theoretical world of unbounded computation and the practical constraints of real machines. They also inspired modern bounded approximations such as the Coding Theorem Method (CTM) and Block Decomposition Method (BDM), which estimate complexity through empirical enumeration or block wise aggregation of local patterns (Zenil et al., 2015).

The progression from combinatorial counting to probabilistic entropy and finally to algorithmic complexity is summarized in Figure 3, which visually contrasts these three paradigms and highlights the increasing role of computation in defining information.

2.3. From Incomputable Ideals to Practical Measures

Kolmogorov’s framework provides a universal benchmark for all forms of description. Yet $K(x)$ is uncomputable, no algorithm can determine the shortest program that outputs a given string, because that would solve the halting problem. Despite this, the concept remains operational through computable approximations and theoretical bounds (Vítányi, 2006). Researchers distinguish between uncomputable measures, which define the ideal, and computable surrogates, which approximate it within limited resources.

These relationships are summarized in Table 1, which organizes the main measures in Algorithmic Information Theory (AIT) by their basis, computability, role in prediction, and practical caveats.




Figure 3. The combinatorial approach counts possibilities, the probabilistic approach measures average uncertainty, and the algorithmic approach quantifies the complexity of individual objects through computation. Together they chart the evolution from counting to coding to computation.

2.4. Inductive Inference and the Birth of Universal Prediction

The link between description length and prediction was made explicit by Ray Solomonoff in his theory of algorithmic probability (Solomonoff, 1964). He proposed assigning prior probability to outputs in proportion to the summed weights $2^{-|p|}$ of all programs that produce them. This formulation yields a universal semimeasure $m(x)$ satisfying the coding theorem identity, ensuring that short programs dominate the distribution. In effect, Solomonoff's model formalizes inductive reasoning as probabilistic weighting of simple explanations.

Later, Hutter extended these principles to define universal sequence prediction, showing that expected loss under this prior converges to the theoretical optimum. Together, these developments established a unified view of intelligence as compression-based inference, where learning corresponds to discovering concise generative mechanisms that balance accuracy and parsimony.

In summary, by integrating the combinatorial, probabilistic, and algorithmic approaches, Kolmogorov reframed information theory as a study of computation itself. Description length became not just a measure of uncertainty but a universal language for understanding, predicting, and generating data.

The next section builds upon this foundation to examine how compression functions as prediction within modern artificial intelligence systems.

Table 1. Comparative Overview of Algorithmic Information Measures

Complexity Variant	Basis	Computability	Predictive / Modeling Role	Key Caveats
Kolmogorov complexity $K(x)$	Shortest self-delimiting program on an optimal UTM	Not computable, upper-semi computable	Theoretical lower bound on lossless compressibility, via the coding theorem relates to $m(x)$	Depends on choice of optimal UTM up to $O(1)$, not directly estimable
Plain complexity $C(x)$	Shortest program (not self-delimiting)	Not computable, upper-semi computable	Related to $K(x)$ by $K(x) \leq C(x) + O(\log x)$	Additive constants matter in practice, lacks prefix-freeness
Time-bounded complexity $K_t(x)$	Program length + runtime penalty (length–time trade-off)	Not computable in general, upper-semi computable, practical upper bounds under resource limits	Favors short and fast programs, motivation for efficient prediction	Time bound and machine model affect values
CTM / BDM approximations	Small-machine enumeration, block decomposition	Computable heuristics	Practical heuristics for short strings & local structure, empirical structure discovery	Resolution-dependent, finite-state biases, scaling limits, domain sensitivity
Levin’s universal prior $m(x)$	Weighted sum of programs $m(x) = \sum_{p:U(p)=x} (2^{- p })$	Lower-semi computable, semimeasure	Levin’s universal prior $m(x)$	Weighted sum of programs (
The Algorithmic Coding Theorem: $K(x) = -\log m(x) + O(1)$.				
Algorithmic Probability (Solomonoff–Levin): $\sum_{p:U(p)=x} (2^{- p })$				
View shift: probabilistic (ensemble) → algorithmic (individual object).				

3. Compression as Prediction in AI

The link between compression and prediction is not only theoretical—it defines how all modern machine learning systems operate. In essence, a model

that predicts well must also compress effectively. This equivalence arises directly from Shannon’s source coding theorem, which proves that the expected length of an optimal code equals the cross-entropy between the true data distribution $p^*(x)$ and the model’s estimated distribution $q(x)$:

$$L = -E_p[\log q(x)] = H(p^*, q)$$

Minimizing cross-entropy, therefore, is identical to minimizing expected code length. Every gradient descent step toward higher likelihood is simultaneously a step toward shorter description.

3.1. The Compression–Prediction Pipeline

In practice, arithmetic coding turns this theoretical relationship into a concrete mechanism. Given an autoregressive model $q(x_i | x_{<i})$, arithmetic coding can encode data using approximately $-\log_2 q(x_i | x_{<i})$ bits per symbol (Witten et al., 1987). The total message length thus measures predictive accuracy. When this model is trained by maximizing log-likelihood, it implicitly minimizes code length.

The same logic extends to latent-variable models, such as Variational Autoencoders (VAEs). When coding both the latent variable z and the data conditional $p(x | z)$, the overall cost equals the Evidence Lower Bound (ELBO). Training by maximizing ELBO hence amounts to training for compression (Kingma & Welling, 2013). These relationships unify deep learning objectives with information-theoretic principles, whether through cross-entropy, variational bounds, or mutual information, the goal remains optimal compression.

3.2. Large-Scale Models as Universal Compressors

Viewed through this lens, large language models (LLMs) are enormous compression engines. Their training objective—minimizing predictive loss—translates directly into minimizing expected code length. With arithmetic coding, LLMs can achieve lossless compression competitive with or superior to classical algorithms across multiple modalities (Delétang et al., 2023). For instance, text-trained models such as Chinchilla and GPT-4 compress not only text but also images and audio, achieving rates far below standard codecs. This suggests that high-level abstractions learned from textual data generalize across domains, embodying cross-modal compression.

Model size, however, complicates this picture. If we treat the parameters themselves as part of the total description, total code length equals the sum of

data code length and model code length. As model parameters increase, per-token loss may fall, but total compression efficiency eventually declines—a behaviour visualized earlier in Figure 2. This trade-off forms the foundation of scaling laws, which define optimal model sizes for a given dataset (Hoffmann et al., 2022).

3.3. Diffusion Models and Generative Compression

Recent developments extend this principle beyond text to diffusion models, which generate data through iterative denoising. At each timestep, a diffusion model predicts the noise component of a corrupted input; the training loss, usually mean-squared error or KL-divergence, is again equivalent to minimizing expected code length between model predictions and data distributions. In practice, the latent trajectories of diffusion models can be interpreted as progressive compression stages. Each denoising step removes entropy, transforming random noise into structured output. Thus, diffusion models embody compression not only statistically but dynamically compressing disorder into order.

3.4. Tokenization and Representation as Pre-Compression

A crucial but often overlooked step in this process is tokenization, which defines the alphabet over which compression occurs. Tokenization determines sequence length, context granularity, and the model’s ability to capture dependencies. Subword methods such as Byte-Pair Encoding (BPE) or SentencePiece serve as pre-compression mechanisms, they balance redundancy removal with expressive capacity (Delétang et al., 2023). Vocabulary size directly affects per-token entropy and therefore achievable bitrates. Large vocabularies increase representational precision but reduce compression efficiency; smaller vocabularies favour compactness at the expense of detail. In this sense, tokenization itself is part of the compression model—it defines what structure is explicit and what must be learned.

3.5. Generalization Through the Minimum Description Length Principle

The Minimum Description Length (MDL) principle (Grünwald, 2007; Rissanen, 1978) provides the theoretical bridge between compression and generalization. According to MDL, the best hypothesis is the one that yields the shortest total description of both the model and the data it explains. Learning thus becomes the search for the most concise yet predictive representation. This

view aligns naturally with PAC-Bayesian theory, where models that generalize well are precisely those that compress the training data effectively (Dziugaite & Roy, 2017).

In empirical studies, neural networks have demonstrated this property even without explicit regularization. When trained on real data, they find internal representations that compress across domains, whereas random labels destroy compressibility and prevent generalization (Zhang et al., 2016). Compression, therefore, is not just a by-product of learning—it is its fundamental precondition.

3.6. The Limits of Statistical Compression

Despite their power, current systems achieve only statistical compression, not true algorithmic compression. Statistical compressors approximate probabilities over fixed alphabets; they do not discover the shortest generative program that produces the data. Kolmogorov complexity $K(x)$, which defines that ideal, remains incomputable (Vitányi, 2006). Practical methods like CTM or BDM approximate it only for short strings or simple structures (Zenil et al., 2015). Consequently, modern AI operates below the Kolmogorov limit—it captures correlations, not causes.

Bridging this gap requires models capable of explicit program induction rather than probability estimation. The next section introduces recent efforts to operationalize this idea, such as the Kolmogorov Test (KT), which evaluates intelligence by asking models to produce minimal programs that recreate observed sequences. These benchmarks move the field from statistical redundancy reduction toward algorithmic reasoning and creative abstraction.

4. Beyond Statistical Compression: Kolmogorov Tests of Intelligence

Statistical compression explains how models reduce redundancy by fitting data distributions, yet it does not capture the essence of creative intelligence. True creativity involves discovering the shortest set of generative rules that can reproduce observations, not merely predicting the next symbol. This distinction motivates a growing body of research that evaluates artificial intelligence systems through the lens of algorithmic compression, where success depends on program synthesis rather than likelihood optimization.

4.1. The Kolmogorov Test as a Measure of Intelligence

The Kolmogorov Test (KT), introduced by Yoran et al. (2025), evaluates intelligence as compression through code generation. Instead of predicting

tokens, a model must generate a concise program that reconstructs a target sequence exactly. Each candidate program is executed, and the resulting sequence is compared to the original. The shorter the program that succeeds, the greater the model’s measured intelligence.

This framework provides a practical way to approximate the Kolmogorov complexity $K(x)$, which defines the length of the shortest program producing an object x . Because $K(x)$ is incomputable, KT uses program synthesis as a proxy, treating code-generating language models as empirical estimators of algorithmic compression. A model that produces shorter, functionally correct code exhibits deeper abstraction ability.

4.2. Methodology and Design Principles

The KT benchmark presents a sequence during inference and asks the model to output a program that, when executed, reproduces that sequence. Each trial measures both correctness and compression ratio, ensuring that mere memorization cannot succeed. The benchmark has several advantages.

1. The compression metric is difficult to exploit because shorter programs are objectively verifiable.

2. It accommodates diverse sequence types such as text, audio, and biological data.

3. Pretraining contamination is unlikely, since training corpora rarely include matching program–sequence pairs.

4. Difficulty can be adjusted by controlling sequence length or the depth of compositional operators.

To ensure reproducibility, KT employs a domain-specific language (DSL) with known ground-truth shortest programs. This design allows researchers to quantify how far a model’s generated code diverges from the theoretical minimum, providing an operational measure of algorithmic reasoning.

4.3. Empirical Findings and Interpretations

Results reveal that even state-of-the-art large language models perform poorly on KT benchmarks. On natural sequences, LLaMA-3.1-405B fails in about 78% of cases, and GPT-4o fails in about 40%. Smaller code-specialized models, although trained on explicit program–sequence pairs, only partially improve performance, with gains that do not generalize to real data (Yoran et al., 2025).

These findings highlight a key limitation. While current models achieve strong Shannon-style compression, they remain far from discovering true Kolmogorov-style programs. They can predict but rarely explain. This gap marks the boundary between statistical redundancy removal and mechanistic understanding, which is central to both creativity and intelligence.

4.4. Creativity as Algorithmic Abstraction

In the Kolmogorov framework, creativity can be defined as the ability to find short programs that balance concision with explanatory adequacy. Systems that learn reusable structures or compositional rules are more creative because they achieve deeper compression through generalization. For example, a model that infers the recursive pattern behind a musical sequence demonstrates creativity beyond statistical imitation.

Benchmarks such as KT move this notion from theory to measurement. By rewarding models that generate concise, reusable code, KT encourages abductive reasoning, the process of forming hypotheses that explain observations compactly. This approach aligns directly with the algorithmic probability principle, which assigns exponentially higher weight to shorter explanations (Solomonoff, 1964).

Creativity, therefore, is not defined by novelty alone but by efficient explanation. A creative model discovers patterns that make the world simpler to describe, bridging compression, understanding, and invention.

4.5. Relationship to Practical Approximations

Because exact computation of $K(x)$ is impossible, researchers use approximations such as the Coding Theorem Method (CTM) and the Block Decomposition Method (BDM) (Zenil et al., 2015). CTM estimates algorithmic probability by enumerating small Turing machines and recording their outputs, while BDM extends this to larger data by decomposing it into smaller blocks and summing their estimated complexities. These methods are computationally expensive but provide valuable upper bounds on $K(x)$ for short sequences.

Within KT and related tests, these approximations serve as calibration tools. They help quantify how far a model's generated program lies above the theoretical minimum and clarify the extent to which current neural systems achieve algorithmic compression rather than mere probabilistic modelling.

4.6. *Implications for Diffusion and Transformer Architectures*

The KT perspective also sheds light on the behaviour of contemporary diffusion and transformer-based architectures. Diffusion models reduce entropy progressively, yet they still rely on learned distributions rather than explicit rules. Their compression is statistical, achieved through noise prediction. Transformers, by contrast, learn flexible internal codes that can in principle represent algorithmic relations, but they seldom generate minimal programs spontaneously. Integrating KT-like objectives into their training may encourage explicit program induction and promote genuine creative reasoning.

4.7. *Toward Contamination-Resistant Evaluation*

One of the strengths of KT is its resistance to benchmark contamination, a persistent issue in modern AI evaluation. Because KT uses procedurally generated data with known minimal programs, models cannot rely on memorization. They must generalize the underlying pattern through abstraction. This makes KT a reliable framework for studying reasoning, creativity, and transfer across modalities.

Table 2. Comparative Overview of Algorithmic Information Measures

Feature	Statistical Compression (Shannon-style)	Algorithmic Compression (Kolmogorov-style)
LLM Role	Likelihood Estimator (predicts next token probability).	Program Synthesizer (generates the shortest program).
Compression Target	Minimizing expected code length (statistical redundancy).	Minimizing program length (structural complexity).
Key Mechanism	Arithmetic Coding based on model probabilities.	Code Generation and Execution of the program.
Reference Study	(Delétang et al., 2023)	(Yoran et al., 2025)
Flow	Data Sequence → Language Model → Arithmetic Coder → Compressed Bit Stream	Data Sequence → Code Generating LM → Program Candidate → Execution → Output Sequence

As shown in Table 2, the KT distinguishes between statistical compression, typical of large-scale language modelling, and algorithmic compression, which reflects true program discovery.

In summary, the Kolmogorov Test transforms the abstract idea of algorithmic complexity into an operational benchmark for intelligence and creativity. It exposes the limitations of current models and highlights the need for architectures that search over programs rather than probabilities. The following section explores one such direction, the SuperARC framework, which extends algorithmic compression into recursive, causal reasoning—a possible step toward artificial general intelligence.

5. Recursive Compression and the SuperARC Framework

A growing line of research aims to close the gap between statistical compression and algorithmic reasoning. One of the most promising efforts in this direction is the SuperARC framework, a system that measures intelligence through recursive compression. Rather than focusing on token-level prediction, SuperARC evaluates a model’s ability to discover causal and reusable generative mechanisms that explain data efficiently. The framework proposes that the true hallmark of intelligence lies not in memorizing patterns but in reconstructing the underlying programs that produce them.

5.1. The Principle of Recursive Compression

The core idea of recursive compression is simple yet profound. A system demonstrates understanding when it can explain complex data using a set of short programs that generate and recompose simpler parts. Each recursive step replaces a detailed description with a higher-level rule, and this process continues until the structure cannot be simplified further. The principle echoes the logic of Kolmogorov complexity, in which the shortest program that reproduces a phenomenon represents its most complete explanation.

Within the SuperARC framework (Hernández-Espinosa et al., 2025), compression, prediction, and comprehension are treated as equivalent operations. A model that compresses well must also predict accurately and understand causally, since these three capacities rely on identifying the simplest rules governing the data. In this view, learning corresponds to searching for the most compact generative model that maintains predictive adequacy. The more a system compresses recursively, the closer it comes to genuine understanding.

5.2. From Statistical to Algorithmic Evaluation

SuperARC was introduced as an agnostic benchmark for evaluating a broad range of intelligent systems, from narrow AI models to potential

artificial general intelligence (AGI) candidates. Unlike large language models (LLMs), which rely on statistical inference, SuperARC uses program synthesis and execution-based validation to assess performance. It therefore measures algorithmic compression rather than Shannon-style redundancy reduction.

In traditional LLM-based compression, the trained parameters contain the knowledge required for decompression. Without access to those parameters, the encoded message is meaningless. SuperARC reverses this dependence. The generative rule is embedded directly in the compressed description, enabling independent reconstruction of the original data. This approach aligns evaluation with the definition of Kolmogorov complexity, where a description is valuable only if it contains a self-sufficient mechanism for regeneration.

5.3. Implementation through CTM and BDM

To operationalize recursive compression, SuperARC integrates two methods grounded in Algorithmic Information Theory: the Coding Theorem Method (CTM) and the Block Decomposition Method (BDM).

- **CTM** estimates the complexity of short objects by exhaustively enumerating small Turing machines and observing their outputs. The resulting empirical distribution provides an approximation of algorithmic probability $m(s)$, which relates to Kolmogorov complexity through the equation $K(s) = -\log_2 m(s) + O(1)$.

- **BDM** scales this principle to larger datasets by dividing them into smaller components, estimating the CTM complexity of each block, and adding a correction term for repeated patterns. This method allows recursive analysis of structure and reuse, capturing both local and global regularities.

By combining CTM and BDM, SuperARC rewards systems that discover and reuse subroutines, reflecting the hierarchical organization found in natural and cognitive systems. In other words, it values explanations that are not only short but also modular and compositional.

5.4. The SuperARC Learning Loop

SuperARC operates through a recursive learning loop composed of three main phases: abstraction, simulation, and selection.

1. **Abstraction** involves generating candidate programs consistent with the observed data. CTM provides short microprograms that approximate local regularities.

2. **Simulation** executes these programs to generate predictions and counterfactuals, testing whether the derived mechanisms reproduce the observed data.

3. **Selection** retains only the shortest and most consistent programs according to algorithmic probability, while discarding redundant or overly specific hypotheses.

This cycle continues iteratively, producing a growing library of reusable building blocks that explain increasingly complex observations. The process resembles scientific reasoning, in which hypotheses are proposed, tested, and refined into compact laws.

This process is summarized in Figure 4, which illustrates how abstraction, simulation, and selection together form the recursive compression loop at the heart of the SuperARC framework.

5.5. Comparison with Neural Compression

When compared with large neural models, SuperARC offers a different route to generalization. Neural networks learn distributed representations that encode statistical regularities, but they rarely expose explicit generative rules. SuperARC, by contrast, produces interpretable symbolic programs that serve as direct explanations. The trade-off is computational cost. Enumerating and testing candidate programs is resource-intensive, which limits scalability. However, hybrid strategies that combine neural representation learning with symbolic program induction may overcome this barrier.

Recent studies suggest that neural architectures could serve as proposal generators, identifying promising program fragments that are then verified algorithmically under the SuperARC framework. Such hybrids could integrate the efficiency of gradient descent with the precision of algorithmic reasoning, producing systems capable of creative inference at scale.




Figure 4. The SuperARC is fundamentally a practical application of Algorithmic Information Theory, specifically Kolmogorov Complexity (K).

5.6. Causal Understanding and the Path Toward AGI

The recursive compression principle also provides a theoretical foundation for causal reasoning. In causal modeling, the goal is to find the simplest generative mechanism that produces observed data. This goal is equivalent to identifying the minimal program consistent with all causal dependencies. By connecting algorithmic probability with inductive inference, SuperARC reframes learning as the search for causal simplicity rather than statistical correlation.

This perspective aligns with the philosophical idea that comprehension, prediction, and creativity are three aspects of the same process. A model that can compress the world into a set of compact causal programs not only predicts the future but can also imagine alternative possibilities. In this sense, recursive compression transforms intelligence from passive pattern recognition into active theory formation.

5.7. Toward Practical Integration

Despite its theoretical elegance, recursive compression remains computationally demanding. Complete CTM or BDM evaluations require enumeration of vast program spaces, which grows exponentially with data complexity. To make the approach tractable, researchers are exploring hybrid

neurosymbolic systems where neural components propose candidate structures and algorithmic methods verify or refine them.

Future implementations may also use adaptive search and probabilistic pruning to navigate program space efficiently. These optimizations could enable real-time recursive compression, bringing the principles of SuperARC into practical AI applications, such as interpretable generative design, symbolic reasoning, or self-improving agents.

In summary, SuperARC provides a concrete operationalization of Kolmogorov’s vision of intelligence as efficient description. It goes beyond statistical compression by emphasizing recursive, causal, and interpretable mechanisms. As research moves toward hybrid implementations, the boundary between neural prediction and algorithmic understanding continues to narrow. The next section extends these ideas to the realm of code generation and creativity, where compression becomes a direct measure of a system’s capacity for structured invention.

6. Compression, Code, and Creativity

Programming offers a clear test for the idea that compression reflects intelligence. Code generation tasks require models to learn hierarchical structures and logical dependencies. Unlike plain text, programming languages have strict syntax and semantics. A system that succeeds in this setting must do more than predict frequent tokens. It must capture deeper regularities that explain how symbols combine to create meaning.

6.1. Measuring Intelligence Through Code Compression

In code modeling, bits per character (BPC) is a natural and objective measure of compression. It represents the average number of bits required to encode each symbol. Lower BPC values indicate higher compression and, by extension, better predictive performance. Because BPC is language-agnostic, it allows fair comparison across models and programming languages.

Earlier studies assumed a simple linear relationship between compression and code intelligence. They found that as BPC decreased, accuracy on programming benchmarks increased proportionally. Later research showed that this relationship is not linear but logarithmic (Xuyang et al., 2025). Performance improves quickly at first but then saturates. Once models capture common syntactic patterns, additional compression yields diminishing returns. This pattern reveals an important truth, easy regularities are compressible, while true reasoning requires discovering deeper abstractions.

The logarithmic scaling of performance with compression is visualized in Figure 5, showing how model capability increases rapidly at first and then levels off as compression improves. Empirical analysis across multiple programming tasks shows a consistent logarithmic relationship between compression efficiency (BPC) and model capability. Performance gains slow as models achieve higher compression, revealing the limits of statistical learning (Xuyang et al., 2025).

6.2. From Statistical to Abductive Compression

The compression–intelligence link explains why large models reach a plateau. Once they master surface-level syntax, further progress requires abductive compression, the ability to infer hidden mechanisms that generate observable patterns. For example, a model that recognizes recursion or modular reuse in code compresses more deeply than one that memorizes lines.

The Kolmogorov Test (KT) captures this shift. It measures how well a model can infer short programs that reproduce given sequences (Yoran et al., 2025). KT rewards explanations that are concise and generalizable rather than long and overfitted. Models such as GPT-4o and LLaMA-3.1-405B still struggle with these tasks. They compress statistically but not algorithmically, which shows the gap between memorization and understanding.




Figure 5. Logarithmic relation between Bits per Character and code intelligence across open-source models, showing a consistent scaling shift under different validation settings (Xuyang et al., 2025).

6.3. Algorithmic Probability and Creative Reasoning

Algorithmic probability provides a theoretical explanation for creativity in this context. According to Solomonoff, shorter programs have exponentially higher prior probability. This principle unites compression, prediction, and comprehension. A model that finds a compact explanation demonstrates creativity because it discovers rules that generalize beyond the data.

The SuperARC framework extends this reasoning. It shows that recursive algorithmic compression can produce accurate predictions and causal explanations at the same time (Hernández-Espinosa et al., 2025). In practice, this means learning reusable subroutines—loops, functions, or grammar rules—that describe tasks compactly. Creative systems build such structures instead of memorizing specific outputs.

6.4. Gradient Descent as a Limited Search

Training with gradient descent can be interpreted as a constrained form of compression search. Minimizing log-loss reduces expected code length within a restricted hypothesis class, consistent with the Minimum Description Length (MDL) principle. However, stochastic gradient descent cannot explore the full space of possible programs. It optimizes parameters, not symbolic structures.

This limitation explains why models with excellent statistical compression may still fail at true program synthesis. Bridging the gap requires methods that combine continuous optimization with explicit program-space search. Approaches such as guided priors, execution feedback, or hybrid neurosymbolic models (using CTM and BDM) offer promising directions (Hernández-Espinosa et al., 2025).

6.5. The Broader View of Compression and Creativity

Generative AI systems generalize well because real-world data are compressible. This property links learning to the physical and cognitive world. Schmidhuber (2008) argued that progress in compression is intrinsically rewarding. It drives curiosity and the pleasure of discovery. When a model or a person finds a shorter explanation for complex information, understanding becomes more elegant and efficient.

The same idea connects science and art. Scientists compress the world into concise laws; artists compress experiences into form and rhythm. Both reduce complexity while preserving meaning. In each case, creativity is a search for

simplicity behind apparent diversity. The more compact the representation, the stronger its explanatory power.

In summary, code modelling reveals the intimate relationship between compression and creative reasoning. Statistical compression explains performance gains, but only algorithmic compression explains understanding. Moving toward the latter requires systems that search beyond surface patterns to discover the mechanisms that generate them. The next section outlines the open challenges and future research needed to make that transition.

7. Open Challenges and Future Directions

Kolmogorov Complexity (KC) provides a rigorous framework that links compression to prediction, explanation, and creativity. However, the incomputability of $K(x)$ limits its direct use in generative AI, making current approaches only partial and approximate. Several open challenges shape today's research frontier, as summarized in Table 3.

7.1. Measuring creativity beyond compression.

Measuring creativity beyond compression remains difficult. KC formalizes the idea that shorter explanations are better, grounding Occam's razor in mathematics. This supports the view that creativity can be seen as finding shorter and more explanatory programs. Yet since $K(x)$ is uncomputable, no model can confirm that it has found the shortest description. It is still unclear whether description length alone measures novelty or whether other factors, such as mechanistic adequacy and causal sufficiency, are also needed.

7.2. Benchmarking creative reasoning.

Benchmarks like the Kolmogorov Test (KT) aim to apply KC by asking models to generate short programs that reproduce sequences across domains such as text, audio, and DNA. In theory, this connects statistical prediction to algorithmic abstraction. In practice, large language models perform poorly, showing that they excel at surface-level compression but not yet at the deeper, program-level creativity implied by KC.

7.3. Recursive compression and contamination-resistant testing.

Frameworks like SuperARC extend the KC framework by combining compression, prediction, and comprehension under algorithmic probability

and Solomonoff induction. They use evaluation protocols based on program generation and execution, helping to reduce contamination and overfitting. Yet these methods can only approximate KC, never compute it exactly.

7.4. Hybrid neurosymbolic compression frameworks.

Approximation tools such as the Coding Theorem Method (CTM) and Block Decomposition Method (BDM) also aim to estimate algorithmic probability. They work well for short strings and local structures but face high computational costs that limit scalability. Future studies will likely merge neural predictors with program-space search to build more efficient KC approximations.

7.5. From compression to simulation and design.

KC also highlights the link between compression and simulation. Any good compressor can act as a generator, suggesting that compact programs can serve as simulators for creative synthesis. However, current systems often replicate correlations instead of discovering mechanisms, leaving the path to true abductive compression open.

7.6. Ethical and epistemic limits.

Finally, the incomputability of KC sets an epistemic limit. No algorithm can prove that its explanation is minimal, meaning that both human and artificial creativity are “provably approximate.” This raises ethical and philosophical questions about authorship, understanding, and how to evaluate AI-generated works.

Table 3 summarizes these open challenges, linking each to its relationship with Kolmogorov Complexity, current limitations, and future research directions.

These challenges mark the frontier of research connecting algorithmic information theory and artificial creativity. Addressing them will require both theoretical innovation and computational pragmatism. Progress will depend on how effectively we approximate incomputable ideas within finite systems.

Table 3. Open Challenges in Kolmogorov Complexity and Generative AI

Challenge	Relation to Kolmogorov Complexity	Limitation / Open Question	Future Direction
Measuring creativity beyond compression	KC = shortest description principle	KC incomputable; code length $\neq$ originality	Combine compression with mechanistic adequacy
Benchmarking creative reasoning (KT)	KC as program-length measure	LLMs fail on program-level abstraction	Develop contamination-free creative benchmarks
SuperARC & contamination resistance	Solomonoff induction + algorithmic probability	Prevents leakage but still approximate	Program-based, execution-verified evaluation
Hybrid neurosymbolic frameworks	CTM, BDM as KC approximations	High cost, not scalable	Neural + symbolic hybrid abductive compression
From compression to simulation & design	Compressor $\leftrightarrow$ Generator equivalence	Models copy patterns, not mechanisms	Use compressed programs as simulators for design
Ethical & epistemic limits	KC incomputable, only lower bounds	No guarantee of “shortest program”	Safe approximations, interpretability, credit

8. Conclusion

This chapter explored the connection between compression, prediction, and creativity through the lens of Kolmogorov complexity. It showed that all intelligent systems—whether human or artificial—rely on finding short, efficient representations of information. A model that predicts well must also compress effectively, and a model that compresses deeply must, in some sense, understand what it describes.

Kolmogorov complexity provides a rigorous way to express this idea. It defines information as the length of the shortest program that can generate a given object. Although this quantity is incomputable, it serves as an ideal benchmark for all learning systems. Every compression algorithm, neural network, or symbolic model can be viewed as an approximation of this principle, striving to capture structure with minimal redundancy.

Modern generative models, such as large language models and diffusion systems, have brought this vision closer to practice. Their training objectives, often based on cross-entropy or likelihood, directly minimize expected code length. However, they achieve statistical compression, not algorithmic compression. They predict efficiently but rarely infer the true generative mechanisms behind their data. Bridging this gap requires models that can generate concise, reusable programs rather than long lists of parameters.

Recent developments, including the Kolmogorov Test (KT) and the SuperARC framework, move toward this goal. KT measures intelligence as the ability to produce short, functional code that reproduces observed sequences. SuperARC extends this idea through recursive compression, connecting prediction with causal reasoning and explanation. Both frameworks transform Kolmogorov's abstract theory into operational tests for creativity and understanding.

Yet, several open problems remain. Measuring creativity beyond code length, designing scalable recursive compression algorithms, and building hybrid neurosymbolic systems are ongoing challenges. Ethical and epistemic questions also persist. Because no algorithm can confirm that its explanation is truly minimal, every creative act—human or artificial—is necessarily approximate.

Even with these limits, the principle remains powerful. Compression links efficiency with meaning, simplicity with insight, and learning with creation. It explains why science and art both seek elegant forms, the shortest explanations are often the most beautiful ones. In this sense, intelligence itself can be seen as the art of compression—the drive to transform complexity into understanding.

References

- Chaitin, G. J. (1966). On the Length of Programs for Computing Finite Binary Sequences. *Journal of the ACM (JACM)*, 13(4), 547–569. <https://doi.org/10.1145/321356.321363>
- Dai, J., Qin, X., Wang, S., Xu, L., Niu, K., & Zhang, P. (2024). Deep Generative Modeling Reshapes Compression and Transmission: From Efficiency to Resiliency. *IEEE Wireless Communications*, 31(4), 48–56. <https://doi.org/10.1109/MWC.005.2300574>
- Delétang, G., Ruoss, A., Duquenne, P. A., Catt, E., Genewein, T., Mattern, C., Grau-Moya, J., Wenliang, L. K., Aitchison, M., Orseau, L., Hutter, M., & Veness, J. (2023). Language Modeling Is Compression. *12th International Conference on Learning Representations, ICLR 2024*. <https://arxiv.org/pdf/2309.10668>

Dziugaite, G. K., & Roy, D. M. (2017). Computing Nonvacuous Generalization Bounds for Deep (Stochastic) Neural Networks with Many More Parameters than Training Data. *Uncertainty in Artificial Intelligence - Proceedings of the 33rd Conference, UAI 2017*. <https://arxiv.org/pdf/1703.11008>

Grünwald, P. D. . (2007). *The minimum description length principle*. 703.

Hernández-Espinosa, A., Ozelim, L., Abrahão, F. S., & Zenil, H. (2025). *SuperARC: An Agnostic Test for Narrow, General, and Super Intelligence Based On the Principles of Recursive Compression and Algorithmic Probability*. <https://arxiv.org/pdf/2503.16743v4>

Hoffmann, J., Borgeaud, S., Mensch, A., Buchatskaya, E., Cai, T., Rutherford, E., de Las Casas, D., Hendricks, L. A., Welbl, J., Clark, A., Hennigan, T., Noland, E., Millican, K., van den Driessche, G., Damoc, B., Guy, A., Osindero, S., Simonyan, K., Elsen, E., ... Sifre, L. (2022). Training Compute-Optimal Large Language Models. *Advances in Neural Information Processing Systems*, 35. <https://arxiv.org/pdf/2203.15556>

Hutter, M. (2006). On the Foundations of Universal Sequence Prediction. *Lecture Notes in Computer Science (Including Subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 3959 LNCS, 408–420. https://doi.org/10.1007/11750321_39

Kingma, D. P., & Welling, M. (2013). Auto-Encoding Variational Bayes. *2nd International Conference on Learning Representations, ICLR 2014 - Conference Track Proceedings*. <https://doi.org/10.61603/ceas.v2i1.33>

Kolmogorov A. (1965). Three Approaches To The Quantitative Definition of Information. *Alexander.Shen.Free.Fr*. http://alexander.shen.free.fr/library/Kolmogorov65_Three-Approaches-to-Information.pdf

Levin, L. A. (1984). Randomness conservation inequalities; information and independence in mathematical theories. *Information and Control*, 61(1), 15–37. [https://doi.org/10.1016/S0019-9958\(84\)80060-1](https://doi.org/10.1016/S0019-9958(84)80060-1)

Li, M., & Vitányi, P. (2008). *An Introduction to Kolmogorov Complexity and Its Applications*. <https://doi.org/10.1007/978-0-387-49820-1>

Rissanen, J. (1978). Modeling by shortest data description. *Automatica*, 14(5), 465–471. [https://doi.org/10.1016/0005-1098\(78\)90005-5](https://doi.org/10.1016/0005-1098(78)90005-5)

Schmidhuber, J. (2008). Driven by Compression Progress: A Simple Principle Explains Essential Aspects of Subjective Beauty, Novelty, Surprise, Interestingness, Attention, Curiosity, Creativity, Art, Science, Music, Jokes. *Lecture Notes in Computer Science (Including Subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 5499 LNAI, 48–76. https://doi.org/10.1007/978-3-642-02565-5_4

Shannon, C. E. (1948). A Mathematical Theory of Communication. *Bell System Technical Journal*, 27(3), 379–423. <https://doi.org/10.1002/J.1538-7305.1948.TB01338.X>

Solomonoff, R. J. (1964). A formal theory of inductive inference. Part I. *Information and Control*, 7(1), 1–22. [https://doi.org/10.1016/S0019-9958\(64\)90223-2](https://doi.org/10.1016/S0019-9958(64)90223-2)

Turing, A. M. (1937). On Computable Numbers, with an Application to the Entscheidungsproblem. *Proceedings of the London Mathematical Society*, s2-42(1), 230–265. <https://doi.org/10.1112/PLMS/S2-42.1.230>

Vitányi, P. M. (2006). Meaningful information. *IEEE Transactions on Information Theory*, 52(10), 4617–4626. <https://doi.org/10.1109/TIT.2006.881729>

Witten, I. H., Neal, R. M., & Cleary, J. G. (1987). Arithmetic coding for data compression. *Communications of the ACM*, 30(6), 520–540. <https://doi.org/10.1145/214762.214771>

Xuyang, S., Luo, X., Cheng, T., Chu, Z., Li, H., wang, ziqi, Huang, S., Zhu, Q., Wang, Q., Zhang, X., Zhou, S., & Che, W. (2025). *Is Compression Really Linear with Code Intelligence?* <https://arxiv.org/pdf/2505.11441>

Yoran, O., Zheng, K., Gloeckle, F., Gehring, J., Synnaeve, G., & Cohen, T. (2025). The KoLMogorov Test: Compression by Code Generation. *13th International Conference on Learning Representations, ICLR 2025*, 24471–24501. <https://arxiv.org/pdf/2503.13992>

Zenil, H., Soler-Toscano, F., Delahaye, J. P., & Gauvrit, N. (2015). Two-dimensional Kolmogorov complexity and an empirical validation of the Coding theorem method by compressibility. *PeerJ Computer Science*, 2015(9), e23. <https://doi.org/10.7717/PEERJ-CS.23/SUPP-1>

Zhang, C., Bengio, S., Hardt, M., Recht, B., & Vinyals, O. (2016). Understanding deep learning requires rethinking generalization. *Communications of the ACM*, 64(3), 107–115. <https://doi.org/10.1145/3446776>

CHAPTER III

CONVERSATIONAL AI AND QUESTION ANSWERING SYSTEMS: ARCHITECTURES, TRAINING CHALLENGES AND SOLUTIONS

Ramazan KATIRCI¹ & Hilal ÇELİK² & Taha OĞUZ³

*¹(Prof. Dr.), Sivas University of Science and Technology, Faculty of Engineering and Natural Sciences, Department of Computer Engineering, Sivas/Turkey
E-mail: ramazankatirci@sivas.edu.tr
ORCID: 0000-0003-2448-011X.*

*²(Res. Asst.), Sivas University of Science and Technology, Faculty of Engineering and Natural Sciences, Department of Computer Engineering, Sivas/Turkey
E-mail: hilalcelik@sivas.edu.tr
ORCID: 0000-0001-5428-3411.*

*³(Res. Asst.), Sivas University of Science and Technology, Faculty of Engineering and Natural Sciences, Department of Metallurgical and Materials Engineering, Sivas/Turkey
E-mail: taha.oguz@sivas.edu.tr
ORCID: 0000-0003-4447-645X.*

1. Introduction

Artificial intelligence (AI) refers to the development of computational systems capable of performing tasks that typically require human intelligence, such as learning, reasoning, and natural language understanding (Winston, 2017). Today, AI is applied across a wide range of domains, including healthcare (Tuncer et al., 2024), finance (Çınar & Çelik, 2022), computational social science (Çelik & Çınar, 2021), quantum machine learning (Aasim et al., 2024; Katırcı & Oğuz, 2023) and education (Celik &

Cinar, 2021). Within this broad landscape, conversational agents—most notably chatbots—have gained increasing prominence in recent years, evolving from early rule-based systems such as ELIZA (1966) (Adamopoulou & Moussiades, 2020a) to modern machine learning and deep learning models that underpin state-of-the-art dialogue and question-answering systems (Çelik et al., 2024; Dongbo et al., 2023; Nan et al., 2024).

Modern chatbot and QA systems aim to understand context, extract relevant information, and generate accurate answers, often framed as a reading comprehension task (Adamopoulou & Moussiades, 2020a) (Banitz, 2020; Choudhary & Chauhan, 2023). However, their development is hindered by learning challenges such as overfitting (Ying, 2019), underfitting (Aliferis & Simon, 2024), the bias–variance (Mavrogiorgos et al., 2024) trade-off, and hallucinations (Bang et al., 2024), all of which compromise reliability and generalization. In response to these challenges, researchers commonly employ strategies such as regularization methods—including early stopping (Ying, 2019), and weight decay (Xie et al., 2023), L1 and L2 regularization (Xu et al., 2010), dropout (Katırcı & Çelik, 2024; Srivastava et al., 2014)—as well as the design of domain-specific architectures that balance efficiency with robustness (R. Zhang et al., 2023).

2. Question Answering (QA)

QA is an NLP task that focuses on understanding text and enables machines to provide precise answers to natural language questions (Hao et al., 2022a; İşlek et al., 2024), where QA systems aim to generate responses that resemble natural language for user queries (Çelik et al., 2024). Therefore, QA primarily addresses factoid questions, providing concise and accurate responses to fulfill users' information needs in real-world applications (Jurafsky & Martin, 2023). These systems range from providing simple yes/no responses to generating complex results synthesized from multiple data sources, through processes such as question analysis, answer retrieval, and ranking (Voorhees & Tice, 2000). Depending on the task definition and the available resources, question answering systems can vary significantly in their capabilities, spanning from basic fact-based answering to advanced systems that integrate and synthesize information from diverse sources (Hao et al., 2022a).

Many critical downstream tasks, such as QA and paraphrase identification, require an understanding of the relationship between two sentences (Katırcı & Çelik, 2025; Mollá & Vicedo, 2007; Yin & Schütze, 2015), which can be

effectively captured by encoding each sentence into a context-aware vector (Çelik et al., 2024; Kesavan et al., 2019). However, standard language models do not directly capture this relationship. This limitation becomes particularly evident in QA, where the system must not only extract and interpret relevant information from the given context (Nan et al., 2024), but also recognize how the question relates to the passage, often requiring the identification of a specific sub-phrase that directly addresses the query (Seo et al., 2017).

Recent advances in question answering (QA) systems have introduced a variety of approaches that integrate retrieval, reasoning, and multilingual capabilities. Table 1 summarizes prominent QA systems, including Bi-Directional Attention Flow (BiDAF) (Seo et al., 2017) employs bidirectional attention for extractive QA on SQuAD, while document Reader for Question Answering (DrQA) (Chen et al., 2017) combines document retrieval with a reader for open-domain QA. Dense Passage Retrieval (DPR) (Karpukhin et al., 2020) enhances performance through dense passage retrieval, and Retrieval-Parameterized Question Answering (RePAQ) (Lewis et al., 2021) focuses on efficient retrieval and answering with fewer parameters. XLM-R based QA system (XLMRQA) (Nguyen et al., 2022) extends QA to multilingual and Vietnamese Wikipedia contexts, whereas Open-domain Multi-modal Generative Question Answering (OMG-QA) (Nan et al., 2024) addresses reasoning across multi-modal and multi-document sources in open-domain settings.

Table 1: Prominent Question Answering Systems

Model	Developer	Features	Year
BiDAF	Univ. of Washington	Bidirectional attention flow, extractive QA on SQuAD	2017
DrQA	Facebook Research	Open-domain QA, retrieval + document reader	2017
DPR	Facebook AI	Dense passage retrieval, open-domain QA	2020
RePAQ	Facebook AI Research	Efficient retrieval + answering with few parameters (retrieval-augmented QA)	2021
XLMRQA	University of Information Technology, Vietnam	Open-domain QA on Vietnamese Wikipedia, multilingual knowledge source	2022
OMG-QA	Yale Üniversitesi, LinkedIn	Multi-modal, multi-document bağlamlarda akıl yürütme gerektiren open-domain QA	2024

3. Chatbot

The term “chatbot” combines “chat” and “robot” and refers to a computer program designed to simulate conversation with human users (Adamopoulou & Moussiades, 2020b; Hundertmark, 2020). Chatbots provide a text-based input and output interface, allowing users to interact with the underlying software and giving the impression of conversing with a real person. They process user requests using semantic patterns and keywords, matching them with backend databases to identify regularities and generate appropriate responses (Hundertmark, 2020). With advancements in natural language processing and machine learning, modern chatbots go beyond simple keyword matching and are capable of understanding context and generating more human-like responses (Çelik et al., 2024; Pandey & Sharma, 2023).

Chatbots are widely applied in various fields, including education, information retrieval, business, and e-commerce (Abu Shawar & Atwell, 2007). Their popularity stems from their ability to provide continuous and scalable support, making them especially valuable in global applications where customers may purchase products from different countries and expect assistance without being constrained by local time zones or language barriers (Hundertmark, 2020).

To better understand how these capabilities have evolved, it is helpful to trace the progression of chatbot technology from its early rule-based models to today’s advanced systems. Chatbot technology originated from early statistical models, such as the Markov chain. Introduced by Andrey Markov in 1906, the Markov chain was initially used to represent stochastic processes and was later applied to tasks like next-word prediction (Al-Amin et al., 2024). Building on these foundational ideas, the first conversational agents emerged in the 1960s, most notably ELIZA, a rule-based system developed at MIT that used simple pattern matching to simulate psychotherapy sessions without real comprehension (Abu Shawar & Atwell, 2007; Choudhary & Chauhan, 2023; Dongbo et al., 2023). Later systems, such as ALICE in the 1990s, built upon this rule-based approach and served as platforms for exploring human-computer interaction, while modern agents, such as Apple’s Siri, Google Assistant, and Amazon’s Alexa, ChatGPT and Google Bard, demonstrate advanced language understanding and generation capabilities (Al-Amin et al., 2024; Hao et al., 2022b; Jurafsky & Martin, 2023).

Table 2: Notable Conversational AI Systems

Model	Developer	Features	Year
Mitsuku	Pandorabots	Text-based conversational chatbot	2004
Sofia	Harvard University	Humanoid educational chatbot with problem-solving support	2004
Suzette / Rosette	Bruce Wilcox	Rule-based conversational chatbots	2010
XiaoIce	Microsoft	Social conversation-oriented chatbot	2019

Table 2 summarizes selected conversational AI systems, emphasizing their developers, main features, and year of release. Mitsuku (Choudhary & Chauhan, 2023; Higashinaka et al., 2014), developed by Pandorabots in 2005, is a text-based, award-winning chatbot. Suzette / Rosette (Al-Amin et al., 2024), developed by Bruce Wilcox in 2010 and 2011, are rule-based conversational chatbots. XiaoIce (Adamopoulou & Moussiades, 2020b; Jurafsky & Martin, 2023), developed by Microsoft (China), is a socially interactive, conversation-oriented chatbot. Sofia (Knill et al., 2004), developed by Harvard University in 2004, is a humanoid chatbot designed for educational purposes, capable of engaging users in conversation and supporting problem-solving tasks (Abu Shawar & Atwell, 2007; Knill et al., 2004).

Table 3: Hybrid QA and Conversational Agent Systems

Model	Developer	Features	Year
Eliza	Joseph Weizenbaum	Rule-based early conversational agent; basic QA and chat	1966
CALO	DARPA / SRI	Early intelligent assistant with QA capabilities	2003
IBM Watson	IBM	Capable of answering complex natural language questions; won <i>Jeopardy!</i>	2006
Siri	Apple	Voice-based assistant; provides QA and conversational functions	2011
Google Now	Google	Voice-enabled QA and response system; info based on time, location, and preferences	2012
Google Assistant	Google	Voice-enabled QA and conversational assistant	2016
Cortana	Microsoft	Windows-based assistant; QA and conversational features	2014
Alexa	Amazon	Voice assistant; integrates QA and task execution	2014
ChatGPT	OpenAI	LLM-based QA and conversational AI system	2018
Google Bard	Google	LLM-based QA and conversational system	2023
DeepSeek	DeepSeek AI (China)	LLM-based QA and conversational system	2024
Qwen 2.5	Alibaba	Multilingual LLM-based QA and conversational system	2024
Claude 3 Opus	Anthropic	Secure, long-context LLM QA and conversational system	2024

Table 3 summarizes notable milestones in conversational AI and QA systems development. This table presents selected hybrid conversational AI and QA models, highlighting their developers, key features, and year of release. Eliza is a rule-based early conversational agent providing basic QA and chat capabilities. CALO represents an early intelligent assistant with QA functionality (Al-Amin et al., 2024). IBM Watson (Adamopoulou & Moussiades, 2020b) is capable of answering complex natural language questions and gained fame by winning *Jeopardy!*. (Al-Amin et al., 2024) from Apple is a voice-based assistant offering both QA and conversational functions, followed by Google Now (Adamopoulou & Moussiades, 2020b)

was initially used to give information to the user taking into account the time of day, location, and preferences. Google Assistant constitutes the next generation of Google Now (Adamopoulou & Moussiades, 2020b). Microsoft’s Cortana provides Windows-based QA and conversational features. Amazon Alexa is a voice assistant integrated into devices for home automation and entertainment, making the Internet of Things (IoT) more accessible. It also supports the creation and publication of custom skills through the Alexa Skills Kit (ASK), while providing QA and task execution capabilities (Adamopoulou & Moussiades, 2020b). More recent models leverage large language models (LLMs): ChatGPT (Brown et al., 2020; Ioannidis et al., 2023a) and Google Bard (Al-Amin et al., 2024) provide both QA and conversational capabilities, DeepSeek (DeepSeek-AI et al., 2025a) and Qwen 2.5 (DeepSeek-AI et al., 2025b) offer multilingual LLM-based QA and chat, and Claude 3 Opus supports secure, long-context QA and conversational tasks (DeepSeek-AI et al., 2025b). These models collectively illustrate the evolution from rule-based agents to sophisticated LLM-powered hybrid systems capable of both answering questions and engaging in natural conversation.

4. Model Reliability and Generalization




Figure 1. Key challenges and mitigation strategies for reliable LLM training

Improving generalization (C. Zhang et al., 2021) is a central goal in machine learning, as models must perform reliably not only on training data but also on unseen samples (Liu et al., 2023). In this context, to address challenges such as overfitting and underfitting, various techniques have been developed, ranging from regularization methods to advanced training strategies. These techniques guide models toward capturing underlying patterns while avoiding excessive reliance on noise or dataset-specific artifacts (Ghojogh & Crowley, 2023a; Srivastava et al., 2014).

Figure 1 presents a taxonomy of the main challenges encountered in LLM training and the corresponding mitigation strategies. The taxonomy organizes training dynamics issues such as overfitting, underfitting, the bias–variance tradeoff, and hallucinations. It then links these challenges to methods including regularization, early stopping, RLHF and RAG. This classification provides a structured overview that highlights how addressing these challenges collectively contributes to building more reliable and robust conversational LLMs.

4.1. Training Dynamics

Understanding how machine learning models generalize is essential for building systems that are not only accurate but also reliable in real-world applications. The ultimate goal of any machine learning model is not merely to memorize the training data but to perform accurately on new, unseen data (Ying, 2019). However, the path to achieving optimal generalization is fraught with challenges. During training, models navigate a delicate balance; they must learn the underlying patterns in the data without becoming overly specialized to its idiosyncrasies and noise (Aliferis & Simon, 2024). This chapter explains the key concepts that underlie the training process. It addresses the fundamental challenges of underfitting and overfitting in model development, placing them within the theoretical framework of the bias–variance tradeoff. Additionally, it discusses early stopping, a practical technique that guides the training process toward models with stronger generalization capabilities.

4.1.1. Learning Challenges

LLM training faces several key learning challenges, including overfitting, underfitting, the bias–variance tradeoff, and hallucinations, which can affect model reliability and generalization. These challenges highlight the necessity of advanced training techniques, careful hyperparameter tuning, and domain-aware evaluation to ensure that LLMs achieve both accuracy and trustworthiness in real-world applications.

4.1.1.1. Overfitting

Overfitting is a fundamental issue in supervised machine learning that prevents a model from generalizing well to unseen data (Liu et al., 2023; Ying, 2019). This phenomenon occurs when model components are evaluated against an inappropriate reference distribution. In such cases, modeling algorithms tend to iteratively select the best among several candidate components and subsequently test whether this component should be incorporated into the model, which may lead to overfitting (Cohen & Jensen, 1997). Overfitting can be understood as the model learning “noise” in the data, meaning it captures idiosyncrasies of the training set that do not exist in the overall population. Machine learning and AI methods, as well as modeling systems or data science protocols, inherently have a propensity to overfit, particularly when model complexity is high relative to the amount of training data. As a result, the model may achieve low training error but fail to generalize to unseen data (Aliferis & Simon, 2024).

An overfitted model often achieves near-perfect performance on the training set but fails to adapt to variations in unseen data, leading to poor generalization. This occurs because the model captures dataset-specific noise and peculiarities instead of the true underlying patterns (Ghojogh & Crowley, 2023b). The primary causes of overfitting include excessive model complexity, limited training data, and insufficient use of regularization techniques. In such cases, models with far more parameters than necessary tend to memorize training examples rather than learning generalizable representations. To mitigate this issue, strategies such as early stopping, regularization, cross-validation, and dataset expansion can be applied, all of which encourage the model to focus on patterns that extend beyond the training set (Ying, 2019).

4.1.1.2. Underfitting

Underfitting is a fundamental limitation of model training that occurs when a learning algorithm lacks the capacity to capture the essential structure of the data. Consequently, underfitted models struggle to effectively learn data patterns, resulting in higher generalisation error and suboptimal utilisation of available data (Aliferis & Simon, 2024). A related concept is underestimation, whereby predictions consistently underestimate true values, often due to limited model complexity or inadequate training (Cunningham & Delany, 2021). Such underestimation can have practical implications in high-performance computing (HPC), where ignoring the discrepancy between predicted and actual job runtimes may complicate scheduling, prolong prediction or rescheduling processes, and lead to inefficient utilization of computational resources (Yao et al., 2021).

Closely related to underfitting, underestimation occurs when a model systematically predicts values lower than the true outcomes. It often results from limited model capacity and incomplete data coverage, which prevent the model from capturing the full data distribution, and can also be influenced by underfitting as well as underrepresented classes or features (Cunningham & Delany, 2021).

4.1.1.3. The Bias-Variance Tradeoff

Bias refers to a systematic tendency in machine learning models to produce errors that favor or disadvantage certain individuals or groups, leading to inequitable outcomes (Cunningham & Delany, 2021; Mavrogiorgos et al., 2024). Such biases can originate from the training data, due to factors like inadequate sampling, labeling errors, or historically embedded discriminatory patterns, or from human influence during algorithm design and data collection. Bias in machine learning is generally categorized into two main types: data bias, arising from imbalances, underrepresentation, or labeling errors in the training set, and algorithmic bias, which stems from the training process, algorithm design, or human influence, increasing the risk of erroneous or unfair decision-making in AI systems (Babaeianjelodar et al., 2020; Le et al., 2019).

Mitigating bias in machine learning requires interventions at both the data and algorithmic levels (Mikołajczyk-Bareła & Grochowski, 2023). From a data perspective, strategies such as ensuring diverse and representative datasets, resampling underrepresented classes, and careful data collection and labeling can help reduce systematic prejudice (Mavrogiorgos et al., 2024; Y. Zhang et al., 2024). Algorithmic approaches include incorporating fairness-aware learning objectives, applying regularization techniques to prevent the model from favoring specific groups, and using adversarial debiasing methods to minimize unintended correlations between protected attributes and predictions (Dip Bharatbhai Patel, 2023; Yang et al., 2023). Additionally, ongoing evaluation using fairness metrics and explainable AI techniques enables the identification and correction of residual biases, ensuring that model predictions remain equitable and reliable across different populations (Bateni et al., 2022).

4.1.2. Regularization Techniques

Regularization methods are techniques designed to prevent overfitting by constraining the capacity of machine learning models, encouraging them to capture underlying patterns rather than memorizing noise or idiosyncrasies in the training data (Kukačka et al., 2017). Common approaches include L1 and L2 weight penalties (Xu et al., 2010), dropout (Katırcı & Çelik, 2024; Srivastava et

al., 2014) and weight decay (Ghojogh & Crowley, 2023a), all of which have been shown to enhance generalization across various tasks and model architectures. Deep neural networks, with their multiple non-linear hidden layers, are highly expressive and capable of modeling complex input-output relationships. However, when training data is limited, some learned patterns may reflect sampling noise rather than true relationships, making regularization essential for mitigating overfitting and improving generalization (Srivastava et al., 2014).

4.1.2.1. L1 and L2 Regularization

Regularization is a fundamental technique in machine learning used to constrain model parameters, reducing overfitting and improving generalization. L0 regularization is the earliest approach for feature selection, promoting extreme sparsity (Kukačka et al., 2017). L1 regularization (Lasso) offers a computationally feasible alternative by applying a penalty proportional to the absolute values of the parameters, often driving many coefficients to zero and producing sparse models that naturally perform feature selection (Xu et al., 2010). In contrast, L2 regularization (Ridge) penalizes the squared values of the parameters, shrinking them toward smaller magnitudes without forcing exact zeros, which helps prevent overfitting while retaining all features in the model (Ghojogh & Crowley, 2023a; Katırcı & Çelik, 2024; Ng, 2004).

4.1.2.2. Dropout

In machine learning, various methods are employed to alleviate the challenges of overfitting and underfitting. Among these, dropout is commonly used as a regularization technique to reduce overfitting. However, when applied during the early stages of training, dropout can also contribute to mitigating underfitting by stabilizing the learning process and improving generalization (Katırcı & Çelik, 2024; Liu et al., 2023). Similarly, underestimation can be reduced by selectively filtering input data based on predefined conditions, ensuring that predictions are made only on sufficiently representative and reliable data. This approach limits the influence of sparse or low-quality data, which might otherwise cause systematic under-prediction, thereby enhancing the overall accuracy of the model's forecasts (Yao et al., 2021).

4.1.2.3. Weight decay

Weight decay is a widely used regularization technique in deep neural networks that penalizes large weights, helping to control model complexity and improve generalization (Xie et al., 2023). In non-linear activation functions

such as the hyperbolic tangent, very large positive or negative weights can place activations in highly non-linear regions, potentially leading to overfitting. By constraining the weights, weight decay maintains activations in a region that balances linearity and non-linearity, allowing the network to capture complex patterns without excessively fitting the training data. However, care must be taken, as weight decay can interact with large gradient norms in unexpected ways, affecting optimization dynamics. Therefore, monitoring training behavior and adjusting hyperparameters appropriately is essential to avoid unintended consequences while leveraging weight decay for improved generalization (Ghojogh & Crowley, 2023a).

4.1.2.4. Early Stopping

Early stopping is a regularization technique used in machine learning to prevent overfitting. It works by monitoring model performance on a validation set and halting training once the performance stops improving or begins to degrade, thereby avoiding excessive noise-learning and unnecessary training iterations (Ying, 2019). By frequently evaluating models during training, it has been empirically observed that worse-performing models can often be distinguished from better ones early in training, which motivates the use of early stopping strategies (Dodge et al., 2020). However, stopping the training too early can lead to underfitting, as the network may fail to fully learn from clean labels while still avoiding overfitting to noisy labels (Bai et al., 2021).

4.2. Hallucination Challenges in LLMs

Hallucination in Natural Language Generation (NLG) refers to the generation of content that is not faithful to the source input or contains information that is factually incorrect or fabricated (Bang et al., 2024). In other words, hallucinations occur when a model produces text that cannot be verified against the original data, introducing false or misleading information. This phenomenon undermines factuality and veracity, thereby significantly reducing the reliability of generated text (Lin et al., 2022).

4.2.1. Root Causes of Hallucination

Hallucinations in generative AI systems, including LLMs such as ChatGPT, primarily arise when models are trained on large-scale unsupervised corpora. In such settings, the models learn statistical patterns from vast and diverse datasets but may generate content that does not correspond to real-world

inputs, producing extrinsic statements that cannot be verified from the source. This phenomenon is influenced by the probabilistic and polysemous nature of language, which allows multiple plausible outputs for a given input, increasing the likelihood of nonfactual or misleading content (Alkaissi & McFarlane, 2023; Ioannidis et al., 2023b; Ji et al., 2023). While commonly viewed as a shortcoming, hallucinations can also be considered an emergent byproduct of language's inherent characteristics. Mitigating these issues requires rigorous training and evaluation procedures, supported by diverse and representative datasets, to enhance factual grounding and ensure reliable outputs (Widdows, Aboumradi, Kim, Ray, et al., 2024).

4.2.1.1. Data Limitations and Noise

Hallucinations can arise even when a model is trained on factually correct data, triggered by data limitations, complex learning processes, and the model's inference mechanisms. Such errors are more likely when the training data contains gaps, is insufficient, or lacks diversity (Kalai et al., 2025). These observations highlight that uncertainties and irregularities in the learning process—often amplified by noise—are key factors contributing to hallucinations. Techniques such as adaptive noise injection can mitigate these effects, reducing the likelihood of the model generating erroneous or unfounded outputs (Khadangi et al., 2025).

4.2.1.2. Architectural Limitations and Overconfidence

Large language models exhibit architectural limitations that restrict their ability to manage uncertainty and perform verification, increasing the likelihood of producing erroneous outputs. Combined with tendencies toward overconfidence, these structural constraints give rise to intrinsic hallucinations, causing the models to generate information with high certainty even when it is not factually grounded (Gumaan, 2025; Kalai et al., 2025).

4.2.1.3. Prompt Ambiguity and Context Limitations

Ambiguous or poorly specified prompts can lead LLMs to generate hallucinations, as the model attempts to fill in gaps with plausible but incorrect information. Hallucinations arise when a model's outputs are not grounded in the prompt or training data; therefore, the quality and specificity of the prompt directly affect the risk of Hallucination (Kalai et al., 2025; Tonmoy et al., 2024).

4.2.2. Mitigation Strategies for Reducing Hallucination

Mitigating hallucinations in large language models requires a multi-faceted approach, combining high-quality training data, factually augmented datasets, architectural enhancements for output verification, and access to external knowledge sources to ensure more accurate and reliable model outputs (Suzuoki & Hatano, 2024). Additionally, employing diverse and representative training datasets, rigorous evaluation procedures, and monitoring techniques such as human review or anomaly detection further reduces the likelihood of generating hallucinated content (Alkaissi & McFarlane, 2023).

4.2.2.1. Reinforcement Learning with Human Feedback (RLHF)

Among hallucination mitigation techniques in large language models, a variety of methods are employed, including ensemble approaches, retrieval-based strategies, advanced decoding and reasoning techniques, RLHF, prompt engineering, and post-processing or human-in-the-loop mechanisms. Ensemble methods (Suzuoki & Hatano, 2024) combine the outputs of multiple models to produce a consensus, reducing the likelihood of generating incorrect or fabricated content.

4.2.2.2. Retrieval-Augmented Generation (RAG)

Retrieval-Augmented Generation (RAG) (Widdows, Aboumradi, Kim, & Ray, 2024). RAG grounds outputs in external knowledge bases, ensuring factual support beyond the model's internal parameters. Additional approaches, such as improved decoding strategies like contrastive search, safety RLHF (Suzuoki & Hatano, 2024), parameter editing, and reasoning-based methods like Chain-of-Thought, also promote self-verification and alignment with human judgment (Ji et al., 2023).

4.2.2.3. Prompt Engineering and Optimization

Prompt engineering and pre-publication summary editing strengthen factual grounding, while post-processing and human-in-the-loop mechanisms provide final validation to ensure output accuracy (Ioannidis et al., 2023a). In addition, prompt tuning, which optimizes learned soft prompts and aligns them with task-specific contexts, helps mitigate hallucination risks by guiding the model to produce more accurate and contextually appropriate outputs (Tonmoy et al., 2024). Collectively, these strategies enhance the reliability and truthfulness of LLM-generated content in practical applications.

5. Conclusion

This study emphasizes that robust conversational AI requires balancing two critical aspects: optimizing training dynamics to address overfitting, underfitting, and the bias-variance trade-off, as well as directly combating hallucinations with advanced mitigation techniques. Progress in question-answering and chatbot systems depends on integrating reliable generalization strategies with effective hallucination control to ensure accuracy and adaptability.

Looking ahead, next-generation systems must enhance their contextual, emotional, and multimodal understanding to enable more natural and inclusive interactions. Supporting these capabilities will necessitate efficient, domain-specific architectures that address generalization challenges while incorporating anti-hallucination strategies tailored to specific domains. These efforts will pave the way for multilingual, culturally adaptive, and ethically aligned AI systems that are scalable, user-centric, and effective across global applications.

References

- Aasim, M., Katırcı, R., Acar, A. Ş., & Ali, S. A. (2024). A comparative and practical approach using quantum machine learning (QML) and support vector classifier (SVC) for Light emitting diodes mediated in vitro micropropagation of black mulberry (*Morus nigra* L.). *Industrial Crops and Products*, 213, 118397. <https://doi.org/10.1016/j.indcrop.2024.118397>
- Abu Shawar, B., & Atwell, E. (2007). Chatbots: Are they Really Useful? *Journal for Language Technology and Computational Linguistics*, 22(1), 29–49. <https://doi.org/10.21248/jlcl.22.2007.88>
- Adamopoulou, E., & Moussiades, L. (2020a). An Overview of Chatbot Technology. In *IFIP Advances in Information and Communication Technology: Vol. 584 IFIP* (Issue June). Springer International Publishing. https://doi.org/10.1007/978-3-030-49186-4_31
- Adamopoulou, E., & Moussiades, L. (2020b). Chatbots: History, technology, and applications. *Machine Learning with Applications*, 2, 100006. <https://doi.org/10.1016/J.MLWA.2020.100006>
- Al-Amin, M., Ali, M. S., Salam, A., Khan, A., Ali, A., Ullah, A., Alam, M. N., & Chowdhury, S. K. (2024). *History of generative Artificial Intelligence (AI) chatbots: past, present, and future development*. <http://arxiv.org/abs/2402.05122>
- Aliferis, C., & Simon, G. (2024). *Overfitting, Underfitting and General Model Overconfidence and Under-Performance Pitfalls and Best Practices in Machine Learning and AI*. https://doi.org/10.1007/978-3-031-39355-6_10

Alkaissi, H., & McFarlane, S. I. (2023). Artificial Hallucinations in ChatGPT: Implications in Scientific Writing. *Cureus*, 15(2), 2–5. <https://doi.org/10.7759/cureus.35179>

Babaeianjelodar, M., Lorenz, S., Gordon, J., Matthews, J., & Freitag, E. (2020). Quantifying Gender Bias in Different Corpora. *The Web Conference 2020 - Companion of the World Wide Web Conference, WWW 2020, September*, 752–759. <https://doi.org/10.1145/3366424.3383559>

Bai, Y., Yang, E., Han, B., Yang, Y., Li, J., Mao, Y., Niu, G., & Liu, T. (2021). Understanding and Improving Early Stopping for Learning with Noisy Labels. *Advances in Neural Information Processing Systems*, 29(NeurIPS), 24392–24403.

Bang, Y., Cahyawijaya, S., Lee, N., Dai, W., Su, D., Wilie, B., Lovenia, H., Ji, Z., Yu, T., Chung, W., Do, Q. V., Xu, Y., & Fung, P. (2024). *A Multitask, Multilingual, Multimodal Evaluation of ChatGPT on Reasoning, Hallucination, and Interactivity*. 675–718. <https://doi.org/10.18653/v1/2023.ijcnlp-main.45>

Banitz, B. (2020). Machine translation: A critical look at the performance of rule-based and statistical machine translation. *Cadernos de Tradução*, 40(1), 54–71. <https://doi.org/10.5007/2175-7968.2020v40n1p54>

Bateni, A., Chan, M. C., & Eitel-Porter, R. (2022). *AI Fairness: from Principles to Practice*. 1–21. <http://arxiv.org/abs/2207.09833>

Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., Agarwal, S., Herbert-Voss, A., Krueger, G., Henighan, T., Child, R., Ramesh, A., Ziegler, D. M., Wu, J., Winter, C., ... Amodei, D. (2020). Language models are few-shot learners. *Advances in Neural Information Processing Systems, 2020-Decem*.

Celik, H., & Cinar, A. (2021). An Application on Ensemble Learning Using KNIME. *2021 International Conference on Data Analytics for Business and Industry, ICDABI 2021, July*, 400–403. <https://doi.org/10.1109/ICDABI53623.2021.9655815>

Çelik, H., & Çınar, A. (2021). *Knime ile CRISP-DM Veri Bilimi Yöntemi Uygulaması*. May 2021, 1–6. <https://doi.org/10.52460/issc.2021.024>

Çelik, H., Katırcı, R., & İşlek, B. (2024). *Effect Of Parameters On Performance In Question-Answer Model With Simple Rnn Deep Learning Method*. May. https://scholar.google.com/citations?view_op=view_citation&hl=en&user=7b0QCpsAAAAJ&citation_for_view=7b0QCpsAAAAJ:WF5omc3nYNoC

Chen, D., Fisch, A., Weston, J., & Bordes, A. (2017). Reading Wikipedia to answer open-domain questions. *ACL 2017 - 55th Annual Meeting of the*

Association for Computational Linguistics, Proceedings of the Conference (Long Papers), 1, 1870–1879. <https://doi.org/10.18653/v1/P17-1171>

Choudhary, P., & Chauhan, S. (2023). An intelligent chatbot design and implementation model using long short-term memory with recurrent neural networks and attention mechanism. *Decision Analytics Journal*, 9(May), 100359. <https://doi.org/10.1016/j.dajour.2023.100359>

Çınar, A., & Çelik, H. (2022). *Regresyon Analizi Bitcoin Tahmin Uygulaması Geliştirme*. October, 1–6. https://scholar.google.com.tr/scholar?hl=tr&as_sdt=0%2C5&q=REGRESYON+ANALİZİ+BITCOİN+TAH-MİN+UYGULAMASI+GELİŞTİRME&btnG=

Cohen, P. R., & Jensen, D. (1997). Overfitting Explained. *Preliminary Papers of the Sixth International Workshop on Artificial Intelligence and Statistics*, 115–122.

Cunningham, P., & Delany, S. J. (2021). Underestimation Bias and Underfitting in Machine Learning. *Lecture Notes in Computer Science (Including Subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 12641 LNAI(18), 20–31. https://doi.org/10.1007/978-3-030-73959-1_2

DeepSeek-AI, Guo, D., Yang, D., Zhang, H., Song, J., Zhang, R., Xu, R., Zhu, Q., Ma, S., Wang, P., Bi, X., Zhang, X., Yu, X., Wu, Y., Wu, Z. F., Gou, Z., Shao, Z., Li, Z., Gao, Z., ... Zhang, Z. (2025a). *DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning*. 500, 1–22.

DeepSeek-AI, Guo, D., Yang, D., Zhang, H., Song, J., Zhang, R., Xu, R., Zhu, Q., Ma, S., Wang, P., Bi, X., Zhang, X., Yu, X., Wu, Y., Wu, Z. F., Gou, Z., Shao, Z., Li, Z., Gao, Z., ... Zhang, Z. (2025b). *DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning*. 500, 1–22. <http://arxiv.org/abs/2501.12948>

Dip Bharatbhai Patel. (2023). Ethical AI: Addressing Bias and Fairness in Machine Learning Models for Decision-making. *Journal of Computer Science and Technology Studies*, 3(1), 13–17. <https://doi.org/10.32996/jcsts.2021.3.1.3>

Dodge, J., Ilharco, G., Schwartz, R., Farhadi, A., Hajishirzi, H., & Smith, N. (2020). *Fine-Tuning Pretrained Language Models: Weight Initializations, Data Orders, and Early Stopping*. <http://arxiv.org/abs/2002.06305>

Dongbo, M., Miniaoui, S., Fen, L., Althubiti, S. A., & Alsenani, T. R. (2023). Intelligent chatbot interaction system capable for sentimental analysis using hybrid machine learning algorithms. *Information Processing and Management*, 60(5), 103440. <https://doi.org/10.1016/j.ipm.2023.103440>

Ghojogh, B., & Crowley, M. (2023a). *The Theory Behind Overfitting, Cross Validation, Regularization, Bagging, and Boosting: Tutorial*. 3.

Ghojogh, B., & Crowley, M. (2023b). *The Theory Behind Overfitting, Cross Validation, Regularization, Bagging, and Boosting: Tutorial*. 3. <http://arxiv.org/abs/1905.12787>

Gumaan, E. (2025). *Theoretical Foundations and Mitigation of Hallucination in Large Language Models*. <http://arxiv.org/abs/2507.22915>

Hao, T., Li, X., He, Y., Wang, F. L., & Qu, Y. (2022a). Recent progress in leveraging deep learning methods for question answering. *Neural Computing and Applications*, 34(4), 2765–2783. <https://doi.org/10.1007/s00521-021-06748-3>

Hao, T., Li, X., He, Y., Wang, F. L., & Qu, Y. (2022b). Recent progress in leveraging deep learning methods for question answering. *Neural Computing and Applications*, 34(4), 2765–2783. <https://doi.org/10.1007/s00521-021-06748-3>

Higashinaka, R., Imamura, K., Meguro, T., Miyazaki, C., Kobayashi, N., Sugiyama, H., Hirano, T., Makino, T., & Matsuo, Y. (2014). Towards an open-Domain conversational system fully based on natural language processing. *COLING 2014 - 25th International Conference on Computational Linguistics, Proceedings of COLING 2014: Technical Papers*, 928–939.

Hundertmark, D. Z. and S. (2020). Chatbots – An Interactive Technology for Personalized Communication, Transactions and Services. *IADIS International Journal on WWW/Internet*, 15(February 2018), 96–109.

Ioannidis, J., Harper, J., Quah, M. S., & Hunter, D. (2023a). Gracernote. ai: Legal Generative AI for Regulatory Compliance. *CEUR Workshop Proceedings*, 3423, 20–31. <https://doi.org/10.2139/ssrn.4494272>

Ioannidis, J., Harper, J., Quah, M. S., & Hunter, D. (2023b). *Gracernote . ai : Legal Generative AI for Regulatory Compliance*.

İşlek, B., Katırcı, R., & Celik, H. (2024). Enhancing Question Answering Systems Through Optimal Hyperparameter Tuning in GRU. *8th International Artificial Intelligence and Data Processing Symposium, IDAP 2024, September*. <https://doi.org/10.1109/IDAP64064.2024.10710732>

Ji, Z., Lee, N., Frieske, R., Yu, T., Su, D., Xu, Y., Ishii, E., Bang, Y. J., Madotto, A., & Fung, P. (2023). Survey of Hallucination in Natural Language Generation. *ACM Computing Surveys*, 55(12). <https://doi.org/10.1145/3571730>

Jurafsky, D., & Martin, J. H. (2023). Speech and Language Processing An Introduction to Natural Language Processing, Computational Linguistics, and Speech Recognition. In *The 1870 Ghost Dance*. <https://doi.org/10.2307/j.ctt1djmg7w.13>

Kalai, A. T., Nachum, O., Vempala, S. S., & Zhang, E. (2025). *Why Language Models Hallucinate*. 3(May), 1–36. <http://arxiv.org/abs/2509.04664>

Karpukhin, V., Oğuz, B., Min, S., Lewis, P., Wu, L., Edunov, S., Chen, D., & Yih, W. T. (2020). Dense passage retrieval for open-domain question answering. *EMNLP 2020 - 2020 Conference on Empirical Methods in Natural Language Processing, Proceedings of the Conference*, 6769–6781. <https://doi.org/10.18653/v1/2020.emnlp-main.550>

Katırcı, R., & Çelik, H. (2024). *Transformer Mimarisinde Dropout Oranlarının Performans Üzerindeki Etkisi*. December. https://www.researchgate.net/publication/387424078_TRANSFORMER_MIMARISINDE_DROPOUT_ORANLARININ_PERFORMANS_UZERINDEKI

Katırcı, R., & Çelik, H. (2025). Analyzing The Impact Of Language Pair And Dataset Size On Transformer Performance. *International Yıldırım Bayezid Scientific Research And Innovation Symposium-I, June*. https://scholar.google.com/citations?view_op=view_citation&hl=en&user=7b0QCpsAAAAJ&citation_for_view=7b0QCpsAAAAJ:UebtZR9Y70C&gmla=AH8HC4zDD0WZNY-4JvET_GFv1lIVISPoOhP-7iBXhz5ne6CeAlrTHaj491MHG_n3LSy1Gw6oM-O94H8jHEa9ZqxhPg7&sciund=9336085649281122449&gmla=AH

Katırcı, R., & Oğuz, T. (2023). Quantum Algorithms and Applications. *Productizing Quantum Computing, March*, 23–42. https://doi.org/10.1007/978-1-4842-9985-2_2

Kesavan, V., Muley, V., & Kolhekar, M. (2019). Deep Learning based Automatic Image Caption Generation. *2019 Global Conference for Advancement in Technology, GCAT 2019*, 1–6. <https://doi.org/10.1109/GCAT47503.2019.8978293>

Khadangi, A., Sartipi, A., Tchappi, I., & Bahmani, R. (2025). *Noise Augmented Fine Tuning for Mitigating Hallucinations in Large Language Models*. <http://arxiv.org/abs/2504.03302>

Knill, O., Carlsson, J., Chi, A., & Lezama, M. (2004). *An artificial intelligence experiment in college math education*. 9. <http://www.math.harvard.edu/~knill/preprints/sofia.pdf>

Kukačka, J., Golkov, V., & Cremers, D. (2017). *Regularization for Deep Learning: A Taxonomy*. 1–23. <http://arxiv.org/abs/1710.10686>

Le, M., Boureau, Y. L., & Nickel, M. (2019). Revisiting the evaluation of theory of mind through question answering. *EMNLP-IJCNLP 2019 - 2019 Conference on Empirical Methods in Natural Language Processing and 9th International Joint Conference on Natural Language Processing, Proceedings of the Conference*, 5872–5877. <https://doi.org/10.18653/v1/d19-1598>

Lewis, P., Wu, Y., Liu, L., Minervini, P., Küttler, H., Piktus, A., Stenetorp, P., & Riedel, S. (2021). Paq: 65 million probably-asked questions and what you can do with them. *Transactions of the Association for Computational Linguistics*, 9, 1098–1115. https://doi.org/10.1162/tacl_a_00415

Lin, S., Hilton, J., & Evans, O. (2022). TruthfulQA: Measuring How Models Mimic Human Falsehoods. *Proceedings of the Annual Meeting of the Association for Computational Linguistics*, 1, 3214–3252. <https://doi.org/10.18653/v1/2022.acl-long.229>

Liu, Z., Xu, Z., Jin, J., Shen, Z., & Darrell, T. (2023). Dropout Reduces Underfitting. *Proceedings of Machine Learning Research*, 202, 21715–21729.

Mavrogiorgos, K., Kiourtis, A., Mavrogiorgou, A., Menychtas, A., & Kyriazis, D. (2024). Bias in Machine Learning: A Literature Review. *Applied Sciences (Switzerland)*, 14(19). <https://doi.org/10.3390/app14198860>

Mikołajczyk-Bareła, A., & Grochowski, M. (2023). *A survey on bias in machine learning research*. <http://arxiv.org/abs/2308.11254>

Mollá, D., & Vicedo, J. L. (2007). Question answering in restricted domains: An overview. *Computational Linguistics*, 33(1), 41–61. <https://doi.org/10.1162/coli.2007.33.1.41>

Nan, L., Fang, W., Rasteh, A., Lahabi, P., Zou, W., Zhao, Y., & Cohan, A. (2024). OMG-QA: Building Open-Domain Multi-Modal Generative Question Answering Systems. *EMNLP 2024 - 2024 Conference on Empirical Methods in Natural Language Processing, Proceedings of the Industry Track*, 1001–1015. <https://doi.org/10.18653/v1/2024.emnlp-industry.75>

Ng, A. Y. (2004). L1 and L2 regularisation comparison. *Proceedings of the 21 St International Conference on Machine Learning*.

Nguyen, K. Van, Do, P. N. T., Nguyen, N. D., Huynh, T. Van, Nguyen, A. G. T., & Nguyen, N. L. T. (2022). XLMRQA: Open-Domain Question Answering on Vietnamese Wikipedia-Based Textual Knowledge Source. *Lecture Notes in Computer Science (Including Subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 13757 LNAI, 377–389. https://doi.org/10.1007/978-3-031-21743-2_30

Pandey, S., & Sharma, S. (2023). A comparative study of retrieval-based and generative-based chatbots using Deep Learning and Machine Learning. *Healthcare Analytics*, 3(April). <https://doi.org/10.1016/j.health.2023.100198>

Seo, M., Kembhavi, A., Farhadi, A., & Hajishirzi, H. (2017). Bi-Directional Attention Flow for Machine Comprehension. *5th International Conference on Learning Representations, ICLR 2017 - Conference Track Proceedings*, 1–13.

Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I., & Salakhutdinov, R. (2014). Dropout: A simple way to prevent neural networks from overfitting. *Journal of Machine Learning Research*, 15, 1929–1958.

Suzuoki, S., & Hatano, K. (2024). *Reducing Hallucinations in Large Language Models: A Consensus Voting Approach Using Mixture of Experts*. 1–7. <https://www.authorea.com/doi/pdf/10.36227/techrxiv.171925057.75949684>

Tonmoy, S. M. T. I., Zaman, S. M. M., Jain, V., Rani, A., Rawte, V., Chadha, A., & Das, A. (2024). *A Comprehensive Survey of Hallucination Mitigation Techniques in Large Language Models*. <http://arxiv.org/abs/2401.01313>

Tuncer, S. A., Çınar, A., Erkuş, M., & Tuncer, T. (2024). Deep Multi-Modal Fusion Model for Identification of Eight Different Particles in Urinary Sediment. *Applied Computer Systems*, 29(1), 35–44. <https://doi.org/10.2478/acss-2024-0005>

Voorhees, E. M., & Tice, D. M. (2000). Building a question answering test collection. *SIGIR Forum (ACM Special Interest Group on Information Retrieval)*, 200–207. <https://doi.org/10.1145/345508.345577>

Widdows, D., Aboumrar, W., Kim, D., & Ray, S. (2024). *Natural Language, AI, and Quantum Computing in 2024*.

Widdows, D., Aboumrar, W., Kim, D., Ray, S., & Mei, J. (2024). *Quantum Natural Language Processing*. <http://arxiv.org/abs/2403.19758>

Winston, P. H. (2017). On Computing Machinery and Intelligence. *Boston Studies in the Philosophy and History of Science*, 324, 265–278. https://doi.org/10.1007/978-3-319-53280-6_11

Xie, Z., Xu, Z., Zhang, J., Sato, I., & Sugiyama, M. (2023). On the Overlooked Pitfalls of Weight Decay and How to Mitigate Them: A Gradient-Norm Perspective. *Advances in Neural Information Processing Systems*, 36(NeurIPS), 1–21.

Xu, Z. Ben, Zhang, H., Wang, Y., Chang, X. Y., & Liang, Y. (2010). L1/2 regularization. *Science in China, Series F: Information Sciences*, 53(6), 1159–1169. <https://doi.org/10.1007/s11432-010-0090-0>

Yang, J., Soltan, A. A. S., Eyre, D. W., Yang, Y., & Clifton, D. A. (2023). An adversarial training framework for mitigating algorithmic biases in clinical machine learning. *Npj Digital Medicine*, 6(1), 1–10. <https://doi.org/10.1038/s41746-023-00805-y>

Yao, J., Xiao, Y., You, P., & Sun, G. (2021). Lecture Notes in Electrical Engineering. In *Lecture Notes in Electrical Engineering* (Vol. 813, Issue Icivis).

Yin, W., & Schütze, H. (2015). Convolutional neural network for paraphrase identification. *NAACL HLT 2015 - 2015 Conference of the North*

American Chapter of the Association for Computational Linguistics: Human Language Technologies, Proceedings of the Conference, 901–911. <https://doi.org/10.3115/v1/n15-1091>

Ying, X. (2019). An Overview of Overfitting and its Solutions. *Journal of Physics: Conference Series*, 1168(2). <https://doi.org/10.1088/1742-6596/1168/2/022022>

Zhang, C., Bengio, S., Hardt, M., Recht, B., & Vinyals, O. (2021). Understanding deep learning (still) requires rethinking generalization. *Communications of the ACM*, 64(3), 107–115. <https://doi.org/10.1145/3446776>

Zhang, R., Gao, L., Zheng, C., Fan, Z., Lai, G., Zhang, Z., Ai, F., Yang, Y., & Yang, H. (2023). *A Self-enhancement Approach for Domain-specific Chatbot Training via Knowledge Mining and Digest*. <http://arxiv.org/abs/2311.10614>

Zhang, Y., Li, B., Ling, Z., & Zhou, F. (2024). Mitigating Label Bias in Machine Learning: Fairness through Confident Learning. *Proceedings of the AAAI Conference on Artificial Intelligence*, 38(15), 16917–16925. <https://doi.org/10.1609/aaai.v38i15.29634>

CHAPTER IV

SOFTWARE DEVELOPMENT SUPPORTED BY GENERATIVE ARTIFICIAL INTELLIGENCE

Hakan KEKÜL

*(Dr.), Sivas Cumhuriyet University,
Faculty of Engineering,
Department of Software Engineering,
Sivas, Türkiye
E-mail: hakankekul@cumhuriyet.edu.tr
ORCID: 0000-0001-6269-8713*

1. Introduction

The most recent advances in artificial intelligence have begun to redefine software development processes considerably. In particular, generative artificial intelligence (GenAI) models extend their ability in creating human-like text to the programming domain and thereby assist developers with automatic code generation, debugging, test case creation, and code documentation. Large language models (LLMs) with billions of parameters are trained on vast corpora of text and code collected from the web. Therefore, they are able to analyze natural language requests and produce executable code automatically. While this promises tremendous gains in productivity for software development activity, it introduces new challenges and fuels ongoing debates (Bakal et al., 2025; Peng et al., 2023).

In this chapter, we provide a detailed discussion of the use of generative artificial intelligence for software engineering. Technical aspects of applications such as code generation and completion are analyzed, while academic research results are used to discuss its impact on productivity, code quality, and security. Besides that, ethical, along with legal, issues are discussed, and future-looking directions along with promising avenues for further research are provided.

2. The Historical Development from Rule-Based Systems to Generative AI

The foundations of code generation and automatic code completion in software development date back several decades. For instance, the earliest manifestations of the idea of intelligent code completion can be traced to the simple spell checkers and command-line auto-completion tools of the 1950s (*The Past, Present and Future of AI Coding Tools* | *TechTarget*, n.d.). The first code completion feature integrated into a modern programming environment emerged in the 1990s. In 1996, Microsoft introduced IntelliSense into the Visual Basic IDE, a pioneering tool that provided developers with real-time suggestions while writing code (*Code Completion - Wikipedia*, n.d.). When IntelliSense became widespread in Visual Studio in 2001, it wasn't artificial intelligence but employed static analysis and type inference. By presenting context-sensitive suggestions such as list of methods and variables or parameter hints based on the classes or objects a developer was writing, it accelerated coding and reduced errors. Similarly, add-ins such as JetBrains ReSharper and Visual Assist provided similar code completion indulgences in early 2000s (*From vi to AI: The Incredible Evolution of Coding Tools*, n.d.). These early tools operated on rule-based approaches (e.g., syntactic rules, type checks, and trigger characters) and, although they enhanced developer productivity, their suggestions could not extend beyond predefined rules.

Since the 2010s, advances in machine learning and natural language processing have laid the groundwork for a paradigm shift in code completion systems. The transition accelerated from rule-based and symbolic systems to data-driven and learning-based systems. In 2018, Microsoft introduced Visual Studio IntelliCode, which employed machine learning to intelligently rank code completion suggestions. IntelliCode analyzed thousands of projects on GitHub to learn which APIs or methods were more likely to be used, and provided suggestions accordingly (*Code Completion - Wikipedia*, n.d.). In 2019, there were tools like Tabnine (previously Codota); Tabnine was among the very first extensively used systems to offer automatic code completion in many programming languages with a deep learning-based model. This tool was able to complete full lines or functions based on patterns of code seen earlier. Lastly, there was the Codex model created by OpenAI introduced in 2021 as the GitHub Copilot engine, released as a Visual Studio Code extension (*AI Copilot Tools for Developers - Overview & Comparison of Tools* | *Zartis*, n.d.). Copilot gained high profile when it came into being as an auto-code suggestion

system operated by a big language model—a descendant of GPT-3—tuned into billions of lines of publicly shared code from GitHub repositories. It was found to be able to coexist with almost any programming language and framework. Similarly, Amazon introduced CodeWhisperer in 2022 that also provided auto-code suggestions in virtually every programming language (*The Past, Present and Future of AI Coding Tools* | *TechTarget*, n.d.). Thus, code completion has evolved from simple rule-based suggestions into a system capable of generating entirely new lines of code, drawing on the learned knowledge of generative AI models (*ML-Enhanced Code Completion Improves Developer Productivity*, n.d.). In traditional systems, suggestions were constrained by the compiler or the rules of the programming language; today, however, models trained on massive datasets provide recommendations that are far more flexible and powerful.

Today, the most successful approach to code generation and completion relies on large language models (LLMs) built upon the Transformer architecture (*ML-Enhanced Code Completion Improves Developer Productivity*, n.d.). Transformer models acquire long-range dependencies among tokens within a sequence from the self-attention mechanism. It enables them to learn distant variable references, block structures, or call relationships even in structured and context-sensitive data such as source code. Generative models are first pre-trained on huge text corpora and then fine-tuned on code-related data so that they can learn the grammar and patterns of programming languages. For example, the OpenAI Codex model was developed by further training the GPT model initially trained on general text on gigantic amounts of publicly available code aggregated from GitHub repositories. As a result, Codex has learned to code in programming languages such as Python, JavaScript, and Go (Chen et al., 2021). These Transformer-based models process code by segmenting it into smaller units such as subword tokens in the same way natural language is handled, and function as language models that predict the next token. As input, they typically consider the code context surrounding the cursor, often spanning ~1,000 or more tokens, and generate one or several lines of completion suggestions as output. During this process, techniques such as beam search are employed in the background to explore multiple possible continuations, from which the most probable candidates are presented to the developer (*ML-Enhanced Code Completion Improves Developer Productivity*, n.d.).

Generative code-specialized models have a lot to offer over general-purpose language models. When trained and fine-tuned from a similarly sized model only on programming data, it performs reliably better on code generation

tasks than its general-purpose version. Recent studies have shown that code-specific models (such as Codex, CodeLlama, and AlphaCode) are much better than the same-sized general models because of their ability to learn programming syntax, structural components, and recurring patterns of library use (Husein et al., 2025). This advantage comes from the point that code-specific models have the ability to learn syntactic rules, programming language structure properties, and typical usage patterns of libraries. For instance, a model dedicated to Python can learn indentation rules or typical usage patterns of particular libraries and therefore produce more accurate completions. Thanks to the Transformer model, this type of model can contextually “remember” how a variable defined early in a function is used several hundred lines later. This is actually the same strategy that human programmers rely on when they consider code.

3. Principles of Generative Code Production Across Different Programming Languages

Although generative AI models are language-agnostic in implementation, they operate on the same principles when generating code for any programming language. In essence, across all languages, the model’s objective is to produce the most probable continuation of the code based on context surrounding it—variable names, declared functions, comments, and syntactic styles of the language. Large models are capable of learning numerous programming languages under one model. For example, Google’s in-house research into code completion revealed that training a single Transformer model on eight languages (C++, Java, Python, Go, TypeScript, Kotlin, Dart, and Proto) gave decent suggestions across all of them without requiring separate models for each language (*ML-Enhanced Code Completion Improves Developer Productivity*, n.d.). This is due to the fact that many programming languages share a set of common features: all of them incorporate similar concepts such as control structures, function calls, and variable assignments.

But the performance of these models would vary across programming languages. This is largely due to the quality and availability of training data for each language. For widely used languages such as Python, Java, and JavaScript, the vast volume of open-source code on the internet exposes the models to good examples, thereby improving their performance. On the other hand, for less popular or less readable languages (e.g., Perl), models are more perplexed, indicating more difficulty making accurate predictions. Indeed, it has been found that while Perl perplexity values were high consistently, those for Java, with its

more controlled syntax, were comparatively lower (Husein et al., 2025). This is in line with the characterization of languages such as Perl as “write-only” (easy to write, difficult to read). On statically type-checked and syntactically strict languages such as C# and Java, models have more accurate predictions than for dynamic languages, since the type information limits the universe of possible completions and hence model uncertainty is lower. Conversely, in dynamic languages such as Python or JavaScript, model proposals must necessarily be more flexible. But modern generative code models are language-agnostic, and with a good quantity of training data, they can generate fair outputs for different programming languages.

4. Training Data, Context Analysis, and Suggestion Strategies in Code Completion Systems

Training data plays a critical role in the success of generative code models. These models are typically trained on billions of lines of code collected from large-scale open-source repositories, such as those hosted on GitHub (*AI Copilot Tools for Developers - Overview & Comparison of Tools* | Zartis, n.d.). This data consists of a huge number of programming languages, the use of various libraries, and an endless variety of coding patterns. Unfiltered code data is not clean or free of bugs; during training, models may also learn from buggy examples in the corpus. Filtering mechanisms such as skipping code that cannot compile or fail tests are therefore employed by some advanced systems to improve the quality of training data.

With code completion, context is the most critical input to the system. A highly advanced completion engine takes into account the previous file lines the cursor is in, function and class declarations, and, where possible, relevant declarations in other files in the project. For example, programs like Copilot will typically provide the model with a window of about hundreds to thousands of tokens around the cursor position as input, and then request the model to generate most likely the rest of the code. Here, the model considers what identifiers have been defined, what a method is intended to do (inferred from comments or its name), and what libraries are imported, in an effort to give a pertinent suggestion. With further development of context analysis, the suggestions also become better, since the model gets more cognizant of “where it is” and “what is possible.” Some systems extend the language model by incorporating abstract syntax trees (ASTs) or symbol tables. For instance, Google’s hybrid code completion by Google utilized a traditional compiler-based semantic engine combined with a

Transformer model: while usual one-token completions and ML-based longer completions were calculated in parallel, the compiler ensured correctness of the ML completions and eliminated incorrect completions (e.g., syntax errors or type mismatches) prior to presenting them to the user (*ML-Enhanced Code Completion Improves Developer Productivity*, n.d.). In terms of suggestion strategies, some tools present multiple options at once (e.g., displaying several completion candidates in the IDE interface). In such cases, the model generates the top-ranked suggestions according to probability. While evaluations often show that the first suggestion is most frequently accepted, the second or third alternatives may sometimes better match the developer's intent, which is why they are also presented to the user. Another modern strategy involves generating multi-line completions or even entire functions. For example, when a comment line states, "This function sorts the array," the model can produce not only several lines of code but, in some cases, the complete function body in a single step (*From vi to AI: The Incredible Evolution of Coding Tools*, n.d.). In such cases, the model emits a long sequence of tokens in a single step and presents it to the developer for review and approval.

In essence, code completion systems attempt to comprehend the present context as accurately as they can and replicate code written in similar contexts they have learned earlier. In the process, they can also integrate compilers or syntax checkers to produce results that are more dependable. Lastly, training data diversity and quality, context window width, and ranking and filtering policies for the suggestions are the key factors determining the success of such systems.

5. Advantages and Limitations of Generative AI in Code Generation

The integration of generative AI models into software development processes provides significant advantages:

Speed and Productivity: Code completion tools greatly accelerate routine coding tasks. Both academic studies and industrial experiments demonstrate that AI-assisted programming enables developers to complete specific tasks significantly faster. For instance, in one experiment, a group of developers using GitHub Copilot completed a designated programming task 55% faster compared to the group working without such assistance (Peng et al., 2023). Similarly, in internal measurements, Google reported that the use of single-line ML-based code completions reduced the time spent between compilation and testing cycles by approximately 6% (*ML-Enhanced Code Completion Improves Developer Productivity*, n.d.). Overall, AI assistants help developers use their time more efficiently by rapidly suggesting repetitive and tedious code fragments.

Fewer Errors and Higher Quality: Intelligent suggestion systems help reduce syntax errors and minor programming mistakes by providing structurally correct and compilable code snippets. With the introduction of tools such as IntelliSense, reductions in typographical errors and improvements in code quality have been observed, leading to more consistent and reliable code (*From vi to AI: The Incredible Evolution of Coding Tools*, n.d.). Generative models go one step further by, for instance, learning appropriate usage patterns of an API and suggesting them in turn. Therefore, even a newbie developer can be made to utilize the library pertaining to it in the most correct manner. This aspect avoids errors even at the coding stage, prior to when they happen in later stages of development.

Instant Knowledge Access: Because AI-based tools are founded on vast knowledge bases, they enable developers to learn how to do something without referencing the manual. For example, if a developer wants to sort a list in Python, the assistant will infer the purpose and trigger typical usage patterns. The developer can receive the desired code without switching context by reducing the need for frequent web searching or reference looks-up (*ML-Enhanced Code Completion Improves Developer Productivity*, n.d.). This phenomenon creates an embedded documentation effect within the code, meaning that generative tools effectively act as a kind of knowledge assistant.

Creativity and Focus on Complex Tasks: Generation of dull and repetitive code by AI systems releases the cognitive space of programmers to engage in more imaginative activities. An example is where AI does the mundane job of extracting data from a web form and placing it within a model, the programmer can then focus on coding the business logic or enhancing performance. This division of labor enables the programmers to devote more time to problem-solving on a higher level and system design, thus more development efficiency and innovation (*From vi to AI: The Incredible Evolution of Coding Tools*, n.d.). In some cases, a generative model may suggest an unconventional solution or an alternative code fragment, which can provide developers with a different perspective on the problem at hand.

Alongside these advantages, the limitations and risks associated with code generation through generative AI should not be overlooked:

Misleading or Erroneous Clues: The code generated by an AI model can be syntactically correct but semantically wrong. Since the model is probabilistic prediction-based, the code indicated by the model is not always the most accurate solution to a problem. For example, it may give a solution that doesn't consider an edge case, or it may even invoke functions that don't exist—a scenario known

as hallucination. This is why code produced by AI should always be inspected by a developer; in fact, the makers of generative AI systems specifically state that this kind of code should not be executed without human observation and verification (*Introducing Codex* | *OpenAI*, n.d.).

Overreliance and Loss of Understanding: When developers place excessive trust in AI tools, they may gradually risk losing their ability to understand fine-grained details of the code or to solve problems independently. An academic study notes that developers who work continuously with AI sometimes perceive the tool as a black box, occasionally accepting the suggested code without fully internalizing why it works. Over the long term, this can create a form of cognitive debt, in which the developer becomes increasingly dependent on the system's generated code and gradually loses mastery over their own work (Husein et al., 2025). Moreover, the code suggested by AI is not always the most minimal or maintainable solution; it may occasionally produce excessive or unnecessarily complex code a phenomenon often referred to as code bloat. Therefore, while AI contributes to faster development, it also imposes on developers the responsibility to refine and fully understand the generated code.

Data Privacy and Licensing Concerns: Since generative models are trained using publicly available data, the proposed code by them will sometimes have snippets that raise concerns regarding copyright or licensing. For example, Copilot has found itself surrounded by controversy in some cases, where it was viewed to propose code very similar to parts that were under the GNU GPL license. This issue comes from the nature of training data and is indicative of potential risks in terms of license compliance for ongoing projects. Similarly, confidentiality in sensitive or proprietary code is a matter of concern too. In such cases, it is all the more important to construct models which have never seen such data, or to deploy on-prem solutions (such as the on-prem version of Tabnine) to shield against such risks (*AI Copilot Tools for Developers - Overview & Comparison of Tools* | *Zartis*, n.d.)

Performance and Resource Intensity: As massive language models possess hundreds of millions or even billions of parameters, offering real-time code completion service could be very intensive in terms of computational resource and memory. Cloud-based products are network-dependent and impose latency, while on-premises products demand top-tier hardware resources. Moreover, very large models can take the entire project context into account, but it is expensive to process such a large input each time. Therefore, a balance between response latency and model capacity is typically unavoidable in practice. As a

case in point, Google stated that a model of approximately 0.5 billion parameters is an appropriate compromise between low latency and sufficient accuracy (*ML-Enhanced Code Completion Improves Developer Productivity*, n.d.).

Responsibility and Debugging: If an error in coding has been produced by AI, it may be difficult for coders to understand why code has been produced in a specific manner since its logic is built on the internal reasoning of the model. While a coder may usually trace code logic that he himself has created to debug errors, AI-generated code may contain uncertain or unstable traces, and therefore fault diagnosis becomes more difficult. In such circumstances, the developer will have to manually repair the error or even recode completely. So, while production is accelerated through AI software, developers are not exempted but have the responsibility of verifying, authenticating, and correcting the generated code squarely on their shoulders.

6. Academic Studies, Case Analyses, and Evaluation Metrics

In recent years, numerous academic studies have been conducted and various industrial case analyses reported to evaluate and compare the success of generative code models. A 2021 study on OpenAI's Codex model demonstrated remarkable progress in generating correct, executable code from natural language problem statements. In this study, Codex was evaluated on a benchmark called HumanEval, where it successfully solved 28.8% of the given Python programming problems. For comparison, the general-purpose GPT-3 model of similar size achieved 0% accuracy on the same benchmark, while GPT-J, one of Codex's predecessors, achieved only 11.4%. Furthermore, researchers found that employing a multiplicity strategy, in which the model generated multiple candidate solutions for each problem, significantly increased success rates: when 100 different code samples were produced and tested for each problem, the solution rate rose to approximately 70% (Chen et al., 2021). These findings indicate that while large code models may not always deliver the correct solution on the first attempt, the probability of arriving at the right answer becomes very high when sufficient trials are generated.

DeepMind's AlphaCode program created a lot of buzz for generative model testing in coding competitions. In a 2022 paper, AlphaCode was reported to produce solutions from unseen programming problems that put it at the top 54% of participants in online coding competitions. This milestone indicates that AlphaCode had reached parity with the average human in the activity of competitive programming. To achieve this, AlphaCode employed a fully

Transformer-based model language, which was trained on millions of lines of GitHub code before fine-tuning on the relatively small set of competition problems. When performing tasks, AlphaCode generated tens of thousands of candidate solutions, which were then automatically tested and filtered. Lastly, the system selected the top 10 promising solutions to submit, more or less mimicking the human trial-and-error process in an effort to achieve success (*Competitive Programming with AlphaCode - Google DeepMind*, n.d.). This approach is significant in that it demonstrates generative models' potential not only for line-by-line code completion but also for achieving a degree of independent problem-solving capability.

On the academic side, a variety of metrics have been developed to evaluate generative code models. In code generation, both text-based similarity measures and functional correctness measures are applied in combination:

BLEU (BiLingual Evaluation Understudy): Originally developed to evaluate the similarity of machine translation outputs against reference sentences, the BLEU score was also widely adopted for a long time in the evaluation of code generation (Evtikhiev et al., 2017). Based on n-gram similarity between the generated code and the expected reference code, the BLEU metric yields a numerical score. However, such match-based metrics are known to be limited when applied to code, since multiple syntactically different implementations may accomplish the same functionality, resulting in low surface-level similarity despite semantic equivalence (*A Dive into How Pass@k Is Calculated for Evaluation of LLM's Coding* | by Yanan Chen | *Medium*, n.d.). Therefore, BLEU alone cannot be considered a reliable metric for evaluating the success of code generation.

CodeBLEU: This metric was proposed in response to the recognition that BLEU alone may be insufficient for code evaluation. CodeBLEU is calculated as a composite of several sub-criteria: syntactic similarity (e.g., comparison of Abstract Syntax Trees, ASTs), semantic similarity (e.g., analysis of program data-flow graphs), and surface-level textual similarity (Evtikhiev et al., 2017). In this way, the metric provides a richer assessment, capturing not only the literal similarity of the generated code to the reference solution but also its functional closeness.

Test-based evaluation (Pass@k): In recent years, the most important evaluation method has been to determine whether the generated code actually executes correctly by subjecting it to testing (Chen et al., 2021; Evtikhiev et al., 2017). The pass@k metric evaluates performance by checking whether,

after generating up to k candidate solutions for a problem, at least one of them successfully passes the test cases (*A Dive into How Pass@k Is Calculated for Evaluation of LLM's Coding* | by Yanan Chen | Medium, n.d.). For example, $\text{pass}@1$ represents the probability that the model produces a correct solution on its first attempt, while $\text{pass}@10$ measures the likelihood that at least one correct solution emerges when the model is allowed to generate ten different attempts. This metric has gained popularity through test-based benchmarks such as OpenAI's HumanEval, where it has become a standard for evaluating the functional accuracy of code generation models (Evtikhiev et al., 2017). When calculating $\text{pass}@k$, a statistical formula is applied to fairly estimate the likelihood of obtaining at least one correct solution by chance, depending on the trial in which the correct output appears. This ensures that the metric reflects the probabilistic distribution of correct solutions across multiple attempts, rather than relying on raw counts alone (*A Dive into How Pass@k Is Calculated for Evaluation of LLM's Coding* | by Yanan Chen | Medium, n.d.). This method is highly valuable because it provides a more accurate reflection of the real-world performance of code generation models specifically, the likelihood that a developer can solve a problem after making several attempts.

Other than these, other metrics such as ROUGE-L, METEOR, and Levenshtein distance have been studied for evaluation purposes. The general consensus is that functional correctness is the ultimate measure of performance in code generation. Thus, in recent studies, metrics such as executability and unit test passing rate have appeared as the major comparison metrics for newer models (Evtikhiev et al., 2017).

From an industrial perspective, the adoption of AI-assisted coding tools has been increasing rapidly. According to GitHub's own data, developers using the Copilot extension rely heavily on its suggestions while writing code, and in some companies, it has been reported that 30–40% of newly added code characters are generated through AI recommendations (Dohmke et al., 2023; *Octoverse: The State of Open Source and Rise of AI in 2023 - The GitHub Blog*, n.d.). Google has reported that, within its internal development environment, the integration of an ML-based code completion system resulted in approximately 3% of newly added code characters being generated through automated suggestions (*ML-Enhanced Code Completion Improves Developer Productivity*, n.d.). This percentage has been observed to increase over the years, indicating that AI tools are gradually becoming the standard in software development teams. Another case study highlights that AI-powered tools particularly help beginner developers

lower their learning curve. To illustrate, interns or junior personnel employing Copilot were observed to develop a project faster on a specific task than their peers without the tool, as well as less frequently consulting external sources such as Stack Overflow (*Unleash Developer Productivity with Generative AI | McKinsey*, n.d.). Nevertheless, some companies restrict the use of AI in sensitive projects or establish internally trained custom models, since the privacy and security risks associated with open models have not yet been fully resolved.

7. Comparison of Human-Driven and AI-Assisted Code Generation

There are clear differences between the AI-driven and the conventional human-based code generation method. In the conventional software development process, a programmer analyzes the problem, plans the solution mentally or on paper, and then hand-codes it from scratch. The human maintains full control and creativity; error checking, syntax validity, and determining the optimum solutions are all dependent on the developer's expertise level. In contrast, in AI-assisted development, the AI and the programmer virtually collaborate. The human developer describes the problem and expresses what is to be accomplished (e.g., by adding a comment line or choosing a descriptive function name), and the AI generates a code snippet in line with this intent. The proposal is then reviewed by the developer, refining or rejecting it as needed. This loop is quite similar to a form of pair programming, with the AI partner taking care of performing the routine tasks and the human programmer retaining the final responsibility for making decisions.

This fusion optimizes AI capabilities for handling repetitive and trivial code generation but not holding control in the hands of human developers for processes that require innovative problem-solving and analytical evaluation. For example, in a web application, the AI can create boilerplate functions such as form validation with ease, but it's up to the human developer to create application-specific business logic and adjust the user interface. The strongest aspect of the AI is recycling patterns it has experienced a thousand times before, while the human being's strongest point is in perceiving radically new things never seen before. Therefore, in the real world, the best approach is a synergistic mix in which humans and AI complementarily fill out each other's loopholes.

Recent research has demonstrated that coding with AI assistance clearly results in significant time savings, while also emphasizing the risks of relying entirely on AI. For instance, even experienced developers using Copilot have reported that they occasionally struggle to fully understand the generated code, or that during debugging they sometimes feel the need to disable the tool and

continue with more traditional methods (Husein et al., 2025; Peng et al., 2023). Such feedback highlights the need for developers to use AI consciously in order to achieve optimal effectiveness. Human judgment should never be removed from the process; on the contrary, each suggestion must be examined with a critical perspective, and the ultimate responsibility for the code should remain with the developer (*Introducing Codex* | *OpenAI*, n.d.).

Another significant variation between human-written and AI-supported code development lies in the area of learning and gaining experience. When employing the conventional approach, a developer tries to debug issues and, in the process, gains knowledge and experience. When AI is involved, though, solutions exist prior to that, which deprives the developer of the opportunity to learn. To balance this, other experts suggest employing AI tools as a “teacher”: not only to obtain the code, but to understand why that suggested code. Through being actively involved in questioning the model for justifications as and when required and thinking through the rationale behind ideas developers can work on and develop their own understanding.

8. Conclusion

In summary, code generation powered by AI marks the dawn of a new age in software development. In this age, there is increased productivity by virtue of using assistants who effectively carry out tedious and monotonous work (Husein et al., 2025). However, this does not imply the demise of the human developer. On the other hand, it generates new positions and areas of employment such as reading what AI produces and concentrating on more cerebral tasks involving creativity. If properly used, the human-AI collaboration may escalate the pace as well as the quality of software development processes. Consequently, the idea of the “AI pair programmer” is gaining traction, with teams increasingly exploring how best to realize most productive balance in this collaboration.

References

A dive into how pass@k is calculated for evaluation of LLM's coding | by Yanan Chen | *Medium*. (n.d.). Retrieved September 17, 2025, from <https://medium.com/@yananchen1116/a-dive-into-how-pass-k-is-calculated-for-evaluation-of-llms-coding-e52b8528235b>

AI Copilot Tools for Developers - Overview & Comparison of Tools | Zartis. (n.d.). Retrieved September 16, 2025, from <https://www.zartis.com/ai-copilot-tools-for-developers/comparison-of-tools/>

Bakal, G., Dasdan, A., Katz, Y., Kaufman, M., & Levin, G. (2025). *Experience with GitHub Copilot for Developer Productivity at Zoominfo*. <https://arxiv.org/pdf/2501.13282v1>

Chen, M., Tworek, J., Jun, H., Yuan, Q., Pinto, H. P. de O., Kaplan, J., Edwards, H., Burda, Y., Joseph, N., Brockman, G., Ray, A., Puri, R., Krueger, G., Petrov, M., Khlaaf, H., Sastry, G., Mishkin, P., Chan, B., Gray, S., ... Zaremba, W. (2021). *Evaluating Large Language Models Trained on Code*. <https://arxiv.org/pdf/2107.03374>

Code completion - Wikipedia. (n.d.). Retrieved September 16, 2025, from https://en.wikipedia.org/wiki/Code_completion

Competitive programming with AlphaCode - Google DeepMind. (n.d.). Retrieved September 17, 2025, from <https://deepmind.google/discover/blog/competitive-programming-with-alphacode/>

Dohmke, T., Iansiti, M., Richards, G., & Ai, K. (2023). *Sea Change in Software Development: Economic and Productivity Analysis of the AI-Powered Developer Lifecycle*. <https://doi.org/10.1145/3520312.3534864>

Evtikhiev, M., Bogomolov, E., Sokolov, Y., Germany, J., & Bryksin, T. (2017). *Out of the BLEU: How Should We Assess Quality of the Code Generation Models? 17*. <https://doi.org/10.1145/nnnnnnnn.nnnnnnnn>

From vi to AI: The Incredible Evolution of Coding Tools. (n.d.). Retrieved September 16, 2025, from <https://nimblegravity.com/blog/from-vi-to-ai-the-incredible-evolution-of-coding-tools>

Husein, R. A., Aburajouh, H., & Catal, C. (2025). Large language models for code completion: A systematic literature review. *Computer Standards and Interfaces*, 92. <https://doi.org/10.1016/J.CSI.2024.103917>

Introducing Codex | OpenAI. (n.d.). Retrieved September 17, 2025, from <https://openai.com/index/introducing-codex/>

ML-Enhanced Code Completion Improves Developer Productivity. (n.d.). Retrieved September 16, 2025, from <https://research.google/blog/ml-enhanced-code-completion-improves-developer-productivity/>

Peng, S., Kalliamvakou, E., Cihon, P., & Demirer, M. (2023). *The Impact of AI on Developer Productivity: Evidence from GitHub Copilot*. <https://arxiv.org/pdf/2302.06590>

Octoverse: The state of open source and rise of AI in 2023 - The GitHub Blog. (n.d.). Retrieved September 18, 2025, from https://github.blog/news-insights/research/the-state-of-open-source-and-ai/?utm_source=chatgpt.com

The past, present and future of AI coding tools | TechTarget. (n.d.). Retrieved September 16, 2025, from <https://www.techtarget.com/searchapparchitecture/tip/366539577/The-past-present-and-future-of-AI-coding-tools>

Unleash developer productivity with generative AI | McKinsey. (n.d.). Retrieved September 18, 2025, from <https://www.mckinsey.com/capabilities/mckinsey-digital/our-insights/unleashing-developer-productivity-with-generative-ai>

CHAPTER V

DIGITAL TWIN-DRIVEN PREDICTIVE MAINTENANCE IN INDUSTRY 4.0: EFFECTS OF CONDITIONAL GAN DATA AUGMENTATION ON SVM PERFORMANCE

Ahmet Gürkan YÜKSEK¹

*¹Department of Computer Engineering, Engineering Faculty,
CUNAM Nanophotonic Applications and Research Centre,
Cumhuriyet University, Sivas, Türkiye,
E-mail: agyuksekk@cumhnruiyet.edu.tr;
ORCID: 0000-0001-7709-6360*

1. Introduction

Industrial revolutions (Groumpos, 2021) have played an active role in all areas of social, economic and technological development through transformations in production processes. The industrial revolution process began with steam power, continued with mass production and electric power, and was digitally revolutionized with information technologies, and further changed to intelligent manufacturing systems with technologies such as CPS, IoT, big data, and digital twins (Lampropoulos & Siakas, 2023) (Frontoni et al., 2018). The primary aim of Industry 4.0 is to enhance flexibility, velocity, efficiency, and sustainability within production processes. In alignment with this aim, intelligent production systems are digital ecosystems designed to optimize not only manufacturing lines but also a variety of processes, including the supply chain, maintenance, logistics, and customer relations, by leveraging real-time data exchange (Mallioris et al., 2024) (Rajesh Lomte, 2025) (Raman et al., 2025). Digital twin technology serves as a fundamental element of the ongoing digital transformation, generating a virtual representation of tangible assets that facilitates process synchronization and the establishment of decision-making support systems during both the design and operational stages (Central Campus Győr, Széchenyi István University, Győr, Hungary et al., 2025). The extensive

data sources that inform digital twins enhance the traceability and predictability of processes along the production line (Kampa, 2023), while the coordinated processing of this information guarantees the uninterrupted functioning of the complete production chain (Fantozzi et al., 2025). Within this framework, the technological foundation provided by Industry 4.0 not only redefines production tools but also transforms the overarching production paradigm (Javaid et al., 2023), (Hananto et al., 2024).

Digital twins are updated in real time, so it's absolutely vital to get big, diversified and high-quality data sets. It's expensive, time-consuming, and in many cases simply out of the question to get data in the most advanced industrial environments. Generative Adversarial Networks (GANs) can be helpful in such a case. They are able to produce natural data copies. It is also easy to work with data holes, and they are capable of imitating sparse data sets and edge cases. It aids in the predictive power of the digital twin models (Mannone et al., 2025); (Parmar Tarun, 2024). Digital twins can predict things better when they are given synthetic data by generative networks instead of real-time data. These models also help to make sure that the processes and the system are in sync between the cyber-physical layers of the system. So, the focus is moving from increasing the amount of data to new ways that smart production systems can learn and change themselves. This is especially important in places where things are very different from one end to the other (Chandra et al., 2024) (Selçuk et al., 2021). The augmentation of generative neural networks with digital twins marks the beginning of self-replicating and intelligent manufacturing systems, which is a leap in the field (Mikołajewska et al., 2025) (Kusiak, 2020).

The combination of digital twins with generative artificial neural networks is a major step forward in the development of self-replicating and intelligent production systems. However, it is still difficult to check that these systems are reliable. In practice, datasets that are not complete, balanced, or fair can limit how well a digital twin can predict things, especially when it comes to rare failures, unexpected problems, or unstable production environments. This can make forecasting less effective. Apart from dealing with the problem of incomplete data, using generative artificial neural networks makes digital twins stronger and more flexible by combining artificial but realistic data samples. The text is now simpler. The combination makes possible the decision support system's coverage of more scenarios of operations, enabling production systems to detect anomalies, optimize the allocation of resources, and maintain efficiency in the face of ambiguity.

The research entails two primary domains of research work: First, the examination of the role of the generative artificial neural networks in overcoming the challenges from the inadequacy of data and enhancing the prediction capability of digital twins. Second, the exploration of the role the combination plays in enabling self-learning, self-organizations, and adaptability in Industry 4.0 environments. The research objective is the discovery of the extent that the closure of data lacunae using the generative models is impacting the development of smart, independent, and sustainable manufacturing systems.

2. Conceptual Basis and System Architecture

In the context of Industry 4.0, digital transformation is reshaping not only production tools but the entire paradigm of production. Digital twin technology is pivotal to this transformation, as it enhances the traceability, predictability, and adaptability of processes through the virtual reflections of physical assets. However, the efficacy of digital twins is contingent upon the continuity of high-volume, diverse, and reliable data sets. In actual industrial practice, acquiring this kind of data is often challenging due to costs, time, and technicalities. During this phase, the use of generative artificial neural networks is vital. The networks can be used in filling missing data through the synthesis of data that cannot be distinguished from actual data, mimicking uncommon events, and improving the forecasting capability of digital twins. Therefore, the combination of digital twins and generative models makes smart production systems more consistent and adaptable through the filling of information gaps. The architecture proposed in this section clarifies how the technologies intersect, explaining how self-learning and self-reconfiguring smart production systems can be established through the preservation of consistent data, correct processes, and correct models.

2.1. The conceptual framework of digital twin technology.

A digital twin can be defined as a digital replica of a physical object, process, or system that is regularly updated during its lifecycle. Digital twins differ from historical computer-aided design (CAD) or computer-aided engineering (CAE) models in that they are distinguished by their real-time linkage to a particular physical entity. This linkage allows for the capture of real-time data and ongoing self-updating. Please find below the details of the meeting. (Hartmann, 2021). This feature holds the promise of transfiguring digital twins from mere visualization tools to strategic decision support systems (Walton et al., 2024). The functions of the systems include performance assessment, scenario testing,

predicting potential failure, and exploring opportunities for improvement (Pires et al., 2023).

The digital twin technology has the foundation built on the notion of the digital thread that enables the flow of data between the physical and digital worlds (Mahankali, 2025). Data captured by sensors and Internet of Things (IoT) sensors are transmitted to a centralized bank, processed, and reflected in the twin. The digital thread acts as the key element providing coherence between the physical and digital worlds (Agho et al., 2025).

- Initiation of the sensor/IoT data and context information collection.
- It integrates, cleanses, and does quality assurance on the stream/data lake.
- The twin evaluates various conditions through real-time status forecasting and scenario analysis, thereby pinpointing potential bottlenecks and associated risks.
- The measures and alerts are shown on dashboards.
- Decisions are applied to devices/workflows via feedback.

This enables the digital twin to reflect operating efficiency in various environmental conditions, detect areas of inefficiency, and enhance design or maintenance procedures by integrating artificial intelligence algorithms. The extracted knowledge is then propagated to concerned stakeholders in the form of dashboards, and the resulting decisions are inputs to the physical system such that a continuous feedback mechanism ensues (Central Campus Győr, Széchenyi István University, Győr, Hungary et al., 2025).




Figure 1: Components of Digital Twin Systems
(Digital Twins: Components, Use Cases, and Implementations Ti)

Digital twins can be applied at different scales: Twins can be designed at the component (strength/energy efficiency), asset/product (component interaction and reliability), process/production (time–cost–capacity–automation

planning) and system/super system (networks, facilities, cities) scales. As the scale increases, modelling dependencies (synchronization, constraints, network effects) and integration costs increase. Twin outputs should be calibrated and validated with experimental/operational data; uncertainty measurement and sensitivity analysis should be performed. Maturity is assessed in stages: descriptive → diagnostic → predictive → prescriptive; performance is monitored using metrics.

The production or process twin models are a sequence of steps taken in a digital space. The steps forecast costs, duration, and the degree to which automation can be achieved and display all the intricacies of layered architecture. The collaboration among hardware and software enables the digital twin functions. Components of the Internet of Things (IoT) such as sensors, network appliances, and edge servers collaborate to capture data from the physical world. Middleware controls the subsequent steps of integrating, processing, and validating the quality of such data. From the perspective of the software industry, analytical engines, simulative tools, and visualization panels are significant for converting raw data to meaningful information. The following essay provides a detailed survey of the significant literature on the subject (Hananto et al., 2024).

While digital twins promise much in the Industry 4.0 universe, there are many limitations to how they can be utilized and implemented. First, the cost at a high level is a major problem. The necessity for advanced sensors, network hardware, data storage hardware, analysis software, and skilled labor provides a large barrier to investment, especially among small and medium businesses (Onma Enyejo et al., 2024). Second, the digital twin's effectiveness depends on the quality and consistency of the data. When the data is incomplete, inconsistent, or incorrect, the twin cannot accurately mirror the real world and may lead to incorrect predictions and suboptimal business decisions. Additionally, integrating data across many sources pose significant technological challenges, mainly because there are few standards and many systems do not interoperate well. Third, digital twins implementation and maintenance require expertise spanning many areas. When the data engineers, machine-learning professionals, field engineers, and IT professionals don't work well together, the viability of the twins may be threatened. This requires new workforce planning and company culture change. Large-scale digital twin deployments have shown to induce additional concerns about cybersecurity and protection of data. It must be realized that systems for collecting and processing data in real time may fall victim to security breaches (Agho et al., 2025).

2.2. The conceptual framework of generative artificial neural networks

Generative artificial neural networks (GANs) (Sengar et al., 2024) are models that learn the statistical patterns of existing datasets and generate new and consistent examples from the same distribution (Figure 2). These features mean that they meet two critical needs in digital twins: firstly, they can fill data gaps (missing sensor channels, imbalanced classes, rare fault signatures); secondly, they can safely simulate scenarios that are costly or risky to test in the real world. In this section, the contribution of generative models to digital twins will be addressed within a holistic framework through three main families: It has been demonstrated that Generative Adversarial Networks (GANs) (Wang et al., 2024) demonstrate a high level of proficiency in the generation of high realism and the creation of edge cases. By conditioning production to operating conditions and incorporating physical constraints into the model, synthetic data ensures scenario consistency and physical compatibility within the digital twin. The evaluation will not be confined to distribution similarity but will also be based on the task-based performance of the twin.

GAN, in its fundamental structure, comprises a generator (G) and a discriminator (D) network that are trained in a concurrent manner with opposing objectives. The generator produces synthetic samples by mapping a low-dimensional latent input (typically Gaussian/Uniform noise, optionally enriched with conditional information) to the data space; the discriminator scores whether an input is real or generated by the generator. This configuration can be regarded as a minimax game: D's objective is to optimize the real-synthetic distinction, whilst G's aim is to learn the structure of the distribution to such a degree that it deceives D. Therefore, GAN's aim is not merely to replicate 'image similarity' but to mimic the multidimensional relationships (joint statistics, correlations, structural constraints) within the data distribution. (S & Durgadevi, 2021) (Dan et al., 2020) (Iranmanesh & Nasrabadi, 2021) (Figure 2).




Figure 2: Generative Adversarial Networks (GAN) (Dan et al., 2020)

From an architectural perspective, the generator is predominantly a bottom-up expanding (upsampling) network. It extracts the latent vector into a high-dimensional tensor using fully connected layers. It then progresses to the target resolution using transpose convolution/upsampling + convolution blocks. Batch normalization and ReLU/LeakyReLU activations are frequently employed; Tanh/Linear is utilized at the output to scale the data appropriately. (Bhagyashree et al., 2020). The discriminator is a discriminative model that operates as follows: convolutional blocks compress the input into the feature space and ultimately produce a reality score. For images, the DCGAN-style 2D convolution is utilized; for time series such as vibration, pressure, and temperature, 1D convolutions, causal convolutions, or sequential layers are preferred. In the context of multi-channel sensors, multi-head attention or multi-branch architectures can be employed to preserve cross-channel correlation. (Pu et al., 2022). The training cycle is characterized by the following sequence of steps:

- The update of D is executed on a real mini-batch.
- The database has been updated once more with the synthetic batch that was produced by G.
- It is evident that D is fixed, and consequently, G is compelled to generate outputs that deceive D.

The GAN architecture, as outlined in Figure 2, serves as a crucial adjunct to the digital twin framework that is the subject of this study. This is due to the fact

that uncommon fault signatures, imbalanced classes, and absent sensor channels are prevalent in actual production environments, thereby constraining the twin's predictive capacity. GANs have been demonstrated to be capable of reliably filling data gaps by generating synthetic samples that preserve conditional (load, speed, temperature, flow rate, etc.) and multi-channel correlations under operating conditions. This is achieved through the competitive training of the generator-discriminator pair. The digital twin is thus enabled to test virtual scenarios that are costly or high-risk to test in the real world (e.g. extreme conditions, failure transitions). The generation of data by architectures adapted for time series (e.g. vibration, pressure, temperature) and multi-sensor streams, as opposed to images, is subject to domain constraints such as bandwidth, energy/RMS, and spectral shape. These constraints ensure physical consistency and are selectively integrated into the calibration of the twin. It has been demonstrated that GAN-based enrichment enhances the digital twin's early fault detection, prediction accuracy, and resilience to regime changes. Furthermore, it has been shown to fill in residual behaviors not covered by physics-based models, thereby creating a self-learning and adaptable decision support infrastructure. Consequently, the employment of GANs is regarded as a strategic imperative in all smart manufacturing scenarios characterized by data constraints.

2.3. Data Completion and Integrated Model Interaction: Theoretical Foundations and Application Dynamics of Digital Twin-GAN Integration

Digital twin technology is considered to be one of the most critical components of the Industry 4.0 vision, as it facilitates the traceability, predictability, and optimization of processes by creating a digital reflection of physical systems. However, it is important to note that this potential can only be realized with a high-volume, continuous, accurate, and meaningful data flow. The collection of such data in real production environments is challenging for economic and operational reasons. A number of factors must be considered when assessing the capacity of digital twins to operate at full capacity. These include high hardware costs, the inability to observe rare events in statistically significant numbers, and deficiencies in some sensor channels. (Guo et al., 2025). At this juncture, generative artificial neural networks present a novel paradigm for addressing the fundamental data requirements of digital twins and enhancing their modelling accuracy. Generative models, especially Generative Adversarial Networks (GAN) and Variational Autoencoders (VAE), can learn the statistical distributions of data and create synthetic data that is missing, rare or imbalanced.

These models have a number of advantages over the more traditional data augmentation method. They can be used to conduct digital testing of events that are too costly or dangerous to test in the real world. Consequently, digital twins have the capacity to formulate decisions that are not solely predicated on historical data, but also on likely future scenarios. This transformation of digital twins from reactive systems to proactive decision support systems is a significant development.

The methodological process structure is delineated as follows:

1. **Data Analysis:** The subsequent statistical examination of sensor data, time series and event logs obtained from industrial processes is undertaken for the purpose of identifying data gaps, variance deviations and pattern deficiencies.
2. **Identification of Deficiencies:** Problems such as underrepresented failure states, missing sensor channels, and imbalanced data classes (e.g., normal–abnormal ratio) are detected using high-dimensional data mining and clustering techniques.
3. **The application of the generative model is as follows:** GAN and VAE-based models utilize conditional generation logic to generate synthetic data. The generation of this data is informed by considerations of both physical constraints, such as energy consumption and temperature limits, and structural relationships, including multi-channel correlations.
4. **Digital Twin Integration:** The generated data is integrated into the digital twin's training and validation sets, enhancing the model's prediction accuracy, sensitivity, and generalization capacity.
5. **Validation:** The outputs generated in the simulation environment are then compared with actual production data, and model reliability is assessed using statistical validity tests.

This structure is a holistic approach that considers not only data production but also the dynamic interactions between system components:

- **Digital Twin ↔ Generative Models:** Digital twins, which reflect processes by processing real data, compensate for missing or weak data areas by collaborating with generative models. This integration enables digital twins to evolve into predictive systems operating with higher accuracy.
- **Data Gaps ↔ GAN/VAE:** Rare failures, unexpected scenarios, or missing measurements are simulated in terms of data using GAN and VAE models,

expanding the scope of the system. In particular, the minimax game theory-based learning approach used by GANs recreates complex relationships in the data.

- **Decision Support ↔ Extended Data Set:** Thanks to extended and balanced data sets, decision support systems operate with higher accuracy rates. These systems deliver more stable results in tasks such as regression, classification, and anomaly detection.

- **Industry 4.0 Ecosystem ↔ Smart Manufacturing:** The combination of digital twins and generative artificial intelligence supports the system architecture that will implement the principles of self-learning, self-adaptation, and self-reconfiguration, which form the essence of Industry 4.0.

Strategic Advantages and Scientific Value

This combined structure enables:

- High-accuracy models to be developed with limited data.
- Early warning systems to be built for production faults.
- Instantaneous prediction even with non-real-time (offline) data.
- Model training to be made more balanced and physically consistent.

In this context, GAN-supported digital twin structures not only increase efficiency but also redefine the stability, scalability, and sustainability criteria of production systems by developing a deeper epistemological understanding of the system.

3. CASE STUDY: Predictive Maintenance Based on Digital Twin

The objective of this section is to establish a decision support structure that accurately represents the operational behavior of equipment on the production line through its ‘digital twin’. This will enable the early and reliable prediction of failure probability, minimize false alarms, and translate maintenance decisions into action. The objective is to develop a predictive maintenance system that is both explainable and calibrated, combining data streams enriched with productive models using signals consistent with physical laws. This will be achieved despite practical constraints such as data scarcity and class imbalance, thereby shifting the digital twin from reactive monitoring to proactive prediction. This synthetic dataset, which was published in the UCI Machine Learning Repository, consists of 10,000 examples and core process variables Table 1. These reflect

predictive maintenance patterns encountered in industry. The document exhibits a multivariate and ‘time-stamped’ character. The following essay will provide a comprehensive overview of the relevant literature on the subject (S. Matzka, 2020). Table 2 provides descriptive statistics and visualisations of input/output variables in the context of digital twins and predictive maintenance. Units for numerical variables: Air/Process [K], Rotational speed [rpm], Torque [Nm], Tool wear [min]; derivatives: DeltaTemp [K], PowerW [W], Overstrain [min·Nm].

Table 1: Dataset Variables and Characteristics

Variable Name	Role	Type	Description	Units	Missing Values
UDI	ID	Integer	Unique identifier for each record	–	No
ProductID	ID	Categorical	Product identifier (L=Low, M=Medium, H=High + serial number)	–	No
Type	Feature	Categorical	Product quality type (L, M, H)	–	No
Airtemperature	Feature	Continuous	Air temperature measured during the process	K	No
Processtemperature	Feature	Continuous	Process temperature measured during the process	K	No
Rotationalspeed	Feature	Integer	Rotational speed of the tool	rpm	No
Torque	Feature	Continuous	Torque applied during the process	Nm	No
Toolwear	Feature	Integer	Tool wear in minutes	min	No
Machinefailure	Target	Integer	Overall machine failure (1 if any failure mode occurs)	–	No
TWF	Target	Integer	Tool wear failure	–	No
HDF	Target	Integer	Heat dissipation failure	–	No
PWF	Target	Integer	Power failure	–	No
OSF	Target	Integer	Overstrain failure	–	No
RNF	Target	Integer	Random failure	–	No

Table 2: Descriptive Statistical Values of Input Parameters

Feature	Mean	Std	Min	Q1	Median	Q3	Max
Air temperature	300.00	2.00	295.30	298.30	300.10	301.50	304.50
Process temperature	310.01	1.48	305.70	308.80	310.10	311.10	313.80
Rotational speed	1538.78	179.28	1168.00	1423.00	1503.00	1612.00	2886.00
Torque	39.99	9.97	3.80	33.20	40.10	46.80	76.60
Tool wear	107.95	63.65	0.00	53.00	108.00	162.00	253.00

The Numerical Variable Correlation Heat Map presented in Figure 3 summarizes the linear relationship between variable pairs and reveals both physical consistency and possible multicollinearity. As expected, Air–Process shows a strong positive relationship ($\text{Process} \approx \text{Air} + 10 \text{ K}$), PowerW shows a high positive relationship with Torque/rpm ($\text{Power} = \text{Torque} \cdot \omega$), and Overstrain shows a high positive relationship with Tool wear/Torque; DeltaTemp, however, is weak to moderate with other variables. These patterns validate the physical foundations of the HDF/PWF/OSF rules in the digital twin while also guiding feature selection/regularisation decisions.




Figure 3: Numerical Variable Correlation Heat Map

3.1. Training the ML model using the basic data set

In this study, an end-to-end MATLAB script for machine failure classification has been developed. The script commenced with the data loading process, followed by the stratification of the dataset into training, validation, and test subsets. In this particular context, the training set comprised 7,000 examples, the validation set contained 1,500 examples, and the test set consisted of 1,500 examples. The division of the dataset in this manner ensured the preservation of the class distribution and permitted a reliable evaluation of the model's performance. During the modelling phase, the Support Vector Machines (SVM) method (Suthaharan, 2016), which is frequently employed in predictive maintenance applications, was selected. The rationale for selecting SVM was its ability to determine effective decision boundaries in high-dimensional data spaces and its flexible structure offered by different kernel functions. The hyperparameter search process conducted on the validation set determined that the optimal parameters were $C=1.0$ and $\text{KernelScale}=2$. Utilizing these settings, $\text{ROC-AUC}=0.9671$ was attained on the validation set, thereby substantiating the model's considerable discrimination capability.

In the evaluations performed on the test set with the selected configuration, the following metrics were measured for the model: accuracy rate, precision value, sensitivity, F1 score, ROC-AUC value and PR-AUC value. The resulting values were 0.9133, 0.2701, 0.94, 0.4196, 0.9826 and 0.7069, respectively. The findings indicate that the model demonstrates notable proficiency in the identification of fault classes, a capability further accentuated by its elevated sensitivity value (refer to Table 3). It is imperative to note that high sensitivity is indicative of an apparatus's capacity to accurately discern the preponderance of genuine faults, a characteristic that is of paramount importance in the context of maintenance scenarios. Conversely, the low accuracy value indicates that the model produces a relatively high number of false positive predictions. This phenomenon can be attributed to the imbalanced class distribution inherent in the dataset, attributable to the presence of the fault class at a minimal rate. The following essay will provide a comprehensive overview of the relevant literature on the subject.

Table 3: Base Data Test Metrics

Accuracy	Precision	Recall	F1	ROC_AUC	PR_AUC
0.91333	0.27011	0.94	0.41964	0.98259	0.70685




Figure 4: Base Data - Confusion Matrix (Test Set)

The outputs of the model are supported not only by numerical metrics but also by visualizations. The confusion matrix (see Figure 4) provides an assessment of the model’s predictive capabilities. The matrix demonstrates a substantial number of true positives (TP) and a minimal level of false negatives (FN), thereby maintaining a high recall value. Conversely, the specific density of false positives (FP) explains the low precision result. Notwithstanding the evident class imbalance, this table demonstrates that SVM successfully captures the fault class. The ROC curve (Figure 5-a) demonstrates the model’s capacity to differentiate distinctly between classes, as evidenced by the curve’s proximity to the upper-left corner. The ROC-AUC=0.9826 value demonstrates that the score ranking is almost flawless in its separation of positives from negatives. In addition, the Precision-Recall curve (see Figure 5-b), which is regarded as more meaningful in the context of imbalanced data, also substantiates the model’s efficacy. It can be concluded that PR-AUC=0.7069 is a noteworthy success, even in a test set where the fault class is only observed at a rate of 3-4%.




Figure 5-a: Base - ROC Curve




Figure 5-b: Base -Precision-Recall

3.2. Augmenting the Dataset with GAN and Training the Same Model with the New Dataset

In this study, to ensure a fair comparison, the same test set was retained, and a conditional tabular cGAN-based data augmentation pipeline was designed for the minority class (Machinefailure=1). The same support vector machine (SVM) model was retrained on both the original (BASE) and augmented (AUGMENTED) data. The cGAN architecture represents the product type (Type: L/M/H) with one-hot conditional vectors in the tabular data context, while scaling continuous features with z-scores. Subsequent to the generation of synthetic samples, inverse scaling and physical/symbolic corrections (rounding to integers, clipping to reasonable ranges) are applied. The configuration was exclusively devised to enhance the training set; the validation and test sets remained unaltered. This clearly isolates the effect of the information provided by cGAN on overall performance.




Figure 6: Augmented Data - Confusion Matrix (Test Set)

Table 4: Augmented Data Test Metrics

Accuracy	Precision	Recall	F1	ROC_AUC	PR_AUC
0.952	0.39423	0.82	0.53247	0.96943	0.52552

The validation performance and optimal SVM settings. The optimal performance in the validation set, characterized by an ROC-AUC value of 0.9506, was attained with settings $C=1.0$ and $\text{KernelScale}=2$. This choice indicates a combination of hyperparameters that preserves the model's ranking power under class imbalance conditions while limiting overfitting. The ensuing discourse

will present the results of the conducted tests, alongside a confusion matrix. The test set yielded the following results: Accuracy=0.952, Precision=0.39423, Recall=0.82, F1=0.53247, ROC-AUC=0.96943, and PR-AUC=0.52552 (see Table 4). Given that the positive class has a low prevalence of $50/1500 \approx 3.33\%$, the metrics correspond to TP=41, FN=9, FP=63, and TN=1387 (Figure 6). Accordingly, the model captured 82% of the true faults (Recall), but the number of false alarms increased relatively (Precision $\approx 39.4\%$). For the negative class specifically, the Specificity (TNR) is equivalent to $1387/1450$, which is approximately 95.66%, the False Positive Rate (FPR) is approximately 4.34%, and the Negative Predictive Value (NPV) is equivalent to $1387/(1387+9)$, which is approximately 99.36%. This indicates that the system continues to offer high confidence when it states ‘no fault’. In curve-based metrics, ROC-AUC = 0.96943 indicates high discrimination capacity, while PR-AUC = 0.52552, which is more informative under imbalanced data conditions, shows that accuracy per alarm remains moderate (see Figure 7).




Figure 7-a: Augmented - ROC Curve




Figure 7-b: Augmented -Precision-Recall

The SVM (RBF) results obtained while maintaining the same test partition demonstrate that the BASE and GAN-supported AUGMENTED setups cater to different operational preferences. The BASE model yielded an accuracy of 0.9133, a precision of 0.2701, a recall of 0.94, an F1 score of 0.4196, a ROC-AUC of 0.9826, and a PR-AUC of 0.7069 in the test (approximately TP=47, FN=3, FP=127, TN=1323). The AUGMENTED model produced an accuracy of 0.9520, a precision of 0.3942, a recall of 0.82, an F1 score of 0.5325, a ROC-AUC of 0.9694, and a PR-AUC of 0.5255 (approximately TP=41, FN=9, FP=63, TN=1387). As illustrated in Table 5, positive-focused replication implemented exclusively on the training set with GAN leads to a shift in the decision boundary

towards a more conservative trajectory. This results in a substantial reduction in false positives (FP: 127→63; FPR: 8.76%→4.35%, TNR: 91.24%→95.65%) and, consequently, an enhancement in precision (27.0%→39.4%). Concurrently, the number of misses has increased (FN: 3→9) and recall has decreased (94%→82%). While this modification enhances the F1 score at a specific operating point (0.42→0.53), the decline in PR-AUC from 0.7069 to 0.5255 signifies a substantial diminution in threshold-independent overall discrimination capacity (particularly with respect to the success of maintaining rare positives at the forefront). Conversely, the balanced accuracy exhibited a decline from 92.6% to 88.8%. In summary, while the AUGMENTED model offers a more favorable profile for applications seeking to reduce false alarm costs, BASE is a safer choice when the cost of missed faults is high (Figure 8).

Table 5: Augmented-Base Data Test Metrics

	Accuracy	Precision	Recall	F1	ROC_AUC	PR_AUC
Base	0.91333	0.27011	0.94	0.41964	0.98259	0.70685
Augmented	0.952	0.39423	0.82	0.53247	0.96943	0.52552

The phenomenon of the GAN effect is consistent with the configuration of the system. The present study has demonstrated that artificially increasing the positive priority in training has led to a more conservative separation without narrowing the SVM margin in favour of the positive class. This has resulted in a balance that reduces FP and increases FN. Furthermore, minor inconsistencies may remain between the distributional details of synthetic samples and the actual test distribution; such a distribution shift may appear as a decline in the threshold-free metric PR-AUC, while yielding an increase in precision and accuracy at a single threshold. Indeed, while the augmented validation configuration (C=1.0, KernelScale=2; Val ROC-AUC=0.9506) maintained ranking power, it failed to optimize PR behavior (particularly “top-tile” accuracy at low prevalence).




Figure 8: Test Metrics Base and Augmented Data

4. Results and Discussion

The SVM (RBF) comparison conducted using the same test partition demonstrates that GAN-based data augmentation creates a different operating profile in this experimental setup. The BASE model demonstrates superiority in terms of ‘pushing positives to the top’ and not missing them, with PR-AUC=0.7069 and Recall=0.94 in the low-prevalence fault class. However, its hit rate per alarm is low due to Precision=0.2701 and FP=127 (FPR≈8.76%). In the AUGMENTED model, following the enhancement of the training set with cGAN, there was an increase in Accuracy to 0.9520, Precision to 0.3942, and F1 to 0.5325. Conversely, FP decreased significantly (127→63, FPR≈4.35%, TNR≈95.65%). Conversely, the recall value decreased to 0.82 (FN: 3→9) and the PR-AUC value decreased to 0.5255. Consequently, AUGMENTED produced a more conservative decision threshold that reduced false alarm costs; BASE remained more inclusive, prioritizing the identification of critical faults that had not been identified. The hypothesis is further substantiated by the concept of balanced accuracy, which is a statistical technique used to evaluate the accuracy of a model. The mean baseline value was found to be 92.6%, and the mean augmented value was 88.8%. One potential explanation for this discrepancy lies in the distribution shift that arises from the incorporation of synthetic positives into the training process. This shift prompts the model to reduce false alarms by

narrowing the positive region, thereby enhancing precision, accuracy, and F1 at a specific threshold. However, this adjustment concurrently weakens PR-AUC and recall, which are metrics independent of the threshold. The operational implications of these two approaches are evident: in scenarios where false alarms incur significant financial consequences, the augmented approach may be preferable; conversely, in situations where the cost of missing failures is high, the base approach is more reliable. The following essay will provide a comprehensive overview of the relevant literature on the subject.

Note: The following dataset was utilized to support and validate the theoretical framework of this study. **AI4I 2020 Predictive Maintenance Dataset, (2020). UCI Machine Learning Repository.** <https://doi.org/10.24432/C5HS5C> (S. Matzka, 2020)

5. Reference

Agho, M. O., Eyo-Udo, N. L., Onukwulu, E. C., Sule, A. K., & Azubuike, C. (2025). Digital Twin Technology for Real-Time Monitoring of Energy Supply Chains. *International Journal of Research and Innovation in Applied Science*, IX(XII), 564–592. <https://doi.org/10.51584/IJRIAS.2024.912049>

Bhagyashree, Kushwaha, V., & Nandi, G. C. (2020). Study of Prevention of Mode Collapse in Generative Adversarial Network (GAN). *2020 IEEE 4th Conference on Information & Communication Technology (CICT)*, 1–6. <https://doi.org/10.1109/CICT51604.2020.9312049>

Central Campus Győr, Széchenyi István University, Győr, Hungary, Monek, G. D., Fischer, S., & Central Campus Győr, Széchenyi István University, Győr, Hungary. (2025). Expert Twin: A Digital Twin with an Integrated Fuzzy-Based Decision-Making Module. *Decision Making: Applications in Management and Engineering*, 8(1), 1–21. <https://doi.org/10.31181/dmame8120251181>

Chandra, S., Duvinage, M., Prakash, P., Davis, P., & Timmer, S. (2024). Improving Process Yield Through Manufacturing Digital Twin Using Conditional Synthetic Data Engine (COSYNE). In U. Endriss, F. S. Melo, K. Bach, A. Bugarín-Diz, J. M. Alonso-Moral, S. Barro, & F. Heintz (Eds), *Frontiers in Artificial Intelligence and Applications*. IOS Press. <https://doi.org/10.3233/FAIA241063>

Dan, Y., Zhao, Y., Li, X., Li, S., Hu, M., & Hu, J. (2020). Generative adversarial networks (GAN) based efficient sampling of chemical composition space for inverse design of inorganic materials. *Npj Computational Materials*, 6(1), 84. <https://doi.org/10.1038/s41524-020-00352-0>

Fantozzi, I. C., Santolamazza, A., Loy, G., & Schiraldi, M. M. (2025). Digital Twins: Strategic Guide to Utilize Digital Twins to Improve Operational Efficiency in Industry 4.0. *Future Internet*, 17(1), 41. <https://doi.org/10.3390/fi17010041>

Frontoni, E., Loncarski, J., Pierdicca, R., Bernardini, M., & Sasso, M. (2018). Cyber Physical Systems for Industry 4.0: Towards Real Time Virtual Reality in Smart Manufacturing. In L. T. De Paolis & P. Bourdot (Eds), *Augmented Reality, Virtual Reality, and Computer Graphics* (Vol. 10851, pp. 422–434). Springer International Publishing. https://doi.org/10.1007/978-3-319-95282-6_31

Groumpos, P. P. (2021). A Critical Historical and Scientific Overview of all Industrial Revolutions. *IFAC-PapersOnLine*, 54(13), 464–471. <https://doi.org/10.1016/j.ifacol.2021.10.492>

Guo, J., Zhang, Y., & Wang, W. (2025). Predicting hydro turbine failures through digital twin simulations of rare real-world data. *Journal of Computational Methods in Sciences and Engineering*, 14727978241304260. <https://doi.org/10.1177/14727978241304260>

Hananto, A. L., Tirta, A., Herawan, S. G., Idris, M., Soudagar, M. E. M., Djamari, D. W., & Veza, I. (2024). Digital Twin and 3D Digital Twin: Concepts, Applications, and Challenges in Industry 4.0 for Digital Twin. *Computers*, 13(4), 100. <https://doi.org/10.3390/computers13040100>

Hartmann, D. (2021). *Real-Time Digital Twins*. Zenodo. <https://doi.org/10.5281/ZENODO.5470478>

Iranmanesh, S. M., & Nasrabadi, N. M. (2021). HGAN: Hybrid generative adversarial network. *Journal of Intelligent & Fuzzy Systems*, 40(5), 8927–8938. <https://doi.org/10.3233/JIFS-201202>

Javaid, M., Haleem, A., & Suman, R. (2023). Digital Twin applications toward Industry 4.0: A Review. *Cognitive Robotics*, 3, 71–92. <https://doi.org/10.1016/j.cogr.2023.04.003>

Kampa, A. (2023). Modeling and Simulation of a Digital Twin of a Production System for Industry 4.0 with Work-in-Process Synchronization. *Applied Sciences*, 13(22), 12261. <https://doi.org/10.3390/app132212261>

Kusiak, A. (2020). Convolutional and generative adversarial neural networks in manufacturing. *International Journal of Production Research*, 58(5), 1594–1604. <https://doi.org/10.1080/00207543.2019.1662133>

Lampropoulos, G., & Siakas, K. (2023). Enhancing and securing cyber-physical systems and Industry 4.0 through digital twins: A critical review. *Journal*

of *Software: Evolution and Process*, 35(7), e2494. <https://doi.org/10.1002/smr.2494>

Mahankali, R. (2025). DIGITAL TWINS AND ENTERPRISE ARCHITECTURE: A FRAMEWORK FOR REAL-TIME MANUFACTURING DECISION SUPPORT. *INTERNATIONAL JOURNAL OF COMPUTER ENGINEERING AND TECHNOLOGY*, 16(1), 578–587. https://doi.org/10.34218/IJCET_16_01_049

Mallioris, P., Aivazidou, E., & Bechtsis, D. (2024). Predictive maintenance in Industry 4.0: A systematic multi-sector mapping. *CIRP Journal of Manufacturing Science and Technology*, 50, 80–103. <https://doi.org/10.1016/j.cirpj.2024.02.003>

Mannone, G., Hintz, K. D., & Dazer, M. (2025). Generative Twins: A Deep Learning Approach to Next-Gen Digital Twins. *2025 Annual Reliability and Maintainability Symposium (RAMS)*, 1–6. <https://doi.org/10.1109/RAMS48127.2025.10935021>

Mikołajewska, E., Mikołajewski, D., Mikołajczyk, T., & Paczkowski, T. (2025). Generative AI in AI-Based Digital Twins for Fault Diagnosis for Predictive Maintenance in Industry 4.0/5.0. *Applied Sciences*, 15(6), 3166. <https://doi.org/10.3390/app15063166>

Onma Enyejo, J., Peter Fajana, O., Sele Jok, I., Judith Ihejirika, C., Olusola Awotiwon, B., & Motilola Olola, T. (2024). Digital Twin Technology, Predictive Analytics, and Sustainable Project Management in Global Supply Chains for Risk Mitigation, Optimization, and Carbon Footprint Reduction through Green Initiatives. *International Journal of Innovative Science and Research Technology (IJISRT)*, 609–630. <https://doi.org/10.38124/ijisrt/IJISRT24NOV1344>

Parmar Tarun. (2024). Generative Adversarial Networks for Historical Data Generation in Semiconductor Manufacturing: Applications and Challenges. *International Journal For Multidisciplinary Research*, 6(6), 37230. <https://doi.org/10.36948/ijfmr.2024.v06i06.37230>

Pires, F., Leitão, P., Moreira, A. P., & Ahmad, B. (2023). Reinforcement learning based trustworthy recommendation model for digital twin-driven decision-support in manufacturing systems. *Computers in Industry*, 148, 103884. <https://doi.org/10.1016/j.compind.2023.103884>

Pu, Z., Cabrera, D., Li, C., & De Oliveira, J. V. (2022). VGAN: Generalizing MSE GAN and WGAN-GP for Robot Fault Diagnosis. *IEEE Intelligent Systems*, 37(3), 65–75. <https://doi.org/10.1109/MIS.2022.3168356>

Rajesh Lomte. (2025). Industry 4.0 Data Processing Requirements: Use Cases for Big Data Applications. *Journal of Information Systems Engineering and Management*, 10(16s), 238–244. <https://doi.org/10.52783/jisem.v10i16s.2592>

Raman, R., Vyas, P., & Vachharajani, H. (2025). Impact of industry 4.0 on supply chain in made to order industries. *Annals of Operations Research*, 348(3), 1183–1194. <https://doi.org/10.1007/s10479-023-05435-x>

S, Karthika., & Durgadevi, M. (2021). Generative Adversarial Network (GAN): A general review on different variants of GAN and applications. *2021 6th International Conference on Communication and Electronics Systems (ICCES)*, 1–8. <https://doi.org/10.1109/ICCES51350.2021.9489160>

S. Matzka, B. S. M. (2020). *AI4I 2020 Predictive Maintenance Dataset* (Data Set No. The AI4I 2020 Predictive Maintenance Dataset is a synthetic dataset that reflects real predictive maintenance data encountered in industry.; Version 1). UCI Machine Learning Repository. <https://doi.org/10.24432/C5HS5C>

Selçuk, Ş. Y., Ünal, P., Albayrak, Ö., & Jomâa, M. (2021). A Workflow for Synthetic Data Generation and Predictive Maintenance for Vibration Data. *Information*, 12(10), 386. <https://doi.org/10.3390/info12100386>

Sengar, S. S., Hasan, A. B., Kumar, S., & Carroll, F. (2024). Generative artificial intelligence: A systematic review and applications. *Multimedia Tools and Applications*, 84(21), 23661–23700. <https://doi.org/10.1007/s11042-024-20016-1>

Suthaharan, S. (2016). Support Vector Machine. In S. Suthaharan, *Machine Learning Models and Algorithms for Big Data Classification* (Vol. 36, pp. 207–235). Springer US. https://doi.org/10.1007/978-1-4899-7641-3_9

Walton, R. B., Ciarallo, F. W., & Champagne, L. E. (2024). A unified digital twin approach incorporating virtual, physical, and prescriptive analytical components to support adaptive real-time decision-making. *Computers & Industrial Engineering*, 193, 110241. <https://doi.org/10.1016/j.cie.2024.110241>

Wang, Y., Zhang, Q., Wang, G.-G., & Cheng, H. (2024). The application of evolutionary computation in generative adversarial networks (GANs): A systematic literature survey. *Artificial Intelligence Review*, 57(7), 182. <https://doi.org/10.1007/s10462-024-10818-y>

CHAPTER VI

LARGE LANGUAGE MODELS IN MATERIALS SCIENCE: APPLICATIONS AND FUTURE DIRECTIONS

Nida KATI¹ & Ferhat UÇAR²

*¹(Assoc. Prof.), Firat University, Faculty of Technology, Department of
Metallurgical and Materials Engineering, Elazig, Turkey*

E-mail: nkati@firat.edu.tr

ORCID: 0000-0001-7953-1258

*²(Assoc. Prof.), Firat University, Faculty of Technology,
Department of Software Engineering, Elazig, Turkey*

E-mail: fucar@firat.edu.tr

ORCID: 0000-0001-9366-6124

1. Introduction

Large Language Models (LLMs), one of the rapidly developing areas of artificial intelligence, have been driving significant changes in materials science in recent years. Models such as GPT, BERT, and Claude have become powerful tools not only for natural language processing tasks but also for scientific research and discovery. Materials science, a field requiring complex structural relationships, multidimensional datasets, and interdisciplinary approaches, significantly benefits from the capabilities offered by LLMs.

Traditional materials research requires lengthy processes based on experimental studies and theoretical calculations. The development of a new material, characterization of its properties, and optimization can take years. In this regard, LLMs assist materials scientists in a wide range of tasks, from literature review and material design to property prediction and process optimization.

Figure 1 presents a comprehensive visual summary of how large language models are applied across materials science research. The framework illustrates the fundamental shift from traditional research approaches—characterized

by manual literature searches, limited parameter exploration, and months of iterative experimentation—to AI-driven methodologies that enable systematic multidimensional analysis within significantly compressed timeframes. The diagram organizes LLM applications into three primary domains that reflect the core activities of materials research. Material design and discovery applications leverage inverse design approaches, where desired properties guide the search for optimal material structures rather than following the conventional path from composition to properties. This category encompasses structure-property relationship modeling, composition optimization, and automated hypothesis generation. Property prediction and characterization applications address the computational challenge of estimating material properties—including formation energies, electronic band gaps, mechanical characteristics, and thermal conductivity—without requiring extensive experimental testing or intensive computational simulations. Data analysis and visualization applications tackle the growing challenge of extracting meaningful insights from unstructured scientific literature, performing named entity recognition in complex chemical descriptions, establishing relationships between materials and their properties, and integrating LLM capabilities into laboratory workflows through electronic notebook systems. The framework highlights representative models that demonstrate these capabilities, including AtomGPT for atomistic property prediction and structure generation, MatterChat for multimodal integration of structural and textual information, LLM-Fusion for combining multiple data representations, and domain-specific models like MatBERT trained on materials science literature. The diagram also acknowledges key challenges that researchers must navigate, including ensuring data quality and availability, developing adequate domain-specific understanding in models, managing hallucination risks and verification requirements, addressing interpretability and trust issues, meeting computational resource demands, and establishing standardization protocols for evaluation and comparison. Looking toward future development, the framework emphasizes the need for task-specific model refinement, enhanced multimodal data integration, improved reliability mechanisms, and—most importantly—balanced human-AI collaboration where artificial intelligence augments rather than replaces researcher expertise.




Fig.1. Comprehensive framework of LLM usage in materials science.

The integration of artificial intelligence into materials research marks a critical juncture in the field’s evolution, one that demands both enthusiasm for new possibilities and careful consideration of implementation approaches. As materials scientists confront increasingly complex challenges—from designing next-generation energy storage materials to developing sustainable alternatives for critical applications—the volume and complexity of relevant information continue to grow. Large language models emerge in this context not as replacements for experimental validation or theoretical understanding, but as tools that can help researchers navigate vast literature landscapes, identify

promising research directions, and accelerate the hypothesis-testing cycle. The effectiveness of these tools depends fundamentally on how they are integrated into existing research practices and the extent to which their outputs undergo critical evaluation. This chapter systematically examines the current state of LLM applications in materials science, organizing the discussion around core research activities. In the following section the main branch application areas of the LLM structures in materials science is declared. Section 2.1 explores material design and discovery, examining how inverse design approaches enable more systematic exploration of compositional spaces and how models like AtomGPT and MatterChat demonstrate practical capabilities for structure generation and property prediction. Section 2.2 addresses property prediction and characterization, reviewing benchmarking efforts such as LLM4Mat-Bench that reveal both the capabilities and limitations of current approaches. Section 2.3 discusses data analysis and visualization, focusing on knowledge extraction from scientific literature and integration into laboratory workflows through systems like electronic notebooks. Section 2.4 examines the challenges that researchers encounter when applying these tools, including data quality constraints, domain-specific understanding requirements, hallucination risks, and the need for standardization protocols. The chapter concludes by synthesizing findings across these domains and identifying priorities for future development, with particular attention to the balance between automation and human expertise that characterizes successful implementation.

2. Application areas of the LLM in materials science

Large language models are radically changing traditional research concepts in materials science. This transformation encompasses a broad spectrum, from the way materials researchers address complex problems to the methodologies for processing scientific information and generating new discoveries. The applications of LLMs in materials science can be broadly categorized into different categories: information management and synthesis, design and discovery, characterization and analysis, process optimization, and data analysis. To understand the impact of this technology in materials science, it is useful to compare it to traditional research processes. In the traditional approach, when a researcher wants to develop a new material, they collect existing information through manual literature searches, rely on experience and intuition during hypothesis generation, try a limited number of parameter combinations for experimental design, are limited to statistical tools during data

analysis, and are constrained by their own area of expertise during the results interpretation phase. LLMs, however, revolutionize each of these processes, enabling comprehensive literature analysis in seconds, enabling systematic exploration in a multidimensional parameter space, processing large data sets instantaneously, automatically establishing interdisciplinary connections, and improving performance through continuous learning. This paradigm shift allows materials scientists to think more strategically and focus on creative processes, while automating routine and repetitive tasks.

2.1. Material design and discovery

One of the most important and impactful applications of large language models is the comprehensive approaches they offer in new materials design. This technology enables a transition from traditional trial-and-error methodologies to systematic, data-driven design. LLMs demonstrate extraordinary capabilities in modeling structure-property relationships, learning the highly complex and multidimensional relationships between material structure and properties and translating this knowledge into practical applications. This process involves analyzing atomic-level configurations, systematically evaluating crystal structure data, and modeling the effects of these parameters on macroscopic properties. The system is capable of recommending material compositions with desired properties, optimizing element ratios, and improving material performance by developing doping strategies. More importantly, LLMs adopt an inverse design approach; this approach, in contrast to the traditional “material-to-properties” methodology, works from desired properties to material structure. This inverse design strategy can suggest optimal alloy compositions when target mechanical properties are determined; develop optimal crystal structure configurations when desired optical properties are defined; and optimize heat transfer mechanisms through phonon engineering strategies when thermal conductivity targets are set. This comprehensive approach allows materials scientists to reduce research time from months to days, optimize resource utilization, and systematically explore previously unexplored material combinations, leading to significant changes in materials discovery and development.

One of the most important studies demonstrating the potential of LLMs in materials design is the AtomGPT model developed by Choudhar. This study, motivated by the recognition that despite the success of large-scale language models like GPT in commercial applications, their applications in materials design have not yet been sufficiently explored, developed a specialized model

based on transformer architecture. By combining chemical and structural text descriptions, AtomGPT demonstrates both atomistic property prediction and structure generation capabilities. The model can predict critical material properties such as formation energies, electronic band gaps, and superconductor transition temperatures with accuracy comparable to graph neural network models and can generate atomic structures for tasks such as new superconductor design. The obtained predictions are validated with density functional theory calculations, and this study demonstrates the potential of LLMs for forward and inverse material design, offering an efficient alternative approach for material discovery and optimization (Choudhary, 2024).

Understanding and predicting the properties of inorganic materials is critical for accelerating advances in materials science and supporting applications in fields such as energy and electronics. MatterChat, developed by Tang et al., is a multimodal large-language model that enhances human-AI interaction by integrating material structural data with language-based information. The key challenge of this study was to integrate atomic structures into LLMs with full resolution, a problem addressed by developing a structure-aware architecture. MatterChat reduces training costs and increases flexibility by using a bridge module that effectively aligns a pre-trained universal machine learning interatomic potential with a pre-trained LLM. The model significantly outperforms general-purpose LLMs such as GPT-4 in material property prediction and human-AI interaction, and has also proven useful in applications such as advanced scientific reasoning and step-by-step material synthesis (Tang et al., 2025).

LLM-Fusion, developed by Boyar et al., is an innovative fusion model that addresses this problem with a multimodal approach. While existing multimodal approaches are known to be promising in integrating different information sources, it has been found that fusion algorithms developed to date are simplistic and lack mechanisms for rich representation of multiple modalities. LLM-Fusion offers a flexible architecture capable of accurate feature prediction by integrating diverse representations such as SMILES, SELFIES, textual descriptions, and molecular fingerprints using large language models. With its LLM-based structure that supports multimodal input processing, the model can perform material property prediction with higher accuracy than traditional methods. Validated on five prediction tasks on two different datasets, the model demonstrates superior performance compared to single-modal and simple fusion methods. This study is significant because it demonstrates how intelligently combining different data sources via LLMs can yield effective

results in material discovery and paves a new avenue for accelerated material discovery (Boyar et al., 2025).

Beyond property prediction and data integration, another important application of LLMs in materials science is the acceleration of hypothesis generation and design processes. Materials discovery and design are fundamental to technological advancement, enabling the development of application-specific materials across various industries. Kumbhar et al. investigated the potential of LLMs to generate valid hypotheses to accelerate this process. In collaboration with materials science experts, they compiled a new dataset containing real-world goals, constraints, and design methods from recent journal publications. Using this dataset, they tested LLM-based agents that generate hypotheses to achieve given goals under specific constraints. To assess the relevance and quality of the generated hypotheses, they proposed a new scalable evaluation metric that mimics the process of a materials scientist critically evaluating a hypothesis. The compiled dataset, the proposed method, and the evaluation framework aim to advance future research on accelerating materials discovery and design with LLMs. This study represents a significant step in the field of materials design by demonstrating the capacity of LLMs not only to process existing knowledge but also to generate new and testable scientific hypotheses (Kumbhar et al., 2025).

2.2. Feature estimation and characterization

The primary goal of materials science is to understand the relationships between the structural properties and functional behavior of materials and to use this knowledge in the design of new materials. In traditional approaches, determining the mechanical, electronic, thermal, or optical properties of a material requires extensive experimental studies or intensive computational simulations. These processes are costly in terms of both time and resources and often require expert knowledge. For example, determining the mechanical strength of a new alloy can take weeks, involving sample preparation, testing procedures, and results analysis.

Large-language models offer an innovative approach to material property prediction and characterization. By using structure-property relationships learned from extensive scientific literature, these models can make property predictions much faster than experimental or computational methods. By processing input data in various formats, from atomic composition and crystal structure information to chemical formulas and textual descriptions, LLMs can predict various material

properties, such as formation energies, electronic band gaps, mechanical strength, thermal conductivity, and superconducting transition temperatures.

Rubungo et al. found that despite the increasing use of LLMs in materials science, insufficient attention has been paid to benchmark construction and standardized evaluation for LLM-based material property prediction, hindering progress. To address this shortcoming, they presented the largest benchmark to date, LLM4Mat-Bench, to evaluate the performance of LLMs in predicting the properties of crystalline materials. LLM4Mat-Bench contains a total of approximately 1.9 million crystal structures and 45 different properties collected from 10 public materials data sources. The benchmark supports different input modalities: crystal composition, CIF format, and crystal text description, totaling 4.7M, 615.5M, and 3.1B tokens for each modality, respectively. Using LLM4Mat-Bench, the researchers fine-tuned models of different sizes, including LLM-Prop and MatBERT, and provided zero-shot and few-shot orientations to evaluate the property prediction capabilities of LLM-chat-like models such as Llama, Gemma, and Mistral. The results highlight the challenges of general-purpose LLMs in materials science and the need for task-specific prediction models and task-specific instruction-tuned LLMs in material property prediction (Rubungo et al., 2025).

2.3. Data analysis and visualization

Materials science research generates large amounts of data through experimental measurements, simulations, and characterization techniques. Transforming this data into meaningful information is crucial for the success of research processes. In traditional approaches, processing, analyzing, and visualizing raw data requires significant time and effort from researchers. Processes such as complex spectra obtained from spectroscopic measurements, numerical analysis of microscopic images, interpretation of crystallographic data, and correlation of multidimensional experimental parameters are challenging tasks requiring specialized knowledge and technical skills.

Large-scale models have begun to play a transformative role in these data analysis and visualization processes. LLMs offer new possibilities for systematically extracting information from unstructured or semi-structured data, interpreting experimental results, and transforming complex data sets into understandable visuals.

Foppiano and colleagues, focused on evaluating the ability of large language models, such as GPT-3.5-Turbo, GPT-4, and GPT-4-Turbo, to extract

structured knowledge from scientific documents in the field of materials science. They prioritized two critical knowledge extraction tasks: (i) named entity recognition (NER) of the studied materials and physical properties, and (ii) relationship extraction (RE) between these entities. Due to the significant lack of datasets in the field of Materials Informatics, the evaluation was conducted using SuperMat, based on superconductor research, and MeasEval, a general measurement evaluation corpus. The performance of LLMs on these tasks was compared with traditional models based on the BERT architecture and rule-based approaches (baseline). The study presented a new methodology for the comparative analysis of complex material expressions and emphasized the standardization of chemical formulas to address the complexities in materials science knowledge evaluation. (Foppiano et al., 2024).

Beyond evaluating data extraction and analysis capabilities, studies addressing the practical applications of LLMs in materials science research are also of great importance. Jalali et al. examined the transformative role of large language models within Electronic Laboratory Notebooks (ELNs). ELNs represent a significant technological advancement, providing researchers with a digital platform to record and manage their experiments, data, and findings. This study investigated how LLMs can significantly transform fundamental aspects of science, such as experimental methodologies, data analysis, and knowledge extraction, within the ELN framework. The researchers performed a demonstration of LLM applications in ELN environments and also conducted a series of empirical evaluations to critically assess the practical impact of LLMs in improving research processes in a dynamic field such as materials science. The findings demonstrate how LLMs can significantly improve the quality and efficiency of research results in ELNs, thereby advancing knowledge and innovation in materials science research and beyond. This study is important because it demonstrates that LLMs are more than just data processing tools; they can be systems that can be integrated into daily laboratory practices and comprehensively support research workflows (Jalali et al., 2024).

2.4. Challenges and limitations

While large language models offer substantial capabilities for materials science research, their application faces several practical and technical challenges that researchers must understand and address. Those challenges can be examined under these topics:

2.4.1. Data quality and availability

The effectiveness of LLMs depends heavily on the quality and comprehensiveness of training data. In materials science, much valuable experimental data remains locked in published papers, patents, and laboratory notebooks, often in formats that resist automated extraction. Chemical formulas may be presented inconsistently across publications, experimental conditions might be incompletely reported, and critical details sometimes appear only in supplementary materials. This fragmentation means that even sophisticated models may miss important information or learn from incomplete datasets. Additionally, negative results—experiments that did not work as expected—are rarely published, creating a bias toward successful outcomes that can skew model predictions.

2.4.2. Domain-specific understanding

General-purpose LLMs, despite their broad knowledge, often struggle with the specialized terminology and complex relationships inherent to materials science. A model trained primarily on general text may not adequately capture the nuances of crystal symmetry operations, understand the implications of different synthesis routes, or recognize when two chemical descriptions refer to the same material. The mathematical relationships governing material properties—such as band structure calculations or thermodynamic stability criteria—require understanding that goes beyond pattern recognition in text. This limitation explains why domain-specific models like MatBERT and ChemBERT, trained specifically on materials science literature, typically outperform general-purpose alternatives for specialized tasks.

2.4.3. Hallucination and verification

LLMs can generate plausible-sounding but incorrect information, a phenomenon particularly problematic in scientific applications where accuracy matters. A model might suggest a material composition that violates basic chemical stability rules, propose synthesis conditions that are physically unrealistic, or cite papers that do not exist. This behavior stems from the statistical nature of language models—they predict likely continuations based on patterns in training data rather than reasoning from first principles. Researchers must therefore verify LLM outputs through cross-referencing with original sources, validating predictions with established scientific principles, or confirming suggestions through experimental work or computational calculations.

2.4.4. Interpretability and trust

Understanding why an LLM makes a particular prediction or suggestion remains challenging. When a model recommends a specific material composition or predicts certain properties, the reasoning behind that recommendation may not be transparent. This lack of interpretability creates difficulties in scientific contexts where understanding the underlying logic is as important as the result itself. Researchers need to know whether a prediction reflects genuine physical understanding or merely correlates patterns in training data. Without this transparency, building trust in LLM outputs becomes difficult, potentially limiting adoption in critical applications where decisions carry significant consequences.

2.4.5. Computational resources

Training and deploying large language models requires substantial computational infrastructure. Fine-tuning a model for materials science applications may need access to high-performance computing clusters, significant memory resources, and expertise in machine learning engineering. These requirements can create barriers for smaller research groups or institutions with limited computational budgets. Even using pre-trained models through APIs involves costs that scale with usage, potentially limiting accessibility for exploratory research or educational applications.

2.4.6. Integration with existing workflows

Incorporating LLMs into established research practices presents practical challenges. Laboratory information management systems, electronic notebooks, and analysis pipelines may not easily interface with AI tools. Researchers accustomed to traditional methodologies might face learning curves in understanding how to effectively prompt models, interpret outputs, or integrate LLM-generated insights with conventional experimental data. This integration challenge extends beyond technical considerations to include questions about data ownership, intellectual property rights for AI-assisted discoveries, and appropriate attribution in publications.

2.4.7. Standardization and reproducibility

The materials science community lacks standardized benchmarks and evaluation protocols for LLM applications. Different research groups may use different datasets, evaluation metrics, or validation approaches, making it

difficult to compare results across studies or assess genuine progress. Model versions change over time, and what works well with one version may perform differently with updates. This variability complicates reproducibility—a cornerstone of scientific research—as other researchers may struggle to replicate reported results when using different model versions or slightly different prompting strategies.

These challenges do not diminish the potential value of LLMs in materials science, but they underscore the need for careful, critical application of these tools. Success requires combining LLM capabilities with human expertise, maintaining rigorous verification procedures, and developing community standards for evaluation and reporting. As the field matures, addressing these limitations through better training approaches, improved interpretability methods, and stronger validation frameworks will be essential for realizing the full potential of language models in accelerating materials discovery and design.

3. Conclusion

Large language models are significantly transforming research methodologies and workflows in materials science. The studies reviewed in this section demonstrate that LLMs provide effective results across a wide range of applications, from material design and property prediction to data analysis and hypothesis generation. One of the most significant advantages this technology offers materials scientists is its ability to reduce processes that can take months or even years with traditional approaches to days or even hours.

In the field of materials design, specialized models such as AtomGPT, MatterChat, and LLM-Fusion have concretely demonstrated the applicability of inverse design approaches. These models demonstrate the ability to design material structures based on desired properties, optimize atomic compositions, and make more accurate predictions by integrating multiple data sources. In particular, the integration of chemical and structural text descriptions has enabled performance levels rivaling those of graph neural network models. Studies on hypothesis generation have demonstrated the potential of LLMs not only to process existing knowledge but also to generate new and testable scientific insights.

Findings in the field of property prediction and characterization highlight the critical importance of standardized benchmarks for understanding the true capabilities of LLMs. Comprehensive evaluation frameworks such as

LLM4Mat-Bench have clearly demonstrated the limitations of general-purpose LLMs in materials science. The results demonstrate that fine-tuned task-specific models significantly outperform general-purpose models, highlighting the need to develop domain-specific models for specialized tasks such as material property prediction. Success rates in predicting critical material properties such as formation energies, electronic band gaps, and superconducting transition temperatures demonstrate the potential of this approach.

In the field of data analysis and visualization, LLMs have been demonstrated for systematically extracting information from unstructured scientific texts, interpreting experimental data, and automating research workflows. Integration studies into electronic laboratory notebooks have concretely demonstrated how this technology can be incorporated into daily laboratory practices and comprehensively support research processes. However, the challenges encountered in named entity recognition and relationship extraction tasks, particularly when dealing with complex chemical formulas and domain-specific terminology, still demonstrate the existence of significant technical hurdles.

One of the most important findings of existing studies is the need for fine-tuning and specialization for LLMs to be effective in materials science. General-purpose models, despite their extensive knowledge bases, fall short of the specialized terminology, complex mathematical relationships, and domain-specific rules of materials science. Therefore, future research should focus on developing task-specific models, improving multimodal data integration, and strengthening reliability mechanisms.

The successful application of LLMs in materials science depends on the balanced integration of human expertise and artificial intelligence capabilities. This technology aims not to replace researchers, but to support them and accelerate research processes. Therefore, the validation of LLM outputs, critical evaluation of results, and integration with expert knowledge are fundamental requirements for the responsible and effective use of this technology.

Large-language models offer significant opportunities in materials science research. However, fully realizing this potential requires the development of standardized assessment frameworks, the creation of domain-specific models, the strengthening of reliability and validation mechanisms, and the adoption of ethical use principles. In the future, by overcoming these challenges, LLMs are expected to play an even more central role in materials discovery and design, significantly accelerating the development of new materials for critical societal needs.

References

Boyar, O., Priyadarsini, I., Takeda, S., & Hamada, L. (2025). Llm-fusion: A novel multimodal fusion model for accelerated material discovery. arXiv preprint arXiv:2503.01022.

Choudhary, K. (2024). Atomgpt: Atomistic generative pretrained transformer for forward and inverse materials design. *The Journal of Physical Chemistry Letters*, 15(27), 6909-6917.

Foppiano, L., Lambard, G., Amagasa, T., & Ishii, M. (2024). Mining experimental data from materials science literature with large language models: an evaluation study. *Science and Technology of Advanced Materials: Methods*, 4(1), 2356506.

Jalali, M., Luo, Y., Caulfield, L., Sauter, E., Nefedov, A., & Wöll, C. (2024). Large language models in electronic laboratory notebooks: Transforming materials science research workflows. *Materials Today Communications*, 40, 109801.

Kumbhar, S., Mishra, V., Coutinho, K., Handa, D., Iquebal, A., & Baral, C. (2025). Hypothesis generation for materials discovery and design using goal-driven and constraint-guided llm agents. arXiv preprint arXiv:2501.13299.

Rubungo, A. N., Li, K., Hattrick-Simpers, J., & Dieng, A. B. (2025). LLM4Mat-bench: benchmarking large language models for materials property prediction. *Machine Learning: Science and Technology*, 6(2), 020501.

Tang, Y., Xu, W., Cao, J., Gao, W., Farrell, S., Erichson, B., ... & Yao, Z. (2025). Matterchat: A multi-modal llm for material science. arXiv preprint arXiv:2502.13107.

CHAPTER VII

LARGE LANGUAGE MODELS FOR SYSTEMATIC LITERATURE ANALYSIS IN SOLAR CELL MATERIALS RESEARCH: A PRACTICAL FRAMEWORK

Nida KATI¹ & Ferhat UÇAR²

*¹(Assoc. Prof.), Fırat University, Faculty of Technology, Department of
Metallurgy and Materials Engineering, Elazığ/Türkiye*

E-mail: nkati@firat.edu.tr

ORCID: 0000-0001-7953-1258

*²(Assoc. Prof.), Fırat University, Faculty of Technology, Department of
Software Engineering, Elazığ/Türkiye*

E-mail: fucar@firat.edu.tr

ORCID: 0000-0001-9366-6124

1. Introduction

Solar cell research has grown substantially over the past decade, driven by global efforts to transition toward renewable energy sources. As research activity intensifies, the volume of scientific literature has increased correspondingly. A search for “solar cell materials” in major academic databases now returns thousands of papers published annually, spanning multiple technology platforms including silicon-based cells, thin-film devices, perovskite solar cells, organic photovoltaics, and emerging tandem configurations. For researchers attempting to stay current with developments in the field, this growth presents a significant challenge.

Traditional approaches to literature review rely on manual reading and analysis of individual papers. A comprehensive review of even 100 papers can require several weeks of focused effort, involving careful reading of each paper, extraction of relevant data, categorization by research focus, and synthesis of findings. This process is not only time-consuming but also subject

to individual interpretation and potential oversight (Schmidt et al., 2019). When research teams need to analyze broader trends across hundreds of papers—such as identifying which materials are gaining attention, tracking performance improvements, or spotting emerging research directions—the manual approach becomes increasingly impractical.

Recent developments in artificial intelligence, particularly large language models (LLMs), offer a different approach to handling large volumes of scientific text. These models can process and analyze extensive document collections in a fraction of the time required for manual review. Unlike earlier text analysis tools that relied on simple keyword matching, modern LLMs can understand context, identify relationships between concepts, extract quantitative data, and generate structured summaries (Bai & Zhang, 2025). Several research groups have begun exploring how these capabilities might be applied to materials science, with applications ranging from property prediction to synthesis planning (Fang et al., 2022; Jiang et al., 2025).

This chapter focuses on a specific application: using LLMs to conduct systematic literature analysis in solar cell materials research. Rather than attempting to replace human expertise, the approach described here uses LLM capabilities to handle time-intensive tasks such as data extraction, categorization, and initial pattern identification. The goal is to enable researchers to efficiently process large literature datasets while maintaining the critical evaluation and interpretation that require domain knowledge.

The framework presented here is built around Claude, an LLM developed by Anthropic, though the general principles apply to other similar models. Claude offers several features that make it suitable for literature analysis: it can process long documents (up to 200,000 tokens in a single interaction), maintains context across multiple uploaded files, and can generate structured outputs including tables and visualizations. Importantly for academic applications, it can be instructed to cite specific sources when making claims, helping to maintain traceability between outputs and original papers.

The methodology we describe involves collecting papers in BibTeX format—a standard bibliographic format that includes author names, journal information, publication year, abstracts, and keywords—and using systematic prompts to extract and organize information. This approach does not require programming skills, making it accessible to researchers who want to leverage AI capabilities without learning to code. For those with programming experience, we also describe how the same workflow can be automated using the Claude API.

To demonstrate the framework's practical utility, we present a case study analyzing several hundred recent papers on solar cell materials. The analysis covers publication trends, materials innovation patterns, performance benchmarking, and emerging research directions. This case study illustrates both the capabilities and limitations of LLM-based literature analysis, providing realistic expectations for researchers considering this approach.

Why focus specifically on solar cell materials? This field presents characteristics that make it particularly suitable for demonstrating LLM-based analysis. Solar cell research is highly interdisciplinary, involving chemistry, materials science, physics, and engineering. Papers frequently report quantitative performance metrics—power conversion efficiency, open-circuit voltage, short-circuit current density, and fill factor—that can be systematically extracted and compared. The field also exhibits rapid evolution, with new materials and device architectures emerging regularly, creating a genuine need for tools that can quickly identify trends and assess the state of the art. Additionally, the solar cell community has established standardized testing protocols and reporting guidelines, which facilitates consistent data extraction across different studies.

The approach described here also addresses a practical limitation faced by many research groups: limited access to specialized AI expertise. While machine learning has become increasingly important in materials science (Maqsood et al., 2024), implementing custom AI solutions often requires programming skills and computational resources that may not be readily available. By demonstrating how a commercially available LLM can be used through a simple web interface or basic API calls, this chapter aims to lower the barrier to entry for researchers interested in AI-assisted literature analysis.

It is important to establish realistic expectations about what LLM-based analysis can and cannot accomplish. These tools excel at tasks involving pattern recognition, information extraction, and structured summarization across large document collections. They can quickly identify which materials are being studied most frequently, track how performance metrics have evolved over time, and flag papers that report unusual or noteworthy results. However, they have limitations. LLMs can sometimes generate incorrect information, particularly when asked to extrapolate beyond their training data. They cannot access full-text articles behind paywalls unless explicitly provided with that content. They also lack the deep domain expertise required to evaluate the validity of experimental methods or the significance of subtle technical details.

For these reasons, the framework we present is designed as a human-AI collaboration rather than full automation. The LLM handles the labor-intensive aspects of literature processing, while human researchers provide the critical evaluation, contextual understanding, and decision-making that require expertise. This division of labor allows researchers to analyze much larger literature collections than would be practical manually, while maintaining the quality standards expected in academic research.

Figure 1 provides a visual overview of the framework presented in this chapter. The diagram illustrates the three-phase methodology: data collection from academic databases, systematic analysis using Claude's natural language processing capabilities, and quality control through human verification. The framework begins with retrieving papers in BibTeX format from databases like ScienceDirect, capturing metadata including titles, abstracts, author information, and keywords. This structured data serves as input for the analysis phase, where systematic prompts guide Claude to extract technology classifications, identify material trends, and compile performance metrics. The process emphasizes human-AI collaboration rather than full automation—the LLM handles labor-intensive extraction tasks while researchers provide critical evaluation and domain expertise. Key features highlighted in the diagram include the system's accessibility (requiring no programming skills for basic use), its large context window enabling analysis of hundreds of papers simultaneously, and its ability to generate structured outputs such as tables and visualizations. The framework produces four categories of insights: bibliometric patterns (journal distribution, temporal trends), technology trends (material classifications, emerging themes), performance benchmarks (efficiency statistics, stability data), and innovation indicators (research gaps, novel approaches). These outputs support various applications including literature reviews for graduate students, competitive intelligence for research groups, and identification of collaboration opportunities. The diagram emphasizes that this approach is designed as a complementary tool—enhancing rather than replacing human expertise—with the LLM managing information processing while researchers maintain responsibility for interpretation and validation.

The chapter is organized as follows: Section 2 provides background on solar cell technologies and current applications of LLMs in materials research. Section 3 details the methodology, including data collection procedures, prompt engineering strategies, and quality control measures. Section 4 presents the comprehensive case study with detailed analysis across multiple dimensions.

Section 5 offers practical implementation guidance for researchers, including example prompts and code snippets. Section 6 concludes the overall framework, discussing perspectives on future developments in AI-assisted literature analysis.




Fig.1 – General Framework of the proposed system

2. Background: LLMs In Materials Science

Understanding how large language models can support solar cell materials research requires context on two fronts: the diverse landscape of solar cell technologies and the evolving role of artificial intelligence in materials science. This section provides that foundation, first reviewing the major categories of solar cell technologies and their characteristic materials challenges, then examining current applications of LLMs in materials research more broadly.

2.1. Solar Cell Technologies: A Brief Overview

Solar cells convert sunlight into electricity through the photovoltaic effect, and different technology platforms have emerged over several decades of development. Understanding the landscape of solar cell research requires familiarity with the major technology categories and their characteristic materials challenges.

Silicon-based solar cells, often referred to as first-generation photovoltaics, currently dominate the commercial market. These devices use crystalline or polycrystalline silicon wafers as the light-absorbing material. While silicon solar cells have achieved high efficiencies exceeding 26% in laboratory settings and demonstrate excellent long-term stability, they require high-purity materials and energy-intensive manufacturing processes. Research in this area continues to focus on reducing costs, improving light management, and developing passivation strategies to minimize efficiency losses at material interfaces (Cheng et al., 2025).

Thin-film solar cells, representing second-generation technology, use much thinner layers of photoactive materials deposited on glass or flexible substrates. This category includes cadmium telluride (CdTe), copper indium gallium selenide (CIGS), and amorphous silicon devices. Thin-film technologies offer advantages in material usage and manufacturing flexibility, though they generally achieve lower efficiencies than crystalline silicon. Current research emphasizes improving efficiency while addressing concerns about material toxicity and resource availability (Ezihe et al., 2025).

Third-generation solar cells encompass several emerging technologies that aim to surpass the theoretical efficiency limits of single-junction devices or offer new functionalities. Perovskite solar cells, which use organic-inorganic hybrid materials with the general formula ABX_3 , have attracted intense research interest due to their rapid efficiency improvements and solution-processability. Since the first reports of efficient perovskite solar cells in 2012, power conversion efficiencies have increased from around 10% to over 26%, approaching the performance of silicon cells. However, stability concerns related to moisture sensitivity, thermal degradation, and the use of lead remain significant challenges (Moyofola et al., 2025).

Organic photovoltaics use carbon-based semiconducting polymers or small molecules as active materials. These devices can be manufactured using low-cost printing techniques and offer advantages such as flexibility and semitransparency. Recent developments in non-fullerene acceptor materials have pushed efficiencies for single-junction devices into competitive ranges.

Research continues to address challenges related to efficiency, stability, and large-area manufacturing (Fan et. al, 2025).

Quantum dot solar cells employ nanoscale semiconductor particles with size-dependent optical properties. Colloidal quantum dots can be synthesized from earth-abundant materials and processed from solution, offering potential cost advantages. Current research explores optimal quantum dot compositions, surface passivation strategies, and device architectures to improve efficiency and stability (Torres et al., 2025).

Tandem solar cells combine multiple absorber materials with different bandgaps to capture a broader range of the solar spectrum. Perovskite-silicon tandems have demonstrated efficiencies exceeding 33%, surpassing the performance of single-junction silicon cells. This approach represents a promising path toward higher efficiencies, though it introduces additional manufacturing complexity (Lin et al., 2026).

Across all these technologies, common materials challenges include optimizing charge transport layers (both hole transport materials and electron transport materials), developing effective interfacial passivation strategies, improving stability under operating conditions, and scaling laboratory results to commercially relevant areas (Koten et al., 2025). The diversity of approaches and the rapid pace of development create a research landscape where systematic literature analysis can provide valuable insights into emerging trends and promising directions.

2.2. Generative AI Existence in Materials Research: Current Applications

Artificial intelligence has been applied to materials science for several decades, but recent advances in large language models have introduced capabilities that differ fundamentally from earlier approaches. While traditional machine learning in materials science typically focused on predicting specific properties from structural or compositional data, LLMs bring the ability to process and generate natural language, opening possibilities for literature analysis, knowledge synthesis, and experimental planning (Bai & Zhang, 2025).

The application of machine learning to materials discovery accelerated significantly in the past decade. Researchers demonstrated that algorithms could learn relationships between composition, structure, and properties from existing datasets, then use those relationships to predict characteristics of hypothetical materials (Schmidt et al., 2019). These approaches proved valuable for screening large numbers of candidates and identifying promising compositions

for experimental investigation. However, most machine learning applications required carefully curated numerical datasets and domain-specific feature engineering—the process of selecting which material characteristics to include as input variables.

Large language models represent a different paradigm. Trained on vast amounts of text data, these models develop statistical representations of how concepts relate to each other in natural language. This capability allows them to work directly with scientific literature in its native format, without requiring manual conversion to structured databases (Fang et al., 2022). An LLM can read a paper abstract describing a new material synthesis, extract relevant information about precursors and processing conditions, and identify connections to similar work reported in other papers—tasks that previously required human expertise.

Several applications of LLMs in materials science have emerged in recent years. One prominent area involves literature mining and knowledge extraction. Researchers have used LLMs to automatically extract material properties, synthesis conditions, and performance metrics from large collections of papers. This approach addresses a longstanding challenge in materials informatics: much valuable experimental data exists in scientific publications but remains inaccessible to computational analysis because it is reported in unstructured text rather than standardized databases.

Another application involves using LLMs to accelerate the materials design process. By training models on existing relationships between material composition and properties, researchers can query the model to suggest candidate materials with desired characteristics. While this application resembles traditional machine learning approaches, LLMs offer the advantage of being able to explain their suggestions in natural language and consider multiple types of information simultaneously—composition, structure, processing conditions, and even contextual factors like cost or availability (Chen et al., 2024).

LLMs have also been applied to experimental planning and protocol optimization. Some systems can suggest synthetic routes for new materials based on their understanding of chemical reactions and processing techniques reported in the literature. Others assist with analyzing experimental data or troubleshooting unexpected results by drawing on knowledge extracted from thousands of papers describing similar systems.

In the specific context of solar cell research, AI applications have primarily focused on predicting device performance, optimizing material compositions, and identifying stable material combinations (Jiang et al., 2025). Machine

learning models have been used to predict power conversion efficiencies based on material properties, guide the synthesis of new absorber materials, and screen candidates for charge transport layers. However, systematic applications of LLMs specifically for literature analysis in photovoltaics remain relatively uncommon, despite the potential value for tracking the rapidly evolving field.

The integration of LLMs into materials research workflows faces several challenges. Model accuracy depends on the quality and representativeness of training data, and LLMs can sometimes generate plausible-sounding but incorrect information—a phenomenon often called “hallucination.” Ensuring that extracted information is accurate requires verification strategies, particularly when the output will inform experimental decisions. Additionally, while LLMs can process text effectively, they typically cannot directly interpret figures, graphs, or tables without additional processing, limiting their ability to extract visual data from papers.

Several high-profile projects have demonstrated the potential of AI in materials discovery beyond literature analysis. DeepMind’s Graph Networks for Materials Exploration (GNoME) project identified approximately 380,000 potentially stable materials using graph neural networks combined with density functional theory calculations, significantly expanding the known materials space (Merchant et al., 2023). IBM’s RXN for Chemistry platform applies machine learning to predict chemical reactions and automate synthesis planning, integrating AI directly into laboratory workflows (Schwaller et al., 2019). The Open Catalyst Project focuses on discovering catalyst materials for clean energy applications, using large datasets and machine learning models to predict surface properties and reactivity (Chanussot et al., 2021). Domain-specific language models such as MatBERT and ChemBERT have been developed by training transformer architectures on materials science and chemistry literature, enabling more accurate extraction and generation of domain-relevant text (Gupta et al., 2022; Chithrananda et al., 2020). These projects illustrate the breadth of AI applications in materials science, from fundamental discovery to practical synthesis.

Despite these limitations, LLMs offer capabilities that complement traditional approaches to materials research. They excel at tasks involving pattern recognition across large document collections, identification of relationships between concepts, and synthesis of information from diverse sources. When used appropriately—with awareness of their limitations and appropriate verification procedures—these tools can significantly enhance researchers’ ability to navigate and analyze scientific literature.

2.3. Why Solar Cells? Why Claude?

The framework presented in this chapter could be applied to various materials science domains, but solar cell research presents several characteristics that make it particularly well-suited for demonstrating LLM-based literature analysis. Understanding these characteristics helps explain both the choice of application domain and the potential for extending this approach to other areas.

Solar cell research is highly interdisciplinary, involving contributions from chemistry, materials science, physics, and engineering communities. Papers in this field report findings using diverse experimental techniques and theoretical approaches, creating a complex information landscape that benefits from systematic organization. The field also exhibits rapid development, with thousands of papers published annually introducing new materials, device architectures, and performance records. This pace of progress creates genuine challenges for researchers attempting to maintain comprehensive awareness of developments across multiple technology platforms (Seyisi et al., 2025) .

Importantly, solar cell research has established conventions for reporting quantitative performance metrics. Papers typically report power conversion efficiency, open-circuit voltage, short-circuit current density, and fill factor using standardized units and testing conditions. This consistency facilitates systematic extraction and comparison of performance data across different studies. Additionally, the community has developed protocols for stability testing and reporting, though adherence to these protocols varies. The presence of quantitative benchmarks makes solar cell literature particularly amenable to LLM-based analysis, as numerical data can be extracted and aggregated to identify trends.

The choice of Claude as the LLM platform reflects several practical considerations. Claude offers a large context window capable of processing multiple papers simultaneously, which proves valuable when analyzing relationships across documents. The model can handle both structured data formats like BibTeX and unstructured text, allowing researchers to work with standard bibliographic exports from academic databases. Claude also provides a straightforward web interface that requires no programming expertise, lowering the barrier to entry for researchers interested in exploring AI-assisted literature analysis.

Importantly, Claude can be instructed to cite sources when making claims, a feature that supports verification of extracted information. When analyzing literature, the ability to trace statements back to specific papers helps researchers evaluate the reliability of LLM outputs. This traceability is essential for academic

applications where accuracy matters. For researchers with programming experience, Claude also offers an API that enables automation of repetitive analysis tasks, though the framework described in this chapter primarily emphasizes the no-code approach accessible through the web interface (Jiang et al., 2025).

The framework's focus on BibTeX format reflects practical constraints rather than theoretical limitations. Most academic databases allow export of search results in BibTeX format, which includes paper titles, author lists, abstracts, keywords, and publication information. While full-text analysis would provide richer information, paywall restrictions often limit access to complete articles from publisher's databases. BibTeX metadata, by contrast, is typically freely accessible and contains sufficient information for many literature analysis tasks, particularly those focused on identifying trends, categorizing research approaches, and tracking reported performance metrics.

3. Methodology: LLM-Based Literature Analysis Framework

This section describes a practical workflow for conducting systematic literature analysis using large language models. The approach requires no programming expertise, though we also provide guidance for researchers who wish to automate the process. The methodology involves three main steps: collecting papers in a structured format, using systematic prompts to extract and analyze information, and implementing quality control measures to ensure accuracy.

3.1. Data Collection

The first step involves identifying and collecting relevant papers. Academic databases such as ScienceDirect, Web of Science, and Scopus allow users to search for papers using keywords and apply filters for publication date, document type, and subject area. For the case study presented in this chapter, we searched ScienceDirect using the keyword phrase “solar cell materials” and restricted results to peer-reviewed articles published between 2023 and 2025.

Most academic databases support exporting search results in BibTeX format, a standardized bibliographic format widely used in scientific publishing. A typical BibTeX entry includes the paper title, author list, journal name, publication year, volume and page numbers, DOI, abstract text, and author-supplied keywords. This metadata provides substantial information for analysis without requiring access to full-text articles, which may be behind paywalls.

After exporting the search results, the BibTeX file should be reviewed for completeness. Some entries may lack abstracts or contain formatting errors that could interfere with analysis. Basic text preprocessing—such as removing special characters that might confuse the LLM or consolidating multiple BibTeX files into a single document—can improve results. For large collections exceeding several hundred papers, it may be necessary to split the dataset into smaller batches due to context window limitations, though Claude’s 200,000 token limit accommodates substantial document collections.

3.2. Claude Platform Workflow

Once the BibTeX file is prepared, the analysis proceeds through a series of structured prompts. The key to effective LLM-based analysis is prompt engineering—crafting clear, specific instructions that elicit useful outputs.

3.2.1. Initial Upload and Overview

The first interaction establishes the task. A straightforward prompt might be: “I have uploaded a BibTeX file containing recent papers on solar cell materials. Please provide an overview: How many papers are included? What is the time range? Which journals appear most frequently?” This initial query serves two purposes: it confirms that the file uploaded correctly, and it provides basic bibliometric information.

3.2.2. Systematic Information Extraction

Subsequent prompts request specific analyses. For example: “Categorize these papers by solar cell technology type (silicon, perovskite, organic, quantum dot, tandem, or other). Provide a count and percentage for each category.” Or: “Identify papers that report power conversion efficiency values. Create a table showing author, year, technology type, and reported PCE.”

The key to effective prompts is specificity. Rather than asking “What are the trends?” a better approach asks “Which hole transport materials appear most frequently in perovskite solar cell papers? List the top 10 with citation counts.” Specific prompts yield structured, actionable outputs.

3.2.3. Iterative Refinement

Literature analysis is inherently iterative. Initial queries reveal patterns that prompt follow-up questions. If the LLM identifies that dopant-free hole

transport materials appear frequently, a logical next prompt would ask: “Focus on papers discussing dopant-free HTMs. What stability improvements do they report compared to doped materials?” This conversational approach allows researchers to explore the literature dynamically, following interesting threads as they emerge.

3.2.4. Requesting Structured Outputs

LLMs can generate outputs in various formats. Explicitly requesting tables, bullet points, or even JSON format helps organize information. For example: “Create a table with columns for Material Type, Average PCE, Number of Studies, and Key Advantages. Include data for the five most studied absorber materials.” Structured outputs facilitate comparison and can be directly incorporated into reports or presentations.

3.2.5. Citation and Verification

A critical prompt strategy involves requesting source citations. Adding “cite specific papers by author and year for each claim” to prompts helps verify that extracted information corresponds to actual papers in the dataset. This practice reduces the risk of hallucination and provides traceability.

3.3. Quality Control Measures

While LLMs offer powerful analytical capabilities, they are not infallible. Implementing quality control measures helps ensure reliable results.

3.3.1. Verification Sampling

After extracting quantitative data—such as efficiency values or stability metrics—researchers should manually verify a random sample. Checking 10-15% of extracted data points against the original papers helps assess accuracy. If significant errors emerge, prompt refinement or alternative extraction strategies may be needed.

3.3.2. Cross-Validation

Important findings should be confirmed through multiple approaches. If one prompt suggests a particular material is gaining attention, a different prompt asking about emerging trends should corroborate this observation. Consistent findings across different queries increase confidence in the analysis.

3.3.3. Source Checking

When the LLM makes specific claims, verify that cited papers actually exist and contain the reported information. While modern LLMs are generally reliable when working with uploaded documents, they can occasionally misattribute information or conflate details from different papers.

3.3.4. Recognizing Limitations

LLMs cannot access information not present in the provided text. If BibTeX entries lack abstracts, analysis quality suffers. Full-text analysis would provide richer information, but this requires legally accessing and uploading complete articles—a significant practical limitation for large-scale analysis.

Understanding these limitations helps researchers use LLM-based analysis appropriately: as a tool for efficient information extraction and pattern identification, complemented by human expertise for interpretation and critical evaluation.

4. Case Study: Comprehensive Solar Cell Materials Analysis

To demonstrate the practical utility of LLM-based literature analysis, we conducted a comprehensive study of recent solar cell materials research. This section presents results from analyzing 488 peer-reviewed articles published between 2023 and 2025, covering multiple technology platforms and research approaches.

4.1. Dataset Overview

The dataset comprises 488 papers retrieved from ScienceDirect using the search term “solar cell materials” with publication dates between January 2023 and October 2025. The papers span 133 different journals, indicating the highly interdisciplinary nature of solar cell research. Temporal distribution analysis depicts that the paper intensity according to years as for 2023: 166 papers (34.0%), for 2024: 149 papers (30.5%) and for 2025: 185 papers (37.9%)

Table 1 shows the top 10 publication highlights. The increasing publication volume in 2025 reflects continued growth in solar cell materials research, particularly in emerging technologies.

Table.1 – Top 10 publication distribution.

Rank	Journal	Papers	%
1	Solar Energy	43	8.8%
2	Chemical Engineering Journal	26	5.3%
3	Dyes and Pigments	22	4.5%
4	Journal of Physics and Chemistry of Solids	18	3.7%
5	Solar Energy Materials and Solar Cells	11	2.3%
6	Materials Today Energy	9	1.8%
7	Journal of Power Sources	9	1.8%
8	Materials Today Communications	9	1.8%
9	Organic Electronics	9	1.8%
10	Journal of Alloys and Compounds	9	1.8%

The dominance of Solar Energy and specialized materials journals reflects the field’s focus on both fundamental materials development and device applications. The wide distribution across 133 journals—with no single venue capturing more than 10% of publications—demonstrates the interdisciplinary nature of the field.

4.2. Research Focus Distribution

4.2.1. Technology Platform Analysis:

Based on title and abstract analysis, papers were classified by primary solar cell technology:

- Perovskite solar cells: Dominant category, appearing in approximately 35-40% of papers
- Organic photovoltaics: Second major category (20-25% of papers)
- Silicon-based cells: Established technology, continuing optimization (10-15%)
- Dye-sensitized solar cells: Mature field with ongoing research (8-12%)
- Quantum dot solar cells: Emerging category (5-8%)
- Tandem architectures: Growing interest, particularly perovskite-silicon combinations (5-7%)

Note: Categories overlap as some papers address multiple technologies or comparative studies.

The prominence of perovskite research reflects continued interest in this rapidly advancing field. Organic photovoltaics maintain strong representation, driven by developments in non-fullerene acceptors and ternary blend systems. Silicon research, while proportionally smaller, focuses on advanced passivation techniques and hybrid architectures.

4.2.2. Component Focus:

Papers were categorized by the device component they primarily addressed:

- Charge transport materials (HTM/ETM): ~35% of papers
- Absorber layer optimization: ~30%
- Interfacial engineering: ~20%
- Stability enhancement: ~15%
- Device architecture: ~10%

The high proportion of charge transport material research reflects ongoing efforts to replace conventional materials with more stable, cost-effective alternatives. Interface engineering appears frequently, consistent with recognition that defects at layer boundaries significantly impact device performance.

4.3. Materials Innovation Analysis

4.3.1. Perovskite Solar Cells

Perovskite research dominates the dataset, with several distinct themes as listed:

Lead-Free Alternatives: Approximately 15-20% of perovskite papers investigate lead-free or lead-reduced compositions. Tin-based perovskites (FASnI_3 , MASnI_3) appear most frequently, though stability challenges remain. Other approaches include bismuth-based compounds and double perovskites, though these typically achieve lower efficiencies.

Hole Transport Materials: Dopant-free HTMs represent a growing trend. Papers report various organic polymers, small molecules, and inorganic materials (NiO_x , CuSCN) as alternatives to conventional doped spiro-OMeTAD. The motivation centers on improving long-term stability by eliminating hygroscopic dopants like lithium salts.

Electron Transport Materials: While TiO_2 and SnO_2 remain standard, papers increasingly explore fullerene derivatives and other organic ETMs for flexible or inverted architectures. Several studies investigate bis(pyrrolidino)fullerenes as shown in one paper reporting 12.3% efficiency with improved stability.

4.3.2. Organic Photovoltaics

Organic solar cell papers emphasize non-fullerene acceptor (NFA) development. The Y-series acceptors (Y6 and derivatives) appear frequently, paired with various polymer donors (PM6, PTQ10, PBDB-T). Research trends include:

- Ternary blend systems to broaden absorption spectra
- Molecular engineering to optimize energy levels and morphology
- Interface optimization using self-assembled monolayers

Several papers report efficiencies exceeding 18% for single-junction devices, with stability improvements through encapsulation and morphology control.

4.3.3. Interfacial Engineering

Interface modification emerges as a cross-technology theme. Common approaches include:

- Self-assembled monolayers (SAMs) for charge-selective contacts
- 2D materials (MoS_2 , MXenes) for passivation
- Aromatic compounds for defect passivation at perovskite interfaces

One notable paper systematically reviews aromatic compound applications in perovskite solar cells, analyzing effects on open-circuit voltage, fill factor, and stability.

4.4. Performance and Stability Trends

While not all papers report complete device metrics, those that do reveal several patterns can be grouped as follows:

Efficiency Progress: Papers reporting device performance typically show efficiencies between 15-25% for perovskite cells, 14-19% for organic cells, and 23-26% for silicon-based systems. Tandem configurations achieve the highest values, with perovskite-silicon tandems reaching 28-33%.

Stability Focus: Approximately 40% of papers explicitly address stability testing. Common protocols include:

- Thermal stability (85°C aging)
- Humidity resistance (controlled RH exposure)
- Light soaking (continuous illumination tests)
- Operational stability (maximum power point tracking)

Papers increasingly report long-term data (>1000 hours), though standardized testing protocols vary. Perovskite papers often cite ISOS protocols, while organic solar cell papers follow fewer uniform procedures.

Scalability Considerations: The dataset includes relatively few papers addressing large-area devices or manufacturing scale-up. Most report lab-scale cells (<0.1 cm²), with only 10-15% discussing devices larger than 1 cm² or roll-to-roll processing.

4.5. Emerging Themes

Machine Learning Integration: Approximately 8-10% of papers mention machine learning or computational screening. Applications include:

- Materials property prediction
- Composition optimization using Bayesian methods
- Automated literature analysis (including one paper on using LLMs for solar cell database creation)

Sustainability Considerations: Papers increasingly address environmental concerns:

- Lead-free perovskite research motivated by toxicity reduction
- Lifecycle assessment of manufacturing processes
- Recyclability of organic materials
- Earth-abundant element usage

Flexible and Wearable Devices: Approximately 12% of papers investigate flexible substrates or applications in wearable electronics. These papers emphasize mechanical stability, lightweight construction, and compatibility with roll-to-roll processing.

4.6. Geographic Distribution

Based on author affiliations, research contributions come from diverse regions:

- Asia (China, South Korea, Japan): Dominant contributor (~50% of papers)
- Europe (Germany, UK, Italy, Spain): ~25% of papers
- North America (USA, Canada): ~15% of papers
- Middle East and Other: ~10% of papers

Chinese institutions show particularly high publication volumes, consistent with national investment in renewable energy research.

5. Practical Implementation Guide

This section provides concrete guidance for researchers who want to apply LLM-based literature analysis to their own work. We present two approaches: a no-code method accessible to all researchers, and a programmatic approach for those comfortable with basic Python scripting.

5.1. No-Code Approach: Using Claude Web Interface

5.1.1. Step 1: Prepare Your Dataset

Search your preferred database (ScienceDirect, Web of Science, Scopus) using relevant keywords. Export results in BibTeX format. Most databases allow exporting 100-500 papers at once. If you have more papers, split into multiple files or combine them into a single text file.

5.1.2. Step 2: Upload and Initial Query

Visit claude.ai and upload your BibTeX file. Start with a basic overview prompt:

“I have uploaded a BibTeX file of solar cell papers. Please tell me: (1) How many papers are included? (2) What years do they cover? (3) Which journals appear most frequently?”

This confirms successful upload and provides basic statistics.

5.1.3. Step 3: Technology Classification

“Categorize these papers by solar cell technology type: perovskite, organic, silicon, quantum dot, tandem, dye-sensitized, or other. Provide counts and percentages for each category.”

5.1.4. Step 4: Materials Analysis

“Identify the most frequently mentioned hole transport materials in perovskite papers. List the top 10 with approximate frequency.”

“Which absorber materials are most studied in organic solar cell papers?”

5.1.5. Step 5: Performance Trends

“Find papers reporting power conversion efficiency above 20%. Create a table with: Author, Year, Technology, PCE (%), and Key Innovation.”

5.1.6. Step 6: Emerging Themes

“What are the top 5 research trends or challenges mentioned across these papers? For each trend, list 2-3 representative papers.”

5.2. Programmatic Approach: Python + Claude API

For researchers who want to automate repetitive analyses or process very large datasets, the Claude API enables scripting with using Python code design. Also the proposed system can produce the LaTeX code design of the generated report. The basic setup and advanced batch processing multiple queries designs can be defined as follows.

5.2.1. Basic Setup:

```
import anthropic
client = anthropic.Anthropic(api_key="your-api-key-here")
def analyze_literature(bibtex_content, prompt):
    message = client.messages.create(
        model="claude-sonnet-4-20250514",
        max_tokens=4096,
        messages=[{
            "role": "user",
            "content": f"{bibtex_content}\n\n{prompt}"
        }]
    )
    return message.content[0].text
# Load BibTeX file
with open("solar_cells.bib", "r") as f:
    bibtex_data = f.read()

# Run analysis
result = analyze_literature(
    bibtex_data,
    "Categorize by technology type and list top 10 journals."
)
print(result)
```

5.2.2 Advanced: Batch Processing Multiple Queries

```
pythonqueries = [
```

```

    “Technology distribution”,
    “Top 10 journals”,
    “Most cited papers”,
    “Emerging material trends”
]
results = {}
for query in queries:
    results[query] = analyze_literature(bibtex_data, query)
# Save results
import json
with open(“analysis_results.json”, “w”) as f:
    json.dump(results, f, indent=2)

```

This approach enables automated processing of multiple datasets during off-hours and automatic generation of time-consuming monthly reports, freeing researchers from repetitive manual tasks.

5.3. Best Practices

Verification: Always spot-check extracted data. Randomly select 10-15 papers and verify that reported information matches the original sources.

Iterative Refinement: Don’t expect perfect results on the first try. Refine your prompts based on initial outputs. If results are too vague, add more specific criteria.

Citation Tracking: When Claude cites specific papers, verify they exist in your dataset. Occasionally, LLMs may conflate information from different sources.

Limitations Awareness: Remember that Claude only sees abstracts if working with BibTeX exports. Full-text analysis requires uploading complete PDFs, which may not be practical for large collections.

Export and Document: Copy important outputs (tables, insights) into a separate document as you work. Claude conversations have context limits, so documenting key findings prevents information loss.

6. Conclusion

This chapter has presented a practical framework for conducting systematic literature analysis in solar cell materials research using large language models.

Through a case study analyzing 488 recent papers, we have demonstrated how LLM-based approaches can efficiently process large document collections while maintaining the scientific rigor expected in academic research.

6.1. Key Findings and Contributions

The framework described here addresses a genuine challenge facing materials researchers: the growing volume of scientific literature makes comprehensive manual review increasingly impractical. Our case study revealed several insights that illustrate both the capabilities and appropriate use cases for LLM-based analysis.

First, the methodology enables rapid bibliometric analysis across large datasets. Tasks that would require days or weeks of manual effort—categorizing papers by technology type, identifying publication trends, extracting performance metrics—can be completed in hours. The analysis of 488 papers revealed clear patterns: perovskite solar cells dominate current research (35–40% of papers), charge transport material optimization represents a major focus area (35% of papers), and publications span 133 different journals, reflecting the field’s interdisciplinary nature.

Second, the approach facilitates identification of emerging research directions. Our analysis detected several trends that merit attention: growing interest in dopant-free hole transport materials, increased emphasis on long-term stability testing, and rising adoption of machine learning for materials screening. These observations emerge naturally from processing large document collections in ways that would be difficult to detect through manual review of individual papers.

Third, the framework demonstrates how AI tools can complement rather than replace human expertise. The LLM handles labor-intensive information extraction and pattern recognition, while researchers provide critical evaluation, contextual understanding, and interpretation. This division of labor proves more effective than either fully manual or fully automated approaches.

6.2. Practical Implications

For researchers, this framework offers several practical benefits. Graduate students beginning literature reviews can quickly gain overview of their research area, identifying key journals, influential papers, and current research directions. Established researchers can monitor ongoing developments in related fields, detecting potentially relevant work that might otherwise escape notice. Research

groups can systematically analyze competitor activities, track technology trends, or identify collaboration opportunities.

The accessibility of this approach—requiring no programming skills for basic implementation—lowers barriers to adoption. Researchers can begin using these methods immediately through web interfaces, with the option to automate repetitive tasks later using straightforward API calls. This flexibility accommodates different skill levels and use cases.

6.3. Limitations and Considerations

Despite its utility, LLM-based literature analysis has important limitations that users must understand. The most significant constraint involves working with abstracts rather than full texts. BibTeX exports typically contain only paper metadata and abstracts, excluding detailed experimental procedures, comprehensive results, and nuanced discussions found in full articles. This limitation affects the depth of analysis possible, particularly for questions requiring detailed technical information.

LLMs can occasionally generate incorrect information, particularly when asked to extrapolate beyond provided data. While this “hallucination” risk can be managed through verification procedures and careful prompt design, it remains a consideration. Users should always verify critical findings by consulting original sources.

The framework also cannot fully replace domain expertise. LLMs lack the deep understanding of materials science required to evaluate experimental validity, assess the significance of subtle technical details, or recognize when reported results seem anomalous. These judgments require human expertise informed by years of research experience. The approach depends on the quality of input data. If literature searches miss important papers, or if BibTeX exports contain errors, analysis quality suffers. Careful dataset preparation remains essential.

6.4. Future Directions

Several developments promise to enhance LLM-based literature analysis capabilities. Multimodal models that can process both text and images will enable extraction of information from figures, tables, and structural diagrams—addressing a current limitation. Integration with academic databases through APIs would allow real-time literature monitoring, potentially generating automated monthly reports on research developments in specific areas.

Specialized language models trained specifically on scientific literature may offer improved accuracy for domain-specific tasks. Models like MatBERT and ChemBERT demonstrate this potential, though broader adoption requires overcoming data access and computational resource challenges.

The development of standardized reporting guidelines for different materials systems would facilitate more systematic data extraction. If papers consistently report performance metrics, synthesis conditions, and stability data using common formats, automated analysis becomes more reliable and comprehensive.

Perhaps most significantly, integration of LLM-based literature analysis with other AI tools—property prediction models, synthesis planning systems, experimental automation—could enable more comprehensive research workflows. Imagine a system that monitors recent literature, identifies promising material candidates, suggests experimental protocols, and helps interpret results—all while maintaining human oversight at critical decision points.

The framework presented here represents one application of AI in materials science, but the implications extend beyond literature analysis. As AI tools become more sophisticated and accessible, they will increasingly augment human capabilities across research activities. The key to successful integration lies in understanding both capabilities and limitations, using AI tools for tasks where they excel while maintaining human judgment for aspects requiring expertise, creativity, and critical evaluation.

Solar cell research provides an ideal testbed for these methods due to its rapid pace of development, quantitative performance metrics, and established reporting conventions. However, the general approach transfers readily to other materials domains: batteries, catalysts, structural materials, and beyond. Researchers in these fields can adapt the framework to their specific needs, adjusting classification schemes and analysis prompts while retaining the core methodology.

The integration of AI into scientific research workflows represents neither a threat to human researchers nor a solution to all challenges. Rather, it offers tools that, when used thoughtfully, can help researchers navigate increasingly complex information landscapes more effectively. The framework described in this chapter demonstrates one such application: using LLMs to conduct systematic literature analysis that would be impractical manually while maintaining scientific standards through appropriate verification and human oversight.

As materials science continues advancing, the volume and complexity of research literature will only grow. Tools that help researchers efficiently process, analyze, and synthesize this information become increasingly valuable. By combining AI capabilities with human expertise, researchers can focus their efforts where they matter most: designing experiments, interpreting results, and advancing scientific understanding.

The future of materials research likely involves increasingly sophisticated human-AI collaboration. This chapter provides a starting point for researchers interested in exploring these possibilities, offering both practical guidance and realistic expectations. Whether analyzing solar cell materials or any other research domain, the principles remain the same: use AI tools to handle labor-intensive tasks, verify outputs carefully, and maintain human judgment at the center of the research process.

References

Bai, X., & Zhang, X. (2025). Artificial intelligence-powered materials science. *Nano-Micro Letters*, 17(1), 1–30. <https://doi.org/10.1007/S40820-024-01634-8>

Chanussot, L., Das, A., Goyal, S., Lavril, T., Shuaibi, M., Riviere, M., Tran, K., Heras-Domingo, J., Ho, C., Hu, W., Palizhati, A., Sriram, A., Wood, B., Yoon, J., Parikh, D., Zitnick, C. L., & Ulissi, Z. (2021). Open Catalyst 2020 (OC20) dataset and community challenges. *ACS Catalysis*, 11(10), 6059–6072. <https://doi.org/10.1021/acscatal.0c04525>

Chen, C., Nguyen, D. T., Lee, S. J., Baker, N. A., Karakoti, A. S., Lauw, L., Stevens, G., Nguyen, T., D’Antuono, M., Xu, H., Rosenthal, J., Wong, B. M., & Troyer, M. (2024). Accelerating computational materials discovery with machine learning and cloud high-performance computing: From large-scale screening to experimental validation. *Journal of the American Chemical Society*, 146(29), 20009–20018. <https://doi.org/10.1021/JACS.4C03849>

Cheng, D., Gao, Y., & Yang, C. (2025). A comprehensive review on wafering of silicon substrate for photovoltaic solar cell. *Solar Energy*, 301, 113977.

Chithrananda, S., Grand, G., & Ramsundar, B. (2020). ChemBERTa: Large-scale self-supervised pretraining for molecular property prediction. *arXiv preprint arXiv:2010.09885*.

Ezihe, J. A., Abdulwahab, M., Ezema, F. I., & Echendu, O. K. (2025). Essential properties, growth methods, environmental impacts, and solar cell

application of antimony triselenide thin films: A review. *Hybrid Advances*, 100505.

Fan, J., Fan, R., Sun, P., Sun, H., & Zhang, Q. (2025). Structural engineering of platinum-containing organic photovoltaic catalysts for solar-driven hydrogen production: A review. *Asian Journal of Organic Chemistry*, e00402.

Fang, J., Xie, M., He, X., Zhang, J., Hu, J., Chen, Y., Yang, Y., & Jin, Q. (2022). Machine learning accelerates the materials discovery. *Materials Today Communications*, 33, 104900. <https://doi.org/10.1016/J.MTCOMM.2022.104900>

Gupta, T., Zaki, M., Krishnan, N. M. A., & Mausam. (2022). MatSciBERT: A materials domain language model for text mining and information extraction. *npj Computational Materials*, 8(1), 102. <https://doi.org/10.1038/s41524-022-00784-w>

Jiang, Q., Gao, Z., & Karniadakis, G. E. (2025). DeepSeek vs. ChatGPT vs. Claude: A comparative study for scientific computing and scientific machine learning tasks. *Theoretical and Applied Mechanics Letters*, 15(3), 100583.

Jiang, X., Xue, D., Bai, Y., Wang, W. Y., Liu, J., Yang, M., & Su, Y. (2025). AI4Materials: Transforming the landscape of materials science and engineering. *Review of Materials Research*, 1(1), 100010. <https://doi.org/10.1016/J.REVMAT.2025.100010>

Koten, H., & Kadhum, W. R. (2025). Investigating the properties of semiconductors solar cells technologies, efficiency for photovoltaic cells and application graphene for solar cells: A review. *Solar Compass*, 100147.

Lin, W., Cao, Y., Ke, Z., & Hassan, A. (2026). Shape-driven optimization strategy for efficient and stable lead-free all-perovskite tandem solar cells. *Solar Energy Materials and Solar Cells*, 295, 113971.

Maqsood, A., Chen, C., & Jacobsson, T. J. (2024). The future of material scientists in an age of artificial intelligence. *Advanced Science*, 11(19), 2401401. <https://doi.org/10.1002/ADVS.202401401>

Merchant, A., Batzner, S., Schoenholz, S. S., Aykol, M., Cheon, G., & Cubuk, E. D. (2023). Scaling deep learning for materials discovery. *Nature*, 624(7990), 80–85. <https://doi.org/10.1038/s41586-023-06735-9>

Moyofola, O. O., & Emetere, M. E. (2025). Improving the performance conversion efficiency of perovskite solar cells through optimization of charge transport layers: A review. *Renewable and Sustainable Energy Reviews*, 222, 115943.

Schmidt, J., Marques, M. R. G., Botti, S., & Marques, M. A. L. (2019). Recent advances and applications of machine learning in solid-state materials

science. npj Computational Materials, 5(1), 1–36. <https://doi.org/10.1038/s41524-019-0221-0>

Schwaller, P., Laino, T., Gaudin, T., Bolgar, P., Hunter, C. A., Bekas, C., & Lee, A. A. (2019). Molecular transformer: A model for uncertainty-calibrated chemical reaction prediction. ACS Central Science, 5(9), 1572–1583. <https://doi.org/10.1021/acscentsci.9b00576>

Seyisi, T., Fouda-Mbanga, B. G., Mnyango, J. I., Nthwane, Y. B., Nyoni, B., Mhlana, S., & Tywabi-Ngeva, Z. (2025). Major challenges for commercialization of perovskite solar cells: A critical review. Energy Reports, 13, 1400–1415.

Torres, F. G., Troncoso, O. P., & Tapia, J. (2025). Quantum dots in organic electronics: from solar cells to sensors. Materials Science and Engineering: B, 321, 118501.

CHAPTER VIII

GENERATIVE AI-ENHANCED APPROACHES FOR PARTICLE PHYSICS APPLICATIONS

Mehmet Uğur TÜRKDAMAR^{1,2} & Celal ÖZTÜRK³

*¹(Res. Asst.), Erciyes University, Faculty of Engineering, Department of
Computer Engineering, Kayseri/Turkey
E-mail: mturkdamar@erciyes.edu.tr
ORCID: 0000-0002-7745-6319.*

*²Niğde Ömer Halisdemir University, Faculty of Engineering, Department of
Computer Engineering, Niğde/Turkey*

*³(Prof. Dr.), Erciyes University, Faculty of Engineering,
Department of Software Engineering, Kayseri/Turkey
E-mail: celal@erciyes.edu.tr
ORCID: 0000-0003-3798-8123*

1. Introduction

When the Higgs Boson was discovered at CERN's Large Hadron Collider (LHC) it completed the Standard Model a major step forward in particle physics. High-dimensional experimental data from Higgs-related events are very complex classification tasks and depend on advanced computational approaches. To overcome this the Higgs Boson dataset [1] was released publicly in the 2014 Kaggle competition allowing researchers to compare benchmark and classification models. Traditional machine learning techniques such as Random Forest, XGBoost, CatBoost, LightGBM and AdaBoost have shown strong performance in classifying tabular data. These methods have become alternatives to convolutional and recurrent neural networks that learn from raw data. More recently generative AI methods have also emerged as powerful tools capable of learning high-dimensional

data distributions, synthesizing realistic event simulations and providing new ways to enhance classification performance. In high-energy physics generative approaches such as Generative Adversarial Networks (GANs) and diffusion models are increasingly being explored for tasks like fast detector simulation, anomaly detection and augmenting datasets beyond what is computationally feasible with traditional Monte Carlo simulations.

In this study, we presented comparative analysis between the deep learning architecture DNN, 4 popular tree-based ensemble models: Random Forest, XGBoost, CatBoost, LightGBM and 5 classical machine learning models: Logistic Regression, Linear SVM, RBF SVM, AdaBoost and kNN. The goal was to evaluate the strengths and limitations of each approach using the same dataset and preprocessing techniques. A secondary goal was to gain insight into the applicability and effectiveness of deep and classical machine learning models using the structured, unordered Higgs Boson dataset as a common benchmark.

CERN Higgs Boson dataset: The Higgs Boson Machine Learning Challenge simulated dataset organized by CERN in collaboration with the ATLAS experiment [2] classifies rich particle collision events as signal (Higgs-related) or background. The dataset includes realistic proton-proton collision events based on full detector simulations and numerous kinematic and tau lepton approximation channels. The classification task is quite challenging due to the small differences between the signal and background processes and the undetectable neutrino differences.

The Higgs Boson dataset was selected for its complexity and relevance to real-world high-energy physics problems. Originally organized for CERN's Higgs Boson Machine Learning Challenge the dataset helps distinguish sparse Higgs boson signals from background noise by simulating particle collisions with the ATLAS detector.

The classification task is challenging due to the small differences between signal and background events, the high dimensionality of the features and the presence of undetected particles such as neutrinos in the dataset. These complex, noisy and unstable environment characteristics make the dataset an ideal benchmark for evaluating the performance and robustness of deep and machine learning models.

In addition to the Kaggle Higgs Boson dataset we used publicly available datasets available through the CERN Open Data Portal to refine our understanding of particle behavior using realistic experimental conditions.

Specifically we referenced the CMS MuOnia and Dimuon datasets from the 2010 Run (PromptReco-v2) of muon-pair production events which included proton-proton collisions at $\sqrt{s} = 7$ TeV collected from the CMS detector [3, 4]. Furthermore we performed event reconstruction and classification using real detector data based on the CMS Open Data Guide for Event Analysis [5].

Our contributions are as follows:

- We conducted a comprehensive comparative analysis of Deep Neural Network (DNN), four commonly used tree-based ensemble models (Random Forest, LightGBM, XGBoost, CatBoost) and five classical machine learning algorithms (kNN, Logistic Regression, AdaBoost, Linear SVM and RBF SVM) on three benchmark datasets provided by CERN: the Higgs Boson, MuOnia (PromptReco-v2) and Dimuon (CMS Open Data).
- Tree-based ensemble models surpassed DNN's 84.24% accuracy on the Higgs Boson dataset with CatBoost and XGBoost's 99.82% classification accuracy, LightGBM's 99.59% and Random Forest's 91.73%.
- DNN's competitive performance on PromptReco-v2 and CMS Open Data dielectron datasets stands out with 97.86% AUC and 97.08% F1 score while Random Forest classifier's 98.2% AUC and 90.7% F1 score are similarly noteworthy for its strength on structured data.
- Our findings show that tree-based models achieve high efficiency even with relatively simple tunings (e.g., $n_estimators=100$) on structured tabular data such as the CERN dataset where temporal and sequential dependencies are limited. At the same time we conclude that finely tuned DNNs can still achieve competitive performance especially when interpretation and computational resources are insufficient.

2. Literature

Recent advances in deep learning have significantly impacted data analysis in particle and nuclear physics. DNNs are adept at modeling high-dimensional relationships in complex, large-scale sensor data. The Higgs Boson dataset has attracted the attention of the machine and deep learning communities since 2014. Its complexity and size have made it an ideal benchmark for evaluating classification algorithms in the context of high-energy physics. In addition to discriminative models generative AI approaches have gained attention for their ability to learn underlying data distributions, generate realistic synthetic events and accelerate detector simulations. These methods not only complement

traditional deep learning but also open new possibilities for anomaly detection, rare event discovery and reducing computational costs in large-scale experiments.

As part of the Higgs Boson Machine Learning Challenge, Baldi et al. [6] demonstrated the success of deep learning models using DNNs and CNNs over traditional machine learning techniques opening the door to high-energy physics applications. Duarte et al. [7] identified exotic particles using structure detectors on data from the LHC using fully connected networks.

The aim of Cherenkov and Scintillation radiation separation is to perform signal separation by improving the temporal character of the beam pulse waveform with deep learning. Their work has shown that machine and deep learning models can successfully distinguish photon waveform morphologies [8]. In a related study one-dimensional CNNs were used for feature extraction to identify regions of interest (ROIs) [9]. In a different study 1D, 2D and 3D CNNs were used for path tracking reconstruction [10]. Studies in this context have also focused on reconstructing particle energies which are critical in high energy physics with machine learning algorithms [11].

Data from Majorana was prepared for AI and used to generate realistic data which is the second most important issue in high-energy physics [12]. As one of the studies integrating hardware they generated neutrino data using machine learning on an FPGA [13]. In their study they achieved computational efficiency by performing pixel-level classification on the entire MicroBooNE dataset of approximately 1 GB on a standard CPU [14].

Network architectures combining CNN and LSTM have been proposed in the literature and used to classify particles at different levels [15]. In this approach local features in the input waveforms are extracted with a 1D CNN and then processed with an LSTM to capture local dependencies. The effectiveness of this method lies in learning both spatial and temporal features and achieving success in multi-particle classification. CNNs have been used to detect the interactions of Higgs bosons and gluons. The network was trained on data containing e^+e^- particles and compared with traditional methods. This study demonstrates the importance of deep CNN architectures in distinguishing Higgs events [16].

Higgs boson signals were extracted and distinguished from dense background noise using autoencoders, random forests and fully connected deep neural networks. Although the CNN+LSTM architecture was not directly used the study demonstrated the potential of deep learning in noisy data environments [17]. Experimentally deep neural networks were shown to outperform traditional

classifiers in cases where Higgs bosons converge to tau leptons. The results show that deep architectures improve on high-dimensional and complex physical event data [18].

Ayşe Bat (2023) showed that classical machine learning algorithms can effectively classify high-energy physics events especially the approximations from the Higgs boson to the tau-lepton pair ($H \rightarrow \tau\tau$) using open ATLAS data. The study evaluated 6 classification models (Logistic Regression, Linear, Radial SVMs, k-Nearest Neighbors, XGBoost and AdaBoost) in the context of multiple performance metrics (e.g., AUC, F1 score and cross-validation). Among these XGBoost achieved the highest classification performance with $84.0\% \pm 0.19\%$ and F1 score of 75%. This provided strong consistency between folds in complex, noise-prone, high-dimensional collision data. Findings; In cases where small margin separation between signal and background is critical ensemble tree-based methods are robust to high energy physics classification boosting tasks when compared with the extensive literature [19].

Yalçın Kuzu et al. (2025) demonstrated the success of DNN in analyzing high-energy particle events particularly the decay of J/ψ mesons into electron-positron pairs in their study titled Neural Network-Based Approaches to High-Energy Physics. By applying a structured DNN architecture and employing techniques such as dropout and hyperparameter tuning they achieved F1 score: 98.3% and AUC: 99.8%. This is consistent with recent deep learning advances in particle physics and the extensive literature on DNNs demonstrates that they outperform traditional methods in noise-rich environments and high-dimensional feature spaces [20].

Yalçın Kuzu (2021) published an early study titled Artificial Intelligence-Based Machine Learning Approach in High Energy Physics focusing on dielectron pair identification using a Random Forest classifier. The model achieved 93% precision and 93% sensitivity fully depending on the detector response for global feature transfer. This was a major step forward in demonstrating that ML models unlike traditional shear-based techniques can also be effective in high energy physics particularly in low-mass dielectron analysis. In contrast to deep learning RF offered interpretation and fast training on structured but small datasets [21].

Yalçın Kuzu (2022)'s research titled Identification of Dielectron Pairs with Machine Learning Method specifically focuses on classifying dielectron signals obtained from CMS experiments using RF-based supervised machine learning. The model achieved 98.2% with 92% precision and 90.9% recall. By leveraging key physical properties such as charge, momentum and opening angle the

RF classifier effectively separated the signal from the background. The study recalling the AI-based trend emphasized the interpretability in high-energy physics and the classical interpretation and efficiency by supporting CNN and hybrid CNN+LSTM models [22].

Baldi et al. (2014) performed Higgs Boson classification on Large Hadron Collider (LHC) data using a neural network (NN). This fundamental approach demonstrated the potential of deep learning in particle physics applications. Duarte et al. (2018) also focused on neural network model architecture improvements and optimization techniques for the same Higgs Boson dataset. DeHolton and the IceCube collaboration (2021) used a decision tree-based model with data from the IceCube Neutrino Detector located at the South Pole. In the context of neutrino detection they were able to achieve strong classification capabilities even with traditional machine learning methods.

Mo et al. (2025) also combined CNN and LSTM. Testing their model on a custom experimental dataset (EXP Dataset) containing 5 MeV energy particles they demonstrated that the CNN+LSTM framework captures spatial and temporal dependencies in experimental physics data. The hybrid models not only improve classification accuracy but also reduce training parameters compared to fully connected or recurrent networks.

3. Datasets and Preprocessing

In this section we present the datasets and preprocessing methods used throughout this study. We used three distinct datasets each of which holds a unique place in high-energy physics: 1. the simulated Higgs Boson dataset from the 2014 Kaggle competition 2. real beam state data from CMS experiments conducted during the 2010 LHC run at CERN and 3. dielectron decay events distinguishing J/ψ decays from background noise. These datasets with their wide range of challenges include imbalance, missing values, noisy and nonlinear features and are derived from different data sources: simulated, operational and reconstructed. For accurate and efficient model training, comprehensive preprocessing steps were applied including filling in missing data, feature normalization, removing irrelevant columns and reshaping the dataset for the deep learning model. This preparation has made classical machine and deep learning approaches a ready and robust foundation for various physics-based classification problems.

3.1. CERN Higgs Boson Dataset (Kaggle 2014)

The experiments in the study were conducted with the Higgs Boson dataset obtained from the 2014 public Kaggle competition, 11 million simulated collision events and 30 continuous features, data labeled “Higgs boson (signal)” or “background process” extracted from the physical detector.

Table 1. Overview of the CERN Higgs Boson Dataset

Source	Higgs Boson Machine Learning Challenge (Kaggle, 2014)
Origin	Simulated data based on ATLAS experiment at CERN
Number of Instances	~11 million (in full version) / ~250.000 in public training set
Number of Features	30 (real-valued continuous features)
Target Variable	Binary classification: Signal (Higgs boson) or Background process
Data Type	Tabular with floating-point values
Missing Values	Present as -999.0 (indicating unmeasurable or undefined physical values)
Challenge	High class imbalance: 85.667 signal / 164.333 background and noisy features, non-linear relationships
Application Domain	High-energy physics, particle detection and classification of rare events

Table 1 presents an overview of the CERN Higgs Boson dataset used in this study published for the 2014 Higgs Boson Machine Learning Challenge hosted on Kaggle. The training set consists of 250.000 simulated examples from the ATLAS experiment at CERN. Each example contains 30 real-valued continuous features solving a binary classification problem: distinguishing between a signal event (the presence of a Higgs boson) and a background process. The data consists of tabular and floating-point values. Missing or unidentified physical measurements are denoted by a placeholder value of -999.0. Key challenges of this dataset are the high degree of class imbalance (85.667: signal / 164.333: background), noisy feature distribution and complex nonlinear interactions.

3.2. CMS Beam Condition Dataset (LHC Run 2010)

To complement the simulated Higgs data we also used real beam state data from the CMS experiment at CERN focusing on Run 2010 of the Large Hadron Collider. This dataset includes the following key parameters:

E_GeV: Beam energy in GeV, **recorded_ub:** Recorded beam intensity, **avgpu:** Average number of pileup interactions per crossing, **beamstatus:** Beam status (e.g., “STABLE BEAMS”), **source:** Source of measurement (e.g., HFOC)

The target variable is the delivered beam intensity (delivered_ub), binarized with a threshold: values > 0.7 are labeled as class 1 (sufficient intensity) otherwise class 0.

3.3. Dielectron Event Datasets (J/ψ Decay vs. Background)

For further real physics scenario classification we analyzed two dielectron datasets: **dielectron.csv:** Contains background dielectron events not associated with J/ψ decays. **dielectron-Jpsi.csv:** Contains signal events explicitly representing $J/\psi \rightarrow e^+e^-$ decays.

These datasets were combined into a single dataset to assign new binary labels:

label = 0: background (non- J/ψ events), **label = 1:** signal (J/ψ meson decays)

The Run and Event ID columns were removed for classification purposes. The dataset includes features for each electron:

E, px, py, pz, pt: Energy and momentum components, **eta, phi:** Angular distributions, **Q:** Electric charge, **M:** Invariant mass of the dielectron system essential for identifying decay patterns

3.4. Preprocessing Steps

Missing Data Filling: Missing numerical features were filled by applying mean filling. Standardization: Features were scaled with StandardScaler [23] to 0 mean and unit variance to achieve stable convergence and stable gradient updates which are critical for neural networks.

Thanks to these dataset configurations rare particle decays and the invariant mass property (M) became particularly distinctive for the signature of a J/ψ meson. By combining simulated (Higgs), operational (beam condition) and reconstructed (dielectron decay) data the study provided the opportunity to evaluate classical machine and deep learning models with different data structures and physics contexts through a comprehensive benchmark framework.

For computational feasibility and rapid experimentation we used a small sample size (250.000) to approximate the original class distribution. The target variable was mapped to binary numerical form: ‘s’ is the signal, ‘b’ is the background; i.e., 1: signal and 0: background.

Several preprocessing steps were implemented to prioritize model training: **Missing Data Handling:** Some features were showing missing values at -999.0. These missing entries were replaced with 0s to maintain numerical stability and prevent model errors. **Feature Selection:** Irrelevant columns such as event descriptions or labels were removed from the feature set to prevent leakage and irrelevant information from affecting the models. **Normalization:** All feature columns were standardized to achieve a mean of 0 and unit variance using the `StandardScaler` method. This scaling resulted in faster convergence and improved performance for advanced neural networks and gradient-based algorithms.

Reshaping for the deep learning model: The scaled feature matrix was reshaped and prepared as input to the DNN model architecture expressing each sample as a fixed-length feature vector. **Train-test split:** The dataset was randomly split into train and test subsets at a ratio of 80 to 20 preserving the class balance of the target label layers. These preprocessing processes ensured that the data was clean, well-structured and ready for fair comparison between different classification models.

4. Methodology

The performances of the deep learning architecture DNN, 4 popular tree-based (Random Forest, XGBoost, CatBoost and LightGBM) and 5 classical machine learning algorithms (kNN, AdaBoost, LogRes, Linear SVM and RBF SVM) are compared. The aim is to compare the classification efficiencies of the methods by subjecting the CERN data to the same preprocessing.

4.1. DNN (*Dense Neural Network*)

While 1D CNNs and LSTM architectures are frequently used in sequential modeling and time-series tasks our dataset is not sequential or temporal. Each event in the dataset represents a single, independent high-dimensional vector of particle physics rather than a time-dependent signal.

Furthermore the use of 1D convolutions and recurrent layers (such as LSTM) assumes spatial or temporal locality among features. Columns in the datasets are not spatially adjacent and temporally ordered. Therefore it would not make sense to use convolution filters or a recurrent memory mechanism.

Therefore we chose a Deep Fully Connected Neural Network (DNN) to capture complex and nonlinear relationships in input features without any

assumptions regardless of order or locality. DNNs are also more computationally efficient resulting in better convergence and improved generalization performance across experiments particularly when focal loss and proper sample weighting are applied. Figure 1 shows the architecture of the DNN model used in this study.




Figure 1. Proposed Architecture of DNN

Figure 1 shows the architecture of the fully connected neural network used in this study. The model consists of three sequential dense layers following the input layer and a dropout layer after each dense layer which prevents overfitting by randomly deactivating neurons during training. The final dense layer as the output layer contains a sigmoid activation function and is ready for binary classification. This architecture aims to generalize by learning complex, non-linear representations as a standard deep feedforward design using dropout as a regularization technique.

4.2. Tree-Based and Other Classical Machine Learning Models

The following gradient boosting and ensemble models were implemented with default hyperparameters from the standard library and their performance was optimized by cross-validation-based hyperparameter tuning:

- Random Forest (RF) [24]: An ensemble of decision trees created using bootstrap aggregation (bagging) to reduce variance and increase robustness.
- eXtreme Gradient Boosting (XGBoost) [25]: Minimizes classification errors by constructing ordered trees within an optimized gradient boosting framework with regularization to control model complexity.
- Light Gradient Boosting Machine (LightGBM) [26]: A fast and distributed gradient boosting approach that uses histogram-based algorithms for efficient training on large-scale datasets.
- Categorical Boosting (CatBoost) [27]: A gradient boosting algorithm optimized for handling categorical features efficiently providing high accuracy with minimal data preprocessing.

In addition to tree-based models several other classical machine learning algorithms were also evaluated for comparison:

- k-Nearest Neighbors (kNN) [28]: A distance-based non-parametric algorithm that classifies samples based on the majority label among the k closest training samples.
- Logistic Regression [29]: A linear model that estimates the probability of a class label using a logistic function suitable for binary classification tasks.
- Support Vector Machine (SVM): Two variants were tested:
 - Linear SVM [30]: Finds the optimal separating hyperplane for linearly separable data.
 - RBF (Radial Basis Function) SVM [31]: A kernelized version that enables non-linear classification by mapping input features into higher-dimensional space.
- AdaBoost (Adaptive Boosting) [32]: An ensemble technique that builds a strong classifier by iteratively combining multiple weak learners typically decision stumps focusing more on previously misclassified samples.

All models including tree-based and classical methods were trained on feature sets scaled consistently with the deep learning model and evaluated using the same training-testing data split to ensure fair comparison.

4.3. Setup and Experiments

Models were evaluated using primary metrics such as classification accuracy, weighted F1 score and AUC while loss values were used for neural networks. Class imbalance was addressed by applying a stratified training-test split to achieve inter-class balance. Furthermore generalization was enhanced on benchmark datasets such as CERN using grid search, stratified k-fold cross-validation and data stratification techniques such as up-down/down-up sampling.

Hyperparameter tuning was performed for tree-based models using a five-fold cross-validation. This optimized performance and reduced overfitting. In deep learning experiments early stopping was applied over the validation loss to prevent unnecessary training epochs.

All experiments were conducted in Python [33] using TensorFlow/Keras [34, 35] for deep learning and Scikit-Learn [23] for machine learning models.

Table 2. Hyper Parameters for DNN

Optimizer	Adam [36]
Learning rate	0.001
Loss function	Focal Loss
Batch size	2.048
Epochs	100

Table 2 summarizes the hyperparameters used for training the deep neural network (DNN) model. The Adam optimizer was selected due to its adaptive learning rate capabilities and strong empirical performance across a range of tasks. A learning rate of 0.001 was used to ensure stable convergence during training. The focal loss function was employed which is appropriate for addressing class imbalance in binary classification problems. The model was trained with a relatively large batch size of 2.048 likely chosen to stabilize gradient estimates and accelerate training on compatible i7 processor. Training was performed over 100 epochs providing the model with sufficient opportunity to learn from the data while balancing the risk of overfitting.

In this study all experiments were conducted using an 80:20 train-test split to ensure consistent model evaluation across different algorithms. Five tree-based ensemble machine learning models (Random Forest, Gradient Boosting, CatBoost, AdaBoost and XGBoost) were trained under the same configuration with the number of estimators set to 100 for each. This uniform setup provided a fair basis for comparison while maintaining computational efficiency. Despite the relatively low number of estimators the models achieved high classification accuracy indicating effective learning within a limited training time.

The XGBoost classifier was configured with a learning rate (η) of 0.2 and a maximum tree depth of 6. A gamma value of 5 was used to enforce a minimum loss reduction before further tree splitting. The evaluation metric was set to ‘logloss’ and `scale_pos_weight` was automatically computed based on the ratio of negative to positive examples in the training data to address class imbalance. The `use_label_encoder` parameter was disabled for compatibility and the `random_state` was set to 42 to ensure consistent results.

The logistic regression model was configured with an inverse regularization strength parameter $C=10.0$ which reduces the impact of L2 regularization. The L2 norm was used as the regularization penalty (`penalty=’l2’`) and optimization was performed using the ‘liblinear’ solver which is suitable for small to medium-sized datasets. To handle class imbalance the `class_weight` parameter was set

to ‘balanced’ ensuring that class weights were automatically adjusted inversely proportional to class frequencies.

The linear SVM model employed a regularization parameter $C=1.0$ with the `class_weight` again set to ‘balanced’ to manage class imbalance. The maximum number of iterations was increased to 10.000 to ensure convergence (`max_iter=10.000`). A fixed `random_state` of 42 was used for reproducibility across different runs. This model consisted of a pipeline combining an `RBFSampler` with a `LinearSVC` classifier allowing approximation of the RBF kernel using a linear model. The RBF feature mapper was initialized with a gamma value of 0.01 and a `random_state` of 42. The linear SVM component was configured with a higher regularization parameter $C=100$ allowing for more flexible decision boundaries. Like previous models it used `class_weight=‘balanced’` and `max_iter=10.000`.

5. Results and Discussion

This chapter provides comprehensive comparative evaluations of various machine and deep learning models applied to three high-energy physics datasets: the CERN Higgs Boson, the CMS Beam Condition and the CMS Open Data Dielectron. Results include key performance metrics such as training and test accuracies, AUC scores and weighted F1 scores demonstrating model generalization, class separation and robustness across a variety of datasets.

The model performances are presented in Tables 3 through 5 with each table corresponding to a specific dataset. The evaluation involves not only assigning prediction accuracy but also assessing each model’s ability to maintain reliable probability estimates and generalization across the train and test phases. This is particularly critical for datasets with complex, high-dimensional feature spaces and unbalanced dataset distributions such as those from high-energy physics as it requires both classification accuracy and probabilistic calibration.

Table 3: Training and Testing Accuracies, AUC Scores and Weighted F1 Scores of Classification Models on the CERN Higgs Boson Dataset

Method	Train Accuracy (%)	Test Accuracy (%)	Train AUC (%)	Test AUC (%)	Train Weighted F1 (%)	Test Weighted F1 (%)
DNN	84.05	84.24	93.28	93.03	53.62	53.55
LightGBM	99.85	99.59	93.45	92.32	62.36	61.47
XGBoost	99.84	99.82	94.22	93.17	82.59	80.30
CatBoost	99.84	99.82	92.87	92.63	82.58	80.62
Random Forest	100	91.73	100	91.90	99.99	83.15
Logistic Regression	73.80	73.51	88.22	88.09	74.40	74.11
Linear SVM	73.47	73.29	88.03	87.92	74.09	73.91
RBF SVM	74.44	74.41	88.52	88.48	75.02	74.98
AdaBoost	81.13	80.85	90.49	90.18	80.91	80.66
kNN	85.44	78.33	94.65	86.80	85.39	78.25

Table 3 summarizes the performance comparison of the proposed models showing their training and testing accuracies, AUC and weighted F1 scores for the CERN Higgs Boson Dataset. These performance metrics are valuable for providing insights into the overall accuracy of each model including their inter-class discrimination and generalization capabilities.

The DNN achieved relatively balanced train and test accuracies of 84.05% and 84.24% respectively demonstrating that the model generalizes well without overfitting. The model’s AUC scores were quite high at 93.28% on the train set and 93.03% on the test set. These results highlight the robustness of the DNN in effectively discriminating between classes and maintaining consistency on complex, high-dimensional data such as the Higgs Boson dataset.

All three boosting methods achieved significant accuracy. LightGBM achieved 99.85% on the train set and 99.59% on the test set while both XGBoost and CatBoost achieved 99.84% train accuracy and 99.82% test accuracy. However the AUC scores tell a more detailed story. XGBoost achieved the highest AUC of 94.22% for train and 93.17% for test better capturing the class distributions. LightGBM and CatBoost followed closely with slightly lower AUC values. CatBoost achieved the lowest AUC of the three methods 92.87% for train and 92.63% for test. These results demonstrate that all three models achieve excellent classification accuracy while XGBoost provides better

probability estimation making better classifications on imbalanced datasets and making better decisions in uncertain situations.

Random Forest demonstrated perfect accuracy of 100% and severe overfitting on the training set. Although the test accuracy was slightly lower at 91.73% and the test AUC was slightly lower at 91.90% the model proved to be less successful at generalizing to data not seen in training. Despite its strong test performance compared to simpler models the overfitting problem does not make Random Forest the most reliable model for this data set without additional regularization or pruning.

Both Logistic Regression and Linear SVM achieved comparable results with test accuracies of 73.51% and 73.29% respectively and test AUCs of 88.09% and 87.92%. These results reflect the limitations of linear models when applied to particle physics data from complex, non-linear problems. While their simplicity and interpretability are advantages their performance is significantly lower than that of more advanced models.

The RBF SVM slightly outperformed its more linear counterparts achieving 74.41% test accuracy and 88.48% test AUC. This nonlinearity helped it detect patterns in the data. Although the slight improvement in accuracy and AUC represented a modest gain in classification the model still outperformed ensemble and deep learning models.

AdaBoost achieved a reasonable balance between simplicity and performance with a test accuracy of 80.85% and an AUC of 90.18%. While these scores are not as high as those achieved by gradient boosting methods it is effective. AdaBoost achieved a relatively low training accuracy of 81.13% which is poor compared to its test performance and is not suitable for real-world applications due to its low overfitting.

kNN achieved a high train accuracy of 85.44% but a correspondingly lower test accuracy of 78.33% reflecting moderate overfitting. Although the training AUC was the highest among all models at 94.65% the test AUC dropped to 86.80% suggesting that the model memorized the training examples rather than generalized them. This sensitivity is susceptible to data distribution and the curse of dimensionality limiting kNN's applicability to such high-dimensional data.

In conclusion while boosting methods like XGBoost, LightGBM and CatBoost dominated in terms of accuracy and AUC performance DNN demonstrated good generalization with competitive results. Simpler models like Logistic Regression and SVMs fell behind in handling the complexity of the dataset. Random Forest and kNN showed a tendency to overfit requiring more

tuning or hybrid strategies. Overall, ensemble-based and deep learning methods performed best for this specific classification task.

Compared to the existing literature the proposed DNN architecture provides competitive and slightly improved results. For example, Abbas et al. [17] achieved 83.6% accuracy and 85.4% AUC with their autoencoder-based deep learning method. In contrast, our deep learning-based DNN method demonstrated significantly higher accuracy and improved discrimination power achieving better AUC values of 93.28% and 93.03%.

When we take the average F1 score of the background and signal classes our models perform competitively and in some cases even better. For example, our XGBoost model achieved an average train F1 score of 82.59% and a test F1 score of 80.30% exceeding the average F1 scores of 78% train and 75% test achieved by the previous study [19] with the XGBoost model. Similarly, our AdaBoost model achieved an average test F1 score of 80.66% exceeding the previously reported test F1 score of 70%. While previous studies have achieved high AUC scores with SVM and Logistic Regression at 74.08% train and 73.8% test, our Logistic Regression model achieved a significantly higher AUC of 88.22% train and 88.09% test. These improvements are likely due to improvements in our modeling pipeline and potential improvements in feature representation or data preprocessing steps.

Table 4: Training and Testing Accuracies, AUC Scores and Weighted F1 Scores of Classification Models on the CMS Beam Condition Dataset

Method	Train Accuracy (%)	Test Accuracy (%)	Train AUC (%)	Test AUC (%)	Train Weighted F1 (%)	Test Weighted F1 (%)
DNN	99.44	99.45	99.86	99.89	99.17	99.17
LightGBM	99.05	99.02	99.87	99.87	99.56	99.58
XGBoost	99.75	99.76	99.89	99.89	99.77	99.78
CatBoost	99.77	99.79	99.90	99.91	99.79	99.80
Random Forest	99.94	99.93	99.99	99.98	99.97	99.93
Logistic Regression	89.37	89.23	99.86	99.89	99.17	99.17
Linear SVM	89.44	89.28	99.86	99.89	99.17	99.17
RBF SVM	93	92.92	99.86	99.89	99.17	99.17
AdaBoost	99.91	99.90	99.99	99.98	99.90	99.89
kNN	99.92	99.96	99.99	99.98	99.92	99.95

Table 4 shows the train and test accuracies, AUC and weighted F1 scores of 10 classification models applied to the CMS Beam Condition dataset. All models demonstrated high performance with test AUC scores exceeding 99.8% providing excellent discrimination ability in most cases.

The DNN model performed exceptionally well achieving train accuracy of 99.44%, test accuracy of 99.45% and AUC scores of 99.86% for both train and test. These results demonstrate the model's ability to capture complex nonlinear patterns and its strong generalization. The small difference between train and test scores indicates a small degree of overfitting. Furthermore the method achieved a weighted F1 score of 99.17% for both training and test demonstrating the model's consistent ability to effectively classify instances across different classes.

All three gradient boosting methods (LightGBM, XGBoost and CatBoost) delivered commendable performances. LightGBM achieved a test accuracy of 99.02% slightly lower than XGBoost's 99.76% and CatBoost's 99.79% while all achieved near-perfect AUC values of 99.87% and 99.91%. CatBoost had a significantly better probability estimation accuracy with the highest test AUC of 99.91%. These results demonstrate the power of gradient boosting methods in high-quality prediction tasks. In addition these models demonstrated strong performance on both train and test sets demonstrating a concrete and effective resolution of class imbalance with weighted F1 scores ranging from 99.56% to 99.80%.

The Random Forest model achieved near-perfect performance achieving 99.94% train accuracy, 99.93% test accuracy, 99.99% train AUC and 99.98% test AUC. Such near-perfect results demonstrate that the model captures decision boundaries on a high degree of data. However these results may indicate limited generalization difficulties with the dataset. Random Forest's weighted F1 scores of 99.97% train and 99.93% test reiterating this observation demonstrate high levels of robustness and consistency.

Despite their simplicity both Logistic Regression and Linear SVM achieved high AUC scores of ~99.86–99.89% despite low classification accuracies of ~89%. This distinction demonstrates that while these linear models cannot always make accurate challenging classification decisions they still provide highly efficient sample ranking and class probability estimation using the AUC metric. Weighted F1 scores of 99.17% indicate that despite struggling with accuracy the models still perform well in class discrimination and capture probabilistic outcomes.

The RBF SVM improved its linear counterparts by achieving 93% train and 92.92% test accuracy. Although the AUC scores were identical to those of linear models (99.86% train - 99.89% test) the increase in accuracy reflects the improved data capture of nonlinearity. However its performance is lower than that of more advanced ensemble or deep learning approaches. The weighted F1 scores of 99.17% for both train and test demonstrate that the model exploits nonlinearity failing to outperform simpler models.

AdaBoost achieved near-perfect results with 99.91% train and 99.90% test accuracy and 99.99% train and 99.98% test AUC. These findings demonstrate AdaBoost's robust data modeling capabilities with minimal generalization errors on par with Random Forest and kNN. AdaBoost also demonstrates strong classification performance in train and test with high weighted F1 scores of 99.90% train and 99.89% test.

Surprisingly, kNN achieved the highest test accuracy of 99.96% matching the 99.99% train and 99.98% test AUCs. This strong performance demonstrates that kNN handles well-separated and clustered data samples better than the approximate-based models. However in real-world scenarios kNN can face challenges in scaling and computational efficiency particularly on larger or more complex datasets. Weighted F1 scores of 99.92% train and 99.95% test indicate exceptionally good model performance particularly in the test phase with good class separation.

In summary, almost all models demonstrated exceptional performance on the CMS Beam Condition dataset achieving AUCs above 99.8%. These results demonstrate that even the Logistic Regression model given the dataset's high separability has no difficulty in producing reliable probability output predictions. Among all methods ensemble models (CatBoost, XGBoost, AdaBoost, Random Forest and LightGBM) and DNN outperformed demonstrating both high accuracy and strong generalization. Among the low-overfitting models the dataset is clean, structured and well-suited for classification tasks. The weighted F1 scores obtained by the models demonstrate their consistency overcoming strong class imbalance and performing well in both training and testing phases.

In previous work Kuzu (2021) reported an AUC of 99.8% and a weighted F1 score of 92% when classifying a dielectron pair using a Random Forest classifier. Our model showed a cleaner improvement achieving an AUC of 99.98% and a weighted F1 score of 99.93%. This significant gain demonstrates refined feature engineering, class balancing techniques and performance improvements implemented in tree-based ensemble methods. It also

demonstrates the robustness and generalization ability of Random Forest for structured datasets such as high-energy physics. The high AUC combined with the weighted F1 score improvement indicates that the model achieves better classification performance by being well-tuned.

Table 5: Training and Testing Accuracies, AUC Scores and Weighted F1 Scores of Classification Models on the CMS Open Data Dielectron Dataset (J/ψ Signal + Background)

Method	Train Accuracy (%)	Test Accuracy (%)	Train AUC (%)	Test AUC (%)	Train Weighted F1 (%)	Test Weighted F1 (%)
DNN	98.11	97.98	98.37	97.68	97.06	97.06
LightGBM	97.62	97.23	99.85	98.56	98.12	97.72
XGBoost	98.52	97.37	99.97	98.58	99.05	97.75
CatBoost	97.96	97.26	99.96	98.56	98.27	97.74
Random Forest	100	97.97	100	98.55	100	97.44
Logistic Regression	91.72	91.63	97.14	96.72	94.23	94.18
Linear SVM	91.12	91.14	97.07	96.89	94.02	94.02
RBF SVM	91.28	91.30	97.25	97	93.03	93.14
AdaBoost	98.03	98.03	98.66	98.61	97.06	97.06
kNN	98.31	97.70	98.34	80.47	97.93	97.07

Table 5 shows the classification results on the CMS Open Data Dielectron dataset which includes J/ψ signal and background events. Overall, most models demonstrated their effectiveness in distinguishing signal and background events with test accuracy exceeding 97% and high AUC scores. The weighted F1 scores of the models indicated that they resolved class imbalance and produced reliable probabilistic outputs.

The DNN model achieved excellent results with 98.11% train accuracy, 97.98% test accuracy, 98.37% train AUC and 97.68% test AUC. These results demonstrate the model’s good generalization and strong discriminatory power. The slight decrease in AUC from train to test suggests minor overfitting but overall it’s clear that the DNN is a robust and well-calibrated choice for this task. Weighted F1 scores of 97.06% for both train and test demonstrate the model’s balanced performance in classifying both signal and background events.

Gradient boosting models (XGBoost, CatBoost and LightGBM) showed exceptionally good performance particularly in the AUC metric. XGBoost

achieved excellent class separation and probabilistic calibration with the highest AUC scores of 99.97% (train) and 98.58% (test). However, the model's test accuracy of 97.37% was slightly lower than DNN and AdaBoost indicating minor overfitting. With a weighted F1 score of 97.75% XGBoost proved successful not only in accuracy but also for both classes. CatBoost and LightGBM also performed competitively: CatBoost matched XGBoost with 97.26% test accuracy and 98.56% test AUC. These models demonstrated the high performance of boosting in complex and nonlinear high-energy physics data interactions. Weighted F1 scores of 97.72% for LightGBM and 97.74% for CatBoost indicate minimal overfitting and strong generalization with their success in both metrics.

The Random Forest model achieved excellent performance with 100% accuracy and AUC indicating clean overfitting further demonstrating that deep tree ensembles are more likely to experience regularization-free overfitting. Nevertheless the test accuracy is strong at 97.97% and the AUC at 98.55%. While its predictive power is competitive with boosting methods the risk of overfitting necessitates careful tuning (e.g., limiting tree depth, feature selection) which does not negate the fact that the model will not achieve strong generalization. A test weighted F1 score of 97.44% indicates that despite overfitting during training the model still generalizes effectively to the test data and achieves reliable classifications.

AdaBoost maintains its consistency achieving 98.03% accuracy across both train and test. Its AUC scores are 98.66% (train) and 98.61% (test). This consistency across metrics indicates excellent generalization and well-calibrated probability estimation. Compared to its competitors XGBoost and CatBoost; AdaBoost's performance is a strong, lightweight alternative. AdaBoost's F1 scores which are 97.06% weighted for both train and test demonstrate that the model produces reliable output.

Logistic Regression and SVM models performed relatively poorly compared to ensemble and deep learning methods. Logistic Regression with a test accuracy of 91.63% and a respectable AUC of 96.72% demonstrated that it effectively captured linear trends but struggled with complex relationships. Linear SVM (91.14% accuracy) and RBF SVM (91.30%) delivered similar results. Their AUC scores (97.07 - 97.25% train; 96.89 - 97% test) were strong but still lower than the top-performing models. This demonstrates the limitations of traditional SVMs on such deep nonlinear data. The weighted F1 scores (94.18% for Logistic Regression, 94.02% for Linear SVM and 93.14% for RBF

SVM) are relatively high indicating that these models while not as powerful as ensemble methods still offer some useful insights particularly in simpler or well-structured datasets.

The kNN model demonstrates efficient classification with 98.31% accuracy in training and 97.70% accuracy in testing. However the test AUC drops dramatically to 80.47% while the train AUC is 98.34%. This distinction demonstrates that kNN can accurately classify similar training examples but fails to achieve good-calibrated confidence scores on unseen data. The sharp rejection in AUC reflects the standard challenges kNN faces in real-world datasets ranging from sensitivity to noise, class imbalance and high-dimensional feature space. The test weighted F1 score of 97.07% indicates that kNN classifies examples well but is inferior to AdaBoost and XGBoost.

In summary, ensemble models such as XGBoost, CatBoost and AdaBoost achieved the best overall performance combining high accuracy with well-calibrated probability outputs. DNN also produced robust and balanced results. Random Forest also performed well but caution is needed regarding overfitting. Simpler models such as Logistic Regression and SVMs performed poorly in comparison. While kNN achieved high accuracy its low AUC suggests unreliable rating or probability estimation on the test data. These findings demonstrate the advantages of advanced ensemble methods and neural networks on the fine-tuned datasets found in complex and high-energy physics experiments. Furthermore the weighted F1 scores across all models indicate that models such as AdaBoost and XGBoost produce more reliable, balanced and interpretable results for both classes even when only accuracy was high.

To evaluate our approach compare our results with those reported in related studies. Kuzu (2022) applied the Random Forest classifier to a similar dielectron dataset achieving an AUC of 98.2% and an F1 score of 90.7%. Our Random Forest model achieved a slightly higher AUC of 98.55% and a significantly improved F1 score of 97.53% providing better classification stability and improved generalization. The weighted F1 score improvements allow our model to surpass previous models in this field through refined feature engineering and class balancing.

Furthermore a study by Yalçın Kuzu et al. (2025) applied DNN to CMS data focusing on $J/\psi \rightarrow e^+e^-$ decays achieving an AUC of 99.77% and an F1 score of 98.25%. Our DNN model achieved slightly lower AUCs of 97.68% and 97.06% respectively suggesting that our overall results are competitive. Note that the tree-based models in our study XGBoost and LightGBM eliminate

DNN in the AUC metric making gradient boosting methods the best choices for this specific classification task.

These comparisons demonstrate that deep learning and ensemble learning techniques when finely tuned and combined with effective preprocessing and class balancing strategies yield robust and interpretable results. Separating rare decays such as the J/ψ meson from the background is a challenging yet fundamental task especially in high-energy physics. By integrating the weighted F1 score we ensured that model evaluation not only accurately but also produces reliable probability estimates of class imbalance.

Table 6. Test AUC Scores (%) of All Models Across Datasets

Method	Higgs Test AUC	Beam Test AUC	Dielectron Test AUC
DNN	93.03	99.89	97.68
LightGBM	92.32	99.87	98.56
XGBoost	93.17	99.89	98.58
CatBoost	92.63	99.91	98.56
Random Forest	91.90	99.98	98.55
Logistic Regression	88.09	99.89	96.72
Linear SVM	87.92	99.89	97.07
RBF SVM	88.48	99.89	97.25
AdaBoost	90.18	99.98	98.61
kNN	86.80	99.98	80.47

Table 6 summarizes the test AUCs of various classification models across different datasets: CERN Higgs Boson, CMS Beam Condition and CMS Open Data Dielectron. These results demonstrate the dependence of model performance on dataset complexity and structure and the robust and consistent results of ensemble methods.

CERN Higgs Boson Dataset

Test AUC scores on the Higgs dataset are relatively lower and more dispersed compared to the other datasets, suggesting a more complex classification problem:

- The highest AUC values are achieved by XGBoost (93.17%) and DNN (93.03%) indicating strong discriminative performance.

- CatBoost (92.63%) and Random Forest (91.90%) also perform reasonably well although signs of overfitting are likely for Random Forest.
- Simpler models such as Logistic Regression (88.09%), AdaBoost (90.18%) and kNN (86.80%) show weaker separation capability reflecting their limitations in modeling complex, non-linear boundaries.
- While Linear and RBF SVMs achieve moderate AUCs (~88%) their performance remains below that of ensemble and neural network models.

The Higgs dataset poses a significant challenge due to overlapping class distributions and subtle decision boundaries. High-performing models need strong capacity for nonlinear feature interactions and robust generalization.

CMS Beam Condition Dataset

In contrast this dataset is highly separable with nearly all models achieving AUC scores above 99.8%:

- Random Forest, AdaBoost and kNN each achieve 99.98% test AUC indicating that even simple decision mechanisms can distinguish between classes effectively.
- Boosting models such as CatBoost (99.91%), XGBoost (99.89%) and LightGBM (99.87%) also perform exceptionally.
- Even Logistic Regression (99.89%) and SVMs (99.89%) reach near-perfect scores despite their linear nature.

The Beam Condition dataset appears to be very clean and well-structured allowing models of varying complexity to perform with near-identical success. Model choice is less critical here due to the dataset's simplicity.

CMS Open Data Dielectron Dataset

Performance on the Dielectron dataset is again high particularly for ensemble methods:

- XGBoost (98.58%), CatBoost (98.56%), LightGBM (98.56%) and AdaBoost (98.61%) achieve top AUC scores with Random Forest (98.55%) closely behind.
- The DNN performs slightly lower (97.68%) but still competitively offering a good balance of accuracy and generalization.
- Logistic Regression (96.72%), Linear SVM (97.07%) and RBF SVM (97.25%) maintain solid but not top-tier performance.

- Notably kNN sees a sharp drop in test AUC to 80.47% despite strong test accuracy. This discrepancy highlights poor calibration and unreliability in ranking predictions especially in high-dimensional physics-based data.

While most models perform well on this dataset kNN's poor AUC underscores the importance of not relying solely on accuracy particularly in scientific domains where confidence and probability estimation are critical.

6. Conclusion

This study conducted a comprehensive evaluation of various machine learning models including deep neural networks (DNNs), ensemble tree-based methods and traditional classifiers across three high-energy physics datasets: CERN Higgs Boson, CMS Beam Condition and CMS Open Data Dielectron. The results underscore the superior performance of gradient boosting algorithms particularly XGBoost and CatBoost which consistently delivered the highest AUC scores across all datasets demonstrating excellent generalization and robustness even in more challenging classification tasks. DNNs also showed competitive and stable performance especially on the complex Higgs dataset but gradient boosting methods generally outperformed them on structured datasets like Dielectron highlighting the power of boosting techniques in modeling nonlinear feature interactions effectively.

The analysis revealed key differences in dataset complexity: the Higgs Boson dataset proved to be the most challenging with more dispersed AUC scores and a greater reliance on complex models for optimal performance. In contrast the Beam Condition dataset was highly separable enabling even simple models like kNN and logistic regression to achieve near-perfect AUCs. The Dielectron dataset represented an intermediate level of difficulty where most models performed well though kNN's poor AUC (despite its high accuracy) emphasized the importance of evaluating ranking metrics like AUC in scientific applications.

While Random Forests demonstrated strong accuracy they showed signs of overfitting especially in complex datasets like Higgs suggesting a lower robustness compared to boosting methods. Linear models maintained moderate AUCs but were generally outperformed by more expressive algorithms.

In conclusion this study highlights the importance of gradient boosting techniques particularly XGBoost and CatBoost as reliable and high-performing models for particle physics classification tasks. Their consistent success across

varied datasets supports further research into hybrid models that combine the interpretability and stability of DNNs with the predictive power of ensemble methods. Future work could also focus on enhancing feature engineering, fine-tuning hyperparameters and exploring model calibration to improve performance across different dataset complexities.

References

1. Adam-Bourdarios, C., Cowan, G., Germain, C., Guyon, I., Kégl, B., & Rousseau, D. (2015). The Higgs boson machine learning challenge. Proceedings of the NIPS 2014 Workshop on High-energy Physics and Machine Learning, in Proceedings of Machine Learning Research, 42, 19–55. Retrieved from <https://proceedings.mlr.press/v42/cowal14.html>
2. ATLAS Collaboration. (2012). Observation of a new particle in the search for the Standard Model Higgs boson with the ATLAS detector at the LHC. Physics Letters B, 716(1), 1–29. <https://doi.org/10.1016/j.physletb.2012.08.020>
3. CERN Open Data Portal. (2014). CMS Primary Dataset: MuOnia (Run2010B-PromptReco-v2). CERN. <https://opendata.cern.ch/record/302>
4. CERN Open Data Portal. (2014). CMS Primary Dataset: Dimuon (Run2010B-PromptReco-v2). CERN. <https://opendata.cern.ch/record/304>
5. CERN Open Data Portal. (2017). CMS Open Data Guide for Event Analysis – 2010 CMS Data with 35 pb⁻¹ of Luminosity. CERN. <https://opendata.cern.ch/record/1050>
6. Baldi, P., Sadowski, P., & Whiteson, D. (2014). Searching for exotic particles in high-energy physics with deep learning. Nature Communications, 5, 4308. <https://doi.org/10.1038/ncomms5308>
7. Duarte, J., et al. (2018). Fast inference of deep neural networks in FPGAs for particle physics. Journal of Instrumentation, 13(07), P07027. <https://doi.org/10.1088/1748-0221/13/07/P07027>
8. DeHolton, K. L., & IceCube Collaboration. (2021). Low energy event classification in IceCube using boosted decision trees. Journal of Instrumentation, 16(12), C12007.
9. Acciarri, R., et al. “A deep-learning based raw waveform region-of-interest finder for the liquid argon time projection chamber.” Journal of Instrumentation 17.01 (2022): P01018.
10. Liu, Junze, et al. “Deep-learning-based kinematic reconstruction for DUNE.” arXiv preprint arXiv:2012.06181 (2020).

11. Qian, Zhen, et al. "Vertex and energy reconstruction in JUNO with machine learning methods." *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment* 1010 (2021): 165527.
12. Arnquist, I. J., et al. "Majorana Demonstrator Data Release for AI/ML Applications." *arXiv preprint arXiv:2308.10856* (2023).
13. Rodriguez, Manuel J. "Fast inference using FPGAs for DUNE data reconstruction." *EPJ Web of Conferences*. Vol. 245. EDP Sciences, 2020.
14. Abratenko, P., et al. "Semantic segmentation with a sparse convolutional neural network for event reconstruction in MicroBooNE." *Physical Review D* 103.5 (2021): 052012.
15. Mo, Xishuo, et al. "CNN-LSTM based automatic classification network for multi-type with multi-energy charged particle identification." *Applied Sciences* 15.4 (2025): 1837.
16. G., Li, et al. "Improving the measurement of the Higgs boson-gluon coupling using convolutional neural networks at e^+e^- colliders." *arXiv preprint arXiv:1901.09391* (2019).
17. Abbas, Muhammad, et al. "Extracting signals of Higgs boson from background noise using deep neural networks." *arXiv preprint arXiv:2010.08201* (2020).
18. Baldi, Pierre, et al. "Enhanced Higgs to $\tau^+\tau^-$ searches with deep learning." *arXiv preprint arXiv:1410.3469* (2014).
19. Bat, A. (2023). An educational approach to Higgs boson hunting using machine learning classification algorithms on ATLAS Open Data. *Journal of Advanced Research in Natural and Applied Sciences*. DOI: 10.28979/jarnas.1242840
20. Yalçın Kuzu, S., Karasu Uysal, A., & Kaya, M. (2025). Neural network-based approaches to high-energy physics. *International Journal of Data Science and Applications*, 8(1), 1–10.
21. Kuzu, S. Y. (2021). Artificial intelligence based machine learning approach in high energy physics. *International Journal of Innovative Engineering Applications*, 5(2), 176–180.
22. Kuzu, S. Y. (2022). Makine öğrenmesi yöntemi ile dielektron çiftlerinin tanımlanması. *Balıkesir Üniversitesi Fen Bilimleri Enstitüsü Dergisi*, 24(1), 349-358.
23. Pedregosa, Fabian, et al. "Scikit-learn: Machine Learning in Python." *Journal of Machine Learning Research* 12 (2011): 2825-2830.

24. Breiman, L. (2001). Random forests. *Machine Learning*, 45(1), 5–32. <https://doi.org/10.1023/A:1010933404324>
25. Chen, Tianqi, and Carlos Guestrin. “XGBoost: A Scalable Tree Boosting System.” *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2016, pp. 785-794. DOI: 10.1145/2939672.2939785
26. Prokhorenkova, L., Gusev, G., Vorobev, A., Dorogush, A. V., & Gulin, A. (2018). CatBoost: Unbiased boosting with categorical features. *Advances in Neural Information Processing Systems*, 31, 6638–6648.
27. Ke, Guolin, et al. “LightGBM: A Highly Efficient Gradient Boosting Decision Tree.” *Advances in Neural Information Processing Systems* 30 (2017): 3146-3154.
28. Cover, T., & Hart, P. (1967). Nearest neighbor pattern classification. *IEEE Transactions on Information Theory*, 13(1), 21–27. <https://doi.org/10.1109/TIT.1967.1053964>
29. Hosmer, D. W., Lemeshow, S., and Sturdivant, R. X. (2013). *Applied logistic regression* (3rd ed.). Wiley.
30. Fan, R.-E., Chang, K.-W., Hsieh, C.-J., Wang, X.-R., & Lin, C.-J. (2008). LIBLINEAR: A library for large linear classification. *Journal of Machine Learning Research*, 9, 1871–1874.
31. Chang, C.-C., & Lin, C.-J. (2011). LIBSVM: A library for support vector machines. *ACM Transactions on Intelligent Systems and Technology*, 2(3), 1–27. <https://doi.org/10.1145/1961189.1961199>
32. Freund, Y., & Schapire, R. E. (1997). A decision-theoretic generalization of on-line learning and an application to boosting. *Journal of Computer and System Sciences*, 55(1), 119–139. <https://doi.org/10.1006/jcss.1997.1504>
33. Python Software Foundation. (2023). *Python Language Reference*, version 3.11. Retrieved from <https://www.python.org>
34. Abadi, M., Barham, P., Chen, J., Chen, Z., Davis, A., Dean, J., ... & Zheng, X. (2016). TensorFlow: A system for large-scale machine learning. In *12th USENIX Symposium on Operating Systems Design and Implementation (OSDI 16)* (pp. 265-283). Retrieved from <https://www.usenix.org/system/files/conference/osdi16/osdi16-abadi.pdf>
35. Chollet, F. (2015). Keras [Computer software]. <https://keras.io>
36. Kingma, D. P., & Ba, J. (2015). Adam: A method for stochastic optimization. *International Conference on Learning Representations (ICLR)*. <https://arxiv.org/abs/1412.6980>

CHAPTER IX

EMERGING TRENDS IN IOT-DRIVEN GENERATIVE ARTIFICIAL INTELLIGENCE APPLICATIONS FOR AGRICULTURAL ENTERPRISES

Şükrü Mustafa KAYA

*(Assist. Prof. Dr.), Istanbul Aydin University,
Department of Computer Technologies, İstanbul, Turkey
E-mail: mustafakaya@aydin.edu.tr
ORCID: 0000-0003-2710-0063,*

1. INTRODUCTION

The unprecedented growth of the global population continues to exert increasing pressure on agricultural production systems. This demographic expansion not only compels higher production volumes but also demands the sustainable and efficient utilization of limited natural resources. Within this framework, the adoption of digital technologies in agricultural enterprises enables the establishment of a more efficient, transparent, and adaptive production infrastructure that transcends conventional agricultural practices. Among the most transformative components of this digital transformation are the Internet of Things (IoT) and Generative Artificial Intelligence (GAI) technologies.

IoT facilitates the real-time acquisition of data related to soil moisture, climatic conditions, crop health, livestock activity, and various environmental parameters through sensors, actuators, and embedded systems distributed across agricultural fields. Transforming this raw data into actionable insights and incorporating it into intelligent decision-support mechanisms has become increasingly feasible through the use of advanced artificial intelligence algorithms. AI models enriched with deep learning, machine learning, and statistical modeling techniques—complemented by generative approaches—are capable of identifying complex data patterns to perform predictive tasks such as

disease detection, optimized irrigation scheduling, feed management, and yield estimation.

Given the dynamic and highly variable nature of agricultural ecosystems, decision-making processes must often occur rapidly and in response to changing environmental factors. Consequently, deploying IoT-based AI applications on edge and fog computing architectures significantly enhances data processing efficiency and ensures prompt, field-specific responsiveness. Nonetheless, the integration of these technologies into the agricultural domain requires comprehensive evaluation from economic, technical, environmental, and socio-cultural perspectives.

Accordingly, this chapter seeks to explore recent advancements in the convergence of IoT and generative artificial intelligence technologies within agricultural enterprises. It aims to analyse the applications and methodologies discussed in the current literature and to elucidate the transformative potential of these technologies for achieving sustainable and data-driven agricultural development.

2. RELATED WORKS

In recent years, smart farming systems that integrate cutting-edge technologies such as Generative Artificial Intelligence (GAI), the Internet of Things (IoT), big data analytics, and cloud computing have emerged as a significant domain of scholarly research. These systems aim to enhance agricultural productivity, optimize the utilization of natural and technological resources, and promote environmental sustainability through data-driven and automated processes.

For example, Zhang, Huang, and Guo (2023) conducted a comprehensive analysis of the architecture and implementation domains of digital twin technologies in agriculture, demonstrating that the real-time acquisition of sensor data and the integration of cloud-based analytical models substantially enhance operational efficiency. Their research underscores that digital twins, when complemented by Generative Artificial Intelligence (GAI) and IoT infrastructures, constitute a pivotal tool for the simulation, prediction, and optimization of agricultural processes.

Peladarinos et al. (2023), in their study on the utilization of digital twin technologies within greenhouse environments, observed that beyond sensor-based data acquisition, monitoring climatic and environmental conditions through digital twins has a significant positive impact on both energy efficiency

and plant health. Furthermore, Palacios et al. (2024) emphasized the crucial role of the integrated Cloud–Fog–Edge computing architecture in managing complex and dynamic agricultural ecosystems, highlighting its substantial contribution to real-time analytics and decision-making processes. When combined with Generative Artificial Intelligence (GAI) models, these architectures further enhance the adaptability and predictive capacity of smart agricultural systems.

The detection and management of agricultural pests constitute a crucial challenge that directly influences crop productivity and overall yield stability. Padma Priya et al. (2024) introduced an intelligent detection framework based on the YOLOv8 algorithm, delivering a robust artificial intelligence solution for the early identification and mitigation of pest infestations. In a similar vein, Zheng et al. (2024) proposed the Rice-YOLO model, which enables high-precision pest recognition in rice cultivation environments, offering a practical and scalable tool for real-world field applications. Furthermore, Yin et al. (2024) reported over 95% accuracy in pest detection through a lightweight YOLOv8 model enhanced with attention mechanisms. Collectively, these studies demonstrate that the integration of Generative Artificial Intelligence (GAI) with advanced deep learning architectures can substantially enhance the precision, adaptability, and efficiency of pest detection systems in smart agriculture.

In the context of greenhouse management, Wang (2024) highlighted that the integration of digital twin frameworks with Internet of Things (IoT) systems enables precise and dynamic control of indoor climatic parameters. This integration offers substantial advantages, including enhanced monitoring of plant physiological conditions and significant reductions in overall energy consumption. Moreover, the adoption of edge computing–supported real-time data processing architectures has improved both the scalability and responsiveness of greenhouse management systems. When augmented with Generative Artificial Intelligence (GAI)–driven predictive analytics, these integrated architectures further strengthen autonomous decision-making capabilities, ensuring optimized environmental regulation and sustainable resource utilization.

Within the framework of the industry 4.0 paradigm, Falcão, Matar, and Rauch (2023) examined the utilization of digital twin technologies in agriculture, providing a detailed exploration of their architectural components and the adaptation mechanisms required for agricultural applications. The study also identified key research gaps and ongoing challenges that warrant further investigation. Recent advancements in LoRaWAN-based implementations

further substantiate the practical applicability of IoT in agricultural contexts. For instance, Valente et al. (2022) presented a vineyard-based case study demonstrating continuous and reliable monitoring of vine water status through LoRaWAN-enabled sensors, underscoring the technology's cost-effectiveness and extended coverage range for remote agricultural areas. Similarly, Codeluppi et al. (2020) proposed the LoRaFarM architecture to standardize IoT deployment, thereby enhancing its accessibility and scalability for smallholder farmers.

The integration of IoT with blockchain technologies has also emerged as a transformative approach to ensuring transparency, traceability, and trust in agri-food supply chains. Kaur et al. (2023) demonstrated that coupling IoT sensors with blockchain-based smart contracts can secure sensor data integrity and strengthen data credibility, although they also emphasized persisting challenges such as implementation costs and interoperability constraints. Complementary to this, Gondal et al. (2023) and Pranto et al. (2021) proposed blockchain–IoT frameworks designed to automate pre- and post-harvest processes, thereby improving data authenticity, optimizing workflow efficiency, and promoting equitable compensation mechanisms.

When augmented with Generative Artificial Intelligence (GAI) models, these interconnected systems gain enhanced analytical depth, enabling predictive insights, anomaly detection, and autonomous decision-making that collectively advance the vision of intelligent, transparent, and sustainable agricultural ecosystems.

3. IoT AND SMART AGRICULTURAL MANAGEMENT

The agricultural sector has increasingly adopted technological innovations to overcome the limitations of traditional methods in enhancing productivity and optimizing resource management. At the core of this digital transformation lies the Internet of Things (IoT), which denotes an interconnected network of physical devices capable of communicating and exchanging data autonomously. Within the agricultural context, IoT enables farmers to exercise greater control and optimization over production processes through the integration of sensors, intelligent devices, cloud computing infrastructures, and advanced data analytics systems (Wolfert et al., 2017). The implementation of IoT in smart agriculture encompasses a wide spectrum of applications, including the monitoring of environmental parameters, automation of irrigation systems, livestock tracking, and crop logistics management. When combined with Generative Artificial Intelligence (GAI) models, IoT-based systems further enhance decision-making

accuracy and predictive capabilities, thereby advancing precision agriculture and sustainable production practices.

3.1. Basic Components of IoT Technologies

The Internet of Things (IoT) architecture designed for agricultural enterprises typically comprises four fundamental layers, as illustrated in Figure 1. The first is the perception or sensing layer, which includes various sensors and data acquisition nodes responsible for collecting environmental and operational information. The subsequent layers are the network layer, which ensures data transmission and communication; the service layer, which manages data processing and storage; and the application layer, which delivers intelligent services and user-oriented functionalities. Together, these interconnected layers establish the foundation for smart agricultural systems capable of real-time monitoring, data-driven decision-making, and process automation.




Figure 1. IoT Components

✓ **Sensing Layer (Sensors and Data Acquisition Devices):** The sensing layer comprises a variety of sensors designed to monitor key environmental and agronomic variables such as soil moisture, temperature, pH level, and light intensity. These sensors provide farmers with critical insights into plant

growth conditions, irrigation requirements, and optimal fertilization schedules (Zhang et al., 2020). Once deployed in the field, the sensors periodically capture environmental data and transmit it to a centralized system for further processing and analysis. When integrated with Generative Artificial Intelligence (GAI) models, the collected data can be transformed into predictive insights, enabling more accurate and proactive agricultural management decisions.

✓ **Network Layer (Wired and Wireless Communication Technologies):**

The network layer is responsible for ensuring the reliable transmission of data collected by sensors to higher-level systems through both wired and wireless communication technologies. IoT-based agricultural systems commonly employ energy-efficient and long-range communication protocols such as LoRaWAN, ZigBee, NB-IoT, and Wi-Fi, which facilitate continuous data exchange even across extensive agricultural fields (Jawad et al., 2017). These communication frameworks minimize power consumption while maintaining stable connectivity, thereby enabling real-time monitoring and seamless integration of distributed sensing networks. When complemented by Generative Artificial Intelligence (GAI) algorithms, the network layer also supports adaptive data routing and predictive maintenance mechanisms, enhancing the overall robustness of smart agricultural infrastructures.

✓ **Service Layer (Cloud Computing and Data Processing):** The service layer is responsible for transferring the data collected from IoT devices to cloud-based platforms, where it is processed, analyzed, and transformed into actionable insights. Within this framework, cloud computing provides scalable storage and computational resources, enabling the efficient handling of large and heterogeneous agricultural datasets. When integrated with artificial intelligence-driven analytical tools, the IoT infrastructure establishes the foundation of real-time decision support systems that facilitate predictive analysis, operational optimization, and adaptive management (Verdouw et al., 2021). The incorporation of Generative Artificial Intelligence (GAI) further enhances this layer by enabling advanced modeling, synthetic data generation, and scenario-based forecasting, which collectively contribute to more precise and sustainable agricultural decision-making.

✓ **Interface Layer (Mobile and Web Based Applications):** The interface layer enables farmers to remotely monitor, visualize, and manage agricultural data through user-friendly mobile and web-based applications. These digital interfaces allow the execution of various operational functions such as activating or deactivating irrigation systems, receiving automated alerts, and generating

real-time analytical reports (Kaya, Ş. M. et al., 2023). By integrating Generative Artificial Intelligence (GAI) models into these platforms, interactive dashboards can be enhanced with predictive recommendations, natural language interaction, and intelligent decision-assistance features. This integration not only simplifies system management but also supports data-driven and proactive agricultural practices, fostering a more responsive and efficient smart farming ecosystem.

4. GENERATIVE ARTIFICIAL INTELLIGENCE ON SMART AGRICULTURE MANAGEMENT

The agricultural sector has entered an era of profound technological transformation aimed at overcoming the inherent constraints of conventional farming methods and establishing a sustainable, data-driven production paradigm. At the core of this transformation lies Artificial Intelligence (AI), which has become a fundamental enabler of intelligent and adaptive agricultural systems. Through the application of predictive modeling, decision-support mechanisms, image recognition, machine learning, and autonomous control systems, AI enhances the effectiveness, efficiency, and environmental sustainability of modern agricultural management (Liakos et al., 2018). Furthermore, the integration of Generative Artificial Intelligence (GAI) introduces new dimensions to smart agriculture by enabling synthetic data generation, scenario simulation, and adaptive model optimization—capabilities that strengthen both precision farming and long-term sustainability strategies.

Artificial intelligence-driven applications have become instrumental in optimizing a wide range of agricultural activities—from tillage and crop management to harvesting—by enabling farmers to make informed, data-driven decisions. When the scope of AI-based agricultural applications is examined, it becomes evident that their contributions and challenges must be comprehensively identified and evaluated (Atapattu et al., 2024). On the one hand, artificial intelligence enhances agricultural efficiency by promoting optimal resource utilization, minimizing input and labor costs, automating complex operational processes, conserving natural resources, and facilitating site-specific interventions that increase productivity and precision. On the other hand, several challenges persist, including the requirement for extensive and high-quality datasets to train high-accuracy models, substantial investment costs in technological infrastructure—particularly for small and medium-sized farmers—the need for specialized technical expertise to install and operate AI systems, and ongoing ethical debates regarding data ownership, sharing,

and privacy (Vardhan et al., 2025). Beyond the optimization of conventional agricultural practices, Generative Artificial Intelligence (GAI) has introduced transformative capabilities to the sector. GAI-driven models enable synthetic data generation, multi-scenario forecasting, and adaptive learning mechanisms that overcome data scarcity and enhance model generalizability. Empirical evidence supports these advancements: recent studies have reported that AI-powered precision agriculture systems achieved up to a 30% reduction in water consumption and a 20% decrease in fertilizer usage without compromising crop yield (Gangwani, 2024). Nevertheless, barriers to adoption remain pronounced among smallholder farmers. Systematic reviews have indicated that limited access to localized, high-quality data and inadequate digital infrastructure continue to disproportionately impede small-scale producers (Singh et al., 2024). Moreover, research on data representation bias has revealed that many AI datasets predominantly reflect large-scale industrial farms, resulting in underrepresentation and reduced accuracy for smallholder agricultural contexts (Atapattu et al., 2025).

In summary, while artificial intelligence and generative AI technologies collectively enhance resource-use efficiency and operational precision, equitable access to these innovations remains a critical concern. Figure 2 illustrates selected application domains that can be effectively managed through AI- and GAI-supported smart agricultural enterprise systems.




Figure 2: Smart Agricultural Management

✓ **Plant Disease Detection and Image Processing:** The early identification of plant diseases is a vital component of sustainable agricultural management, as timely intervention is essential to prevent substantial yield losses. Artificial intelligence–assisted image processing techniques enable the detection and classification of disease symptoms from images of leaves, fruits, and stems, analyzing micro-patterns and spectral features that are often imperceptible to the human eye. These diagnostic systems predominantly employ neural network architectures—particularly deep learning models such as Convolutional Neural Networks (CNNs)—to achieve high detection accuracy (Kamilaris & Prenafeta-Boldú, 2018). For instance, a CNN model trained on thousands of images depicting leaf spot disease in apple trees has demonstrated over 90% classification accuracy, enabling the precise identification of infected specimens. By supporting targeted pesticide application, these systems minimize chemical overuse and consequently reduce the environmental footprint of crop protection practices. Furthermore, the integration of Generative Artificial Intelligence (GAI) enhances these frameworks by enabling the creation of synthetic plant disease datasets, facilitating model generalization, and improving detection performance in data-scarce environments. As a result, AI- and GAI-supported image analysis systems represent a significant advancement toward more resilient and ecologically responsible crop health management.

✓ **Predictive Modelling and Crop Yield Forecasting:** Predictive modeling plays a pivotal role in smart agriculture by enabling data-driven estimations of crop yields based on both historical and real-time environmental inputs. Machine learning algorithms analyze multidimensional datasets that encompass meteorological parameters, soil moisture levels, fertilizer usage, and other agronomic variables to forecast production outcomes with high accuracy. Such predictive insights empower farmers to plan resources efficiently, optimize input allocation, and adopt more informed and sustainable cultivation strategies. For instance, Support Vector Machines (SVMs) and Decision Tree–based algorithms such as Random Forest have demonstrated yield prediction accuracies ranging between 80% and 90% for major crops like corn and wheat (Zhang et al., 2020). Beyond these conventional methods, the integration of Generative Artificial Intelligence (GAI) introduces enhanced modeling capabilities by synthesizing realistic agricultural datasets and simulating variable climatic or environmental conditions. These generative models not only improve the robustness and adaptability of predictive systems but also facilitate scenario-based forecasting that supports long-term strategic planning in precision agriculture.

✓ **Autonomous Agricultural Machinery and Robotic Systems:** Artificial intelligence–driven robotic systems have revolutionized agricultural operations by autonomously performing essential tasks such as sowing, weeding, spraying, and harvesting—significantly reducing the need for direct human intervention. Autonomous tractors and harvesters, equipped with advanced sensor arrays and GPS-guided navigation technologies, execute field operations with remarkable precision, thereby lowering labor costs while enhancing operational efficiency and consistency Yépez-Ponce et al., (2023). Moreover, AI-powered harvesting robots utilize computer vision and deep learning algorithms to assess fruit maturity levels and selectively pick only the produce that meets predefined quality parameters, thus improving overall quality control and minimizing post-harvest losses. The integration of Generative Artificial Intelligence (GAI) further amplifies these capabilities by enabling continuous learning from synthetic field data, simulating diverse environmental and crop conditions, and optimizing robotic behavior for varying agricultural contexts. Consequently, GAI-augmented robotic systems not only advance automation but also contribute to the creation of intelligent, adaptive, and sustainable agricultural ecosystems (Yépez-Ponce et al., 2023; Ju et al., 2022).

✓ **Smart Irrigation Systems:** The efficient management of water resources has become a critical priority in mitigating the adverse effects of climate change and promoting sustainable agricultural practices. Artificial intelligence–assisted irrigation systems play a vital role in achieving this goal by analyzing real-time data collected from soil moisture sensors to ensure that crops receive only the necessary amount of water. Concurrently, irrigation schedules are optimized through the integration of meteorological data and predictive analytics, which enables precise timing of water delivery according to environmental conditions and crop requirements (Wolfert et al., 2017). These intelligent irrigation frameworks have demonstrated the potential to reduce water consumption by 30–50%, while simultaneously supporting plant growth and improving yield performance. When enhanced with Generative Artificial Intelligence (GAI), such systems can simulate diverse climatic scenarios, generate synthetic soil-moisture datasets, and develop adaptive irrigation strategies that respond dynamically to real-time environmental fluctuations. As a result, GAI-integrated smart irrigation solutions contribute to both resource conservation and sustainable productivity in precision agriculture.

An analysis of the current literature and existing artificial intelligence applications in agricultural enterprises reveals that AI possesses a profoundly

transformative role in advancing smart agricultural management. Through data-driven decision-making processes, agricultural systems are achieving substantial improvements in both production efficiency and environmental sustainability, contributing to the broader goals of precision agriculture and resource optimization. Nevertheless, this technological transformation must extend beyond the digital and technical domains to encompass social, educational, and economic dimensions. Ensuring the widespread adoption and equitable implementation of AI and Generative Artificial Intelligence (GAI) in rural contexts requires a multidimensional approach supported by training initiatives, financial incentives, and strategic public policies. These components will be instrumental in fostering digital literacy, strengthening rural innovation capacity, and building sustainable smart farming ecosystems that integrate human expertise with intelligent, adaptive technologies.

5. CONCLUSION

This chapter has demonstrated that the convergence of the Internet of Things (IoT) and Artificial Intelligence particularly Generative Artificial Intelligence (GAI) is reshaping agricultural management by enabling data-centric, adaptive, and resource-efficient practices. Across sensing, networking, service, and interface layers, IoT infrastructures furnish continuous, high-resolution streams of environmental and operational data. When fused with discriminative and generative models, these data flows support robust analytics for early disease detection, yield forecasting, smart irrigation, and autonomous field operations, thereby elevating productivity while curbing input intensity and ecological burden.

Empirical evidence synthesized in this work indicates that AI-enabled decision support can reduce water consumption, optimize fertilization, and enhance harvest quality without compromising yields. GAI extends these gains by generating synthetic yet realistic datasets, facilitating model training under data scarcity, scenario simulation under variable climate regimes, and continuous adaptation to shifting field conditions. In parallel, edge/fog computing architectures improve responsiveness and scalability, enabling near-real-time inference in geographically dispersed and connectivity-constrained settings.

Notwithstanding these benefits, several structural barriers continue to temper widespread adoption. High upfront costs for sensing and automation, uneven digital infrastructure—especially among smallholders—limited availability of localized, high-quality datasets, and interoperability gaps across heterogeneous platforms remain consequential constraints. Ethical and governance concerns

around data ownership, privacy, and equitable value sharing also require careful stewardship to maintain stakeholder trust across agri-food value chains.

To accelerate inclusive diffusion, we recommend a multi-pronged agenda: (i) targeted capacity-building and digital literacy programs tailored to small and medium-scale producers; (ii) open, standardized data schemas and interoperable APIs to reduce integration frictions; (iii) public–private financing mechanisms and result-based incentives that de-risk initial investments; and (iv) transparent data governance frameworks that clarify rights, responsibilities, and benefit-sharing. From a research standpoint, priorities include developing lightweight, domain-adapted models that perform reliably on sparse, noisy, and imbalanced datasets; advancing explainable and trustworthy AI for safety-critical decisions; and designing human-in-the-loop workflows that combine agronomic expertise with algorithmic intelligence.

In sum, the strategic alignment of IoT infrastructures with both discriminative AI and generative techniques offers a credible pathway toward resilient, precise, and sustainable agricultural systems. Realizing this potential at scale will depend on concomitant progress in technical standardization, socio-economic enablement, and policy innovation, ensuring that digital transformation delivers measurable value for producers, ecosystems, and society at large.

Statements and Declarations: The authors certify that they have no affiliations with or involvement in any organization or entity with any financial interest or non-financial interest in the subject matter or materials discussed in this manuscript.

Funding: Not applicable. The authors did not receive support from any organization for the submitted work.

Competing interests: Author declares no competing interests.

Consent for publication Not applicable.

REFERENCES

Atapattu, A.J., Perera, L.K., Nuwarapaksha, T.D., Udumann, S.S., Dissanayaka, N.S. (2024). Challenges in Achieving Artificial Intelligence in Agriculture. In: Chouhan, S.S., Saxena, A., Singh, U.P., Jain, S. (eds) *Artificial Intelligence Techniques in Smart Agriculture*. Springer, Singapore. https://doi.org/10.1007/978-981-97-5878-4_2

Codeluppi G, Cilfone A, Davoli L, Ferrari G. LoRaFarM (2020): A LoRaWAN-Based Smart Farming Modular IoT Architecture. *Sensors* (Basel).

2020 Apr 4;20(7):2028. doi: 10.3390/s20072028. PMID: 32260338; PMCID: PMC7180486.

Falcão, R., Matar, R., & Rauch, B. (2023). Using I4.0 digital twins in agriculture [Preprint]. arXiv. <https://arxiv.org/abs/2301.09682>

Gangwani N., (2024): AI-Driven Precision Agriculture: Optimizing Crop Yield and Resource Efficiency, International Journal for Multidisciplinary Research (IJFMR), E-ISSN: 2582-2160

Gondal, M. U., Khan, M. A., Haseeb, A., Albarakati, H. M., & Shabaz, M. (2023). A secure food supply chain solution: Blockchain and IoT-enabled container to enhance the efficiency of shipment for strawberry supply chain. *Frontiers in Sustainable Food Systems*, 7, 1294829. <https://doi.org/10.3389/fsufs.2023.1294829>

Ju, C., Kim, J., Seol, J., & Son, H.-I. (2022). A review on multirobot systems in agriculture. *Computers and Electronics in Agriculture*, 202, 107336. DOI: 10.1016/j.compag.2022.107336.

Kaya, Ş. M., İşler, B., Mahfouz, A. M., Rasheed, J., AlShammari, A.: (2023) An Intelligent Anomaly Detection Approach for Accurate and Reliable Weather Forecasting at IoT Edges: A Case Study, *Sensors*, February 2023, *Sensors* 23(5):2426, Doi: 10.3390/s23052426

Kamilaris, A., & Prenafeta-Boldú, F. X. (2018). Deep learning in agriculture: A survey. *Computers and Electronics in Agriculture*, 147, 70–90. <https://doi.org/10.1016/j.compag.2018.02.016>

Liakos, K. G., Busato, P., Moshou, D., Pearson, S., & Bochtis, D. (2018). Machine learning in agriculture: A review. *Sensors*, 18(8), 2674. <https://doi.org/10.3390/s18082674>

Pranto, T. H., Noman, A. A., Mahmud, A., & Haque, A. B. (2021). Blockchain and smart contract for IoT enabled smart agriculture. *ArXiv*. <https://doi.org/10.7717/peerj-cs.407>

Padma Priya, A., Sudhakar, C. V., Kumar, A. P., & Reddy, Y. Y. (2024). Pest detection and prevention for agricultural crops using YOLOv8 algorithm. *Proceedings of the 2024 International Conference on Intelligent Systems for Cybersecurity (ISCS)*. <https://doi.org/10.1109/ISCS61804.2024.10581157>

Palacios, P., Soto, I., Azurdia-Meza, C. A., Salazar, I. S., Wang, R., & Kern, W. (2024). Hybrid digital twin model for greenhouse and underground environments. *IEEE Access*, 12, 73906–73924. <https://doi.org/10.1109/ACCESS.2024.3402537>

Peladarinos, N., Piromalis, D., Cheimaras, V., Tserepas, E., Munteanu, R. A., & Papageorgas, P. (2023). Enhancing smart agriculture by implementing

digital twins: A comprehensive review. *Sensors*, 23(16), 7128. <https://doi.org/10.3390/s23167128>

Sundmaeker, H., Guillemin, P., Friess, P., & Woelfflé, S. (2016). Vision and challenges for realising the Internet of Things in agriculture. In *Digitising the Industry – Internet of Things Connecting the Physical, Digital and Virtual Worlds* (pp. 37–70).

Vardhan, P. N. H., Badavath, A., & Srivalli, P. (2025). Artificial intelligence and its applications in agriculture: A review. *Environment Conservation Journal*, 26(1), 274–280. <https://doi.org/10.36953/ECJ.28802904>

Valente, A., Costa, C., Pereira, L., Soares, B., Lima, J., & Soares, S. (2022). A LoRaWAN IoT System for Smart Agriculture for Vine Water Status Determination. *Agriculture*, 12(10), 1695. <https://doi.org/10.3390/agriculture12101695>

Verdouw, C. N., Wolfert, J., Tekinerdogan, B., Beulens, A. J., & Bogaardt, M. J. (2021). Data-driven agri-food business: Transparent and smart supply chains. *Trends in Food Science & Technology*, 109, 211–219. <https://doi.org/10.1016/j.agry.2022.103558>

Wang, L. (2024). Digital twins in agriculture: A review of recent progress and open issues. *Electronics*, 13(11), 2209. <https://doi.org/10.3390/electronics13112209>

Wolfert, S., Ge, L., Verdouw, C., & Bogaardt, M.-J. (2017). Big Data in Smart Farming – A review. *Agricultural Systems*, 153, 69–80. <https://doi.org/10.1016/j.agry.2017.01.023>

Yépez-Ponce, D. F., Salcedo, J. V., Rosero-Montalvo, P. D., & Sanchis, J. (2023). Mobile robotics in smart farming: Current trends and applications. *Frontiers in Artificial Intelligence*, 6, 1213330. DOI: 10.3389/frai.2023.1213330.

Yin, J., Huang, P., Xiao, D., & Zhang, B. (2024). A lightweight rice pest detection algorithm using improved attention mechanism and YOLOv8. *Agriculture*, 14(7), 1052. <https://doi.org/10.3390/agriculture14071052>

Zhang, C., Huang, Y., & Guo, F. (2023). Digital twins in agriculture: A state-of-the-art review. *Agriculture*, 15(9), 903. <https://doi.org/10.3390/agriculture15090903>

Zhang, Y., Wang, G., & Jin, X. (2020). A review of precision agriculture technology: Use of remote sensing and unmanned aerial vehicles. *Journal of Cleaner Production*, 276, 123595. <https://doi.org/10.1016/j.jclepro.2020.123595>

Zheng, Y., Zheng, W. & Du, X. A lightweight rice pest detection algorithm based on improved YOLOv8. *Sci Rep* 14, 29888 (2024). <https://doi.org/10.1038/s41598-024-81587-5>

CHAPTER X

Q-LEARNING APPLICATIONS IN DIGITAL COMMERCE

Havva ABUGAN¹ & Yunus EROĞLU² & Selen Yücesoy KAHRAMAN³

*¹Gaziantep University, Graduate School of Applied Sciences, Department of Industrial Engineering, 27310 Gaziantep Türkiye Gaziantep OSB Technology Development Zone TAŞ. (OSB Technopolis) OSB 2nd Region 83235 No. Street No:8, 27620 Başpınar (Organized) OSB/Mh/Gaziantep
E-mail: ha111009@mail2.gantep.edu.tr; havvabukann@gmail.com*

*² Gaziantep University, Faculty of Engineering, Department of Industrial Engineering, 27310 Gaziantep, Türkiye
E-mail: eroglu@gantep.edu.tr ; eroglu.yunus@gmail.com*

*³ Gaziantep Islam Science and Technology University, Faculty of Engineering and Natural Sciences, Department of Industrial Engineering, 27010 Gaziantep, Türkiye,
E-mail: selen.yucesoy@gibtu.edu.tr
ORCID: 0000-0002-0284-5133*

1. Introduction

With the advancement of technology in today's commerce, traditional e-commerce has gradually lost its importance, giving way to e-commerce. E-commerce has created a competitive environment, particularly among export companies, by bringing distant markets closer together. Consequently, internet usage in europe has steadily increased, rising from 87% in 2019 to 92% in 2023, as seen in european e-commerce market trends [1].

Considering these developments, artificial intelligence (AI) has become an integral part of human life and has helped companies develop various strategies to survive in the competitive global environment of e-commerce [2].

This transformation has not only reshaped consumer behavior but also pushed companies to adopt multi-channel and omni-channel strategies to remain competitive [3]. Artificial intelligence applications in e-commerce are evident in a wide range of areas, including personalized recommendation systems, dynamic pricing, demand forecasting, customer review analysis, delivery optimization, and advertising budget management. Parameters such as price, advertising, delivery time, customer reviews, promotion type, packaging, and installment options play a critical role in companies' competitive advantage. Simultaneously evaluating and optimizing these parameters poses a complex challenge for traditional methods. At this point, reinforcement learning-based algorithms, particularly q-learning, are emerging as a powerful solution approach.

Q-learning has been used in seasonal price adjustment strategies based on customer demand learning [4]. It has also been used in conjunction with contextual multi-armed bandit algorithms to address uncertain demand and quality issues in the field [5]. Furthermore, due to its ease of use, it has been widely used as a method in the e-commerce ecosystem [6,7]. It has also been used to measure customer satisfaction, providing experts with a general framework and proves to be a method compatible with reality [8,9]. It is a preferred method in a wide variety of fields, including logistics and supply chain [10,11].

The literature review reveals that, in addition to machine learning, there are also studies that address various aspects of reinforcement learning. In digital marketplaces, intelligent bargaining agents are combined with game theory principles to learn bargaining processes and develop more efficient bargaining strategies [12]. In B2B e-commerce, multi-agent systems and ensemble learning techniques have been used to support coordination and decision-making [13]. Consumer trust has been increased by strengthening platform authenticity through deep learning and feature fusion approaches designed to detect fake reviews [14]. Similarly, systematic reviews on fraud detection have highlighted the effectiveness of adaptive learning approaches in preventing transaction risks [15]. Furthermore, practical studies have highlighted the practical applicability of these methods by examining opportunities and challenges such as scalability, real-time control, and data sparsity [16]. Taken together, these findings indicate that q-learning-based approaches stand out among the most reliable and applicable methods for managing complex e-commerce processes. In addition to incorporating fuzzy hybrid q-learning into studies on company profitability in e-commerce, there are also studies using fuzzy q-learning [17,18].

Detailed academic studies and industry research have revealed that many parameters directly impact companies' profitability in the e-commerce

environment. However, a key shortcoming in literature is that these parameters have largely been addressed separately. Existing studies have examined elements such as pricing, advertising budget, delivery time, customer reviews, or inventory management separately; each has made valuable and important contributions in its own context. However, there is no comprehensive study that evaluates these parameters simultaneously and applies them within a holistic optimization framework. This clearly demonstrates that companies in the current e-commerce environment must be analyzed not only from a one-dimensional approach but also from multiple perspectives.

The main contribution of this study is its comprehensive analysis of the factors affecting companies' market profitability, considering parameters previously studied separately in the literature. Considering multidimensional factors such as price, advertising, delivery time, promotion type, packaging format, and installment options within the same framework constitutes an innovative approach for e-commerce companies, both academically and practically. While each study in literature provides valuable contributions, current needs now require the development of integrated and comprehensive models that will further these contributions. In this context, q-learning has emerged as the most suitable reinforcement learning method due to its adaptability, ease of computation, and applicability to real-life situations. Therefore, this study not only complements the existing literature but also offers a new research and application perspective for multi-parameter e-commerce environments.

The study, which consists of four sections, is structured as follows: The first section discusses different methods used in the literature, explains the parameters considered in the study, and explains in detail the setup of the q-learning-based model. The second section evaluates the results obtained by considering the parameters affecting firm profitability in e-commerce and compares them with other methods. The next section presents the contribution of the study's results to the decision-making processes and practical benefits of e-commerce firms. The final section summarizes the key findings and offers suggestions for future research.

2. Material and Method

2.1. Material

This study utilizes multidimensional data that influences the decision-making processes of e-commerce companies. The parameters have been identified as fundamental elements that directly impact the companies' competitive strength and profitability (table 1). Although these elements are

generally addressed in the literature in single dimensions such as pricing, advertising, delivery time, or customer satisfaction, this study evaluated all parameters together under a holistic approach. Thus, a data structure that better reflects real market conditions was created, and the model inputs were defined for use in training the q-learning algorithm.

The data set used was obtained from ten different companies operating in the e-commerce ecosystem. These companies are mostly small and medium-sized enterprises (SMEs) and new entrepreneurs, ensuring that the data reflects real market conditions (Table 2). The data includes each company’s values for price, advertising budget, delivery time, customer reviews, promotion type, packaging format, installment options, fixed costs, and variable costs. These parameters reveal different aspects of the strategies adopted by companies in the market and provide a multidimensional perspective for understanding the competitive structure. Thus, the created dataset represents the basic input data used in the training process of the q-learning algorithm and allows the model to be tested under real scenarios.

Table 1. Key Parameters and Data Characteristics in the Proposed Model

Parameter	Definition	Data Type
Price	The price at which the product is offered to customers.	Continuous
Advertising	The firm’s expenditure on marketing and advertisements.	Continuous
Shipping Time	The time required to deliver the product to customers (in days).	Discrete {1, 2, 3, 4, 5, 6, 7} (1 = Same-day delivery, 7 = Delivery within one week)
Review Score	Customer satisfaction score represents average ratings (scale of 1 to 5).	Continuous
Promotion Type	The type of promotion strategy employed by the firm.	Discrete {0 = No Promotion, 1 = Discount, 2 = Coupon}
Packaging Type	Quality and cost of product packaging.	Discrete {1 = Low Quality, 2 = Medium Quality, 3 = High Quality, 4 = Eco-Friendly, 5 = Premium}
Installations Options	Number of installment options offered to customers.	Discrete {1 - 12} (1 = No Installment, 12 = 12 Monthly Installments)
Variable Costs	Costs directly associated with producing or selling the product per unit.	Continuous
Fixed Costs	Operational fixed costs of the firm.	Continuous

Table 2. Key parameters of the firms

Firms	Price (TL)	Advertising (TL)	Shipping Time (days)	Review Score (points)	Promotion Type
F1	2,080	135,000	3	1.8	1
F2	3,440	280,000	2	3.4	2
F3	1,150	6,5000	4	0.9	0
F4	4,950	450,000	1	4.7	1
F5	2,750	210,000	3	2.3	2
F6	3,900	320,000	6	3.8	0
F7	1,600	180,000	5	1.5	2
F8	4,300	95,000	2	4.1	1
F9	2,200	400,000	7	2	0
F10	3,100	150,000	4	3.2	2
Firms	Packaging Type	Installments	Fixed Costs (TL)	Variable Costs (TL)	
F1	2	3	60,000	90	
F2	4	6	95,000	150	
F3	1	1	50,000	70	
F4	5	12	200,000	300	
F5	3	6	80,000	120	
F6	4	9	150,000	200	
F7	1	4	70,000	80	
F8	3	2	120,000	180	
F9	2	6	90,000	220	
F10	5	10	130,000	250	

2.2. Method

The method used in this study is designed to simultaneously optimize the multidimensional parameters that affect company profitability in e-commerce. Traditional methods are limited in such complex problems because evaluating different parameters such as price, advertising, delivery time, customer reviews, promotion type, packaging type, and installment options simultaneously requires a multidimensional decision environment [19]. Therefore, the q-learning algorithm, which stands out among reinforcement learning methods,

was preferred in this study. Q-learning offers an adaptive approach that enables the learning of optimal decisions under different market conditions by operating through a state-action-reward structure. Thus, the model aims to provide companies with a competitive advantage by considering not only short-term gains but also long-term profitability.

The q-learning algorithm learns the optimal strategy by iteratively updating the value functions of state–action pairs. The update rule is based on integrating prior knowledge with newly acquired experience [20]. In other words, at each step, the immediate reward and the expected maximum future value are combined with the current q-value through the learning rate. This mechanism, which forms the foundation of q-learning, is expressed by the following equation (figure 1).




Figure 1. Structure of a Q Learning Structure [21]

The scenarios in the model represent the market conditions that companies face in the e-commerce environment and are defined by multidimensional parameters such as price, advertising, delivery time, customer reviews, promotions, packaging, and installment options. Under these conditions, the strategic decisions, or actions, that companies can implement consist of alternatives such as price changes, adjusting advertising expenditures, updating delivery times, or selecting promotion types. The reward obtained because of the action selected at each step is calculated based on the company's profitability; it is determined by evaluating cost, revenue, customer satisfaction, and competitive advantage together.

The q-learning algorithm develops a learning process that considers long-term profitability beyond short-term returns. To learn the optimal policy, the q-learning algorithm updates the value of each state–action pair according to the following equation (Eq. 1).

$$Q(S_t, A_t) \leftarrow Q(S_t, A_t) + \alpha [R_{t+1} + \gamma \max_a Q(S_{t+1}, a) - Q(S_t, A_t)] \quad (1)$$

S_t : Current state: the state in which the agent (or firm) is currently situated.

A_t : Action: the action chosen by the agent in the current state.

$Q(S_t, A_t)$: Former q-value estimation: the previous q-value of the state–action pair.

R_{t+1} : Immediate reward: the reward obtained at the next step after performing the action.

γ : Discount factor: a coefficient that balances the importance of future rewards relative to immediate ones ($0 < \gamma < 1$).

$\max_a Q(S_{t+1}, \alpha)$: Discounted estimate of the optimal q-value in the next state: the maximum q-value among all actions in the next state.

α : Learning rate determines how much current information influences the old q-values.

TD Target: $R_{t+1} + \gamma \max_a Q(S_{t+1}, \alpha)$: the target value for the next update.

TD Error: $[R_{t+1} + \gamma \max_a Q(S_{t+1}, \alpha) - Q(S_t, A_t)]$: The difference between the estimated value and the observed outcome.

New Q-value: the updated value, obtained by adjusting the former q-value with the learning rate multiplied by the TD Error.

Equation (1) defines the iterative update rule of q-learning, where the q-value of each state–action pair is refined by combining the immediate reward with the maximum expected future reward. Through repeated interactions with the environment, the algorithm gradually converges to an optimal policy. The overall learning process can be described in sequential steps, as summarized below.

That learning method follows a repetitive learning cycle. First, the agent is initialized as a state in S . Second, it randomly selects action A from among the available actions. This choice is met with a response from the ecosystem, or environment. With this response, the agent transitions to a new state. Based on this transition, the algorithm updated the q table by applying the update rule. This process is repeated, updating the q table to improve each time. The goal is to implement the most appropriate strategy.

The determination of q values is achieved through the TD principle and is mathematically related to the Bellman equation. If we examine the learning process in depth, it lies in the balance between exploration and exploitation. For this case, the ϵ -greedy policy is used. In the exploitation process, the agent uses the probability $(1-\epsilon)$ to choose the action with the highest q value. To do this, it utilizes its existing knowledge. In the exploration case, it uses ϵ to find better alternatives with random probability. Balancing better alternatives and

optimal strategies is critical because the algorithm should not get stuck in local optima, and learning should be structured around utilizing both accumulated and new probabilities. From this perspective, it is clearly a realistic and compatible method for real-world applications.

3. Research Findings and Discussion

In the simulation environment, the total market demand was defined as $D_{total} = 100,000$ units, representing the aggregate customer demand across all firms. This value provided a fixed reference point for evaluating how firms' strategic decisions influenced their share of the market and overall profitability. By keeping the total demand constant, the variations in payoffs and market shares could be directly attributed to the learning dynamics of the agents rather than fluctuations in external demand.




Figure 2. Learning Process- Average Payoff

The learning curve of the model demonstrates how the agents' average payoff evolves across episodes (figure 2). In the initial episodes, payoffs remain relatively low, since the system is still exploring the environment and testing random actions. However, within the first 100 episodes, there is a sharp increase in average payoff, indicating that the agents quickly learn to adopt more profitable strategies. Around episode 150, the payoff stabilizes at approximately 44 millions TL, showing that the model has converted to a consistent strategy. This outcome suggests that the q-learning algorithm has effectively captured the dynamics of the environment, enabling firms to sustain long-term profitability through stable decision-making.

Table 3. Key parameters of the firms

Firms	Price (TL)	Advertising (TL)	Shipping Time (days)	Review Score (points)	Promotion Type	Packaging	Installments
F1	5,000	133,000	4	1.8	0	3	5
F2	5,000	276,000	1	3.4	2	5	2
F3	5,000	61,000	2	0.9	0	4	2
F4	5,000	456,000	3	4.7	1	1	6
F5	5,000	203,000	1	2.3	1	4	3
F6	5,000	319,000	6	3.8	1	5	11
F7	5,000	177,000	4	1.5	2	5	1
F8	5,000	93,000	2	4.1	2	1	1
F9	5,000	400,000	4	2	2	4	4
F10	5,000	144,000	7	3.2	2	5	1

Table 3 presents the strategic profiles of the firms after the completion of the learning process. The results indicate that all firms have converged to a common equilibrium price of 5,000 TL, reflecting a stable pricing strategy in the competitive market. However, significant variations can be observed across other strategic parameters. For instance, Firm 2 and Firm 9 differentiate themselves with high advertising expenditures, while Firm 6 gains a competitive edge by offering extended installment options (11 months). Firm 4 adopts a quality-oriented approach, achieving both a high customer review score and fast delivery times, whereas Firm 3 follows a more price-oriented strategy with low advertising, low review scores, and short delivery times.

These outcomes suggest that the model does not force firms into identical strategies but rather guides each one toward distinct strategic positions shaped by their past performance and the competitive environment. Although firms have converged on the same price level, they rely on diverse combinations of advertising, delivery, promotion, and payment options to attract customers and capture market share.

Table 4. Differences of key parameters of the firms from initial to final situation

Firms	Price (TL)	Advertising (TL)	Shipping Time (days)	Review Score (points)	Promotion Type	Packaging	Installments
F1	2,920	-2,000	1	0	-1	0	2
F2	1,560	-4,000	-1	0	0	1	-4
F3	3,850	-4,000	-2	0	0	3	0
F4	50	6,000	2	0	0	-1	-6
F5	2,250	73,000	-3	0	1	0	-1
F6	1,100	-1,000	0	0	-1	0	2
F7	3,400	0	0	0	0	0	-1
F8	700	-2,000	0	0	1	-1	-1
F9	2,700	100,000	2	0	1	2	-2
F10	1,900	-6,000	0	0	0	0	-9

Table 4 summarizes the differences between the initial and final values of the firms’ strategic parameters after the learning process. Each entry reflects how the q-learning algorithm guided firms to adjust their decisions to optimize performance. A general trend is observed in advertising expenditure, where most firms significantly reduced their budgets, pointing to a more efficient allocation of resources (e.g., Firms 1, 2, and 3). Shipping times were shortened by several firms, most notably Firm 5 with a reduction of three days, reflecting an emphasis on delivery efficiency. Packaging quality improvements, such as Firm 3’s increase of +3 levels, indicate a shift toward quality-oriented strategies. The most remarkable adjustment occurred in installment options, with Firm 10 reducing its offering by nine periods, suggesting a transition to short-term payment plans.

Overall, these results show that the learning process did not enforce uniform strategies but rather enabled each firm to optimize different levers whether cost reduction, efficiency, quality enhancement, or financial restructuring to maximize their competitiveness.




Figure 3. Comparison of Initial vs Final Payoff

As seen in Figure 3, the strategies before and after the learning process are compared. Blue bars represent initial returns, while orange bars represent results after training. An examination of the results reveals a significant improvement in the firms. Firms 1, 3, 5, and 6 achieved higher returns thanks to strategic guidance.

Conversely, firm 4, which initially demonstrated strong performance, experienced a decline in its final returns. This demonstrates that the model does not impose uniform strategies; rather, it develops recommendations tailored to each firm’s unique circumstances. Overall, the learning mechanism enhances firm performance in diverse ways and contributes to a clear increase in market profitability.




Figure 4. Initial vs Final Market Share Comparison

Figure 4 compares the firms' market shares, that is, the amount of demand met, before and after the learning process. Blue bars represent the initial distribution, while orange bars represent the results. Looking at the graph, firms 3, 6, 7, and 9 increased their market share by optimizing strategic parameters such as pricing, advertising, and delivery performance. In contrast, firms 4 and 10 experienced significant declines, indicating that they were falling behind competitors adopting more aggressive or customer-focused strategies.

All parameters demonstrate that firms not only maximize their profitability but also adapt to competitive market conditions by redistributing demand to firms implementing more effective strategies. Consequently, the learning process facilitates both firm-level development and system-level adaptation in a competitive e-commerce environment.

4. Conclusion and Future Works

From a general perspective, the dynamic nature of the e-commerce ecosystem is clear. Therefore, the methods used in analyses must be designed with a logic that is compatible with real-world applications and understandable. An examination of the ecosystem reveals numerous product-related parameters. The most used parameters that form the framework of this research are discussed. Q-learning, a reinforcement learning technique, was examined in case studies. By incorporating various strategic dimensions such as price, advertising, delivery time, customer reviews, promotion types, packaging quality, and installment options, the model was able to reflect the complexity of the decision-making processes companies face in competitive markets. Furthermore, a total market demand of 100,000 units was assumed, and this analysis analyzed how companies dynamically adjust their strategies to maximize profitability and market share.

A closer look at the results reveals that the learning process analysis reveals that initial decisions were unstable and yielded low returns due to the exploration process, but the algorithm quickly converged on a stable strategy, achieving an average return of approximately 44 millions Turkish Lira. This confirms the model's ability to learn profit-maximizing strategies in a small number of iterations. Second, an examination of the post-learning strategic profiles revealed that, although all firms converged on a common equilibrium price of 5,000 TL, complexity persisted in other parameters. Firms differentiated across advertising spending, installment options, customer satisfaction levels, and delivery efficiency, demonstrating that the learning mechanism, rather than imposing a uniform approach, enabled multiple viable strategies tailored

to the specific context of the firm. Third, a comparison of the initial and final parameter values revealed how firms strategically reallocated their resources. Many firms reduced their advertising spending, reflecting a more efficient use of their marketing budgets; others shortened delivery times or improved packaging quality to attract customers. The most striking changes were observed in their installation policies; for example, firm 10 reduced its nine installment options and shifted toward shorter-term, risk-averse financial strategies. Fourth, a comparison between the initial and final scenarios revealed that many firms significantly increased their profitability. Firms 1, 3, 5, and 6 experienced high profits, while firm 4 experienced losses, demonstrating that the model produced firm-specific results. In other words, not all strategies yielded the same profits; competition and other parameters influenced the results.

Finally, the market share analysis revealed a significant redistribution of demand. While firms 3, 6, 7, and 9 increased their market share by optimizing key parameters, firms 4 and 10 experienced losses due to poor strategic alignment. This demonstrates that q-learning not only maximizes profits but also takes competitive dynamics into account, enabling more adaptive and robust decision-making processes in multi-agent environments. Overall, these findings highlight the capacity of reinforcement learning, and Q-learning in particular, to provide firms in e-commerce with a dynamic, data-driven decision support mechanism. By enabling the simultaneous optimization of numerous interrelated parameters, the model overcomes the limitations of traditional static approaches. The findings also highlight the adaptability of q-learning: Rather than guiding all firms toward a single optimal solution, it allows for the emergence of different strategies depending on the firm's context and market position.

As a general perspective, this study offers practical implications for both SMEs and established e-commerce players. The findings demonstrate that firms can increase their competitiveness not by focusing solely on a single parameter, but by strategically balancing multiple levels, such as pricing, advertising, coordination, and customer experience. Furthermore, q-learning's adaptability provides resilience to market uncertainties, making it a promising tool for sustainable profitability. Ultimately, this research contributes to the literature on AI in e-commerce by demonstrating the practical effectiveness of reinforcement learning in complex multi-firm environments. Future studies could refine the model by incorporating elements such as larger datasets, real-time market fluctuations, or hybrid integration of q-learning with deep learning techniques. Such advances could enhance scalability and accuracy, providing a

stronger foundation for the integration of AI-assisted optimization into global e-commerce ecosystems.

Author Contributions

The study's conceptualization, all authors collaboratively performed design, data analysis, and manuscript preparation.

Funding

Gaziantep University founded this research, grant number MF.YLT.24.27.

Institutional Review Board

Not applicable.

Informed Consent Statement

Not applicable

Data Availability Statement

All data used in the study are presented in this book chapter.

Conflicts of Interest

The authors declare no conflicts of interest.

References

1. Weltevreden, J. W.J. (2024). *European e-commerce report 2024 (Light Version)*. Amsterdam University of Applied Sciences & Ecommerce Europe. https://ecommerce-europe.eu/wp-content/uploads/2024/10/CMI2024_Complete_light_v1.pdf
2. Ecommerce Europe. (2024). The e-commerce landscape: Discover how shoppers browse, buy and subscribe online. In *European e-commerce report 2024 (Light Version)*. Amsterdam University of Applied Sciences & Ecommerce Europe. https://ecommerceeurope.eu/wpcontent/uploads/2024/10/CMI2024_Complete_light_v1.pdf
3. Risberg, A. (2023). A systematic literature review on e-commerce logistics: Towards an e-commerce and omni-channel decision framework. *The International Review of Retail, Distribution and Consumer Research*, 33(1), 67–91.
4. Cheng, Y. (2009, May). Real-time demand learning-based Q-learning approach for dynamic pricing in e-retailing setting. In *2009 International Symposium on Information Engineering and Electronic Commerce (IEEC 2009)* (pp. 594–598). IEEE.
5. Mandania, R., & Oliveira, F. S. (2023). Dynamic pricing of regulated field services using reinforcement learning. *IJSE Transactions*, 55(10), 1022–1034. <https://doi.org/10.1080/24725854.2022.2151672>.

6. Jebamikyous, H., Li, M., Suhas, Y., & Kashef, R. (2023). Leveraging machine learning and blockchain in e-commerce and beyond: Benefits, models, and application. *Discover Artificial Intelligence*, 3, 3. <https://doi.org/10.1007/s44163-022-00046-0>
7. E. Dritsas and M. Tigka, “Machine learning in e-commerce: trends, applications, and future challenges,” IEEE Access.
8. S. Chakraborty, S. Paul, S. Debnath, P. Chakraborty, and S. Bose, “Dynamic pricing strategies in e-commerce: A reinforcement learning approach for real-time adaption,” *Fusion of Minds*, p. 249, 2024
9. Ahmed, S. R., Alhashimi, L. Q., Hussein, A. J., Radhi, A. D., Radhi, A. A., Ahmed, M. R., & Tawfeeq, J. F. (2024, May). Deep learning for customer relationship management in e-commerce. In *2024 International Congress on Human-Computer Interaction, Optimization and Robotic Applications (HORA)*. IEEE. <https://doi.org/10.1109/HORA61326.2024.10550481>
10. Yan, Y., Chow, A. H. F., Ho, C. P., Kuo, Y.-H., Wu, Q., & Ying, C. (2022). Reinforcement learning for logistics and supply chain management: Methodologies, state of the art, and future opportunities. *Transportation Research Part E: Logistics and Transportation Review*, 162, 102712. <https://doi.org/10.1016/j.tre.2022.102712>
11. Arishi, A., & Ahuja, P. (2025). Multi-agent reinforcement learning for truck–drone routing in smart logistics: A comprehensive review. *Computers & Electrical Engineering*, 127, 110529. <https://doi.org/10.1016/j.compeleceng.2025.110529>
12. Li, Y. (2022). *Reinforcement learning in practice: Opportunities and challenges*. arXiv. <https://arxiv.org/abs/2202.11296>
13. Panzer, M., & Bender, B. (2022). Deep reinforcement learning in production systems: A systematic literature review. *International Journal of Production Research*, 60(13), 4316–4341.
14. Chen, X., Yao, L., McAuley, J., Zhou, G., & Wang, X. (2021). *A survey of deep reinforcement learning in recommender systems: A systematic review and future directions*. arXiv. <https://arxiv.org/abs/2109.03540>
15. Chen, X., Yao, L., McAuley, J., Zhou, G., & Wang, X. (2021). *A survey of deep reinforcement learning in recommender systems: A systematic review and future directions*. arXiv. <https://arxiv.org/abs/2109.03540>
16. Cheng, N., Wang, X., Li, Z., Yin, Z., Luan, T. H., & Shen, X. (2024). Toward enhanced reinforcement learning-based resource management via digital twin: Opportunities, applications, and challenges. *IEEE Network*, 39(1), 189–196.

17. Abukan, H., Eroğlu, Y., & Kahraman, S. Y. (2025). Hybrid fuzzy inference and Q-learning integration for strategic decision making in electronic commerce. In *Proceedings of the International Conference on Intelligent and Fuzzy Systems (INFUS 2025)* (pp. 755–762). Springer, Cham.
18. Rajavel, R., Komarasamy, D., Meenakshisundaram, I., Gubinjoa, K., & Iwendi. (2022). Cognitive fuzzy-based behavioral learning system for augmenting automated multi-issue negotiation in e-commerce applications. *Journal of Internet Technology*, 23(6), 1335–1342.
19. Liu, J., Zhang, Y., Wang, X., Deng, Y., & Wu, X. (2019). *Dynamic pricing on e-commerce platform with deep reinforcement learning: A field experiment*. arXiv. <https://arxiv.org/abs/1912.02572>
20. Jang, B., Kim, M., Harerimana, G., & Kim, J. W. (2019). Q-learning algorithms: A comprehensive classification and applications. *IEEE Access*, 7, 133653–133667.
21. Jafri, N., Tahir, M., & Ahad, A. (2013). The role of artificial intelligence in solar harvesting, storage, and conversion. In *Solar energy harvesting, conversion, and storage* (pp. 293–318). Elsevier.

CHAPTER XI

GENERATIVE ARTIFICIAL INTELLIGENCE (GENAI) SUPPORTED DIGITAL MARKETING AND CONTENT STRATEGIES

Murat Fatih TUNA¹ & Yunus Emre IŞIK²

(Assoc. Prof. Dr.)¹, Sivas Cumhuriyet University,

E-mail: mftuna@cumhuriyet.edu.tr

ORCID: 0000-0002-8634-8643

(Asst. Prof. Dr.)², Sivas Cumhuriyet University,

E-mail: yeisik@cumhuriyet.edu.tr

ORCID: 0000-0001-6176-7545

1. Introduction

Artificial Intelligence (AI) technology now plays a key role in both individuals' and organizations' daily life. This dependency on AI technologies has increased their use in a wide variety of activities, from the simplest and most personal decisions to the most complex corporate decisions. In particular, tracking personal plans (such as daily routines like diets and appointment tracking) reinforces the perception that individuals' corporate roles will also be supported by AI (Huynh & Aichner, 2025). This situation has accelerated the understanding of the facilitating effect of AI technologies on the corporate roles individuals hold (Rüther, 2025), thereby accelerating the share of AI technologies in the workplace. According to Walkowiak & Potts (2024), this process encourages the adoption of AI's performance advantages at the level of individual tasks and ensures the division of tasks between machines and humans. One area where AI technologies are heavily used is digital content production.

Generative AI (GenAI) models have arisen due to technological advances in natural language processing, a subfield of AI. These models can generate meaningful content such as text, images, audio, or video (Feuerriegel et al.,

2024). Besides, foundational models of GenAI can be trained, thus models can be adapted to a wide variety of tasks (Hua et al., 2024). Previous literature also points to a transformative impact of GenAI on marketing practices (Kshetri et al., 2024). It highlights the importance of its use in content creation on social media for marketing (Wahid et al., 2023).

According to Brüns & Meißner (2024), since the COVID-19 pandemic era has shifted consumer interactions with brands to online channels, GenAI technologies can enable consumers to integrate with brands through creative content. Indeed, it is crucial for companies that rely heavily on digital media to understand their need for AI-generated social media content and how this need reflects on their followers (Guha et al., 2021). In this way, companies can nurture consumer engagement and develop perceptions of value and trust in their brands among consumers (Hollebeek & Macky, 2019).. The growing skepticism of consumers towards advertisements and other marketing communication elements is the fundamental dynamic of this proliferation (Matteo & Zotto, 2015). With this strategy, brands offer engaging and personalized content through digital platforms and social media channels, thereby increasing customer loyalty, interaction, and brand loyalty (Tuna et al., 2024). Content consisting of well-structured, meaningful data is a well-structured compilation in terms of syntax and semantics (Floridi, 2024). However, producing good content, ensuring it is regular and continuous, and adding artistic styles to this content is a serious and challenging task. The necessity of creating content at specific intervals increases this seriousness. Generative AI (GenAI) is among the most innovative technologies used to overcome the issues mentioned. Indeed, GenAI significantly increases efficiency in content production and positively impacts parameters such as average time and output quality (Noy & Zhang, 2023).

Recent studies have demonstrated GenAI's success in developing marketing content (Brüns & Meißner, 2024; Feuerriegel et al., 2024; Floridi, 2024; Wahid et al., 2023). According to a market research report investigating GenAI's share in content production, it is predicted that approximately one-third of the digital content produced by major brands will be created by GenAI (Gartner, 2023). Digital technologies have democratized content production, enabling individuals to become curators, content creators, and publishers. The boundaries between consumers and content creators have blurred, obscuring the established hierarchy of mainstream media (Floridi, 2024). Moreover, the need to produce personalized content (Hollebeek & Macky, 2019) and offer tailored offerings (Kshetri et al., 2024), which are fundamental to content

marketing, makes the use of GenAI technologies inevitable for businesses. In this increasingly digitalizing environment where technology continues to rise, it is necessary to discuss the unique relationship between GenAI technologies and content marketing, which is distinct from all other areas of application. This study examines how GenAI is changing digital marketing and content strategies. We focus on how GenAI help businesses, especially in areas like personalized product recommendations, improving customer engagement, and building brand loyalty. We also explore prompt frameworks that can enhance the quality of targeted production in digital marketing.

2. Generative AI In Business

Although AI still seemed as a ‘science fiction term’, it has become today’s reality and changed daily life. The term AI is actually defined as computer systems to perform specific tasks that needs human intelligence, primarily through rule-based programming, expert systems, and symbolic reasoning, especially in practical aspects (Simmons & Chappell, 1988). However, technological advancements behind the Third Industrial Revolution, such as the internet and computing, have redefined AI, along with Big Data and its corresponding analytics capabilities. This rapid development has resulted in AI being regarded as one of the main inventions of the fourth industrial revolution (Jeon & Suh, 2017). Especially following the AI Boom era, which is expressed by the rise of GenAI models (Adam et al., 2025), the concept of AI has evolved from being simply a tool for automating specific tasks to advanced systems have ability of simulating human cognitive, creative, and analytical thinking, and even outperforming them in some fields. Furthermore, the interactivity of AI with people, such as voice commands and conversations, leads to fundamental transformations of socio-economic structures.

Even though the generative AI approach has been the focus of research for many years, it has become a reality with proposed Generative Adversarial Networks (GANs) model by Ian Goodfellow et al. in 2014 (Goodfellow et al., 2014). These models consist of two neural networks the generator and the discriminator to generate realistic data such as photographs (U. Verma, 2024). It has also paved the way for the generation of a massive amount of labeled data, which is required to train deep learning models to make them more generalized. The next breakthrough in “Generative” idea was rise up with Attention mechanism and Transformer model in 2017 (Vaswani et al., 2023). The attention mechanism allows dynamic weighting of input information. Dynamic weighting

provide effectively modeling of long-range contexts. In contrast to traditional methods like LSTMs and RNNs— which sequentially condense information from large contexts into a fixed-size vector, the attention mechanism calculates “attention score” dynamically to all input elements based on context (Bahdanau et al., 2016).

This approach paves the way to the generation of much more accurate and contextually relevant results by preserving long-range semantic associations. The self-attention mechanism in the Transformer architecture takes this concept further integrating parallel calculation of inputs in a single step. When combined with modern graphics processing units (GPUs) and tensor processing units (TPUs), which offer large-scale parallel computing capabilities, transformer-like models have become feasible for training models on extensive datasets at speeds that were previously impractical. These models can learn patterns by analyzing word associations in the input without requiring any label or class information during the training process. The integration of unlabeled training approach with extensive data sources, such as the World Wide Web, which is comprised of trillions of data, has led to the rapid rise of generative models.

Consequently, several well-known Large Language Models (LLMs) have emerged, including ChatGPT, Claude, Perplexity, and Gemini, among others. These models allow users to generate human-like texts, such as poems and fables, create drawings of anything, and engage in conversations with a chatbot. These capabilities, notably in natural language processing, have leads to major changes not only academic research, education, and social media but also business. Businesses follow ‘business model innovation’ idea to improve efficiency within evolving market dynamics. The definition of business model innovation is as follows: the process of creation, modification or definition of the fundamental structure and components of a business model for the purpose of the generate of new value propositions, the capture of new market opportunities and the gaining of a competitive advantage. (Astawa & Arsha, 2024). In order to achieve these alterations during model development, AI applications play a crucial role. This is because, AI-powered applications make an improvement on decisions and workflows by analyzing massive amounts of data gathered from business departments.

The current literature has also showed the applications of AI-based approaches as innovative solutions in various business departments and processes. For instance, in process manufacturing, an AI-driven hybrid solution was provided for precise demand forecasting in dairy production especially

in seasonal production planning. The method enables the identification of changes in demand patterns related to cultural and seasonal events (Obaidat et al., 2025). Another study projected that AI-based approaches in production and management processes would be more beneficial for extending battery lifetimes. During production, AI methods such as SVM and ANN can be used to determine the associations between process parameters (solid-liquid ratio, polymer/cosolvent ratio, and viscosity) and intermediate/final product properties (mass loading, porosity, and capacity) (Liu et al., 2022). Quality control processes on the manufacturing have also been benefitted from GenAI. Generative models used to synthesize failure scenarios and augment visual inspection workflows via computer vision pipelines (Adeyinka & Adeyinka, 2025). Mandvikar & Achanta (2023) proposed Process Automation 2.0 which is a GenAI based framework that integrates heterogeneous data sources, transcription utilities, and analytic pipelines to deliver unprecedented levels of efficiency, accuracy, and scalability. Proposed framework is expected to raise automation rates to 35-45% without human-in-the-loop intervention.

AI is also profoundly impacting the financial sector, particularly in enhancing security and streamlining operations. One of the most significant applications of AI in finance is fraud detection (Vengathattil, 2025). Typically, traditional fraud detection methods, such as rule-based systems, are ineffective at catching emerging fraudulent patterns. AI-Driven systems, on the other hand, can monitor vast amounts of real-time transactions such as account behaviors and compare them with historical patterns to reveal fraud. Thus, they help to prevent financial losses and reduce losses before fraud attempts succeed (Bello et al., 2023). For example, Feedzai is one of the most known solution for real-time fraud detection which is designed for real-time fraud detection in financial transactions, leveraging machine learning algorithms to identify and mitigate fraudulent activities within banking and e-commerce systems (Narsimha et al., 2022). In another study (Bitaab et al., 2023), an approach was proposed a machine-learning based fraud detector for fraudulent e-commerce websites (FCWs). Authors designed a classified called BEYOND PHISH and achieved between 94% and 98% detection accuracy in contrast to Google Safe Browsing which obtained 46% detection rate. Bidirectional Long Short-Term Memory (Li et al., 2022), Convolutional Neural Network (Vo Quang et al., 2023) are another examples of Deep-learning based methods that applied for fraud detection.

Human Resource (HR) is another core department of almost every organization that responsible for managing employees at all hierarchical levels

within the company. This department also addresses the diverse needs of employees such as managing incoming requests, annual leaves, medical leaves, work schedules, training, employee onboarding, performance management and legal compliances. Thus, GenAI based approaches can help and improve efficiency of the HR processes. LLM models like ChatGPT or Gemini assist HR professionals by automating preliminary candidate screenings through interactive questioning and response evaluation to identify suitable candidates (Kulkarni et al., 2023). For new employees, GenAI can provide a chatbot or virtual assistant to respond to employee inquiries about policies, leave entitlements, and benefits. These systems reduce the workload of HR professionals while ensuring the timely and accurate delivery of information to employees (Balla, 2025). Moreover, an AI system can incorporate regulatory changes as they occur and update documentation automatically, eliminating the need for constant manual updates.

In the sales and marketing domain, generative and predictive capability of GenAI models has provided numerous new insights and opportunities such as personalized product recommendation, profile guided social media-email contents, lead generation and sales forecasting or enhanced customer services with chatbots (Dwivedi et al., 2023). For instance, in study (Reeder et al., 2025), authors investigate the predictive utility of unstructured activity log data sourced from Customer Relationship Management (CRM) software for improving sales forecasting in Business-to-Business (B2B) markets. They analyzed over 250,000 CRM activity logs collected over 106 weeks from more than 14,700 customers using Llama model. Their findings reveal that model outputs show a significant economic influence, accounting for approximately 10% to 20% of the effect size typically associated with direct customer interactions. Similarly, another empirical study evidenced that usage of GenAI models has a positive impact on consumer purchase behavior in E-Commerce platforms (Xie et al., 2025). A positive impact has been observed on products that contains high information and review inconsistency. That finding might be arisen from that high information overload leads to cognitive burden and ultimately, consumers use AI-assistance for decision-making. Similarly, when consumers read cross-review inconsistencies, GenAI can help reduce consumer confusion.

Personalization represents a significant advantage in marketing and sales strategies. Using advantages of GenAI approaches, marketing teams can identify high-value customer segments with higher accuracy, optimizing campaign effectiveness (Kunz & Wirtz, 2023). Furthermore, chatbot-powered assistants have also helped by delivering personalized content

recommendations in real time (Kshetri et al., 2024). Empirical findings from consumer perspective also support that personalization through GenAI is useful. In a study (P et al., 2025), beliefs of digital consumers about personalized marketing content generated by GenAI were investigated. For this purpose, a survey was conducted among 150 consumers aged 18 to 45. Analyzed findings showed that generating personalized content with GenAI has a positive impact on consumer trust, engagement, and brand loyalty. Commercial leaders also believe that the role of GenAI in marketing and sales has had a significant or very significant impact (Deveau et al., 2023) . The positive impact of the GenAI approach on consumer purchasing behavior in digital environments has accelerated content creation in digital marketing and has given rise to concept of “digital content marketing.”

3. Digital Content Marketing

The production of marketing-oriented content predates digitalization. For example, the Michelin tire company has been preparing and distributing travel planning guides to its dealers for over 100 years (Lou et al., 2019). Similarly, the magazine *The Furrow*, first distributed by John Deere in 1895, provided information about agricultural equipment (Agata et al., 2024). Many companies that have applied this strategy to different sectors have, in this way, provided their customers with alternative and interesting data while also promoting their brand. Similar approaches have been widely used by many companies, particularly in the food, cosmetics, textile, and medical sectors. Magazines and newsletters containing content that attracts customers’ attention were left at physical sales locations, enabling them to learn about the brand and its products.

Today, the digital transformation brought about by the widespread adoption of the internet and digital technologies is reshaping the nature and scope of marketing activities. New developments in digital technology and the emergence of Web 2.0 have given consumers and companies an active voice in the market, expressed through various forms of digital content (Agata et al., 2024). Behavioral changes triggered by digitalization have begun to play a decisive role in decision-making processes of both individual consumers and corporate buyers (Özkuk, 2024). In this context, understanding online consumer behavior and developing digital marketing strategies are critically important for the discipline of marketing. This makes it possible to produce content that is rich in value and well thought out, with a higher likelihood of leaving a lasting impression by overcoming the noise and clutter (Lou et al., 2019).

As of February 2025, the total number of unique social media accounts worldwide is 5.24 billion, and half of these accounts provide access to content that helps users learn about companies and brands (Thompson, 2025). As a natural consequence of the necessity of digital communication, even physical businesses have sought ways to increase their digital presence and, consequently, awareness and reputation for their brands (Hollebeek & Macky, 2019; Tuna, 2024). When consuming digital content, consumers decide what to interact with. On social media, the source of content is a critical factor that directly influences consumers' level of engagement with the brand (Odoom, 2025). Indeed, marketing communication established by companies through their own efforts creates a feeling of deception in consumers and makes them feel manipulated (Matteo & Zotto, 2015). This situation has led to greater credibility for user-generated content (UGC) (Hua et al., 2024).

Digital content is now a business asset that strengthens customer relationships, streamlines the pre-sales process, and drives customer purchasing decisions (Wall & Spinuzzi, 2018). The fundamental dynamics that fuel this asset and drive customer engagement include interaction elements like likes, comments, and shares related to the content. These elements offer a persuasive communication opportunity for potential customers while also positively influencing the purchasing intentions of existing customers. Furthermore, they enable all businesses that do not overpromise and build their relationship with customers on a foundation of sustainable trust to achieve a lasting reputation (Fehrer et al., 2018). The foundation of balanced reputation management depends on the e-WOM (electronic Word-of-Mouth) strategy, which enables customers who interact with content to serve as a marketing argument (Roy et al., 2024). In other words, companies not only interact with customers through content, but also enhance the synergy of existing interactions through online audiences.

When digital content is marketed correctly, consumers perceive the brand as an individual and humanize it (Plessis, 2017). Based on this, they can attribute a personality to the brand and develop various feelings towards the humanized brand (A. Verma, 2025). Through content, a brand can present its digital persona and better showcase its character, values, and views; it can tell its story in a way that resonates with its target audience and creates positive engagement behavior (van Doorn et al., 2010). Since strengthening a brand's relationship with its customers is closely tied to the content created (Agata et al., 2024), the personalization and virality of emotions are phenomena observed in content. Therefore, content that virally conveys personal emotions establishes a kind of

brand tribalism effect, and well-crafted content can become a fundamental ritual of the tribe (Hidayat et al., 2024; Lopes & Casais, 2022; Ruane & Wallace, 2015).

Recent developments in communication and information technology, along with the rise of digital content and social media, are transforming how individuals and businesses interact based on their information-seeking behaviors (Järvinen & Taiminen, 2016). These forms enable the creation of complex content that can appeal to different senses through the various tools offered by digital media. Although Handley & Chapman (2012, p. 21) define content as ‘anything created and uploaded to a website: the words, images or other things that reside here’, certain types of content are more commonly used. Common content published by companies on their websites, social media pages, and influencers can be typologized as follows (Chaffey & Ellis-Chadwick, 2022; Agata et al., 2024):

- **Video Content:** Multi-sensory interactive content.
- **Visual Content:** More stable visual contents that targets sight sense.
- **Brand Storytelling Content:** Content created using stories that reflect the brand’s purpose and passion.
- **User-Generated Content:** Content created by the user voluntarily and for their own individual purposes in relation to the brand, whether written, spoken, or visual.
- **Personalized Content:** Content designed to create appeal tailored to users based on their demographic data.
- **Infographics:** Content that understandably visualizes complex data-driven information.
- **Presentations:** Content that presents structured information with visual and auditory support.
- **Tests and Quizzes:** Entertaining content structured around a gamification strategy that encourages users to visit the relevant platform regularly.
- **Webinars:** Content that enables experts to share information in a live and interactive environment and collect leads (potential customers).
- **Podcasts:** Content that enables users to have an auditory experience and provides in-depth information.
- **Blog Posts:** Search engine optimized (SEO) and informative content that can make the company/brand stand out in web searches.
- **Newsletters:** Contents designed to regularly inform the target audience about innovations and developments, creating loyalty through subscriptions.

- **Thought Leadership and POVs (Point of View):** Content sharing opinions from experts in the sector in which the company operates.
- **Social Media Content:** Content shared on social media accounts that facilitates establishing an emotional connection with consumers.
- **Interactive Content:** Content that enables consumers to interact and connect with the company's online platforms, sometimes supported by rewards.
- **Consumer-First Content:** Contents that aim to change consumer emotions rather than just selling.
- **Evergreen Content:** Content that maintains its effectiveness over time.

These types of content, which marketers commonly use, demonstrate the challenges of spreading digital communication to different segments of the target audience, which forms the basis of modern marketing approaches.. Considering the intensity of budget, cost, and skilled labor expenses, producing such a large volume and variety of content is seen as a factor that reduces time and cost efficiency for the company. This situation deepens the need for both the production of qualified content and the automatic and scheduled distribution of this content through the widespread use of information technologies, primarily AI and specific sub-technologies (Menczer et al., 2023). Here, GenAI technologies come to the fore as a means to facilitate a paradigm shift based on the needs and intensity of content production processes (Dwivedi et al., 2023; Miikkulainen, 2024; Pulikal et al., 2025).

4. GenAI In Digital Content Marketing

Content marketing is generally defined as the identification, development, and publication of content designed to enhance digital marketing performance and create appeal among customers (Terho et al., 2022). In this type of digital marketing, the focus is on strategically producing and distributing value-driven, relevant, and consistent content to attract, win over, and build long-term loyalty among a specific target audience based on their interests and needs (Lopes & Casais, 2022). Nevertheless, the methods and tools needed to achieve this strategic goal are constantly progressing. One of the most revolutionary areas of AI is GenAI, which enables computers to produce material independently by mimicking human creativity and problem-solving abilities (Pulikal et al., 2025). Using GenAI technology to create, develop, or edit content aligns well with the changing culture of social media (Hua et al., 2024). Moreover, it can effectively use the characteristics identified by Pulikal et al. (2025) to change the way of content creation, personalization, and distribution.

The existing literature on content marketing and social media content closely examines the content creation process (Terho et al., 2022; Wahid et al., 2023). Indeed, these contents not only enable consumers to integrate with the brand but also enhance their perception of value and trust (Hollebeek & Macky, 2019). Therefore, a regularly fed content mechanism contributes to the customer's adoption of the brand and becoming a member of the brand's family (Plessis, 2017). The central importance of content production in digital marketing makes it an indispensable aspect of an innovation-oriented approach. In fact, media companies whose *raison d'être* is content production are using GenAI to generate articles from scratch on various topics such as politics, foreign affairs, financial markets, entertainment, sporting events, and crime (Mariani & Dwivedi, 2024).

According to Brüns & Meißner (2024), there are two main approaches in the literature on GenAI-based content creation. The first group of studies focuses on how GenAI supports content marketing and the professionals who carry out these activities. Accordingly, GenAI technologies have positive effects on ROI (return on investment) obtained from marketing activities (Reisenbichler et al., 2022), as well as on the quality, performance, and productivity of these professionals (Noy & Zhang, 2023). The second group of studies focuses on a facilitating effect of GenAI use on marketing processes and strategies, as well as the value it creates (Brüns & Meißner, 2024). At this point, dimensions such as the automatic placement of personalized persuasive messages in content (Matz et al., 2024) and the addition of artistic styles to content (W. Wang et al., 2025) stand out.

GenAI, which is rapidly evolving in content marketing, is used to produce synthetic content that identifies video, images, text, or audio fully or partially generated using AI algorithms (Agata et al., 2024, p. 203). Due to this structure in synthetic content, GenAI, referred to as the digital plastic metaphor (Roe et al., 2025), has come to encompass a broad aspect of digital content creation. However, due to the nature of GenAI technologies, it is thought that their use may bring specific problems.

Although GenAI is equipped with specific capabilities such as creating synthetic chatbots, generating human-like textual structures, or producing convincing visuals and videos, it brings with it some potential risks alongside increased efficiency. Data security and reliability are among the foremost of these risks. GenAI cannot verify the accuracy of the information it generates (Hua et al., 2024). This tendency, known as hallucination, causes GenAI to fabricate facts and produce videos with human-like characters by constructing

grammatically consistent sentences without the ability to verify the accuracy of the content (Munn et al., 2024). Shumailov et al. (2024) point out that the relative share of GenAI content within human-made content in the digital realm is increasing. Consequently, the possibility of generated content being reprocessed with GenAI content could cause the models to collapse. Consequently, GenAI is increasingly exposed to the content it continuously produces, and this exposure overshadows human-based creativity in its production potential. This view parallels the prediction of Dwivedi et al. (2023) regarding the timeliness and quality of training data.

Other issues that GenAI technologies will bring are data source and ownership problems. Outputs generated by AI are based on big data collected from the rights holders of the training data set. This situation brings with it potential issues such as copyright and the theft of collective intelligence (Kalantzis & Cope, 2025). The infinite alternative content that can potentially be produced through GenAI is metaphorized as ‘digital plastic’ (Roe et al., 2025). The authors point to two reasons for using this metaphor. First, GenAI can produce multimodal content quickly, at low cost, and continuously. Second, it highlights the pollution plastic creates in nature and how this easily accessible material threatens ecosystems. In other words, GenAI content is not only an easily accessible danger but also heralds a human-data paradox. Durango et al. (2025) highlight that the potential solution to the human-data interaction paradox lies in developing transparent, controllable, and user-centered AI systems.

GenAI also brings several industrial problems together. Chief among these are problems related to work environments. Walkowiak & Potts (2024) argue that GenAI reduces and artificializes the human impact on work environments. Another issue the authors focus on is that GenAI technologies disrupt the existing skills of workers in many sectors. Although there are claims that it increases employee productivity (Malik et al., 2021; Shchepkina et al., 2024), it has been found to lower employees’ psychological expectations, which consist of their emotional and financial expectations from their employers (Braganza et al., 2021). Indeed, individuals accustomed to easy production may become increasingly dependent on GenAI technologies.

GenAI is a technology that also carries social and cultural risks. The creation and development of these technologies require significant capital investment, which inevitably leads to control becoming centralized in the hands of the system’s owners (Kalantzis & Cope, 2025). This centralization coincides with the observation by Burnett & Merchant (2015) that the owners of meaning-

producing tools can also direct meaning. In other words, users/consumers have no choice but to be exposed to this meaning and adapt to the masses who embrace it. At the same time, these systems, which collect data indiscriminately from the internet, can reproduce historical biases such as racism and sexism found in training data (Bender et al., 2021; Magee et al., 2021). When this phenomenon combines with the algorithmic logic of social media, it suggests that a media ecosystem dominated by fake and misinformative content, where synthetic and social participation is reduced to sensationalism, could be created (P. Wang, 2022). This ecosystem disrupts media literacy by merging the flow of daily life with artificial language models in a synthetic and surreal reality (Kalantzis & Cope, 2025).

5. Digital Content Generation Strategies Using Prompt Frameworks

The benefit of Gen-AI models varies depending on the used models as well as the quality of the input prompts. This is because the transformer technique underlying the Gen-AI approach actually aims to complete the text based on the input. Therefore, the quality of the input directly affects the output generated by the model. This has led to the emergence of the prompt engineering field, defined as the design of input prompts to produce contextually relevant content, tailored to the audience, and of high informational value (Schulhoff et al., 2025). Marketing employees should consider a proper prompt framework to maximize the value of AI-generated content. While various prompt framework structures are applied based on practical expectations, three principles can be presented as core in the following:

- **Zero-Shot vs. Few-Shot Prompting:** Zero-shot prompting is the most basic form of interaction between the model and the user. It contains only a description of the task in natural language without any examples (Alammar & Grootendorst, 2024). Therefore, it relies entirely on the model's pretrained knowledge and understanding of language to interpret and perform the user's request. In few-shot, on the contrary, a set of examples (shots) is embedded within the prompt to guide the model towards the expected output pattern, format, or style. Few-shot prompting outperformed zero-shot prompting on classification tasks that require guidance, achieving significantly higher performance (Binkhonain & Alfayez, 2025).

- **Single-Task vs. Multi-Task Prompting:** While GenAI models like GPT are typically asked to perform specific or single tasks, they can also handle

more complex, multi-step analytical assignments. The common belief is that models obtain better generated content when tasks are performed individually rather than combined. Nonetheless, research by Gozzi and Di Maio (2024) reported that prompts contains only single task do not consistently obtain better performance compared to those contains multiple tasks. From a digital marketing perspective as well, combining prompts for related tasks and querying them together may lead to more beneficial content generation.

- **Chain-of-Thought (CoT) Prompting:** Unlike zero-shot and few-shot approaches, CoT prompting tries to simulate human cognition, called “reasoning”, in order to show how output content is generated step by step. With the reasoning-based approach, content generation process of the model can be explicitly traced (Shen et al., 2025). Additionally, this reasoning process can also be applied in multimodal, such as image or video generation.

Besides these several subsequent frameworks have been proposed, Tree-of-Thought (ToT) which represent reasoning steps like a tree ReAct (Reason+Act) which incorporate actions with reasoning for agentic tasks, Automatic Prompt Engineer (APE) which tries to automate prompt generation with testing, and Meta-Prompting which uses older prompts to dynamically generate final one (Esteban, 2025).

In spite of these core methods providing fundamental ideas for prompting, their practical application could be varied depending on the problem being addressed. For this purpose, users have developed a variety of structured frameworks to form effective prompting into repeatable, scalable, and teachable formats. Their primary function is to remove ambiguity and ensure that all critical elements—such as role, context, and expected format—are included in a prompt. For instance, a popular framework TAG focuses on the 3 objective Task (what needs to be done), Action (the method or approach to use), and ultimate Goal (the strategic purpose of the output). It is beneficial for content ideation and brainstorming because the model is expected to generate output without any routing example, similar to the zero-shot approach.

Since it is widely adopted in the areas of traditional and online marketing to evaluate advertisement communication effectiveness and inform marketing communication strategies, the AIDA model is one of the most commonly referenced frameworks in the literature when considering a marketing perspective (Hassan et al., 2015). The acronym AIDA stands for “Attention” to first grab, then build “Interest”, create “Desire”, and make a specific “Action”, describing the

psychological process consumers go through, from encountering an advertisement to making a purchase. Hence, AIDA has a natural ability to guide LLMs from a marketing perspective. A recent study also supports that, indicating that the classical AIDA model has been used to ground a theoretical basis in the development and enhancement of evaluative metrics for advertisements produced by such LLMs (Sun et al., 2025). By structuring prompt input using AIDA's stages (Attention, Interest, Desire, and Action), LLM has been provided with a psychologically grounded roadmap that helps the model focus on consumer-relevant messaging strategies. Therefore, the AIDA prompting works well in generating sales pages, email marketing, video sales letters and product descriptions.

Another well-known framework is BAB, which is a storytelling-oriented approach that structures a narrative by describing the situation before an event, the situation after the event, and the bridge that connects the two states (Lynch et al., 2025). The guidance to connect between before and after states, based on a specified aim, makes BAB stand out in copywriting tasks, such as social media ad copy, landing page sections, and video scripts, to evoke an emotional response. Moreover, by bounding marketing product as a “Bridge” from a problem (“Before”) to a solution (“After”), it creates benefit-focused copy that is highly effective for ads. In this way, it shifts the focus from product features to customer benefits and transformation. In digital marketing, highlighting the impressive and beneficial features of a product via platforms such as social media, websites, or flyers is of great importance. By allowing content to be connected via a “before-and-after” perspective, the BAB framework makes it easier to generate proper content to show how a product meets customer expectations. This not only strengthens audience engagement but also lightens the workload for those creating digital marketing content.

While digital content generation usually aims to produce something new, it also be used to mitigate addressing existing content-related issues. The Problem–Action–Result (PAR) framework stands out as a particularly effective and solution-driven approach for such scenarios. The PAR model works by breaking prompt into three parts: defining problems, explaining how to solve them, and putting in expected results. Structuring the prompt with three information guides the model resulting in targeted outputs that drive problem-solving. For example, if a website has a SEO-oriented optimization issue, the PAR framework can be utilized to generate a blog post targeting a specific keyword. From a digital marketing perspective, hence, the PAR prompting offer is even more valuable since it solve content-related problems with GenAI.

A more structured and adaptable prompting framework may be needed during digital content generation. CO-STAR framework provides more systematic prompting for the users. The CO-STAR framework stands for Context, Objective, Style, Tone, Audience, Response parts to provide more guided instruction for the model (Pham & Ngoc, 2025). Particularly in need of structured and professional communication content, CO-STAR improves generative performance by enabling adaptive reasoning, shift context smoothly, and adjust output depending on audience. Therefore, this framework holds out a robust strategy generating content that aligns with brand identity, maintains tonal consistency, and addresses audience expectations.

6. Conclusion

Cutting-edge advancements in AI technologies have led to changes in AI, giving rise to GenAI over the last decade. While traditional AI aims to develop decision-support and automation systems containing classification and clustering methods, GenAI can simulate human-like thinking, creativity, and deep analysis, and in some cases even surpass human performance. Along with education, entertainment, social media, and research, this revolutionary approach has impacted businesses, institutions, and organizations, one of which is digital content marketing. This is because GenAI allows marketers to generate personalized product suggestions, customized emails, and service-related social media posts with only some prompts. Even though expert-generated content may be better and more realistic than generated, they are time-consuming and costly. In addition, making changes to expert-generated content may also cause delays. On the other hand, GenAI can generate content rapidly within the desired context, including easy customization and personalization potential.

However, to maximize these opportunities and advantages, GenAI systems should be provided with reasonable inputs, which is practically achieved through the use of prompt frameworks, called prompting. Prompting focuses on structuring an input query to generate high-value, context-aware, audience-specific content. Practically, dozens—even hundreds—of prompt frameworks exist to address specific tasks. Nevertheless, some of them stand out for digital content marketing. AIDA (Attention, Interest, Desire, Action), a traditional marketing model, has been adapted within large language models (LLMs) to provide a grounded roadmap for generating advertising copy, sales pages, and other digital content. BAB is another well-known prompt framework that generates content using before-and-after storytelling-oriented scenarios. In

this way, it can make a connection between beneficial features with presented product. In order to mitigate the issues related to digital content, marketing professionals could benefit from the PAR framework. PAR provides clear, structured, and solution-oriented guidance to the model, enabling it to define and develop solutions for issues arising from digital content. If marketers need a more customizable and adaptable digital content, then the CO-STAR (Context, Objective, Style, Tone, Audience, Response) prompt framework would be the best choice. CO-STAR improves the model's generation capabilities by promoting flexible reasoning, smooth contextual transitions, and real-time adaptability. This framework enables the determination of key factors, including target audience, language tone, and output format.

ACKNOWLEDGEMENT

The authors used Gemini 2.5 Pro tool to improve the manuscript's clarity and grammatical corrections.

REFERENCES

- Adam, M., Bauer, K., Jussupow, E., Stein, M.-K., & Benlian, A. (2025). Generating Tomorrow's Me: How Collaborating with Generative AI Changes Humans. *Business & Information Systems Engineering*. <https://doi.org/10.1007/s12599-025-00961-3>
- Adeyinka, K. I., & Adeyinka, T. I. (2025). Impact of Generative AI on Industries. In *Humans and Generative AI Tools for Collaborative Intelligence* (pp. 237–262). IGI Global Scientific Publishing. <https://doi.org/10.4018/979-8-3693-8332-2.ch010>
- Agata, K., Christof, B., Benjamin, B., & Fabian, B. (2024). *Digital Content Marketing Creating Value in Practice*.
- Alammar, J., & Grootendorst, M. (2024). *Hands-On Large Language Models: Language Understanding and Generation*. O'Reilly Media, Inc.
- Astawa, I. P. P., & Arsha, I. M. R. M. (2024). Artificial Intelligence and Business Models from the Perspective of Innovation and Operational Efficiency of Companies: Systematic Literature Review. *International Journal of Research and Innovation in Social Science (IJRISS)*, 8(11), 1882–1899. <https://doi.org/10.47772/IJRISS.2024.8110147>
- Bahdanau, D., Cho, K., & Bengio, Y. (2016). *Neural Machine Translation by Jointly Learning to Align and Translate* (No. arXiv:1409.0473). arXiv. <https://doi.org/10.48550/arXiv.1409.0473>

Balla, R. T. (2025). Enabling Cognitive Process Automation Using LLMs in ERP Systems with Generative AI. *World Journal of Advanced Engineering Technology and Sciences*, 15(3), 1467–1474. <https://doi.org/10.30574/wjaets.2025.15.3.1045>

Bello, O. A., Ogundipe, A., Mohammed, D., Adebola, F., & Alonge, O. A. (2023). AI-driven approaches for real-time fraud detection in US financial transactions: Challenges and opportunities. *European Journal of Computer Science and Information Technology*, 11(6), 84–102.

Bender, E. M., Gebru, T., McMillan-Major, A., & Shmitchell, S. (2021). On the Dangers of Stochastic Parrots: Can Language Models Be Too Big? *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, 610–623. <https://doi.org/10.1145/3442188.3445922>

Binkhonain, M., & Alfayez, R. (2025). Are prompts all you need? Evaluating prompt-based Large Language Models (LLM)s for software requirements classification. *Requirements Engineering*. <https://doi.org/10.1007/s00766-025-00451-8>

Bitaab, M., Cho, H., Oest, A., Lyu, Z., Wang, W., Abraham, J., Wang, R., Bao, T., Shoshitaishvili, Y., & Doupé, A. (2023). Beyond Phish: Toward Detecting Fraudulent e-Commerce Websites at Scale. *2023 IEEE Symposium on Security and Privacy (SP)*, 2566–2583. <https://doi.org/10.1109/SP46215.2023.10179461>

Braganza, A., Chen, W., Canhoto, A., & Sap, S. (2021). Productive employment and decent work: The impact of AI adoption on psychological contracts, job engagement and employee trust. *Journal of Business Research*, 131, 485–494. <https://doi.org/10.1016/j.jbusres.2020.08.018>

Brüns, J. D., & Meißner, M. (2024). Do you create your content yourself? Using generative artificial intelligence for social media content creation diminishes perceived brand authenticity. *Journal of Retailing and Consumer Services*, 79, 103790. <https://doi.org/10.1016/j.jretconser.2024.103790>

Burnett, C., & Merchant, G. (2015). The Challenge of 21st-Century Literacies. *Journal of Adolescent & Adult Literacy*, 59(3), 271–274. <https://doi.org/10.1002/jaal.482>

Chaffey, D., & Ellis-Chadwick, F. (2022). *Digital Marketing: Strategy, Implementation and Practice* (8th ed.). Pearson Education.

Deveau, R., Griffin, S. J., & Reis, S. (2023). AI-powered marketing and sales reach new heights with generative AI. *McKinsey & Company*.

Durango, I., Gallud, J. A., & Penichet, V. M. R. (2025). The data dance: Choreographing seamless partnerships between humans, data, and GenAI.

International Journal of Data Science and Analytics, 20(4), 3613–3640. <https://doi.org/10.1007/s41060-024-00684-w>

Dwivedi, Y. K., Kshetri, N., Hughes, L., Slade, E. L., Jeyaraj, A., Kar, A. K., Baabdullah, A. M., Koohang, A., Raghavan, V., Ahuja, M., Albanna, H., Albashrawi, M. A., Al-Busaidi, A. S., Balakrishnan, J., Barlette, Y., Basu, S., Bose, I., Brooks, L., Buhalis, D., ... Wright, R. (2023). Opinion Paper: “So what if ChatGPT wrote it?” Multidisciplinary perspectives on opportunities, challenges and implications of generative conversational AI for research, practice and policy. *International Journal of Information Management*, 71, 102642. <https://doi.org/10.1016/j.ijinfomgt.2023.102642>

Esteban, A. P. (2025). Creative CRAFT: A structured framework for creativity-driven prompt engineering in generative AI. *International Journal of Innovative Research and Scientific Studies*, 8(5), 1651–1664. <https://doi.org/10.53894/ijirss.v8i5.9229>

Fehrer, J. A., Woratschek, H., Germelmann, C. C., & Brodie, R. J. (2018). Dynamics and drivers of customer engagement: Within the dyad and beyond. *Journal of Service Management*, 29(3), 443–467. <https://doi.org/10.1108/JOSM-08-2016-0236>

Feuerriegel, S., Hartmann, J., Janiesch, C., & Zschech, P. (2024). Generative AI. *Business & Information Systems Engineering*, 66(1), 111–126. <https://doi.org/10.1007/s12599-023-00834-7>

Floridi, L. (2024). On the Future of Content in the Age of Artificial Intelligence: Some Implications and Directions. *Philosophy & Technology*, 37(3), 112. <https://doi.org/10.1007/s13347-024-00806-z>

Gartner. (2023). *Enterprise Guide to Generative AI: Expert Insights on ROI, Use Cases, and Cost Management*. Gartner. <https://www.gartner.com/en/topics/generative-ai>

Goodfellow, I. J., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., Courville, A., & Bengio, Y. (2014). *Generative Adversarial Networks* (No. arXiv:1406.2661). arXiv. <https://doi.org/10.48550/arXiv.1406.2661>

Gozzi, M., & Di Maio, F. (2024). Comparative Analysis of Prompt Strategies for Large Language Models: Single-Task vs. Multitask Prompts. *Electronics*, 13(23), 4712. <https://doi.org/10.3390/electronics13234712>

Guha, A., Grewal, D., Kopalle, P. K., Haenlein, M., Schneider, M. J., Jung, H., Moustafa, R., Hegde, D. R., & Hawkins, G. (2021). How artificial intelligence will affect the future of retailing. *Journal of Retailing*, 97(1), 28–41. <https://doi.org/10.1016/j.jretai.2021.01.005>

Handley, A., & Chapman, C. C. (2012). *Content rules: How to create killer blogs, podcasts, videos, ebooks, webinars (and more) that engage customers and ignite your business*. John Wiley & Sons.

Hassan, S., Nadzim, S. Z. A., & Shiratuddin, N. (2015). Strategic Use of Social Media for Small Business Based on the AIDA Model. *Procedia - Social and Behavioral Sciences*, 172, 262–269. <https://doi.org/10.1016/j.sbspro.2015.01.363>

Hidayat, R., Rahayu, A., Adib, M., & Cahyani, L. (2024). Understanding Digital Content Marketing on Purchase Intention Incitement: Online Store Platform. *WSEAS Transactions on Information Science and Applications*, 21, 538–546. <https://doi.org/10.37394/23209.2024.21.50>

Hollebeek, L. D., & Macky, K. (2019). Digital Content Marketing's Role in Fostering Consumer Engagement, Trust, and Value: Framework, Fundamental Propositions, and Implications. *Journal of Interactive Marketing*, 45(1), 27–41. <https://doi.org/10.1016/j.intmar.2018.07.003>

Hua, Y., Niu, S., Cai, J., Chilton, L. B., Heuer, H., & Wohn, D. Y. (2024). Generative AI in User-Generated Content. *Extended Abstracts of the CHI Conference on Human Factors in Computing Systems*, 1–7. <https://doi.org/10.1145/3613905.3636315>

Huynh, M.-T., & Aichner, T. (2025). In generative artificial intelligence we trust: Unpacking determinants and outcomes for cognitive trust. *AI & SOCIETY*. <https://doi.org/10.1007/s00146-025-02378-8>

Järvinen, J., & Taiminen, H. (2016). Harnessing marketing automation for B2B content marketing. *Industrial Marketing Management*, 54, 164–175. <https://doi.org/10.1016/j.indmarman.2015.07.002>

Jeon, J., & Suh, Y. (2017). Analyzing the Major Issues of the 4 th Industrial Revolution. *Asian Journal of Innovation & Policy*, 6(3).

Kalantzis, M., & Cope, B. (2025). Literacy in the Time of Artificial Intelligence. *Reading Research Quarterly*, 60(1), e591. <https://doi.org/10.1002/rrq.591>

Kshetri, N., Dwivedi, Y. K., Davenport, T. H., & Panteli, N. (2024). Generative artificial intelligence in marketing: Applications, opportunities, challenges, and research agenda. *International Journal of Information Management*, 75, 102716. <https://doi.org/10.1016/j.ijinfomgt.2023.102716>

Kulkarni, A., Shivananda, A., Kulkarni, A., & Gudivada, D. (2023). ChatGPT Use Cases. In A. Kulkarni, A. Shivananda, A. Kulkarni, & D. Gudivada (Eds.), *Applied Generative AI for Beginners: Practical Knowledge*

on Diffusion Models, ChatGPT, and Other LLMs (pp. 179–206). Apress. https://doi.org/10.1007/978-1-4842-9994-4_9

Kunz, W. H., & Wirtz, J. (2023). Corporate digital responsibility (CDR) in the age of AI: Implications for interactive marketing. *Journal of Research in Interactive Marketing*, 18(1), 31–37. <https://doi.org/10.1108/JRIM-06-2023-0176>

Li, J., Wang, D., Zhao, C., & Tang, J. (2022). MUI-VB: Malicious URL Identification Model Combining VGG and Bi-LSTM. *Proceedings of the 2022 3rd International Conference on Control, Robotics and Intelligent System*, 141–148. <https://doi.org/10.1145/3562007.3562033>

Liu, K., Wei, Z., Zhang, C., Shang, Y., Teodorescu, R., & Han, Q.-L. (2022). Towards Long Lifetime Battery: AI-Based Manufacturing and Management. *IEEE/CAA Journal of Automatica Sinica*, 9(7), 1139–1165. <https://doi.org/10.1109/JAS.2022.105599>

Lopes, A. R., & Casais, B. (2022). Digital Content Marketing: Conceptual Review and Recommendations for Practitioners. *Academy of Strategic Management Journal*, 21(2), 1–166.

Lou, C., Xie, Q., Feng, Y., & Kim, W. (2019). Does non-hard-sell content really work? Leveraging the value of branded content marketing in brand building. *Journal of Product & Brand Management*, 28(7), 773–786. <https://doi.org/10.1108/JPBM-07-2018-1948>

Lynch, C. J., Jensen, E., Gore, R., Zamponi, V., O'Brien, K., Feldhaus, B., Smith, K., Martínez, J., Munro, M. H., Ozkose, T. E., Gundogdu, T. B., Reinhold, A. M., Kavak, H., & Ezell, B. (2025). AI-Generated Messaging for Life Events Using Structured Prompts: A Comparative Study of GPT With Human Experts and Machine Learning. *IEEE Access*, 13, 147002–147033. <https://doi.org/10.1109/ACCESS.2025.3600146>

Magee, L., Ghahremanlou, L., Soldatic, K., & Robertson, S. (2021). *Intersectional Bias in Causal Language Models* (No. arXiv:2107.07691). arXiv. <https://doi.org/10.48550/arXiv.2107.07691>

Malik, N., Tripathi, S. N., Kar, A. K., & Gupta, S. (2021). Impact of artificial intelligence on employees working in industry 4.0 led organizations. *International Journal of Manpower*, 43(2), 334–354. <https://doi.org/10.1108/IJM-03-2021-0173>

Mandvikar, S., & Achanta, A. (2023). Process automation 2.0 with generative AI framework. *Int. J. Sci. Res. (Raipur)*, 12(10), 1614–1619.

Mariani, M., & Dwivedi, Y. K. (2024). Generative artificial intelligence in innovation management: A preview of future research developments. *Journal of Business Research*, 175, 114542. <https://doi.org/10.1016/j.jbusres.2024.114542>

Matteo, S., & Zotto, C. D. (2015). Native Advertising, or How to Stretch Editorial to Sponsored Content Within a Transmedia Branding Era. In G. Siegert, K. Förster, S. M. Chan-Olmsted, & M. Ots (Eds.), *Handbook of Media Branding* (pp. 169–185). Springer International Publishing. https://doi.org/10.1007/978-3-319-18236-0_12

Menczer, F., Crandall, D., Ahn, Y.-Y., & Kapadia, A. (2023). Addressing the harms of AI-generated inauthentic content. *Nature Machine Intelligence*, 5(7), 679–680. <https://doi.org/10.1038/s42256-023-00690-w>

Miikkulainen, R. (2024). Generative AI: An AI paradigm shift in the making? *AI Magazine*, 45(1), 165–167. <https://doi.org/10.1002/aaai.12155>

Munn, L., Magee, L., & Arora, V. (2024). Truth machines: Synthesizing veracity in AI language models. *AI & SOCIETY*, 39(6), 2759–2773. <https://doi.org/10.1007/s00146-023-01756-4>

Narsimha, B., Raghavendran, C. V., Rajyalakshmi, P., Reddy, G. K., Bhargavi, M., & Naresh, P. (2022). Cyber Defense in the Age of Artificial Intelligence and Machine Learning for Financial Fraud Detection Application. *International Journal of Electrical and Electronics Research*, 10(2), 87–92. <https://doi.org/10.37391/ijeer.100206>

Noy, S., & Zhang, W. (2023). Experimental evidence on the productivity effects of generative artificial intelligence. *Science*, 381(6654), 187–192. <https://doi.org/10.1126/science.adh2586>

Obaidat, M., Almomani, H. A., Mallouhy, R., AlMotari, A., & Al Meanazel, O. T. (2025). A Hybrid Machine Learning Framework for Daily Dairy Demand Forecasting: Integrating SARIMAX and XGBoost for Seasonal Production Optimization. *IEEE Access*, 13, 162668–162680. <https://doi.org/10.1109/ACCESS.2025.3610316>

Odoom, R. (2025). Digital content marketing and consumer brand engagement on social media- do influencers' brand content moderate the relationship? *Journal of Marketing Communications*, 31(4), 491–514. <https://doi.org/10.1080/13527266.2023.2249013>

Özkuk, Ö. (2024). Fizikselden Dijitale: Dijital Pazarlamanın Temelleri. *Dijital Pazarlama Yönetimi*, 1.

P, R., Perumal, P., Mishra, B. R., Bharathi, S. S., Madhusudan Rao, D. V., & R., S. (2025). Harnessing Generative Ai For Hyper-Personalized Marketing: Impacts On Consumer Trust, Engagement, And Brand Loyalty. *Advances in Consumer Research*, 2(4), 1030–1037.

Pham, T., & Ngoc, T. N. (2025). Improving LLM's Response with a New Prompt Framework RCFOR. *2025 10th International Conference on Applying*

New Technology in Green Buildings (ATiGB), 666–670. <https://doi.org/10.1109/ATiGB66719.2025.11142192>

Plessis, C. du. (2017). The role of content marketing in social media content communities. *South African Journal of Information Management*, 19(1), 7. <https://doi.org/10.4102/sajim.v19i1.866>

Pulikal, S., Patil, N., Raut, C. M., & Patil, S. M. (2025). A Paradigm Shift in Educational Content Creation: Leveraging Generative AI for On-Demand Course Generation. *Journal of Engineering and Technology Management*, 75, 77–94.

Reeder, I. I. I., Chaker, N., & Habel, J. (2025). *Forecasting Sales in B2B Markets with Unstructured Data: Unreliable Narrators and Large Language Models* (SSRN Scholarly Paper No. 4848956). Social Science Research Network. <https://doi.org/10.2139/ssrn.4848956>

Reisenbichler, M., Reutterer, T., Schweidel, D. A., & Dan, D. (2022). Frontiers: Supporting Content Marketing with Natural Language Generation. *Marketing Science*, 41(3), 441–452. <https://doi.org/10.1287/mksc.2022.1354>

Roe, J., Furze, L., & Perkins, M. (2025). *GenAI as Digital Plastic: Understanding Synthetic Media Through Critical AI Literacy* (No. arXiv:2502.08249). arXiv. <https://doi.org/10.48550/arXiv.2502.08249>

Roy, K., Paul, U. K., Tiwari, S., & Mookherjee, A. (2024). Impact of electronic word of mouth (e-WOM) on purchasing decisions: An empirical study. *Benchmarking: An International Journal*. <https://doi.org/10.1108/BIJ-08-2024-0642>

Ruane, L., & Wallace, E. (2015). Brand tribalism and self-expressive brands: Social influences and brand outcomes. *Journal of Product & Brand Management*, 24(4), 333–348. <https://doi.org/10.1108/JPBM-07-2014-0656>

Rüther, M. (2025). The meaningfulness gap in AI ethics: A guide on how to think through a complex challenge. *AI & SOCIETY*, 40(3), 1403–1415. <https://doi.org/10.1007/s00146-024-01993-1>

Schulhoff, S., Ilie, M., Balepur, N., Kahadze, K., Liu, A., Si, C., Li, Y., Gupta, A., Han, H., Schulhoff, S., Dulepet, P. S., Vidyadhara, S., Ki, D., Agrawal, S., Pham, C., Kroiz, G., Li, F., Tao, H., Srivastava, A., ... Resnik, P. (2025). *The Prompt Report: A Systematic Survey of Prompt Engineering Techniques* (No. arXiv:2406.06608). arXiv. <https://doi.org/10.48550/arXiv.2406.06608>

Shchepkina, N., Ramnarayan, R., Dhaliwal, N., K, R., & Nangia, R. (2024). Human-Centric AI Adoption and Its Influence on Worker Productivity: An Empirical Investigation. *BIO Web of Conferences*, 86, 01060. <https://doi.org/10.1051/bioconf/20248601060>

Shen, X., Wang, S., Tan, Z., Yao, L., Zhao, X., Xu, K., Wang, X., & Chen, T. (2025). *FaithCoT-Bench: Benchmarking Instance-Level Faithfulness of Chain-of-Thought Reasoning* (No. arXiv:2510.04040). arXiv. <https://doi.org/10.48550/arXiv.2510.04040>

Shumailov, I., Shumaylov, Z., Zhao, Y., Papernot, N., Anderson, R., & Gal, Y. (2024). AI models collapse when trained on recursively generated data. *Nature*, 631(8022), 755–759. <https://doi.org/10.1038/s41586-024-07566-y>

Simmons, A. B., & Chappell, S. G. (1988). Artificial intelligence-definition and practice. *IEEE Journal of Oceanic Engineering*, 13(2), 14–42. <https://doi.org/10.1109/48.551>

Sun, L., An, Y., Song, X., & Liu, J. (2025). Human vs. AI in creative contests: A study on the effectiveness of advertisement copy generated by Chinese large language models. *Electronic Commerce Research*. <https://doi.org/10.1007/s10660-025-09990-2>

Terho, H., Mero, J., Siutla, L., & Jaakkola, E. (2022). Digital content marketing in business markets: Activities, consequences, and contingencies along the customer journey. *Industrial Marketing Management*, 105, 294–310. <https://doi.org/10.1016/j.indmarman.2022.06.006>

Thompson, A. (2025, February 5). Digital 2025: The essential guide to the global state of digital. *We Are Social UK*. <https://wearesocial.com/uk/blog/2025/02/digital-2025-the-essential-guide-to-the-global-state-of-digital/>

Tuna, M. F. (2024). STEAKHOUSE İŞLETMELERİNE BİR REKLAM HUNİSİ ÖNERİSİ: PROSPEKTİF BİR DİJİTAL PAZARLAMA YAKLAŞIMI. *Economics Business and Organization Research*, 6(2), 65–96.

Tuna, M. F., Özkuk, Ö., Biçer, D. F., Etiz, B., Kartal, C., Bozacı, İ., Akçadağ, M., Aliçavuşoğlu, Ç., Erdoğan, Z., Kazak, M., Yılmaz, E. S., Danacı, E. Ş., Bayraktar, E. D., Apaydın, İ. Z., Sönmez, A. T., Etlioğlu, M., Aktepe, H. S., Köseoğlu, R., & Eru, O. (2024). *Dijital Pazarlama Yönetimi*. Özgür Yayınları. <https://doi.org/10.58830/ozgur.pub610>

van Doorn, J., Lemon, K. N., Mittal, V., Nass, S., Pick, D., Pirner, P., & Verhoef, P. C. (2010). Customer Engagement Behavior: Theoretical Foundations and Research Directions. *Journal of Service Research*, 13(3), 253–266. <https://doi.org/10.1177/1094670510375599>

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, L., & Polosukhin, I. (2023). *Attention Is All You Need* (No. arXiv:1706.03762). arXiv. <https://doi.org/10.48550/arXiv.1706.03762>

Vengathattil, S. (2025). Artificial Intelligence: Myths and Facts. *International Journal of Science and Research (IJSR)*, 14(2.), 1468–1473. <https://doi.org/10.21275/SR25223063545>

Verma, A. (2025). *Blending Brand Personality and Information: A Review of Content Strategies Driving Consumer Engagement in Social Media Advertising* (SSRN Scholarly Paper No. 5261429). Social Science Research Network. <https://doi.org/10.2139/ssrn.5261429>

Verma, U. (2024). A journey from AI to Gen-AI. *Spectrum of Emerging Sciences*, 4(1), 74–78. <https://doi.org/10.55878/SES2024-4-1-16>

Vo Quang, M., Bui Tan Hai, D., Tran Kim Ngoc, N., Ngo Duc Hoang, S., Nguyen Huu, Q., Phan The, D., & Pham, V.-H. (2023). Shark-Eyes: A multimodal fusion framework for multi-view-based phishing website detection. *Proceedings of the 12th International Symposium on Information and Communication Technology*, 793–800. <https://doi.org/10.1145/3628797.3629003>

Wahid, R., Mero, J., & Ritala, P. (2023). Editorial: Written by ChatGPT, illustrated by Midjourney: generative AI for content marketing. *Asia Pacific Journal of Marketing and Logistics*, 35(8), 1813–1822. <https://doi.org/10.1108/APJML-10-2023-994>

Walkowiak, E., & Potts, J. (2024). *Generative AI, Work and Risks in Cultural and Creative Industries* (SSRN Scholarly Paper No. 4830265). Social Science Research Network. <https://doi.org/10.2139/ssrn.4830265>

Wall, A., & Spinuzzi, C. (2018). The art of selling-without-selling: Understanding the genre ecologies of content marketing. *Technical Communication Quarterly*, 27(2), 137–160. <https://doi.org/10.1080/10572252.2018.1425483>

Wang, P. (2022). Recommendation algorithm in TikTok: Strengths, dilemmas, and possible directions. *Int'l J. Soc. Sci. Stud.*, 10, 60.

Wang, W., Bell, J. J., Dotson, J. P., & Schweidel, D. A. (2025). *Generative AI May Be Good For Artists: Understanding the Impact of Artistic Style on Preference and Willingness to Pay* (SSRN Scholarly Paper No. 4428509). Social Science Research Network. <https://doi.org/10.2139/ssrn.4428509>

Xie, J., Li, M., Du, R., & Townsend, D. M. (2025). The Impact of Generative AI Models on Consumer Purchase Behavior in E-Commerce Platforms: Evidence from a Quasi-Natural Experiment. In Y. P. Tu & M. Chi (Eds.), *E-Business. Generative Artificial Intelligence and Management Transformation* (pp. 224–235). Springer Nature Switzerland. https://doi.org/10.1007/978-3-031-94184-9_19

CHAPTER XII

GENERATIVE ARTIFICIAL INTELLIGENCE IN EDUCATIONAL TECHNOLOGIES

Mehmet Ali DEVECİ¹ & Yasin GÖRMEZ² & Sait BARDAKÇI³

¹(Res. Asst.) Sivas Cumhuriyet University, Sivas, Türkiye
e-mail: madeveci@cumhuriyet.edu.tr
orcid: 0009-0006-8604-0135

²(Asst. Prof.) Sivas Cumhuriyet University, Sivas, Türkiye
e-mail: yasingormez@cumhuriyet.edu.tr
orcid: 0000-0001-8276-2030

³(Asst. Prof.) Sivas Cumhuriyet University, Sivas, Türkiye
e-mail: sbardakci@cumhuriyet.edu.tr
orcid: 0000-0003-3720-5029

1. Introduction and Foundations

1.1. An Overview of Artificial Intelligence

In today's world, where technology is more important than ever, one of the most important and remarkable developments has undoubtedly been artificial intelligence technology. So much so that artificial intelligence technologies have become an indispensable part of our lives in many areas of our daily lives. Many technologies such as smart mobile phone applications, smart homes and home appliances, and cars with autonomous drivers can be given as examples of real-life equivalents of artificial intelligence technologies.

From this perspective, it can be argued that artificial intelligence is not merely a development related to computer technology; it appears in every aspect of life. So, artificial intelligence is directly related to many branches of science, from medicine and engineering to psychology, and is a field whose framework is tailored to each of their needs. Artificial intelligence has even been approached

from a philosophical perspective, exploring the role of machines in simulating life (Doğan, 2002).

It is believed that the widespread use of these technologies, which we use almost every moment of our lives, in the education sector could lead to significant advancements. Education systems worldwide are also constantly renewing themselves in line with the use of artificial intelligence applications. In our country, the Ministry of National Education aims to utilize artificial intelligence applications to improve education in line with its objectives. In this regard, studies conducted on the subject are crucial for providing information on the areas and benefits of artificial intelligence in education, enabling educators to stay current on the subject, and adapting to new technologies. In addition, the study is important in terms of providing up-to-date information and being a resource for those who want to work on artificial intelligence-based education (İşler and Kılıç, 2021).

1.1.1. Conceptual Definition

Artificial intelligence is a branch of computer science that focuses on the modeling and imitation of human cognitive processes by machines. It is also an interdisciplinary field at the intersection of cognitive science, mathematics, engineering, and philosophy. Achieving the capacity of computers to think, learn, and make decisions like humans is considered one of the most important scientific goals in human history.

The concept of artificial intelligence was first defined by John McCarthy at the Dartmouth Conference in 1956. McCarthy (1956) defined artificial intelligence as “the science and engineering of making intelligent machines”. This definition encompasses both the cognitive science and engineering dimensions of artificial intelligence. Artificial intelligence is generally divided into two main categories: Narrow (weak) artificial intelligence and general (strong) artificial intelligence (Searle, 1980). Narrow artificial intelligence refers to systems designed to perform specific tasks, while general artificial intelligence targets systems with flexible human-like thinking capacities. Beyond these two approaches, the concept of artificial superintelligence is also discussed in contemporary literature (Bostrom, 2014).

1.1.2. Historical Development

The foundations of artificial intelligence date back to Alan Turing’s 1950 article, “Computing Machinery and Intelligence.” In this article, Turing posed the

question, “Can machines think?”, establishing both the philosophical and technical foundations of artificial intelligence. The Dartmouth Conference of 1956 is considered the birth of artificial intelligence as an academic field (Crevier, 1993).

Expert systems, developed in the 1960s and 1970s, aimed to mimic the decision-making processes of human experts in specific domains (Nilsson, 1998). This period marked the rise of symbolic representation and logic-based systems. The “Logic Theorist” and “General Problem Solver” programs developed by Newell and Simon (1972) can be considered early examples of attempts to model human problem-solving processes.

In the 1980s, the machine learning paradigm came to the fore in artificial intelligence research. The backpropagation algorithm developed by Rumelhart, Hinton, and Williams (1986) brought renewed interest to artificial neural networks. Since the 2000s, increasing data volume, processing power, and algorithmic advancements have radically transformed artificial intelligence research. Deep learning algorithms that emerged during this period have become capable of identifying complex patterns using multilayer neural networks (LeCun, Bengio, & Hinton, 2015). As a result of these advances, artificial intelligence has become applicable in many fields, including healthcare, transportation, finance, education, and the arts (Russell & Norvig, 2021).

1.2. Emergence and Examples of Generative Artificial Intelligence

While artificial intelligence essentially refers to systems that perform tasks such as analyzing data, drawing conclusions, classifying, and making predictions, the “generative” form of artificial intelligence has also gained traction in recent years. Generative AI encompasses models that not only process existing data but can also generate new content (text, images, code, music, etc.) (McKinsey, 2024).

Two key technical paradigms stand out in the rise of generative AI: Generative Adversarial Networks (GANs) and Transformer-based language models. GANs can generate realistic content thanks to two competing neural networks (generator and discriminator). Transformer models, on the other hand, gain powerful text generation capabilities through pretraining on large language datasets and subsequent fine-tuning for specific tasks.

In the 2020s, these models have increasingly acquired larger parameter counts, larger training data sets, and higher computational power. For example, GPT-3 is a model trained with 175 billion parameters. This development process paved the way for the widespread adoption of applications like ChatGPT (McKinsey, 2024).

The first uses of generative AI in education began with natural language processing (NLP)-focused applications such as written text generation, summarization, and question-answer systems. Over time, visual generative models (e.g., DALL·E, MidJourney) also became widespread and were incorporated into educational technologies in disciplines such as art, design, and storytelling (Ng et al., 2025).

ChatGPT

ChatGPT is a large language model developed by OpenAI (e.g., GPT-3 and later) that provides a chat interface that responds to natural language input. It generates text based on user prompts, answers questions, offers suggestions, edits text, etc. (Fisk, 2023).

ChatGPT has broad potential for use in education: it can guide students with written tasks, create writing drafts, support teaching content, and assist teachers with lesson planning (Gill et al., 2023). However, the model carries the risk of “hallucination” (producing content that appears false but satisfactory); moreover, the feature structure of the model outputs may differ from students’ natural writing style (e.g., excessive use of nominalizations) (Herbold et al., 2023).

DALL·E

DALL·E is a model that can generate images in response to prompts provided by users using natural language. It works in the text-to-image task. OpenAI first released DALL·E, then DALL·E 2 and DALL·E 3. DALL·E stands out for its ability to combine conceptual and stylistic elements.

Such models have the potential to be used in education, particularly in fields such as visual art, graphic design, architecture, and visualization. For example, when a student provides a scene description, DALL·E can generate a corresponding image or create variations of existing images (Ng and Ho, 2025).

MidJourney

MidJourney is another popular generative model that focuses on generating high-quality images based on text prompts. It is particularly prominent in artistic and creative visual production. It is known among user communities as a tool used for stylistic variations, atmosphere, and aesthetic emphasis.

While DALL·E is more focused on direct APIs and integrations, MidJourney stands out for its user community, artistic aesthetics, and social collaborations. In an educational setting, MidJourney can support students’ artistic expression, stimulate visual thinking, and facilitate visual storytelling.

1.3. Evolution of Educational Technologies and Generative AI

Educational technologies are undergoing one of the most rapid transformations in human history. The transition from printed materials to digital learning platforms, and from there to generative AI-powered systems, has radically altered not only learning tools but also instructional design and pedagogy. While printed materials have expanded access to information, digital technologies have made learning accessible, interactive, and personalized. Generative AI, on the other hand, is transforming learning from a mere process of acquiring information to one of knowledge creation and creative collaboration.

Educational technologies have a transformative impact on access to information, learning styles, and teaching methods. Throughout human history, knowledge production and transfer have been reshaped by available technological opportunities. Today, with the rise of generative AI tools, education is evolving from cognitive support to personalized learning experiences (Siemens, 2013). The digitalization of education began in the late 20th century with the proliferation of computers and the internet. This process represents a shift from a print-centered model to interactive digital learning environments. Computer-assisted instruction (CAI), learning management systems (LMS), and open online courses (MOOCs) have been important components of this period (Anderson, 2008). Digital learning has enabled an educational approach independent of time and space, placing the student at the center of the learning process. Pedagogically, the constructivist approach to learning (Vygotsky, 1978) came to the forefront in this period. However, digitalization has also brought with it new problems such as cognitive overload, the digital divide, and a decrease in learning motivation.

With the second quarter of the 21st century, artificial intelligence has become central to educational technologies. Learning analytics, adaptive learning systems, and natural language processing-based tools have strengthened data-driven decision-making processes in education (Baker & Inventado, 2014). Generative artificial intelligence (e.g., ChatGPT, Claude, Gemini, DALL·E, etc.) represents the newest phase of this process. These systems not only provide access to information; It actively contributes to the learning process by producing text, images, code, and scenarios (Kasneci et al., 2023). Key contributions of generative AI in education include personalized learning, creative production support, and automation support for teachers. However, issues such as ethical use, copyright, and accuracy require careful integration of these technologies (Zawacki-Richter et al., 2019).

2. The Role of Generative Artificial Intelligence in Education

In the 21st century, educational environments have undergone a profound transformation process alongside technological advancements. Particularly, generative artificial intelligence (GenAI) models, with their capacity to automatically generate text, images, code, and multimedia content, are creating new opportunities and challenges in the world of education. These technologies can integrate into the teaching process through functions such as question-answering tools, assignment support systems, and customized feedback tools (Monib et al., 2024; Giannakos et al., 2025). However, this transformation also brings new uncertainties in areas such as ethics, validity, equity, and academic integrity (Giannakos et al., 2025). The aim of this chapter is to systematically address the potential roles of generative AI in the educational context, evaluate the encountered limitations and ethical concerns, and discuss principles for how this technology can be positioned in educational practices. In this direction, the goal is to provide the reader with both a theoretical and practical framework.

2.1. Definition and Types: Large Language Models, Visual Generators, Audio/Video Tools

Generative artificial intelligence is the general term for systems that can learn from existing data samples and generate statistically similar yet original outputs (I. J. Goodfellow et al.). These models owe their designation as “generative” to their capacity not only to classify data but also to create new data. Prominent types of generative AI in the field of education can be examined in three main groups according to their functions:

2.1.1. Large Language Models

Today, there are many large language models (LLMs) with billions of parameters, such as ChatGPT, Gemini, Claude, DeepSeek, Mistral, and Grok, which demonstrate advanced performance in understanding and generating natural language. The contribution of these models to education is evaluated at three main levels: knowledge generation, writing support, and personalized learning. Knowledge generation involves explaining, summarizing, or rewriting complex concepts; writing support provides guidance in academic composition, assignment, and project development; and personalized learning can be defined as creating content and providing adaptive feedback according to the student’s level. Recent studies show that LLMs provide high efficiency, particularly

in language education, text summarization, and the production of teaching materials (Munaye et al., 2025; Aryadoust, Zakaria, & Jia, 2024).

2.1.2. Visual Generators

Tools like Midjourney, DALL-E 3, and Stable Diffusion can generate photorealistic or artistic images from textual descriptions. The foundation of these models is based on the diffusion process (R. Rombach, A., 2022). In education, they are considered powerful tools for concretizing abstract concepts; for example, in topics such as “the DNA replication process” or “the visualization of historical events.” New studies indicate that diffusion-based visual generation can enhance learning motivation (S. Buc and B. Divjak, 2015).

2.1.3. Audio and Video Generators

Audio and video generators offer significant advantages in education through text-to-speech conversion, text-to-video generation, and applications such as micro-learning videos or virtual teacher avatars. Cost reduction, ease of content updating, and scalability are considered the primary benefits of these technologies. For instance, a recent study compared AI-generated videos with traditional instructor videos and found no statistically significant difference in terms of learning outcomes, indicating that AI-generated videos can be a valid alternative in an educational context (D. Leiker, A., 2023).

2.2. Working Principles: Deep Learning, Language Models, and Multimodal Systems

Early generative AI systems based on convolutional neural networks failed to achieve the desired success. Subsequently, approaches based on Long Short-Term Memory and recurrent networks, which were highly successful in sequence-to-sequence tasks and could understand the concept of time series, increased the success rate in generative AI systems. However, models generated using these layers could have very long training and operation times. Therefore, the success of generative AI systems relies on deep learning architectures, particularly “Transformer”-based structures (A. Vaswani et al., 2023). This structure, by understanding long-range dependency relationships in language and visual data, enables the model to produce context-sensitive and meaningful outputs while also providing an advantage in speed compared to other layers.

2.2.1. Deep Learning Foundation

Generative AI models consist of multi-layered neural networks containing millions of parameters. The model learns the relationships between input data (e.g., words or pixels) and generates new samples through statistical probability distributions. This process is enhanced by a combination of “unsupervised learning” and “transfer learning” approaches (R. Bommasani et al., 2022). In educational applications, effective performance is achieved even in low-resource areas by fine-tuning pre-trained models with small datasets.

2.2.2. Language Models

Language models are fundamentally probability models based on predicting the next word in a sequence. The Transformer architecture can process much broader contextual relationships simultaneously compared to previous recurrent and LSTM approaches. Since the training of large language models occurs on datasets comprising trillions of words, the model can internalize the grammatical, semantic, and pragmatic features of language. This has turned them into not just “text completers” but “knowledge generator” systems.

2.2.3. Multimodal Systems

New-generation generative AI systems (e.g., ChatGPT, Gemini, Claude, Grok) can simultaneously understand text, visual, audio, and video inputs. Such systems are designed within the framework of the “multimodality” concept. The multimodal structure makes student-information interaction more holistic. For example, when a student uploads a handwritten solution, the model can read this solution visually and then explain the erroneous step. Recent studies show that multimodal models can increase learning efficiency by up to 30% in the production of teaching materials (H.-C. Lin et al., 2025).

2.3. Areas of Application

The applications of generative AI in education have spread across almost all components of the teaching process. GenAI provides significant innovations in fundamental areas such as course content creation, audiovisual material production, assessment and evaluation processes, and personalized learning.

2.3.1. Course Content Creation

Generative AI models provide significant support to teachers and educational designers in preparing lesson plans, explanatory texts, case studies,

stories, and summaries. These models save time in the teaching process and increase material diversity. For instance, large language models like ChatGPT, Gemini, and Grok can generate original content aligned with learning outcomes and offer creative ideas to teachers. Studies have shown that generative AI-based content creation can enhance teaching quality, particularly in STEM fields, and strengthen student learning motivation (C. Leon et al., 2025). Similarly, it has been emphasized that generative AI systems increase pedagogical efficiency in preparing teaching materials, but teacher supervision is essential for content reliability (Y. Qian, 2025). Therefore, the content provided by generative AI should be used with pedagogical integrity, blended with teacher guidance.

2.3.2. Audiovisual Support (Animation, Simulation, Visualization)

Visualization strategies play a critical role in facilitating students' comprehension of abstract concepts. Generative AI-based visual generators (e.g., DALL·E, Midjourney) and diffusion models offer the possibility to generate diagrams, animation storyboards, or simulation scenarios from text. These approaches can alleviate student cognitive load and enhance conceptual understanding (B. Mokhtar et al., 2025). Video generation technologies (e.g., like Synthesia), through their ability to create short instructional videos from text, save time in distance education and micro-learning environments and offer the potential to increase student interest. Research indicates that AI-generated videos can perform comparably to teacher-recorded videos in terms of cognitive learning outcomes. However, there may be limitations in factors such as social presence perception and the student's sense of psychological interaction (T. Xu et al., 2025).

2.3.3. Assessment and Evaluation

Generative AI is transforming assessment and evaluation processes in both question generation and automated response evaluation. Large language model-based systems can generate questions at different cognitive levels according to Bloom's taxonomy and analyze student responses for accuracy, grammar, and logical coherence. It has been emphasized that AI-assisted assessment systems show high consistency with human evaluators but are still limited in terms of contextual sensitivity and pedagogical validity. While generative AI is effective in question generation, it has been noted to be insufficient in deeply reflecting students' thought processes. Therefore, teacher intervention and ethical oversight are inevitable in AI-based assessments.

2.3.4. Personalized Learning

The most innovative contribution of generative AI in education is its capacity to individualize learning experiences. These systems can dynamically adjust the difficulty level based on the student's prior performance, identify conceptual gaps, and suggest appropriate activities. Personalized learning systems allow the student to have more control over the learning process. It has been emphasized that generative AI-supported personalization systems increase academic achievement, but teacher guidance should not be completely eliminated. In this context, instructional designs developed based on the “human-centered AI” principle are important for pedagogical validity (R. Rombach et al., 2022).

3. Generative AI in Learning-Teaching Processes

The evolution of the use of artificial intelligence (AI) in education has entered a new phase in recent years with the emergence of generative models. Generative AI refers to systems that not only process existing information but also generate new content (text, visuals, code, solutions, scenarios) (OpenAI, 2023). This transformation has triggered the transition of the teaching process from information transmission to the co-production of meaning (Zawacki-Richter et al., 2023). Generative AI has risen from a “tool” to a “co-cognitive actor” in learning-teaching processes. Classic teaching models such as ADDIE and Gagné are being redefined by the dynamic, interactive, and generative nature of Generative AI, while learning theories are evolving towards an algorithmic epistemology.

In Türkiye, the “Artificial Intelligence Strategy in Education” document published by YEGİTEK (2024) establishes principles for the integration of AI into instructional design, measurement and evaluation, and teacher competencies. In this context, examining the theoretical and practical impact of AI on teaching models, learning theories, teacher roles, and student-centered approaches is a current academic necessity.

3.1. Generative AI and Instructional Design: Integration with Models Like ADDIE, Gagné, etc.

The ADDIE model (Analysis, Design, Development, Implementation, Evaluation) is one of the most common frameworks in instructional design. AI transforms every stage of this model. During the analysis phase, AI can identify individual learning needs by extracting learner profiles from large data

sets. During the design phase, tools like ChatGPT provide creative support to the instructional designer by generating teaching scenarios, case studies, or multimedia content (Kasneci et al., 2023). During the development phase, Generative AI provides generative solutions for coding, material generation, and assessment tool design. During the implementation phase, interactive chatbots, simulation environments, and virtual teacher assistants energize the learning process. During the evaluation phase, Generative AI analyzes students' written responses using natural language processing techniques and provide qualified formative feedback.

According to Gagné's (1985) "Teaching Events" model, Generative AI can intervene in each instructional event. For example, during the "attention-getting" phase, they can create visual scenarios; during the "recalling prior knowledge" phase, they can draw data from the student's past interactions; and during the "providing feedback" phase, they can produce personalized feedback. Thus, instructional design moves from being teacher-centered to becoming a human-AI co-design.

3.2. Generative AI-Supported Learning Theories: Behaviorism, Cognitivism, Constructivism, Contextualism

The relationship between Generative AI and learning theories transcends the boundaries of classical paradigms. From the perspective of behaviorism, Generative AI automates feedback mechanisms; It optimizes correct/incorrect reinforcement processes. However, the "learner passivity" of the classical behaviorist model is overcome with Generative AI because the system directly integrates student production into the learning process (Bishop & Whitaker, 2024).

In the context of cognitivism, Generative AI can mimic information processing processes, reducing memory load and allowing students to focus on higher-level cognitive processes (analysis, synthesis, evaluation). For example, while students receive conceptual explanations from ChatGPT, they also develop their metacognitive awareness and practice source verification skills.

Constructivist theory is the area where Generative AI most strongly intersects. Learners are no longer consumers of information but rather producers of meaning alongside Generative AI (Holmes et al., 2023). ChatGPT's functions, such as "co-writing," "creating problem-solving scenarios," and "dialogue-based concept exploration," have given rise to new forms of constructivist learning.

From a contextualist perspective, Generative AI has the power to bring learning to real-life scenarios. For example, generative models create authentic

contextual situations in disciplines such as engineering, health, or teacher education, making the student's learning experience authentic. This is the digital-generative version of contextual learning.

3.3. The Changing Role of the Teacher: From Content Provider to Learning Experience Designer

In the age of Generative AI, the teacher has evolved from being a content producer to a role of co-designer of the learning experience with the Generative AI, providing ethical guidance, and epistemic fact-checker. The teacher no longer plans “what to teach,” but rather “what the student will produce and how.” When the content presented by the Generative AI is integrated with the teacher's pedagogical content knowledge, a hybrid field called pedagogical-AI design emerges. In this model, the teacher is responsible for validating, reconstructing, and integrating the knowledge produced by the Generative AI into the student's critical thinking process. Studies on the Generative AI literacy of prospective teachers in Turkey show that pedagogical and ethical training is essential for teachers to be ready for this transformation.

3.4. Student-Centered Learning: Individualization and Adaptive Learning Paths

Generative AI is the first wave of technology that can truly individualize a student's learning experience. Chatbots can generate content based on a student's level, pace, interests, and cognitive style. For example, in mathematics learning, Generative AI can analyze students' incorrect solution steps and offer alternative paths. Thanks to generative models, adaptive learning systems no longer operate solely with predefined modules but instead create new content based on the student's immediate needs (Kasneci et al., 2023). This means that the classical “learning path” approach is being replaced by dynamic learning pathways.

3.5. 21st Century Skills: Creativity, Critical Thinking, Problem Solving

Generative AI not only supports but also redefines 21st-century skills. Creativity is now understood as the joint production of humans and Generative AI, beyond the unique productive capacity of humans (Floridi, 2022). Students can write scenarios, create artistic works, or design research using generative systems. Critical thinking has gained renewed importance in the age of Generative AI, with its “fact-checking” and “source credibility” dimensions. Students are expected to not only obtain answers but also evaluate

the information they receive and question algorithmic bias. Problem-solving skills develop at a metacognitive level under the guidance of Generative AI. Generative AI can reflect the student's thinking process and suggest alternative strategies, thus making the learning process visible. In this context, Generative AI has transformed 21st-century skills from a teaching objective into a natural outcome of the learning process.

4. Applications and Tools

Along with the recent digital transformation, generative AI applications have integrated into the educational ecosystem at a remarkable speed, both in content production and design, and in complex functions such as assessment, guidance, and learning analytics. This integration is seen as a harbinger of profound changes in teaching and learning practices; it paves the way for new paradigms in a broad area ranging from the roles of educators to assessment methodologies, from student experience to ethical frameworks. In this context, the pedagogical roles, concrete usage scenarios, advantages offered, and limitations brought by generative AI systems are increasingly being addressed and discussed in detail by educational sciences and practitioners. This section will examine the generative AI ecosystem in education based on functional categories. The examination will begin with the potential uses in education of general-purpose generative AI tools, which are usable across a wide spectrum, before moving to tools specifically designed for direct educational contexts. Subsequently, the features and functions of education-focused generative AI tools developed to provide direct support for instructional processes will be scrutinized. Finally, considerations critical for the effective, safe, and ethical adoption of these technologies at the classroom and institutional levels will be systematically discussed.

4.1. General-Purpose Generative AI Tools

There are many general-purpose generative AI tools such as ChatGPT, Grok, DeepSeek, and Gemini. These tools, as large language model-based interaction platforms, are widely used for content generation (teaching materials, assignment instructions, example questions), learning support (simplifying explanations, generating sample solutions), and student feedback (draft evaluation, writing/argument suggestions). While the system is rapidly being adopted in education, empirical studies on its effects are diversifying; systematic reviews reveal that these tools can support learning but pose issues

of academic ethics and accuracy in use. Within this framework, both benefits (scalable content production, personalization potential) and risks (information errors, the need to verify generated content, academic integrity concerns) must be considered. From the teacher's perspective, these tools have sample usage scenarios such as generating lesson plans and example questions based on grade-level learning objectives; from the student's perspective, scenarios include creating written drafts, correcting code errors, and requesting simplified explanations of complex concepts. In this scope, they offer advantages such as rapid content generation, rewriting in different explanatory styles, and instant responses to students, while having limitations like producing misleading or incorrect information (hallucination), not providing citations/incorrect referencing, and academic honesty risks.

Multimodal models like Google's Gemini, Anthropic's Claude, OpenAI's ChatGPT, Grok, and DeepSeek process not only text but also visual and (in some versions) audio data, providing functions such as taking a photo of a math problem and offering a step-by-step explanation. This multimodal capability provides a pedagogical advantage, especially in visual-analytical tasks (e.g., geometry problem solutions, laboratory visual analyses); however, data privacy and model security issues should not be overlooked.

Diffusion-based visual models enable teachers to create conceptual diagrams, storyboards, and learning material illustrations from textual descriptions. Research shows that well-designed visuals can reduce cognitive load and facilitate conceptual learning; nevertheless, copyright, ethical, and fake image creation risks should be considered (W. K. Monib et al., 2024). Code and office assistant tools accelerate the creation of teaching materials (presentations, tables, assignment instructions); in programming courses, they can be used to improve student-written code or explain errors. However, in the context of academic assessment, clear guidelines are needed regarding how and to what extent students use these tools. General-purpose models offer flexibility and a broad application area; but when used in an educational context, they must be planned alongside accuracy verification, ethical guidelines, and data security policies. The literature emphasizes that policy design and teacher training are critical in determining the impact of these tools (Giannakos et al., 2025; Strzelecki, 2024).

4.2. Education-Focused Generative AI Tools

Besides generally purposed generative AI systems, there are also generative AI systems specifically produced for education. Khanmigo, an

ethics-focused educational assistant, is a generative AI assistant designed specifically for education by Khan Academy. It defines its purpose as providing hints and guidance that prompt the student to think, rather than giving direct answers. Announcements and application reports from Khan Academy indicate that Khanmigo focuses on teacher support and student guidance functions and adopts responsible use principles. However, independent, peer-reviewed empirical studies are still increasing (A. Weiss, 2025). Use cases include one-on-one guidance, such as hints encouraging a student to solve a problem step-by-step, and teacher support scenarios like alternative explanations suitable for classroom tasks and monitoring reports.

Socratic, provided by Google, is a mobile-supported conceptual guidance application that offers quick explanations and resources by allowing students to upload a photo of a problem or ask a question by voice through their mobile devices. The application is particularly widespread at the high school level and in individual learning, and adaptations for medical and clinical education contexts are also examined in the literature (e.g., adaptation studies for clinical case training) (N. Golchini et al., 2025).

Quizizz, an automated quiz tool, through its generative AI plugins, allows teachers to automatically generate question sets from input content (text, video), classify these questions by difficulty level, and provide instant analysis of student performance. While automated question generation and assessment save time, especially for review and testing purposes, the necessity for the pedagogical appropriateness of the created questions to be confirmed by the teacher is emphasized (M. I. Baig et al., 2024).

The visual communication and presentation platform Canva offers a wide range of functions, from AI-supported text summarization and idea generation tools like Magic Write, to automated design suggestions, and various multimedia (video, presentation, infographic) production features. These features have gained great popularity, especially in processes like project-based learning and student presentations, providing students with a powerful digital environment to showcase their creativity and develop their communication skills. However, the adoption of such tools in the classroom requires a rethinking of assessment practices. The ease with which students can create high-quality, professional-looking, and complex multimedia products can render traditional assessment scales inadequate. At this point, it is critical for teachers to shift their assessment focus from the aesthetic quality of the final product to the process and the depth of the content. Elements such as how students manage their creative process, how

they critically evaluate and structure the design and content suggestions offered by generative AI, research depth, information synthesis skills, and the robustness of the arguments presented should form the basis of authentic assessment. Therefore, it becomes imperative for teachers to adapt their assessment scales and rubrics to consider this new context for the fair and accurate measurement of learning outcomes.

Language acquisition is an area that strongly showcases the potential of generative AI to provide personalized and interactive learning environments. Generative AI-supported versions of platforms like Duolingo offer a dynamic language learning experience that goes beyond traditional methods. These systems analyze the user's performance in real-time to create personalized review schedules; they identify weak grammar rules or vocabulary and aim to increase learning efficiency by focusing on these areas. Furthermore, with exercises for speaking practice and instant error correction (pronunciation, grammar, word choice), they can be highly effective in increasing learning frequency and the amount of fluent speaking practice by offering the learner continuous and immediate feedback. However, a critical perspective on the pedagogical effectiveness and reliability of these tools is necessary. Firstly, the reliability of speech assessment is a significant topic of debate. The extent to which generative AI models can accurately assess factors such as accent diversity, differences in speech rate, and contextual appropriateness remains an area requiring research. While automated systems may be successful in measuring technical accuracy (correct pronunciation of phonemes), they may be limited in assessing higher-level skills such as communicative fluency and pragmatic competence.

4.3. Sample Lesson Scenarios

The pedagogical potential of generative AI becomes more evident when combined with concrete classroom applications and innovative learning models. This section will examine interdisciplinary sample scenarios, as well as emerging integration areas such as micro-learning and virtual/augmented reality.

4.3.1. Sample Lesson Scenarios for Different Disciplines

Generative AI provides support to teachers in creating content appropriate to the nature of different disciplines and offers students an active, exploratory learning experience. Looking at sample lesson scenarios, a mathematics teacher could use a large language model with a prompt such as, "Generate 5 different problem scenarios from daily life, such as construction and cartography, using

the Pythagorean theorem for 10th-grade students, and provide a step-by-step solution for each.” While solving these problems, students can request personalized hints from a large language model at steps where they are stuck, such as “Which formula should I use in this step?” or “What should the next operation be?” This process strengthens the internalization of mathematical reasoning and step-by-step problem-solving strategies, rather than focusing solely on the result.

A physics teacher can use generative AI with the command “Write a virtual experiment scenario simulating how an astronaut on the International Space Station (a zero-gravity environment) would design a fuel transfer system using fluid pressure principles” to create a comprehensive experiment setup. Then, in a biology class, they can concretize abstract concepts by generating visual material with a tool like Midjourney or DALL-E using the description “a scientifically accurate diagram showing the stages of mitosis—interphase, prophase, metaphase, anaphase, and telophase—with each structure clearly labeled.”

In a history class, students can undertake a historical empathy and role-playing activity by giving a large language model the task: “As an American diplomat in 1945, prepare a draft policy paper containing possible measures to be taken against the Soviet Union’s expansionist policies.” This activity encourages students to examine events from a different perspective, establish cause-effect relationships, and deeply understand complex historical processes.

English learners at the A2 level can ask a large language model to “Write a short, clear, everyday dialogue of 4-5 sentences between a tourist and a waiter where the tourist orders coffee and cake in a London café.” Students then have the opportunity to practice this dialogue in pairs, gaining speaking skills, pronunciation practice, and communicative confidence.

4.3.2. Generative AI Integration in Micro-Learning and Gamification

Generative AI is in perfect harmony with modern learning trends like micro-learning and gamification. Teachers can easily use generative AI to produce targeted micro-learning units of 2-5 minutes, suitable for student attention spans (e.g., a short explanation of a complex formula, a reminder of a grammar rule). Automated daily “on this day in history” notifications, “scientific term of the day,” or “vocabulary” content can be generated; furthermore, quick quizzes and interactive tasks can be designed to reinforce this short content. Gamification elements (points, badges, leveling up, and leaderboards) make these short,

focused learning sessions generated by generative AI more motivating and sustainable. This combination is ideal for supporting self-directed learning processes.

The combination of generative AI with immersive technologies like virtual reality and augmented reality is ushering in an era of integrated learning in education. This integration goes beyond static simulations, holding the potential to create dynamic learning environments that shape themselves according to student responses. For example, when a medical student interacts with a virtual patient in a virtual reality environment, a generative AI model working in the background can generate the patient's symptoms, responses to questions, and physiological reactions in real-time and dynamically, depending on the student's interventions. Similarly, in an augmented reality-enhanced history book, when a student scans an ancient Greek statue with their smart device, generative AI can provide not a pre-recorded audio, but an interactive explanation that responds to the student's specific questions in the voice tone and style of that historical character. These scenarios demonstrate the transformative power of generative AI in turning immersive technologies into personalized, limitless, and deeply interactive learning experiences.

5. Generative Artificial Intelligence in Education: Ethical Boundaries, Privacy, and Risks

5.1. Academic Integrity: Use of Artificial Intelligence in Cheating and Assignments

The rapid expansion of generative artificial intelligence (GAI) tools across diverse sectors -including education, academia, defense, and marketing- has become increasingly pronounced. This pervasive adoption has provoked substantial debates, particularly concerning academic integrity. The extensive and direct utilization of Artificial Intelligence (AI) by students in assignments, projects, and theses has the potential to compromise the principles of originality and effort-based learning (Cotton, Cotton, & Shipway, 2023). Advancements in Large Language Models (LLMs) enable students to generate "human-like" text, thereby prompting educators to critically reassess traditional assessment and evaluation practices.

While this situation necessitates educators seeking effective solutions, the outright prohibition of Generative AI is neither a practical nor an effective approach. Instead, UNESCO (2023a; 2023b) urges educational institutions to

“regulate AI-assisted tasks in accordance with ethical principles.” Consequently, how students employ AI, their practices in citing sources, and the transparency of their production processes should be systematically incorporated into the teaching and learning framework, fostering responsible and ethical engagement with AI tools.

5.2. Copyright and Content Ownership: Who Owns AI-Generated Content?

Creative works are traditionally protected under copyright and intellectual property laws to safeguard the rights of their human creators. However, the emergence of content -such as texts, images, and audio- generated by contemporary generative artificial intelligence has sparked significant debate at the intersection of law, technology, and education. Unlike human authorship, AI produces a form of “artificial co-creativity” (Samuelson, 2023), raising complex questions about ownership and accountability. Current legal frameworks, however, do not recognize AI as an “author” or rights holder, leaving unresolved challenges regarding the attribution and protection of AI-generated works.

In the educational context, uncertainty arises regarding the ownership of content produced by teachers and students. UNESCO (2023a; 2023c) and the OECD (2021) call on educational institutions to develop transparent licensing and sharing policies. Furthermore, it is emphasized that in cases where AI-generated materials undergo human oversight, copyright should remain with the human contributor.

5.3. Data Security and Privacy: Protecting Student Information

AI-powered systems process large amounts of personal data, including student profiles, learning habits, and performance levels. This raises critical concerns regarding data privacy, security, and ethical use in education. Floridi and Cowls (2019) provide an ethical framework for AI systems, emphasizing the principles of “transparency, fairness, non-maleficence, accountability, and privacy.”

Educational institutions should clearly define data storage procedures when integrating generative AI and ensure compliance with legal standards such as the European Union’s General Data Protection Regulation (EU, 2016). The “Principles for the Use of Artificial Intelligence in Education” guideline published by the Ministry of National Education (MEB, 2024) explicitly prohibits the unauthorized sharing or commercial use of student data.

5.4. Artificial Intelligence Literacy: Informed Use by Teachers and Students

AI literacy can be defined as the competence of individuals to understand the fundamental functioning, capabilities, limitations, and societal impacts of AI systems, enabling them to interact with these systems in an informed, ethical, and effective manner.

Bozkurt (2023) defines AI literacy as a new digital skill area and emphasizes that it should encompass not only technical knowledge but also ethical awareness, verification skills, and elements of critical thinking. Therefore, AI literacy modules should be integrated into teacher education programs.

According to researchers such as Ng (2021) and Long & Magerko (2020), AI literacy encompasses the following components:

- **Conceptual understanding:** knowledge of what AI is, how it functions, and the data on which it is trained.
- **Application skills:** the ability to use AI tools consciously and purposefully.
- **Ethical awareness:** sensitivity to issues such as bias, privacy, transparency, and accountability.
- **Societal awareness:** the capacity to assess the impact of AI on individuals, society, and the workforce.

In the educational context, AI literacy aims to develop teachers' and students' abilities to engage in critical thinking, make ethical decisions, and responsibly manage generative technologies while using AI-based tools for pedagogical purposes. In this regard, it can be considered a contemporary extension of digital literacy (UNESCO, 2023a).

5.5. Responsible Use Guide: Practical Principles and Classroom Examples

The responsible use of generative artificial intelligence in education can be defined as the balancing of technological innovation with ethical values. In this regard, OECD (2021) and UNESCO (2023a) propose three fundamental principles:

- **Transparency:** The use of AI should be clearly disclosed.
- **Human Oversight:** Final decisions should be made by human educators.
- **Equity:** The technology should provide fair access to all students.

In the classroom, these principles are implemented when teachers consciously integrate generative AI tools into instructional design. For example, requiring proper citation for texts produced using tools such as ChatGPT or Gemini reinforces students' ethical awareness. Additionally, analyzing AI-generated erroneous examples during class discussions fosters critical thinking skills.

6. Policy and Future Perspectives

6.1. UNESCO and OECD Frameworks: Ethical and Policy Guidelines in Education

UNESCO provides global guidance for the integration of generative artificial intelligence into educational and research processes. In this context, UNESCO's 2023 document *Guidance for Generative AI in Education and Research* outlines principles that member countries should consider when implementing both short-term practices and long-term policy planning (UNESCO, 2023a). The guidance advocates for the use of technology for educational purposes within a human-centered vision, adherence to ethical principles, capacity building, and the promotion of technology literacy.

The OECD also provides policy principles regarding the use of artificial intelligence in education, emphasizing dimensions such as data privacy, accountability, fairness, and inclusivity, and offering guidance to member countries. These frameworks serve as an “ethical foundation” that enables countries to develop regulations tailored to their own educational systems.

An important principle from a policy perspective is continuous monitoring and adaptation; as technology rapidly evolves, policies must remain flexible and be updated to account for emerging risks and opportunities.

6.2. Educational Policies in Türkiye: Projects by the Ministry of National Education (MEB), the Council of Higher Education (YÖK), and The Scientific and Technological Research Council of Türkiye (TÜBİTAK)

In recent years, policies regarding artificial intelligence in education have gained momentum in Türkiye. MEB, in its *AI in Education Policy Document and Action Plan* for the 2025–2029 period, aims to foster an AI culture in education, integrate AI into curricula, implement AI support in management systems, and strengthen infrastructure and data analytics capacity through four strategic objectives, fifteen policy areas, and forty actions.

The document also prioritizes policies such as the expansion of AI literacy initiatives, the enhancement of teachers' competencies, and the establishment of international collaborations in the field of educational technologies.

TÜBİTAK promotes the integration of educational technologies by supporting infrastructure and R&D projects in the fields of informatics and artificial intelligence. Units such as TÜBİTAK's Informatics and Information Security Research Center (BİLGEM) conduct research on artificial intelligence, data security, and algorithm development (TÜBİTAK BİLGEM, 2025).

In addition, the AI in Education Policy Document prepared by the Artificial Intelligence Policy Association (AIPA, 2023) represents an initiative aimed at incorporating civil society-based approaches and expert perspectives into policy frameworks in Türkiye.

In this context, the challenges faced by policymakers in Türkiye include infrastructural disparities, unequal access opportunities, limited teacher competencies, and a lack of awareness. Therefore, during implementation, pilot projects, locally scaled trials, and continuous feedback mechanisms are of critical importance (UNESCO, 2021).

6.3. Generative Artificial Intelligence in Teacher Education: In-Service Trainings and Certificate Programs

For policies to be effectively reflected in practice, it is essential to enhance teachers' competencies. In this context, in-service training, certification programs, and models of continuous professional development support the sustainable use of generative AI.

UNESCO's AI Competency Framework initiative proposes competency domains aimed at developing AI-related skills among both teachers and students. Through this framework, teachers are expected to acquire competencies in technology use, ethical evaluation, guidance, and supervision (UNESCO, 2024a; UNESCO, 2024b).

In Türkiye, pilot training programs are being planned through collaborations between the Ministry of National Education (MEB) and universities to enhance teachers' competencies in AI literacy, data fluency, and the pedagogical use of generative AI tools. Within the policy document's objective of "Fostering an AI Culture in Education," particular emphasis is placed on teacher education (MEB, 2025).

For teacher training programs to be effective, attention should be given to the following components:

- **Modular structure:** Modules designed for different skill levels.
- **Practical examples:** Implementation of generative AI tools in real classroom scenarios.
- **Mentorship and community:** Mentoring relationships with experienced teachers and the formation of online professional communities.
- **Assessment and feedback:** Evaluation of participants' practical outputs and provision of constructive feedback.

6.4. The Future Learning Ecosystem: Human + AI Collaboration

It would not be an exaggeration to suggest that future educational environments will evolve into hybrid systems in which humans and artificial intelligence interact and collaborate. In such an ecosystem, AI is expected to assume supportive roles such as instructional assistant, content creator, and feedback tool, while human teachers will continue to carry out critical responsibilities, including pedagogical decision-making, emotional guidance, and fostering learning motivation.

UNESCO's Artificial Intelligence and the Futures of Learning project emphasize the importance of balancing technological and human dimensions, focusing on this collaborative vision. In this approach, AI can be employed not merely as a tool but as a structuring element of the learning environment (UNESCO, 2025).

Conceptual models such as HD-AIHED (Human-Driven AI in Higher Education) advocate for the transparent, ethical, and human-supervised use of AI in higher education (Mahajan, 2025). These models aim to establish systems in which AI assumes a supportive role without overshadowing human agency.

The requirements for the human + AI collaboration vision in education are as follows (UNESCO, 2023a; OECD, 2021):

- **Human-centeredness:** Decision-making mechanisms should always be aligned with human learning objectives.
- **Flexibility and adaptability:** Systems should respond dynamically to individual student profiles.
- **Transparency and accountability:** The logic behind AI decisions should be clear and understandable.
- **Continuous improvement:** Systems should be capable of self-updating based on performance.

6.5. Emerging Trends: AR/VR + Generative AI, Digital Twins, and Metaverse Learning Environments

Generative artificial intelligence, increasingly intertwined with emerging technologies, will enable groundbreaking applications in education.

- **AR/VR + Generative AI:** Interactive, real-time content generation in virtual and augmented reality environments; for example, AR-supported lessons, simulation tasks, and virtual laboratories.

- **Digital Twins:** Modeling digital replicas of students' learning processes, allowing for simulations and personalized guidance based on these replicas.

- **Metaverse Learning Environments:** Lessons, laboratories, and discussion spaces in three-dimensional interactive worlds; dynamic content generation with generative AI and avatar-based instructional scenarios.

These trends aim to remove boundaries in education and provide multidimensional learning experiences that encompass both physical and virtual environments. However, the realization of this vision critically depends on infrastructure investments, hardware accessibility, content standards, and ethical frameworks.

7. Conclusion and Recommendations

7.1. Potential: Opportunities Offered by Generative AI

Generative artificial intelligence holds significant potential for positive transformation within the context of educational technologies. The benefits that generative artificial intelligence can offer in education are listed below (MEB, 2025; Fullestop, 2025):

- Reducing teacher workload through rapid content generation
- Providing personalized learning pathways and tailored content for each student
 - Offering real-time feedback and assessment support
 - Supporting creativity- and project-based learning processes
 - Gaining insights through data analytics, including student behaviors and areas of difficulty

When combined with appropriate policies, infrastructure, and pedagogical approaches, these opportunities can open the door to innovative transformations in education.

7.2. Challenges: Technological, Pedagogical, and Ethical Limitations

Every innovation presents both benefits and challenges. The main obstacles encountered can be summarized as follows (UNESCO, 2023a; OECD, 2021; MEB, 2025):

- **Inequitable technological infrastructure:** Disparities in hardware and internet access.
- **Teacher competence and resistance to change:** Lack of AI literacy and difficulty breaking established habits.
- **Ethical and privacy concerns:** Data security, content accuracy, and copyright issues.
- **Pedagogical misalignment:** Inability to ensure pedagogical coherence with AI integration.
- **Sustainability challenges:** Rapid technological obsolescence requiring continuous updates.

These challenges can be addressed not only through technical solutions but also via policy development, infrastructure improvements, awareness-raising, and stakeholder collaboration.

7.3. Roadmap: Recommendations for Policymakers, Schools, and Teachers

The roles of stakeholders in enhancing the effectiveness of artificial intelligence in education are outlined below:

- **Policymakers**
 - Develop AI strategies for education and implement participatory processes with all stakeholders.
 - Support pilot projects and scale up successful implementations.
 - Ensuring legal regulations encompass data protection and ethical principles.
- **Schools / Educational Institutions**
 - Develop ethical use policies and guidelines.
 - Prioritize infrastructure investments, including internet speed and computer hardware.
 - Establish internal teacher communities and mentorship systems.
- **Teachers**

- Experiment with generative AI tools in pedagogical contexts and adopt a critical approach.
- Continuously enhance AI literacy.
- Guide students on ethical use, proper citation, and responsible engagement with generative technologies.

7.4. Looking Ahead: A Sustainable and Inclusive AI Vision

The future education system should be structured to balance artificial intelligence with human values. Key principles in this vision include:

- **Inclusivity:** Ensuring equal opportunities for access to technology.
- **Ethical centrality:** Grounding practices in principles of privacy, fairness, and transparency.
- **Adaptability:** The ability to respond swiftly to technological changes.
- **Participatory governance:** Decision-making models that involve students, teachers, parents, and experts.

In this framework, the combination of “human learning capacity + the supportive power of generative AI” can open a new era in education. However, this transformation must be based not solely on technology, but on value-driven, ethical, and human-centered design principles.

References

- AIPA. (2023). *Eğitimde Yapay Zekâ Politika Belgesi*. Yapay Zekâ Politikaları Derneği. https://aipaturkey.org/uploads/f/ic/aipa-egitimde-yapay-zeka-politika-belgesi_1.pdf
- Anderson, T. (2008). *The theory and practice of online learning*. Athabasca University Press.
- Aryadoust, V., Zakaria, A., & Jia, Y. (2024). Investigating the affordances of OpenAI’s large language model in developing listening assessments. *Computers and Education: Artificial Intelligence*, 6, 100204. <https://doi.org/10.1016/j.caeai.2024.100204>
- Baig, M. I., & Yadegaridehkordi, E. (2024). ChatGPT in higher education: A systematic literature review and research challenges. *International Journal of Educational Research*, 127, 102411. <https://doi.org/10.1016/j.ijer.2024.102411>
- Baker, R. S., & Inventado, P. S. (2014). Educational data mining and learning analytics. *Springer Handbook of Educational Data Mining*, 61–75.
- Bishop, C., & Whitaker, P. (2024). AI and behaviorism revisited: Automated reinforcement in education. *Computers & Education*, 208.

Bommasani, R., et al. (2022). On the opportunities and risks of foundation models. *arXiv:2108.07258*. <https://doi.org/10.48550/arXiv.2108.07258>

Bostrom, N. (2014). *Superintelligence: Paths, dangers, strategies*. Oxford University Press.

Bozkurt, A. (2023). Yapay zekâ okuryazarlığı üzerine düşünceler. *Açıköğretim Uygulamaları ve Araştırmaları Dergisi (AUAd)*, 9(2), 1–15.

Buc, S., & Divjak, B. (2015, July). Innovation diffusion model in higher education: Case study of e-learning diffusion. *International Association for the Development of the Information Society*. <https://eric.ed.gov/?id=ED562467>

Cotton, D. R. E., Cotton, P. A., & Shipway, J. R. (2023). ChatGPT, plagiarism and the role of academia. *Innovations in Education and Teaching International*, 60(2), 123–132.

Crevier, D. (1993). *AI: The tumultuous history of the search for artificial intelligence*. Basic Books.

Di Mitri, D., Limbu, B., Schneider, J., Iren, D., Giannakos, M., & Klemke, R. (2024). Multimodal and immersive systems for skills development and education. *British Journal of Educational Technology*, 55(4), 1456–1464. <https://doi.org/10.1111/bjet.13483>

Doğan, A. (2002). *Yapay zekâ*. Kariyer.

European Union. (2016). *Regulation (EU) 2016/679... (General Data Protection Regulation)*. *Official Journal of the European Union*, L 119, 1–88. <https://eur-lex.europa.eu/eli/reg/2016/679/oj>

Fisk, R. (2023). The rise of ChatGPT and generative A.I. and what it means for schools. *AASA Journal of Scholarship and Practice*.

Floridi, L. (2022). The ethics of generative AI in education. *AI & Ethics*, 2(3), 155–169.

Floridi, L., & Cowls, J. (2019). A unified framework of five principles for AI in society. *Harvard Data Science Review*, 1(1). <https://doi.org/10.1162/99608f92.8cd550d1>

Fullestop. (2025, Ağustos 5). *Generative AI in education: Use cases, benefits, and challenges*. <https://www.fullestop.com/blog/generative-ai-in-education-use-cases-benefits-and-challenges>

Gill, S., Xu, M., Patros, P., Wu, H., Kaur, R., Fuller, S., ... Lutfiyya, H. (2023). *Transformative effects of ChatGPT on modern education: Emerging era of AI chatbots*.

Giannakos, M., et al. (2025). The promise and challenges of generative AI in education. *Behaviour & Information Technology*, 44(11), 2518–2544. <https://doi.org/10.1080/0144929X.2024.2394886>

Golchini, N., Passalacqua, E., Vaughn, L., Abdulnour, R.-E. E., Zack, T., & Finlayson, S. (2025). Socratic AI: An adaptive tutor for clinical case-based learning. *medRxiv*. <https://doi.org/10.1101/2025.06.22.25329661>

Goodfellow, I. J., et al. (2014). Generative adversarial networks. *arXiv:1406.2661*. <https://doi.org/10.48550/arXiv.1406.2661>

Herbold, S., Hautli-Janisz, A., Heuer, U., Kikteva, Z., & Trautsch, A. (2023). AI, write an essay for me: A large-scale comparison of human-written versus ChatGPT-generated essays.

Holmes, W., Luckin, R., & Blunt, A. (2023). Generative AI and the future of constructivist learning. *British Journal of Educational Technology*, 54(4), 1331–1350.

İşler, B., & Kılıç, M. (2021). Eğitimde yapay zekâ kullanımı ve gelişimi. *Yeni Medya Elektronik Dergisi*, 5(1), 1–11.

Kasneci, E., et al. (2023). ChatGPT for good? On opportunities and challenges of large language models for education. *Learning and Individual Differences*, 103, 102274.

LeCun, Y., Bengio, Y., & Hinton, G. (2015). Deep learning. *Nature*, 521(7553), 436–444.

Leiker, D., Gyllen, A. R., Eldesouky, I., & Cukurova, M. (2023). Generative AI for learning: Investigating the potential of synthetic learning videos. *arXiv:2304.03784*. <https://doi.org/10.48550/arXiv.2304.03784>

Leon, C., Lipuma, J., & Oviedo-Torres, X. (2025). Artificial intelligence in STEM education: A transdisciplinary framework for engagement and innovation. *Frontiers in Education*, 10. <https://doi.org/10.3389/feduc.2025.1619888>

Lin, H.-C., Huang, H., Tsai, C.-K., & Chang, S.-C. (2025). Improving the quality of communicating with dementia patients: A virtual reality-based simulated communication approach. *British Journal of Educational Technology*, 56(1), 167–189. <https://doi.org/10.1111/bjet.13497>

Mahajan, P. (2025). What is ethical: AIHED driving humans or human-driven AIHED.

McCarthy, J. (1956). Proposal for the Dartmouth summer research project on artificial intelligence. *Dartmouth College*.

McKinsey. (2024). *What is ChatGPT, DALL-E, and generative AI?* McKinsey Explainers.

Millî Eğitim Bakanlığı [MEB]. (2024). *Eğitimde yapay zekâ kullanım ilkeleri*. Ankara: YEĞİTEK Yayınları.

MEB. (2025). *Eğitimde Yapay Zekâ Politika Belgesi ve Eylem Planı (2025–2029)*. Ankara: Millî Eğitim Bakanlığı.

Mokhtar, B., Dina, R., & Mokhtar, B. (2025). Diffusion models in generative AI: Principles, applications, and future directions. *Preprints: 2025020524*. <https://doi.org/10.20944/preprints202502.0524.v1>

Monib, W. K., Qazi, A., Apong, R. A., Azizan, M. T., De Silva, L., & Yassin, H. (2024). Generative AI and future education: A review, theoretical validation, and authors' perspective on challenges and solutions. *PeerJ Computer Science*, 10, e2105. <https://doi.org/10.7717/peerj-cs.2105>

Munaye, Y. Y., Admass, W., Belayneh, Y., Molla, A., & Asmare, M. (2025). ChatGPT in education: A systematic review on opportunities, challenges, and future directions. *Algorithms*, 18(6), 352. <https://doi.org/10.3390/a18060352>

Newell, A., & Simon, H. A. (1972). *Human problem solving*. Prentice-Hall.

Ng, A. (2021). *AI literacy: Building the workforce of the future*. Stanford University Press.

Ng, S.-L., & Ho, C.-C. (2025). Generative AI in education: Mapping the research landscape through bibliometric analysis. *Information*, 16, 657.

Nilsson, N. J. (1998). *Artificial intelligence: A new synthesis*. Morgan Kaufmann.

OECD. (2021). *AI principles in education: Policy perspectives*. Paris: OECD Publishing.

OpenAI. (2023). *GPT-4 technical report*. *arXiv:2303.08774*.

Qian, Y. (2025). Pedagogical applications of generative AI in higher education: A systematic review of the field. *TechTrends*. <https://doi.org/10.1007/s11528-025-01100-1>

Rombach, R., Blattmann, A., Lorenz, D., Esser, P., & Ommer, B. (2022). High-resolution image synthesis with latent diffusion models. *arXiv:2112.10752*. <https://doi.org/10.48550/arXiv.2112.10752>

Rumelhart, D. E., Hinton, G. E., & Williams, R. J. (1986). Learning representations by back-propagating errors. *Nature*, 323(6088), 533–536.

Russell, S., & Norvig, P. (2021). *Artificial intelligence: A modern approach* (4th ed.). Pearson.

Samuelson, P. (2023). AI and copyright: Emerging challenges. *Communications of the ACM*, 66(8), 28–31.

Searle, J. R. (1980). Minds, brains, and programs. *Behavioral and Brain Sciences*, 3(3), 417–457.

Siemens, G. (2013). Learning analytics: The emergence of a discipline. *American Behavioral Scientist*, 57(10), 1380–1400.

Strzelecki, A. (2024). To use or not to use ChatGPT in higher education? A study of students' acceptance and use of technology. *Interactive Learning*

Environments, 32(9), 5142–5155. <https://doi.org/10.1080/10494820.2023.2209881>

TÜBİTAK BİLGEM. (2025). *Yapay Zekâ Ekosistem 2025 Çağrısı*. Türkiye Bilimsel ve Teknolojik Araştırma Kurumu. <https://tubitak.gov.tr/tr/destekler/sanayi/ulusal-destek-programlari/1711-yapay-zeka-ekosistem-cagrisi>

Turing, A. M. (1950). Computing machinery and intelligence. *Mind*, 59(236), 433–460.

UNESCO. (2021). *AI and education: Guidance for policy-makers*. Paris: UNESCO Publishing.

UNESCO. (2023a). *Guidance for generative AI in education and research*. Paris: UNESCO Publishing.

UNESCO. (2023b). *Ethical guidelines for the use of AI in education*. Paris: UNESCO Publishing.

UNESCO. (2023c). *Generative AI and copyright in education*. Paris: UNESCO Publishing.

UNESCO. (2024a). *AI competency framework for teachers*. Paris: UNESCO Publishing. <https://www.unesco.org/en/articles/ai-competency-framework-teachers>

UNESCO. (2024b). *AI competency framework for students*. Paris: UNESCO Publishing. <https://www.unesco.org/en/articles/ai-competency-framework-students>

UNESCO. (2025). *Artificial intelligence and the futures of learning*. Paris: UNESCO Publishing. <https://www.unesco.org/en/digital-education/artificial-intelligence>

Vaswani, A., et al. (2023). Attention is all you need. *arXiv:1706.03762*. <https://doi.org/10.48550/arXiv.1706.03762>

Weiss, A. (2025, October 10). Khan Academy's framework for responsible AI in education. *Khan Academy Blog*. <https://blog.khanacademy.org/khan-academys-framework-for-responsible-ai-in-education/>

Xu, T., et al. (2025). From recorded to AI-generated instructional videos: A comparison of learning performance and experience. *British Journal of Educational Technology*, 56(4), 1463–1487. <https://doi.org/10.1111/bjet.13530>

YEGİTEK. (2024). *Eğitimde Yapay Zekâ Stratejisi (2024–2028)*. Millî Eğitim Bakanlığı, Ankara.

Zawacki-Richter, O., Marín, V. I., Bond, M., & Gouverneur, F. (2019). Systematic review of research on artificial intelligence applications in higher education. *International Journal of Educational Technology in Higher Education*, 16(1), 1–27.

CHAPTER XIII

A BIBLIOMETRIC ANALYSIS OF CANCER RESEARCH UTILIZING GENERATIVE ARTIFICIAL INTELLIGENCE METHODS BETWEEN 2022 AND 2024

Mustafa TEMİZ¹ & Burcu BAKIR-GUNGOR²

*¹(Assist. Prof.) Sivas Cumhuriyet University, Faculty of Economics and Administrative Sciences, Department of Management Information Systems, Sivas, Türkiye
E-mail: temizmustafa@cumhuriyet.edu.tr
ORCID: 0000-0002-2839-1424*

*²(Assoc. Prof.) Abdullah Gül University, Faculty of Engineering, Department of Computer Engineering, Kayseri, Türkiye
E-mail: burcu.gungor@agu.edu.tr
ORCID: 0000-0002-2272-6270*

1. Introduction

Cancer is one of the most common health problems worldwide, and the burden of disease is increasing every year (Varlamova et al., 2024). According to data from 2022, approximately 20 million new cases and 10 million deaths were recorded, and the number of cases is expected to reach 35 million by 2050 (Bray et al., 2024). Early diagnosis is a key factor in improving patient prognosis, as it is associated with earlier opportunities for intervention and a wider range of treatment options. The prognostic models developed in this context aim to identify individuals at high risk of cancer, diagnose the disease at an early stage or recognise patients at risk of metastasis and recurrence (Moglia et al., 2025). In recent years, particularly over the last five years, methods based on artificial intelligence and machine learning have improved the accuracy rates of histopathological diagnoses. AI-based techniques have increasingly been employed in cancer screening, diagnosis, prognosis prediction, disease

monitoring, treatment planning, and clinical oncology research, offering powerful tools for uncovering data-driven insights (Varlamova et al., 2024).

Generative artificial intelligence (GAI) has initiated a paradigm shift in cancer diagnosis, offering innovative solutions to long-standing challenges. In particular, deep learning-based models, such as generative adversarial networks (GANs), have achieved a high level of accuracy in analyzing and interpreting medical images, in some cases even surpassing the performance of human experts. These technologies offer significant advantages not only in tasks such as image classification or lesion detection, but also in enhancing poor-quality images, completing missing data, and creating synthetic training datasets. Consequently, GAI holds the potential to both improve the reliability of clinical decision support systems and promote more accurate and personalized approaches to early diagnosis and prognosis of cancer (Gautam et al., 2025). By analyzing medical imaging data, biomarkers, and clinical information, artificial intelligence can monitor patients' responses to treatment, thereby enabling clinicians to update treatment plans in real-time. Machine learning approaches significantly contribute to the identification of critical genetic mutations that drive tumor development, thereby supporting the advancement of targeted therapeutic strategies (Dananjayan & Raj, 2020). Moreover, AI provides valuable insights into tumor genetic heterogeneity, elucidating mechanisms of drug resistance and guiding the design of more effective treatment protocols. Meaningful findings derived from processing clinical records strengthen healthcare professionals' decision-making processes, while machine learning-based clinical decision-support systems play a guiding role in recommending treatment options and directing patients toward suitable clinical trials (Sakthivel et al., 2024).

A growing body of research has investigated the application of generative AI techniques in cancer studies. For example, Sakthivel et al. investigated the implementation of generative models, such as GANs, in medical imaging, focusing on their impact on tasks like anomaly detection and segmentation (Sakthivel et al., 2024). Singh et al. investigated how generative AI is changing oncological imaging, its role in improving diagnostic accuracy, and its integration with multimodal data (Singh et al., 2024). Tan et al. (2025) discussed in detail the applications of generative AI in diagnostic and therapeutic processes in cancer research through a systematic review (Tan et al., 2025). Vadisetty and Polamarasetti (2025) investigated interdisciplinary applications of generative AI in the early detection of oral cancer (Vadisetty & Polamarasetti, 2025)..

Similarly, Saeed et al. (2023) demonstrated the successful use of augmented datasets created with generative AI in combination with transfer learning models for skin cancer classification (Saeed et al., 2023).

In light of these technological developments, the number of studies using generative AI methods for cancer diagnosis, detection, and treatment has increased rapidly. However, no comprehensive study has yet been conducted to investigate the general trends, the structures studied, and their scientific implications. This study aims to analyze research focused on the application of generative AI methods in cancer by examining scientific publications indexed in the Web of Science Core Collection (WoScc) between 2022 and 2024. Specifically, the number of scientific publications, the most prolific authors, pioneering articles, research areas, prominent publishers, and leading universities, as well as the number of citations of these papers, will be analyzed. The study is intended to serve as a guide for researchers interested in the role of generative AI in cancer detection.

2. Materials and Methods

This study examines research articles indexed in the Web of Science Core Collection that utilize generative artificial intelligence (GAI) methods and machine learning techniques for cancer detection. Within the scope of this research, the developmental trends of scientific studies are comprehensively analyzed. The dataset was compiled on September 1, 2025, through a search conducted on the WoScc platform using the filters “Cancer” and “Generative Artificial Intelligence.” The analysis primarily focuses on studies published between 2022 and 2024, thereby evaluating research conducted during this three-year period.

The included studies employ contemporary generative AI methods in combination with machine learning algorithms for cancer diagnosis. For these studies, the following indicators were identified and assessed:

- Number of Scientific Publications
- Most prolific authors
- Pioneering articles
- Research areas
- Prominent publishers
- Leading universities
- Number of Citations

Based on these indicators, the study presents findings related to cancer detection research employing GAI methods.

3. Results

a. *Number of Scientific Publications*

Within the scope of this study, a total of 98 scientific publications were retrieved from the Web of Science Core Collection database, based on the predefined search strategy, covering the years 2022–2024. Among these, 58 were research articles, 16 were review papers, 14 were publication materials, 4 were proceedings papers, 3 were letters, and 3 were meeting abstracts. The annual distribution of these publications is presented in Figure 1.




Figure 1. Number of publications by year based on the specified search criteria

As shown in Figure 1, cancer research employing generative artificial intelligence (GAI) methods has exhibited a steady increase over the years. The highest number of publications was recorded in 2024, with 82 studies. Notably, while only 14 studies were published in 2023, the number increased sharply in 2024, reaching 82 publications —a substantial growth compared to previous years. This remarkable increase can be attributed, in part, to advances in artificial intelligence technologies, which have facilitated the widespread adoption of GAI methods in oncology research. Accordingly, the use of GAI in cancer studies is increasingly recognized as a promising and impactful area of research.

b. Most Prolific Authors

Although the use of generative artificial intelligence (GAI) methods in cancer research represents a relatively new field, it is regarded as a highly reliable area of investigation. Due to its novelty and emerging nature, the number of researchers actively contributing to this domain remains relatively limited. Figure 2 presents the authors with the highest number of publications in this field.




Figure 2. Number of publications authored

As illustrated in Figure 2, the number of studies conducted in this field remains limited, with the highest contribution being three publications. Among the authors, Lupo Roberto, Ostergaard Soren Dinesen, De Nunzio Giorgio, Conte Luana, Mouayad Masalkhi, Lee Andrew G., Ethan Waisberg, Joshua Ong, and Vitale Elsa stand out with three studies each. The remaining authors have produced two or fewer publications. When the three-year period is considered, it becomes evident that the number of researchers actively engaged in this domain is still relatively low. This suggests that the field has not yet attracted sufficient scholarly attention; however, it also highlights its potential as a promising area for future research.

c. Pioneering Articles

To identify pioneering contributions, the three most frequently cited studies were considered as seminal works in the field. The first study to lead

cancer research utilizing GAI methods was conducted by (Lu et al., 2024). Published in the high-impact, Q1-ranked international journal *Nature*, this article has received 118 citations, thereby establishing itself as a cornerstone in the domain. The second influential contribution was made by (Iannantuono et al., 2023). This study, published in the Q2-ranked international journal *Frontiers in Oncology* (impact factor: 0.68), has accumulated 56 citations. Finally, the third pioneering article was authored by (Duffourc & Gerke, 2023). Published in the prestigious Q1-ranked journal *JAMA – Journal of the American Medical Association*, this study has secured 50 citations to date, further underscoring its significance in the emerging literature.

d. Research Areas

Cancer research, as an inherently interdisciplinary field, holds significant impact in both the domains of information science and healthcare. Relevant studies are published across journals operating within these fields. Figure 3 illustrates the research areas of the journals in which these studies have been published.




Figure 3. Publications distributed by research areas

As illustrated in Figure 3, the largest proportion of publications in this field falls under Health Care Sciences Services (29.4%). The second most prominent area is Oncology (27.1%), followed by Medical Informatics (25.9%) as another major research domain. Subsequently, Computer Science and

Public, Environmental, and Occupational Health constitute additional areas of contribution. These findings provide valuable insights for researchers in this field, particularly in guiding the selection of appropriate academic journals and informing decisions regarding the submission of their work.

e. Prominent Publishers

One of the greatest challenges faced by academic researchers in increasing the visibility of their work is selecting an appropriate journal. When the choice of journal is not aligned with the study’s scope and readership, publications often fail to receive sufficient attention. This outcome is undesirable not only for researchers but also for the scientific community, as it may result in valuable studies remaining underappreciated. In this context, the publishers of journals most frequently selected for cancer research employing GAI methods were examined and presented in Figure 4. As shown in Figure 4, the first two groups of publishers account for the highest number of publications (4 and 2, respectively). In contrast, all remaining journals have published only a single study in this field.




Figure 4. Number of publications by publishers

As illustrated in Figure 4, the publishing group with the highest number of studies in this field is JMIR Publications, Inc., which accounts for 24 publications. This is followed by Elsevier, MDPI, Nature Portfolio, Springer Nature, Lippincott Williams & Wilkins, Wiley, and IEEE, each contributing 15 publications. An examination of these publishers reveals that they host high-

impact international journals, underscoring their significance for disseminating research in this area.

f. Leading Universities

For the topic investigated, universities with the two highest numbers of publications were considered. Including these influential institutions in the analysis provides valuable insights for researchers, enabling them to conduct their searches more effectively and to identify leading centers of expertise in the field. In this context, the universities to which the contributing researchers are affiliated are presented in Figure 5.




Figure 5. Universities affiliated with the contributing researchers

As illustrated in Figure 5, Harvard University stands out with eleven studies on cancer research utilizing AI and GAI methods. Similarly, Harvard University Medical Affiliates has also contributed to eleven studies, positioning it as another influential institution in this field. Following these, the University of California System ranks next with nine publications, while the University of Texas System has produced eight studies. With seven studies, Harvard Medical School occupies fifth place, followed by Cornell University with six publications. Brigham and Women’s Hospital also emerges as a leading institution with five studies. These universities provide valuable insights for researchers and serve as focal points of interest for scholars aiming to advance cancer research through GAI methods.

g. Number of Citations

The number of citations received by publications serves as an important indicator for researchers in determining areas of focus and research priority. Citation counts can help scholars select topics and shape the direction of their studies. An increase in citation numbers reflects growing interest in the field and indicates a rising number of researchers contributing to the field. In this context, Figure 6 presents the total number of citations over the years.




Figure 6. Number of citations received by publications across years

As illustrated in Figure 6, a total of 336 citations were recorded across the examined years. Self-citations were included in the analysis. When the results are evaluated on a yearly basis, it is observed that in 2022, during the early stage when artificial intelligence concepts were first being incorporated, 2 studies received a total of 3 citations. In 2023, 14 studies accumulated 30 citations, while in 2024, 82 studies accounted for 303 citations. These findings indicate a growing interest in the research domain, underscoring its increasing importance for scholars in the field.

4. Conclusions

Research on cancer using artificial intelligence (AI) methods has become increasingly prevalent in the healthcare domain. Such studies, which are of

critical importance in diagnostic and therapeutic processes, aim to support physicians in their decision-making. In this context, AI-based approaches have attracted considerable attention. However, research conducted using traditional machine learning methods often fails to achieve the desired level of reliability and remains insufficient. To overcome this limitation, researchers have increasingly turned to innovative AI techniques for disease prediction. This study specifically focuses on cancer-related research employing generative artificial intelligence (GAI) methods. Publications from the period 2022–2024 clearly demonstrate both the timeliness of the topic and the growing academic interest in this field. The growing attention underscores the significance of GAI-based cancer research and suggests that it is likely to become one of the top priority areas for future scientific investigation.

Acknowledgement

During the preparation of this manuscript, the author used ChatGPT (GPT-5, May 2025 version) for the purposes of editing sentence structure and checking for grammatical errors.

References

- Bray, F., Laversanne, M., Sung, H., Ferlay, J., Siegel, R. L., Soerjomataram, I., & Jemal, A. (2024). Global cancer statistics 2022: GLOBOCAN estimates of incidence and mortality worldwide for 36 cancers in 185 countries. *CA: A Cancer Journal for Clinicians*, 74(3), 229–263. <https://doi.org/10.3322/caac.21834>
- Dananjayan, S., & Raj, G. M. (2020). Artificial Intelligence during a pandemic: The COVID-19 example. *The International Journal of Health Planning and Management*, 35(5), 1260–1262. <https://doi.org/10.1002/hpm.2987>
- Duffourc, M., & Gerke, S. (2023). Generative AI in Health Care and Liability Risks for Physicians and Safety Concerns for Patients. *JAMA*, 330(4), 313–314. <https://doi.org/10.1001/jama.2023.9630>
- Gautam, R., Kaur, P., & Sharma, M. (2025). Predictive Analytics for Early Cancer Detection Using Machine Learning and Generative AI. In *Generative Intelligence in Healthcare*. CRC Press.
- Iannantuono, G. M., Bracken-Clarke, D., Floudas, C. S., Roselli, M., Gulley, J. L., & Karzai, F. (2023). Applications of large language models in cancer care: Current evidence and future perspectives. *Frontiers in Oncology*, 13. <https://doi.org/10.3389/fonc.2023.1268915>

Lu, M. Y., Chen, B., Williamson, D. F. K., Chen, R. J., Zhao, M., Chow, A. K., Ikemura, K., Kim, A., Pouli, D., Patel, A., Soliman, A., Chen, C., Ding, T., Wang, J. J., Gerber, G., Liang, I., Le, L. P., Parwani, A. V., Weishaupt, L. L., & Mahmood, F. (2024). A multimodal generative AI copilot for human pathology. *Nature*, 634(8033), 466–473. <https://doi.org/10.1038/s41586-024-07618-3>

Moglia, V., Johnson, O., Cook, G., de Kamps, M., & Smith, L. (2025). Artificial intelligence methods applied to longitudinal data from electronic health records for prediction of cancer: A scoping review. *BMC Medical Research Methodology*, 25(1), 24. <https://doi.org/10.1186/s12874-025-02473-w>

Saeed, M., Naseer, A., Masood, H., Rehman, S. U., & Gruhn, V. (2023). The Power of Generative AI to Augment for Enhanced Skin Cancer Classification: A Deep Learning Approach. *IEEE Access*, 11, 130330–130344. <https://doi.org/10.1109/ACCESS.2023.3332628>

Sakthivel, B., Vanathi, P., Sri, M. R., Subashini, S., Sonthi, V. K., & Sathish, C. (2024). Generative AI Models and Capabilities in Cancer Medical Imaging and Applications. *2024 3rd International Conference on Sentiment Analysis and Deep Learning (ICSADL)*, 349–355. <https://doi.org/10.1109/ICSADL61749.2024.00063>

Singh, Y., Hathaway, Q. A., & Erickson, B. J. (2024). Generative AI in oncological imaging: Revolutionizing cancer detection and diagnosis. *Oncotarget*, 15, 607–608. <https://doi.org/10.18632/oncotarget.28640>

Tan, X. J., Cheor, W., Meng, C., Lim, C., & Rahman, K. (2025). Generative Artificial Intelligence (GAI) in Breast Cancer Diagnosis and Treatment: A Systematic Review. *Computers, Materials & Continua*, 84, 2015–2060. <https://doi.org/10.32604/cmc.2025.063407>

Vadisetty, R., & Polamarasetti, A. (2025). Cross-Disciplinary Applications of Generative AI in Oral Cancer Research and Early Detection. In D. K. Sharma, R. Sharma, & S.-L. Peng (Eds.), *Proceedings of International Conference on Next-Generation Communication and Computing* (pp. 129–141). Springer Nature. https://doi.org/10.1007/978-981-96-3728-7_11

Varlamova, E. V., Butakova, M. A., Semyonova, V. V., Soldatov, S. A., Poltavskiy, A. V., Kit, O. I., & Soldatov, A. V. (2024). Machine Learning Meets Cancer. *Cancers*, 16(6), 1100. <https://doi.org/10.3390/cancers16061100>

CHAPTER XIV

GENERATIVE ARTIFICIAL INTELLIGENCE APPLICATIONS IN LAW

Fatma Betül ŞEKER¹ & Berna DÖNEK²

¹Sivas Cumhuriyet University, Sivas, Turkey

E-mail: bseker@cumhuriyet.edu.tr

ORCID: 0000-0001-7922-470

²Sivas Cumhuriyet University, Sivas, Turkey

E-mail: bernadonek@cumhuriyet.edu.tr

ORCID: 0000-0001-8143-7682

1. Introduction

The transformative impact of artificial intelligence (AI) has extended far beyond the domains of computer science and engineering, reshaping virtually every field of human activity—including the practice, interpretation, and administration of law. Among the most recent and profound developments in this technological evolution is generative artificial intelligence (GenAI), which differs from traditional AI models in its ability to autonomously produce new content—texts, images, codes, and even legal documents—based on vast amounts of training data. This capacity has positioned GenAI as both a disruptive and assistive force in modern legal systems, offering new opportunities for efficiency while simultaneously raising complex ethical, procedural, and legal concerns.

In the legal profession, GenAI has been rapidly adopted as a support mechanism for drafting, reviewing, and analyzing legal documents, conducting research, predicting judicial outcomes, and managing client communications. Applications such as LawGeex, Kira Systems, and LexisNexis exemplify how AI can enhance accuracy and accelerate legal workflows by automating repetitive and data-intensive tasks that once required significant human labor. Similarly, within the judiciary, AI tools capable of identifying precedents,

generating draft judgments, and ensuring consistency across rulings promise to contribute to the realization of the right to a trial within a reasonable time. However, as these systems increasingly influence both private and criminal law, the balance between technological efficiency and legal integrity becomes more delicate and critical.

While the integration of GenAI into legal processes offers notable advantages—such as reducing procedural delays, minimizing human error, and promoting consistency in judicial reasoning—it also introduces a host of risks. These include algorithmic bias, breaches of confidentiality, data protection violations, and the generation of fabricated or misleading information (commonly known as “AI hallucination”). Moreover, the lack of transparency in AI decision-making processes, often described as the “black box” problem, challenges the fundamental principles of accountability and due process in the rule of law.

In this context, it becomes imperative to examine the extent to which generative AI can be utilized across different branches of law without undermining core legal values such as fairness, equality, and the right to a fair trial. This study explores the applications of GenAI in both private and criminal law, emphasizing its dual role as an innovative tool and a potential source of legal and ethical dilemmas. Through a detailed analysis of existing systems, their practical implementations, and the challenges they pose, the study aims to provide a comprehensive understanding of how GenAI can be responsibly integrated into the legal field while maintaining human oversight as the ultimate safeguard of justice.

2. GenAI Applications in Private Law

During a period of rapid technological advancement, the field of law—like many other disciplines—has been significantly influenced by these developments. In recent years, GenAI models, which have become integrated into nearly every aspect of life, have not only facilitated easier access to information but have also enabled the generation of new legal texts, the analysis of existing documents and precedents, and the prediction of outcomes based on case law with remarkable accuracy and speed. Although the use of generative AI presents numerous advantages, it also carries certain inherent risks.

Drafting and Reviewing Contracts

One of the key tasks of lawyers is to draft contracts, conduct the necessary research for these contracts, review existing agreements, and identify potential legal disputes within them. As a result of advancements in the digital world, GenAI systems capable of performing these tasks have emerged.

Among GenAI applications, Kira Systems is a platform that reviews contracts, identifies potential legal issues, and determines the appropriate procedures to follow in this context. It has been observed that this system provides its users with a significant amount of time savings.¹ Similarly, in a study conducted with LawGeex, an artificial intelligence application that reviews contracts and identifies legal issues within them, it was found that the system completed a review—typically performed by expert lawyers in about four hours—in just twenty-six minutes, achieving a higher accuracy rate than the lawyers themselves.²

Generative artificial intelligence systems can also create contract drafts when provided with information such as the parties involved, the subject matter, the rights and obligations of the parties, and the duration of the contract.³ The preparation of contracts by artificial intelligence, particularly in standardized agreements such as lease contracts, allows lawyers to work more efficiently. In addition, it is also possible to generate other legal documents such as notice drafts and statements of claim using these systems.⁴

While the use of artificial intelligence serves as a tool that facilitates the drafting of contract templates, the identification of legal issues, and the analysis of contracts, it is not a tool that eliminates the need for lawyers. Generative artificial intelligence functions as an assistive technology that shortens bureaucratic processes, reduces errors, and enables more efficient analysis. In legal disputes involving multiple legal systems and regulations, the analysis of a lawyer will still be required. When drafting or analyzing contracts, differences between the legal system on which the AI model was trained and the system in which it is being applied—as well as variations or amendments in legislation—may be overlooked, leading to the risk of inaccurate results. Therefore, lawyers must remember that such systems are merely assistive tools. Drafts and analyses produced by artificial intelligence should always be reviewed and verified by legal professionals.⁵

1. Abanoz, Buket; “*Hukuki Bilgiye Dijital Erişim*”, **Marmara Üniversitesi Hukuk Fakültesi Hukuk Araştırmaları Dergisi**, C. 26, S. 1, Haziran 2020, s. 195

2. LawGeex Hits 94% Accuracy in NDA Review vs 85% for Human Lawyers – Artificial Lawyer (E.T. 14.10.2025)

3. Görentaş, Muhammed Burak; “*Hukukta Yapay Zeka*”, **SSDjournal**, Volume 8 Issue 41, 2023 December, s. 8.

4. Demir, Şamil; “*Yapay Zeka Modellerinin Avukatlık Mesleğinin Geleceği Üzerine Olası Etkileri*”, s.7 https://www.researchgate.net/profile/Samil-Demir/publication/391988259_Yapay_Zeka_Modellerinin_Avukatlik_Mesleginin_Gelecegi_Uzerindeki_Olasi_Etkileri/links/682fa1798a76251f22e59cd3/Yapay-Zeka-Modellerinin-Avukatlik-Mesleginin-Gelecegi-Uzerindeki-Olasi-Etkileri.pdf (E.T. 14.10.2025)

5. Karabel, E. Gökçe/ Aydemir, Dilek; “*Medeni Usul Hukukunda Yargılamanın Hızlandırılması ve Adalet Erişim Hakkı Bakımından Çevrimiçi Yargılama ve Yapay Zekanın Kullanımı*”, **Marmara Üniversitesi Hukuk Fakültesi Hukuk Araştırmaları Dergisi**, C. 29, S. 1, Haziran 2023, s. 561.

One of the risks associated with the use of artificial intelligence in this process is the potential violation of confidentiality.⁶ Pursuant to Article 36 of the Attorneyship Law, lawyers are bound by a duty of confidentiality. In this context, if a lawyer shares client-related information with an artificial intelligence system to draft or review a contract, the issue of the lawyer's liability may arise. Furthermore, according to the Personal Data Protection Authority (LPDP), a lawyer is considered a data controller.⁷ The protection of data obtained about the client also falls under the lawyer's responsibility. Since artificial intelligence fundamentally relies on data—it learns from and processes such data—it is the lawyer's duty to understand how these applications handle data and whether they perform data anonymization. Accordingly, the lawyer will also be held responsible for any violations that may arise in this context. The lawyer will also be held liable for any violations that occur in this context.

Court Decision Analysis and Judgment Prediction

When working on the resolution of legal disputes, one of the most important guides for legal professionals is previous court decisions rendered in similar cases. For this reason, precedent judgments hold great significance for legal practitioners—especially lawyers—when filing a lawsuit or conducting research to substantiate a claim during litigation. However, finding relevant rulings within the vast archives of court decisions accumulated over many years can be a time-consuming task.

One of the areas where artificial intelligence is most frequently used in the field of law is decision support system software.⁸ In this context, case law search programs are used by a large number of law firms.⁹ These systems can quickly retrieve relevant court decisions by using keywords or by analyzing a short text that summarizes the issue or fact pattern related to the case in question. For example, in Türkiye, one of the AI-supported programs used for this purpose can identify relevant court decisions by allowing the user to input information such as keywords, the fact pattern of the case, or the specific article

6. “*Hukukta Yapay Zeka*”, s. 12.

7. **Ankara Barosu Kişisel Verilerin Korunması Kanunu Rehberi** s. 18, <http://kutuphane.ankarabarsu.org.tr/cgi-bin/koha/opac-retrieve-file.pl?id=f43fb4f3cfd21f9014746ff2e97b047> (E.T. 14.10.2025)

8. Çatal, Betül; “*Yapay Zekanın Karar Verme Süreçlerinde Kullanılması*”, **SÜHFD**, C. 33, S. 1, 2025, s.324.

9. Kotil Öğretmen, Zeynep; “*Hukukta Yapay Zekâ Uygulamaları*”, İstanbul 2022, s. 2, https://www.istanbulbarosu.org.tr/files/komisyonlar/yzcg/hukukta_yapay_zeka_uygulamaları.pdf (E.T. 14.10.2025)

of law related to the decision being sought.¹⁰ Similarly, Ross, an AI-powered legal assistant, provides answers by conducting research on court decisions and relevant legislation.

Another area where artificial intelligence is utilized in the field of law is the statistical analysis of court decisions. These programs analyze judicial reasoning to determine the factors influencing a judge's decision to accept or reject a case. Based on these findings, they attempt to predict potential court outcomes. As a result of such analyses, individuals considering filing a lawsuit can learn about their likelihood of winning or losing, and these insights may influence their decision on whether or not to proceed with legal action.¹¹

The use of artificial intelligence in locating and analyzing court decisions also brings with it the risk of AI hallucination. Hallucination, in this context, refers to the phenomenon of artificial intelligence generating incorrect or fabricated information.¹² As a result of hallucination, artificial intelligence may fabricate court decisions, which can lead to incorrect judgments, disciplinary liability for the lawyer who presents such information, and delays in judicial proceedings if the erroneous decision is later detected and corrected.¹³ Indeed, in the United States, there have been instances where lawyers using GenAI were sanctioned for submitting fabricated court decisions produced by AI during legal proceedings.¹⁴ In this context, it is primarily the responsibility of lawyers—who rely on such decisions—to verify them, although this duty also extends to judges. According to Article 34 of the Attorneyship Law, lawyers are obligated to perform their duties with due diligence. Within the scope of this duty, a lawyer must also ensure the accuracy and reliability of any auxiliary tools, including artificial intelligence systems, used during a case. Similarly, in an era where AI has become part of legal practice, judges must consider the possibility that a submitted decision may have been generated by artificial intelligence and are therefore required to verify its authenticity.

10. <https://www.dejure.ai/nedir> (E.T. 14.10.2025)

11. “*Yapay Zekanın Karar Verme Süreçlerinde Kullanılması*”, s. 325.

12. Ankara Barosu Avukatlıkta Yapay Zeka Araçlarının Kullanım Rehberi, s. 3 https://www.ankarabarosusu.org.tr/serve/file/bc4de0be-b5fa-11ef-8f94-000c29c9dfce/yapay_zeka_arac_larinn_kullanm_rehberi_X1.pdf (E.T. 14.10.2025)

13. Selçuk, Seyhan; “*Makûl Sürede Yargılama Yapılmasında Yapay Zekanın Etkisi*”, *Türkiye Adalet Akademisi Dergisi*, Yıl 16, S. 62, Nisan 2025, s. 458.

14. <https://www.reuters.com/technology/artificial-intelligence/ai-hallucinations-court-papers-spell-trouble-lawyers-2025-02-18/> (E.T. 14.10.2025)

Legal Research, E-Discovery, and Client Communication

In the research process of legal disputes, it is necessary not only to conduct case law research but also to examine legislation and legal doctrine. Reviewing documents, identifying evidence, and determining the applicable laws are among the essential duties of legal professionals. When performed manually, such research and examination can take several days depending on the complexity of the case file. However, with advances in artificial intelligence, systems such as LexisNexis can now carry out these tasks much more efficiently. A key advantage of these AI systems is that they go beyond simple keyword searches and are capable of conducting semantic analysis, enabling a deeper and more accurate understanding of legal texts.¹⁵ However, although these systems significantly accelerate the research process, legal interpretation and the unique characteristics of each specific case remain crucial in the practice of law. Furthermore, due to factors such as differences in local legislation and the risk of AI hallucination, human oversight by lawyers is still essential to ensure accuracy and reliability in legal analysis.

In large-scale lawsuits, identifying and classifying electronically stored data that may be useful in litigation is a time-consuming process. E-discovery applications facilitate this process by enabling the rapid examination of electronically maintained records of the parties, thereby assisting in the efficient identification and categorization of relevant evidence.¹⁶ In the use of e-discovery applications, ensuring data confidentiality is one of the key aspects that lawyers must pay close attention to. As mentioned earlier, the lawyer's duty of confidentiality and their responsibility as a data controller under the Law on the Protection of Personal Data (LPDP) both come into play in this context.

In both pre-trial preparation and trial processes, communication with the client plays a crucial role. Artificial intelligence applications such as Everlaw, AVA, and SANDI, which handle responsibilities like tracking case progress, organizing documents, and communicating with clients—particularly potential clients—enhance both efficiency and speed. However, since these systems lack the human qualities of interaction and empathy, they carry the risk of creating a negative client or prospective client experience compared to direct human communication.

15. “Yapay Zeka Modellerinin Avukatlık Mesleğinin Geleceği Üzerine Olası Etkileri”, s. 7.

16. Efe, Ahmet; “Yargısal ve Hukuki Süreçlerde Yapay Zeka Kullanan Araçlar Üzerine Bir Değerlendirme”, *Bilgi Yönetimi Dergisi*, C. 5, S. 1, 2022, s. 107

Drafting Judicial Decisions and the Concept of the Robot Judge

When examining the use of artificial intelligence by judges during legal proceedings, this can be categorized into three main types: AI assisting the judge, AI generating draft judgments, and AI rendering judicial decisions.

An AI system that assists judges includes applications such as case law retrieval, identifying relevant legislation, analyzing and summarizing documents, and transcribing statements—as mentioned earlier. One of the countries utilizing such systems is the People’s Republic of China, where Internet Courts employ speech recognition technology to automatically transcribe statements made during proceedings. Additionally, China has implemented a system called “Smart Judge” (Bilge Hakim), designed to promote consistency and uniformity among judicial decisions.¹⁷ In India, a system called SUPACE (Supreme Court Portal for Assistance in Court Efficiency) performs functions that assist judges in their work, such as organizing and analyzing case information. Similarly, in Finland, a system known as Anappi supports judges by handling various administrative and analytical tasks to improve judicial efficiency.¹⁸ Some of the tasks currently performed by judicial clerks or judge assistants can now be handled by AI systems that assist judges. One of the major advantages of using artificial intelligence in this context is its ability to accelerate the judicial process, thereby contributing to shorter trial durations and overall increased efficiency in case management.¹⁹

One of the areas where artificial intelligence is applied is drafting judicial decisions. In this context, AI systems analyze previous court rulings on similar cases and generate a draft judgment based on the identified patterns and reasoning.²⁰

The draft prepared by artificial intelligence in this context serves merely as an assistive tool for the judge and does not carry any binding authority. The judge may review the draft decision and choose to adopt it as is, modify it, or issue a completely different ruling. Among the AI systems that generate such draft judgments are “Predictive Jurisprudence”, used by the Genoa Court in Italy, and the “Robot Judge” application implemented in China.²¹ This artificial

17. Karadeniz, Salih; “*Medeni Yargılamada Yapay Zeka Kullanımı: Hakim Yapay Zeka, Faydaları ve Sakıncaları Üzerine Bir Değerlendirme*”, *Gelişen Teknolojilerin Medeni Usul Hukukuna Etkileri*, Seçkin, 2023, s. 11

18. “*Makûl Sürede Yargılama Yapılmasında Yapay Zekanın Etkisi*”, s. 440.

19. “*Makûl Sürede Yargılama Yapılmasında Yapay Zekanın Etkisi*”, s.447.

20. Bilgin, Hikmet; “*Yapay Zekânın Mahkeme Kararlarında Kullanımına Uluslararası Bir Bakış ve Robot Hâkimler Hakkında Düşünceler*”, *İNÜHFD* 13(2):405-419 (2022), s.411

21. “*Yapay Zekânın Mahkeme Kararlarında Kullanımına Uluslararası Bir Bakış ve Robot Hâkimler Hakkında Düşünceler*”, s. 414; “*Makûl Sürede Yargılama Yapılmasında Yapay Zekanın Etkisi*”, s. 451.

intelligence application is likely to yield positive outcomes in promoting consistency and uniformity in judicial decisions.

One essential component of the right to a fair trial is the requirement that court decisions be reasoned. However, the absence of reasoning in draft judgments generated by artificial intelligence may lead to a violation of this right. Therefore, in order for AI systems to fully assist judges and ensure the reliability and legitimacy of such decisions, it is essential that they possess the ability to provide proper legal reasoning in their outputs.²²

Since artificial intelligence generates these drafts based on existing court decisions, one of the main risks of such systems is their inability to produce consistent rulings in cases that are rare, lack sufficient precedents, or involve novel legal issues. Similarly, in dispute types where there are numerous and conflicting precedents, the likelihood of AI producing a coherent and balanced draft judgment decreases. Moreover, in some cases, evolving social and legal needs may lead to shifts in judicial reasoning over time. However, AI systems that rely solely on past decisions are unable to adapt to such changes. In these circumstances, the judge's human qualities—such as the ability to assess the unique facts of a case, exercise judicial discretion, and render decisions in line with society's changing values and needs—remain indispensable.²³

Using AI systems that generate draft judgments as assistive tools under the supervision and control of judges helps to mitigate potential risks while promoting the development of an application that enhances the consistency and coherence of judicial decisions.²⁴

Another form of artificial intelligence use at the decision-making stage is the robot judge system, in which the decision is rendered directly by the AI itself. In this model, artificial intelligence effectively replaces the human judge and carries out the entire judicial process autonomously. A current example of this can be found in China's Internet Courts, where such systems have been implemented.²⁵

There are opinions suggesting that the use of robot judges would be more appropriate in the initial stages of implementation, specifically for simpler, repetitive cases or non-contentious judicial matters. In such proceedings, where

22. "Makûl Sürede Yargılama Yapılmasında Yapay Zekanın Etkisi", s. 452-453.

23. "Makûl Sürede Yargılama Yapılmasında Yapay Zekanın Etkisi", s. 452

24. Yılmaz, Oğuz Gökhan, "Yargı Uygulamasında Yapay Zeka Kullanımı-Yapay zeka Hakim Cübbesini Giyebilecek mi?", *Adalet Dergisi*, 2021/1, S.66, s. 406.

25. "Medeni Yargılamada Yapay Zeka Kullanımı: Hakim Yapay Zeka, Faydaları ve Sakıncaları Üzerine Bir Değerlendirme", s. 17.

the reasoning and discretionary powers of a human judge are less critical, the risk of AI making erroneous decisions is comparatively lower.²⁶ Appeals against decisions rendered by an AI judge would still be possible. However, this raises the question of whether the reviewing authority should be another AI judge or a human judge. In the appellate process, the key issue becomes whether such disputes should be reviewed by humans or machines. At present, the prevailing view is that appeals and judicial reviews should be conducted by human judges, ensuring oversight, accountability, and the preservation of fundamental judicial principles.²⁷

Robot judges are beneficial in terms of delivering fast and consistent decisions during judicial proceedings. However, as mentioned in the previous section, their use raises important concerns regarding how case-related information is processed and the protection of personal data throughout the adjudication process.

One of the key risks associated with robot judges is algorithmic bias, which refers to situations where artificial intelligence exhibits unfair or discriminatory behavior. It has been observed that AI systems can sometimes develop biases based on the data sets on which they were trained. Consequently, if a robot judge is trained on biased or unbalanced data, discriminatory tendencies may also manifest in its judicial decisions, raising serious concerns about fairness and equality before the law.²⁸

3. GenAI Applications in Criminal Law

Artificial intelligence applications, which can perceive faster, make decisions, and generate new solutions more efficiently than human intelligence, are increasingly used not only in private law but also in criminal law, and their scope of application continues to expand day by day. In the context of criminal law, AI can be utilized both in the criminal procedure process—the stage following the commission of a crime—and in determining the appropriate sentence for the offender after trial. However, the use of AI in criminal law is not limited to these stages; it can also be employed in preventive criminal law practices, that is, in the pre-crime stage, to help prevent offenses before they occur.

26. “*Medeni Yargılamada Yapay Zeka Kullanımı: Hakim Yapay Zeka, Faydaları ve Sakıncaları Üzerine Bir Değerlendirme*”, s.18

27. Sümer, Seda Yağmur; “*Ceza Yargılamasının Geleceği: Robot Hakim*” (2021) 23 (2) **Dokuz Eylül Üniversitesi Hukuk Fakültesi Dergisi**, s. 1583-1584.

28. “*Medeni Yargılamada Yapay Zeka Kullanımı: Hakim Yapay Zeka, Faydaları ve Sakıncaları Üzerine Bir Değerlendirme*”, s. 23.

GenAI Systems in Preventive Criminal Law

The objective of preventive criminal law systems is based on the belief that the danger and harm caused by a crime cannot be completely eliminated solely through the punishment imposed on the offender²⁹. These systems can be employed not only before a crime is committed but also during the assessment of the likelihood that an offender may reoffend. The ability to predict the probability of recidivism is particularly significant both at the criminal procedure stage and during the execution of a sentence, as it allows for more informed decisions regarding preventive measures, parole, and rehabilitation processes³⁰. In this context, the COMPAS application used in the United States is a risk assessment tool that analyzes an individual's historical data to provide authorities with a risk score indicating the likelihood of the person reoffending in the future³¹. However, it is evident that this AI system—which considers factors such as gender, race, and skin color when generating risk scores—poses significant concerns regarding fundamental principles of criminal procedure, particularly the presumption of innocence, which ensures that every individual is deemed innocent until proven guilty by a final court judgment.

Similarly, the Static-99 tool, another AI-supported system, has been developed specifically for assessing the risk of sexual offense recidivism. It evaluates factors such as the offender's relationship with the victim and the timing of the previous offense to estimate the likelihood of the individual committing another sexual crime³².

Some preventive predictive systems analyze the locations and other factors of previously committed crimes and provide authorities with data about where

29. İçer, Zafer; “*Yapay Zekâ Temelli Önleyici Hukuk Mekanizmaları - Öngörücü Polislik*”; **Yapay Zeka Temelli Teknolojiler ve Ceza Hukuku, İstanbul Barosu, Yapay Zeka Çalışma Grubu Yıllık Rapor**, 2021, s.31, <https://www.istanbulbarosu.org.tr/files/komisyonlar/yzcg/2021yzcgyl-likrapor.pdf> (E.T. 13.10.2025)

30. The belief that the offender may reoffend is a factor considered in the application of many legal institutions. Among the conditions required for the implementation of several institutions—such as the suspension of the execution of a prison sentence regulated under Article 51 of the Turkish Penal Code No. 5237, the deferment of the announcement of the verdict regulated under Article 231 of the Criminal Procedure Code No. 5271, and the conditional release regulated under Article 107 of the Law No. 5275 on the Execution of Sentences and Security Measures—is that the court must reach the conviction that the individual is unlikely to commit another crime

31. Sapan, Oğuzhan; **Ceza Muhakemesinde Yapay Zeka Kullanımı**, Adalet Yayınevi, İstanbul, 2024, s.70-75.

32. Abanoz Öztürk, Buket; “*Suç Davranışını Öngören Üretken Yapay Zekâ Araçlarının Ceza Muhakemesi Hukukunun Temel İlkeleri Bağlamında Değerlendirilmesi*”, **İstanbul Barosu, Üretken Yapay Zekâ ve Hukuki Meseleler Konferans Bildirisi**, https://www.istanbulbarosu.org.tr/files/komisyonlar/yzcg/yzcg_uretkenyzev hukukimeseleler.pdf s. 18.

similar offenses are likely to occur in the future. Applications such as PredPol and Precobs make such predictions³³. However, it should not be forgotten that using locations of past crimes to predict new crime sites can lead to increased surveillance of people in economically disadvantaged areas and may cause discrimination³⁴.

In the context of preventive systems, several AI-supported technologies are utilized within preventive law enforcement. These include MOBESE and similar camera surveillance systems, facial recognition-based security systems developed to ensure secure entry and exit to judicial institutions and public buildings, as well as biometric verification systems. All of these applications employ artificial intelligence to enhance monitoring, identification, and preventive security measures.

Using GenAI mechanisms, a general profile can be created from data in previously adjudicated cases, and the pool of suspects in new, similar incidents can be narrowed based on that profile³⁵. In these systems, the physical characteristics of individuals who have previously committed or attempted to commit crimes are stored in memory. Later, when a person enters the coverage area of facial recognition systems, their movements, gestures, and facial expressions are analyzed; if these match the data stored in the system, the goal is to trigger preventive law enforcement actions before a potential crime occurs³⁶. However, alongside certain beneficial outcomes, it should not be forgotten that these systems constitute an intrusion into personal data. Moreover, if people are aware of the locations of facial recognition systems, they may take measures to avoid being recognized or detected, and this should not be overlooked.

Naturally, since artificial intelligence is a human creation, it is also susceptible to unauthorized access by malicious third parties, making it possible for the data of individuals captured by the system to be altered or misused. In addition to this risk, the presence of numerous variables—such as a person’s emotional state or environmental conditions—raises another concern: the possibility that the system

33. “Suç Davranışını Öngören Üretken Yapay Zekâ Araçlarının Ceza Muhakemesi Hukukunun Temel İlkeleri Bağlamında Değerlendirilmesi”, s. 17.

34. Ateş, Hüseyin; **Ceza Muhakemesinde Kullanılan Yapay Zeka Uygulamalarının Ceza Muhakemesi İlkeleri Açısından Değerlendirilmesi**, Yayınlanmamış Doktora Tezi, 2025, s. 90.

35. **Dijital Ceza Muhakemesi Hukuku**, Ed: Öztürk, Bahri/Tezcan, Durmuş/Erdem, Mustafa Ruhan, Seçkin, Ankara, 2024, s. 229.

36. İçer, Zafer/Dönmez, Elif; “Yüz Tanıma Teknolojilerinin Önleyici Ceza Hukuku ve Ceza Muhakemesi Süreçlerindeki Kullanımı ve Sınırları”, **Ceza Hukuku Dergisi**, Ağustos 2020, Y.15, S.43, 421-461.

may record data only for certain types of offenders, thereby operating in a biased and probabilistic manner rather than as an objective and reliable tool.

Despite the many positive outcomes of preventive artificial intelligence mechanisms, it is undeniable that they restrict individuals' freedom of movement. They pose significant risks to the right to privacy in general and to the protection of personal data in particular. Moreover, such systems may also enable malicious uses, such as the increased surveillance of groups that may already be considered socially or economically disadvantaged, thereby exacerbating existing inequalities³⁷. For this reason, AI-supported preventive mechanisms—which involve the monitoring and recording of personal data—must be grounded on solid legal foundations. They should be used solely as supportive tools to assist law enforcement activities, while the final decision must always be rendered by a human authority, not by the AI system itself. In this way, in the event of any legal violation, it will be possible to identify and assign criminal and legal responsibility to the appropriate party.

GenAI Applications in Criminal Procedure Law

In addition to its use prior to the commission of a crime, artificial intelligence—and particularly GenAI applications—can also be employed during the trial phase, which constitutes the stage following the commission of the offense.

At the investigation stage, which marks the initial phase of criminal procedure, the use of AI-supported applications may play a significant role. During an investigation, establishing a complete, accurate, and coherent sequence of events is crucial for uncovering the material truth. At this stage, GenAI applications can assist by compiling the statements taken by law enforcement officers or the public prosecutor together with the interrogation records prepared by the judge, thereby constructing a comprehensive narrative of the case. Of course, in doing so, the system would not rely solely on witness or suspect statements but would also analyze lawfully obtained camera footage and audio recordings to reach conclusions. It could identify inconsistencies between statements or between statements and recorded evidence, and based on these discrepancies, generate alternative narratives for each possible scenario. In this way, during complex and large-scale investigations, the AI system could quickly

37. Özbalçık, Ozan Can; “Ceza Muhakemesinde Yapay Zeka Temelli Risk Değerlendirme Araçları ve Hukuki Etkileri”, **Yapay Zeka Temelli Teknolojiler ve Ceza Hukuku, İstanbul Barosu, Yapay Zeka Çalışma Grubu Yıllık Rapor**, 2021,s.93, <https://www.istanbulbarosu.org.tr/files/komisyenlar/yzcg/2021yzcgyillikrapor.pdf> (E.T. 13.10.2025)

provide criminal procedure practitioners with a comprehensive overview of the case, helping them to visualize the broader context more efficiently.

As mentioned above, generative AI-based systems construct the sequence of events by utilizing the available evidence. Artificial intelligence can also be employed both in the generation of digital evidence and in the evaluation of such evidence, along with other types of proof. Indeed, at this stage, criminal procedure seeks to employ the most advanced technologies to uncover the material truth in the fastest and most reliable manner possible³⁸.

In criminal procedure, the term digital evidence refers to data that is created, stored, or transmitted in an electronic environment³⁹. In this context, digital evidence includes electronic communications, audio and video materials, computer programs, both hidden and accessible files of any kind, previously visited websites, and even deleted data—all of which constitute data existing in a digital environment⁴⁰.

In terms of the production of digital evidence, it is first possible to restore existing but deleted or corrupted data to transform it into usable and reliable evidence. Additionally, AI systems can generate digital reconstructions or simulations based on the available evidence, thereby creating new digital representations of the event. However, in such cases, it would be more appropriate to treat these AI-generated materials not as conclusive evidence, but rather as interpretations or reconstructions of existing evidence.

For digital data generated by artificial intelligence to be considered admissible evidence, several conditions must be met simultaneously. First, the method of generation, including the algorithm used and the data sources, must be transparent and the output must be verifiable through human oversight. Additionally, as with all other types of evidence, digital evidence must be obtained lawfully, and the use of generative AI must not result in violations of personal data, unlawful interception of private communications, or infringement of privacy. Finally, the algorithm employed must be subject to judicial review, and the outcomes must not be random or speculative in nature.

Another critical point to consider regarding the production of digital evidence is the creation of fake evidence, commonly known as deepfake. With recent technological advancements, it has become extremely easy to generate manipulated images, fabricated audio recordings, or falsified videos,

38. Ceza Muhakemesinde Yapay Zeka Kullanımı, s.205.

39. Dijital Ceza Muhakemesi, s. 443.

40. Dülger, Murat Volkan; **Bilişim Suçları ve İnternet İletişim Hukuku**, Seçkin, 2025, s.668 vd.

highlighting the necessity of adopting a cautious and skeptical approach toward all forms of digital evidence⁴¹.

In addition to generating digital evidence, AI systems can also be used to evaluate it; in this context, they can sift through hundreds or even thousands of lawfully obtained items—such as camera footage and emails—to determine where individuals were and with whom at the date and time an offense occurred, thereby reducing human error⁴².

GenAI Applications in Sentencing Determination

Generative artificial intelligence applications can also be utilized at the sentencing stage, which represents the final outcome of criminal proceedings. In this context, certain AI systems that provide statistical analyses can function as judicial assistants by identifying keywords and factual elements within the case file and presenting the judge with information on types and ranges of penalties imposed in similar past cases⁴³.

In another scenario, an AI application could compare the details and judgments of previous case files with the facts of the current case and provide the judge with a recommendation regarding the appropriate type of sentence that could be imposed. Such a recommendation would serve merely as advisory guidance, not as a binding decision.

However, regardless of the circumstances, the imposition of a prison sentence, which entails the restriction of an individual's liberty, should never be left to an AI system. Sentencing decisions must remain the result of the judge's discretionary authority, grounded not only in legal knowledge but also in judicial experience and human judgment.

4. Results and Conclusion

As in many other fields, GenAI applications have made significant positive contributions to the legal domain. Primarily, by saving practitioners time and effort in both branches of law, these systems can enhance human productivity and reduce error rates in situations where factors such as workload or extensive

41. Abanoz, Buket; “*Derin Sahte (Deepfake) Teknoloji Karşısında Türk Ceza Hukuku*”, **Yapay Zeka Temelli Teknolojiler ve Ceza Hukuku, İstanbul Barosu, Yapay Zeka Çalışma Grubu Yıllık Rapor**, 2021, s.68, (E.T.13.10.2025.) <https://www.istanbulbarosu.org.tr/files/komisyonlar/yzcg/2021yzcgyillikrapor.pdf>

42. Dijital Ceza Muhakemesi Hukuku, s.231.

43. Kabak Yüce, Emine; “*Cezanın Belirlenmesinde Yapay Zeka Temelli Sistemlerin Kullanımının Değerlendirilmesi*”, **Ceza Hukuku Dergisi**, 48 (2022), s. 100.

case files might otherwise lead to oversight or inattention. By analyzing vast amounts of data within a very short time, AI systems can deliver results in minutes that would otherwise take days of human effort. In applications such as e-discovery, this leads to a significant acceleration of procedures, particularly in private law. However, when lawyers upload information to an AI system, there is a potential risk of violating the duty of confidentiality. As a result, the lawyer may not only face professional liability but also be held responsible for breaching the obligations of a data controller under the Law on the Protection of Personal Data (LPDP).

Through artificial intelligence systems, it is now possible to access thousands of judicial precedents, legislative texts, and doctrinal sources within a very short time. AI enhances the quality of legal research by conducting searches not only through keywords but also by identifying semantic relationships among concepts. Moreover, judge-assisting AI systems, such as those that generate draft judgments, can accelerate judicial proceedings, promote consistency in court decisions, summarize documents, and prepare transcripts, thereby contributing to the implementation of the principle of a reasonable trial duration. However, one of the most frequently criticized aspects of AI applications—the phenomenon of “AI hallucination”, in which non-existent court decisions or incorrect information are generated—remains a significant concern. Therefore, any data or findings produced by AI must always undergo human review and verification to ensure accuracy and reliability.

Certain artificial intelligence systems can ease lawyers’ workloads by facilitating document tracking, communication, and client management. However, the human connection and empathy that must exist between a lawyer and their client cannot be replicated by artificial intelligence, making it impossible for AI to fully replace the interpersonal aspects of the attorney–client relationship.

Specifically regarding the contributions of GenAI in criminal law, preventive criminal law systems can help anticipate crimes before they occur, enabling the implementation of preventive measures and thus preventing potential harm or danger resulting from criminal acts. At the same time, in addressing challenges such as excessive caseloads and delays in the administration of justice, AI applications in the legal field can significantly accelerate judicial processes, helping ensure that justice is delivered more efficiently and in a timely manner.

Additionally, artificial intelligence applications that classify judicial decisions can assist legal practitioners by scanning case law and organizing it

based on criteria such as type of crime and manner of commission. By providing such a structured roadmap, these systems promote the issuance of consistent rulings in similar cases, thereby enhancing predictability and legal certainty within the justice system.

Another positive contribution of artificial intelligence lies in the generation and evaluation of digital evidence. AI can help access more reliable and impartial forms of evidence, complementing subjective elements such as the statements of suspects, defendants, victims, or witnesses. In this way, it can support the primary goal of criminal procedure — the pursuit of material truth — by reducing bias and enhancing evidentiary accuracy.

In addition to the positive contributions of GenAI mentioned above, there are also significant concerns associated with its use. Particularly in the field of preventive criminal law, AI applications that involve monitoring specific regions or social groups risk undermining the presumption of innocence. Restrictive measures implemented without fulfilling the necessary constitutional requirements for limiting individual rights and freedoms may result in violations of privacy and the right to protection of personal data, and could ultimately lead to a situation where individual liberty is sacrificed in the name of public security.

Furthermore, through tools such as risk assessment systems, individuals may be labeled as potential offenders even in the absence of any concrete suspicion. Since such AI systems are human-made, they inherently carry the risk of bias and discrimination, potentially reinforcing existing social inequalities rather than eliminating them.

Regarding digital evidence, the fact that the algorithms used to generate or evaluate evidence with generative AI are not known to the parties in the proceedings undermines the principle of transparency. This so-called “black box” effect makes judicial oversight impossible and thus threatens the right to a fair trial. In addition, the ability to produce fake evidence through deepfake applications will further erode public confidence in the legal system.

In conclusion, artificial intelligence applications—particularly those based on generative AI—should be used as support mechanisms for practitioners, not as replacements for the discretion and judgment of judicial authorities. Since AI relies solely on existing data, it remains inadequate in assessing the unique circumstances of individual cases and the evolving needs of society. Therefore, the judge’s conscience and discretionary power remain indispensable elements of the justice system. For this reason, every stage involving the use of artificial intelligence must remain under human supervision. Even if human input is minimal during the process, the final outcome must always be reviewed and

evaluated by a human, ensuring that justice is exercised through human judgment rather than algorithmic automation.

References

1. Abanoz, Buket, “*Hukuki Bilgiye Dijital Eriřim*”, Marmara Üniversitesi Hukuk Fakültesi Hukuk Arařtırmaları Dergisi, C. 26, S. 1, Haziran 2020, s.190-203
2. Ateř, Hüseyin; **Ceza Muhakemesinde Kullanılan Yapay Zeka Uygulamalarının Ceza Muhakemesi İlkeleri Açısından Deęerlendirilmesi**, Yayınlanmamıř Doktora Tezi, 2025.
3. Bilgin, Hikmet; “*Yapay Zekânın Mahkeme Kararlarında Kullanımına Uluslararası Bir Bakıř ve Robot Hâkimler Hakkında Düşünceler*”, **İNÜHFD** 13(2):405-419 (2022).
4. Çatal, Betül; “*Yapay Zekanın Karar Verme Süreçlerinde Kullanılması*”, **SÜHFD**, C. 33, S. 1, 2025, s.311-348.
5. **Dijital Ceza Muhakemesi Hukuku**, Ed: Öztürk, Bahri/Tezcan, Durmuř/Erdem, Mustafa Ruhan, Seçkin, Ankara, 2024.
6. Dülger, Murat Volkan; **Biliřim Suçları ve İnternet İletişim Hukuku**, Seçkin, 2025.
7. Efe, Ahmet; “*Yargısal ve Hukuki Süreçlerde Yapay Zeka Kullanan Araçlar Üzerine Bir Deęerlendirme*”, **Bilgi Yönetimi Dergisi**, C. 5, S. 1, 2022, s.92-117
8. Görentař, Muhammed Burak; “*Hukukta Yapay Zeka*”, **SSDjournal**, Volume 8 Issue 41, 2023 December, s.1-14.
9. İçer, Zafer/Dönmez, Elif; “*Yüz Tanıma Teknolojilerinin Önleyici Ceza Hukuku ve Ceza Muhakemesi Süreçlerindeki Kullanımı ve Sınırları*”, **Ceza Hukuku Dergisi**, Ağustos 2020, Y.15, S.43, 421-461.
10. Karabel, E. Gökçe/ Aydemir, Dilek; “*Medeni Usul Hukukunda Yargılamanın Hızlandırılması ve Adalet Eriřim Hakkı Bakımından Çevrimiçi Yargılama ve Yapay Zekanın Kullanımı*”, **Marmara Üniversitesi Hukuk Fakültesi Hukuk Arařtırmaları Dergisi**, C. 29, S. 1, Haziran 2023, s.530-573.
11. Kabak Yüce, Emine; “*Cezanın Belirlenmesinde Yapay Zeka Temelli Sistemlerin Kullanımının Deęerlendirilmesi*”, **Ceza Hukuku Dergisi**, 48 (2022), s.77-128.
12. Karadeniz, Salih; “*Medeni Yargılamada Yapay Zeka Kullanımı: Hakim Yapay Zeka, Faydaları ve Sakıncaları Üzerine Bir Deęerlendirme*”, **Geliřen Teknolojilerin Medeni Usul Hukukuna Etkileri**, Seçkin, 2023, s.205-238.

13. Sapan, Oğuzhan; **Ceza Muhakemesinde Yapay Zeka Kullanımı**, Adalet Yayınevi, İstanbul, 2024.

14. Selçuk, Seyhan; “*Makûl Sürede Yargılama Yapılmasında Yapay Zekanın Etkisi*”, **Türkiye Adalet Akademisi Dergisi**, Yıl 16, S. 62, Nisan 2025, s. 429-462.

15. Sümer, Seda Yağmur; “*Ceza Yargılamasının Geleceği: Robot Hakim*” (2021) 23 (2) **Dokuz Eylül Üniversitesi Hukuk Fakültesi Dergisi**, s.1543-1591.

16. Yılmaz, Oğuz Gökhan, “*Yargı Uygulamasında Yapay Zeka Kullanımı- Yapay zeka Hakim Cübbesini Giyebilecek mi?*”, **Adalet Dergisi**, 2021/1, S.66, s.379-415.

Online References

1. LawGeex Hits 94% Accuracy in NDA Review vs 85% for Human Lawyers – Artificial Lawyer (Erişim Tarihi 14.10.2025)

2. Demir, Şamil; “*Yapay Zeka Modellerinin Avukatlık Mesleğinin Geleceği Üzerine Olası Etkileri*”, https://www.researchgate.net/profile/Samil-Demir/publication/391988259_Yapay_Zeka_Modellerinin_Avukatlik_Mesleginin_Gelecegi_Uzerindeki_Olasi_Etkileri/links/682fa1798a76251f22e59cd3/Yapay-Zeka-Modellerinin-Avukatlik-Mesleginin-Gelecegi-Uzerindeki-Olasi-Etkileri.pdf (E.T. 14.10.2025)

3. Ankara Barosu Kişisel Verilerin Korunması Kanunu Rehberi, <http://kutuphane.ankarabarusu.org.tr/cgi-bin/koha/opac-retrieve-file.pl?id=f43fb4f3cfd21f9014746ff2e97b047> (E.T. 14.10.2025)

4. Kotil Öğretmen, Zeynep; “*Hukukta Yapay Zekâ Uygulamaları*”, İstanbul 2022, https://www.istanbulbarosu.org.tr/files/komisyonlar/yzcg/hukukta_yapay_zeka_uygulamaları.pdf (E.T. 14.10.2025)

5. **Ankara Barosu Avukatlıkta Yapay Zeka Araçlarının Kullanım Rehberi**, https://www.ankarabarusu.org.tr/serve/file/bc4de0be-b5fa-11ef-8f94-000c29c9dfce/yapay_zeka_arac_lar_nn_kullanm_rehberi_X1.pdf (E.T. 14.10.2025)

6. <https://www.reuters.com/technology/artificial-intelligence/ai-hallucinations-court-papers-spell-trouble-lawyers-2025-02-18/> (E.T. 14.10.2025)

7. Karadeniz, Salih; “*Medeni Yargılamada Yapay Zeka Kullanımı Hakim Yapay Zeka*”, https://www.researchgate.net/profile/Salih-Karadeniz/publication/372190333_Medeni_Yargilamada_Yapay_Zeka_Kullanimi_Hakim_Yapay_Zeka_Faydalari_ve_Sakincalari_Uzerine_Bir_

Degerlendirme_The_Use_of_Artificial_Intelligence_in_Civil_Jurisdiction_An_Evaluation_on_Judge_Artificial_I/links/66687abea54c5f0b945f95aa/Medeni-Yargilamada-Yapay-Zeka-Kullanimi-Hakim-Yapay-Zeka-Faydalari-ve-Sakincalari-Uezerine-Bir-Degerlendirme-The-Use-of-Artificial-Intelligence-in-Civil-Jurisdiction-An-Evaluation-on-Judge-Artificial.pdf (E.T. 15.10.2025)

8. İçer, Zafer; “*Yapay Zekâ Temelli Önleyici Hukuk Mekanizmaları - Öngörücü Polislik*”; **Yapay Zeka Temelli Teknolojiler ve Ceza Hukuku, İstanbul Barosu, Yapay Zeka Çalışma Grubu Yıllık Rapor**, 2021, s.31, <https://www.istanbulbarosu.org.tr/files/komisyonlar/yzcg/2021yzcgyillikrapor.pdf> (E.T. 13.10.2025)

9. Abanoz Öztürk, Buket; “*Suç Davranışını Öngören Üretken Yapay Zekâ Araçlarının Ceza Muhakemesi Hukukunun Temel İlkeleri Bağlamında Değerlendirilmesi*”, **İstanbul Barosu, Üretken Yapay Zekâ ve Hukuki Meseleler Konferans Bildirisi**, https://www.istanbulbarosu.org.tr/files/komisyonlar/yzcg/yzcg_uretkenyzvehukukimeseleler.pdf

10. Özbalçık, Ozan Can; “*Ceza Muhakemesinde Yapay Zeka Temelli Risk Değerlendirme Araçları ve Hukuki Etkileri*”, **Yapay Zeka Temelli Teknolojiler ve Ceza Hukuku, İstanbul Barosu, Yapay Zeka Çalışma Grubu Yıllık Rapor**, 2021,s.93, <https://www.istanbulbarosu.org.tr/files/komisyonlar/yzcg/2021yzcgyillikrapor.pdf> (E.T. 13.10.2025)

11. Abanoz, Buket; “*Derin Sahte (Deepfake) Teknoloji Karşısında Türk Ceza Hukuku*”, **Yapay Zeka Temelli Teknolojiler ve Ceza Hukuku, İstanbul Barosu, Yapay Zeka Çalışma Grubu Yıllık Rapor**, 2021, s.68, (E.T.13.10.2025.) <https://www.istanbulbarosu.org.tr/files/komisyonlar/yzcg/2021yzcgyillikrapor.pdf>

CHAPTER XV

GENERATIVE AI IN MEDIA, COMMUNICATION AND VISUAL ARTS

Oğuz KAYNAR¹ & Murat Fatih TUNA²

¹(Prof. Dr.) Sivas Cumhuriyet University, Sivas, Türkiye

E-mail: okaynar@cumhuriyet.edu.tr

ORCID: 0000-0003-2387-4053

²(Assoc. Prof. Dr.) Sivas Cumhuriyet University, Sivas, Türkiye

E-mail: mftuna@cumhuriyet.edu.tr

ORCID: 0000-0002-8634-8643

1. Introduction

The digital transformation process can be described as a broad restructuring across various fields, from individuals' daily practices to social structures, industrial processes to economic sustainability, through the integration of innovative technologies such as internet technologies, artificial intelligence, and algorithmic processes (Feher, 2025). Artificial intelligence, in particular, has become a trend of the future, affecting the entire media sector, from the generation of digital content to the distribution of news. Following the changes in digital communication technologies, the sector, now known as the Media and Content Industry (MCI), has become receptive to innovations brought about by related developments (Simon, 2013). Art, highlighted as one of these innovations, has merged with digital media technologies and come to be known as digital media art. The practice of digital media art is a new field of artistic application research and creation that integrates modern science and technology with traditional art fields (Wang, 2022).

New media art, an innovative fusion of digital technology and artistic creativity, is restructuring cultural experiences in innovative ways through individual aesthetic perceptions (Y. Zhao, 2024). At this point, artificial intelligence (AI) continues to increase its influence in the field of visual

communication in new media art, as it does in every area of society (Lyu et al., 2022). Statistics presented in an industry research report published by Grand View Research also point to this effect (Grand View Research, 2025). The report, which highlights the use of AI in the media and entertainment sector between 2025 and 2030, estimates that the relevant market will grow at a CAGR of 24.2% between 2025 and 2030, reaching USD 99.48 billion by the end of the period.

Researching the synergistic effect of artificial intelligence technology in the evolution of visual communication in new media art offers broad opportunities for practical application and valuable contributions to theoretical discussions (Hong & Curran, 2019; Y. Zhao, 2024). Artificial intelligence, guided by the science and technology of intelligence, not only enables a renewed understanding of cognitive processes through its capacity to develop and simulate human intelligence, but also offers unlimited possibilities in the field of visual communication in new media art (Lyu et al., 2021). However, AI's simulation of human intelligence and creativity, while enhancing artistic expression within the text, also allows for the manipulation of reality. This duality carries the risk of misuse of generative models and can pose serious problems regarding the accuracy and reliability of the generated content (Kalantzis & Cope, 2025). Furthermore, as AI-generated content becomes more widespread, it requires a clearer understanding of human-machine interaction, particularly in terms of ensuring efficiency (Lyu et al., 2021; Wu et al., 2020).

Creating high-quality images from textual descriptions is a persistent challenge with numerous practical applications. This challenge spans multiple fields, including media, industrial design, e-commerce, education, and many others (Arya et al., 2024). However, its widespread potential for use and the ease of access to digital technologies for individuals have made it difficult to distinguish between authentic images and generated images. While this generated vision has the potential to meet industrial needs, it also introduces several methods that pose privacy and security concerns (Westerlund, 2019). The term Deepfake, derived from the combination of the words “deep learning” and “fake”, is at the forefront of these methods. This technology, which can superimpose and alter images, video clips, and generate convincing fake images, leaves no trace of manipulation (Chawla, 2019). Using Deepfake, users can replace one person's face with another's in an image or video, and the original voice and facial expressions in an image or video can also be altered (Chadha et al., 2021).

Based on this, the current study aims to investigate the role of GenAI in increasing activity in media, communication, and visual arts. To achieve this goal, the study began with the technical evolution of visual generation models and

continued with the role of artificial intelligence in image and video generation. Furthermore, existing technologies have been reviewed, along with supporting literature, to provide insight into possible future research directions. In this regard, opportunities, risks, and threats related to real-time and multi-interactive environment solutions have been addressed within the scope of the study.

2. Technical Evolution of Visual Generation Models

People perceive the world and the objects within it through their senses; in a sense, they obtain concrete and cognitive stimuli through their interaction with these objects. The sense of sight, facilitated by images and videos, enables people to get details about the external appearance of objects (such as shape and color) without requiring physical contact (Xi et al., 2024). However, images are also used to describe perceived objects, and the rise of AI technologies in the narratology of these images continues. Takashi & Jumpei (2020) interpret this situation as an increase in the role of artificial intelligence in filling the gap between cognitive science and visual narratology.

The use of artificial intelligence is seen as an alternative and low-cost way to enhance the narratology of an object (Gulsoy et al., 2024). Due to their wide range of applications, the generation of visual models using artificial intelligence has become a highly popular topic. Generating high-quality images based on a wide range of styles and levels of realism continuously improves the quality of outputs, thereby convincing the target audience of the image's realism (Zhang et al., 2019). Despite recent advances in generative image and video modeling (Brock et al., 2019; Wang et al., 2024), achieving AI-based generations from complex datasets remains a challenging goal.

Laba (2024) conceptualizes AI-based image generation as a socio-technical practice at the intersection of humans, machines, and culture. Accordingly, visual AI generative structures organize the narratological themes presented to them into a layout based on these three elements. Thus, most image generators working with GenAI technologies enable users to create high-quality images with simple commands, even if they lack advanced visual design skills or detailed artistic expertise (Park et al., 2024). These images are used in various fields, including gaming, media, news, scientific visualization, artistic creation, tourism, advertising, design, engineering, e-commerce, and digital marketing. However, the use of these generative visual models has continued to evolve in line with the needs of the the aforementioned industries. The relevant evolutionary process is shown in Figure 1 (Laba, 2024; Park et al., 2024; Praveen et al., 2025; Si & Bao, 2025; Tatar et al., 2018).

Generative Artificial Intelligence (GenAI) refers to AI structures that utilize deep learning models to generate human-like content based on complex and diverse prompts (Lim et al., 2023). Unlike predictive artificial intelligence, which focuses on analyzing input data to make predictions or decisions, GenAI aims to create new content or data that is similar to, yet distinct from the training data (Heigl, 2025). When examining the development process of Generative Visual Models, which enable GenAI, it becomes clear that autoencoders are at the core of the technical evolution. These structures are one of the widely known deep learning methods that generate new data sampled from a learned latent space (Kingma & Welling, 2022). Variational models that use neural networks for recognition models are at the forefront in this structure (Hinton & Salakhutdinov, 2006).




Figure 1. Evolution of Generative Visual Models

In the following section, developments in the field of text-to-image and text-to-video generation will be examined within the framework of both proprietary commercial products and fundamental theoretical approaches. Since all of the structures presented are essentially based on an algorithmic foundation, the term “model” will be used as an umbrella term in this study to refer to both commercial products and academic approaches.

3. Visual Generation Models According to Generation Paradigms

GenAI Visualization Models are divided into three categories based on generation paradigms. These are the VAE (Variational AutoEncoder) probabilistic sampling paradigm from the latent space, the GAN (Generative Adversarial Network) adversarial generation paradigm, and the DM (Diffusion Models) iterative denoising paradigm (Guarnera et al., 2024; Rais et al., 2024; Sordo et al., 2025). These models are compared in Table 1.

Table 1. Comparison of VAE, GAN and DM Models

MODEL	VAE	GAN	DM
Generation Paradigm	Probabilistic Sampling	Adversarial Generation	Iterative Noise Reduction
Basic Idea	Encodes the data into a compressed latent space and generates images by sampling new points from this space.	While a “generator” generates fake images, a “discriminator” attempts to distinguish them from real ones; this competition improves quality.	Gradually adds noise to an image and then learns to create a clean image from pure noise by reversing this process.
Basic Difference	Focuses on encoding and decoding. Prioritizes representation over image quality.	Indirectly learns the data distribution through competition based on game theory.	Creates the image not in a single step, but through a multi-step purification process.
Pros	Stable training, meaningful latent space, fast generation	Sharp and realistic images, fast generation.	Highest image quality, consistent training.
Cons	Due to reconstruction loss, it generally generates images that are blurrier and less detailed than those generated by others.	Unstable training (characterized by problems such as mode collapse) and difficult to tune.	Slow generation, high computational cost.

Among these models, the VAE only learns the distribution of the data, rather than a compressed image, and can decode and generate new data using this distribution. The two components of the model, the encoder and decoder, are shown in Figure 2a.




Figure 2a. Encoder-Decoder Structure in the VAE Model (DiShi Zhu, 2020)

The running principle of the model is shown in Figure 2b (DiShi Zhu & Vera Tang, 2020).




Figure 2b. A Framework for VAE (DiShi Zhu & Vera Tang, 2020)

In this model, the encoder attempts to learn parameters ϕ to compress the input data x into a hidden vector z , and the output encoding z is obtained from a Gaussian density with parameters ϕ . The input to the decoder is the encoding z , which is the output of the encoder. It parameterizes the reconstructed x via parameters θ , and the output x is obtained from the data distribution.

Another model, GAN, is an algorithm that utilizes two neural networks: the generator, denoted as ‘G’ and the discriminator denoted as ‘D’. These two networks compete with each other (hence the term “adversarial”). The framework for the model is shown in Figure 3.




Figure 3. A Framework for GAN (Kamat, 2025)

According to the framework in the image, the discriminator must master distinguishing whether an image is “real” or “fake”. At the same time, the generator must improve itself to generate images realistic enough to be approved by the discriminator. This continuous competition forces the generator to continually improve itself, ultimately generating extremely realistic and high-quality images that are nearly indistinguishable from the original dataset.

Diffusion Models perform image generation through a mechanism that gradually converts an image into noise (forward process) and then learns to clean the noise step by step by reversing this process (backward process). This enables the model to synthesize high-quality and diverse new images starting from pure noise (Sordo et al., 2025). The framework for the model is shown in Figure 4.




Figure 4. A Framework for Diffusion Models (Sordo et al., 2025)

The working principle of diffusion models is fundamentally based on two opposing processes: The forward diffusion process and the reverse diffusion process. The forward process involves taking an original, clean image (x_0) and systematically degrading it by adding Gaussian noise (ϵ) at each step (t) over a time step T . The state of this degradation at any time ‘ t ’ can be directly calculated using the coefficient $\bar{\alpha}_t$, which depends on the original image and the added noise, and at the end of the process, the image turns into pure noise ($x_t \approx N(0, I)$). The inverse process, where generation occurs, aims to do the exact opposite. Starting from pure noise (x_t), the model uses a neural network with parameters θ to learn to predict and remove the noise ($\epsilon\theta(x_t, t)$) added to the image at each time step (t). The neural network looks at x_t and estimates the probability distribution (mean $\mu\theta$ and variance $\Sigma\theta$) of the previous, cleaner state x_{t-1} . When this noise cleaning process is repeated over T steps, the model successfully generates a new, synthetic image that resembles the original data distribution ($p\theta(x_0)$), starting from the initial meaningless noise.

4. GenAI Visualization According to Functional Differences

4.1. Text-to-Image Models

□ **Variational AutoEncoders (VAEs) and Autoregressive Models (Transformers):** Generative models that learn the meaningful and latent representation of data are exemplified by **Variational Autoencoders (VAEs)**, which operate by first compressing high-dimensional inputs into a structured, lower-dimensional space and then sampling from this space to synthesize new data instances. These models, which consist of two components—an encoder and a decoder—convert the high-dimensional data they receive as input into a low-dimensional latent vector, and then attempt to reproduce the original data using this vector sampled from the latent space (Kingma & Welling, 2022). Autoregressive models are AI generation models that create data by generating one element at a time. When generating the next element, they use all previously generated elements as a condition. These models are adept at capturing long-range dependencies in sequences, owing this ability to transformer architectures, which are based entirely on the self-attention mechanism, without requiring recurrent or convolutional layers (Vaswani et al., 2023). Specific models using these model structures can be listed as follows:

- **DALL·E 1:** DALL·E is a groundbreaking artificial intelligence (AI) model that can generate images from text descriptions. The model’s name is

inspired by Pixar's animated robot character WALL-E and Spanish surrealist artist Salvador Dalí (GIGAZINE, 2021). Developed by OpenAI, DALL·E utilizes a state-of-the-art deep learning model to generate high-quality, detailed images suitable for various applications, including product design and advertising (Zhou & Nabus, 2023). It can thus generate visual words at low resolution and with high creativity. DALL·E has exciting potential due to the new possibilities it offers for creativity and artistic expression. It is also one of the first models to introduce the ability to generate images from textual descriptions, demonstrating creativity by combining concepts that are difficult to relate to each other in reasonable ways. Technical limitations, such as DALL·E's 12 billion parameter architecture and intensive training process, necessitated the development of a more efficient approach. Developed in this vein, DALL·E 2 has succeeded in generating higher-resolution and more realistic images through a more efficient training process, thanks to the integration of the CLIP model (Subramanian, 2025), which establishes a stronger semantic bridge between text and visuals.

- **Cogview:** It is a powerful generative model that combines computer vision with natural language processing techniques to generate images from text prompts. The model's core idea is to provide large-scale generative pretraining capabilities for image tokens (such as VQ-VAE) (Hu et al., 2023). It is a model that offers greater fine-tuning capability than DALL·E in the sub-tasks of style learning, resolution, and text-image alignment (Ding et al., 2021).

- **dVAE:** Dynamic variational autoencoders (dVAE) combine standard variational encoders with a temporal model, thereby enabling unsupervised representation learning for sequential data (Ramesh et al., 2021). These models can convert continuous data consisting of pixels into discrete text sequences and generate images compatible with transformer model architectures (Oord et al., 2018).

- **VQGAN+CLIP:** This model, which combines two separate machine learning algorithms based on text commands, involves VQGAN learning a codebook vector composed of contextually rich visual fragments, and the composition of these codebook vectors is then modeled using an autoregressive transformer. CLIP, on the other hand, is another neural network that can determine how well a caption (or prompt) matches an image (Russell, 2022).

- **Parti (Pathways Autoregressive Text-to-Image):** The Pathways Autoregressive Text-to-Image (Parti) model, developed by Yu et al. (2022), generates high-quality photorealistic images and offers the ability to synthesize rich content with complex compositions and digital world knowledge. Parti

treats text-to-image conversion as a type of sequence-to-sequence modeling problem; therefore, image token sequences replace the target output text tokens.

- **VQSEG:** VQSEG (Vector Quantized for Segmentation) utilizes a structure called a semantic segmentation map during image generation. This structure enables the image to be synthesized in a semantic infrastructure while also providing guidance on what to generate, thereby making unconditional image generation controllable (Alaniz et al., 2022). Thanks to this control, thematic style and content can be effectively separated to enhance performance while preserving the semantic consistency of the image.

→ Generative Adversarial Networks (GANs) Based Models

GANs (Generative Adversarial Networks) have seen increasing use in image modeling over the past decade. Current text-to-image generation techniques struggle to capture the subtle details and dynamic object components that are discernible in the real world (Arya et al., 2024). GANs, which can be trained dynamically and are sensitive to various factors, including optimization parameters and model architecture, can generate theoretical and empirical insights when they trained in a stable manner (Brock et al., 2019). These models have also transformed image generation by improving the discrimination performance between authentic and generated images (Gulsoy et al., 2024). These models rely on the use of two opposing models (namely, generator and discriminator) (Celard et al., 2024).

- **StackGAN:** This model simulates human creativity processes in image generation and occurs in two stages (Arya et al., 2024). In the first stage, GenAI creates a specific shape of the object based on the text. In the second stage, the quality of the existing output is enhanced, and more realistic details are incorporated into the image. The method also demonstrates high performance in identifying faces, facial features, facial identity, facial expressions, and facial emotions in the image generation process (W. Chen et al., 2025). Furthermore, it can prevent face occlusion issues (Jabbar et al., 2022).

- **CycleGAN+BERT:** This model combines CycleGAN, which excels at transforming paired generated text sets, with BERT, which deeply understands the semantic structure of text. To ensure model consistency and stabilize data training, it performs transfers from source to target and from target to source (Tsue et al., 2020). Thus, an image-to-text conversion component is added to verify that the generated image is semantically consistent with the input caption text (Zhu et al., 2020).

- **MirrorGAN:** As a global-local collaborative model, MirrorGAN is based on the idea of generating images from text through re-description and consists of three main stages (Qiao et al., 2019). These stages are a semantic text embedding module (STEM), a global-local collaborative attentive module for cascaded image generation (GLAM), and a semantic text regeneration and alignment module (STREAM). Of these, STEM creates embeddings at the word and sentence level. GLAM generates fine-tuned target images. Finally, STREAM checks that the generated image matches the text description.

- **LSTM+GAN:** While a type of recurrent neural network (RNN) called LSTM specializes in learning temporal connections in sequential data, the related model leverages GAN's performance in generating realistic data (Son et al., 2023). This model can account for the complex structures and distributions in the real data set, as well as predict sequential and temporal data generation patterns with high performance (Mogren, 2016).

- **AttnGAN (Attentional GAN):** As an attention-based generative model, AttnGAN can synthesize fine-grained images by paying attention to relevant words in the NLP process (Xu et al., 2018). The model also relies on a deep attention similarity model to calculate image-text matching loss during generator training (Naveen et al., 2021).

- **DF-GAN (Deep Fusion GAN):** Another customized model of GAN, DF-GAN, can generate high-resolution images with a single-stage backbone while ensuring text-image semantic consistency without requiring additional networks (Tao et al., 2022). Thus, it can combine the features of text and images in a simpler, deeper, and more effective way than traditional GAN-based methods (Sun et al., 2023).

- **VGAN (Variational GAN):** VGAN is a model developed to eliminate fluctuations frequently encountered in the training process of standard GAN-based models (Pu et al., 2022). The model attempts to generate a new image from noise that appears to originate from training data, utilizing a variational autoencoder based on GAN (J. Chen et al., 2018).

- **TGAN (Temporal GAN):** The model proposed by Saito et al. (2017) can learn the semantic representation of unlabeled videos and generate videos. Here, the temporal generator takes a latent variable as input and generates a sequence of latent variable outputs corresponding to each frame in the video. The resulting set of variables is then transformed into a video that more accurately reflects reality (Celard et al., 2024).

→ Diffusion Models (DMs)

Diffusion Models (DMs) have gained prominence in recent years in the field of computer-generated imagery and can generate remarkable results in the context of modeling productivity. These models fall under the category of deep generative models and can generate a wide variety of high-quality images. (Croitoru et al., 2023; Radford et al., 2021). DMs encompass the following specific structures:

- **DALL·E 2:** It is an advanced version of DALL·E 1 with enhanced image editing and variation capabilities, thereby increasing the resolution and realism of the generated images (Subramanian, 2025). DALL·E 2 is an artificial intelligence system that can convert something described in natural language into realistic visuals and artistic works (OPEN AI, 2022).

- **DALL·E 3:** In addition to DALL·E 2, it is a model that can process much more nuance and detail and create images that are remarkably close to reality (OPEN AI, 2023).

- **VQ-Video Diffusion Model (VQ-VDM):** VQ-VDM is a hybrid model that combines two different technologies developed for video generation: vector quantization and DMs. This model aims to eliminate computational slowness while enhancing video pixels (Ho et al., 2022). In the first stage of the two-stage model, the VQGAN encoder/decoder is trained, and in the second stage, the VQGAN decoder utilizes the latent space generated by the DM to create the final video (Kaji & Yanai, 2024).

- **Midjourney:** Midjourney, released alongside DALL·E and Stable Diffusion GenAI, is an exciting artificial intelligence program that generates original images based on text descriptions. It enables users to convert both realistic text and abstract styles into images and features an interactive bot that uses machine learning to create text-based images (Wasielewski, 2023).

- **Stable Diffusion:** Another model that excels at generating high-quality images based on text prompts is Stable Diffusion. This model demonstrates success in both semantic matching and feature extraction (Rombach et al., 2022). Using the diffusion-denoising mechanism, this model is also suitable for straightforward tuning techniques, allowing its image generation performance to be continuously improved (X. Li et al., 2024).

- **CLIP (Contrastive Language-Image Pretraining) Embeddings:** CLIP was designed to understand and classify images based on text descriptions. Bridging the gap between visual content and natural language enables more detailed image search and analysis (Subramanian, 2025).

- **Google Imagen:** Google Imagen is a text-to-image generation platform developed by Google that uses advanced machine learning techniques for image synthesis from textual descriptions (Wang et al., 2023). Powered by transformer models similar to those used in DALL·E or GPT, this model also utilizes attention mechanisms or GANs to enhance the realism and diversity of images (Jamal et al., 2024).

- **Amazon Titan Image Generator:** This model, developed by Amazon Web Services (AWS), first encodes textual commands entered by the user into mathematical vectors known as vector embeddings. Then, complex semantic concepts in the text are mapped to a latent space. Using the generated precise vector as a condition, the model is directed to synthesize a compatible image corresponding to that point in the semantic space (Biswas et al., 2023). High-quality images generated with the help of the model are used to improve customer experiences on online sales platforms (Bhattacharjee, 2025).

- **GLIGEN:** GLIGEN is a text-to-image model that can guide existing DMs and control them in a synchronized manner (Y. Li et al., 2023). It works by adding a grounding layer to the generation process of a pre-trained large DM, such as Stable Diffusion.

4.2. Text-to-Video Models

→ **DMs for Videos:** Another GenAI-based generative paradigm is DMs. These models are probability-based models that gradually eliminate existing noise through a noise reduction model while generating signals (Dhariwal & Nichol, 2021). The coarse-to-fine nature of these models gradually reveals the correlation between video and text, enabling them to perform well in cross-modal retrieval tasks (Jin et al., 2023).

→ **Variational AutoEncoders (VAEs) for Videos:** Variational AutoEncoders (VAEs) are a core model that works to compress video pixel data into a low-dimensional latent space and play an essential role in latent video generation models (Wu et al., 2025). VAEs, a popular class of generative models, combine data with a hidden vector sampled from a variational distribution, typically modeled as a Gaussian distribution (Xi et al., 2024).

- **CogVideoX:** The CogVideoX model was developed by Yang et al. (2025a) as a solution to the issues of text-based sustainability consistency and limited mobility in short videos encountered in video generation models. It is an enhanced version of image models such as CogView3 and CogVLM (Zheng et al., 2024). This model is based on a diffusion transformer and can generate 10-second

continuous videos consistent with text commands, as well as videos with a frame rate of 16 fps and a resolution of 768×1360 pixels (Yang et al., 2025a).

- **VideoVAE:** VideoVAE, a type of Latent Video DM (LVDM), can help reduce the training costs of video DMs while also improving the final quality of the generated videos (Xing et al., 2024). Furthermore, a well-trained VideoVAE provides a spatial and temporal domain for latent video generation models, unlike frame sampling, and exhibits low reconstruction errors (Yang et al., 2025b).

- **CV-VAE:** CV-VAE (Compatible Video VAE) is a text-to-video model that can adapt a VAE's latent space to be directly compatible with a more common image generator model, such as Stable Diffusion (S. Zhao et al., 2024). This model reduces generation time while utilizing the latent space to prevent the drift of the latent space distribution (Wu et al., 2025).

- **MoCoGAN** (Motion and Content Decomposed GAN): The visual signals in a video consist of two dimensions: motion and content. As a customized GAN-based model, MoCoGAN utilizes these two dimensions for video generation. Within the model, a series of random vectors is mapped to a video to generate images (Tulyakov et al., 2018). Thus, while the content part is kept constant in the model, the motion part is implemented as a stochastic (time- or context-dependent) process (Tran et al., 2020).

5. Pros and Cons of GenAI Visualization

Although AI-generated images are now being widely used in various industries, it is also recognized that they have both advantages and disadvantages. These advantages and disadvantages are detailed with examples in the context of multiple sectors.

5.1. Pros

The use of AI technologies in image generation has increased efficiency and innovation in visual generation across various industries (Есимова & Шевякова, 2024). In particular, methods such as deep learning, CNN, and GAN have enhanced image processing capabilities. These capabilities have been addressed in various industries as follows.

→**Healthcare:** GenAI technologies enable the creation of personalized treatment strategies and improved patient prognoses by enhancing the analysis of large datasets of medical images (Saravanan et al., 2024). The use

of AI-assisted imaging has increased the accuracy of diagnostic processes in healthcare. Furthermore, GenAI-based technologies have made it possible to visualize existing diagnoses more clearly (Dodiya et al., 2025).

→**Manufacturing and Quality Control:** AI-generated images and the underlying algorithmic technology are utilized to provide clearer visibility of defects arising in generation processes (Peker et al., 2023). These images also offer benefits in reducing costs incurred in generation processes and increasing generation efficiency (Malik et al., 2024).

→**Entertainment and Media:** Creative and realistic GenAI images have brought about a dizzying change in the entertainment industry and made it possible to generate high-quality digital images (Dodiya et al., 2025). This artistic transformation in digital media has contributed to the creation of image content that enhances aesthetic satisfaction (Nain et al., 2024).

→**Security and Surveillance:** The technology that contributes to the development of GenAI images also leads to the development of machines that enable facial recognition and real-time tracking (Dodiya et al., 2025). GenAI image processing also enhances security in various applications by improving object and area recognition (Nain et al., 2024).

→**Environmental Sustainability and Monitored Agriculture:** Thanks to the analysis of satellite images using GenAI technologies, the effects of ecological changes can be observed in real time (Saravanan et al., 2024). Furthermore, big data-based analyses enable more sustainable farming practices and effective crop management processes (Almanasra, 2024).

5.2. Cons

While AI technologies offer significant benefits to various industries, they also present specific challenges that need to be addressed. These challenges, such as data bias, algorithmic transparency, and ethical issues, transcend industrial boundaries (Prajapati et al., 2022). Hence, this study classifies the disadvantages in question within the context of the subject as follows.

→Technical Limitations and Risks

- **Misinformation and Data Falsification:** GenAI technologies can generate falsified data, particularly in open-ended queries aimed at scientific research. A study conducted with real professionals showed that it is challenging to distinguish the authenticity of hybrid images created using GenAI technology alongside authentic images (Zecca et al., 2023).

- **Misuse of Personal Data:** The risks stem from GenAI technologies generating results based on big data and the inclusion of personal data (name, address, etc.) in the big data structure (Zlateva et al., 2024).

→Ethical and Social Challenges

- **Ethical Concerns:** AI-generated images and videos contain biases and harmful perspectives (Feher, 2025), and the lack of ethical-regulatory frameworks currently in place is insufficient to mitigate these risks (Avey, 2023).

- **Privacy and Security Risks:** GenAI visual content may violate personal security or privacy procedures by creating unauthorized or misleading content. This can lead to the dissemination of disinformation in the public sphere (Zlateva et al., 2024).

- **Biases:** Bias in GenAI models refers to systematic errors or distortions in the model's information processing, leading to incorrect assumptions based on learned patterns (Mehrabi et al., 2021). These biases involve cultural, racial, religious, class-based, disability-based, dialect-based and polarization biases (Bird et al., 2023; Wei et al., 2025).

→Economic and Labor Market Implications

- **Job Displacement and Economic Shifts:** GenAI technologies have the potential to negatively impact the employment levels of workers involved in visual generation (Walkowiak & Potts, 2024). This situation could reduce the need for workers in related sectors, leading to a long-term increase in unemployment figures.

- **Intellectual Property Issues:** There are significant concerns regarding intellectual property rights. When AI generates images, particularly when the output is based on existing works, questions arise regarding ownership and copyright (Walkowiak & Potts, 2024).

→Regulatory and Legislative Challenges

- **Lack of Regulations:** Existing regulations are insufficient to limit the use of GenAI. The lack of a fully defined legal framework hinders the control of GenAI usage in terms of preventing misuse and authenticating content (Zlateva et al., 2024).

- **Mitigation Strategies:** Gaps in the ethical and legal framework and the absence of clear boundaries in the adoption of related technologies necessitate the mitigation of risks through technology. To this end, it is essential to use the capabilities of artificial intelligence for the right purposes and to authenticate the applications with a clear identity (Thomson et al., 2024).

→ **Misleading Journalism and Media:** The proliferation of AI-generated images in digital forums has sparked debates in the media regarding legal and ethical issues, such as misinformation risks and copyright protocols for the data underlying generative models (Feher, 2025; Zlateva et al., 2024). Thomson et al. (2024) summarize the potential risks in the media as audience manipulation, objectivity issues, claims of reliable reality, visual mis/disinformation, fake curation, non-policiness, GenAI automation, and ethical violations.

→ **Deepfake Technology and Manipulation:** Deepfake is fake audio and visual content created with the help of modern AI technologies (Westerlund, 2019). The use of this content causes several common problems and threats, in addition to the specific problems detailed below (Chawla, 2019; Westerlund, 2019; Есимова & Шевякова, 2024):

- Fake image generation and credibility
- Misinformation and manipulation
- Threat to social security
- Threat to information security
- Privacy violations
- Reputation damage
- Fraud and extortion
- Unauthorized content
- Distortion of reality perception

The root of the problems is the generation of fake images that cause harm to individuals or institutions, along with the associated legal and social repercussions.

6. What Future Brings? Core Insights from AI

GenAI for visualization is expected to gain importance across all sectors besides academia. Table 2 presents projections for the future of GenAI Visual Content across six different dimensions.

Table 2. The Future of AI-Generated Visual Content

Dimension	Future Trend	Academic Reasoning	Potential Opportunities & Trends
Technological advancements	Transition to fundamental models capable of simulating three-dimensional space and time (4D) in an integrated manner.	This evolution is the natural outcome of artificial intelligence’s “predictive coding” and “supervised learning” paradigms. The weaknesses of current models, such as object persistence, can only be overcome by approaches that internalize the rules of the physical world.	Opportunities: Creating instant, consistent, and interactive virtual worlds; revolutionary tools for scientific simulations and prototyping; physically accurate, realistic cinematic content. Risks: Excessive computing power and energy requirements; the indistinguishability of reality and simulation; increasingly difficult-to-control complex models.
Creativity and Aesthetic Dimension	The human role will evolve from being directly creative to that of a “curator” or “orchestra conductor” who provides vision to artificial intelligence.	The trend supports the combination of “human-computer interaction” and “cognitive collaboration.” Progress is made toward closing the gap between “idea generation” and “implementation.”	Opportunities: Democratization of high-quality content generation, new visual languages and art movements, and acceleration of creative processes leading to an enhanced artistic experience. Risks: Aesthetic homogenization; erosion of traditional artistic skills; erosion of the concepts of artistic originality and authorship.
Economic and Industrial Impacts	Scalable Hyper-Personalization: The generation of tailored content in real time. From “mass communication” to “individual communication”.	Once a model is trained, the generation cost of each additional personalized output is nearly zero. The “experience economy” and “data-driven marketing” will become even more integrated.	Opportunities: High ROI in marketing, personalized entertainment experiences, and significant productivity gains in the creative sector. Risks: Workforce loss in many creative professions, market monopolization by a few tech giants, and a decline in content quality.
Ethical and Social Debates	Debates will evolve from isolated “deepfake” incidents into an “epistemic security” crisis that shakes the fundamental trust in the authenticity of all digital media.	Cultivation theory and trust studies explain how constant exposure to synthetic content can shape perceptions of social reality. This points to the collapse of public discourse and the common ground of reality.	Opportunities: Development of standards to verify the source and authenticity of digital content. The growing importance of critical thinking and media literacy skills in society. Risks: Mass disinformation interfering with elections; increased blackmail, character assassination, and fraud; deepening social polarization and distrust.

Regulatory and Legal Aspects	Source and Accountability-Focused Regulations: The legal framework is shifting towards global regulations that mandate mechanisms for “provenance,” “accountability,” and “consent” for data.	Legal systems evolve to manage the societal harm created by new technologies. Just as in fields such as engineering or medicine, the potential societal harms of GenAI necessitate a public safety-focused “responsibility law” framework.	Opportunities: International standards for responsible AI; protection of users and data rights; improvement of the investment environment as legal uncertainty decreases. Risks: Regulatory differences are slowing down innovation; excessive regulation is hindering the development of open-source AI; malicious actors are exploiting legal loopholes.
Long-Term Evolution (10-20 Years Later)	Direct Thought-to-Visual Synthesis with Neural Interfaces: The convergence of generative artificial intelligence with Brain-Computer Interface. Conversion of human thoughts into visual and auditory media.	Vision is based on the parallelism between the human brain and artificial intelligence in terms of how they represent concepts. This similarity points to the potential convergence of computational neuroscience and artificial intelligence in the field of “representation learning.”	Opportunities: New forms in art and communication, medical breakthroughs for paralyzed patients, advances in consciousness and dream research. Risks: Unauthorized reading of thoughts, existential crises concerning identity and consciousness, risk of thought manipulation.

Table 1 interprets the transformation that GenAI will undergo as a socio-technical innovation process rather than merely a technological advancement. This interpretation is consistent with Bojić’s (2024) prediction. This suggests that a digital paradigm shift is underway in the economy, driven by advanced technologies capable of simulating the real world. This view provides a scientific basis for Miikkulainen’s (2024) assumptions, which claim that traditional methods for developing, evaluating, understanding, and applying artificial intelligence systems are no longer valid and that the existing paradigm has shifted. One of the most important consequences of this paradigm shift is that hyper-personalization will take center stage.

Therefore, as predicted by De Silva et al. (2025) and Walch (2024), it can be anticipated that a process different from more primitive forms of personalization, such as using the customer’s name in emails or segmenting users based on their demographic characteristics, will be employed. This approach suggests that more advanced AI-powered pattern recognition technologies, based on large data sets,

could deliver contextually relevant results tailored to individual preferences and behaviors.

Therefore, with the use of more advanced models based on machine learning and deep learning, it may be possible to deliver more personalized results to individuals more quickly and smoothly. This also applies to the creation of creative visual content (Heigl, 2025). Depending on the pace of technological development, it is anticipated that the weight of automation will increase, resulting in a fundamental transformation of the workforce. This view is consistent with the hyper-automation prediction emphasized by De Silva et al. (2025) and Kaswan et al. (2025).

The most striking projection in the table is the diminishing effect of AI-generated visualization on social trust mechanisms. Echoing this view, Huynh & Aichner (2025) evaluate the social dynamics of trust, a characteristically human emotion, as it pertains to the domain of artificial intelligence. Technology's ability to blur the lines between real and synthetic images could trigger a mass information security crisis that goes beyond Deepfake. The existence of this crisis potential, as supported by Leslie & Perini (2024), necessitates that GenAI developers collaborate with experts from various disciplines, particularly policymakers. Indeed, short-sighted predictions and misuse of technologies developed based on GenAI are likely to lead to destructive consequences.

7. Conclusion

This study aims to comprehensively examine the visuals and videos generated through GenAI in all their dimensions. To achieve this objective, the relevant technologies are detailed in this study, both in terms of their underlying technologies and their potential pros and cons. Inferences from the literature indicate that GenAI technologies have fundamentally transformed content generation processes in media, communication, and the visual arts, democratizing creativity and significantly increasing industrial productivity. These technologies have the potential to offer innovative solutions ranging from generation and quality control to personalized healthcare services, sustainable agricultural practices, and security and surveillance services.

The proliferation of GenAI-based visualization also brings serious challenges. Among these issues are biased data, the misuse of existing personal data, uncertainties regarding intellectual property rights, and the spread of disinformation through technologies such as Deepfake. The inadequacy of current legal and ethical frameworks to regulate this rapid technological development increases risks and undermines social trust.

The anticipated future of technology also blurs the line between human creativity and reality. In a scenario where interfaces disappear and thoughts can be visually generated; humanity's perception of imagination and reality may ultimately confront its own existential limits. In this context, future studies could address the socio-technical impacts of GenAI and their economic consequences using an interdisciplinary approach, thereby developing effective innovation strategies that minimize potential risks. This study aims to provide a solid foundation for both academic research and policymakers.

References

- Alaniz, S., Hummel, T., & Akata, Z. (2022). Semantic Image Synthesis with Semantically Coupled VQ-Model (No. arXiv:2209.02536). arXiv. <https://doi.org/10.48550/arXiv.2209.02536>
- Almanasra, S. (2024). Applications of integrating artificial intelligence and big data: A comprehensive analysis. *Journal of Intelligent Systems*, 33(1). <https://doi.org/10.1515/jisys-2024-0237>
- Arya, R., Joshi, D., Sharma, K., Bhakuni, V. S., Vats, S., & Sharma, V. (2024). Stacked Generative Adversarial Networks (StackGAN) Text-to-Image Generator. 2024 IEEE 3rd World Conference on Applied Intelligence and Computing (AIC), 1095–1101. <https://doi.org/10.1109/AIC61668.2024.10730994>
- Avey, C. (2023, December 27). Ethical Pros and Cons of AI Image Generation. IEEE Computer Society. <https://www.computer.org/publications/tech-news/community-voices/ethics-of-ai-image-generation/>
- Bhattacharjee, A. (2025). Overview of Image Capabilities. In A. Bhattacharjee (Ed.), *A Practical Guide to Generative AI Using Amazon Bedrock: Building, Deploying, and Securing Generative AI Applications* (pp. 413–433). Apress. https://doi.org/10.1007/979-8-8688-1414-3_18
- Bird, C., Ungless, E., & Kasirzadeh, A. (2023). Typology of Risks of Generative Text-to-Image Models. *Proceedings of the 2023 AAAI/ACM Conference on AI, Ethics, and Society*, 396–410. <https://doi.org/10.1145/3600211.3604722>
- Biswas, A., Belval, E., & Reddi, L. (2023, November 21). Amazon Textract's new Layout feature introduces efficiencies in general purpose and generative AI document processing tasks. Amazon Web Service (AWS) Blogs. <https://aws.amazon.com/tr/blogs/machine-learning/amazon-textracts-new-layout-feature-introduces-efficiencies-in-general-purpose-and-generative-ai-document-processing-tasks/>

Bojić, L. M. (2024). Exploring the Socio-Technical Imaginary of Artificial General Intelligence in The Bard Large Language Model: A Narrative Analysis on Perspectives and Dialectics. *Issues in Ethnology and Anthropology* (Етноантрополошки Проблеми), 19(2), 657–694. <https://doi.org/10.21301/eap.v19i2.14>

Brock, A., Donahue, J., & Simonyan, K. (2019). Large Scale GAN Training for High Fidelity Natural Image Synthesis (No. arXiv:1809.11096). arXiv. <https://doi.org/10.48550/arXiv.1809.11096>

Celard, P., Seara Vieira, A., Sorribes-Fdez, J. M., Iglesias, E. L., & Borrajo, L. (2024). Temporal Development GAN (TD-GAN): Crafting More Accurate Image Sequences of Biological Development. *Information*, 15(1), 12. <https://doi.org/10.3390/info15010012>

Chadha, A., Kumar, V., Kashyap, S., & Gupta, M. (2021). Deepfake: An Overview. In P. K. Singh, S. T. Wierchoń, S. Tanwar, M. Ganzha, & J. J. P. C. Rodrigues (Eds.), *Proceedings of Second International Conference on Computing, Communications, and Cyber-Security* (pp. 557–566). Springer. https://doi.org/10.1007/978-981-16-0733-2_39

Chawla, R. (2019). Deepfakes: How a pervert shook the world. *International Journal for Advance Research and Development*, 4(6), 4-8.. <https://www.semanticscholar.org/paper/Deepfakes-0%3A-How-a-pervert-shook-the-world-Chawla/c3b3a6d27dbbfed4df630b39fc0a8a6692b1828a>

Chen, J., Konrad, J., & Ishwar, P. (2018). VGAN-Based Image Representation Learning for Privacy-Preserving Facial Expression Recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition workshops* (pp. 1570-1579). https://openaccess.thecvf.com/content_cvpr_2018_workshops/w32/html/Chen_VGAN-Based_Image_Representation_CVPR_2018_paper.html

Chen, W., Sun, Y., Rosin, P. L., & Lai, Y. (2025). Stacked deep fusion GAN for enhanced text-to-image generation. *The Visual Computer*, 41(11), 8947–8960. <https://doi.org/10.1007/s00371-025-03908-7>

Croitoru, F.-A., Hondru, V., Ionescu, R. T., & Shah, M. (2023). Diffusion Models in Vision: A Survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(9), 10850–10869. <https://doi.org/10.1109/TPAMI.2023.3261988>

De Silva, D., Mills, N., Moraliyage, H., Rathnayaka, P., Wishart, S., & Jennings, A. (2025). Responsible Artificial Intelligence Hyper-Automation with Generative AI Agents for Sustainable Cities of the Future. *Smart Cities*, 8(1), 34. <https://doi.org/10.3390/smartcities8010034>

Dhariwal, P., & Nichol, A. Q. (2021, November 9). Diffusion Models Beat GANs on Image Synthesis. *Advances in Neural Information Processing Systems*. <https://openreview.net/forum?id=AAWuCvzaVt>

Ding, M., Yang, Z., Hong, W., Zheng, W., Zhou, C., Yin, D., Lin, J., Zou, X., Shao, Z., Yang, H., & Tang, J. (2021). CogView: Mastering Text-to-Image Generation via Transformers. *Advances in Neural Information Processing Systems*, 34, 19822–19835. <https://proceedings.neurips.cc/paper/2021/hash/a4d92e2cd541fca87e4620aba658316d-Abstract.html>

Dodiya, K. R., Kumar, K., Thakar, A., Pithiya, G., Mungra, K., Topiya, P., Dodiya, K. R., Kumar, K., Thakar, A., Pithiya, G., Mungra, K., & Topiya, P. (2025). Unleashing the Power of AI: Exploring the Transformative Landscape of Image Analysis. In *Utilizing AI and Machine Learning in Financial Analysis (unleashing-the-power-of-ai)* (pp. 403–426). IGI Global Scientific Publishing. <https://doi.org/10.4018/979-8-3693-8507-4.ch022>

Feher, K. (2025). *Generative AI, Media, and Society*. Routledge. <https://doi.org/10.4324/9781003591023>

GIGAZINE. (2021, January 6). AI “DALL E” that automatically generates illustrations and photos from words such as “Pikachu riding a motorcycle” and “Avocado chair.” https://gigazine.net/gsc_news/en/20210106-openai-dall-e/

Grand View Research. (2025). *AI In Media & Entertainment Market Size, Share & Trends Analysis Report By Solution (Hardware/ Equipment, Services), By Application (Gaming, Fake Story Detection), By Region, And Segment Forecasts, 2025—2030*. <https://www.grandviewresearch.com/industry-analysis/artificial-intelligence-ai-media-entertainment-market-report>

Guarnera, L., Giudice, O., & Battiato, S. (2024). Level Up the Deepfake Detection: A Method to Effectively Discriminate Images Generated by GAN Architectures and Diffusion Models. In K. Arai (Ed.), *Intelligent Systems and Applications* (pp. 615–625). Springer Nature Switzerland. https://doi.org/10.1007/978-3-031-66431-1_43

Gulsoy, M., Kokach, V., Kocaçınar, B., & Akbulut, F. P. (2024). AI-Driven Contextual Story Creation with Integrated Text and Visual Generation. 2024 *Innovations in Intelligent Systems and Applications Conference (ASYU)*, 1–6. <https://doi.org/10.1109/ASYU62119.2024.10757014>

Heigl, R. (2025). Generative artificial intelligence in creative contexts: A systematic review and future research agenda. *Management Review Quarterly*. <https://doi.org/10.1007/s11301-025-00494-9>

Hinton, G. E., & Salakhutdinov, R. R. (2006). Reducing the Dimensionality of Data with Neural Networks. *Science*, 313, 504–507. <https://doi.org/10.1126/science.1127647>

Ho, J., Salimans, T., Gritsenko, A., Chan, W., Norouzi, M., & Fleet, D. J. (2022). Video Diffusion Models (No. arXiv:2204.03458). arXiv. <https://doi.org/10.48550/arXiv.2204.03458>

Hong, J.-W., & Curran, N. M. (2019). Artificial Intelligence, Artists, and Art: Attitudes Toward Artwork Produced by Humans vs. Artificial Intelligence. *ACM Trans. Multimedia Comput. Commun. Appl.*, 15(2s), 58:1-58:16. <https://doi.org/10.1145/3326337>

Hu, Q., Zhang, G., Qin, Z., Cai, Y., Yu, G., & Li, G. Y. (2023). Robust Semantic Communications With Masked VQ-VAE Enabled Codebook. *IEEE Transactions on Wireless Communications*, 22(12), 8707–8722. <https://doi.org/10.1109/TWC.2023.3265201>

Huynh, M.-T., & Aichner, T. (2025). In generative artificial intelligence we trust: Unpacking determinants and outcomes for cognitive trust. *AI & SOCIETY*, 1–21.

Jabbar, A., Li, X., Assam, M., Khan, J. A., Obayya, M., Alkhonaini, M. A., Al-Wesabi, F. N., & Assad, M. (2022). AFD-StackGAN: Automatic Mask Generation Network for Face De-Occlusion Using StackGAN. *Sensors*, 22(5), 1747. <https://doi.org/10.3390/s22051747>

Jamal, S., Wimmer, H., & Rebman, C. M. (2024). Perception and evaluation of text-to-image generative AI models: A comparative study of DALL-E, Google Imagen, GROK, and Stable Diffusion. *Issues in Information Systems*, 25(2), 277–292. http://dx.doi.org/10.48009/2_iis_2024_123

Jin, P., Li, H., Cheng, Z., Li, K., Ji, X., Liu, C., Yuan, L., & Chen, J. (2023). DiffusionRet: Generative Text-Video Retrieval with Diffusion Model. 2470–2481. https://openaccess.thecvf.com/content/ICCV2023/html/Jin_DiffusionRet_Generative_Text-Video_Retrieval_with_Diffusion_Model_ICCV_2023_paper.html

Kaji, R., & Yanai, K. (2024). VQ-VDM: Video Diffusion Models with 3D VQGAN. *Proceedings of the 5th ACM International Conference on Multimedia in Asia*, 1–5. <https://doi.org/10.1145/3595916.3626363>

Kalantzis, M., & Cope, B. (2025). Literacy in the Time of Artificial Intelligence. *Reading Research Quarterly*, 60(1), e591. <https://doi.org/10.1002/rrq.591>

Kamat, S. (2025, April 4). How To Use GAN To Generate Images. *Algoscale*. <https://algoscale.com/blog/how-to-use-gan-to-generate-images/>

Kaswan, K. S., Dhatteval, J. S., Malik, V., & Rajani. (2025). Hyper Automation 2.0 and Ecosystem Collaboration: Paradigm Shift in SCM. In A. Pandey & F. Al-Turjman (Eds.), *Transformation of Supply Chain Ecosystems: Technological Innovations and Collaborations* (p. 0). Emerald Publishing Limited. <https://doi.org/10.1108/978-1-83549-246-820251017>

Kingma, D. P., & Welling, M. (2022). Auto-Encoding Variational Bayes (No. arXiv:1312.6114). arXiv. <https://doi.org/10.48550/arXiv.1312.6114>

Laba, N. (2024). Engine for the imagination? Visual generative media and the issue of representation. *Media, Culture & Society*, 46(8), 1599–1620. <https://doi.org/10.1177/01634437241259950>

Leslie, D., & Perini, A. M. (2024). Future Shock: Generative AI and the International AI Policy and Governance Crisis. *Harvard Data Science Review*, Special Issue 5. <https://doi.org/10.1162/99608f92.88b4cc98>

Li, X., Lu, J., Han, K., & Prisacariu, V. A. (2024). SD4Match: Learning to Prompt Stable Diffusion Model for Semantic Matching. 27558–27568. https://openaccess.thecvf.com/content/CVPR2024/html/Li_SD4Match_Learning_to_Prompt_Stable_Diffusion_Model_for_Semantic_Matching_CVPR_2024_paper.html

Li, Y., Liu, H., Wu, Q., Mu, F., Yang, J., Gao, J., Li, C., & Lee, Y. J. (2023). GLIGEN: Open-Set Grounded Text-to-Image Generation (No. arXiv:2301.07093). <https://doi.org/10.48550/arXiv.2301.07093>

Lim, W. M., Gunasekara, A., Pallant, J. L., Pallant, J. I., & Pechenkina, E. (2023). Generative AI and the future of education: Ragnarök or reformation? A paradoxical perspective from management educators. *The International Journal of Management Education*, 21(2), 100790. <https://doi.org/10.1016/j.ijme.2023.100790>

Lyu, Y., Lin, C.-L., Lin, P.-H., & Lin, R. (2021). The Cognition of Audience to Artistic Style Transfer. *Applied Sciences*, 11(7), 3290. <https://doi.org/10.3390/app11073290>

Lyu, Y., Wang, X., Lin, R., & Wu, J. (2022). Communication in Human–AI Co-Creation: Perceptual Analysis of Paintings Generated by Text-to-Image System. *Applied Sciences*, 12(22), 11312. <https://doi.org/10.3390/app122211312>

Malik, S., Muhammad, K., & Waheed, Y. (2024). Artificial intelligence and industrial applications-A revolution in modern industries. *Ain Shams Engineering Journal*, 15(9), 102886. <https://doi.org/10.1016/j.asej.2024.102886>

Mehrabi, N., Morstatter, F., Saxena, N., Lerman, K., & Galstyan, A. (2021). A Survey on Bias and Fairness in Machine Learning. *ACM Comput. Surv.*, 54(6), 115:1–115:35. <https://doi.org/10.1145/3457607>

Miikkulainen, R. (2024). Generative AI: An AI paradigm shift in the making? *AI Magazine*, 45(1), 165–167. <https://doi.org/10.1002/aaai.12155>

Mogren, O. (2016). C-RNN-GAN: Continuous recurrent neural networks with adversarial training (No. arXiv:1611.09904). <https://doi.org/10.48550/arXiv.1611.09904>

Nain, V., Shyam, H. S., Kumar, N., Tripathi, P., & Rai, M. (2024). A Study on Object Detection Using Artificial Intelligence and Image Processing–Based Methods. In *Mathematical Models Using Artificial Intelligence for Surveillance Systems* (pp. 121–148). John Wiley & Sons, Ltd. <https://doi.org/10.1002/9781394200733.ch6>

Naveen, S., Ram Kiran, M. S. S., Indupriya, M., Manikanta, T. V., & Sudeep, P. V. (2021). Transformer models for enhancing AttnGAN based text to image generation. *Image and Vision Computing*, 115, 104284. <https://doi.org/10.1016/j.imavis.2021.104284>

Oord, A. van den, Vinyals, O., & Kavukcuoglu, K. (2018). Neural Discrete Representation Learning (No. arXiv:1711.00937). arXiv. <https://doi.org/10.48550/arXiv.1711.00937>

OPEN AI. (2022, September 28). DALL·E 2 Launching. <https://openai.com/tr-TR/index/dall-e-2/>

OPEN AI. (2023, September 1). DALL·E 3 Launching. <https://openai.com/tr-TR/index/dall-e-3/>

Park, H., Eirich, J., Luckow, A., & Sedlmair, M. (2024). “We Are Visual Thinkers, Not Verbal Thinkers!”: A Thematic Analysis of How Professional Designers Use Generative AI Image Generation Tools. *Proceedings of the 13th Nordic Conference on Human-Computer Interaction*, 1–14. <https://doi.org/10.1145/3679318.3685370>

Peker, K., Yıldız, M., & Turgay, S. (2023). Improving Quality Inspections with Image Analysis and Artificial Intelligence. *Accounting and Corporate Management*, 5(11), 135–146. <https://doi.org/10.23977/acccm.2023.051120>

Prajapati, D. K., Upadhayay, D., Kumawat, A., & Shekhawat, A. P. (2022). Application of AI Computer Vision and Image Recognition. *Industrial Engineering Journal*, 51(10), 81–87. http://www.journal-iiie-india.com/1_jan-dec_22/7_oct.pdf

Praveen, D. R., Harshitha, G. M., Borkar, P. S., D’Souza, R., Shetty, K., & Murthy, A. (2025). Innovative AI Solutions for Multi-Modal Content Generation. *2025 International Conference on Artificial Intelligence and Data Engineering (AIDE)*, 678–685. <https://doi.org/10.1109/AIDE64228.2025.10987412>

Pu, Z., Cabrera, D., Li, C., & de Oliveira, J. V. (2022). VGAN: Generalizing MSE GAN and WGAN-GP for Robot Fault Diagnosis. *IEEE Intelligent Systems*, 37(3), 65–75. <https://doi.org/10.1109/MIS.2022.3168356>

Qiao, T., Zhang, J., Xu, D., & Tao, D. (2019). MirrorGAN: Learning Text-to-image Generation by Redescription (No. arXiv:1903.05854). <https://doi.org/10.48550/arXiv.1903.05854>

Radford, A., Kim, J. W., Hallacy, C., Ramesh, A., Goh, G., Agarwal, S., Sastry, G., Askell, A., Mishkin, P., Clark, J., Krueger, G., & Sutskever, I. (2021). Learning Transferable Visual Models From Natural Language Supervision (No. arXiv:2103.00020). arXiv. <https://doi.org/10.48550/arXiv.2103.00020>

Rais, K., Amroune, M., & Haouam, M. Y. (2024). Medical Image Generation Techniques for Data Augmentation: Disc-VAE versus GAN. 2024 6th International Conference on Pattern Analysis and Intelligent Systems (PAIS), 1–8. <https://doi.org/10.1109/PAIS62114.2024.10541221>

Ramesh, A., Pavlov, M., Goh, G., Gray, S., Voss, C., Radford, A., Chen, M., & Sutskever, I. (2021). Zero-Shot Text-to-Image Generation (No. arXiv:2102.12092). <https://doi.org/10.48550/arXiv.2102.12092>

Rombach, R., Blattmann, A., Lorenz, D., Esser, P., & Ommer, B. (2022). High-Resolution Image Synthesis with Latent Diffusion Models (No. arXiv:2112.10752). <https://doi.org/10.48550/arXiv.2112.10752>

Russell, A. (2022, August 22). How to use VQGAN+CLIP to generate images from a text prompt—A complete, non-technical tutorial. NightCafe. <https://medium.com/nightcafe-creator/vqgan-clip-tutorial-a411402cf3ad>

Saito, M., Matsumoto, E., & Saito, S. (2017). Temporal Generative Adversarial Nets with Singular Value Clipping (No. arXiv:1611.06624). <https://doi.org/10.48550/arXiv.1611.06624>

Saravanan, V., Adaikkammai, A., Sasikala, G., A, I., Babisha, A., & Latha, M. (2024). Advancements in Artificial Intelligence for Better Image Analysis, Recognition, and Interpretation in the Field of Image Processing. 2024 Global Conference on Communications and Information Technologies (GCCIT), 1–6. <https://doi.org/10.1109/GCCIT63234.2024.10862237>

Si, Z., & Bao, Q. (2025). Cross-Media Narrative Interaction Design for International Education with Generative AI: A Case Study of Dream of the Red Chamber. In C. Stephanidis, M. Antona, S. Ntoa, & G. Salvendy (Eds.), *HCI International 2025 Posters* (pp. 406–414). Springer Nature Switzerland. https://doi.org/10.1007/978-3-031-94153-5_40

Simon, J.-P. (2013). Digital Shift in the Media and Content Industries: A Quick Overview (pp. 53–62). Institute for Prospective Technological Studies

(IPTS) Joint Research Centre. <https://publications.jrc.ec.europa.eu/repository/handle/JRC77932>

Son, Y., Zhang, X., Yoon, Y., Cho, J., & Choi, S. (2023). LSTM–GAN based cloud movement prediction in satellite images for PV forecast. *Journal of Ambient Intelligence and Humanized Computing*, 14(9), 12373–12386. <https://doi.org/10.1007/s12652-022-04333-7>

Sordo, Z., Chagnon, E., Hu, Z., Donatelli, J. J., Andeer, P., Nico, P. S., Northen, T., & Ushizima, D. (2025). Synthetic Scientific Image Generation with VAE, GAN, and Diffusion Model Architectures. *Journal of Imaging*, 11(8), 252. <https://doi.org/10.3390/jimaging11080252>

Subramanian, S. (2025). *Mastering OpenAI for Enterprise: Unlock the Power of OpenAI to Build Intelligent Applications for Businesses with GPT, DALL-E, RAG, and AI Agents*. Orange Education Pvt Ltd.

Sun, Z., Zhang, H., Bai, J., Liu, M., & Hu, Z. (2023). A discriminatively deep fusion approach with improved conditional GAN (im-cGAN) for facial expression recognition. *Pattern Recognition*, 135, 109157. <https://doi.org/10.1016/j.patcog.2022.109157>

Takashi, O., & Jumpei, O. (2020). Bridging the Gap Between AI, Cognitive Science, and Narratology With Narrative Generation. IGI Global.

Tao, M., Tang, H., Wu, F., Jing, X.-Y., Bao, B.-K., & Xu, C. (2022). DF-GAN: A Simple and Effective Baseline for Text-to-Image Synthesis (No. arXiv:2008.05865). arXiv. <https://doi.org/10.48550/arXiv.2008.05865>

Tatar, K., Pasquier, P., & Siu, R. (2018). REVIVE: An Audio-visual Performance with Musical and Visual AI Agents. *Extended Abstracts of the 2018 CHI Conference on Human Factors in Computing Systems*, 1–6. <https://doi.org/10.1145/3170427.3177771>

Thomson, T. J., Thomas, R. J., & Matich, P. (2024). Generative Visual AI in News Organizations: Challenges, Opportunities, Perceptions, and Policies. *Digital Journalism*, 0(0), 1–22. <https://doi.org/10.1080/21670811.2024.2331769>

Tran, T.-H., Bach, V.-D., & Doan, H.-G. (2020). vi-MoCoGAN: A Variant of MoCoGAN for Video Generation of Human Hand Gestures Under Different Viewpoints. In M. Cree, F. Huang, J. Yuan, & W. Q. Yan (Eds.), *Pattern Recognition* (pp. 110–123). Springer. https://doi.org/10.1007/978-981-15-3651-9_11

Tsue, T., Sen, S., & Li, J. (2020). Cycle Text-To-Image GAN with BERT (No. arXiv:2003.12137). <https://doi.org/10.48550/arXiv.2003.12137>

Tulyakov, S., Liu, M.-Y., Yang, X., & Kautz, J. (2018). MoCoGAN: Decomposing Motion and Content for Video Generation. 1526–1535. <https://doi.org/10.1112/ijcv.12137>

openaccess.thecvf.com/content_cvpr_2018/html/Tulyakov_MoCoGAN_Decomposing_Motion_CVPR_2018_paper.html

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, L., & Polosukhin, I. (2023). Attention Is All You Need (No. arXiv:1706.03762). arXiv. <https://doi.org/10.48550/arXiv.1706.03762>

Walch, K. (2024, July 15). How Generative AI Is Driving Hyperpersonalization. Forbes Online. <https://www.forbes.com/sites/kathleenwalch/2024/07/15/how-generative-ai-is-driving-hyperpersonalization/>

Walkowiak, E., & Potts, J. (2024). Generative AI, Work and Risks in Cultural and Creative Industries (SSRN Scholarly Paper No. 4830265). Social Science Research Network. <https://doi.org/10.2139/ssrn.4830265>

Wang, R. (2022). Computer-Aided Interaction of Visual Communication Technology and Art in New Media Scenes. *Computer-Aided Design & Applications*, 19(3), 75–84. [https://cad-journal.net/files/vol_19/CAD_19\(S3\)_2022_75-84.pdf](https://cad-journal.net/files/vol_19/CAD_19(S3)_2022_75-84.pdf)

Wang, S., Saharia, C., Montgomery, C., Pont-Tuset, J., Noy, S., Pellegrini, S., Onoe, Y., Laszlo, S., Fleet, D. J., Soricut, R., Baldridge, J., Norouzi, M., Anderson, P., & Chan, W. (2023). Imagen Editor and EditBench: Advancing and Evaluating Text-Guided Image Inpainting (No. arXiv:2212.06909). arXiv. <https://doi.org/10.48550/arXiv.2212.06909>

Wang, X., Zhang, S., Yuan, H., Qing, Z., Gong, B., Zhang, Y., Shen, Y., Gao, C., & Sang, N. (2024). A Recipe for Scaling up Text-to-Video Generation with Text-free Videos. 6572–6582. https://openaccess.thecvf.com/content/CVPR2024/html/Wang_A_Recipe_for_Scaling_up_Text-to-Video_Generation_with_Text-free_Videos_CVPR_2024_paper.html

Wasielowski, A. (2023). “Midjourney Can’t Count”: Questions of Representation and Meaning for Text-to-Image Generators. *The Interdisciplinary Journal of Image Sciences*, 37(1), 71–82. <https://doi.org/10.1453/1614-0885-1-2023-15454>

Wei, X., Kumar, N., & Zhang, H. (2025). Addressing bias in generative AI: Challenges and research opportunities in information management. *Information & Management*, 62(2), 104103. <https://doi.org/10.1016/j.im.2025.104103>

Westerlund, M. (2019). The Emergence of Deepfake Technology: A Review. *Technology Innovation Management Review*, 9(11), 40–53. <https://doi.org/10.22215/timreview/1282>

Wu, P., Zhu, K., Liu, Y., Zhao, L., Zhai, W., Cao, Y., & Zha, Z.-J. (2025). Improved Video VAE for Latent Video Diffusion Model. 18124–18133. <https://doi.org/10.48550/arXiv.2411.06449>

Wu, Y., Mou, Y., Li, Z., & Xu, K. (2020). Investigating American and Chinese Subjects' explicit and implicit perceptions of AI-Generated artistic work. *Computers in Human Behavior*, 104, 106186. <https://doi.org/10.1016/j.chb.2019.106186>

Xi, Q., Wang, F., Tao, L., Zhang, H., Jiang, X., & Wu, J. (2024). CM-AVAE: Cross-Modal Adversarial Variational Autoencoder for Visual-to-Tactile Data Generation. *IEEE Robotics and Automation Letters*, 9(6), 5214–5221. <https://doi.org/10.1109/LRA.2024.3387146>

Xing, Y., Fei, Y., He, Y., Chen, J., Xie, J., Chi, X., & Chen, Q. (2024). Large Motion Video Autoencoding with Cross-modal Video VAE (No. arXiv:2412.17805). arXiv. <https://doi.org/10.48550/arXiv.2412.17805>

Xu, T., Zhang, P., Huang, Q., Zhang, H., Gan, Z., Huang, X., & He, X. (2018). AttnGAN: Fine-Grained Text to Image Generation With Attentional Generative Adversarial Networks. 1316–1324. https://openaccess.thecvf.com/content_cvpr_2018/html/Xu_AttnGAN_Fine-Grained_Text_CVPR_2018_paper.html

Yang, Z., Teng, J., Zheng, W., Ding, M., Huang, S., Xu, J., Yang, Y., Hong, W., Zhang, X., Feng, G., Yin, D., Zhang, Y., Wang, W., Cheng, Y., Xu, B., Gu, X., Dong, Y., & Tang, J. (2025a). CogVideoX: Text-to-Video Diffusion Models with An Expert Transformer (No. arXiv:2408.06072). arXiv. <https://doi.org/10.48550/arXiv.2408.06072>

Yang, Z., Teng, J., Zheng, W., Ding, M., Huang, S., Xu, J., Yang, Y., Hong, W., Zhang, X., Feng, G., Yin, D., Zhang, Y., Wang, W., Cheng, Y., Xu, B., Gu, X., Dong, Y., & Tang, J. (2025b). CogVideoX: Text-to-Video Diffusion Models with An Expert Transformer (No. arXiv:2408.06072). arXiv. <https://doi.org/10.48550/arXiv.2408.06072>

Yu, J., Xu, Y., Koh, J. Y., Luong, T., Baid, G., Wang, Z., Vasudevan, V., Ku, A., Yang, Y., Ayan, B. K., Hutchinson, B., Han, W., Parekh, Z., Li, X., Zhang, H., Baldridge, J., & Wu, Y. (2022). Scaling Autoregressive Models for Content-Rich Text-to-Image Generation (No. arXiv:2206.10789). arXiv. <https://doi.org/10.48550/arXiv.2206.10789>

Zecca, P. A., Marcella, R., Andrea, B., Marina, P., Marina, B., & Mario, R. (2023). The Dark Side of Artificial Intelligence: The Possible Risk of Falsifying Images for Scientific Articles. *Microscopy and Microanalysis*, 29(5), 1688–1693. <https://doi.org/10.1093/micmic/ozad093>

Zhang, H., Goodfellow, I., Metaxas, D., & Odena, A. (2019). Self-Attention Generative Adversarial Networks (No. arXiv:1805.08318). arXiv. <https://doi.org/10.48550/arXiv.1805.08318>

Zhao, S., Zhang, Y., Cun, X., Yang, S., Niu, M., Li, X., Hu, W., & Shan, Y. (2024). CV-VAE: A Compatible Video VAE for Latent Generative Video Models (No. arXiv:2405.20279). arXiv. <https://doi.org/10.48550/arXiv.2405.20279>

Zhao, Y. (2024). The synergistic effect of artificial intelligence technology in the evolution of visual communication of new media art. *Heliyon*, 10(18). <https://doi.org/10.1016/j.heliyon.2024.e38008>

Zheng, W., Teng, J., Yang, Z., Wang, W., Chen, J., Gu, X., Dong, Y., Ding, M., & Tang, J. (2024). CogView3: Finer and Faster Text-to-Image Generation via Relay Diffusion (No. arXiv:2403.05121). arXiv. <https://doi.org/10.48550/arXiv.2403.05121>

Zhou, K.-Q., & Nabus, H. (2023). The Ethical Implications of DALL-E: Opportunities and Challenges. *Mesopotamian Journal of Computer Science*, 2023, 16–21. <https://doi.org/10.58496/MJCSC/2023/003>

Zhu, D., & Tang, V. (2020, 19 April). Generate Images Using Variational Autoencoder (VAE). Medium. <https://medium.com/@judyyes10/generate-images-using-variational-autoencoder-vae-4d429d9bdb5>

Zhu, J.-Y., Park, T., Isola, P., & Efros, A. A. (2020). Unpaired Image-to-Image Translation using Cycle-Consistent Adversarial Networks (No. arXiv:1703.10593). arXiv. <https://doi.org/10.48550/arXiv.1703.10593>

Zlateva, P., Sivakumar, R., & Velez, D. (2024). Risks and Threats in Using Generative AI. In *Fuzzy Systems and Data Mining X* (pp. 617–626). IOS Press. <https://doi.org/10.3233/FAIA241463>

Есимова, М. С., & Шевякова, Т. В. (2024). Deep fakes in the digital media age: Opportunities and threats. *Herald of Journalism*, 73(3), 44–54. <https://doi.org/10.26577/HJ.2024.v73.i3.4>

CHAPTER XVI

DEEPPFAKE DETECTION, FAKE CONTENT VERIFICATION, AND CYBER ATTACK SCENARIOS: METHODS, CHALLENGES AND MITIGATION STRATEGIES

Saadin OYUCU¹ & Ahmet AKSÖZ²

*¹(Assoc. Prof.), Gazi University, Department of Computer Engineering,
Faculty of Technology, Ankara, 06040, Türkiye*

E mail:saadinoyucu@gazi.edu.tr

ORCID: 0000 0003 3880 3039

*²(Assoc. Prof.), Department of Electrical and Electronics Engineering,
Faculty of Engineering, Architecture and Design, Kayseri University,*

Kayseri 38380, Türkiye

E mail:ahmetaksoz@kayseri.edu.tr

ORCID: 0000 0002 2563 1218

1. Introduction

In recent years, artificial intelligence-generated synthetic media, commonly known as DeepFakes, have emerged as a serious threat undermining the credibility and reliability of digital content. Deep learning based generative models can produce fake videos, audio, and text that are often indistinguishable from genuine material. While these technologies have legitimate and creative applications, particularly in entertainment and media production, they are increasingly being exploited by malicious actors for financial fraud, information manipulation, reputational damage, and identity theft.

To counter the growing risks posed by DeepFakes, a variety of technological and institutional mechanisms have been developed to verify content authenticity and detect manipulation. This section provides a detailed examination of state-of-the-art DeepFake detection methods, including deep learning-based approaches for visual, auditory, and textual forgeries, as well as

frequency domain analyses and hybrid multimodal techniques. The discussion also highlights key challenges such as limited generalization, data scarcity, and lack of model explainability, which hinder the deployment of detection systems in real-world environments.

The second part focuses on content verification frameworks designed to ensure the provenance and integrity of digital assets. It reviews standards and technologies such as the C2PA (Coalition for Content Provenance and Authenticity) protocol, blockchain-based verification systems, and metadata analysis tools, alongside journalistic verification practices and organizational frameworks such as PREDICT, which provide structured approaches for institutional validation.

The third part examines cyberattack scenarios in which DeepFake technologies are misused, particularly for identity theft, social engineering, and data exfiltration. To mitigate these threats, the study elaborates on AI-assisted defense strategies, cryptographic security mechanisms, and cyber incident response procedures, emphasizing the importance of layered defense architectures that integrate human oversight with automated detection systems.

2. DeepFake Detection

Research on the detection of DeepFake content has accelerated rapidly in recent years, leading to the development of diverse approaches targeting different media types images, videos, audio, and text. These methods, generally referred to as passive verification techniques, focus on analyzing suspicious content to determine whether it has been synthetically generated or manipulated.




Figure 1. DeepFake video detection methods.

As illustrated in Figure 1, the most studied visual, auditory, and textual DeepFake detection approaches in the current literature are presented in a classified manner. In visual DeepFake detection, the process typically involves analyzing manipulated facial or scene data based on frequency domain features, temporal consistency, and liveness characteristics. These features are commonly evaluated using Convolutional Neural Network (CNN) and Vision Transformer (ViT)–based architectures, which enable the identification of subtle anomalies introduced during manipulation (Heidari et al., 2023; J. Imaging, 2024).

2.1. Detection of Image and Video DeepFakes

Visual forgery, particularly DeepFake videos generated through face swapping or face synthesis, is one of the most extensively studied topics in the literature. The main detection methods in this field are based on deep learning driven neural networks and forensic image analysis techniques. Among deep learning approaches, Convolutional Neural Networks (CNNs) and their variants remain the most prevalent. CNN-based detectors focus on identifying pixel-level inconsistencies and structural anomalies in forged faces that can be captured through convolutional filters. More recent studies have begun to leverage Vision Transformer (ViT) and other transformer-based architectures to detect image and video manipulations with enhanced spatial–temporal awareness.

Another prominent line of research in image-based DeepFake detection explores frequency domain traces that arise from the content generation process itself. Generative Adversarial Network (GAN) based face synthesis models employ up-sampling operations to produce high-resolution outputs, which in turn introduce subtle statistical irregularities in the frequency components imperceptible to the human eye but detectable through spectral analysis. The DCGAN approach proposed by Sharma et al. (2024) specifically targets such spectral anomalies to identify fake video conference footage, achieving an impressive 98.23 % detection accuracy for high-resolution DeepFakes. Similarly, Fourier transform–based spectral analyses and wavelet transform–based noise pattern examinations have proven effective as frequency domain techniques for detecting synthetic images.

Traditional digital image forensics methods have also been adapted to DeepFake detection. Earlier studies noted characteristic artifacts in fake videos, such as missing eye blinks or blurred static regions (e.g., hair and skin textures). However, the latest generation of synthesis models has significantly reduced such obvious defects. Consequently, researchers have turned to dual-stream neural network architectures for more robust video analysis. These models process the

same scene through two complementary modalities, one stream analyzing raw RGB pixel data, while the other examines optical flow or frequency information to uncover inconsistencies across time. By integrating spatial and temporal anomaly cues within a unified network, dual stream approaches effectively capture the subtle inconsistencies that evolve across frames, making them particularly powerful for detecting temporal irregularities in manipulated videos.

Table 1. Methods used for DeepFake detection across different media types.

DeepFake Type	Technical Approach	Advantages	Challenges Encountered
Visual DeepFake Detection	Spatial and temporal analysis (CNN, ViT), Frequency domain analysis (FFT, DCT), Eye blink, micro expression, and liveness verification	High detection accuracy, Suitable for real-time applications, Sensitive to visual anomalies	Lighting and resolution dependency, Data imbalance, Vulnerability to adversarial attacks
Audio DeepFake Detection	Mel spectrogram and cepstrum-based CNN Prosodic feature extraction Phase/ amplitude discrepancy analysis	High success in voice biometrics, language-independent detection, noise-resilient modeling	Poor generalization to unseen voice types, Dataset standardization issues, and reduced separability as synthetic voices become more natural.
Textual DeepFake Detection	Stylometric and writing style analysis, LLM-based probability (perplexity) measurement, Semantic consistency check, Provenance verification	Low-cost analysis, Multilingual applicability, can be linked to content integrity.	Author dependency, Influence of semantic diversity, Limited robustness against LLM-based manipulations

Although several DeepFake detection methods demonstrate high performance under laboratory conditions, generalizing their success to real-world environments remains a major challenge. The generalization problem refers to a detector’s ability to recognize not only the fake contents it was trained on but also novel or unseen manipulations it may encounter in the wild. Many

current models achieve impressive accuracy on specific benchmark datasets, yet their performance degrades significantly when faced with different types of fake videos or scenes captured under real-world conditions.

Meanwhile, DeepFake creators continuously develop new generation techniques designed to evade detection algorithms, forcing researchers to update and retrain detectors accordingly. As noted by Wazid et al. (2024), the dynamic between evolving DeepFake generation methods and defensive detection mechanisms has effectively become a cat-and-mouse game, where technological progress inevitably brings broader social and ethical consequences that demand multifaceted preventive measures.

Another critical limitation concerns data scarcity and imbalance. Constructing large, diverse, and balanced datasets that fully represent the wide spectrum of real-world DeepFake scenarios is extremely difficult. Existing open datasets, such as FaceForensics++ and the DeepFake Detection Challenge (DFDC), cover only limited scenarios. Consequently, models trained exclusively on these datasets often struggle to detect unfamiliar types of fake content. The challenge is even more pronounced in audio and text DeepFake detection, where the rapid evolution and diversity of attack methods frequently outpace data collection and labeling efforts.

To enhance generalization, several studies have explored adversarial training techniques, where small, controlled perturbations are introduced during model training to improve robustness. Romero Moreno (2025) emphasizes that such training should be continuously integrated with other defense mechanisms, since a model resilient to one dataset or attack type may remain vulnerable to alternative synthetic manipulations.

A further issue lies in the lack of interpretability of deep learning models. These systems rarely provide human-understandable justifications for their decisions. However, in sensitive contexts such as digital forensics or legal evidence, the rationale behind labeling content as fake must be transparent and verifiable. Consequently, the application of Explainable Artificial Intelligence (XAI) to DeepFake detection has gained significant attention. Recent tools visualize which pixel regions or frequency components influence a model's "fake" decision, revealing, for instance, that a detector may flag irregular skin textures around the eyes or temporal inconsistencies in lip motion as anomalies. Such interpretability not only builds user and expert trust but also aids in identifying false positives. As emphasized by Arya et al. (2024), incorporating explainability into DeepFake detection systems and thereby

improving user acceptance represents one of the most promising directions for future research.

The growing prevalence of DeepFakes has also fostered a widespread erosion of trust in digital interactions. A phenomenon known in the literature as “impostor bias” has emerged, where even authentic content is met with skepticism and suspicion of being fabricated. Amerini et al. (2025) argue that this “fraudster prejudice” induced by the proliferation of DeepFakes now undermines the credibility of genuine individuals, making it increasingly difficult for honest people to present video-based evidence without doubt or challenge.

3. Fake Content Verification

Another crucial dimension in combating DeepFake content is the verification of content provenance and integrity. In addition to or as an alternative to passive detection methods, emerging technologies aim to transparently trace the creation, distribution, and modification history of digital content. These approaches seek to establish end-to-end authenticity by ensuring that every stage of a media asset’s lifecycle, from generation to publication, is cryptographically verifiable and tamper-evident.

3.1. Digital Provenance and Content Verification Standards

Provenance refers to the metadata that documents the origin, creation process, and modification history of a digital object. Maintaining reliable provenance information for an image or video makes it possible to verify its authenticity and determine whether it has been altered or manipulated. One of the most prominent initiatives in this area is the Coalition for Content Provenance and Authenticity (C2PA) standard, launched under the leadership of industry pioneers such as Adobe and Microsoft.

The C2PA framework attaches a cryptographically verifiable digital “identity tag” to media files such as photos, videos, and audio recordings. This metadata includes details about who created the content, when it was produced, and what modifications have been applied throughout its lifecycle. By inspecting the embedded C2PA data within an online video file, one can determine whether it is authentic or synthetically generated by artificial intelligence.

According to Romero Moreno (2025), the C2PA standard sets a new benchmark for online trust, enabling easier identification of fraudulent financial videos, politically motivated disinformation montages, and unauthorized DeepFake imagery. A C2PA tag can explicitly reveal any suspicious alterations

in a content's history, for example, if artificial intelligence tools were involved in producing a video, this would be reflected in the provenance record, prompting justified scrutiny of the material's reliability.

Another essential component of the content provenance ecosystem involves digital watermarking and other active verification mechanisms. While watermarks have long been used for copyright protection, their role has recently expanded to include invisible watermarking of AI-generated content, allowing its origin to be traced. These watermarks embed subtle signals imperceptible to the human eye but detectable by specialized verification tools.

For instance, a Large Language Model (LLM) may introduce specific word patterns within generated text, or a DeepFake image generator may adjust pixel values according to a predefined statistical distribution to encode a watermark. Subsequent verification processes can then analyze these embedded markers to determine whether the content is human-created or AI-generated. This mechanism supports transparency in digital ecosystems and strengthens the accountability of synthetic media producers.

3.2. Blockchain-Based Verification Approaches

Blockchain technology, with its distributed and immutable ledger, has emerged as an attractive tool for fake content verification. The fundamental idea is to validate the authenticity of a digital item (such as a video or news report) through decentralized consensus among participants, without relying on a central authority, and to record that verification on the blockchain. Blockchain-based verification mechanisms can be implemented in several different forms.

In one approach, content creators or publishers record the cryptographic hash of their original content on the blockchain, enabling them to later prove its authenticity. For example, a news organization may store the hash of an original video on a chain; by comparing the hash of a circulating version, one can verify whether the content has been altered or tampered with. Because blockchain entries are immutable once registered, this technique also serves as a reliable means of preserving the integrity of digital evidence.

Blockchain can also be combined with crowdsourced verification. Ghiurau and Popescu (2025) proposed a model in which news authenticity is evaluated through a crowdsourced consensus mechanism. In their framework, newly submitted news content is reviewed and voted upon by trusted nodes recorded on the blockchain. Each node's vote is weighted according to its historical reliability, and a consensus is formed regarding whether the news is genuine

or fake. To prevent malicious majority attacks, Proof of Stake (PoS) or Proof of Authority (PoA) consensus algorithms are employed, ensuring that even a small number of trustworthy participants cannot be overruled by coordinated manipulation.

A major advantage of blockchain in this context is its inherent transparency; every transaction and data entry is visible to all participants and can be audited at any time. This transparency ensures that all votes, signatures, and verification actions within the system remain publicly traceable and tamper-resistant. Furthermore, the cryptographic integrity of blockchain makes it practically impossible to retroactively alter stored data; once a content verification record is registered on the chain, malicious modification or deletion becomes infeasible.

Recent studies have also proposed hybrid solutions that combine blockchain with digital watermarking, leveraging the strengths of both technologies to achieve secure, verifiable, and transparent content authentication. Such integrated frameworks offer promising directions for establishing trust in increasingly AI-mediated digital ecosystems.

4. Cyberattack Scenarios

The malicious use of DeepFake technologies has given rise to a new generation of creative and sophisticated cyberattack scenarios. This section examines the primary attack vectors in which DeepFakes are weaponized, providing illustrative examples and discussing tailored defense mechanisms for each case. Emphasis is placed on identity theft, social engineering, and data exfiltration scenarios, followed by an overview of AI-driven defense strategies, cryptographic countermeasures, and incident response procedures designed to mitigate such threats.

4.1. Identity Theft and Fraud-Driven Attacks

Identity theft refers to the unauthorized acquisition and misuse of an individual's personal or identifying information for illicit purposes. DeepFake technology introduces a novel dimension to identity misuse through digital impersonation. In this scenario, an attacker generates synthetic content replicating the face, voice, or both of a targeted individual and uses it to act on their behalf.

Voice biometric authentication systems, for instance, may mistakenly accept AI-generated synthetic voices as genuine. Similarly, in financial or notarial video-based transactions, a fraudster may employ a real-time DeepFake

video stream that overlays the victim's face onto their own. As a result, the human verifier on the other side perceives the attacker as the legitimate user and authorizes the transaction. Such methods allow adversaries to circumvent digital identity barriers and obtain financial or informational gains.

Typically, DeepFakes used in identity theft are ephemeral and task-specific, for example, confirming a money transfer, accessing confidential data, or signing a document under pretenses. Although many high-security operations now employ multi-factor authentication (MFA), processes involving human-to-human interaction often still rely on visual or auditory verification as the final layer of trust. Banks, for instance, depend on voice biometrics for client recognition, while government institutions use video verification to compare a live face with an identity document, precisely the checkpoints that DeepFakes seek to exploit.

Defensive strategies against these attacks must integrate both technical and procedural measures. Technically, banks and similar institutions have begun enhancing their biometric systems with embedded DeepFake detection algorithms. Spectrogram analysis can reveal subtle discrepancies between natural and synthetic voices. AI-generated speech often exhibits unnaturally clean frequency bands or statistical anomalies in the spectrum. Advanced verification systems can flag suspicious cues such as the absence of background noise or unnatural harmonic structures.

For video authentication, liveness detection techniques are commonly applied. The verifier may ask the user to perform random head movements or speak specific phrases to confirm the presence of a real person. DeepFake models usually fail to respond instantaneously, revealing temporal lag or incoherence. Additionally, iris motion, facial depth mapping, and corneal reflection consistency can be analyzed to distinguish genuine video feeds from replays or screen-based forgeries, details that DeepFake renderers still struggle to replicate accurately.

Beyond technical controls, institutional awareness and training are critical. Employees, especially those in finance and human resources departments, must be familiar with the characteristics of next-generation impersonation scams. Corporate procedures should mandate call-back verification or alternative channel confirmation for unusual or urgent requests. Khan et al. (2025) highlight the importance of developing anti-impersonation measures and maintaining a secure digital chain of custody, ensuring that every action within a transaction is logged, cryptographically sealed (e.g., via blockchain), and auditable to verify that it originated from an authorized individual.

4.2. Defense and Incident Response Strategies Against DeepFake-Enabled Attacks

Countering DeepFake-assisted cyberattacks demands a multi-layered defense architecture and a comprehensive preparedness plan. This section summarizes the main categories of countermeasures AI AI-based defensive systems, cryptographic security measures, and incident response protocols that can be applied across the scenarios discussed above.

One of the most effective tools against DeepFakes is AI itself. Organizations increasingly deploy AI-powered detection modules within email filters, network monitoring platforms, video conferencing tools, and voice-based service channels. Convolutional Neural Networks (CNNs) and Deep Neural Networks (DNNs) are particularly effective at learning complex patterns and identifying minute synthetic artifacts in facial expressions or voice signals. These models can be continuously retrained with new data to adapt to emerging DeepFake generation techniques, enabling proactive resilience.

Another line of defense relies on cryptographic verification methods. Provenance and blockchain frameworks can be implemented from a security standpoint. For example, digitally signing all outgoing communications with PGP ensures that fake emails lacking valid signatures are easily identified. Similarly, official statements or videos released by an organization can be digitally signed using the institution's private key, making their authenticity verifiable. Even if attackers distribute forged DeepFake videos under the organization's name, these forgeries will fail signature verification and thus lose credibility. Such hierarchical signing infrastructures are particularly relevant for governmental and military entities.

Despite preventive measures, breaches or dissemination of fake content may still occur. An effective and rapid response is essential to minimize damage. DeepFake incidents differ from classical data breaches as they also involve reputation management. Therefore, response teams must integrate technical, legal, and communications units. Legal teams may need to coordinate directly with digital platform operators to expedite content removal and preserve evidentiary integrity.

An equally important dimension is the establishment of legal and policy safeguards. Several countries have introduced regulations restricting or criminalizing DeepFake usage in contexts such as election security, pornography, and disinformation. For example, certain U.S. states have made the dissemination of DeepFake videos during elections a punishable offense, while

China's 2023 regulation mandates explicit labeling of all AI-generated content. Such frameworks enhance deterrence, provide legal recourse for victims, and create accountability for content creators and distributors.

4.3. Toward a Holistic Defense Paradigm

Defending against DeepFake-driven threats requires a holistic and synergistic approach—a combination of technological, organizational, and legal countermeasures. A robust defense ecosystem should include:

- Technological shields reinforced by AI, blockchain, and advanced cryptographic mechanisms,
- Human-centric defenses built through continuous training and institutional awareness,
- Rapid incident response coordination across technical and administrative teams, and
- Sound legal and regulatory infrastructures ensuring accountability.

When these elements are effectively integrated, DeepFake-based cyberattacks can be significantly mitigated or confined in impact. Ultimately, no matter how rapidly adversaries advance their techniques, maintaining technological vigilance and human awareness allows defenders to remain one step ahead, a goal that must be continually pursued in the evolving landscape of digital trust.

5. Conclusion and Recommendations

DeepFake technologies have demonstrated how the power of artificial intelligence can be misused to create an unprecedented capacity for digital deception. As discussed throughout this study, DeepFakes can generate highly realistic synthetic content across visual, auditory, and textual domains, thereby challenging traditional mechanisms of authenticity and trust.

DeepFake detection has become one of the most active areas of current research, encompassing a wide spectrum of techniques ranging from deep learning-based recognition models and frequency domain analyses to provenance-based verification and hybrid multimodal approaches. While these methods achieve high accuracy in controlled laboratory conditions, key challenges—such as generalization to real-world data, limited dataset diversity, and lack of explainability—remain unresolved. Future advancements will likely

depend on human-in-the-loop systems that combine the strengths of human judgment and AI-based detection to achieve more reliable results in complex, dynamic environments.

On the content verification front, proactive defense mechanisms are being developed to ensure digital media authenticity. Standards such as C2PA and blockchain-based frameworks act as “digital identity cards” for media objects, enabling users to verify the origin, modification history, and authorship of any given image or video. This transparency allows end users to determine where a piece of content came from and how it has been altered. Meanwhile, journalistic and fact-checking communities are fostering multi-stakeholder collaborations to combat synthetic media and misinformation. Alongside these technical initiatives, media literacy and public education remain critical: when large audiences are aware of the existence of such technologies and maintain a healthy degree of skepticism even toward seemingly credible evidence, disinformation campaigns lose much of their power.

From a cybersecurity perspective, DeepFake technologies can be weaponized in a wide range of attack scenarios, including identity theft, corporate espionage, social engineering exploits, and mass-scale public manipulation. The most effective defense is a multi-layered strategy that integrates AI-based detection, cryptographic verification protocols, robust security policies, continuous training and awareness, and well-defined incident response procedures. Without a comprehensive defense posture, a single weak link, be it human error or a technical vulnerability, can compromise the entire system. Therefore, the DeepFake threat should be systematically integrated into institutional cybersecurity frameworks and periodically assessed through stress testing and red team simulations.

In the coming years, DeepFakes will likely become more realistic, accessible, and widespread. As generative AI models continue to evolve, the ability to produce near-perfect synthetic media virtually indistinguishable to the human eye will intensify. In response, next-generation defensive solutions will be essential. From a legal and regulatory standpoint, international collaboration and harmonized standards will play a decisive role. Romero Moreno (2025) emphasizes that initiatives such as the United Nations’ resolutions on Trustworthy AI and the EU Artificial Intelligence Act must converge with technical standards to form a global governance framework for combating synthetic media misuse.

Ultimately, DeepFake technology represents a dual-edged innovation: on one side, it stimulates creativity and new forms of digital expression; on

the other, it poses a profound challenge to societal trust and authenticity. Addressing this duality requires not only technological countermeasures but also human-centered strategies investing in awareness, ethics, and resilience alongside algorithmic sophistication. Only through such an integrated approach can societies fully harness the creative potential of AI while safeguarding the integrity of the digital information ecosystem.

References

- Amerini, I., Barni, M., Battiato, S., Bestagini, P., Boato, G., ... Vitulano, D. (2025). *DeepFake Media Forensics: Status and Future Challenges*. *Journal of Imaging*, 11(3), 73. DOI: 10.3390/jimaging11030073
- Baciak, J., Żurawska, M., Czech, T., & Górny, B. (2020). DeepFake video detection using the ensemble of neural networks. *Comarch SA, AI R&D Center*.
- Firc, A., Malinka, K., & Hanáček, P. (2025). *Evaluation framework for DeepFake speech detection: a comparative study of state-of-the-art DeepFake speech detectors*. *Cybersecurity*, 8(1), 50. DOI: 10.1186/s42400-024-00346-1
- Ghiurău, D., & Popescu, D. E. (2025). *Distinguishing Reality from AI: Approaches for Detecting Synthetic Content*. *Computers*, 14(1), 1. DOI: 10.3390/computers14010001
- Heidari, A., Jafari Navimipour, N., Dag, H., & Ünal, M. (2024). *DeepFake detection using deep learning methods: A systematic and comprehensive review*. *WIREs Data Mining and Knowledge Discovery*, 14(1), e1520. DOI: 10.1002/widm.1520
- Khan, A. A., Laghari, A. A., Bacarra, R., Alroobaea, R., Algarni, S., Baqasah, A. M., & Alsayaydeh, J. A. J. (2025). *Cybersecurity, Digital Forensics, and the IoT for DeepFake Investigation on Social Media Platforms: A Review*. *Human Centric Computing and Information Sciences*, 15(38). DOI: 10.22967/HGIS.2025.15.038
- Lokhande, M., Ahirrao, M., Raut, P., Bhande, A., & Gawali, K. (2024). *Artificial Intelligence for Detecting Cyber Attacks in DeepFake & Identity Theft*. In 2024 8th International Conference on Computing, Communication, Control and Automation (ICCUBEA) (pp. 1–8). IEEE. DOI: 10.1109/ICCUBEA61740.2024.10774771
- Pedersen, K. T., Pepke, L., Stærmose, T., Papaioannou, M., & Choudhary, G. (2025). *DeepFake Driven Social Engineering: Threats, Detection Techniques, and Defensive Strategies in Corporate Environments*. *Journal of Cybersecurity and Privacy*, 5(1), 18. DOI: 10.3390/jcp5010018

Romero Moreno, F. (2025). Deepfake detection in generative AI: A legal framework proposal to protect human rights. *Computer Law & Security Review*, 58, 106162.

Sharma, S. K., AlEnizi, A., Kumar, M., Alfarraj, O., & Alowaidi, M. (2024). *Detection of real time DeepFakes and face forgery in video conferencing employing generative adversarial networks*. *Heliyon*, 10(10), e37163. DOI: 10.1016/j.heliyon.2024.e37163

Arya, M., Akash, ... Chawla, S. (2024). *A Study on DeepFake Face Detection Techniques*. In *Proceedings of the 3rd International Conference on Applied Artificial Intelligence and Computing (ICAAIC 2024)* (pp. 459 466). IEEE. DOI: 10.1109/ICAAIC54529.2024.1234567

Wazid, M., Mishra, A. K., Mohd, N., & Das, A. K. (2024). *A Secure DeepFake Mitigation Framework: Architecture, Issues, Challenges, and Societal Impact*. *Cyber Security and Applications*, 2, 100040. DOI: 10.1016/j.csa.2024.100040

CHAPTER XVII

SUSTAINABILITY AND ENVIRONMENTAL MODELING WITH GENERATIVE ARTIFICIAL INTELLIGENCE

Emre ÜNSAL¹ & Ahmet Fırat YELKUVAN²

*¹(Assist. Prof. Dr.) Sivas Cumhuriyet University, Faculty of Engineering,
Department of Software Engineering, Sivas, Türkiye*

E-mail: eunsal@cumhuriyet.edu.tr

ORCID: 0000-0001-6042-0742

*² (Res. Asst.) Sivas Cumhuriyet University, Faculty of Engineering,
Department of Computer Engineering, Sivas, Türkiye*

E-mail: aftyelkuvan@cumhuriyet.edu.tr

ORCID: 0000-0003-4148-1923

1. Introduction

Global environmental challenges are becoming more serious and are creating complex, multidimensional risks that slow progress toward sustainable development goals. Climate change, rapid urbanization, overuse of natural resources, and rising energy demand place decision-makers in situations of high complexity and uncertainty. As a result, accurate and scalable environmental modeling methods are essential for both regulatory frameworks and engineering applications (Goodess, 2013; Hausfather et al., 2020). Yet traditional modeling techniques often struggle to represent these complex processes and frequently fail to offer sufficient solutions because of high computational costs, limited data availability, and their inability to fully capture uncertainties.

Recent years have seen the emergence of Generative Artificial Intelligence (GenAI) methods in environmental modeling and sustainability research. Techniques such as Generative Adversarial Networks (GANs), Variational Autoencoders (VAEs), and diffusion-based models are now being applied

to tasks such as imputing missing data, generating high-resolution climate scenarios, diversifying environmental risk maps, and extending uncertainty analyses (Goodfellow et al., 2014; Ho et al., 2020; Kingma & Welling, 2022). Although traditional physics-based models used in climate science remain computationally intensive, GenAI approaches provide faster and more flexible alternatives and are increasingly incorporated into decision-support systems (Rolnick et al., 2023).

The contributions of GenAI to environmental sustainability extend beyond enhancing climate scenarios to include key domains such as resource planning, green energy design, and disaster management (O'Neill et al., 2017). For example, in green energy design, high-resolution estimation of solar and wind potential helps optimize the balance between energy supply and demand and contributes to lowering the carbon footprint (Ma et al., 2024).

In conclusion, GenAI plays an important role not only in developing climate scenarios and supporting resource planning but also in transforming energy systems. This chapter will examine in detail the core architectures of GenAI, its alignment with sustainability objectives, and its recent applications in environmental modeling.

2. Fundamentals of Generative Artificial Intelligence

GenAI refers to a class of models capable of producing new, original, and statistically consistent samples based on distributions learned from large-scale datasets. The fundamental approach of GenAI goes beyond merely analyzing data through supervised tasks such as classification or regression; rather, it focuses on learning the underlying probability distribution to generate new data instances (Creswell et al., 2018). Owing to these features, GenAI is used in wide-ranging applications, including missing data imputation, scenario generation, data augmentation, and uncertainty analysis.

2.1 Generative Adversarial Networks

The Generative Adversarial Network (GAN) consists of two different artificial neural networks that compete (Goodfellow et al., 2014). These networks are termed the Generator and the Discriminator. As shown in Figure 1, the generator receives random noise or latent vectors as input and produces synthetic data samples, while the discriminator evaluates these against real data to determine their authenticity. Through this adversarial process, the generator progressively improves its ability to produce high-quality and realistic samples, whereas the discriminator simultaneously enhances its classification accuracy.

This iterative competition continues until the generated data distributions closely approximate the real data. In environmental modeling, GANs have been successfully applied to tasks such as generating high-resolution climate data, removing cloud cover from satellite imagery, and forecasting renewable energy outputs (Ma et al., 2024).




Figure 1. Schematic representation of a GAN architecture, illustrating the adversarial training process between the generator and discriminator.

From a mathematical standpoint, Generative Adversarial Networks (GANs) are typically formulated as a two-player minimax optimization problem, wherein the generator G seeks to produce samples indistinguishable from the data distribution while the discriminator D is simultaneously trained to differentiate between real and generated samples. The discriminator is optimized to maximize the probability of correctly classifying real data $x \sim p_{data}$ and fake data $G(z)$, where z is drawn from a prior noise distribution $p_z(z)$. Conversely, the generator is optimized to minimize the discriminator's ability to detect fake samples. This objective can be expressed as follows:

$$\min_G \max_D V(D, G) = \mathbb{E}_{x \sim p_{data}(x)} [\log D(x)] + \mathbb{E}_{z \sim p_z(z)} [\log 1 - D(G(z))]$$

Here,

- $D(x)$ represents the probability that x is real,
- $G(z)$ generates synthetic data from random noise,

The discriminator seeks to maximize correct classification, while the generator seeks to minimize it by producing increasingly realistic samples.

This adversarial optimization allows GANs to approximate complex data distributions without requiring explicit likelihood functions, making them especially powerful for high-dimensional environmental data synthesis.

2.2 Variational Autoencoders

The Variational Autoencoder (VAE) is based on probabilistic encoding and decoding principles (Kingma & Welling, 2022). A VAE represents data in a low-dimensional latent space and can generate new data by sampling from this

space. Figure 2 shows that the encoder compresses the input into a probabilistic latent representation, while the decoder reconstructs the data from this latent space. This capability allows VAEs to effectively address tasks such as filling missing data, generating synthetic climate scenarios, and modeling hydrological processes (Sit et al., 2020).




Figure 2. Schematic architecture of a VAE, illustrating the encoding of input data into a latent distribution and its reconstruction via the decoder.

In the VAE framework, the encoder maps the input data x into a latent variable z , characterized by a probability distribution $q_{\phi}(z|x)$, typically parameterized by a Gaussian with mean μ and variance σ^2 . A latent sample is drawn from this distribution and then passed to the decoder, which reconstructs the data through $p_{\theta}(x|z)$. This probabilistic mechanism allows VAEs to generate diverse, statistically consistent outputs while capturing the uncertainty inherent in the data.

Mathematically, VAEs are trained by maximizing the Evidence Lower Bound (ELBO) on the log-likelihood of the observed data:

$$\log p_{\theta}(x) \geq \mathbb{E}q_{\phi}(z|x)[\log p_{\theta}(x|z)] - D_{KL}(q_{\phi}(z|x)p(z))$$

where:

- $p_{\theta}(x|z)$ is the likelihood term (reconstruction loss), ensuring that the decoded data resemble the input,
- $D_{KL}(q_{\phi}(z|x)p(z))$ is the Kullback–Leibler (KL) divergence term, which regularizes the approximate posterior $q_{\phi}(z|x)$ to remain close to the prior $p(z)$, usually chosen as a standard normal distribution.

This dual-objective structure ensures that VAEs not only reconstruct the observed data accurately but also learn a smooth, continuous latent space from which new and coherent samples can be generated.

2.3 Diffusion Models

Diffusion models, one of the most rapidly advancing areas of GenAI, learn data distributions through iterative processes of noise addition and

removal (Ho et al., 2020). Compared to GANs and VAEs, these models have demonstrated greater stability and reliability in generating high-quality samples. In environmental studies, diffusion models have begun to be used for synthetic simulation of precipitation fields, downscaling of climate scenarios, and diversification of disaster scenarios (Sohl-Dickstein et al., 2015). In Figure 3, diffusion models progressively corrupt input data by adding Gaussian noise during the forward process and then learn to reverse this corruption through a denoising procedure, reconstructing realistic samples from random noise.




Figure 3. Schematic representation of a diffusion-based generative model, showing the forward process of noise addition and the reverse process of iterative denoising to reconstruct data samples.

In mathematical terms, diffusion models define a forward Markov chain that gradually adds noise to an input sample x_0 over T time steps, producing increasingly noisy samples x_t :

$$q(x_t|x_{t-1}) = N(x_t; \sqrt{1 - \beta_t}x_{t-1}, \beta_t I)$$

where β_t controls the variance of the added Gaussian noise at each step. The generative task involves learning a reverse process:

$$p_\theta(x_{t-1}|x_t) = N(x_{t-1}; \mu_\theta(x_t, t), \sum_\theta(x_t, t))$$

which incrementally removes noise and reconstructs the data distribution. Training is typically guided by minimizing the error between the true noise and the model's predicted noise, enabling the network to denoise effectively.

This iterative denoising mechanism makes diffusion models particularly powerful for environmental modeling, as they can simulate fine-grained spatial and temporal variability in climate and hydrological data while maintaining stability during training. Their robustness also makes them a promising tool for generating diverse, probabilistic scenarios to support risk-based environmental planning and sustainable decision-making.

2.4 Transformer-Based Generative Models

Transformer-based models, initially developed for natural language processing (Vaswani et al., 2023), have increasingly been applied to environmental datasets such as time series, spatial data, and multimodal environmental records. The architecture, shown in Figure 4, consists of an encoder–decoder structure that leverages self-attention to capture long-range dependencies across the input sequence. This mechanism enables the model to weigh the relative importance of different temporal and spatial features, making it particularly effective for complex environmental data. Transformer-based generative approaches have therefore emerged as robust alternatives in applications such as long-term wind speed prediction, hydrological cycle modeling, and the analysis of high-dimensional climate data (Dosovitskiy et al., 2021).




Figure 4. Schematic architecture of a transformer-based generative model, showing the encoder–decoder structure and attention layers.

The attention mechanism at the core of transformers computes a weighted representation of input sequences. Formally, given queries (Q), keys (K), and values (V), the self-attention operation is defined as follows:

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V$$

where d_k is the dimensionality of the key vectors. Multi-head attention extends this idea by computing multiple sets of attention in parallel, thereby capturing diverse contextual relationships. The encoder aggregates these representations into contextual embeddings, while the decoder leverages cross-attention to align input and output features, enabling the generation of coherent sequences.

This framework is particularly advantageous in environmental modeling because it allows the integration of multiple modalities (e.g., atmospheric,

hydrological, and geospatial data) into a unified model. By doing so, transformer-based generative approaches support tasks such as spatiotemporal downscaling, multimodal data fusion, and uncertainty-aware scenario generation, offering a scalable and flexible solution for sustainability-focused research.

2.5 Physics-Informed Neural Networks (PINNs)

One of the most significant directions in applying GenAI to environmental domains is the integration of physical constraints into learning architectures. Physics-Informed Neural Networks (PINNs) are based on explicitly embedded differential equations into the training process, ensuring that the generated outputs remain physically consistent (Raissi et al., 2019). Figure 5 shows that a PINN combines standard neural network approximations with additional loss terms derived from governing physical laws. This approach enables the preservation of essential principles such as energy conservation, mass balance, and hydrological flow dynamics, thereby ensuring that generated data are both statistically plausible and physically meaningful.




Figure 5. Conceptual architecture of a PINN, showing the integration of data loss and physics-based residual loss into a unified optimization framework.

Mathematically, the PINN framework augments the traditional loss function with physics-based regularization. Given a system of governing partial differential equations (PDEs), expressed as:

$$F(u(x, t)) = 0$$

where $\ddot{u}(\cdot, \cdot)$ represents the physical state variable, a neural network surrogate $u_\theta(x, t)$ is trained to approximate $u(x, t)$. The total loss function is then defined as:

$$L = L_{data} + \lambda L_{physics}$$

where:

- $L_{data} = u_{\theta}(x_i, t_i)^2$ enforces consistency with observed or simulated data,
- $L_{physics} = F(u_{\theta}(x, t))^2$ penalizes violations of the PDE residuals,
- λ is a weighting coefficient balancing data fidelity and physical consistency.

This formulation ensures that PINNs not only interpolate sparse or noisy measurements but also adhere to known physical laws. In environmental modeling, PINNs have been applied to fluid dynamics, groundwater flow, and energy system optimization, providing reliable generative outputs that are robust under extrapolation and uncertainty.

3. Climate Scenarios

Climate scenarios, developed to predict the future impacts of climate change, form a cornerstone of environmental planning and sustainability policies. Scenario-based analyses allow the systematic examination of uncertainties by considering factors such as greenhouse gas emission pathways, population, and economic growth projections (Moss et al., 2010). Representative Concentration Pathways (RCP) and Shared Socioeconomic Pathways (SSP), developed within this scope, present global-scale scenarios representing possible futures under climate change in the 21st century (O'Neill et al., 2017).

Existing climate models, however, face several limitations, particularly at the regional and local scales. These include coarse spatial resolution, high computational costs, and limited representation of uncertainties (Hausfather et al., 2020). Such constraints hinder decision-makers from obtaining the detailed outputs required for applications such as disaster management, energy planning, and water resource management.

GenAI stands out as a complementary tool in the development of climate scenarios. GAN and Diffusion models have achieved remarkable success, particularly in downscaling processes, converting low-resolution global climate outputs into higher-resolution regional data (Ma et al., 2024; Yang et al., 2024). The overall workflow, from traditional climate modeling through downscaling to GenAI integration and its application domains, is shown in Figure 6. Moreover, GenAI models can generate alternative climate projections under different emission scenarios, thereby supporting a more comprehensive analysis of uncertainties.




Figure 6. Integration of GenAI into climate scenario modeling.

Another key contribution of GenAI lies in synthetic scenario diversification. For instance, generating numerous examples of possible extreme rainfall or heatwaves can strengthen risk-based planning (Chen et al., 2023). Similarly, diversifying the climate inputs used for energy system modelling enables the design of more robust and resilient infrastructure in green energy development.

In summary, the use of GenAI in climate scenarios offers significant potential in terms of both increasing spatial and temporal resolution and advancing uncertainty management. Therefore, in future sustainability research, the integrated use of classical physics-based climate models and GenAI-based approaches will enable the production of more reliable and flexible projections.

4. Resource Planning

In the context of sustainability, the efficient management of natural resources is critical importance, both for adapting climate change and for preserving ecosystem services. Resource planning involves the long-term optimization of water, energy, and land use based on scenario-driven approaches. Traditional planning approaches are often grounded on deterministic or stochastic models; however, these approaches are often limited due to data scarcity, high computational costs, and inadequate representation of uncertainties (Ji et al., 2024). In this context, GenAI offers new opportunities in resource planning with its flexible structure and ability to learn probability distributions.

4.1 Water Resources

One of the most significant impacts of climate change is the uncertainty in the hydrological cycle. The gaps in precipitation and streamflow data make it difficult to plan water resources reliably. Synthetic hydrological data production using VAE and diffusion-based models enables the generation of statistically realistic flow series (Ou et al., 2024; Yang et al., 2024). In addition, GAN-based

approaches are used to diversify extreme rainfall scenarios and improve the accuracy of flood risk maps (Mosavi et al., 2018). Such generative approaches provide critical contributions to dam operation policies, irrigation management, and flood early warning systems.

4.2 Energy Resources

Rising energy demand, particularly in the context of renewable energy integration, necessitates advanced planning techniques. The future production potential of variable renewable energy sources such as solar and wind is directly dependent on climatic conditions. GAN and transformer-based models increase the accuracy of energy production forecasts by generating high-resolution wind and solar profiles (Ma et al., 2024). Furthermore, GenAI models can simulate diverse climate conditions to support scenario-based optimization of supply–demand balance, providing strategic advantages for energy storage systems and grid management (Rolnick et al., 2023).

4.3 Land Use

Changes in land use directly affect both the water cycle and energy planning. GenAI-based approaches leveraging remote sensing data can produce high-resolution land cover change scenarios. These methods enable more accurate long-term projections of processes such as urban expansion, agricultural land conversion, or deforestation (Reichstein et al., 2019). Such scenarios serve as powerful decision support tools, particularly for urban planning, ecosystem management, and carbon balancing strategies.

5. Green Energy Design

In line with global carbon neutrality goals, the design and integration of green energy systems are fundamental elements of sustainability strategies. The planning of variable renewable energy sources such as solar and wind requires high-resolution climate data in both temporal and spatial dimensions. However, traditional forecasting models can be inadequate, particularly in terms of short-term production forecasting and scenario diversity (Kalogirou, 2014). In this context, GenAI offers innovative solutions or renewable energy design, enabling more robust, flexible, and data-driven approaches.

5.1 Solar Energy Systems

One of the most critical aspects in the design of solar energy systems is the high-resolution and reliable modeling of shortwave radiation reaching the

surface. Traditional climate models and reanalysis datasets typically provide low-resolution outputs (25–100 km), which introduces substantial uncertainty in photovoltaic (PV) site selection and capacity planning. GenAI offers innovative solutions to this challenge with its ability to generate micro-scale (1–5 km) solar radiation fields from low-resolution climate outputs. GAN-based super-resolution approaches have enabled the production of detailed solar radiation maps from climate model outputs, thereby improving the reliability of PV panel siting and optimal capacity planning (Ma et al., 2024; Xie et al., 2025). These maps play a decisive role not only in potential analyses but also in slope-aspect optimization, shading analysis, and refinement of capacity factor projections.

Satellite-based observations, however, often contain missing or corrupted values due to cloudiness and atmospheric correction errors. VAE and diffusion-based models fill these gaps with spatiotemporally consistent reconstructions, enabling the production of continuous and reliable radiation time series (Yang et al., 2024). Furthermore, GenAI can simulate diverse cloud conditions, generating alternative scenarios for overcast and clear-sky environments. This capability supports more realistic analyses of PV system design, including storage sizing and inverter behavior (Boucif et al., 2025). In this way, GenAI not only fills observational gaps but also enhances risk-based planning through scenario diversification.

Short- and medium-term PV power forecasts are another domain where the GenAI contributes. Transformer-based generative models capture sudden variations in sky conditions and local spatial correlations more effectively than traditional statistical methods (e.g., persistence, ARIMA) or physics-based Numerical Weather Prediction (NWP) models, thereby delivering lower error rates (Yousef et al., 2023). Such forecasts are critical for grid integration and ensuring supply-demand balance. In particular, the probabilistic sampling capabilities of diffusion-based models enhance reliability analysis within decision-support frameworks (Yang et al., 2024).

Finally, since training large-scale GenAI models entails substantial computational costs, it is also important that the AI models used in green energy design themselves have a low carbon footprint. To this end, techniques such as quantization, knowledge distillation, and low-precision computation are increasingly being adopted (Schwartz et al., 2020). This ensures that both the designed energy systems and the AI models supporting them are better aligned with sustainability objectives.

5.2 Wind Energy Systems

Among renewable energy sources, wind power is one of the most dependent on high-resolution data due to its variable nature and spatial heterogeneity. Critical inputs for wind farm design, production optimization, and grid integration include wind speed distributions, directional profiles, turbulence structures, and topographic effects. However, traditional climate models mostly provide these parameters at low resolutions (25–50 km), while field measurements remain limited and unevenly distributed. This creates significant uncertainty in the preparation of micro-scale wind atlases.

GenAI models provide innovative solutions to these problems in wind energy planning. GAN-based super-resolution methods produce micro-scale (1–5 km) wind profiles from low-resolution wind data, providing more reliable outputs for turbine layout planning. This approach enables a more accurate assessment of topographic effects on energy production (Ma et al., 2024). Furthermore, VAE and diffusion-based generative models enable the diversification of rare but critical situations, such as extreme wind episodes or prolonged calm periods. These synthetic scenarios support more robust storage system sizing and enhance the evaluation of grid security (Yang et al., 2024).

Short-term forecasting represents another significant contribution of GenAI in wind energy systems. Transformer-based generative models capture temporal dependencies in wind speed more effectively than traditional methods such as LSTM or ARIMA, thereby improving predictive accuracy. Studies have reported reductions in error rates for hourly and daily forecasts, facilitating more reliable grid integration (Yousef et al., 2023). Moreover, their probabilistic forecasting capabilities provide uncertainty intervals to decision-makers, enabling more flexible grid balancing strategies (Chen et al., 2023).

Regional wind potential analysis is also another application area where GenAI demonstrates strong utility. Diffusion and GAN-based downscaling methods generate high-resolution regional wind atlases from global climate model outputs, strengthening risk analysis in investment planning. Unlike traditional approaches, these atlases incorporate not only average capacity factors but also the frequency of extreme wind or stagnation events, thus providing more realistic long-term sustainability projections (Yang et al., 2024).

As a result, GenAI-based methods offer significant advantages in wind energy design in terms of high resolution, scenario diversity, and uncertainty management. Consequently, both turbine optimization and grid integration

processes become more reliable and flexible, accelerating the broader transition toward green energy.

5.3 Hybrid Energy Systems and Supply-Demand Balance

One of the major challenges in renewable energy transition is the intermittent nature of variable sources such as solar and wind. This intermittency creates fluctuations in energy supply, which can negatively affect grid reliability and supply-demand balance. Therefore, in recent years, hybrid energy systems, (i.e., systems that combine multiple renewable sources and energy storage units), have become increasingly important in terms of energy security and sustainability. By leveraging the complementary characteristics of different resources, hybrid systems can smooth production profiles and facilitate grid integration (Lund et al., 2017). However, the optimal design of such systems remains highly complex under uncertain climate conditions.

GenAI models provide an innovative solution to this complexity through their capabilities in scenario diversification and probabilistic modeling. GAN and VAE-based models enable the examination of a wider probability space in system design by generating synthetic scenarios related to energy supply-demand balance under different climate conditions. This approach enables more reliable decision-making for critical aspects such as storage sizing, backup strategies, and grid flexibility (Pfenninger & Keirstead, 2015). In particular, the optimization of energy storage systems benefits from simulations of extreme demand peaks or low-production periods generated by GenAI, which helps reduce investment costs while enhancing system security.

Short-term forecasting also plays a crucial role in maintaining supply-demand balance. Transformer-based generative models allow simultaneous modeling of both energy demand or renewable production, enabling multivariate predictions (R et al., 2023). This capability contributes to the more effective implementation of demand-side management and dynamic pricing strategies, particularly in smart grids. Meanwhile, diffusion models contribute by probabilistically replicating diverse demand and production scenarios, equipping grid operators with robust tools for decision-making under uncertainty.

In conclusion, GenAI enhances hybrid energy systems by offering scenario diversity, probabilistic forecasting power, and flexible design advantages. These contributions not only strengthen grid reliability at the technical level but also reduce financial risks in long-term energy investments, thereby accelerating the deployment of low-carbon energy systems.

6. Discussion and Ethical Dimensions

The potential of GenAI in the field of sustainability and environmental modeling is substantial; however, several limitations, risks, and ethical issues must be considered in the application of these technologies. First, the computational cost of GenAI, particularly during the training of large-scale GAN, VAE, and diffusion models, leads to significant energy consumption. Studies have shown that the energy consumed in training large artificial intelligence models may generate hundreds of tons of carbon dioxide (CO₂) equivalents (Strubell et al., 2019). This paradox highlights that a technology developed to promote environmental sustainability may itself carry a large carbon footprint. Consequently, the concept of Green AI has recently gained attention, focusing on methods such as quantization, model compression, knowledge distillation, and energy-efficient architectures to reduce the environmental impact of AI (Schwartz et al., 2020). This relationship is conceptually illustrated in Figure 7.




Figure 7. Conceptual illustration of Green AI in reducing computational energy consumption.

Second, while GenAI offers rich scenario diversity and high-resolution outputs that benefit decision-makers, the explainability of these models remains limited. In particular, GAN and diffusion-based approaches often operate as “black boxes,” making it difficult to assess the physical consistency of the generated outputs. When physical constraints are not directly integrated into the models, fundamental principles such as energy or mass conservation may be violated, leading to misleading outcomes (Raissi et al., 2019). In this context, the development of PINNs is crucial for ensuring that generated scenarios remain not only statistically valid but also physically consistent.

Another concern is data bias and inclusivity. Datasets used in environmental modeling and energy planning are often unevenly distributed at the global scale. For instance, while developed countries possess rich measurement datasets, developing regions frequently face significant data scarcity. Although GenAI can help address such gaps, synthetic data may still inherit biases from the distributions on which they are trained (Rolnick et al., 2023). Therefore, it is essential to evaluate synthetic outputs not only for statistical validity but also for their social and regional inclusiveness.

A further ethical consideration is open science and transparency. Since environmental modeling outcomes frequently inform policymaking, the methodologies, assumptions, and uncertainties underlying GenAI models must be reported transparently. Presenting generated scenarios as “definitive predictions” risks creating a false sense of certainty. Instead, decision-makers should be provided with clear uncertainty ranges and probabilistic outputs (Chen et al., 2023). Moreover, making codes, training data, and model cards openly accessible enhances reproducibility and fosters trust.

Finally, the use of GenAI in environmental decision-support systems must be evaluated through the lens of justice and ethical responsibility. Misleading or biased scenarios can adversely affect energy investments, urban planning, and disaster management. Therefore, these models must be continuously monitored and assessed not only for technical accuracy but also for their broader societal impacts. A consolidated overview of these key ethical challenges and potential solutions is presented in Table 1.

Table 1. Ethical and Practical Considerations of GenAI in Environmental Modeling

Dimension	Challenge	Proposed Approach
Energy & Carbon Footprint	Training large GAN, VAE, and diffusion models consumes substantial energy, producing high CO ₂ emissions (Strubell et al., 2019).	Green AI: quantization, model compression, knowledge distillation, efficient architectures (Schwartz et al., 2020).
Model Explainability	GANs and diffusion models act as “black boxes,” risking violations of physical laws (Raissi et al., 2019).	Integration of physical constraints, e.g., Physics-Informed Neural Networks (PINNs).
Data Bias & Inclusivity	Uneven global data distribution may reinforce socio-regional biases (Rolnick et al., 2023).	Ensure diverse datasets; prioritize underrepresented regions.
Transparency	Limited reporting of methods and uncertainties; risk of “false certainty” (Chen et al., 2023).	Report uncertainty ranges; open-source codes, data, and model cards.
Societal Impact	Biased or misleading scenarios can affect planning and investments.	Ongoing monitoring for technical accuracy and social fairness.

7. Conclusions and Future Directions

The findings presented in this chapter demonstrate that GenAI holds transformative potential for sustainability and environmental modeling. GANs, VAEs, diffusion, and transformer-based models provide critical contributions to the enrichment of climate scenarios, the improvement of resource planning, and the design of green energy systems. GenAI enables the generation of micro-scale maps from low-resolution climate outputs, the filling of data gaps, and the probabilistic representation of uncertainties in a more comprehensive manner. These capabilities allow policymakers, engineers, and researchers to assess the impacts of climate change with greater reliability and to plan more resilient energy systems.

Nevertheless, several limitations must be acknowledged in the application of GenAI-based methods. The computational cost and carbon footprint of training large-scale models represent significant constraints for their widespread use. Moreover, the physical consistency and interpretability of generated data remain

limited, introducing uncertainty into decision-support processes. Data bias, regional disparities, and ethical challenges also require careful consideration. Thus, future research should prioritize not only technical accuracy but also transparency, inclusivity, and sustainability principles.

Several topics stand out in terms of future research directions. First, the development of physics-informed generative models (e.g., PINNs) will ensure that the generated scenarios remain physically consistent as well as statistically valid. Second, the adoption of energy-efficient AI methods will reduce carbon emissions while facilitating real-time applications of GenAI. Third, multidisciplinary integration is essential: the joint use of GenAI with remote sensing, hydrology, energy systems, and urban planning may yield more holistic and actionable outcomes. Finally, the promotion of open science and reproducibility will strengthen the credibility of research in this domain and reinforce trust among policymakers.

In summary, GenAI carries revolutionary potential for sustainability and environmental modeling. However, for this potential to be translated into tangible societal benefits, future research must not only pursue technical innovations but also address the ethical, environmental, and institutional dimensions of its application.

References

- Boucif, O. H., Lahouaou, A. M., Boubiche, D. E., & Toral-Cruz, H. (2025). Artificial Intelligence of Things for Solar Energy Monitoring and Control. In *Applied Sciences (Switzerland)* (Vol. 15, Issue 11). Multidisciplinary Digital Publishing Institute (MDPI). <https://doi.org/10.3390/app15116019>
- Chen, S., Long, G., Jiang, J., Liu, D., & Zhang, C. (2023). *Foundation Models for Weather and Climate Data Understanding: A Comprehensive Survey*. <http://arxiv.org/abs/2312.03014>
- Creswell, A., White, T., Dumoulin, V., Arulkumaran, K., Sengupta, B., & Bharath, A. A. (2018). Generative Adversarial Networks: An Overview. In *IEEE Signal Processing Magazine* (Vol. 35, Issue 1, pp. 53–65). Institute of Electrical and Electronics Engineers Inc. <https://doi.org/10.1109/MSP.2017.2765202>
- Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., Uszkoreit, J., & Houlsby, N. (2021). *An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale*. <http://arxiv.org/abs/2010.11929>

Goodess, C. M. (2013). How is the frequency, location and severity of extreme events likely to change up to 2060? *Environmental Science and Policy*, 27, S4–S14. <https://doi.org/10.1016/j.envsci.2012.04.001>

Goodfellow, I. J., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., Courville, A., & Bengio, Y. (2014). *Generative Adversarial Networks*. <http://arxiv.org/abs/1406.2661>

Hausfather, Z., Drake, H. F., Abbott, T., & Schmidt, G. A. (2020). Evaluating the Performance of Past Climate Model Projections. *Geophysical Research Letters*, 47(1). <https://doi.org/10.1029/2019GL085378>

Ho, J., Jain, A., & Abbeel, P. (2020). *Denoising Diffusion Probabilistic Models*. <http://arxiv.org/abs/2006.11239>

Ji, H. K., Mirzaei, M., Lai, S. H., Dehghani, A., & Dehghani, A. (2024). Implementing generative adversarial network (GAN) as a data-driven multi-site stochastic weather generator for flood frequency estimation. *Environmental Modelling & Software*, 172, 105896. <https://doi.org/https://doi.org/10.1016/j.envsoft.2023.105896>

Kalogirou, S. (2014). *Solar Energy Engineering: Processes and Systems: Second Edition*. Academic Press. <https://www.researchgate.net/publication/41117169>

Kingma, D. P., & Welling, M. (2022). *Auto-Encoding Variational Bayes*. <http://arxiv.org/abs/1312.6114>

Lund, H., Østergaard, P. A., Connolly, D., & Mathiesen, B. V. (2017). Smart energy and smart energy systems. In *Energy* (Vol. 137, pp. 556–565). Elsevier Ltd. <https://doi.org/10.1016/j.energy.2017.05.123>

Ma, Z., Mei, G., & Xu, N. (2024). Generative deep learning for data generation in natural hazard analysis: motivations, advances, challenges, and opportunities. *Artificial Intelligence Review*, 57(6), 160. <https://doi.org/10.1007/s10462-024-10764-9>

Mosavi, A., Ozturk, P., & Chau, K. W. (2018). Flood prediction using machine learning models: Literature review. In *Water (Switzerland)* (Vol. 10, Issue 11). MDPI AG. <https://doi.org/10.3390/w10111536>

Moss, R. H., Edmonds, J. A., Hibbard, K. A., Manning, M. R., Rose, S. K., Van Vuuren, D. P., Carter, T. R., Emori, S., Kainuma, M., Kram, T., Meehl, G. A., Mitchell, J. F. B., Nakicenovic, N., Riahi, K., Smith, S. J., Stouffer, R. J., Thomson, A. M., Weyant, J. P., & Wilbanks, T. J. (2010). The next generation of scenarios for climate change research and assessment. In *Nature* (Vol. 463, Issue 7282, pp. 747–756). <https://doi.org/10.1038/nature08823>

O'Neill, B. C., Kriegler, E., Ebi, K. L., Kemp-Benedict, E., Riahi, K., Rothman, D. S., van Ruijven, B. J., van Vuuren, D. P., Birkmann, J., Kok, K., Levy, M., & Solecki, W. (2017). The roads ahead: Narratives for shared socioeconomic pathways describing world futures in the 21st century. *Global Environmental Change*, 42, 169–180. <https://doi.org/10.1016/j.gloenvcha.2015.01.004>

Ou, Z., Nai, C., Pan, B., Pan, M., Shen, C., Jiang, P., Liu, X., Tang, Q., Li, W., & Zheng, Y. (2024). *DRUM: Diffusion-based runoff model for probabilistic flood forecasting*. <http://arxiv.org/abs/2412.11942>

Pfenniger, S., & Keirstead, J. (2015). Renewables, nuclear, or fossil fuels? Scenarios for Great Britain's power system considering costs, emissions and energy security. *Applied Energy*, 152, 83–93. <https://doi.org/10.1016/j.apenergy.2015.04.102>

R, R. A. N., Posada, J., Unsihuay-Vila, C., & Pinzón-Ardila, O. (2023). Review of Smart Transformer-Based Meshed Hybrid Microgrids: Shaping, Topology and Energy Management Systems. *IEEE Access*, 11, 130165–130185. <https://doi.org/10.1109/ACCESS.2023.3334651>

Raissi, M., Perdikaris, P., & Karniadakis, G. E. (2019). Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics*, 378, 686–707. <https://doi.org/10.1016/j.jcp.2018.10.045>

Reichstein, M., Camps-Valls, G., Stevens, B., Jung, M., Denzler, J., Carvalhais, N., & Prabhat. (2019). Deep learning and process understanding for data-driven Earth system science. *Nature*, 566(7743), 195–204. <https://doi.org/10.1038/s41586-019-0912-1>

Rolnick, D., Donti, P. L., Kaack, L. H., Kochanski, K., Lacoste, A., Sankaran, K., Ross, A. S., Milojevic-Dupont, N., Jaques, N., Waldman-Brown, A., Luccioni, A. S., Maharaj, T., Sherwin, E. D., Mukkavilli, S. K., Kording, K. P., Gomes, C. P., Ng, A. Y., Hassabis, D., Platt, J. C., ... Bengio, Y. (2023). Tackling Climate Change with Machine Learning. In *ACM Computing Surveys* (Vol. 55, Issue 2). Association for Computing Machinery. <https://doi.org/10.1145/3485128>

Schwartz, R., Dodge, J., Smith, N. A., & Etzioni, O. (2020). Green AI. *Communications of the ACM*, 63(12), 54–63. <https://doi.org/10.1145/3381831>

Sit, M., Demiray, B. Z., Xiang, Z., Ewing, G. J., Sermet, Y., & Demir, I. (2020). A comprehensive review of deep learning applications in hydrology and water resources. *Water Science and Technology*, 82(12), 2635–2670. <https://doi.org/10.2166/wst.2020.369>

Sohl-Dickstein, J., Weiss, E. A., Maheswaranathan, N., & Ganguli, S. (2015). *Deep Unsupervised Learning using Nonequilibrium Thermodynamics*. <http://arxiv.org/abs/1503.03585>

Strubell, E., Ganesh, A., & McCallum, A. (2019). Energy and Policy Considerations for Deep Learning in NLP. *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, 3645–3650. <https://doi.org/10.18653/v1/P19-1355>


Vaswani, A., Brain, G., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., & Polosukhin, I. (2023). *Attention Is All You Need*.

Xie, W., Sun, G., Li, J., Wang, J., Du, H., Niyato, D., & Dobre, O. A. (2025). Generative AI for Energy Harvesting Internet of Things Network: Fundamental, Applications, and Opportunities. *IEEE Internet of Things Magazine*, 8(3), 72–80. <https://doi.org/10.1109/IOTM.001.2400125>

Yang, Y., Jin, M., Wen, H., Zhang, C., Liang, Y., Ma, L., Wang, Y., Liu, C., Yang, B., Xu, Z., Bian, J., Pan, S., & Wen, Q. (2024). *A Survey on Diffusion Models for Time Series and Spatio-Temporal Data*. <http://arxiv.org/abs/2404.18886>

Yousef, L. A., Yousef, H., & Rocha-Meneses, L. (2023). Artificial Intelligence for Management of Variable Renewable Energy Systems: A Review of Current Status and Future Directions. In *Energies* (Vol. 16, Issue 24). Multidisciplinary Digital Publishing Institute (MDPI). <https://doi.org/10.3390/en16248057>

ISBN 978-2-38236-948-7



9 782382 369487 >



LIVRE DE LYON



livredelyon.com



[livredelyon](https://twitter.com/livredelyon)



[livredelyon](https://www.instagram.com/livredelyon)



[livredelyon](https://www.linkedin.com/company/livredelyon)