

## Experiment 10: A\* Search

### Aim:

Implement an Algorithm in Python for solving A\* Search.

### Python Program:

```
import heapq

class Node:
    def __init__(self, x, y, obstacle=False):
        self.x = x
        self.y = y
        self.obstacle = obstacle
        self.g = float('inf')
        self.h = 0
        self.f = 0
        self.parent = None

    def __lt__(self, other):
        return self.f < other.f

def calculate_heuristic(current, goal):
    return abs(current.x - goal.x) + abs(current.y - goal.y)

def get_neighbors(grid, node):
    neighbors = []
    rows, cols = len(grid), len(grid[0])
    directions = [(1, 0), (-1, 0), (0, 1), (0, -1)]

    for dx, dy in directions:
        x, y = node.x + dx, node.y + dy
        if 0 <= x < rows and 0 <= y < cols and not grid[x][y].obstacle:
            neighbors.append(grid[x][y])

    return neighbors
```

```

def astar(grid, start, goal):
    open_set = []
    heapq.heappush(open_set, start)
    start.g = 0
    start.h = calculate_heuristic(start, goal)
    start.f = start.g + start.h

    while open_set:
        current = heapq.heappop(open_set)

        if current == goal:
            path = []
            while current:
                path.append((current.x, current.y))
                current = current.parent
            return path[::-1]

        for neighbor in get_neighbors(grid, current):
            tentative_g = current.g + 1
            if tentative_g < neighbor.g:
                neighbor.parent = current
                neighbor.g = tentative_g
                neighbor.h = calculate_heuristic(neighbor, goal)
                neighbor.f = neighbor.g + neighbor.h
                if neighbor not in open_set:
                    heapq.heappush(open_set, neighbor)

    return None

if __name__ == "__main__":

    grid = [[Node(x, y, obstacle=False) for y in range(5)] for x in range(5)]
    grid[1][2].obstacle = True
    grid[2][2].obstacle = True
    grid[3][2].obstacle = True

    start_node = grid[0][0]
    goal_node = grid[4][4]

    path = astar(grid, start_node, goal_node)

    if path:
        print("Path found:")
        for x, y in path:
            print(f"({x}, {y})", end=" ")
    else:
        print("No path found.")

```

### Output:

Path found:

(0, 0) (1, 0) (2, 0) (3, 0) (4, 0) (4, 1) (4, 2) (4, 3) (4, 4)

### Result:

Code has been Implemented successfully.