Adaptive Multi-Agent AI Tutoring System for Personalized Programming Education

Project report submitted in partial fulfilment of the requirements for the award of the degree of

BACHELOR OF TECHNOLOGY

in

COMPUTER SCIENCE AND ENGINEERING

Submitted by

Bharath Bommineni	AM.SC.U4CSE23112
Chimmili Lokesh	AM.SC.U4CSE23114
Kataru Reddy Eswar	AM.SC.U4CSE23126
Ramisetti Gowtham Tej	AM.SC.U4CSE23144

Under the guidance of

Ms. Anju Sukumar

School of computing ,Amritapuri



AMRITA SCHOOL OF COMPUTING

AMRITA VISHWA VIDYAPEETHAM

AMRITAPURI CAMPUS

KOLLAM 690525

NOVEMBER 2026

AMRITA VISHWA VIDYAPEETHAM
DEEMED TO BE UNIVERSITY UNDER SECTION 3 OF UGC ACT, 1956

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

Amrita School of Computing, Amritapuri Campus

BONAFIDE CERTIFICATE

This is to certify that the project report entitled "Adaptive Multi-Agent AI Tutoring System for Personalized Programming Education", submitted by Bharath Bommineni (AM.SC.U4CSE23112), Chimmili Lokesh (AM.SC.U4CSE23114), Kataru Reddy Eswar (AM.SC.U4CSE23126) and Ramisetti Gowtham Tej (AM.SC.U4CSE23144), in partial fulfilment of the requirements for the award of the degree of Bachelor of Technology in Computer Science and Engineering at Amrita Vishwa Vidyapeetham, is a bonafide record of the work carried out by them under guidance of Ms.Anju Sukumar and supervision at Amrita School of Computing, Amritapuri, during Semester 7 of the academic year 2026 - 2027.

Ms. Anju Sukumar
Project Guide
Signature _____

Smriti Govind
Project Coordinator
Signature _____

Swaminathan J
Chairperson, CSE
Signature _____

Reviewers
Signature _____

Signature _____

Place: Amritapuri
Date: 11 November 2026

AMRITA VISHWA VIDYAPEETHAM
DEEMED TO BE UNIVERSITY UNDER SECTION 3 OF UGC ACT, 1956

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

Amrita School of Computing, Amritapuri Campus

DECLARATION

We, Bharath Bommineni (AM.SC.U4CSE23112), Chimmili Lokesh (AM.SC.U4CSE23114), Kataru Reddy Eswar (AM.SC.U4CSE23126) and Ramisetti Gowtham Tej (AM.SC.U4CSE23144), hereby declare that the project entitled "Adaptive Multi-Agent AI Tutoring System for Personalized Programming Education" is a record of our original work carried out under the guidance of Ms. Anju Sukumar, Department of Computer Science and Engineering, Amrita Vishwa Vidyapeetham, Amritapuri. To the best of our knowledge, this work has not formed the basis for the award of any degree, diploma, fellowship or similar qualification to any candidate at any university. All sources and contributions of others have been appropriately acknowledged.

Place: Amritapuri
Date: 11 November 2026

Student details	**Signature of the student**
Bharath Bommineni AM.SC.U4CSE23112	_____
Chimmili Lokesh AM.SC.U4CSE23114	_____
Kataru Reddy Eswar AM.SC.U4CSE23126	_____
Ramisetti Gowtham Tej AM.SC.U4CSE23144	_____

Project Guide: Ms. Anju Sukumar

Signature of the Project Guide: _____

ACKNOWLEDGEMENT

We are sincerely grateful to our project guide, Ms. Anju Sukumar, Department of Computer Science and Engineering, for guiding us throughout this project. She kept asking us how a tutor should decide when to help a beginner and how much, and those questions shaped the design of the scaffolding and reflection components. She also reviewed our progress at each stage, which kept our attention on the learner as much as on the technology.

We thank the Project Coordinator and the Chairperson of the Department of Computer Science and Engineering for organising the project reviews and for their feedback. We also thank the faculty members of the department. This work builds on their courses in programming, databases, software engineering and artificial intelligence.

We are grateful to Amrita School of Computing, Amrita Vishwa Vidyapeetham, Amritapuri Campus, for the academic environment and the facilities we used for this project.

We acknowledge the authors and maintainers of the open-source software used in this project, including Python, FastAPI, LangGraph, PostgreSQL, ChromaDB, React and Docker, and the researchers whose published work we review and cite in this report.

Finally, we thank our families and friends for their encouragement and their patience while we worked on this.

Bharath Bommineni
Chimmili Lokesh
Kataru Reddy Eswar
Ramisetti Gowtham Tej

ABSTRACT

A large language model (LLM) assistant will write out the full answer to a beginner's programming exercise in a few seconds. A learner who copies that answer has finished the exercise but skipped the reasoning it was set to practise, and most LLM tutors also keep no lasting record of what the learner knows. In this project we designed and built CodePath, a web-based tutor for novice Python programmers. It implements the Cognitive-State Guided Multi-Agent Adaptive Scaffolding Framework (CSMASF). Six agents run in a cyclic LangGraph workflow after every run, submission or help request. The Diagnostic agent analyses the test results and the program's syntax tree. The Cognitive State agent estimates topic mastery with Bayesian Knowledge Tracing and also tracks confusion, workload and progress. Past situations like the current one are found by the Similar Learner Retrieval agent, which searches ChromaDB by cosine similarity. The Adaptive Scaffolding agent applies the Dynamic Scaffolding Decision Algorithm (DSDA) to decide whether to help, at which of five levels and with which strategy, and then generates the hint and validates it. A Reflection agent asks the learner about their own code and replies to the answer, and a Learning Planner orders practice by technique and difficulty. A hint never contains a complete solution and is never repeated, and the amount of help grows only when the learner asks. The system has 496 verified problems across 17 topics, with 15,717 tests. On the final code, 551 backend tests, 59 browser tests and 21 frontend unit tests passed. We also ran an audit that drives nine real scenarios through all the agents, and it passed all 37 of its behavioural checks. We have not yet carried out a study with real learners, so the effect on learning is still to be measured. The project contributes to United Nations Sustainable Development Goal 4, Quality Education, through Target 4.4: it helps novices acquire programming skills relevant to employment while they stay responsible for their own reasoning.

Keywords: Intelligent tutoring systems; Multi-agent systems; Adaptive scaffolding; Knowledge tracing; Programming education; Large language models

Table of Contents

Acknowledgement i

Abstract ii

List of Figures v

List of Tables vi

1 Introduction 1

1.1 Background and motivation 1

1.2 Objectives 2

1.3 Scope and constraints 3

1.4 Project report organization 4

2 Problem Definition 5

2.1 Problem statement 5

2.2 Existing system and limitations 6

3 Literature Review 7

3.1 Review scope and selection 7

3.2 Descriptive review of literature works 7

3.3 Comparison of reviewed literature 13

4 Requirements 15

4.1 Functional requirements 15

4.2 Non-functional requirements 17

4.3 Hardware requirements 18

4.4 Software and data requirements 18

5 Proposed Methodology **20**

5.1 Design (architecture) or conceptual framework 20

5.2 Proposed approach and procedure 21

6 Results and Analysis **33**

6.1 Evaluation setup 33

6.2 Evaluation criteria 34

6.3 Result 34

6.4 Comparative Analysis 41

6.5 Discussion and Interpretation 42

6.6 Limitations 43

7 Conclusion **44**

7.1 Conclusion 44

7.2 Future work 45

References **46**

A Source Code and Reproducibility **48**

A.1 Setup and execution 48

A.2 Supporting material 49

List of Figures

5.1 System architecture of CodePath 20

5.2 The cyclic learning workflow implemented as a LangGraph graph 22

5.3 Decision flow of the Dynamic Scaffolding Decision Algorithm 27

5.4 Core entities of the data model (simplified; lines show references) 32

6.1 Backend tests per test file (551 in total, all passed) 35

6.2 Agent audit: checks passed per scenario (39 of 39) 35

6.3 First wrong submission: the tutor gives one targeted hint built from the learner's own failing call, values and loop variable, with the concept, a link to the lesson and a "Why this hint?" explanation 37

6.4 Second wrong submission on the same issue: the next hint is only offered, and the offer says once what it will focus on 37

6.5 After three failed attempts: a reflection question about the learner's own loop, and the tutor's reply to the answer "no idea" 38

6.6 After the solve: a question about the technique, and a next step on the same technique without hints, with the route ahead 38

6.7 Home screen after the session: the same next step as the plan, with the route through the course 39

6.8 Teacher dashboard with the clearly labelled synthetic demonstration class; the numbers are generated and are not evidence that the tutor works 39

6.9 Mastery estimates produced by the implemented weighted knowledge-tracing update for three attempt sequences 40

6.10 Curriculum problems per topic and difficulty (496 in total) 40

6.11 Hidden tests by kind of input (14,717 in total) 40

A.1 A topic lesson, opened from the problem's "Read the lesson" link 50

A.2 The practice library, grouping problems by topic in learning order 50

List of Tables

1.1 Objectives, evaluation methods, deliverables and status 2

3.1 Comparison of reviewed literature 13

4.1 Functional requirements 15
4.2 Non-functional requirements 17
4.3 Software used and versions in the tested environment 18

5.1 Isolation applied to each code-execution container 22
5.2 Main diagnostic rules 23
5.3 Evidence weight of each kind of attempt 25
5.4 Help levels and presentation limits 28
5.5 Strategy ladders (level in parentheses) 28

6.1 Evaluation criteria 34
6.2 Results of the automated test suites on the final code 35
6.3 Representative audit checks and recorded evidence 36
6.4 Behaviour before and after the agent improvements 41
6.5 Capabilities of CodePath and closely related systems 42

A.1 Backend test files 50

Chapter 1

Introduction

1.1 Background and motivation

Most engineering and science students now have to learn programming, and many find the first course hard. A stuck beginner needs help that comes quickly and fits what they already understand. A human tutor can give this but cannot cover a large class, and intelligent tutoring systems (ITS) were developed to fill that gap. In a widely cited review, VanLehn found that step-based tutoring systems raised learning outcomes by an effect size of 0.76 against no tutoring, close to the 0.79 of human tutoring [16].

The *amount* of help matters as much as its correctness, and two ideas from learning science explain why. In *scaffolding*, described by Wood, Bruner and Ross, the tutor controls the parts of a task that are beyond the learner so the learner can complete the rest, and withdraws that support as the learner grows more competent [14]. Sweller's cognitive load theory adds that problem solving already loads working memory heavily, so a hint that is too long, or hints that arrive too often, can get in the way of learning [15]. Help-seeking research gives a further caution: learners do not always use on-demand help well, and teaching them to seek help more deliberately does not automatically improve their learning [4].

Large language model (LLM) assistants make the question more pressing. They answer almost any programming question at once, give everyone the same kind of help, and readily produce complete solutions. An eleven-week classroom study of PyTutor, a ChatGPT-based tutor, found clear benefits for students with weak foundations and a risk of over-reliance that may hinder independent problem solving [8]. Tools such as CodeHelp and CodeAid add guardrails so that the assistant does not give away solutions [6, 7], but their published descriptions include no lasting model of each learner that decides how much help to give.

We worked on that gap. We built CodePath, a tutor for novice Python programmers, on the Cognitive-State Guided Multi-Agent Adaptive Scaffolding Framework (CSMASF) proposed in our initial project submission. Its six cooperating agents diagnose each attempt, estimate

the learner's state, look at what helped in similar situations, decide how much help fits, prompt reflection and plan the next problem. We wanted the tutor to behave like a patient teacher sitting beside the student, who gives only the help needed at that moment, never gives the full answer, and leaves the thinking to the student.

Relevant Sustainable Development Goal. The project is aligned with United Nations SDG 4, Quality Education: "Ensure inclusive and equitable quality education and promote lifelong learning opportunities for all" [17]. The most relevant target is Target 4.4: "By 2030, substantially increase the number of youth and adults who have relevant skills, including technical and vocational skills, for employment, decent jobs and entrepreneurship."

The project maps to this target in four ways. Programming skill is in demand, but beginners who receive complete answers from AI tools may not develop it. Our objectives answer this directly, since the tutor adapts the amount of help to each learner and protects the learner's own reasoning (Section 1.2). The contribution is a working, open, web-based tutor with a verified 496-problem Python curriculum, which can run alongside a course at low cost and without a paid model, because every agent has a built-in deterministic mode. The intended beneficiaries are novice programmers, including those with no access to a personal tutor, and teachers, who get a class dashboard showing who may need support. The contribution to Target 4.4 is an *expected* benefit: we have built the system and verified it as software, but we have not yet measured its effect on learners' skills (Chapter 6).

1.2 Objectives

The five objectives come from the initial project submission. Table 1.1 gives each one's evaluation method, deliverable and status at the time of writing.

Table 1.1: Objectives, evaluation methods, deliverables and status

No.	Objective	Evaluation method	Deliverable	Status
O1	Build an adaptive tutor as several collaborating agents instead of one conversational model.	Pipeline tests confirm that all six agents run in order and receive each other's outputs; per-stage traces are inspected.	Six agents in a LangGraph workflow inside a web platform.	Achieved.
O2	Continuously estimate mastery, confidence, confusion, cognitive load and progress from behaviour.	Unit and pipeline tests; audit checks that unknown values stay unknown and that estimates react to repeated requests and progress.	Cognitive State agent (method `cs-1.2`).	Achieved as behavioural estimates; not validated against an external measure.

No.	Objective	Evaluation method	Deliverable	Status
O3	Retrieve similar learners with vector cosine similarity over multidimensional profiles.	Tests of filtering, exclusion of approaches already shown, reliability thresholds and absence of identities in the output.	Retrieval agent over ChromaDB and PostgreSQL (vectors `sv-1`).	Achieved technically; real learner outcomes are not yet available.
O4	Design a scoring algorithm that selects the scaffolding level from mastery, confidence, hint history and response time.	Policy tests, including a documented worked example recomputed by the code; audit checks of escalation and timing.	DSDA, policy version `dsda-2.2`.	Achieved; weights are starting values, not tuned on learners.
O5	Test the framework's effectiveness on programming datasets.	Offline verification of every curriculum problem in the sandbox; scenario audit of all agents; planned learner study.	Verified curriculum, audit tool and evaluation plan.	Partly achieved: software behaviour verified; learning effectiveness not yet measured.

Two more objectives follow from how we wanted the tutor to behave, and they are evaluated in the same way: (i) the tutor never reveals a complete solution, reference solutions or hidden tests, and (ii) help is not repeated and does not increase unless the learner asks.

1.3 Scope and constraints

CodePath is meant for novice and early intermediate learners of Python, typically first-year undergraduates, and for the teachers of such courses. The system includes a browser workspace with an editor, separate Run, Submit and Hint actions, test results and saved drafts, and a curriculum of 17 topics with lessons, 74 techniques and 496 problems. It has the six tutoring agents, typed questions about selected lines, reflection questions and replies, a learning plan with a route ahead, learner progress and profile pages, and a teacher dashboard. A learner can also add a question by pasting it or from a link, with suggested tests always labelled as suggestions.

Four things are outside the scope of this phase. Languages other than Python are not offered. No model is trained: every agent is rule-based, and an LLM is optional and used only for wording. No study with real learners has been carried out. The large IBM Project CodeNet archive was not imported, and only its importer exists. We assume that learners use a modern desktop or mobile browser and that the server host can run Docker containers for code execution.

We worked under three constraints. Development and testing used one laptop with 8 GB of memory, so the test suites had to run one at a time. The code-execution sandbox was tested on Docker Desktop for macOS and has not been independently audited. The only model key we had carried no credit, so the LLM path was tested with a scripted stand-in.

1.4 Project report organization

Chapter 2 defines the problem and the limitations of existing systems. Chapter 3 reviews and compares thirteen research works. Chapter 4 lists the requirements with the hardware, software and data used. Chapter 5 presents the architecture and each agent's inputs, outputs and algorithm. Chapter 6 covers the evaluation setup and criteria, the results, a comparison with existing approaches and the limitations. Chapter 7 concludes with future work, and the appendix gives the setup and reproduction steps.

Chapter 2

Problem Definition

2.1 Problem statement

A beginner working on a programming exercise writes some code, runs it, sees it fail and tries again, usually many times. Each time, a good tutor decides what went wrong in this version of the code, how much the learner already understands, whether to step in, and how much help to give. Too little help leaves the learner stuck and frustrated. Too much help, or the answer itself, takes away the thinking the exercise was set for. The problem we address is to build a tutor that makes these decisions automatically, consistently and transparently for every learner action and never hands over a complete solution.

For each learner action the system receives three inputs. The first is the action itself: Run (try the code on visible examples), Submit (graded against all tests), Ask for a hint (optionally "just a small nudge" or "I need more help"), or a typed question about selected lines. The second is the exact version of the learner's code and the problem it belongs to. The third is this learner's stored history on the problem and topic: earlier attempts and results, hints already shown and whether progress followed, reflection answers, and time spent.

From these it is expected to produce:

- a diagnosis of the attempt, with the evidence that supports it;
- an updated estimate of the learner's state, with "unknown" where evidence is missing;
- a help decision (wait, offer or show help) with a stated level, strategy and reason;
- when help is shown, a new hint specific to the learner's code and free of solution code;
- when useful, one reflection question about the learner's reasoning, with a reply;
- a recommendation of what to do next, with the route ahead.

There are three stakeholders. Learners need help that keeps them thinking. Teachers need to know which learners may need a conversation without reading every submission. The insti-

tution needs a tool that is safe to run on its servers and protects learners' data. If the problem is left unsolved, learners who rely on instant complete answers may pass exercises yet be unable to solve similar problems alone, an over-reliance risk the PyTutor study reported explicitly [8]. Teachers in large courses cannot give every learner timely individual help [6], and running untrusted student code without isolation would expose the server.

2.2 Existing system and limitations

Four kinds of existing solutions are relevant, and their limitations, as reported in the literature we reviewed, define the gap this project addresses. The first kind is the general-purpose LLM assistant, a conversational question-and-answer tool. Such assistants are always available and fluent, but they keep no model of the individual learner, give everyone the same help, and readily produce complete code. The second kind is the LLM programming assistant with guardrails. CodeHelp [6], CodeAid [7] and RAGMan [9] restrict the assistant so that it explains, gives pseudo-code or answers within a course scope without writing solutions. All three were deployed in real courses with positive student feedback, but their published descriptions include no persistent learner model that decides *how much* help each learner should receive, and RAGMan retrieves course material and not what helped similar learners. PyTutor does provide a structured ladder of hints, but one hint type is a coding solution, and its authors observed over-reliance [8].

Classical intelligent tutoring systems, the third kind, model the learner explicitly. In the ACT Programming Tutor, knowledge tracing estimates the probability that each skill has been learned, and that estimate drives mastery learning [1]. Conversational tutors such as DeepTutor showed that tutoring dialogue can be delivered over the web at scale [3]. These systems depend on carefully authored domain models, expensive to build for each new subject. The fourth kind is learner-modelling research. Deep Knowledge Tracing predicts a learner's next answer more accurately than earlier models [2], and newer work simulates learners or verifies tutoring dialogue [11, 12]. These methods predict, simulate or evaluate. Alone, they do not decide when and how much to help a real learner during live programming.

No single system among the works we reviewed combines all of the following for live programming practice: (i) a continuously updated, explainable learner state, (ii) an explicit decision about whether and how much to help that escalates only on request and never reveals a solution, (iii) retrieval of what helped in similar learners' situations, and (iv) reflection and next-step planning that react to the learner's own answers. A survey of LLM applications in programming education concludes similarly that interventions work best with scaffolding and human oversight, while fully automated approaches often miss pedagogical nuance [13]. CSMASF is designed to fill this gap in an open, testable system.

Chapter 3

Literature Review

3.1 Review scope and selection

We reviewed research in four areas: learner modelling, tutoring and hint provision for programming, LLM-based programming assistants, and multi-agent or conversational tutors. We searched the ACM Digital Library, the ACL Anthology, arXiv, the AAAI and IJCAI proceedings, and the Springer and Elsevier journal platforms, using combinations of the keywords *intelligent tutoring system*, *knowledge tracing*, *programming education*, *hint generation*, *LLM programming assistant*, *help seeking*, *scaffolding* and *multi-agent tutoring*.

A work was selected if it was a primary research article in a peer-reviewed venue or a widely used preprint, addressed learner modelling, help provision, programming practice or LLM-based tutoring, and informed a specific design decision in CSMASF. The publication period is 1995 to 2025. We reviewed thirteen works. Nine were listed in the initial project submission, and we added four to cover the foundations of knowledge tracing [1], help-seeking research [4], guardrails for LLM help [6] and multi-agent LLM tutoring [10].

We checked each work's bibliographic details against its publisher or index record (DOI, ACL Anthology, IJCAI, arXiv, Crossref or OpenAlex). Findings are reported as stated in each work's abstract or published record, and numerical values only where they appear there or, for Deep Knowledge Tracing, in its results table. Where the material we consulted does not state a detail, we say so.

3.2 Descriptive review of literature works

The works are presented in order of publication year. Their full titles are in the reference list.

3.2.1 Knowledge tracing

Corbett and Anderson (1995) [1] ask how a tutor can model a student's knowledge as it changes during skill acquisition. In their ACT Programming Tutor, students write short

programs, and the tutor holds a cognitive model of programming made of production rules (the "ideal student model", grounded in ACT-R theory). In *knowledge tracing*, it keeps for every rule an estimate of the probability that the student has learned it. Each rule is either learned or not learned, with parameters for initial knowledge, the chance of learning at each opportunity, guessing and slipping. The estimates drive mastery learning: the tutor presents an individualised sequence of exercises until each rule is mastered. The authors report that the model predicts students' performance on test exercises well. Its cost is the hand-authored rule model that every domain needs. Our Cognitive State agent takes its mastery model from this paper, using the same two-state update with fixed guess, slip and learning parameters, because that is interpretable and needs no training data.

3.2.2 Deep knowledge tracing

Piech et al. (2015) [2] take up the same task for large online learning platforms. They use long short-term memory (LSTM) recurrent networks, which learn from response sequences and need no expert annotation of the skills behind each exercise. The study uses simulated students, Khan Academy mathematics data (47,495 students, 69 exercise tags, about 1.4 million answers) and the ASSISTments benchmark (15,931 students, 124 exercise tags, about 526 thousand answers). The model is evaluated on predicting the next response, by area under the ROC curve (AUC) with five-fold cross-validation on the real datasets. The reported AUC is 0.85 on the Khan data against 0.68 for standard Bayesian Knowledge Tracing (BKT), 0.86 on ASSISTments against the best previously reported 0.69 (a 25% gain), and 0.82 on simulated data against 0.54 for BKT. The model predicts performance but does not decide what help to give, and its internal state is harder to interpret than BKT's parameters. We kept BKT, the baseline in this paper, because it is interpretable. A learned model becomes an option once real interaction data exists.

3.2.3 DeepTutor

Rus, Niraula and Banjade (2015) [3] ask how educational technology can deliver instruction tailored to each learner. DeepTutor is a conversational ITS delivered as a web application, so learners can reach it at any time from a browser-connected device. It was used in large-scale experiments with high-school students, which the authors report as evidence that conversational tutoring can work at scale over the web. The published abstract gives no detailed metrics. The system predates current LLMs and is not designed for programming practice with code execution. Its result that dialogue-based tutoring can be delivered at scale through the web supports CodePath's browser-based design and its conversational reflection step.

3.2.4 Help seeking with intelligent tutors

Aleven, Roll, McLaren and Koedinger (2016) [4] study how learners seek and use on-demand help. They built the Help Tutor, an agent that gave students real-time, in-context feedback on their help-seeking behaviour, driven by a knowledge-engineered, rule-based executable model of help seeking. A classroom study measured help-seeking behaviour and domain learning, and the paper adds a theoretical analysis and a review of later empirical work. The feedback made students use on-demand help more deliberately, and the effect lasted after the feedback stopped, but domain-level learning did not improve. The authors now place less weight on on-demand, principle-based help during problem solving, though they still recommend that tutors include it, and they call helping students become better self-regulated learners an open challenge. Three of our decisions come from this paper: unrequested help is offered and shown only if accepted, help climbs only when the learner asks, and the help is designed to keep the learner thinking.

3.2.5 Project CodeNet

Puri et al. (2021) [5] respond to the lack of large, diverse datasets for training AI models on coding tasks. CodeNet has over 14 million code samples, about 500 million lines of code, in 55 programming languages. The samples are submissions to online programming problems, annotated to support code similarity and classification, translation between languages, and runtime and memory improvement. Sample input and output tests are provided for 98.5% of them. The authors supply preprocessing tools that turn source code into model inputs, and they report baseline results for code classification and code similarity. CodeNet holds submissions and their outcomes but no records of tutoring, hints or learner states, so by itself it does not support learner modelling or tutoring. For us it is a candidate data source for offline evaluation. CodePath's CodeNet importer aggregates problem statistics and was tested on a fixture, but the archive itself was not imported in this phase.

3.2.6 CodeHelp

Liffiton, Sheese, Savelka and Denny (2023) [6] write about large computing classes, where students need timely help but should not be encouraged to over-rely on LLMs. CodeHelp is an LLM-based tool with guardrails, so it helps students without revealing solutions. It has instructor-facing features and uses a sequence of prompting strategies to keep its outputs suitable for students. It was used in a first-year computer and data science course with 52 students over 12 weeks, and the evaluation covers usage patterns, student perceptions and the instructor's reflections. Students valued the tool's availability and its help in resolving errors. Instructors found it easy to deploy, and it complemented their support without replacing it. The published description has no per-learner model that adapts the amount of help over time. CodePath's rule that help never contains a solution comes from this work, as does its

validator, which checks every hint before it is shown.

3.2.7 CodeAid

Kazemitabaar et al. (2024) [7] wanted an LLM assistant that gives students helpful, technically correct support without revealing code solutions. CodeAid answers conceptual questions, produces pseudo-code with explanations and suggests fixes for incorrect student code. It was deployed for 12 weeks in a course with 700 students. The authors analysed about 8,000 uses together with weekly surveys and 22 student interviews, and then interviewed eight educators. They derive four design considerations: exploit what AI uniquely offers, simplify query formulation while promoting cognitive engagement, avoid direct answers while encouraging motivated learning, and keep the assistant transparent and controllable for students. The published description includes neither a continuous learner model nor retrieval of what helped similar learners. Two CodePath features follow from this work: typed questions are answered from what the selected lines actually did, and the "Why this hint?" explanation gives transparency.

3.2.8 PyTutor

Yang, Lin, Lin and Ogata (2024) [8] test whether a ChatGPT-based tutoring system can help beginners learn Python. PyTutor gives continuous guidance, problem-solving hints and code explanations. Each question has a structured set of hints covering pseudocode, cloze, basic and advanced coding solutions. In an eleven-week experiment 35 students used PyTutor and 36 did not, and the authors compared engagement, completion and success rates in in-class and after-class exercises. PyTutor was especially effective for students with weak foundations, who showed higher engagement, completion and success. The authors also identify a risk of over-reliance that may hinder independent problem-solving skills, and they recommend balanced use. A single LLM generates the help, and the hint set includes coding solutions. The study supports a graded ladder of help, and its over-reliance finding is the reason for two CodePath rules: no level contains a solution, and unrequested help is only offered.

3.2.9 Integrating AI tutors in a programming course

Ma, Krone Martins and Lopes (2024) [9] deal with course-specific AI tutoring for programming homework. Their system, RAGMan, is LLM-powered and supports course-specific and homework-specific tutors through retrieval-augmented generation and strict instructions. An introductory programming course with 455 students offered it as five optional homework-specific tutors. The authors evaluate usage, in-scope answer accuracy and student perceptions. About half of the students used the tutors, mostly for legitimate homework questions. Within scope the tutors answered accurately 98% of the time. Of the students who used them,

78% said the tutors helped their learning, and students valued the non-judgmental environment. The outcomes are largely self-reported. RAGMan retrieves course content, whereas CodePath retrieves what helped in similar *learner situations*.

3.2.10 Ruffle&Riley

Schmucker, Xia, Azaria and Mitchell (2024) [10] look at how LLMs can lower the cost of authoring conversational tutoring systems. Their system generates an editable tutoring script from a lesson text and then runs a learning-by-teaching format in which two LLM agents play a student and a professor. The evaluation used biology lessons in two between-subject online studies with 200 participants in total, and compared the system with simpler question-answering chatbots and a reading activity. Users found the system engaging and helpful, felt they understood the material and spent more time on the activity, yet their short-term learning gains did not differ significantly from those of the reading activity. The domain is not programming. The paper shows that several cooperating agents can structure a tutoring interaction. It also cautions that engagement and perceived helpfulness are not evidence of learning, which is why this report claims no learning gains without a learner study.

3.2.11 CoderAgent

Zhan et al. (2025) [11] start from a practical difficulty: real programming data is scarce, and offline evaluation of personalised programming tutoring often does not match real learning. They propose CoderAgent, an LLM-based agent inspired by the ACT-R cognitive architecture, which simulates students' iterative programming processes. It models programming knowledge and coding ability, and its Programming Tree of Thought breaks each step into why, how, where and what. The study uses real-world datasets, including a Python subset of CodeNet and a college-level Java dataset (CSEDM). The simulation is evaluated on four predictions (a student's next modification intention, its location, the next submission and whether that submission will be accepted), measured by accuracy, CodeBLEU and AUC. The authors report that CoderAgent gives interpretable insights into learning trajectories and simulates students accurately. It simulates learners and does not tutor them in real time, so for us it is a possible way to test tutoring policies offline before a learner study.

3.2.12 TRAVER

Wang, Dai, Zhang, Ma, Li and Chai (2025) [12] study how LLM tutoring agents can proactively guide learners to complete predefined coding tasks. Their method, Trace-and-Verify (TRAVER), has two parts: knowledge tracing estimates the student's knowledge state, and turn-by-turn verification keeps the tutor's guidance on track. The paper also introduces DICT, an automatic evaluation protocol based on controlled student simulation and code-generation tests. The authors report that coding tutoring is challenging and that TRAVER

achieves a significantly higher success rate. The evaluation relies on simulated students, and the approach includes neither retrieval of similar learners' experience nor an explicit decision about how much help to give. CodePath pairs a learner-state estimate with a verification step in a similar way, since a validator checks every hint before it is shown.

3.2.13 Survey of LLM applications in programming education

The last work is a survey. Pitts, Hridi and Lekshmi Narayanan (2025) [13] ask how LLMs can scale timely, personalised support for novice programmers when instructor time is limited. They survey recent LLM applications in formative code feedback, assessment and knowledge modelling. The published abstract does not state how many works were reviewed. The authors identify recurring design patterns and report that interventions work best when educator expertise complements model output through human-in-the-loop oversight, scaffolding and evaluation, while fully automated approaches often fail to capture the pedagogical nuances of programming education. They call for greater transparency, closer alignment with pedagogy and systems that adapt to varied learning contexts. Being a survey, the paper proposes and evaluates no system. Three CodePath design choices follow its conclusions: the policy, and not an LLM, controls the help decisions, every decision is explained, and teachers get a dashboard.

3.3 Comparison of reviewed literature

Table 3.1 compares the reviewed works. “Not reported” means that the detail is not stated in the material we consulted, and “Not applicable” means that it does not apply to that work.

Table 3.1: Comparison of reviewed literature

Work and citation	**Problem or objective**	**Approach and contribution**	**Study context**	**Evaluation criteria**	**Key findings**	**Limitations and gap**
Work 01 [1] Corbett and Anderson, 1995	Model changing knowledge during skill learning	Knowledge tracing: probability each rule is learned, used for mastery learning	ACT Programming Tutor; students writing short programs	Prediction of performance on test exercises	Predicts test performance well	Needs hand-authored rule model per domain
Work 02 [2] Piech et al., 2015	Predict student performance over time	LSTM-based Deep Knowledge Tracing without expert skill labels	Simulated data, Khan Academy, ASSISTments	AUC, 5-fold cross-validation	AUC 0.86 vs 0.69 (ASSISTments); 0.85 vs 0.68 (Khan)	Predicts but does not choose help; less interpretable
Work 03 [3] Rus et al., 2015	Tailor instruction to each learner	DeepTutor, a web-based conversational ITS	Large-scale experiments with high-school students	Experimental evidence at scale	Conversational ITS shown to work at scale over the web	Pre-LLM; not designed for programming
Work 04 [4] Aleven et al., 2016	Improve learners’ use of on-demand help	Help Tutor feedback; rule-based model of help seeking; review	Classroom study with tutoring systems	Help-seeking behaviour; domain learning	More deliberate help use, lasting; no gain in domain learning	Self-regulated help use remains an open challenge
Work 05 [5] Puri et al., 2021	Lack of large AI-for-code datasets	CodeNet: over 14M samples, 55 languages, with tests	Online programming submissions	Baseline classification and similarity results	Test cases for 98.5% of samples	No tutoring or learner-state data
Work 06 [6] Liffiton et al., 2023	Scalable help without over-reliance	CodeHelp: LLM with guardrails, no solutions	First-year course, 52 students, 12 weeks	Usage patterns, perceptions, instructor reflection	Valued availability and error help; easy to deploy	No per-learner adaptive model reported

Work and citation	Problem or objective	Approach and contribution	Study context	Evaluation criteria	Key findings	Limitations and gap
Work 07 [7] Kazemitabaar et al., 2024	Helpful support without revealing code	CodeAid: conceptual answers, pseudo-code, fix suggestions	12 weeks, 700 students, about 8,000 uses	Usage logs, surveys, 22 student and 8 educator interviews	Four design considerations for AI assistants	No continuous learner model or similar-learner retrieval reported
Work 08 [8] Yang et al., 2024	Help beginners learn Python	PyTutor: ChatGPT ITS with structured hints	11 weeks; 35 users vs 36 non-users	Engagement, completion and success rates	Most effective for weak-foundation students; over-reliance risk	Single LLM; hints include coding solutions
Work 09 [9] Ma et al., 2024	Course-specific AI tutoring	RAGMan: retrieval-augmented, homework-specific tutors	Intro course, 455 students, 5 tutors	Usage, in-scope accuracy, perceptions	About half used; 98% accurate in scope; 78% said it helped	Retrieves course content only, no learner experience; self-report
Work 10 [10] Schmucker et al., 2024	Cheaper authoring of conversational tutors	Ruffle&Riley: scripts from lesson text; two LLM agents	Biology lessons; 2 online studies, 200 participants	Engagement, perceptions, learning gain	Engaging and helpful; no significant learning difference vs reading	Not programming; engagement is not learning
Work 11 [11] Zhan et al., 2025	Evaluate tutoring with scarce data	CoderAgent: ACT-R-inspired LLM simulation of programming	CodeNet Python subset; CSEDM Java	Accuracy, CodeBLEU, AUC on next-step tasks	Interpretable, accurate simulation	Simulation only; no live tutoring
Work 12 [12] Wang et al., 2025	Proactive guidance in coding tutoring	TRAVER: knowledge tracing plus turn-by-turn verification; DICT protocol	Simulated students; code-generation tests	Task success rate	Significantly higher success rate	Simulated evaluation; no help-amount decision or retrieval
Work 13 [13] Pitts et al., 2025	Scale personalised novice support	Survey of feedback, assessment and knowledge modelling	Recent LLM programming-education studies	Not applicable (survey)	Human-in-the-loop and scaffolding work best	Not reported (count of works); proposes no system

Chapter 4

Requirements

4.1 Functional requirements

There are three actors: the learner, the teacher and the system (the tutoring agents). Table 4.1 lists the functional requirements. Each acceptance criterion is checked by automated tests, either named in the table or listed in Appendix A. Files named `test_*.py` are backend tests, and "browser" means the Playwright end-to-end suite.

Table 4.1: Functional requirements

ID	**Requirement**	**Actor**	**Input and expected behaviour or output**	**Acceptance criterion**
FR1	Accounts and onboarding	Learner, teacher	Register, sign in, or start a labelled demo session; a short onboarding records experience and goal.	Browser: real accounts work; demo access is labelled; signed-out visitors are sent to sign in.
FR2	Curriculum and lessons	Learner	Browse 17 topics in learning order; each topic has a lesson per technique with runnable examples.	Browser: the path shows position and leaves every topic open; a topic teaches first, then offers problems by technique.
FR3	Code workspace	Learner	Editor with Python highlighting, find and replace, font size and saved drafts.	Browser: drafts survive a refresh; the editor behaves like a code editor.
FR4	Run	Learner	Run code on visible examples or own test cases; not graded.	`test_hint_request_is_not_a_graded_attempt`; browser: Run, Submit and Hint are separate.
FR5	Submit and results	Learner	Grade against public and hidden tests in the sandbox; results name the code version they belong to.	`test_older_results_never_overwrite_newer_state`; duplicate clicks create one attempt.

ID	Requirement	Actor	Input and expected behaviour or output	Acceptance criterion
FR6	Diagnose each attempt	System	Output category, issue label, evidence, likely cause and comparison with the previous version.	`test_diagnosis.py` (69 tests); audit checks on syntax, runtime and logic issues.
FR7	Estimate learner state	System	Update mastery (with range) and confusion, workload and progress, or report "unknown".	`test_unknown_confidence_is_left_out_not_assumed`; `test_cognitive_state_updates_from_repeated_requests`.
FR8	Retrieve similar situations	System	Suggest a level and strategy from similar past situations, or report no reliable match; no identities or code.	`test_retrieval_output_exposes_no_identities_or_code`; `test_retrieval_does_not_suggest_what_this_learner_already_saw`.
FR9	Decide help (DSDA)	System	Decide wait, offer or show; choose level and strategy; never more than one level up; unrequested help after a hint is only offered.	`test_policy.py` (30 tests), including `test_help_never_climbs_the_ladder_without_a_request`.
FR10	Generate and validate hints	System	Write a hint from the learner's own evidence; reject repeats, vague advice, invented lines and solution code; retry or fall back.	`test_repeated_requests_never_show_the_same_hint`; `test_never_returns_the_solution_through_the_ladder`.
FR11	Questions about code	Learner	Ask a typed question or select lines; the answer uses what the lines really did on a visible example.	Browser: asking about selected lines still runs the agents and answers.
FR12	Reflection	System, learner	Ask one question about the learner's own code when useful; reply to the answer without grading.	`test_reflection_and_planner.py` (27 tests); browser: a reflection answer gets a reply.
FR13	Learning plan	System	Recommend the next problem with a reason and show the route ahead; the home screen agrees with the plan.	`test_planner_keeps_unresolved_task_active`; `test_home_agrees_with_the_plan_after_a_first_try_solve`.
FR14	Progress and profile	Learner	Show solved problems, activity, per-topic state with evidence, and improvement measures.	Browser: the profile shows what was done and each topic's learning state.
FR15	Teacher dashboard	Teacher	Show class measures and learners who may need support; open a student's profile.	Browser: a student's numbers match the teacher's; teacher demo labels its data as synthetic.

ID	Requirement	Actor	Input and expected behaviour or output	Acceptance criterion
FR16	Add a question	Learner	Paste a question or give a link; review parsed fields; suggested tests are labelled, never presented as official.	`test_link_import.py` (90 tests); browser Add Question flows.
FR17	Preferences	Learner	Theme, learning mode, automatic hints and editor settings are saved per account.	Browser: theme persists; font size persists across sessions.

4.2 Non-functional requirements

Table 4.2 gives the quality requirements with measurable criteria. A value marked "configured" is a limit set in the code, not measured performance.

Table 4.2: Non-functional requirements

ID	Quality	Requirement and measurable criterion	Verification
NFR1	Security of execution	Student code is untrusted. Each job runs in a fresh container with no network, a read-only root filesystem, all capabilities dropped, an unprivileged user, 256 MB memory, one CPU and at most 64 processes (configured).	Execution-service suite (39 tests, including isolation attacks).
NFR2	Solution protection	No response contains a reference solution, hidden test values or hidden-test output; no hint level contains a complete solution.	`test_hidden_tests_never_reach_the_client`; `test_reference_solution_never_reaches_the_client`; validator tests.
NFR3	Privacy	Retrieval returns only aggregates; learners are stored only as a hash in pooled cases; pooling requires consent.	`test_retrieval_output_exposes_no_identities_or_code`; `test_profile_shows_similar_learners_only_as_counts`.
NFR4	Reliability	A failing agent falls back to a safe default; an execution-service failure is never counted as a learner mistake; a repeated request with the same idempotency key creates one record.	`test_service_failure_is_not_treated_as_learner_mistake`; `test_model_failure_uses_labelled_fallback`; idempotency tests.
NFR5	Explainability	Every decision carries reason codes and a learner-facing reason; every stage writes a trace row.	Audit reads each agent's output from its trace.
NFR6	Robustness to manipulation	Instructions hidden in student code cannot change the policy.	`test_prompt_injection_in_code_cannot_change_the_policy`.

ID	Quality	Requirement and measurable criterion	Verification
NFR7	Accessibility	No violations of automated WCAG 2.0 and 2.1 level A and AA rules on the main screens, in both themes; no sideways scrolling at phone width.	Browser accessibility suite (axe-core) and phone-layout test.
NFR8	Fair use	Per-user limits per minute (configured): 30 runs, 15 submissions, 15 hints, 12 sign-in attempts, 20 imports. A saved draft may hold at most 20,000 characters, and code sent to run, submit or ask is limited to 100,000 characters by request validation.	`test_rate_limit` (with the run limit set to two per minute, the third run is refused with status 429); a longer draft is refused with status 413.
NFR9	Responsiveness	Per-test time limit 2 s by default, total job limit at most 25 s, at most 3 concurrent jobs with a queue of 12 (configured).	Execution-service tests; timeout scenario in the audit.
NFR10	Maintainability	All policy weights, thresholds and ladders live in one versioned file (`policy.yaml`); each hint records the policy version.	Policy tests; recorded `policy_version`.

4.3 Hardware requirements

No special hardware is needed, because no model is trained and the optional LLM is reached over the network.

- Development and testing used an Apple MacBook Air (Apple M2 processor, 8 GB of memory) running macOS 27.2 with Docker Desktop 29.8.
- The deployment server must be a 64-bit machine able to run Docker containers. Each code job starts a container with a 256 MB memory limit and up to three jobs run at once, on top of the memory for the database, API and vector store. No GPU is required.
- A learner can use any device with a current web browser, at phone, tablet or desktop width.

4.4 Software and data requirements

Table 4.3 lists the main software with the versions installed in the tested environment.

Table 4.3: Software used and versions in the tested environment

Component	Version	Role
Python	3.12.13	Backend and execution service; the sandbox image uses Python 3.12 slim.
FastAPI, Uvicorn	0.162.2, 0.54.0	HTTP API [21].
Pydantic	2.14.3	Typed contracts between agents.

Component	Version	Role
LangGraph, checkpoint-postgres	1.2.20, 3.2.0	Agent graph, pause and resume [19].
SQLAlchemy, Alembic, psycopg	2.1.8, 1.20.1, 3.3.8	Database access and five migrations.
PostgreSQL	16.15	Main database and graph checkpoints.
ChromaDB	1.5.9	Vector store with cosine HNSW index [20, 18].
httpx	0.28.1	Calls to the execution service and optional LLM providers.
Docker	29.8.0	Isolated execution of student code.
Node.js	26.4.0	Frontend build and browser tests.
React, React Router	18.3.1, 6.30.1	Web interface.
TypeScript, Vite	5.8.3, 6.3.5	Typed frontend code and build tool.
CodeMirror	6 (view 6.36.8)	Code editor with Python support.
TanStack Query, Radix UI	5.80.7, 1.x and 2.x	Server state and accessible interface components.
pytest, Vitest, Playwright	9.2.0, 3.2.4, 1.53.1	Backend, unit and browser tests [22].
axe-core for Playwright	4.10.2	Automated accessibility checks [23].

The system uses the following data.

- The curriculum, authored for the project, has 17 topics, 74 techniques and 496 Python problems (237 easy, 218 medium, 41 hard). Each problem has a statement, starter code, a reference solution kept on the server, and tests.
- There are 15,717 tests: 1,000 visible examples and 14,717 hidden. Of the total, 2,665 were written with the curriculum and 13,052 were generated from each problem's examples or a problem-specific input generator. Generated tests take their expected answers from the reference solution, and every test, written or generated, is checked against it. In all, 487 problems have 30 or more tests (median 32). In the real sandbox, each reference solution passes all of its tests and each starter fails.
- The similar-situation records are pooled, anonymous outcomes of real hints, stored only for consenting real accounts. Synthetic demonstration records also exist, always labelled, and can be switched off.
- For IBM Project CodeNet [5], we built an importer that aggregates problem statistics and tested it on a small fixture. The archive was not imported in this phase.
- Questions added from links are read only where the site's terms and `robots.txt` permit. Otherwise the link supplies attribution and the learner pastes the statement.

Chapter 5

Proposed Methodology

5.1 Design (architecture) or conceptual framework

CodePath is a three-tier web application, with a separate, isolated service for running student code. Figure 5.1 shows the components and how they communicate.




Figure 5.1: System architecture of CodePath

The web application is a single-page React application. It provides the learner workspace (editor, test cases, results and the tutor pane), the learning path with lessons, the practice library, search, progress and profile pages, settings and the teacher dashboard. It talks to the backend only through a typed JSON API, and its TypeScript types are generated from the backend's OpenAPI schema.

In the backend, FastAPI routers handle authentication (Argon2-hashed passwords and server-side sessions), the workspace (drafts, runs, submissions, hints, questions and reflections),

content, imports, learner data and teacher views. The tutoring service queues each learner's actions so that they are processed in order. It attaches an idempotency key, so a double click creates one record, and it starts the agent pipeline in a worker thread. The browser polls the run and shows the real status of each stage.

The six agents run as nodes of a LangGraph graph (Section 5.2.1). Each agent has a typed input and output contract, written as Pydantic models, and reads the learner's stored history from the database. There are two data stores. PostgreSQL holds the 25 application tables (Section 5.2.9) and the LangGraph checkpoints, which let a paused learning cycle resume. ChromaDB stores the 14-dimensional situation vectors used for similar-learner retrieval and searches them with cosine similarity over an HNSW index [20, 18]. The outcomes behind each vector are stored in PostgreSQL.

Student code is never run inside the API process. A separate execution service receives the code and tests over HTTP, starts a fresh, locked-down Docker container for each job, runs the tests through a small trusted harness and returns structured results. The LLM gateway is optional. It is a provider-neutral adapter that can call OpenAI, Anthropic or a local Ollama model to reword hints, and it is off by default (`LLM_PROVIDER=none`). Every caller has a deterministic built-in alternative, so tutoring never depends on a model.

5.2 Proposed approach and procedure

5.2.1 The learning cycle

The same graph processes every learner action, whether it is a Run, a Submit, a hint request or a typed question (Figure 5.2). The graph state (`TutorState`) carries only the current cycle. A history loader reads anything earlier from the database, which is how the agents remember earlier hints, attempts and answers across requests.

The graph has four conditional edges, implemented by the routing functions in `graph.py`.

- After `evaluate`, if the code could not be checked (service failure or cancellation), every agent is recorded as skipped and the cycle goes straight to `finalize`, so a service problem is never treated as a learner mistake.
- After the Cognitive State agent, retrieval is skipped when the problem is solved, because there is no help to choose.
- After DSDA, hint generation runs only when the decision is to show help. An offer generates nothing, and accepting it starts a new cycle.
- After validation, a rejected draft returns to generation at the same level and strategy, at most three times in total.

After `finalize`, the `await_learner` node calls LangGraph's `interrupt`. The PostgreSQL




Figure 5.2: The cyclic learning workflow implemented as a LangGraph graph

checkpointer saves the state under a thread for that learner and problem, and nothing runs until the learner acts again. No loop in the graph can generate more help by itself. Each node runs inside a guard that records an `agent_steps` row (status, input and output summaries, retries, duration). If the node fails, the guard substitutes a safe fallback output so that the cycle still completes.

5.2.2 Code execution and grading

Table 5.1 lists the isolation applied to every job. Inside the container, the harness also sets operating-system resource limits (CPU time, address space, file size and open files), and it records a trace of selected lines when a learner asks about them.

Table 5.1: Isolation applied to each code-execution container

Setting	**Effect**
`-network none`	No network access.
`-read-only`, `-tmpfs /tmp` (32 MB, `noexec`)	Read-only root filesystem; a small temporary folder from which programs cannot be executed.
`-memory 256m`, `-cpus 1`, `-pids-limit 64`	Bounded memory, CPU and number of processes.
`-cap-drop ALL`, `no-new-privileges`, `-user 65534`	No Linux capabilities, no privilege escalation, unprivileged user.

Setting	Effect
`-ipc private`, `-log-driver none`, core dumps off	No shared memory with the host, no logs kept, no core files.
Image `python:3.12-slim` without `pip`	Only the standard library and the trusted harness are available.

To grade a test, the service converts the returned value and the expected value to a canonical form and compares them. Integers must match exactly. Floating-point values are equal within a relative and absolute tolerance of 10^{-9}. Booleans equal only Booleans. Lists are compared element by element and dictionaries by keys and values, and for tasks where order does not matter both lists are sorted first. Printed output is compared after normalising line endings and trailing spaces. Each test receives a category (passed, wrong answer, runtime error, time limit and so on). The overall verdict is *accepted* if all tests pass, *syntax error* if the code cannot be parsed, *partial* if some tests pass, and otherwise the most serious failure. The inputs, expected values and printed output of hidden tests never leave the server.

5.2.3 Agent 1: Diagnostic

The Diagnostic agent explains what went wrong in this exact version of the code and gives its evidence, keeping observed facts separate from inferred misconceptions. Its inputs are the verdict and per-test results, the code, the problem (function name, concepts), recent issue labels, the previous attempt and the number of hint requests on the same code.

It outputs a category and a stable issue label such as `logic:off_by_one`. It also outputs facts, each tagged with its source (runner, tests or code analysis), inferences with a confidence, the affected lines, a confidence value in $[0, 1]$ and the repeat count. The remaining outputs are the failing visible example (input, value returned, value expected), facts about the main loop (its line, source and variable, and the variable it builds up), and a comparison with the previous version.

The agent is rule-based and deterministic. It uses Python's `ast` module to analyse the code's structure without running it, regular expressions over Python's error messages, and `difflib` to find changed lines. Table 5.2 summarises the main rules.

Table 5.2: Main diagnostic rules

Verdict	Evidence used	Issue label
Syntax error	Python's message, e.g. "expected ':'", "was never closed", indentation errors, unterminated strings, "maybe you meant '==' "; line from Python	`syntax:missing_colon`, `syntax:unbalanced_bracket`, `syntax:indentation`, ...

Verdict	**Evidence used**	**Issue label**
Time limit	A `while` loop whose condition variables are never updated in its body; a recursive function with no base case	`timeout:loop_no_progress`, `timeout:recursion_no_base`, `timeout:general`
Runtime error	Exception type and message matched against a table of causes; for `NameError` and `UnboundLocalError`, where the name is defined relative to where it is used	`runtime:TypeError:mix_text_number`, `runtime:UnboundLocalError:used_before_assignment`, …
All answers `None`	Empty body; `print` instead of `return`; no `return`	`logic:not_implemented`, `logic:print_instead_of_return`, `logic:missing_return`
Wrong answer	A `return` as a direct child of a loop body	`logic:early_return_in_loop`
Wrong answer	Every numeric answer differs by exactly 1, or by exactly one of the input's end values, plus a `range` loop	`logic:off_by_one`
Wrong answer	Same items in a different order; only spacing or capitalisation differs; wrong type	`logic:wrong_order`, `logic:text_format`, `logic:wrong_return_type`

Take the code in Figure 6.3, which loops over `range(1, n)`. The call `sum_to_n(3)` returns 3 where 6 is expected. The difference, 3, equals the input $n = 3$, which is an end value of the range, so the agent reports `logic:off_by_one` on line 3. The comparison with the previous version records whether the code changed, which lines changed, whether the issue is the same, and whether the new version gets further. Getting further is judged by the order syntax error $<$ crash $<$ wrong answer $<$ partial $<$ accepted and by the change in tests passed.

5.2.4 Agent 2: Cognitive State

The Cognitive State agent estimates topic mastery, confidence, confusion, cognitive load and progress, each with its evidence. A value without enough evidence is left unknown. Its inputs are the topic's previous mastery and evidence weight, the current result (category, pass ratio, graded or not, same code as before), the problem's difficulty and origin, earlier attempts on the problem, the hints used and their highest level, hints not followed by progress, active time, the learner's own ratings, the latest reflection answer and requests on unchanged code.

For mastery the agent uses a weighted form of Bayesian Knowledge Tracing, built on the two-state knowledge tracing model of Corbett and Anderson [1]. With prior mastery p, guess probability $g = 0.20$, slip probability $s = 0.10$ and learning probability $t = 0.12$ (fixed

in `policy.yaml`), the posterior after an observation is

$$p_{|\text{obs}} = \begin{cases} \dfrac{p(1-s)}{p(1-s)+(1-p)\,g} & \text{if solved,} \\ \dfrac{p\,s}{p\,s+(1-p)(1-g)} & \text{otherwise,} \end{cases} \qquad p_{\text{learn}} = p_{|\text{obs}} + (1-p_{|\text{obs}})\,t. \tag{5.1}$$

Standard BKT applies this update in full. Our version weights it by how much the attempt counts as evidence:

$$p_{\text{new}} = p + w\,(p_{\text{learn}} - p), \tag{5.2}$$

where the weight w is given in Table 5.3. Runs, hint requests and resubmissions of unchanged code have $w = 0$, so they leave mastery unchanged. Mastery starts at 0.20. From there, one failed attempt ($w = 0.8$) gives 0.157 and one solve without help ($w = 1$) gives 0.586.

Table 5.3: Evidence weight of each kind of attempt

Attempt	**Weight** w
Solved without hints	1.0
Solved after hints, by highest hint level L0 to L4	1.0, 0.8, 0.6, 0.35, 0.2
Logic failure (wrong answer, partial, runtime error, missing function)	0.8
Time, memory or output limit	0.6
Syntax error	0.15
Imported (learner-added) problem	weight above $\times 0.5$
Run, hint request, or the same code resubmitted	0

The total evidence E is the sum of the weights so far. Mastery is shown with a range $p \pm 0.35/\sqrt{1+E}$, clipped to $[0,1]$, so the range narrows as evidence accumulates. It is also shown with a band: "not enough evidence" while $E < 1.5$, then starting ($p < 0.40$), developing (< 0.65), proficient (< 0.85) or strong.

Confusion is estimated by counting signals: the same issue in two or more attempts in a row; a hint not followed by progress; the kind of error changing across three attempts; the learner saying they feel stuck; an unsure reflection answer; two or more requests on unchanged code; and a hint marked unhelpful. With no history and no signals the value is *unknown*, because one failure is not evidence of confusion. One signal gives moderate, and two or more give high.

Cognitive load is counted in the same way. Its signals are active time above twice the usual for the difficulty (easy 4, medium 10, hard 20 minutes), three or more hints on the problem, three attempts in a row passing no tests, and the learner saying the task feels like a lot. A single long pause is treated as moderate at most, because it may be a break.

Progress is one of solved, improving (the code gets further, or more tests pass than the best so far), regressing, stalled (the same issue repeating), steady or unknown. Confidence comes only from the learner's own rating and is never inferred.

5.2.5 Agent 3: Similar Learner Retrieval

The Similar Learner Retrieval agent looks for past situations similar to the current one and reports which kind of help was followed by progress, or reports that there is no reliable match. Each situation is stored as a vector. Eight state values are mapped from $[0,1]$ to $[-1,1]$ by $c(x) = 2(x-0.5)$ and six category slots are added, giving the 14-dimensional vector

$$\mathbf{v} = \big(c(m), c(\kappa), c(f), c(\ell), c(r), c(d), c(\min(a,6)/6), c(\min(h,4)/4), \mathbf{e}\big), \tag{5.3}$$

where m is mastery, κ confidence, f confusion, ℓ load, r progress, d difficulty, a attempts, h hints and $\mathbf{e}$ has 0.8 for the current error category (syntax, runtime, wrong answer, partial, timeout, resource) and -0.1 for the others. The centring is needed because cosine similarity ignores vector length, so without it a weak learner and a strong learner would point in the same direction. Similarity is

$$\mathrm{sim}(\mathbf{u},\mathbf{v}) = \frac{\mathbf{u}\cdot\mathbf{v}}{\|\mathbf{u}\|\,\|\mathbf{v}\|}. \tag{5.4}$$

ChromaDB returns up to 150 nearest stored situations in the same category group. The agent then reads the corresponding outcome records from PostgreSQL and filters them. A case is kept only if it belongs to another learner (owners are compared by a SHA-256 hash), has similarity of at least 0.72, has a usable outcome, differs in difficulty by at most 0.35, and shares the issue or the topic. At least five such candidates are required. Measured ("live") cases are preferred when at least five exist, and otherwise labelled synthetic cases may be used. The candidates are grouped by (level, strategy), leaving out strategies this learner has already seen on the issue, and the agent chooses the group with the best cautious success rate:

$$\hat{p} = \frac{k+1}{n+2}, \qquad \mathrm{LB} = \hat{p} - \sqrt{\frac{\hat{p}(1-\hat{p})}{n+2}}, \tag{5.5}$$

where k of the group's n cases were followed by progress or a solve. With this bound, one success out of one cannot outrank eight out of ten. The chosen group must contain at least three cases. The output gives the suggested level and strategy, the smoothed effectiveness $\hat{p}$, the support n, the provenance (live, synthetic or mixed) and the mean similarity. It never contains an identity or code.

DSDA uses a suggestion only when its support is at least 3 and its effectiveness at least 0.55, and the suggestion may move the level by at most one. We do not treat similarity as proof that a kind of help will work.

5.2.6 Agent 4: Adaptive Scaffolding (DSDA)

The Dynamic Scaffolding Decision Algorithm has three separate steps. A *policy* decides whether and how much to help, *generation* writes the words, and *validation* checks them.

A configured LLM may only write the words. It cannot change the level, the strategy, the length limits, the solution constraint or the decision to wait. Figure 5.3 summarises the flow.




Figure 5.3: Decision flow of the Dynamic Scaffolding Decision Algorithm

The support score is computed first. Let K be the set of inputs whose value is known. The score is a weighted mean over K, so an unknown value never counts as a number:

$$S = \mathrm{clip}_{[0,1]}\Big(\sum_{k\in K}\frac{w_k}{\sum_{j\in K} w_j}x_k \;-\; 0.15\cdot[\text{improving}]\Big). \tag{5.6}$$

The inputs $x_k \in [0,1]$ and their weights w_k are as follows: low mastery $1-m$ (0.5 with no evidence), weight 0.22; confusion (low 0.2, moderate 0.55, high 0.9), 0.18; repeated issue $(\text{repeats}-1)/3$, 0.16; hints not followed by progress $/2$, 0.12; requests on unchanged code $/3$, 0.12; low confidence $1-\kappa$, 0.08; load (as confusion), 0.08; stalled time (seconds since last action$/600$), 0.04. The level is L0 if $S < 0.20$, L1 if $S < 0.40$, L2 if $S < 0.60$, L3 if $S < 0.80$ and L4 otherwise.

Table 5.4 lists the help levels with their presentation limits, and Table 5.5 lists the strategy ladders. Each issue climbs its own ladder one unused step at a time, which stops help from repeating.

Once the level and strategy are chosen, Algorithm 1 makes the timing decision. After a first hint on an issue, help the learner did not ask for is only offered, so help never climbs the ladder unless the learner asks.

Table 5.4: Help levels and presentation limits

Level	Name	Format	Limit
L0	Independent attempt	No hint; an offer of help	None
L1	Conceptual question	A question	2 sentences, 45 words
L2	Targeted hint	Points at what to examine	3 sentences, 70 words
L3	Step-by-step outline	Numbered steps, no code	6 sentences, 110 words
L4	Analogous worked example	Code on a *different* task	7 sentences, 150 words

Table 5.5: Strategy ladders (level in parentheses)

Step	Most issues	Syntax errors	Missing names
1	conceptual question (1)	syntax pinpoint (2)	conceptual question (1)
2	targeted hint (2)	read the tokens (2)	targeted hint (2)
3	trace the failing case (2)	syntax checklist (3)	name options (2)
4	print debugging (2)	analogous line (4)	step outline (3)
5	step outline (3)	exact fix (4)	analogous example (4)
6	analogous example (4)		direct pointer (4)
7	direct pointer (4)		

Algorithm 1 DSDA timing decision

if solved and no question asked **then return** NONE (`SOLVED`)
end if
if service failure or no tests **then return** WAIT
end if
choose level and strategy (score, rules, ladder)
if no unused step and code unchanged since last hint **then return** WAIT (`LADDER_EXHAUSTED`)
end if
if learner asked (hint, "more", "nudge" or question) **then return** SHOW
end if
if level is L0 and not a syntax error **then return** OFFER
end if
if automatic hints switched off **then return** OFFER (`AUTO_HINTS_OFF`)
end if
if learner is improving and not a syntax error **then return** OFFER (`PROGRESS_NO_HELP`)
end if
if same issue and at least one hint already shown on it **then return** OFFER (`OFFER_NEXT_STEP`)
end if
if first failure, mastery ≥ 0.7 with evidence **then return** OFFER (`OFFER_INDEPENDENT`)
end if
return SHOW

As a worked example, take a learner's second wrong submission with the same off-by-one bug. Mastery is 0.25 (evidence present), confusion is moderate, the issue has been seen in two attempts and one earlier hint was not followed by progress. Confidence, load and time are unknown and are left out. The known weights sum to 0.80 and the score components are $0.22 \cdot 0.75/0.80 = 0.206$, $0.18 \cdot 0.55/0.80 = 0.124$, $0.16 \cdot 0.33/0.80 = 0.067$ and $0.12 \cdot 0.50/0.80 = 0.075$, giving $S = 0.472$ and level L2. The next unused step at or above L2 is `targeted_hint`. This was a submission and not a request, and a hint had already been shown on the issue, so the decision is to *offer* the hint (reason codes `SUPPORT_NEEDED`, `ESCALATE_NO_PROGRESS`, `OFFER_NEXT_STEP`). We recomputed these values by running the implemented functions, and `test_worked_example_in_the_documentation_is_`

`accurate` also checks them.

For generation, built-in text is chosen by strategy and filled only with observed evidence. For ten common logic and timeout issues, the hint quotes the learner's own failing call, the values returned and expected, and the loop's line, source and variable. Other builders produce trace instructions, exactly what to print and where, analogous examples on a different task, and direct pointers in words. Text is trimmed to the level's sentence and word limits without cutting inside quoted code. When an LLM is configured, its prompt contains the task, the learner's code (marked as data), the evidence, the limits and every earlier hint. It never contains the reference solution or hidden tests.

Validation happens before anything is shown. The validator rejects a draft that contains a code block or code-like lines below L4, defines the function the learner must write, overlaps the reference solution or rewrites the learner's own code. It also rejects a draft that reveals hidden-test values or mentions internal details, is too long, is not a question at L1, repeats an earlier hint, is vague with nothing specific, names a line that does not exist or test counts that match neither result, contradicts the diagnosis, ignores the diagnosed cause or only repeats Python's error message. LLM text is rejected as well if it names nothing concrete from the learner's code. Two of the checks are quantitative. Solution overlap uses token 6-grams:

$$\text{overlap}(h,\sigma) = \frac{|N_6(\sigma) \cap N_6(h)|}{|N_6(\sigma)|} \geq 0.25 \;\Rightarrow\; \text{reject}, \tag{5.7}$$

where $N_6(x)$ is the set of six-token sequences of text x and σ is the reference solution. Repetition uses

$$\text{rep}(a,b) = \max\big(\text{SeqMatch}(a,b),\, J(a,b)\big) \geq 0.8 \;\Rightarrow\; \text{reject}, \tag{5.8}$$

where SeqMatch is the in-order word match ratio of Python's `difflib.SequenceMatcher` and J is the Jaccard overlap of the word sets. A rejected draft is regenerated, and each time the generator is told what was wrong. After three attempts a labelled built-in hint is used. If that hint would repeat an earlier one, the next unused step is tried, and if nothing passes, nothing is shown.

The outcome of each hint is recorded. On the learner's next checked attempt with changed code, each pending hint is marked *solved*, *progress* (more tests pass on the same kind of check, or the issue changed without getting worse) or *no progress*. These outcomes feed DSDA's "hints not followed by progress" input and the confusion estimate. For consenting real accounts they also go into the anonymous retrieval pool.

5.2.7 Agent 5: Reflection

The Reflection agent asks one short question that makes the learner explain their own reasoning, when such a question helps. It then replies to the answer as a tutor would, without grading it and without giving code or a fix.

The agent does not always ask. It defers when load is high. It skips the question when one is still unanswered, when there is no learning event, for a syntax slip on unsolved code, before three failed attempts, within three events of the last question, when the question would repeat the hint, or when it was already asked. After a solve it asks about the technique, and this question has three variants: solved with help, solved on the first try, and other.

The question is built from the cycle's evidence. For the example above it reads: "Trace `sum_to_n(3)` by hand: which values does `i` take in `for i in range(1, n):`, and which values does the answer need?" Anything that was not observed is left out, with no placeholder in its place.

To reply, Algorithm 2 classifies the answer. It uses regular expressions for the key ideas of the issue or technique (for example "where `range` stops" or "keeping a running total"), for reasoning words (because, so, since, therefore) and for honest uncertainty ("I don't know", "not sure"). It also checks whether the answer is concrete (backticks, numbers, or the learner's own variable names).

Algorithm 2 Reflection reply classification

$M \leftarrow$ key ideas matched; $R \leftarrow$ reasoning words present; $C \leftarrow$ answer is concrete
if uncertainty expressed and not R and not (C and $M \neq \emptyset$) **then return** UNSURE: kind reply and one small thing to try
end if
if fewer than 3 words and $M = \emptyset$ **then return** BRIEF: ask for a little more
end if
if $M \neq \emptyset$ and (C or R) **then return** SPECIFIC: name what was right, push one step further
end if
if $M \neq \emptyset$ or at least 8 words **then return** PARTIAL: one concrete thing to check
end if
return BRIEF

The question, answer, reply and quality are stored, and they affect the other agents. In the next cycle an unsure answer counts as one confusion signal. After a solve, an unsure answer holds back a plan that was moving on, and the planner suggests one more problem of the same technique first. If the plan shown with the question already gives such a problem, the plan stands, so the learner is not told the same thing twice. Clear, partial and short answers leave the plan unchanged.

5.2.8 Agent 6: Learning Planner

The Learning Planner recommends what to do next and gives a reason, moving the learner step by step from where they are towards harder work. Its inputs are topic mastery and evi-

dence, prerequisites, each topic's techniques in lesson order, and each problem's technique, difficulty and status. The status includes whether the problem was solved fluently, meaning that the first graded submission was accepted with no hint shown before it. The planner also takes the current problem, the attempts, the highest hint level, and the learner's goal and experience. It outputs an action, a title, a reason, reason codes, a problem and topic, whether the current task stays active, alternatives and a *route*: the current topic and up to three topics ahead in course order.

Algorithm 3 Next-step selection after an attempt

if problem not solved **then**
    if 4 or more attempts and a prerequisite topic is weak (mastery < 0.45 with evidence) **then return** practise prerequisite (task kept)
    end if
    return stay on this problem (`UNRESOLVED`)
end if
if solved with L3+ help, or with hints while over 60% of the topic's solves used hints **then return** same technique, same difficulty, on your own
end if
if topic secure: mastery ≥ 0.75, ≥ 2 solves without help, evidence ≥ 2.5 **then return** harder problem, else the next topic forward
end if
for level in easy, medium, hard **do**
    for technique in lesson order **do**
        if not practised at this level (easy: 2 solves or 1 fluent solve; above: 1 solve) and an unsolved problem exists **then**
            return that problem (`CONSOLIDATE_TECHNIQUE`, `NEXT_TECHNIQUE` or `STEP_UP_DIFFICULTY`)
        end if
    end for
end for
return next topic forward (`UNIT_EXHAUSTED`)

The next topic is the next one forward in the learner's track order. An earlier topic comes back only when it has work in it and is not yet secure. A weak prerequisite holds a topic back only while it still has problems to practise. A held-back topic also holds back every topic that builds on it, so the planner never jumps past it. The route is a preview in course order and always shows the topic after the current one. The home screen applies the same rules as the plan shown after a submission, so both suggest the same next step.

5.2.9 Persistence and data model

The schema has 25 tables, managed through five Alembic migrations. Figure 5.4 shows the core entities of the learning cycle.

Every learning cycle writes one `interaction_records` row with the outputs of all agents, so the next cycle can read what the tutor concluded and decided before. A hint is stored with its validation result and the starting pass ratio, which lets its outcome be judged later. `learner_topic_state` holds the current estimate per topic, and `learner_state_snapshots` holds its history, which the profile page shows. Hidden-test contents, reference




Figure 5.4: Core entities of the data model (simplified; lines show references)

solutions and prompts are not stored in these records.

5.2.10 Learner and teacher interfaces

In the workspace, the problem, lesson, submissions and tutor sit in tabs beside the editor and the test results (Figure 6.3). Run, Submit and Ask for a hint are separate buttons, and a hint is never graded. The tutor pane shows the current hint with its level, its concept and a link to the matching lesson section. It also has a collapsible "Why this hint?" explanation, "I need more help", a box for typed questions, the reflection card and the suggested next step with the route.

The teacher dashboard computes class measures from stored data. These are completion rate (problems solved divided by problems with at least one graded attempt), hints per solved problem, median active time to the first accepted submission, satisfaction (median of four Likert items) and learning gain $\frac{\text{post}-\text{pre}}{\text{max}-\text{pre}}$. Learning gain is shown only for learners who have taken both knowledge checks. The dashboard also lists learners who may need support, with the evidence for each flag.

Chapter 6

Results and Analysis

6.1 Evaluation setup

In this phase we evaluated whether the system is correct, is safe and behaves as designed. We did not measure learning gains, because no study with real learners has been carried out yet (Chapter 7 describes the planned study).

All runs used the development machine and software versions listed in Chapter 4, with PostgreSQL in a container. Every test used the real database, the real execution service with Docker sandbox containers, the real LangGraph pipeline and ChromaDB. No LLM was configured (`LLM_PROVIDER=none`), so every hint, question and reply used the built-in, evidence-based wording, and the LLM path was tested with a scripted stand-in model.

The evaluation had four parts.

- We ran four automated test suites: backend (pytest), frontend unit (Vitest), browser end-to-end (Playwright with Google Chrome and axe-core) and execution service. For the browser tests, a separate API and web server ran on other ports with raised rate limits, so test traffic did not affect the developers' server.
- We ran an agent audit. The script `scripts/agent_audit.py` registers a fresh learner for each of nine scenarios, submits code or asks for hints on the problem "Sum from 1 to N", and reads each agent's output back from the run response and its per-stage trace, checking 37 behavioural rules plus two rules over every hint shown.
- We verified the curriculum by running every problem's reference solution against all of its tests in the sandbox and confirming that every starter program fails.
- We inspected the interface. A script that drives the running application as a demo learner and a demo teacher captured the screenshots.

We took precautions against invalid results.

- The suites were run one at a time, after an earlier parallel run overloaded Docker on

the 8 GB machine and produced false failures. The counts reported here are from final runs made after the last code change.

- The audit reads the agents' outputs from the stored traces, not from the code under test, so it checks what the agents actually produced.
- All synthetic data (the teacher demo class and the demonstration retrieval records) is labelled in the interface and is not used as evidence that the tutor works.

6.2 Evaluation criteria

Table 6.1 defines the criteria used.

Table 6.1: Evaluation criteria

Criterion	**Measure and interpretation**	**Target**
Functional correctness	Tests passed ÷ tests run, per suite.	100% on the final code.
Agent behaviour	Audit checks passed ÷ checks, over nine scenarios that exercise all six agents.	All checks pass.
Non-repetition of help	Distinct hints among repeated requests on unchanged code; highest pairwise similarity $\mathrm{rep}(a,b)$ (Section 5.2).	All distinct; similarity < 0.8.
Controlled escalation	Level change between consecutive hints on one issue; hints shown without a request after a first hint.	At most $+1$; none shown unasked.
Hint specificity	Share of hints that name a line, value or name from the learner's code, and share free of generic advice.	100% of hints shown.
Solution protection	Responses containing hidden-test values or reference solutions; hints exceeding the solution-overlap threshold.	None.
Curriculum validity	Problems whose reference solution passes all tests and whose starter fails.	All 496 problems.
Test coverage	Tests per problem; share of problems with at least 30 tests.	Coverage reported.
Accessibility	Automated WCAG 2.0 and 2.1 A and AA violations on main screens, both themes.	Zero violations.

6.3 Result

6.3.1 Automated test suites

Table 6.2 summarises the final runs. Every suite passed in full.

Figure 6.1 shows the 551 backend tests by test file. The largest file covers repeated-hint behaviour, where we found the most serious defect during development (Section 6.4).

Table 6.2: Results of the automated test suites on the final code

Suite	Result	What it exercises
Backend (pytest)	551 of 551	API, all six agents, the full pipeline, persistence, retrieval, policy, hint quality, imports and content, with real PostgreSQL, sandbox, LangGraph and ChromaDB.
Browser end-to-end (Playwright)	59 of 59	54 learner and teacher flows in real Chrome, and 5 automated accessibility tests in light and dark themes.
Frontend unit (Vitest)	21 of 21	Shared interface components, draft restoration, test-case editing, display formatting, saved-data migration and new-tab links.
Execution service	39 of 39	26 execution tests and 13 isolation tests in real containers (run on 9 November 2026; this service did not change afterwards).
Agent audit	37 of 37, plus 2 of 2	Nine scenarios through the running stack; two further checks over all 17 hints shown.
Curriculum verification	496 of 496	Each reference solution passes all of its tests (15,717 in total) and each starter fails, in the sandbox.
Static checks	Passed	Ruff lint (backend), TypeScript strict type check and production build (frontend).




Figure 6.1: Backend tests per test file (551 in total, all passed)

6.3.2 Agent audit

In the final audit run all 37 behavioural checks and both checks over every hint passed (Figure 6.2). Table 6.3 lists representative checks with the recorded evidence.




Figure 6.2: Agent audit: checks passed per scenario (39 of 39)

Table 6.3: Representative audit checks and recorded evidence

Check	**Evidence recorded in the final run**
Every request on unchanged code gets a different hint	4 requests, 4 different hints; pairwise similarities 0.16 to 0.38 (all below 0.8).
Escalation is gradual	Levels 2, 2, 2, 3; strategies targeted hint, trace the failing case, print debugging, step outline.
Retrieval leaves out approaches already shown	Excluded strategies grew with each request: none; targeted hint; then also trace; then also print debugging.
Syntax error is diagnosed with its line	`SyntaxError: expected ':'`; first hint: "Look at line 1. A line that opens a block … must end with one particular punctuation mark. Which mark is missing there?"
Runtime cause is told apart from a generic error	`UnboundLocalError` diagnosed as "used before assignment", confidence 0.95.
Endless loop is diagnosed as a timeout	`timeout:loop_no_progress`; the hint asks the learner to follow `while i <= n:` on line 4 by hand.
Help is offered without being pushed	First failed submission: a hint. Next two failed submissions: `offer_help` both times. Asking then: next step, level 2.
Overloaded learner	One short action of 33 words and no reflection question (deferred).
Unknown stays unknown	With no history, confusion is reported as unknown and is not assumed.
Reflection holds back a plan that was moving on	After a first-try solve the plan was "Count the Digits" (next technique); the answer "not sure, I just changed it until it passed" changed it to "Sum Odds Only" (one more running-totals problem).
Reflection does not repeat the plan	After a solve with help the plan already gave one more running-totals problem; the same unsure answer left it unchanged.
Planner moves forward	Route: Loops, Functions, Strings, Lists and dictionaries; the home screen suggested the same next problem as the plan.
Every hint is specific	All 17 hints shown named a line, value or name from the learner's code, and none used generic advice such as "check your logic".

6.3.3 Tutoring behaviour in the interface

Figures 6.3 to 6.7 show one learner session on "Sum from 1 to N", captured from the running application. The code loops over `range(1, n)`, so it misses the last value. Figure 6.8 shows the teacher dashboard.




Figure 6.3: First wrong submission: the tutor gives one targeted hint built from the learner's own failing call, values and loop variable, with the concept, a link to the lesson and a "Why this hint?" explanation




Figure 6.4: Second wrong submission on the same issue: the next hint is only offered, and the offer says once what it will focus on

6.3.4 Learner-state estimates

Figure 6.9 shows how the implemented mastery update responds to three attempt sequences, computed by running the Cognitive State agent's own functions with its configured parameters. A learner who solves five times without help rises quickly. One who fails twice, solves once with a level-2 hint and then solves twice alone drops first and then recovers. One who keeps failing stays low. The dotted lines mark the band boundaries, and the band stays "not enough evidence" until the total evidence weight reaches 1.5. The curves come from the model alone and involve no data from real learners.




Figure 6.5: After three failed attempts: a reflection question about the learner's own loop, and the tutor's reply to the answer "no idea"




Figure 6.6: After the solve: a question about the technique, and a next step on the same technique without hints, with the route ahead

6.3.5 Curriculum and tests

The curriculum has 496 verified problems in 17 topics (Figure 6.10). The earlier topics are mostly easy, and the later data-structure topics mostly medium and hard. Of the 15,717 tests, 1,000 are visible and 14,717 hidden. In all, 487 problems have at least 30 tests (median 32, maximum 34), and the other nine have few possible inputs, for example a problem that takes no input. Hidden tests are chosen to cover different kinds of input (Figure 6.11).




Figure 6.7: Home screen after the session: the same next step as the plan, with the route through the course




Figure 6.8: Teacher dashboard with the clearly labelled synthetic demonstration class; the numbers are generated and are not evidence that the tutor works




Figure 6.9: Mastery estimates produced by the implemented weighted knowledge-tracing update for three attempt sequences




Figure 6.10: Curriculum problems per topic and difficulty (496 in total)




Figure 6.11: Hidden tests by kind of input (14,717 in total)

6.4 Comparative Analysis

6.4.1 Before and after the agent improvements

During development we reproduced the repeated-hint defect and recorded the behaviour before the fix, with five requests on unchanged code per scenario (Table 6.4).

Table 6.4: Behaviour before and after the agent improvements

Behaviour	**Before**	**After (final system)**
Repeated hint requests on unchanged code	1 distinct hint in 5 requests in every scenario (syntax, missing colon, off-by-one, runtime, timeout); constant level and support score 0.208	4 different hints in 4 requests, highest similarity 0.38; levels 2, 2, 2, 3; a different strategy each time; then the tutor waits for a code change
Wrong submissions without asking	Each further failed submission on an issue could show the next, more revealing hint automatically	After a first hint, help is offered and shown only when asked, at most one level higher
Reflection	Fixed questions, the same for every learner; answers stored with no reply and no effect	Questions name the learner's own code or technique; every answer gets a reply; an unsure answer reaches the Cognitive State and the Planner
Planning	Next problem chosen by difficulty only; next topic could be an earlier topic with no work in it	Technique-by-technique sequencing at each difficulty; forward topic order; route shown; home screen and plan agree
Hints for logic mistakes	8 of 16 hints in the first audit run named nothing concrete from the learner's code	All 17 hints in the final run name a line, value or name from the learner's code

6.4.2 Comparison with existing approaches

Table 6.5 compares what CodePath implements with what is described for the most closely related systems we reviewed. Entries for the other systems state only what their published records describe, and "Not reported" does not mean the system lacks the capability. The CodePath row lists implemented and tested functions, none of which is a measured learning effect.

Table 6.5: Capabilities of CodePath and closely related systems

System	Persistent learner model	Decides how much help	Withholds full solutions	Retrieval	Several agents	Live programming practice
Knowledge tracing [1]	Yes (per skill)	Selects exercises until mastery	Not applicable	Not reported	Not reported	Yes
CodeHelp [6]	Not reported	Not reported	Yes (guardrails)	Not reported	Not reported	Yes
CodeAid [7]	Not reported	Not reported	Yes	Not reported	Not reported	Yes
PyTutor [8]	Not reported	Structured hint types	No (hints include coding solutions)	Not reported	Not reported	Yes
RAGMan [9]	Not reported	Not reported	Not reported	Course material	Not reported	Yes
Ruffle&Riley [10]	Not reported	Not reported	Not applicable	Not reported	Yes (two agents)	No (biology)
TRAVER [12]	Yes (knowledge tracing)	Not reported	Not reported	Not reported	Not reported	Simulated students
CodePath (this work)	**Yes: mastery with range, confusion, load, progress**	**Yes: DSDA level, strategy and timing**	**Yes: validator and tests**	**Similar learners' outcomes**	**Yes: six agents**	**Yes**

6.4.3 Comparison with the proposal's evaluation metrics

The initial submission proposed four evaluation measures: learning gain, hint efficiency and hints per problem, task completion rate and time to completion, and student satisfaction. All four are implemented as defined formulas in the teacher dashboard (Section 5.2), and tests cover their computation, but we do not yet have their values for real learners. The only numbers shown at present come from the labelled synthetic demonstration class (Figure 6.8). Learning gain is deliberately shown only for learners who took both knowledge checks.

6.5 Discussion and Interpretation

Objective O1 (multiple collaborating agents) is met. Every learner action runs through six agents with typed contracts that read each other's outputs and the stored history, and the pipeline tests and the audit confirm the order and the data passed between them. Objective O2 (cognitive state) is met as explainable behavioural estimates. In the audit, confusion stays unknown without evidence and rises with repeated requests, and progress is detected when a new version gets further. These estimates have not been compared with any external measure of a learner's state, so they are the tutor's working hypotheses.

Objective O3 (similar-learner retrieval) is met as a mechanism. Retrieval filters by similar-

ity, outcome, difficulty and topic, skips approaches already seen and refuses to answer on thin evidence. Its usefulness depends on real learners' outcomes, which do not exist yet. Objective O4 (scaffolding algorithm) is met. DSDA gives a level, strategy and timing with stated reasons, and the code reproduces its documented worked example exactly. The audit confirms the intended behaviours: help does not repeat, rises at most one level at a time, is not pushed after a first hint, stays short under overload and never contains a solution. Objective O5 (effectiveness on datasets) is partly met. The curriculum and the system's behaviour across realistic scenarios are verified, but whether the tutor improves learning is unknown.

The results also say something about *how* help is given, which is where this project started. In Table 6.4 the final system behaves much more like a patient human tutor than the earlier version. It waits for the learner to try their own idea, gives one specific next step when asked, reacts to what the learner says in reflection, and moves through the course at a pace set by the learner's own work. The literature advises caution: help-seeking feedback can change behaviour without improving learning [4], and engaging tutors do not necessarily outperform reading [10]. The next phase therefore has to measure learning directly.

6.6 Limitations

- We have no evidence yet that the tutor improves learning. No real learners have used the system, and every policy weight and threshold is a starting value set by judgement. Confusion and load are inferred from behaviour and not externally validated.
- The similar-situation records are currently synthetic demonstration cases plus outcomes pooled from automated test and audit runs. These count as "live" in the development database, so any study needs a fresh database.
- No real model was tested, as the available key had no credit. Model wording, rejection rates and latency are unknown, and the observed behaviour used built-in wording.
- Some checks are heuristic. The validator catches copied or lightly reworded solutions and repeats, but determined rewording could pass. Reflection replies spot key ideas by keywords, so an unusual but correct answer can read as partial. Error-cause analysis covers common causes, and an unusual error gets general help with lower confidence. Built-in hints quote the learner's code for ten common logic and timeout issues.
- The sandbox was tested on Docker Desktop for macOS, not a Linux server, and has not been independently audited. The worker pool, queue and rate limits live in memory, so the API runs as one process.
- Only Python is supported. The curriculum was written for this project, its difficulty labels are our judgement, and CodeNet was not imported. Accessibility was checked automatically, not with screen-reader users, and browser tests ran on Chrome only.

Chapter 7

Conclusion

7.1 Conclusion

AI assistants can answer a beginner's programming question instantly, but help that is too much, comes too soon or is the same for everyone can take away the thinking a learner needs to do. We addressed this by designing and building CodePath, a web-based tutor for novice Python programmers based on the Cognitive-State Guided Multi-Agent Adaptive Scaffolding Framework.

What we implemented consists of:

- a cyclic LangGraph workflow of six agents with typed contracts, shared persistent history and a pause after every cycle, so that the tutor acts only in response to the learner;
- a rule-based Diagnostic agent that uses test results and syntax-tree analysis to label issues and quote the learner's own code;
- a Cognitive State agent that applies an evidence-weighted knowledge-tracing update and reports confusion, load and progress with their evidence, or "unknown";
- a Similar Learner Retrieval agent that combines ChromaDB cosine search with outcome records in PostgreSQL and refuses to answer on thin evidence;
- the Dynamic Scaffolding Decision Algorithm, which uses an explainable score, strategy ladders and timing rules to decide whether, when and how much to help, followed by validated generation that never reveals a solution and never repeats a hint;
- a Reflection agent that asks about the learner's own reasoning and replies to the answer, and a Learning Planner that sequences practice technique by technique and moves forward through the course;
- a safe execution service, a verified curriculum of 496 problems with 15,717 tests, and learner and teacher interfaces.

The evidence supports objectives O1 to O4 as software. On the final code, 551 backend tests, 59 browser tests, 21 unit tests and 39 execution-service tests passed. Every curriculum problem was verified in the sandbox. An audit of nine scenarios passed all 37 of its behavioural checks and both checks over every hint. Objective O5 is partly achieved, because the system's behaviour and its curriculum are verified but its effect on learning has not yet been measured with real learners. In line with Chapter 6, this report claims a working, tested tutor whose teaching behaviour matches its design, and it makes no claim of a demonstrated improvement in learning.

7.2 Future work

- The next phase, and our highest priority, is a learner study. We plan a pilot with about 30 or more learners, randomly assigned and balanced on the starting knowledge check, comparing CodePath with the same interface using a plain LLM assistant or fixed hints. The measures are normalised learning gain between parallel pre- and post-checks with an effect size, completion rate, hints per solved problem, time to completion and satisfaction. The ablations are without retrieval, with DSDA constrained through `policy.yaml`, and with a fixed problem order. The study depends on institutional ethics approval, informed consent, participants and a fresh database. For validity, the analysis will be pre-registered and a small sample treated as preliminary.
- The system should be evaluated with a real model. This means configuring an LLM provider and measuring the draft rejection rate, leak rates against a fixed set of solution-extraction prompts, wording quality and latency. This needs model access with credit.
- The knowledge-tracing parameters and DSDA weights could be fitted to logged interactions. The fitted model's prediction of the next result would then be compared, using AUC, with the current values or with Deep Knowledge Tracing [2]. This needs data from the learner study.
- For offline evaluation on CodeNet [5], we would import problem statistics and attempt sequences, check difficulty labels against acceptance rates, and replay sequences through the Cognitive State agent. Simulated learners [11] could also test policies before a study.
- For deployment, the sandbox should be tested on a Linux server and independently reviewed for security. The queue and rate limits should move to a shared store so the API can run as several processes. Email verification, password reset and automated data retention should be added.
- The scope can then be widened with JavaScript, and Java or C++ once Python is stable, more Diagnostic rules, and accessibility tests with screen-reader users.

References

[1] A. T. Corbett and J. R. Anderson, "Knowledge tracing: Modeling the acquisition of procedural knowledge," *User Model. User-Adapt. Interact.*, vol. 4, no. 4, pp. 253–278, 1995, doi: 10.1007/BF01099821.

[2] C. Piech, J. Spencer, J. Huang, S. Ganguli, M. Sahami, L. Guibas, and J. Sohl-Dickstein, "Deep knowledge tracing," in *Advances in Neural Information Processing Systems 28 (NIPS 2015)*, 2015. [Online]. Available: arXiv:1506.05908.

[3] V. Rus, N. B. Niraula, and R. Banjade, "DeepTutor: An effective, online intelligent tutoring system that promotes deep learning," in *Proc. AAAI Conf. Artif. Intell.*, vol. 29, no. 1, 2015, doi: 10.1609/aaai.v29i1.9269.

[4] V. Aleven, I. Roll, B. M. McLaren, and K. R. Koedinger, "Help helps, but only so much: Research on help seeking with intelligent tutoring systems," *Int. J. Artif. Intell. Educ.*, vol. 26, no. 1, pp. 205–223, 2016, doi: 10.1007/s40593-015-0089-1.

[5] R. Puri *et al.*, "Project CodeNet: A large-scale AI for code dataset for learning a diversity of coding tasks," arXiv:2105.12655, 2021, doi: 10.48550/arXiv.2105.12655.

[6] M. Liffiton, B. Sheese, J. Savelka, and P. Denny, "CodeHelp: Using large language models with guardrails for scalable support in programming classes," arXiv:2308.06921, 2023, doi: 10.48550/arXiv.2308.06921.

[7] M. Kazemitabaar, R. Ye, X. Wang, A. Z. Henley, P. Denny, M. Craig, and T. Grossman, "CodeAid: Evaluating a classroom deployment of an LLM-based programming assistant that balances student and educator needs," in *Proc. CHI Conf. Human Factors Comput. Syst. (CHI '24)*, Honolulu, HI, USA, 2024, doi: 10.1145/3613904.3642773.

[8] A. C. M. Yang, J.-Y. Lin, C.-Y. Lin, and H. Ogata, "Enhancing Python learning with PyTutor: Efficacy of a ChatGPT-based intelligent tutoring system in programming education," *Comput. Educ. Artif. Intell.*, vol. 7, Art. no. 100309, 2024, doi: 10.1016/j.caeai.2024.100309.

[9] I. Ma, A. Krone Martins, and C. V. Lopes, "Integrating AI tutors in a programming course," accepted at SIGCSE Virtual 2024, arXiv:2407.15718, 2024, doi: 10.48550/arXiv.2407.15718.

[10] R. Schmucker, M. Xia, A. Azaria, and T. Mitchell, "Ruffle&Riley: Insights from designing and evaluating a large language model-based conversational tutoring system,"

arXiv:2404.17460, 2024, doi: 10.48550/arXiv.2404.17460.

[11] Y. Zhan, Q. Liu, W. Gao, Z. Zhang, T. Wang, S. Shen, J. Lu, and Z. Huang, "CoderAgent: Simulating student behavior for personalized programming learning with large language models," in *Proc. 34th Int. Joint Conf. Artif. Intell. (IJCAI-25)*, 2025, pp. 293–301, doi: 10.24963/ijcai.2025/34.

[12] J. Wang, Y. Dai, Y. Zhang, Z. Ma, W. Li, and J. Chai, "Training turn-by-turn verifiers for dialogue tutoring agents: The curious case of LLMs as your coding tutors," in *Findings Assoc. Comput. Linguistics: ACL 2025*, Vienna, Austria, 2025, pp. 12416–12436, doi: 10.18653/v1/2025.findings-acl.642.

[13] G. Pitts, A. P. Hridi, and A. B. Lekshmi Narayanan, "A survey of LLM-based applications in programming education: Balancing automation and human oversight," in *Proc. 4th Workshop Bridging Human-Comput. Interact. Natural Lang. Process. (HCI+NLP)*, Suzhou, China, 2025, pp. 255–262, doi: 10.18653/v1/2025.hcinlp-1.21.

[14] D. Wood, J. S. Bruner, and G. Ross, "The role of tutoring in problem solving," *J. Child Psychol. Psychiatry*, vol. 17, no. 2, pp. 89–100, 1976, doi: 10.1111/j.1469-7610.1976.tb00381.x.

[15] J. Sweller, "Cognitive load during problem solving: Effects on learning," *Cogn. Sci.*, vol. 12, no. 2, pp. 257–285, 1988, doi: 10.1207/s15516709cog1202_4.

[16] K. VanLehn, "The relative effectiveness of human tutoring, intelligent tutoring systems, and other tutoring systems," *Educ. Psychol.*, vol. 46, no. 4, pp. 197–221, 2011, doi: 10.1080/00461520.2011.611369.

[17] United Nations General Assembly, "Transforming our world: The 2030 Agenda for Sustainable Development," Resolution A/RES/70/1, Oct. 2015.

[18] Y. A. Malkov and D. A. Yashunin, "Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 42, no. 4, pp. 824–836, 2020, doi: 10.1109/TPAMI.2018.2889473.

[19] LangChain, "LangGraph," GitHub repository. [Online]. Available: `https://github.com/langchain-ai/langgraph`

[20] Chroma, "Chroma: the open-source embedding database," GitHub repository. [Online]. Available: `https://github.com/chroma-core/chroma`

[21] S. Ramírez, "FastAPI," GitHub repository. [Online]. Available: `https://github.com/fastapi/fastapi`

[22] Microsoft, "Playwright," GitHub repository. [Online]. Available: `https://github.com/microsoft/playwright`

[23] Deque Systems, "axe-core: Accessibility engine for automated web UI testing," GitHub repository. [Online]. Available: `https://github.com/dequelabs/axe-core`

Appendix A

Source Code and Reproducibility

The complete source code, curriculum, tests and documentation are in the project repository `https://github.com/lokesh12125/AdaptiveAITutor`, on the branch `Trellis`. Version used for this report: commit [commit identifier, to be recorded after the final work is committed]. The repository's `.env.example` lists every configuration value without secrets. No passwords, tokens or keys are included in this report or in the repository.

The repository is organised as follows:

- `backend/`: FastAPI application; `app/tutoring/` holds the six agents (`diagnostic.py`, `error_analysis.py`, `cognitive.py`, `retrieval.py`, `dsda.py`, `hints.py`, `reflection.py`, `planner.py`), the graph (`graph.py`, `nodes.py`) and the policy file `policy.yaml`; `migrations/` holds the five database migrations; `tests/` the backend tests.
- `runner/`: the execution service and the sandbox image definition.
- `frontend/`: the React application, unit tests and the Playwright browser tests (`e2e/`).
- `content/`: lessons, topic notes and technique guides; `scripts/`: the problem bank, test generation, content verification and the agent audit.
- `docs/`: architecture, agent contracts, DSDA, security, evaluation, limitations and test results; `report/`: this report, its figure data and the scripts that produced them.

A.1 Setup and execution

The prerequisites are Docker (running), the `uv` Python package manager, Python 3.12 and Node.js 20 or later. No AI key is needed.
For automatic setup, run the following from the repository root:

```
./scripts/setup.sh
./scripts/dev.sh
```

`setup.sh` creates `.env` with fresh secrets, starts PostgreSQL on port 5544, builds the sandbox image, installs the dependencies, runs the migrations and loads the content. `dev.sh` starts the execution service (port 8102), the API (port 8101) and the web application (port 5173). Open `http://127.0.0.1:5173` and choose "Try as a learner" or "Try as a teacher". For manual setup, the steps are:

```
cp .env.example .env    # then set RUNNER_TOKEN
docker compose up -d db
docker build -t csmasf-sandbox:py312 runner/sandbox

cd runner && uv venv --python 3.12 .venv
uv pip install --python .venv/bin/python -e '.[dev]'
.venv/bin/uvicorn runner_service.main:app --host 127.0.0.1 --port 8102

cd backend && uv venv --python 3.12 .venv
uv pip install --python .venv/bin/python -e '.[dev]'
.venv/bin/alembic upgrade head
.venv/bin/python -m app.seed
.venv/bin/uvicorn app.main:app --host 127.0.0.1 --port 8101

cd frontend && npm ci && npx vite --host 127.0.0.1 --port 5173
```

The tests are run one suite at a time:

```
cd runner && .venv/bin/python -m pytest
cd backend && .venv/bin/python -m pytest
cd frontend && npm test
cd frontend && E2E_CHROME_CHANNEL=chrome npm run e2e
cd backend && PYTHONPATH=. .venv/bin/python ../scripts/verify_content.py
backend/.venv/bin/python scripts/agent_audit.py http://127.0.0.1:8101
```

The browser tests need the stack running with raised rate limits: set `RATE_RUN_PER_MINUTE`, `RATE_SUBMIT_PER_MINUTE`, `RATE_HINT_PER_MINUTE`, `RATE_AUTH_PER_MINUTE` and `RATE_IMPORT_PER_MINUTE` to a large value such as 100000 before starting it.
To reproduce the report's figures, the chart data is computed from the database and from the agents' own code, and the screenshots are captured from the running application:

```
backend/.venv/bin/python report/tools/make_figure_data.py
NODE_PATH=frontend/node_modules node report/tools/screenshots.cjs
cd report && tectonic -X compile main.tex
```

A.2 Supporting material

Table A.1 lists the backend test files and what each verifies.

Table A.1: Backend test files

File	Tests	What it verifies
`test_repeated_hints.py`	118	Persistent interaction state, varied help on repeated requests, retrieval filtering and privacy.
`test_link_import.py`	90	Adding questions from pasted text and links, site rules and labelled suggested tests.
`test_api.py`	84	Authentication, demo access, rate limits, progress, profile, teacher views and dashboard measures.
`test_diagnosis.py`	69	Diagnostic rules and error-cause analysis.
`test_agents.py`	54	Individual agents: cognitive estimates, reflection decisions, planner rules, validator checks.
`test_pipeline.py`	43	The full graph: agent order and data flow, persistence, solution protection, idempotency, failure handling.
`test_policy.py`	30	DSDA score, levels, ladders, timing and the documented worked example.
`test_reflection_and_planner.py`	27	Reflection questions and replies, their effects, and planner sequencing and agreement.
`test_hint_quality.py`	23	Specific, non-generic hint wording and validator behaviour.
`test_content.py`	13	Curriculum integrity: lessons, techniques and test coverage.

In brief, the system is used as follows. A learner chooses a topic or the recommended next step, reads the lesson if needed, writes code in the workspace, uses Run to try visible examples and Submit to be graded. The tutor responds after a submission or when the learner presses “Ask for a hint”. “I need more help” asks for the next step, and selecting lines lets the learner ask about them. A teacher creates a class, shares its join code, and follows learners on the class dashboard.

Figures A.1 and A.2 show two more screens, a topic lesson and the practice library.




Figure A.1: A topic lesson, opened from the problem’s “Read the lesson” link




Figure A.2: The practice library, grouping problems by topic in learning order