GRIT Level Clearance Interview Scheduling

1. Problem and product flow

Students who finish required skills need a clear, fair last step to earn a GRIT track badge. This prototype connects student booking, interviewer operations, outcomes, and badge eligibility to a persisted interview record. The same record drives the student dashboard, interviewer schedule, Interview Ops tracker, audit timeline, and in-app notification.

Persona	Main task
Student	Check eligibility, select a slot, manage a booking, and follow the result.
Interviewer	Publish availability, run a schedule, and record a reasoned outcome.
Interview Ops	Track students, nudge, export, and review malpractice flags.

2. States and transitions

The state model distinguishes eligibility, booking, attendance, outcomes, and post-award review. `CANCELLED_STUDENT` and `CANCELLED_INTERVIEWER` are the persisted status codes.

State	Entry	Next state / rule
`SLOT_HELD`	Student selects a slot	`BOOKED` on confirmation; `ELIGIBLE` on hold timeout. Transient design state.
`IN_PROGRESS`	Required skill levels are incomplete	`ELIGIBLE` once requirements clear.
`ELIGIBLE`	Skills clear and cooldown expires	`BOOKED`; `INELIGIBLE` if policy checks fail.
`BOOKED`	Student confirms an open slot	`AWAITING_OUTCOME`, `CANCELLED_STUDENT`, or `CANCELLED_INTERVIEWER`.
`AWAITING_OUTCOME`	Interview starts; outcome is pending	`PASSED`, `FAILED`, `RETAKE_REQUIRED`, or `NO_SHOW`.
`PASSED`	Interviewer records a pass	Terminal unless malpractice is confirmed.
`FAILED`	Interviewer records a fail	`ELIGIBLE` after 14 days; stop self-service at 3 attempts.
`RETAKE_REQUIRED`	Interviewer asks the student to return	`ELIGIBLE` after 7 days.
`NO_SHOW`	Interviewer marks a no-show after the grace period	`ELIGIBLE` after 7 days; second no-show needs Ops review.
`CANCELLED_STUDENT`	Student cancels 24+ hours ahead	`ELIGIBLE`; no attempt consumed.
`CANCELLED_INTERVIEWER`	Interviewer cancels / blocks availability	`ELIGIBLE`; no attempt consumed; 48-hour priority rebooking is communicated.
`EXPIRED`	Slot passes without a recorded outcome	Ops follow-up to resolve the attendance/outcome.
`INELIGIBLE`	Attendance, registration, or conduct guard fails	`ELIGIBLE` if restored; active booking must be reviewed.
`REVOKED`	Malpractice is confirmed after award	Appeal upheld may restore `PASSED`, with an audit event.

Every implemented interview transition writes an `InterviewEvent`. Timed slot holds, automatic expiry, appeal processing, and scheduled jobs are design states, not automated services in this local prototype.

3. Rules, assumptions, and edge cases

• One-to-one interviews last 30 minutes, with a 5-minute interviewer buffer. Bookable slots are within 14 days and close 24 hours before start.

• Free student cancellation and rescheduling close at the 24-hour boundary. An interview may be rescheduled at most twice; a badge permits at most three outcome attempts.

• Fail cooldown is 14 days; retake and no-show cooldowns are 7 days. A pass awards the badge, 250 Miles for the seeded Novice badge, and Qualiflyer status.

• All timestamps are stored as UTC. Display uses `Asia/Kolkata` (IST, UTC+5:30; no daylight-saving shift).

• Eligibility is checked server-side for registration, conduct, attendance (75% minimum), cooldown, maximum attempts, and an existing active interview.

• Booking conditionally claims an `OPEN` slot in a transaction. A unique `SlotLock` row prevents two live bookings from owning one slot; on a failed claim, the student must choose another slot.

• Availability edits regenerate future open slots without changing existing bookings. Interviewer time off cancels affected bookings, releases their locks, returns the attempt, and creates a student notification.

• Confirmed malpractice revokes the badge, removes its credential and Qualiflyer status, reverses Miles, and appends an audit event.

Assumptions: one demo badge progress per student view, one interviewer per slot, no payments, and no production identity system. Persona switching is a demo cookie. Notifications are persisted in-app rows; email, WhatsApp, scheduled reminders, waitlist delivery, priority ranking, and appeals are not connected to external services. The seeded accounts and sample data are fictional demo data.

4. Data model and integrity

Prisma models: `User`, `StudentProfile`, `InterviewerProfile`, `Track`, `Badge`, `BadgeProgress`, `AvailabilityRule`, `AvailabilityException`, `InterviewSlot`, `SlotLock`, `Interview`, `InterviewEvent`, `Notification`, `MalpracticeFlag`, and `OpsNudge`.

`BadgeProgress` is unique per student and badge. An `Interview` is unique per student, badge, and attempt number. `SlotLock` contains only active bookings and is unique by slot and interview. Events are append-only transition records; notifications retain their template, copy, and read time. SQLite is the local demo provider; PostgreSQL is the intended Vercel provider. The schema avoids provider-specific enums and native types.

5. Student messages

The templates below are the fixed copy used by `lib/messages.ts`; names, badge, time, URL, and outcome details are interpolated when a message is created.

1 ? Booking confirmed

Title: `Interview booked ? {trackName} ? {badgeName}`

> *Hi {studentName}, your Level Clearance Interview is confirmed.*
>
> *{date} ? {time range} IST Interviewer: {interviewerName} Google Meet: {meetingUrl}*

> *Join 5 minutes early with your student ID ready. You can reschedule or cancel up to 24 hours before your slot.*

2 ? 24-hour reminder

Title: `Your interview is tomorrow, {time range} IST`

> *Quick reminder for your Level Clearance Interview.*

>

> *{trackName} ? {badgeName} {date} ? {time range} IST Interviewer: {interviewerName} Google Meet: {meetingUrl}*

>

> *Have your screen share ready and be online 5 minutes early. Running late- Mark it from your dashboard so your interviewer knows.*

3 ? Result variants

Pass ? title: `You cleared it ? {badgeName} Badge unlocked ?`

> *Congratulations, {studentName}. You passed your Level Clearance Interview for {trackName} ? {badgeName}.*

>

> *+{milesAward} Miles credited Badge added to your profile Qualiflyer status unlocked*

>

> *Your credential ID is {credentialId}. Share it on your profile ? your next badge is already waiting.*

Retake ? title: `Retake recommended ? available from {date}`

> *Your interviewer has asked for a retake rather than a fail. That's a good sign ? you're close.*

>

> *{trackName} ? {badgeName} Available to rebook: {date} Attempt {nextAttempt} of {maxAttempts}*

>

> *{optional focus area} Book as soon as the window opens ? slots for that week go live 7 days ahead.*

Fail ? title: `Interview result: not cleared this time`

> *Hi {studentName}, you didn't clear the {badgeName} Level Clearance Interview for {trackName}.*

>

> *{optional interviewer feedback}*

>

> *You can book a retake from {cooldown date} (attempt {nextAttempt} of {maxAttempts}). Use the time before then on the skill your interviewer flagged ? it's the one that will move the needle.*

The reminder template is shown in the message gallery and seeded as demo data; no production scheduler or external delivery is configured.

6. Before / after

Surface	Before	After pass	After fail / retake
Student home	Badge locked; book interview	Badge earned; +250 Miles; Qualiflyer	Cooldown and next attempt
Track / credential	Interview pending	Awarded with credential ID	Locked until eligible
Leaderboard projection	Not listed	Qualiflyer row	Pre-Qualiflyer
Interview Ops	Booked / not booked	Completed ? passed	In cooldown
Interviewer schedule	Appointment	Completed ? outcome	Completed ? outcome

The `/student/before-after` gallery uses the same dashboard components with representative snapshots. Its leaderboard rank is illustrative, not connected to a live leaderboard.

7. Architecture and local run

• Next.js App Router, TypeScript, Tailwind CSS, Lucide icons, Prisma, and SQLite for local demo data.

• Server Actions handle booking, cancellation/rescheduling, availability, outcomes, and Ops actions; role checks are performed server-side.

• `InterviewEvent` and `Notification` records make outcomes observable across personas.

• No real authentication, email, WhatsApp, or external meeting integration. Meet links are demo URLs.

```
npm install | npm run db:push | npm run db:seed | npm run dev
```

Use the persona switcher at `/`. PostgreSQL setup: run `npm run db:postgres`, set `DATABASE_URL` to the database connection string, then run `npm run db:push` and `npm run db:seed`. Return to local mode with `npm run db:sqlite` and `DATABASE_URL="file:./dev.db"`.