TYBCS Practical Slip Solutions

Object Oriented Programming using Java — IT

Slip 1)

1. Write a Java program to display all the alphabets between ‘A’ to *Z” after every 2 seconds.

```
public class Slip1 extends Thread
{
char c;
public void run()
{
for(c ='A’; c<=’Z’;c++)
{
System.out.println(""+c);
try{
Thread.sleep(2000);
catch(Exception e)
{
e.printStackTrace();
} } }
public static void main(String args[])
{
Slip1 t= new Slip1();
t.start();
} }
```

2. Write a Java program to accept the details of Employee (Eno, EName, Designation, Salary) from a user and store it into the database. (Use Swing)

```
import java.awt.*;
import javax.swing.*;
```

```
import java.awt.event.*;
import java.sql.*;
public class Ass1 extends Frame implements ActionListener
Label l1,l2,l3;TextField t1,t2,t3:
Button b;
Connection cn;
Statement st;
ResultSet rs;
public Ass1(){
setLayout(null);
l1=new Label("Eno");
l2=new Label("EName");
l3=new Label("Salary");
t1=new TextField();
t2=new TextField();
t3=new TextField();
b=new Button("Save");
l1.setBounds(50,50,100,30);
t1.setBounds(160,50,100,30);
l2.setBounds(50,90,100,30);
t2.setBounds(160,90,100,30);
l3.setBounds(160,130,100,30);
t3.setBounds(50,130,100,30);
b.setBounds(50,170,100,30);
add(l1);
add(t1);
add(l2);
add(t2);
add(l3);
```

```
add(t3);
add(b);
b.addActionListener(this);
setSize(500,500);
setVisible(true);
addWindowListener(new WindowAdapter()
public void windowClosing(WindowEvent e)
{   System.exit(0);
} }  );
public void actionPerformed(ActionEvent oe)
String str=oe.getActionCommand();
if(str.equals("Save"))
{
Try   {
Class.forName("sun.jdbc.odbc.JdbcOdbcDriver");
cn=DriverManager.getConnection("jdbc:odbe:Ass","","””);
st=cn.createStatement();
int en=Integer.parseInt(t3.getText());
String strr =” insert into emp values(“ + en +”,’”+ enn+”’,”+ sal +”)”;
Int k=st.executeUpdate(strr);
If(k>0)   {
JOptionPane.showMessageDialog(null, "Record Is Added");
}     }
catch(Exception er)      {
System.out.println("Error");
}  }     }
public static void main(String args[])    {
new Ass1().show();     }     }
```