

```
UtherVNC Viewer - Connection dropped, trying to reconnect (1)

C:\WINDOWS\system32\cmd.exe

Pinging 221.0.50.10 with 32 bytes of data:
Reply from 221.0.50.10: bytes=32 time=1ms TTL=125
Reply from 221.0.50.10: bytes=32 time=1ms TTL=125
Reply from 221.0.50.10: bytes=32 time=1ms TTL=125
Reply from 221.0.50.10: bytes=32 time=2ms TTL=125

Ping statistics for 221.0.50.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>ping 172.36.0.10

Pinging 172.36.0.10 with 32 bytes of data:
Reply from 172.36.0.10: bytes=32 time=2ms TTL=124
Reply from 172.36.0.10: bytes=32 time=2ms TTL=124
Reply from 172.36.0.10: bytes=32 time=3ms TTL=124
Reply from 172.36.0.10: bytes=32 time=2ms TTL=124

Ping statistics for 172.36.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 3ms, Average = 2ms

C:\Documents and Settings\user>
```

```
QEMU (Win-2)

C:\WINDOWS\system32\cmd.exe

Microsoft Windows [Version 5.1.2600]
(C) Copyright 1985-2003 Microsoft Corp.

C:\Documents and Settings\user>ipconfig

Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix . : 
    IP Address . . . . . : 221.0.50.10
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 221.0.50.1

C:\Documents and Settings\user>ping 192.50.20.100

Pinging 192.50.20.100 with 32 bytes of data:
Reply from 192.50.20.100: bytes=32 time=1ms TTL=125
Reply from 192.50.20.100: bytes=32 time=2ms TTL=125
Reply from 192.50.20.100: bytes=32 time=1ms TTL=125
Reply from 192.50.20.100: bytes=32 time=1ms TTL=125

Ping statistics for 192.50.20.100:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>ping 172.36.0.10

Pinging 172.36.0.10 with 32 bytes of data:
Reply from 172.36.0.10: bytes=32 time=2ms TTL=124
Reply from 172.36.0.10: bytes=32 time=2ms TTL=124
Reply from 172.36.0.10: bytes=32 time=2ms TTL=124
Reply from 172.36.0.10: bytes=32 time=2ms TTL=124

Ping statistics for 172.36.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 2ms, Average = 2ms

C:\Documents and Settings\user>
```

```
QEMU (Win-3)

C:\WINDOWS\system32\cmd.exe

Microsoft Windows [Version 5.1.2600]
(C) Copyright 1985-2003 Microsoft Corp.

C:\Documents and Settings\user>ipconfig

Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix . : 
    IP Address . . . . . : 172.36.0.10
    Subnet Mask . . . . . : 255.255.0.0
    Default Gateway . . . . . : 172.36.0.1

C:\Documents and Settings\user>ping 192.50.20.100

Pinging 192.50.20.100 with 32 bytes of data:
Reply from 192.50.20.100: bytes=32 time=2ms TTL=124
Reply from 192.50.20.100: bytes=32 time=2ms TTL=124
Reply from 192.50.20.100: bytes=32 time=2ms TTL=124
Reply from 192.50.20.100: bytes=32 time=2ms TTL=124

Ping statistics for 192.50.20.100:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 2ms, Average = 2ms

C:\Documents and Settings\user>ping 221.0.50.10

Pinging 221.0.50.10 with 32 bytes of data:
Reply from 221.0.50.10: bytes=32 time=1ms TTL=124
Reply from 221.0.50.10: bytes=32 time=2ms TTL=124
Reply from 221.0.50.10: bytes=32 time=2ms TTL=124
Reply from 221.0.50.10: bytes=32 time=2ms TTL=124

Ping statistics for 221.0.50.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>
```

```

R1
Interface      IP-Address      OK? Method Status      Prot
Gig0/0/0
Ethernet0/0     192.50.20.1     YES manual up          up
Ethernet0/1     12.0.0.1        YES manual up          up
Ethernet0/2     unassigned      YES TFTP  down        down
Ethernet0/3     unassigned      YES TFTP  down        down

R1#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       O - OSPF, EX - OSPF external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       I - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, I - IGRP
       a - application route
       * - replicated route, h - next hop override, p - overrides from pfk

Gateway of last resort is not set

    12.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
    C    12.0.0.0/8 is directly connected, Ethernet0/1
    L    12.0.0.1/32 is directly connected, Ethernet0/1
    S    23.0.0.0/8 [1/0] via 12.0.0.2
    S    24.0.0.0/8 [1/0] via 12.0.0.2
    S    26.0.0.0/8 [1/0] via 12.0.0.2
    S    32.0.0.0/8 [1/0] via 12.0.0.2
    S    45.0.0.0/8 [1/0] via 12.0.0.2
    S    172.16.0.0/16 [1/0] via 12.0.0.2
    S    192.50.20.0/24 is variably subnetted, 2 subnets, 2 masks
    C    192.50.20.0/24 is directly connected, Ethernet0/0
    L    192.50.20.1/32 is directly connected, Ethernet0/0
    S    223.0.50.0/24 [1/0] via 12.0.0.2

R1#
R1#
R1#

```

```

R2
Interface      IP-Address      OK? Method Status      Prot
Gig0/0/0
Ethernet0/0     12.0.0.2        YES manual up          up
Ethernet0/1     26.0.0.1        YES manual up          up
Ethernet0/2     23.0.0.1        YES manual up          up
Ethernet0/3     24.0.0.1        YES manual up          up

R2#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       O - OSPF, EX - OSPF external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       I - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, I - IGRP
       a - application route
       * - replicated route, h - next hop override, p - overrides from pfk

Gateway of last resort is not set

    12.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
    C    12.0.0.0/8 is directly connected, Ethernet0/0
    L    12.0.0.2/32 is directly connected, Ethernet0/0
    S    23.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
    C    23.0.0.0/8 is directly connected, Ethernet0/2
    L    23.0.0.1/32 is directly connected, Ethernet0/2
    S    24.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
    C    24.0.0.0/8 is directly connected, Ethernet0/3
    L    24.0.0.1/32 is directly connected, Ethernet0/3
    S    26.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
    C    26.0.0.0/8 is directly connected, Ethernet0/1
    L    26.0.0.1/32 is directly connected, Ethernet0/1
    S    32.0.0.0/8 [1/0] via 23.0.0.2
    S    45.0.0.0/8 [1/0] via 24.0.0.2
    S    172.16.0.0/16 [1/0] via 24.0.0.2
    S    192.50.20.0/24 [1/0] via 12.0.0.1
    S    223.0.50.0/24 [1/0] via 26.0.0.2

R2#

```

```

Router#sh ip int brief
Interface      IP-Address      OK? Method Status      Prot
Gig0/0/0       24.0.0.2        YES manual up          up
Ethernet0/0     45.0.0.1        YES manual up          up
Ethernet0/1     unassigned      YES unset  administratively down down
Ethernet0/2     unassigned      YES unset  administratively down down
Ethernet0/3     unassigned      YES unset  administratively down down

Router#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       +- replicated route, % - next hop override, p - overrides from PBR

Gateway of last resort is not set

S 12.0.0.0/8 [1/0] via 24.0.0.1
C 24.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C   24.0.0.0/8 is directly connected, Ethernet0/0
L   24.0.0.2/32 is directly connected, Ethernet0/0
S 26.0.0.0/8 [1/0] via 24.0.0.1
C 45.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C   45.0.0.0/8 is directly connected, Ethernet0/1
L   45.0.0.1/32 is directly connected, Ethernet0/1
S 172.36.0.0/16 [1/0] via 45.0.0.2
S 192.50.20.0/24 [1/0] via 24.0.0.1
S 223.0.50.0/24 [1/0] via 24.0.0.1

Router#
Router#
Router#

```

```

Router#
Router#sh ip int brief
Interface      IP-Address      OK? Method Status      Prot
Gig0/0/0       23.0.0.2        YES manual up          up
Ethernet0/0     32.0.0.1        YES manual up          up
Ethernet0/1     unassigned      YES unset  administratively down down
Ethernet0/2     unassigned      YES unset  administratively down down
Ethernet0/3     unassigned      YES unset  administratively down down

Router#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       +- replicated route, % - next hop override, p - overrides from PBR

Gateway of last resort is not set

S 12.0.0.0/8 [1/0] via 23.0.0.1
C 23.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C   23.0.0.0/8 is directly connected, Ethernet0/0
L   23.0.0.2/32 is directly connected, Ethernet0/0
S 26.0.0.0/8 [1/0] via 23.0.0.1
C 32.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C   32.0.0.0/8 is directly connected, Ethernet0/1
L   32.0.0.1/32 is directly connected, Ethernet0/1
S 172.36.0.0/16 [1/0] via 32.0.0.2
S 192.50.20.0/24 [1/0] via 23.0.0.1
S 223.0.50.0/24 [1/0] via 23.0.0.1

Router#
Router#
Router#

```

```

R5#
R5#sh ip int brief
Interface IP-Address OK? Method Status Protocol
Ethernet0/0 172.36.0.1 YES manual up up
Ethernet0/1 32.0.0.2 YES manual up up
Ethernet0/2 45.0.0.2 YES manual up up
Ethernet0/3 unassigned YES TFTP down down

R5#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        I - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route, H - NHRP, I - IGRP
        a - application route
        * - replicated route, % - next hop override, p - overrides from PFR

Gateway of last resort is not set

S 12.0.0.0/8 [1/0] via 32.0.0.1
S 23.0.0.0/8 [1/0] via 32.0.0.1
S 24.0.0.0/8 [1/0] via 45.0.0.1
   [1/0] via 32.0.0.1
S 26.0.0.0/8 [1/0] via 32.0.0.1
C 32.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
   32.0.0.0/8 is directly connected, Ethernet0/1
   32.0.0.2/32 is directly connected, Ethernet0/1
C 45.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
   45.0.0.0/8 is directly connected, Ethernet0/2
   45.0.0.2/32 is directly connected, Ethernet0/2
C 172.36.0.0/16 is variably subnetted, 2 subnets, 2 masks
   172.36.0.0/16 is directly connected, Ethernet0/0
   172.36.0.1/32 is directly connected, Ethernet0/0
L 192.50.20.0/24 [1/0] via 32.0.0.1
S 223.0.50.0/24 [1/0] via 45.0.0.1
   [1/0] via 32.0.0.1

```

```

R6#
R6#sh ip int brief
Interface IP-Address OK? Method Status Protocol
Ethernet0/0 223.0.50.1 YES manual up up
Ethernet0/1 26.0.0.2 YES manual up up
Ethernet0/2 unassigned YES TFTP down down
Ethernet0/3 unassigned YES TFTP down down

R6#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        I - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route, H - NHRP, I - IGRP
        a - application route
        * - replicated route, % - next hop override, p - overrides from PFR

Gateway of last resort is not set

S 12.0.0.0/8 [1/0] via 26.0.0.1
S 23.0.0.0/8 [1/0] via 26.0.0.1
S 24.0.0.0/8 [1/0] via 26.0.0.1
S 26.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
   26.0.0.0/8 is directly connected, Ethernet0/1
   26.0.0.2/32 is directly connected, Ethernet0/1
S 32.0.0.0/8 [1/0] via 26.0.0.1
S 45.0.0.0/8 [1/0] via 26.0.0.1
S 172.36.0.0/16 [1/0] via 26.0.0.1
S 192.50.20.0/24 [1/0] via 26.0.0.1
C 223.0.50.0/24 is variably subnetted, 2 subnets, 2 masks
   223.0.50.0/24 is directly connected, Ethernet0/0
   223.0.50.1/32 is directly connected, Ethernet0/0
R6#
R6#
R6#

```