

R2

R2#

*Jul 15 07:37:12.379: %SYS-5-CONFIG_I: Configured from console by console

R2#show ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

S 10.0.0.0/8 [1/0] via 20.0.0.1

20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

C 20.0.0.0/8 is directly connected, Ethernet0/0

L 20.0.0.2/32 is directly connected, Ethernet0/0

30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

C 30.0.0.0/8 is directly connected, Ethernet0/1

L 30.0.0.1/32 is directly connected, Ethernet0/1



R3

-



```
R3#config terminal
```

```
*Jul 15 07:33:15.141: %SYS-5-CONFIG_I: Configured from console by console
```

```
R3#show ip route
```

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2  
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2  
ia - IS-IS inter area, * - candidate default, U - per-user static route  
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP  
a - application route  
+ - replicated route, % - next hop override, p - overrides from PfR
```

```
Gateway of last resort is not set
```

```
S    10.0.0.0/8 [1/0] via 30.0.0.1
```

```
S    20.0.0.0/8 [1/0] via 30.0.0.1
```

```
30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
```

```
C    30.0.0.0/8 is directly connected, Ethernet0/1
```

```
L    30.0.0.2/32 is directly connected, Ethernet0/1
```

```
40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
```

```
C    40.0.0.0/8 is directly connected, Ethernet0/0
```

```
L    40.0.0.1/32 is directly connected, Ethernet0/0
```

```
R3#
```

```
R1
R1#exi
*Jul 15 07:38:22.748: %SYS-5-CONFIG_I: Configured from console by console
R1#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       10.0.0.0/8 is directly connected, Ethernet0/0
L       10.0.0.1/32 is directly connected, Ethernet0/0
    20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       20.0.0.0/8 is directly connected, Ethernet0/1
L       20.0.0.1/32 is directly connected, Ethernet0/1
S       30.0.0.0/8 [1/0] via 20.0.0.2
S       40.0.0.0/8 [1/0] via 20.0.0.2
R1#
```

C:\WINDOWS\system32\cmd.exe

\Documents and Settings\user>ipconfig

Windows IP Configuration

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix . :
IP Address. : 40.0.0.10
Subnet Mask : 255.0.0.0
Default Gateway : 40.0.0.1

\Documents and Settings\user>ping 10.0.0.10

Pinging 10.0.0.10 with 32 bytes of data:

Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=1ms TTL=125

ping statistics for 10.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\WINDOWS\system32\cmd.exe

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix	:	
IP Address	:	10.0.0.10
Subnet Mask	:	255.0.0.0
Default Gateway	:	10.0.0.1

C:\Documents and Settings\user>ping 40.0.0.10

Pinging 40.0.0.10 with 32 bytes of data:

Reply from 40.0.0.10: bytes=32 time=4ms TTL=125
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125

Ping statistics for 40.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 2ms, Maximum = 4ms, Average = 2ms

C:\Documents and Settings\user>