# 315 PLOTS API (1.0)

Download OpenAPI specification: Download

License: Proprietary

Backend for the 315 PLOTS mobile app.

**Roles** — `USER` (every customer; becomes a partner after admin approval) and `ADMIN` (operations, `/admin/*`).

**Try it here**

1. `POST /auth/otp/request` with your mobile.
2. `POST /auth/otp/verify` with the code (in staging the code is in the server logs).
3. Click **Authorize** and paste `accessToken`.

**Conventions**

- Money is **integer paise**: `amountPaise: 2100000` = ₹21,000. Display ₹ = paise ÷ 100.
- Lists take `page` (from 0) and `size` (1–50) and return `{ items, page, size, total }`.
- Every error is `{ code, message, requestId }` — branch on `code`.
- Access tokens last 15 minutes; refresh with `POST /auth/refresh` (one refresh at a time).
- Dates are ISO-8601 UTC.

## Auth

Sign in with mobile OTP or Google, refresh and revoke tokens.

## Send login OTP

Sends a 6-digit OTP by SMS. The code is valid for 5 minutes. Limits: 3 requests per mobile per 15 minutes, 30 per IP per minute.

REQUEST BODY SCHEMA: application/json

required

mobile
required

string^[6-9]\d{9}$
10-digit Indian mobile number without +91, starting with 6–9

## Responses

**— 200**

OTP sent

**> 400**

Bad request: VALIDATION_FAILED

**> 429**

Too many requests: OTP_RATE_LIMITED

POST /auth/otp/request

### Request samples

Payload

Content type
application/json

Copy

```
{
   "mobile": "9876543210"
}
```

### Response samples

200 400 429

Content type
application/json

Copy

```
{
    "expiresInSec": 300,
    "resendAfterSec": 30
}
```

## Verify OTP and sign in

Checks the OTP and returns tokens. Creates the account on first login (optionally under a referral code). `profileComplete: false` means send the user to the profile screen before booking.

REQUEST BODY SCHEMA: application/json
required

- **mobile** (required)
  string ^[6-9]\d{9}$
  Same mobile the OTP was requested for
- **code** (required)
  string = 6 characters ^\d{6}$
  6-digit code received by SMS (valid 5 minutes, 5 attempts)
- **referralCode**
  string <= 20 characters
  Optional. Partner's referral code; applied only when this creates a new account
- **leg**
  string
  Enum: `"L"` `"R"`
  Optional. Side of the sponsor's team (L or R). Omit to auto-balance
- **deviceId**
  string <= 200 characters
  Optional. Device identifier, stored with the refresh token

## Responses

**— 200**

Signed in

**400**

Bad request: OTP_INVALID, OTP_EXPIRED, INVALID_REFERRAL, VALIDATION_FAILED

**403**

Not allowed: ACCOUNT_DISABLED

**429**

Too many requests: OTP_LOCKED

POST /auth/otp/verify

## Request samples

Payload

Content type
application/json

Copy

```
{
   "mobile": "9876543210",
   "code": "482913",
   "referralCode": "P7KQ2XM",
   "deviceId": "pixel-7-a1b2"
}
```

## Response samples

200 400 403 429

Content type
application/json

Copy

```
{
   "accessToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiI2ZjFj…",
   "refreshToken": "q8V2c1sY9…",
```

```
    "expiresIn": 900,
    "isNewUser": true,
    "profileComplete": false
}
```


## Sign in with Google

Verifies a Google ID token (verified email required) and returns tokens. Links to an existing account with the same email. Returns 501 if Google sign-in isn't configured.

REQUEST BODY SCHEMA: application/json
required

- **idToken** (required)
  string
  ID token from Google Sign-In on the device (requested with the Web client ID)
- **referralCode**
  string <= 20 characters
  Optional. Applied only for a new account
- **leg**
  string
  Enum: `"L"` `"R"`
  Optional. L or R
- **deviceId**
  string <= 200 characters
  Optional. Device identifier

## Responses

**— 200**

Signed in

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: GOOGLE_TOKEN_INVALID, GOOGLE_EMAIL_UNVERIFIED

> 501

Not configured: NOT_CONFIGURED

POST /auth/google

## Request samples

Payload

Content type
application/json

Copy

```
{
    "idToken": "eyJhbGciOiJSUzI1NiIsImtpZCI6…",
    "referralCode": "P7KQ2XM"
}
```

## Response samples

200 | 400 | 401 | 501

Content type
application/json

Copy

```
{
    "accessToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiI2ZjFj…",
    "refreshToken": "q8V2c1sY9…",
    "expiresIn": 900,
    "isNewUser": false,
    "profileComplete": true
}
```

# Sign in with Firebase Phone Auth

The app verifies the mobile number with Firebase (Firebase sends and checks the SMS code), then sends the Firebase ID token here. Creates the account on first sign-in. Only +91 numbers are accepted.

REQUEST BODY SCHEMA: application/json
required

| | | |
|---|---|---|
| idToken<br>required | string | |
| referralCode | string | <= 20 characters |
| leg | string<br>Enum: `"L"` `"R"` | |
| deviceId | string | <= 200 characters |

## Responses

**— 200**

Signed in

**> 400**

Bad request: PHONE_NOT_SUPPORTED, VALIDATION_FAILED

**> 401**

Not signed in or token expired: FIREBASE_TOKEN_INVALID

**> 403**

Not allowed: ACCOUNT_DISABLED

**> 501**

Not configured: NOT_CONFIGURED

POST /auth/firebase

### Request samples

Payload

Content type
application/json

Copy

```
{
   "idToken": "eyJhbGciOiJSUzI1NiIsImtpZCI6…",
   "referralCode": "P7KQ2XM"
}
```

### Response samples

200 | 400 | 401 | 403 | 501

Content type
application/json

Copy

```
{
   "accessToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiI2ZjFj…",
   "refreshToken": "q8V2c1sY9…",
   "expiresIn": 900,
   "isNewUser": false,
   "profileComplete": true
}
```

## Refresh tokens

Exchanges a refresh token for a new access + refresh token pair; the old refresh token stops working. Run one refresh at a time: reusing an old refresh token signs the user out on every device.

REQUEST BODY SCHEMA: application/json

required

refreshToken
required

string

Refresh token from the last login or refresh

## Responses

**— 200**

New tokens

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: TOKEN_INVALID, TOKEN_REUSED

**> 403**

Not allowed: ACCOUNT_DISABLED

POST /auth/refresh

### Request samples

Payload

Content type

application/json

Copy

```
{
   "refreshToken": "q8V2c1sY9…"
}
```

### Response samples

200 400 401 403

**Content type**
application/json

Copy

```
{
    "accessToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiI2ZjFj…",
    "refreshToken": "q8V2c1sY9…",
    "expiresIn": 900
}
```

## Log out this device

Revokes the given refresh token.

REQUEST BODY SCHEMA: application/json
required

| | | |
|---|---|---|
| refreshToken<br>required | string | Refresh token from the last login or refresh |

## Responses

**— 200**

Logged out

**> 400**

Bad request: VALIDATION_FAILED

POST /auth/logout

### Request samples

Payload

Content type
application/json

Copy

```
{
    "refreshToken": "q8V2c1sY9…"
}
```

### Response samples

200 400

Content type
application/json

Copy

```
{
    "ok": true
}
```

## Profile

The signed-in user's profile, nominee, push token and sponsor.

## Splash-screen data

Everything the app needs at launch: user, whether the profile is complete, minimum app version, whether bookings are open, support contacts. Route: 401 → login; old app → force update; profileComplete false → profile; role ADMIN → admin panel.

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

Bootstrap data

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 429**

Too many requests: RATE_LIMITED

GET /me/bootstrap

### Response samples

200 | 401 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
  - "user": {
        "id": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
        "role": "USER",
        "mobile": "9876543210",
        "email": "asha@example.com",
        "name": "Asha Patil",
        "address": "Baner, Pune",
        "partnerStatus": "APPROVED",
        "sponsorId": "9a2b3c4d-5e6f-4a7b-8c9d-0e1f2a3b4c5d",
        "leg": "L",
        "referralCode": "P7KQ2XM",
        "active": true,
        "createdAt": "2026-10-22T09:30:00.000Z"
    },
```

```
    "profileComplete": true,
    "minAppVersion": "1.0.0",
    "bookingsEnabled": true,
  - "support": {
        "phone": "+91 20 0000 0000",
        "email": "support@315plots.app"
    }
}
```


# My profile

Profile with nominee.

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

Profile

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /me

**Response samples**

200 401 429

**Content type**
application/json

Copy Expand all Collapse all


```
{
   "id": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
   "role": "USER",
   "mobile": "9876543210",
   "email": "asha@example.com",
   "name": "Asha Patil",
   "address": "Baner, Pune",
   "partnerStatus": "APPROVED",
   "sponsorId": "9a2b3c4d-5e6f-4a7b-8c9d-0e1f2a3b4c5d",
   "leg": "L",
   "referralCode": "P7KQ2XM",
   "active": true,
   "createdAt": "2026-10-22T09:30:00.000Z",
 - "nominee": {
      "name": "Rahul Patil",
      "relation": "Spouse",
      "mobile": "9876500000"
   }
}
```


## Update my profile

Name is required before booking. Email must be unique.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- `name` required — string <= 100 characters
  Full name (required before booking)
- `email` — string <= 200 characters
  Optional. Must be unique across accounts

address

string <= 500 characters

Optional. Postal address

## Responses

**— 200**

Updated profile

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 409**

Conflict (state changed): CONFLICT

**> 429**

Too many requests: RATE_LIMITED

PUT /me

### Request samples

Payload

Content type

application/json

Copy

```
{
    "name": "Asha Patil",
    "email": "asha@example.com",
    "address": "Baner, Pune 411045"
```

```
}
```

### Response samples

200 | 400 | 401 | 409 | 429

Content type
application/json

Copy


```
{
    "id": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
    "role": "USER",
    "mobile": "9876543210",
    "email": "asha@example.com",
    "name": "Asha Patil",
    "address": "Baner, Pune",
    "partnerStatus": "APPROVED",
    "sponsorId": "9a2b3c4d-5e6f-4a7b-8c9d-0e1f2a3b4c5d",
    "leg": "L",
    "referralCode": "P7KQ2XM",
    "active": true,
    "createdAt": "2026-10-22T09:30:00.000Z",
    "nominee": null
}
```


## Set nominee

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **name** (required) — string <= 100 characters
  Nominee's full name
- **relation** (required) — string <= 50 characters
  Relation to the customer

mobile

string^[6-9]\d{9}$

Optional. Nominee's 10-digit mobile

## Responses

**— 200**

Updated profile

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

PUT /me/nominee

### Request samples

Payload

Content type

application/json

Copy

```
{
   "name": "Rahul Patil",
   "relation": "Spouse",
   "mobile": "9876500000"
}
```

### Response samples

200 | 400 | 401 | 429

**Content type**
application/json

Copy Expand all Collapse all


```
{
   "id": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
   "role": "USER",
   "mobile": "9876543210",
   "email": "asha@example.com",
   "name": "Asha Patil",
   "address": "Baner, Pune",
   "partnerStatus": "APPROVED",
   "sponsorId": "9a2b3c4d-5e6f-4a7b-8c9d-0e1f2a3b4c5d",
   "leg": "L",
   "referralCode": "P7KQ2XM",
   "active": true,
   "createdAt": "2026-10-22T09:30:00.000Z",
 - "nominee": {
      "name": "Rahul Patil",
      "relation": "Spouse",
      "mobile": "9876500000"
   }
}
```


# Register push token

Call after every login and whenever Firebase rotates the token. Push notifications go to every registered device.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **token** (required) — string <= 4096 characters
  Firebase Cloud Messaging registration token
- **platform** — string

required

Enum: `"android"` `"ios"`
android or ios

## Responses

**— 201**

Registered

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

POST /me/devices

### Request samples

Payload

Content type
application/json

Copy

```
{
   "token": "fcm-token-dGhpc2lz…",
   "platform": "android"
}
```

### Response samples

201 400 401 429

**Content type**
application/json

Copy

```
{
    "ok": true
}
```

## Add a referral code later

For users who signed up without a code. Not allowed once a sponsor is set or after the first booking.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- `referralCode` required
  string <= 20 characters
  Approved partner's referral code
- `leg`
  string
  Enum: `"L"` `"R"`
  Optional. L or R; omit to auto-balance

### Responses

**— 200**

Updated profile

**> 400**

Bad request: INVALID_REFERRAL, INVALID_SPONSOR, VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

> 409

Conflict (state changed): SPONSOR_LOCKED, SPONSOR_ALREADY_SET

> 429

Too many requests: RATE_LIMITED

PUT /me/sponsor

## Request samples

Payload

Content type
application/json

Copy

```
{
    "referralCode": "P7KQ2XM",
    "leg": "L"
}
```

## Response samples

200 | 400 | 401 | 409 | 429

Content type
application/json

Copy

```
{
    "id": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
    "role": "USER",
    "mobile": "9876543210",
    "email": "asha@example.com",
    "name": "Asha Patil",
    "address": "Baner, Pune",
    "partnerStatus": "APPROVED",
```

```
    "sponsorId": "9a2b3c4d-5e6f-4a7b-8c9d-0e1f2a3b4c5d",
    "leg": "L",
    "referralCode": "P7KQ2XM",
    "active": true,
    "createdAt": "2026-10-22T09:30:00.000Z"
}
```


# Partner

Referral programme: apply, referral link, team, leads. Requires partner approval except apply.

## Apply to become a partner

Moves partnerStatus NONE/REJECTED → PENDING. An admin approves or rejects; the user is notified.

AUTHORIZATIONS: > *bearer*

### Responses

**— 201**

Application submitted

**> 400**

Bad request: PROFILE_INCOMPLETE

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 409**

Conflict (state changed): INVALID_STATE

> 429

Too many requests: RATE_LIMITED

POST /partners/apply

**Response samples**

201 | 400 | 401 | 409 | 429

Content type
application/json

Copy

```
{
   "partnerStatus": "PENDING"
}
```

## My partner status and referral link

referralCode and referralLink are null until approved. directLeft/directRight count direct recruits per leg.

AUTHORIZATIONS: > *bearer*

### Responses

— 200

Partner info

> 401

Not signed in or token expired: UNAUTHORIZED

**429**

Too many requests: RATE_LIMITED

GET /partners/me

### Response samples

200 | 401 | 429

Content type
application/json

Copy


```
{
   "partnerStatus": "APPROVED",
   "referralCode": "P7KQ2XM",
   "referralLink": "https://315plots.app/r/P7KQ2XM",
   "directLeft": 4,
   "directRight": 2
}
```


## My team (3 levels)

Members below me. Query `level` 0 = all three levels, or 1/2/3. `side` is which of my two legs the member is in. Mobiles are masked.

AUTHORIZATIONS: *bearer*

QUERY PARAMETERS

- `page` — integer `>= 0`
  Default: `0`
  Page number, starting at 0
- `size` — integer `[ 1 .. 50 ]`

Default: `20`

Items per page (1–50)

`level`

integer `[ 0 .. 3 ]`

Default: `0`

Team level: 0 = all three, or 1, 2, 3

## Responses

**— 200**

Team members

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 403**

Not allowed: PARTNER_NOT_APPROVED

**› 429**

Too many requests: RATE_LIMITED

GET `/partners/network`

### Response samples

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
```

```
    "page": 0,
    "size": 20,
    "total": 9
}
```


## Register a lead

Records a prospect. When that mobile signs up without a referral code, you become their sponsor automatically.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **name** (required)
  string <= 100 characters
  Prospect's name
- **mobile** (required)
  string^[6-9]\d{9}$
  Prospect's 10-digit mobile; links to you when they sign up
- **note**
  string <= 500 characters
  Optional. Private note

### Responses

**— 201**

Lead created

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**403**

Not allowed: PARTNER_NOT_APPROVED

**409**

Conflict (state changed): ALREADY_REGISTERED

**429**

Too many requests: RATE_LIMITED

POST /leads

## Request samples

Payload

Content type
application/json

Copy

```
{
    "name": "Neha Shah",
    "mobile": "9822000000",
    "note": "Met at site visit"
}
```

## Response samples

201 | 400 | 401 | 403 | 409 | 429

Content type
application/json

Copy

```
{
    "id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c55",
    "partnerId": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
    "name": "Neha Shah",
```

```
    "mobile": "9822000000",
    "note": "Met at site visit",
    "convertedUserId": null,
    "createdAt": "2026-10-22T09:30:00.000Z"
}
```


# My leads

Status: NEW (not signed up), REGISTERED (signed up), BOOKED (has a confirmed booking).

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

- `page` — integer `>= 0`
  Default: `0`
  Page number, starting at 0
- `size` — integer `[ 1 .. 50 ]`
  Default: `20`
  Items per page (1–50)

## Responses

**— 200**

Leads

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: PARTNER_NOT_APPROVED

> 429

Too many requests: RATE_LIMITED

GET /leads

**Response samples**

200 401 403 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
   "total": 1
}
```


# Plots

Plot inventory and booking plans.

## List plots

Filter by status (AVAILABLE, HELD, BOOKED, BLOCKED), block and facing. `summary` gives the count per status for the whole project. Use lat/lng for map pins. Only AVAILABLE plots can be booked.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

| | |
|---|---|
| `status` | string<br>Enum: `"AVAILABLE"` `"HELD"` `"BOOKED"` `"BLOCKED"`<br>Filter by status |
| `block` | string `<= 50 characters`<br>Filter by block |
| `facing` | string `<= 50 characters`<br>Filter by facing direction |
| `page` | integer `>= 0`<br>Default: `0`<br>Page number, starting at 0 |
| `size` | integer `[ 1 .. 50 ]`<br>Default: `20`<br>Items per page (1–50) |

## Responses

**— 200**

Plots

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET `/plots`

**Response samples**

200 401 429

Content type
application/json

Copy Expand all Collapse all


```
{
  - "items": [
      + { … }
    ],
    "page": 0,
    "size": 20,
    "total": 312,
  - "summary": [
      + { … },
      + { … }
    ]
}
```


## Plot details

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | |
|---|---|
| id<br>required | string<br>Resource ID |

## Responses

**— 200**

Plot

**> 401**

Not signed in or token expired: UNAUTHORIZED

> 404

Not found: NOT_FOUND

> 429

Too many requests: RATE_LIMITED

GET /plots/{id}

**Response samples**

200 | 401 | 404 | 429

Content type
application/json

Copy


```
{
    "id": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
    "plotNo": "P-001",
    "block": "A",
    "facing": "East",
    "areaSqft": 1200,
    "pricePaise": 500000000,
    "lat": 18.52,
    "lng": 73.85,
    "status": "AVAILABLE"
}
```


## Booking plans

Active plans in display order. Always show prices from here. Commission rates are basis points (2000 = 20%).

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

Plans

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /tiers

### Response samples

200 | 401 | 429

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "id": "a3c5e7f9-1b2d-4f6a-8c0e-2d4f6a8c0e11",
      "code": "EXPRESS",
      "name": "Express Token",
      "amountPaise": 2100000,
      "l1Bps": 1000,
      "l2Bps": 500,
      "l3Bps": 500,
      "benefits": null,
      "active": true
   },
```

```
  - {
        "id": "b7a1c3e5-9d2f-4b6a-8e0c-1f3d5a7b9c22",
        "code": "GOLD",
        "name": "Gold",
        "amountPaise": 30000000,
        "l1Bps": 2000,
        "l2Bps": 1000,
        "l3Bps": 1000,
        "benefits": null,
        "active": true
    }
]
```


# Bookings

Hold a plot and pay through Razorpay.

## Book a plot (start checkout)

Holds the plot for 15 minutes and creates a Razorpay order. Open Razorpay Checkout with razorpayKeyId, razorpayOrderId and amountPaise, then call POST /payments/verify. The booking becomes CONFIRMED only after the server verifies the payment.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **plotId** (required) — string
  Plot to book (from GET /plots, must be AVAILABLE)
- **tierId** (required) — string
  Booking plan (from GET /tiers)
- **termsAccepted** (required) — boolean
  Must be true: the customer accepted the booking terms

## Responses

**— 201**

Checkout started

**> 400**

Bad request: PROFILE_INCOMPLETE, VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 404**

Not found: NOT_FOUND

**> 409**

Conflict (state changed): PLOT_UNAVAILABLE, PENDING_BOOKING_EXISTS

**> 429**

Too many requests: RATE_LIMITED

**> 502**

Payment/payout provider error: PROVIDER_ERROR

**> 503**

Temporarily unavailable: BOOKINGS_PAUSED

POST `/bookings`

### Request samples

Payload

Content type
application/json

Copy


```
{
    "plotId": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
    "tierId": "b7a1c3e5-9d2f-4b6a-8e0c-1f3d5a7b9c22",
    "termsAccepted": true
}
```


### Response samples

201 | 400 | 401 | 404 | 409 | 429 | 502 | 503

Content type
application/json

Copy


```
{
    "bookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
    "bookingRef": "BK-2026-000123",
    "paymentId": "d1e2f3a4-b5c6-4d7e-8f9a-0b1c2d3e4f88",
    "paymentRef": "PAY-2026-000124",
    "amountPaise": 30000000,
    "currency": "INR",
    "razorpayOrderId": "order_N8xQ2LkP3a",
    "razorpayKeyId": "rzp_live_AbC123",
    "holdExpiresAt": "2026-10-22T09:45:00.000Z"
}
```


## My bookings

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

page

integer >= 0

Default: 0

Page number, starting at 0

size

integer [ 1 .. 50 ]

Default: 20

Items per page (1–50)

## Responses

**— 200**

Bookings

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /bookings

### Response samples

200 401 429

Content type

application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
```

```
    "total": 1
}
```


## Booking details

Status: PENDING_PAYMENT, CONFIRMED, EXPIRED, CANCELLED, REFUND_PENDING, REFUNDED. Poll this after payment until CONFIRMED.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | | |
|---|---|---|
| id<br>required | string | Resource ID |

### Responses

**— 200**

Booking

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

GET /bookings/{id}

**Response samples**

200 401 404 429

Content type
application/json

Copy Expand all Collapse all


```
{
   "id": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
   "internalRef": "BK-2026-000123",
   "status": "CONFIRMED",
   "amountPaise": 30000000,
   "holdExpiresAt": "2026-10-22T09:45:00.000Z",
   "confirmedAt": "2026-10-22T09:30:00.000Z",
   "createdAt": "2026-10-22T09:30:00.000Z",
 - "plot": {
      "id": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
      "plotNo": "P-001",
      "block": "A",
      "facing": "East",
      "areaSqft": 1200,
      "lat": 18.52,
      "lng": 73.85
   },
 - "tier": {
      "id": "b7a1c3e5-9d2f-4b6a-8e0c-1f3d5a7b9c22",
      "code": "GOLD",
      "name": "Gold"
   },
 - "payments": [
    + { … }
   ],
 - "documents": [
    + { … }
   ]
}
```


## Retry payment

New Razorpay order for an unpaid booking while its hold is still live.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | | |
|---|---|---|
| id<br>required | string | Resource ID |

## Responses

**— 201**

New checkout

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 404**

Not found: NOT_FOUND

**> 409**

Conflict (state changed): HOLD_EXPIRED

**> 429**

Too many requests: RATE_LIMITED

**> 502**

Payment/payout provider error: PROVIDER_ERROR

POST /bookings/{id}/retry-payment

### Response samples

201 | 401 | 404 | 409 | 429 | 502

**Content type**
application/json

Copy


```
{
    "bookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
    "bookingRef": "BK-2026-000123",
    "paymentId": "d1e2f3a4-b5c6-4d7e-8f9a-0b1c2d3e4f88",
    "paymentRef": "PAY-2026-000124",
    "amountPaise": 30000000,
    "currency": "INR",
    "razorpayOrderId": "order_N8xQ2LkP3a",
    "razorpayKeyId": "rzp_live_AbC123",
    "holdExpiresAt": "2026-10-22T09:45:00.000Z"
}
```


# Payments

Payment verification, history and receipts.

## Confirm payment after Checkout

Send the three values from the Razorpay Checkout success callback. The server checks the signature and asks Razorpay for the real status. If bookingStatus is still PENDING_PAYMENT, poll GET /bookings/{id}.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- `razorpayOrderId` — required
  string <= 100 characters
  razorpay_order_id from the Checkout success callback
- `razorpayPaymentId` — required
  string <= 100 characters
  razorpay_payment_id from the Checkout success callback

razorpaySignature
required

string <= 200 characters

razorpay_signature from the Checkout success callback

## Responses

**— 200**

Payment status

**> 400**

Bad request: SIGNATURE_INVALID, VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

POST /payments/verify

### Request samples

Payload

Content type
application/json

Copy

```
{
  "razorpayOrderId": "order_N8xQ2LkP3a",
  "razorpayPaymentId": "pay_N8yR7mT2b",
  "razorpaySignature": "9e1c4b7a2f…"
```

```
}
```

### Response samples

200 | 400 | 401 | 404 | 429

Content type
application/json

Copy


```
{
    "id": "d1e2f3a4-b5c6-4d7e-8f9a-0b1c2d3e4f88",
    "internalRef": "PAY-2026-000124",
    "status": "VERIFIED",
    "amountPaise": 30000000,
    "providerPaymentId": "pay_N8yR7mT2b",
    "failureReason": null,
    "verifiedAt": "2026-10-22T09:30:00.000Z",
    "createdAt": "2026-10-22T09:30:00.000Z",
    "bookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
    "bookingRef": "BK-2026-000123",
    "bookingStatus": "CONFIRMED"
}
```


## My payments

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

**page** integer >= 0
Default: 0
Page number, starting at 0

**size** integer [ 1 .. 50 ]
Default: 20
Items per page (1–50)

## Responses

**— 200**

Payments

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 429**

Too many requests: RATE_LIMITED

GET /payments

### Response samples

200 | 401 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
   "total": 1
}
```


## Payment status

Status: CREATED, PENDING, VERIFIED, FAILED, REFUND_PENDING, REFUNDED.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | | |
|---|---|---|
| id<br>required | string | Resource ID |

## Responses

**— 200**

Payment

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

GET /payments/{id}

### Response samples

200 | 401 | 404 | 429

**Content type**
application/json

Copy


```
{
    "id": "d1e2f3a4-b5c6-4d7e-8f9a-0b1c2d3e4f88",
    "internalRef": "PAY-2026-000124",
    "status": "VERIFIED",
```

```
    "amountPaise": 30000000,
    "providerPaymentId": "pay_N8yR7mT2b",
    "failureReason": null,
    "verifiedAt": "2026-10-22T09:30:00.000Z",
    "createdAt": "2026-10-22T09:30:00.000Z",
    "bookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
    "bookingRef": "BK-2026-000123",
    "bookingStatus": "CONFIRMED"
}
```


# Payment receipt

Receipt data for a verified payment; the app renders and shares it.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | |
|---|---|
| id<br>required | string<br>Resource ID |

## Responses

**— 200**

Receipt

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 404**

Not found: NOT_FOUND

> 429

Too many requests: RATE_LIMITED

GET /payments/{id}/receipt

**Response samples**

200 | 401 | 404 | 429

Content type
application/json

Copy


```
{
  "receiptNo": "PAY-2026-000124",
  "amountPaise": 30000000,
  "providerPaymentId": "pay_N8yR7mT2b",
  "verifiedAt": "2026-10-22T09:30:00.000Z",
  "bookingRef": "BK-2026-000123",
  "plotNo": "P-001",
  "tierName": "Gold",
  "customerName": "Asha Patil",
  "mobile": "9876543210",
  "email": "asha@example.com"
}
```


## Earnings

Commission ledger and 70:30 matching (partners).

## Commission totals

Totals per status, each split into gross, 20% admin, 5% TDS and net.

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

Summary

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: PARTNER_NOT_APPROVED

**> 429**

Too many requests: RATE_LIMITED

GET /commissions/summary

### Response samples

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "byStatus": [
     + { … }
   ]
}
```

# Commission ledger

My ledger entries, newest first. kind COMMISSION (default) or MATCHING. Status flow: PENDING → ELIGIBLE (after 7 days) → APPROVED (admin) → PAID; ON_HOLD and REVERSED possible. Negative amounts are reversals of cancelled bookings.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

- `status` — string
  Enum: `"PENDING"` `"ELIGIBLE"` `"APPROVED"` `"PAID"` `"ON_HOLD"` `"REVERSED"`
  Filter by status
- `kind` — string
  Enum: `"COMMISSION"` `"MATCHING"`
  COMMISSION or MATCHING
- `page` — integer `>= 0`
  Default: `0`
  Page number, starting at 0
- `size` — integer `[ 1 .. 50 ]`
  Default: `20`
  Items per page (1–50)

## Responses

**— 200**

Entries

**> 401**

Not signed in or token expired: UNAUTHORIZED

**403**

Not allowed: PARTNER_NOT_APPROVED

**429**

Too many requests: RATE_LIMITED

GET /commissions

### Response samples

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
   "total": 1
}
```


## Commission entry details

One entry with booking context and its full status history.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

id
required

string
Resource ID

## Responses

**— 200**

Entry

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

GET /commissions/{id}

### Response samples

200 | 401 | 404 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
  "id": "e9f8a7b6-c5d4-4e3f-8a2b-1c0d9e8f7a66",
  "kind": "COMMISSION",
  "level": 1,
  "grossPaise": 6000000,
  "adminPaise": 1200000,
  "tdsPaise": 300000,
  "netPaise": 4500000,
```

```
    "status": "APPROVED",
    "statusAt": "2026-10-22T09:30:00.000Z",
    "reversesId": null,
    "createdAt": "2026-10-22T09:30:00.000Z",
    "bookingRef": "BK-2026-000123",
    "plotNo": "P-001",
    "tierName": "Gold",
    "userId": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
    "sourceBookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
    "buyerName": "Rohan Mehta",
  - "history": [
     + { … },
     + { … },
     + { … }
    ]
}
```


## 70:30 matching summary

Business volume on each leg, unmatched carry-forward, the stronger (power) leg and matching bonus totals.

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

Matching

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: PARTNER_NOT_APPROVED

> 429

Too many requests: RATE_LIMITED

GET /matching/summary

### Response samples

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
   "leftVolumePaise": 30000000,
   "rightVolumePaise": 7100000,
   "carryLeftPaise": 30000000,
   "carryRightPaise": 7100000,
   "powerLeg": "L",
 - "byStatus": [
     + { … }
   ]
}
```


## Matching history

One row per daily matching run that paid a bonus.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

page

integer >= 0

Default: 0

Page number, starting at 0

size

integer [ 1 .. 50 ]

Default: 20

Items per page (1–50)

## Responses

**— 200**

Runs

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: PARTNER_NOT_APPROVED

**> 429**

Too many requests: RATE_LIMITED

GET /matching/runs

### Response samples

200 | 401 | 403 | 429

Content type

application/json

Copy Expand all Collapse all

```
{
  - "items": [
      + { … }
    ],
    "page": 0,
    "size": 20,
    "total": 1
}
```


# Payouts

Bank details and commission payouts (partners).

## My bank details (masked)

Empty object if none saved.

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

Beneficiary

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /payouts/beneficiary

**Response samples**

200 | 401 | 429

Content type
application/json

Copy


```
{
    "holderName": "Asha Patil",
    "accountMasked": "****9012",
    "ifsc": "HDFC0001234",
    "panMasked": "******234F",
    "status": "VERIFIED",
    "updatedAt": "2026-10-22T09:30:00.000Z"
}
```


# Save bank details

Registers the account with Cashfree. Account number and PAN are stored encrypted and only returned masked.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **holderName** required
  string <= 100 characters
  Account holder name as per bank records
- **accountNumber** required
  string^\d{9,18}$
  Bank account number, 9–18 digits (stored encrypted)
- **ifsc** required
  string^[A-Z]{4}0[A-Z0-9]{6}$
  IFSC code, e.g. HDFC0001234

pan
required

string^[A-Z]{5}[0-9]{4}[A-Z]$
PAN, required for TDS (stored encrypted)

## Responses

**— 200**

Saved (masked)

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: PARTNER_NOT_APPROVED

**> 429**

Too many requests: RATE_LIMITED

**> 502**

Payment/payout provider error: PROVIDER_ERROR

PUT /payouts/beneficiary

### Request samples

Payload

**Content type**
application/json

Copy

```
{
    "holderName": "Asha Patil",
    "accountNumber": "123456789012",
    "ifsc": "HDFC0001234",
    "pan": "ABCDE1234F"
}
```


### Response samples

200 | 400 | 401 | 403 | 429 | 502

Content type
application/json

Copy


```
{
    "holderName": "Asha Patil",
    "accountMasked": "****9012",
    "ifsc": "HDFC0001234",
    "panMasked": "******234F",
    "status": "VERIFIED",
    "updatedAt": "2026-10-22T09:30:00.000Z"
}
```


## My payouts

Payout history plus availablePaise: approved net amount waiting for the next payout. Status: REQUESTED → PROCESSING → PAID or FAILED.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

`page` integer `>= 0`
Default: `0`
Page number, starting at 0

`size` integer `[ 1 .. 50 ]`
Default: `20`

Items per page (1–50)

## Responses

**— 200**

Payouts

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 403**

Not allowed: PARTNER_NOT_APPROVED

**› 429**

Too many requests: RATE_LIMITED

GET /payouts

### Response samples

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all

```
{
  - "items": [
      + { … }
    ],
    "page": 0,
    "size": 20,
    "total": 1,
    "availablePaise": 0
}
```


# Documents

Agreements and receipts shared with the customer.

## My documents

Type: AGREEMENT, RECEIPT, ALLOTMENT, OTHER. Status: PENDING, SENT, SIGNED, REJECTED, EXPIRED.

AUTHORIZATIONS: › *bearer*

QUERY PARAMETERS

`page` integer `>= 0`
Default: `0`
Page number, starting at 0

`size` integer `[ 1 .. 50 ]`
Default: `20`
Items per page (1–50)

### Responses

**— 200**

Documents

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /documents

**Response samples**

200 401 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
   "total": 1
}
```


## Download link

A private link valid for 5 minutes. Request a new one every time; never cache it.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | |
|---|---|
| id<br>required | string<br>Resource ID |

## Responses

**— 200**

Signed URL

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 404**

Not found: NOT_FOUND

**› 429**

Too many requests: RATE_LIMITED

GET /documents/{id}/url

### Response samples

200 | 401 | 404 | 429

Content type
application/json

Copy


```
{
   "url": "https://plots315-docs.s3.ap-south-1.amazonaws.com/documents/…?X-Amz-
   "expiresInSec": 300
}
```

# Sign a document (eSign)

Reserved for eSign. Until a provider is connected this always returns 501 ESIGN_NOT_CONFIGURED; admins set the status with PATCH /admin/documents/{id}/status.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | | |
|---|---|---|
| id<br>required | string | Resource ID |

## Responses

**— 200**

Signing session (when eSign is connected)

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

**> 501**

Not configured: ESIGN_NOT_CONFIGURED

POST /documents/{id}/sign

**Response samples**

401 | 429 | 501

Content type
application/json

Copy

```
{
    "code": "UNAUTHORIZED",
    "message": "Unauthorized",
    "requestId": "3f0c9b2e-1a4d-4c8b-9e7f-2d1a6b5c4e30"
}
```

# Notifications

In-app inbox; the same items arrive as push notifications.

## Notification inbox

Newest first, with the unread count. deepLink: booking/{id}, payment/{id}, document/{id}, commission, matching, payout/{id}, partner.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

- `page` — integer `>= 0`
  Default: `0`
  Page number, starting at 0
- `size` — integer `[ 1 .. 50 ]`
  Default: `20`
  Items per page (1–50)

### Responses

**— 200**

Notifications

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /notifications

### Response samples

200 | 401 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
   "total": 12,
   "unread": 3
}
```


## Mark one as read

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

id
required

string
Resource ID

## Responses

**— 201**

Marked

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

POST /notifications/{id}/read

### Response samples

201 | 401 | 404 | 429

Content type
application/json

Copy

```
{
  "ok": true
}
```

# Mark all as read

AUTHORIZATIONS: > *bearer*

## Responses

**— 201**

Marked

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

POST /notifications/read-all

### Response samples

201 | 401 | 429

Content type
application/json

Copy

```
{
   "ok": true
}
```

# Admin

Operations for ADMIN accounts only. Every change is audit-logged.

# Admin dashboard

Plots by status, confirmed sales by plan, partner counts, ledger totals by status, payout totals by status.

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

Dashboard

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 429**

Too many requests: RATE_LIMITED

GET /admin/dashboard

### Response samples

200 | 401 | 403 | 429

Content type

application/json

Copy Expand all Collapse all

```
{
 - "plots": [
    + { … },
    + { … }
   ],
 - "bookings": [
    + { … }
   ],
 - "partners": {
      "pending": 2,
      "approved": 14
   },
 - "ledger": [
    + { … }
   ],
 - "payouts": [
    + { … }
   ]
}
```


# All plots

Same filters as GET /plots.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

- `status` — string
  Enum: `"AVAILABLE"` `"HELD"` `"BOOKED"` `"BLOCKED"`
  Filter by status
- `block` — string <= 50 characters
  Filter by block
- `facing` — string <= 50 characters
  Filter by facing direction
- `page` — integer >= 0

Default: `0`

Page number, starting at 0

size

integer `[ 1 .. 50 ]`

Default: `20`

Items per page (1–50)

## Responses

**— 200**

Plots

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 403**

Not allowed: FORBIDDEN

**› 429**

Too many requests: RATE_LIMITED

GET `/admin/plots`

### Response samples

200 | 401 | 403 | 429

Content type

application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
```

```
    "page": 0,
    "size": 20,
    "total": 315,
  - "summary": [
      + { … }
    ]
}
```


# Add a plot

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **plotNo** required
  string <= 20 characters
  Unique plot number
- **block**
  string <= 50 characters
  Optional. Block / sector
- **facing**
  string <= 50 characters
  Optional. Facing direction
- **areaSqft**
  number >= 1
  Optional. Area in square feet
- **pricePaise** required
  number >= 1
  Plot price in paise (₹50,00,000 = 500000000)
- **lat**
  number
  Optional. Latitude for the map
- **lng**
  number
  Optional. Longitude for the map

## Responses

**— 201**

Created plot (raw row)

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 409**

Conflict (state changed): CONFLICT

**> 429**

Too many requests: RATE_LIMITED

POST /admin/plots

## Request samples

Payload

Content type
application/json

Copy

```
{
    "plotNo": "P-316",
    "block": "D",
    "facing": "North",
    "areaSqft": 1500,
    "pricePaise": 500000000,
    "lat": 18.53,
    "lng": 73.86
```

```
}
```

### Response samples

201 | 400 | 401 | 403 | 409 | 429

Content type
application/json

Copy


```
{
    "id": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
    "plotNo": "P-316",
    "block": "A",
    "facing": "East",
    "areaSqft": 1200,
    "pricePaise": 500000000,
    "lat": 18.52,
    "lng": 73.85,
    "status": "AVAILABLE",
    "heldUntil": null,
    "createdAt": "2026-10-22T09:30:00.000Z",
    "updatedAt": "2026-10-22T09:30:00.000Z"
}
```


## Edit or block a plot

Status may only change between AVAILABLE and BLOCKED; held or booked plots keep their status.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | | |
|---|---|---|
| id<br>required | string | Resource ID |

REQUEST BODY SCHEMA: application/json
required

- `plotNo` *required*
  string <= 20 characters
  Unique plot number

- `block`
  string <= 50 characters
  Optional. Block / sector

- `facing`
  string <= 50 characters
  Optional. Facing direction

- `areaSqft`
  number >= 1
  Optional. Area in square feet

- `pricePaise` *required*
  number >= 1
  Plot price in paise (₹50,00,000 = 500000000)

- `lat`
  number
  Optional. Latitude for the map

- `lng`
  number
  Optional. Longitude for the map

- `status`
  string
  Enum: `"AVAILABLE"` `"BLOCKED"`
  Optional. AVAILABLE or BLOCKED (only when the plot is not held or booked)

## Responses

**— 200**

Updated plot

**› 400**

Bad request: VALIDATION_FAILED

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 403**

Not allowed: FORBIDDEN

> **404**

Not found: NOT_FOUND

> **409**

Conflict (state changed): PLOT_LOCKED

> **429**

Too many requests: RATE_LIMITED

PUT /admin/plots/{id}

## Request samples

Payload

Content type
application/json

Copy

```
{
    "plotNo": "P-001",
    "block": "A",
    "facing": "East",
    "areaSqft": 1200,
    "pricePaise": 500000000,
    "lat": 18.52,
    "lng": 73.85,
    "status": "BLOCKED"
}
```

## Response samples

200 | 400 | 401 | 403 | 404 | 409 | 429

Content type
application/json

Copy


```
{
    "id": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
    "plotNo": "P-001",
    "block": "A",
    "facing": "East",
    "areaSqft": 1200,
    "pricePaise": 500000000,
    "lat": 18.52,
    "lng": 73.85,
    "status": "BLOCKED",
    "heldUntil": null,
    "createdAt": "2026-10-22T09:30:00.000Z",
    "updatedAt": "2026-10-22T09:30:00.000Z"
}
```


## Import plots from CSV

Upserts plots by plot_no. Header must be exactly `plot_no,block,facing,area_sqft,price_paise,lat,lng`. Never changes a plot status. Max 2 MB.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: multipart/form-data
required

| | | |
|---|---|---|
| ⊣ file<br>required | string <binary> | CSV file |

### Responses

**— 201**

Imported

**> 400**

Bad request: BAD_CSV, FILE_REQUIRED

**401**

Not signed in or token expired: UNAUTHORIZED

**403**

Not allowed: FORBIDDEN

**429**

Too many requests: RATE_LIMITED

POST /admin/plots/import

**Response samples**

201 | 400 | 401 | 403 | 429

Content type
application/json

Copy


```
{
    "imported": 315
}
```


## All plans (incl. inactive)

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

Plans

**401**

Not signed in or token expired: UNAUTHORIZED

**403**

Not allowed: FORBIDDEN

**429**

Too many requests: RATE_LIMITED

GET /admin/tiers

### Response samples

200 401 403 429

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "id": "b7a1c3e5-9d2f-4b6a-8e0c-1f3d5a7b9c22",
      "code": "GOLD",
      "name": "Gold",
      "amountPaise": 30000000,
      "l1Bps": 2000,
      "l2Bps": 1000,
      "l3Bps": 1000,
      "benefits": null,
      "active": true
   }
]
```


## Create a plan

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **code** required
  string <= 20 characters
  Unique plan code (stored upper-case)
- **name** required
  string <= 50 characters
  Display name
- **amountPaise** required
  number >= 1
  Booking amount in paise (₹3,00,000 = 30000000)
- **l1Bps** required
  number [ 0 .. 10000 ]
  Level-1 commission in basis points (2000 = 20%)
- **l2Bps** required
  number [ 0 .. 10000 ]
  Level-2 commission in basis points
- **l3Bps** required
  number [ 0 .. 10000 ]
  Level-3 commission in basis points
- **benefits**
  string <= 2000 characters
  Optional. Benefits text shown to customers
- **active** required
  boolean
  Whether customers can choose this plan
- **sort** required
  number >= 0
  Display order (ascending)

## Responses

**— 201**

Created plan

**> 400**

Bad request: VALIDATION_FAILED

> 401

Not signed in or token expired: UNAUTHORIZED

> 403

Not allowed: FORBIDDEN

> 429

Too many requests: RATE_LIMITED

POST /admin/tiers

## Request samples

Payload

Content type
application/json

Copy

```
{
    "code": "DIAMOND",
    "name": "Diamond",
    "amountPaise": 100000000,
    "l1Bps": 2500,
    "l2Bps": 1500,
    "l3Bps": 1000,
    "benefits": "Corner plot priority",
    "active": true,
    "sort": 6
}
```

## Response samples

201 | 400 | 401 | 403 | 429

Content type
application/json

Copy


```
{
    "id": "b7a1c3e5-9d2f-4b6a-8e0c-1f3d5a7b9c22",
    "code": "DIAMOND",
    "name": "Diamond",
    "amountPaise": 100000000,
    "l1Bps": 2000,
    "l2Bps": 1000,
    "l3Bps": 1000,
    "benefits": null,
    "active": true,
    "sort": 6
}
```


# Edit a plan

Existing bookings keep the price and commission rates they were booked at.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

- `id` — required — string — Resource ID

REQUEST BODY SCHEMA: application/json — required

- `code` — required — string <= 20 characters — Unique plan code (stored upper-case)
- `name` — required — string <= 50 characters — Display name
- `amountPaise` — required — number >= 1 — Booking amount in paise (₹3,00,000 = 30000000)
- `l1Bps` — required — number [ 0 .. 10000 ] — Level-1 commission in basis points (2000 = 20%)

- `l2Bps` required
  number [ 0 .. 10000 ]
  Level-2 commission in basis points
- `l3Bps` required
  number [ 0 .. 10000 ]
  Level-3 commission in basis points
- `benefits`
  string <= 2000 characters
  Optional. Benefits text shown to customers
- `active` required
  boolean
  Whether customers can choose this plan
- `sort` required
  number >= 0
  Display order (ascending)

## Responses

**— 200**

Updated plan

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

PUT /admin/tiers/{id}

## Request samples

Payload

Content type
application/json

Copy


```
{
    "code": "GOLD",
    "name": "Gold",
    "amountPaise": 31000000,
    "l1Bps": 2000,
    "l2Bps": 1000,
    "l3Bps": 1000,
    "benefits": "Priority plot selection",
    "active": true,
    "sort": 4
}
```


## Response samples

200 400 401 403 404 429

Content type
application/json

Copy


```
{
    "id": "b7a1c3e5-9d2f-4b6a-8e0c-1f3d5a7b9c22",
    "code": "GOLD",
    "name": "Gold",
    "amountPaise": 31000000,
    "l1Bps": 2000,
    "l2Bps": 1000,
    "l3Bps": 1000,
    "benefits": null,
    "active": true,
```

```
    "sort": 4
}
```

## Search users

search matches name, mobile, email or referral code. Filters: role, partnerStatus.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

- **search** — string <= 100 characters
  Name, mobile, email or referral code
- **role** — string
  Enum: `"USER"` `"ADMIN"`
  USER or ADMIN
- **partnerStatus** — string
  Enum: `"NONE"` `"PENDING"` `"APPROVED"` `"REJECTED"` `"SUSPENDED"`
  NONE, PENDING, APPROVED, REJECTED or SUSPENDED
- **page** — integer >= 0
  Default: `0`
  Page number, starting at 0
- **size** — integer [ 1 .. 50 ]
  Default: `20`
  Items per page (1–50)

## Responses

**— 200**

Users

**> 401**

Not signed in or token expired: UNAUTHORIZED

> **403**

Not allowed: FORBIDDEN

> **429**

Too many requests: RATE_LIMITED

GET /admin/users

### Response samples

200 | 401 | 403 | 429

**Content type**
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
   "total": 1
}
```


## User details

Profile, bookings, ledger totals and masked bank details.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

id
required

string
Resource ID

## Responses

**— 200**

User

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

GET /admin/users/{id}

### Response samples

200 | 401 | 403 | 404 | 429

Content type
application/json

Copy Expand all Collapse all

```
{
  - "user": {
        "id": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
        "role": "USER",
        "mobile": "9876543210",
        "email": "asha@example.com",
        "name": "Asha Patil",
        "address": "Baner, Pune",
        "partnerStatus": "APPROVED",
        "sponsorId": "9a2b3c4d-5e6f-4a7b-8c9d-0e1f2a3b4c5d",
        "leg": "L",
        "referralCode": "P7KQ2XM",
        "active": true,
        "createdAt": "2026-10-22T09:30:00.000Z"
    },
  - "bookings": [
      + { … }
    ],
  - "ledger": [
      + { … }
    ],
    "beneficiary": null
}
```


## Approve / reject / suspend a partner

APPROVE (from PENDING, REJECTED or SUSPENDED) creates the referral code. REJECT only from PENDING. SUSPEND only from APPROVED. The user is notified.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | | |
|---|---|---|
| id<br>required | string | Resource ID |

REQUEST BODY SCHEMA: application/json
required

| | | |
|---|---|---|
| action | string | |

required

Enum: `"APPROVE"` `"REJECT"` `"SUSPEND"`
APPROVE, REJECT or SUSPEND

note

string `<= 500 characters`
Optional. Shown to the user in the notification

## Responses

**— 201**

New status

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 404**

Not found: NOT_FOUND

**> 409**

Conflict (state changed): INVALID_STATE

**> 429**

Too many requests: RATE_LIMITED

POST `/admin/users/{id}/partner`

### Request samples

Payload

Content type
application/json

Copy

```
{
   "action": "APPROVE",
   "note": "Welcome aboard"
}
```

### Response samples

201 | 400 | 401 | 403 | 404 | 409 | 429

Content type
application/json

Copy

```
{
   "partnerStatus": "APPROVED",
   "referralCode": "P7KQ2XM"
}
```

## Activate / deactivate a user

Deactivating signs the user out of every device.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | |
|---|---|
| id<br>required | string<br>Resource ID |

REQUEST BODY SCHEMA: application/json
required

| | |
|---|---|
| active<br>required | boolean<br>false deactivates the account and signs it out everywhere |

## Responses

**— 201**

New state

**> 400**

Bad request: SELF, VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

POST /admin/users/{id}/active

### Request samples

Payload

Content type
application/json

Copy

```
{
   "active": false
}
```

**Response samples**

201 | 400 | 401 | 403 | 404 | 429

Content type
application/json

Copy

```
{
    "active": false
}
```

# All bookings

Filters: status, userId.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

- `status` — string <= 30 characters
  Filter by status
- `userId` — string
  Filter by user ID
- `page` — integer >= 0
  Default: 0
  Page number, starting at 0
- `size` — integer [ 1 .. 50 ]
  Default: 20
  Items per page (1–50)

## Responses

**— 200**

Bookings

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 429**

Too many requests: RATE_LIMITED

GET /admin/bookings

**Response samples**

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
   "total": 1
}
```


## Booking details (admin)

Booking with all payments and the commission entries it created.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | | |
|---|---|---|
| id<br>required | string | Resource ID |

## Responses

**— 200**

Booking

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

GET /admin/bookings/{id}

### Response samples

200 | 401 | 403 | 404 | 429

**Content type**
application/json

Copy Expand all Collapse all


```
{
   "id": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
   "internalRef": "BK-2026-000123",
   "status": "CONFIRMED",
   "amountPaise": 30000000,
   "holdExpiresAt": "2026-10-22T09:45:00.000Z",
   "confirmedAt": "2026-10-22T09:30:00.000Z",
   "createdAt": "2026-10-22T09:30:00.000Z",
 - "plot": {
      "id": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
      "plotNo": "P-001",
      "block": "A",
      "facing": "East",
      "areaSqft": 1200,
      "lat": 18.52,
      "lng": 73.85
   },
 - "tier": {
      "id": "b7a1c3e5-9d2f-4b6a-8e0c-1f3d5a7b9c22",
      "code": "GOLD",
      "name": "Gold"
   },
 - "payments": [
    + { … }
   ],
 - "commissions": [
    + { … }
   ]
}
```


## Cancel a booking

Frees the plot and reverses every commission from it. With refund true, verified payments are refunded through Razorpay. Already-paid commission is deducted from the next payout.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | |
|---|---|
| id<br>required | string<br>Resource ID |

REQUEST BODY SCHEMA: application/json
required

| | |
|---|---|
| refund<br>required | boolean<br>true also refunds verified payments through Razorpay |
| reason<br>required | string <= 500 characters<br>Why the booking is cancelled (audit log) |

## Responses

**— 201**

Cancelled

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 404**

Not found: NOT_FOUND

**> 409**

Conflict (state changed): INVALID_STATE

**> 429**

Too many requests: RATE_LIMITED

POST /admin/bookings/{id}/cancel

### Request samples

Payload

Content type
application/json

Copy

```
{
    "refund": true,
    "reason": "Customer request"
}
```

### Response samples

201 | 400 | 401 | 403 | 404 | 409 | 429

Content type
application/json

Copy

```
{
    "ok": true
}
```

## All payments

Filters: status, userId.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

| | | |
|---|---|---|
| status | string <= 30 characters | Filter by status |
| userId | string | Filter by user ID |
| page | integer >= 0 | Default: 0<br>Page number, starting at 0 |
| size | integer [ 1 .. 50 ] | Default: 20<br>Items per page (1–50) |

## Responses

**— 200**

Payments

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 403**

Not allowed: FORBIDDEN

**› 429**

Too many requests: RATE_LIMITED

GET /admin/payments

### Response samples

200 401 403 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
   "total": 1
}
```


## All ledger entries

Filters: status, kind (COMMISSION, MATCHING), userId.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

**status**
string
Enum: `"PENDING"` `"ELIGIBLE"` `"APPROVED"` `"PAID"` `"ON_HOLD"` `"REVERSED"`
Filter by status

**kind**
string
Enum: `"COMMISSION"` `"MATCHING"`
COMMISSION or MATCHING

**userId**
string
Filter by user ID

**page**
integer `>= 0`
Default: `0`
Page number, starting at 0

**size**
integer `[ 1 .. 50 ]`
Default: `20`
Items per page (1–50)

## Responses

**— 200**

Entries

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 403**

Not allowed: FORBIDDEN

**› 429**

Too many requests: RATE_LIMITED

GET /admin/commissions

### Response samples

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
   "total": 1
}
```

# Approve commission

ELIGIBLE → APPROVED. Entries in any other status are skipped (see `changed`).

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **ids** *required* — Array of strings
  Ledger entry IDs (max 500)
- **note** — string <= 500 characters
  Optional. Stored in the status history

## Responses

**— 201**

Result

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 429**

Too many requests: RATE_LIMITED

POST /admin/commissions/approve

### Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
 - "ids": [
       "e9f8a7b6-c5d4-4e3f-8a2b-1c0d9e8f7a66"
   ],
   "note": "Verified"
}
```

### Response samples

201 400 401 403 429

Content type
application/json

Copy

```
{
   "requested": 1,
   "changed": 1
}
```

## Put commission on hold

PENDING / ELIGIBLE / APPROVED → ON_HOLD. Entries already in a payout are skipped.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

ids
required

Array of strings
Ledger entry IDs (max 500)

note

string <= 500 characters

Optional. Stored in the status history

## Responses

**— 201**

Result

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 429**

Too many requests: RATE_LIMITED

POST /admin/commissions/hold

### Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "ids": [
        "e9f8a7b6-c5d4-4e3f-8a2b-1c0d9e8f7a66"
    ],
```

```
    "note": "Under review"
}
```

### Response samples

201 | 400 | 401 | 403 | 429

**Content type**
application/json

Copy

```
{
    "requested": 1,
    "changed": 1
}
```

## Release held commission

ON_HOLD → ELIGIBLE.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **ids** (required) — Array of strings
  Ledger entry IDs (max 500)
- **note** — string <= 500 characters
  Optional. Stored in the status history

### Responses

**— 201**

Result

> **400**

Bad request: VALIDATION_FAILED

> **401**

Not signed in or token expired: UNAUTHORIZED

> **403**

Not allowed: FORBIDDEN

> **429**

Too many requests: RATE_LIMITED

POST `/admin/commissions/release`

## Request samples

**Payload**

**Content type**
application/json

Copy Expand all Collapse all

```
{
 - "ids": [
       "e9f8a7b6-c5d4-4e3f-8a2b-1c0d9e8f7a66"
   ]
}
```

## Response samples

**201** | **400** | **401** | **403** | **429**

**Content type**
application/json

Copy

```
{
    "requested": 1,
    "changed": 1
}
```


## All payouts

Filters: status, userId.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

- `status` — string <= 30 characters
  Filter by status
- `userId` — string
  Filter by user ID
- `page` — integer >= 0
  Default: 0
  Page number, starting at 0
- `size` — integer [ 1 .. 50 ]
  Default: 20
  Items per page (1–50)

## Responses

**— 200**

Payouts

**> 401**

Not signed in or token expired: UNAUTHORIZED

> **403**

Not allowed: FORBIDDEN

> **429**

Too many requests: RATE_LIMITED

GET /admin/payouts

**Response samples**

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
   "total": 1
}
```


## Run a payout batch

Pays every partner (or only userIds) whose approved net amount is at least the configured minimum and who has verified bank details. Each becomes a Cashfree transfer.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

| | | |
|---|---|---|
| userIds | Array of strings | Optional. Pay only these partners; omit to pay everyone eligible |

## Responses

**— 201**

Batch result

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 429**

Too many requests: RATE_LIMITED

POST /admin/payouts

### Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "userIds": [
        "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11"
    ]
```

```
}
```

### Response samples

201 | 400 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all

```
{
   "created": 1,
 - "results": [
    + { … }
   ]
}
```

## Upload a document for a customer

PDF, JPEG or PNG up to 10 MB. Stored privately; the customer is notified. Status starts as SENT.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: multipart/form-data
required

| | | |
|---|---|---|
| file<br>required | string <binary> | The document (PDF/JPEG/PNG) |
| userId<br>required | string | Customer ID |
| bookingId | string | Optional booking ID of that customer |
| type<br>required | string | AGREEMENT, RECEIPT, ALLOTMENT or OTHER |
| title<br>required | string | Title shown to the customer |

## Responses

**— 201**

Uploaded

**> 400**

Bad request: FILE_REQUIRED, FILE_TYPE, BOOKING_MISMATCH

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

POST /admin/documents

### Response samples

201 | 400 | 401 | 403 | 404 | 429

Content type
application/json

Copy


```
{
    "id": "f0e1d2c3-b4a5-4968-8776-655443322110",
    "userId": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
    "bookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
```

```
    "type": "AGREEMENT",
    "title": "Sale Agreement",
    "status": "SENT",
    "createdAt": "2026-10-22T09:30:00.000Z"
}
```


## Set document status

Used until an eSign provider is connected. The customer is notified.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

- `id` — required — string — Resource ID

REQUEST BODY SCHEMA: application/json — required

- `status` — required — string — Enum: `"PENDING"` `"SENT"` `"SIGNED"` `"REJECTED"` `"EXPIRED"` — PENDING, SENT, SIGNED, REJECTED or EXPIRED

### Responses

**— 200**

New status

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

> **403**

Not allowed: FORBIDDEN

> **404**

Not found: NOT_FOUND

> **429**

Too many requests: RATE_LIMITED

PATCH `/admin/documents/{id}/status`

## Request samples

**Payload**

Content type
application/json

Copy

```
{
    "status": "SIGNED"
}
```

## Response samples

**200** | 400 | 401 | 403 | 404 | 429

Content type
application/json

Copy

```
{
    "status": "SIGNED"
}
```

# Broadcast a notification

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **audience** required
  string
  Enum: `"ALL"` `"PARTNERS"`
  ALL users or only approved PARTNERS
- **title** required
  string <= 100 characters
  Notification title
- **body** required
  string <= 1000 characters
  Notification text

## Responses

**— 201**

Number of users notified

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 429**

Too many requests: RATE_LIMITED

POST /admin/notifications/broadcast

### Request samples

Payload

Content type
application/json

Copy

```
{
   "audience": "PARTNERS",
   "title": "New phase launched",
   "body": "Phase 2 plots are now open for booking."
}
```

### Response samples

201 | 400 | 401 | 403 | 429

Content type
application/json

Copy

```
{
   "sent": 14
}
```

## Business settings

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

Settings

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 429**

Too many requests: RATE_LIMITED

GET /admin/config

## Response samples

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "key": "bookings_enabled",
      "value": "true"
   },
 - {
      "key": "hold_minutes",
      "value": "15"
   },
 - {
      "key": "cooling_days",
      "value": "7"
   },
```

```
  - {
        "key": "min_payout_paise",
        "value": "10000"
    }
]
```


## Change a business setting

Keys: bookings_enabled (true/false), hold_minutes (5–60), cooling_days (0–90), min_payout_paise, admin_bps, tds_bps, matching_power_pct, matching_weak_pct, matching_bonus_bps, min_app_version (x.y.z), support_phone, support_email.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | |
|---|---|
| key<br>required | string<br>Setting key |

REQUEST BODY SCHEMA: application/json
required

| | |
|---|---|
| value<br>required | string <= 200 characters<br>New value (validated per key) |

### Responses

**— 200**

Saved

**> 400**

Bad request: INVALID_VALUE, VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

> **403**

Not allowed: FORBIDDEN

> **404**

Not found: NOT_FOUND

> **429**

Too many requests: RATE_LIMITED

PUT `/admin/config/{key}`

## Request samples

**Payload**

Content type
application/json

Copy

```
{
    "value": "15"
}
```

## Response samples

**200** | 400 | 401 | 403 | 404 | 429

Content type
application/json

Copy

```
{
    "key": "hold_minutes",
    "value": "15"
}
```

# Audit log

Every admin change with before/after values. Filters: entity (plot, tier, user, booking, ledger_entry, payout, document, app_config), entityId.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

- `entity` — string <= 50 characters
  Entity type, e.g. user, booking, plot
- `entityId` — string <= 100 characters
  Entity ID
- `page` — integer >= 0
  Default: 0
  Page number, starting at 0
- `size` — integer [ 1 .. 50 ]
  Default: 20
  Items per page (1–50)

## Responses

**— 200**

Audit entries

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

> 429

Too many requests: RATE_LIMITED

GET /admin/audit

**Response samples**

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
   "size": 20,
   "total": 1
}
```


## Background jobs

Queued work (push notifications, refunds). dead=true lists jobs that failed 8 times.

AUTHORIZATIONS: > *bearer*

QUERY PARAMETERS

- **dead** — boolean
  true = only jobs that failed permanently
- **page** — integer >= 0
  Default: 0

Page number, starting at 0

size

integer [ 1 .. 50 ]
Default: 20
Items per page (1–50)

## Responses

**— 200**

Jobs

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 403**

Not allowed: FORBIDDEN

**› 429**

Too many requests: RATE_LIMITED

GET /admin/jobs

### Response samples

200 401 403 429

Content type
application/json

Copy Expand all Collapse all


```
{
 - "items": [
     + { … }
   ],
   "page": 0,
```

```
    "size": 20,
    "total": 1
}
```


## Retry a failed job

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | |
|---|---|
| id<br>required | number<br>Resource ID |

### Responses

**— 201**

Requeued

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: FORBIDDEN

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

POST /admin/jobs/{id}/retry

**Response samples**

201 | 401 | 403 | 404 | 429

Content type
application/json

Copy

```
{
    "ok": true
}
```

# Webhooks

Server-to-server callbacks from Razorpay and Cashfree. Not for the app.

## Razorpay webhook (server-to-server)

Called by Razorpay, never by the app. Body is the raw Razorpay event; the X-Razorpay-Signature header must be the HMAC-SHA256 of the raw body with the webhook secret. Handles payment.captured, payment.failed, refund.processed. Repeated events are accepted and ignored.

HEADER PARAMETERS

| | | |
|---|---|---|
| x-razorpay-signature<br>required | string | |
| x-razorpay-event-id<br>required | string | |

REQUEST BODY SCHEMA: application/json
required

object

### Responses

**— 200**

Event stored and applied

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: SIGNATURE_INVALID

POST /webhooks/razorpay

## Request samples

Payload

Content type
application/json

Copy Expand all Collapse all


```
{
   "event": "payment.captured",
 - "payload": {
    + "payment": { … }
   }
}
```


## Response samples

200 400 401

Content type
application/json

Copy

```
{
    "ok": true
}
```


## Cashfree Payouts webhook (server-to-server)

Called by Cashfree. x-webhook-signature = base64 HMAC-SHA256 of (x-webhook-timestamp + raw body) with the client secret. Handles TRANSFER_SUCCESS, TRANSFER_FAILED, TRANSFER_REJECTED, TRANSFER_REVERSED.

HEADER PARAMETERS

| | | |
|---|---|---|
| x-webhook-signature<br>required | string | |
| x-webhook-timestamp<br>required | string | |

REQUEST BODY SCHEMA: application/json
required

object

### Responses

**— 200**

Event stored and applied

**> 400**

Bad request: VALIDATION_FAILED

**> 401**

Not signed in or token expired: SIGNATURE_INVALID

POST /webhooks/cashfree

### Request samples

Payload

Content type
application/json

Copy Expand all Collapse all


```
{
   "type": "TRANSFER_SUCCESS",
 - "data": {
      "transfer_id": "PO-2026-000210"
   }
}
```


### Response samples

200 400 401

Content type
application/json

Copy


```
{
   "ok": true
}
```


## System

Health check.

## Health check

Returns ok when the API and its database are reachable. Use for load balancer and uptime checks.

### Responses

**— 200**

Healthy

**› 500**

Server error: INTERNAL

GET /health

**Response samples**

200 500

Content type
application/json

Copy


```
{
   "status": "ok"
}
```


## App v1

Endpoints in the exact shape the 315 PLOTS Kotlin app expects (ApiConfig.Endpoints), under /api/v1. Amounts are pre-formatted for display.

## App: send OTP

Sends a 6-digit login OTP. Returns AuthResult; on failure success=false with errorMessage (HTTP 429 when rate limited).

REQUEST BODY SCHEMA: application/json
required

| | |
|---|---|
| phone<br>required | string^[6-9]\d{9}$ |

### Responses

**— 200**

AuthResult

**> 400**

Bad request: VALIDATION_FAILED

**> 429**

Too many requests: OTP_RATE_LIMITED

POST /api/v1/auth/send-otp

**Request samples**

Payload

Content type
application/json

Copy

```
{
    "phone": "9876543210"
}
```

### Response samples

200 | 400 | 429

Content type
application/json

Copy

```
{
    "success": true,
    "token": null,
    "role": null,
    "errorMessage": null,
    "expiresInSec": 300,
    "resendAfterSec": 30
}
```

## App: resend OTP

Same as send-otp.

REQUEST BODY SCHEMA: application/json
required

| | | |
|---|---|---|
| phone<br>required | string | ^[6-9]\d{9}$ |

### Responses

**— 200**

AuthResult

> 400

Bad request: VALIDATION_FAILED

POST /api/v1/auth/resend-otp

### Request samples

Payload

Content type
application/json

Copy

```
{
    "phone": "9876543210"
}
```

### Response samples

200 400

Content type
application/json

Copy

```
{
    "success": true,
    "token": null,
    "role": null,
    "errorMessage": null
}
```

## App: verify OTP and sign in

token is the access token for `Authorization: Bearer`. role is CUSTOMER, AGENT (approved partner) or ADMIN. Wrong/expired OTP → success=false with errorMessage.

REQUEST BODY SCHEMA: application/json
required

| | |
|---|---|
| phone<br>required | string^[6-9]\d{9}$ |
| otp<br>required | string^\d{6}$ |
| referralCode | string <= 20 characters |

## Responses

**— 200**

AuthResult

**> 400**

Bad request: VALIDATION_FAILED

POST /api/v1/auth/verify-otp

### Request samples

Payload

Content type
application/json

Copy

```
{
    "phone": "9876543210",
    "otp": "482913",
    "referralCode": "P7KQ2XM"
}
```

### Response samples

200 400

Content type
application/json

Copy


```
{
    "success": true,
    "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiI2ZjFj…",
    "role": "CUSTOMER",
    "errorMessage": null,
    "refreshToken": "q8V2c1sY9…",
    "expiresIn": 900,
    "isNewUser": true,
    "profileComplete": false
}
```


## App: Google sign-in

REQUEST BODY SCHEMA: application/json
required

idToken
required
string

### Responses

**— 200**

AuthResult

**> 400**

Bad request: VALIDATION_FAILED

POST /api/v1/auth/google-login

### Request samples

Payload

Content type
application/json

Copy

```
{
    "idToken": "eyJhbGciOiJSUzI1NiIsImtpZCI6…"
}
```

### Response samples

200 400

Content type
application/json

Copy

```
{
    "success": true,
    "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiI2ZjFj…",
    "role": "CUSTOMER",
    "errorMessage": null,
    "refreshToken": "q8V2c1sY9…",
    "expiresIn": 900,
    "isNewUser": false,
    "profileComplete": false
}
```

## App: Firebase phone sign-in

Call after Firebase PhoneAuthProvider signs the user in: send FirebaseUser.getIdToken(). Firebase sends the SMS, so send-otp/verify-otp are not used. Failures → success=false with errorMessage.

REQUEST BODY SCHEMA: application/json
required

| | | |
|---|---|---|
| idToken<br>required | string | |
| referralCode | string | <= 20 characters |

## Responses

**— 200**

AuthResult

**> 400**

Bad request: VALIDATION_FAILED

POST /api/v1/auth/firebase-login

### Request samples

Payload

Content type
application/json

Copy

```
{
    "idToken": "eyJhbGciOiJSUzI1NiIsImtpZCI6…",
    "referralCode": "P7KQ2XM"
}
```

### Response samples

200 400

Content type
application/json

Copy


```
{
    "success": true,
    "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiI2ZjFj…",
    "role": "CUSTOMER",
    "errorMessage": null,
    "refreshToken": "q8V2c1sY9…",
    "expiresIn": 900,
    "isNewUser": true,
    "profileComplete": false
}
```


## App: log out

Send the refresh token to revoke it.

REQUEST BODY SCHEMA: application/json
required

| | | |
|---|---|---|
| ⊣ refreshToken | string | |

### Responses

**— 200**

Logged out

**> 400**

Bad request: VALIDATION_FAILED

POST /api/v1/auth/logout

### Request samples

Payload

Content type
application/json

Copy

```
{
    "refreshToken": "q8V2c1sY9…"
}
```

### Response samples

200 400

Content type
application/json

Copy

```
{
    "success": true,
    "token": null,
    "role": null,
    "errorMessage": null
}
```

## App: all plots

Plot cards for list and map. status: AVAILABLE, BOOKED, ON_HOLD. mapOffsetX/Y are 0–1 positions on the site map.

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

Plot[]

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/customer/plots

### Response samples

200 401 429

**Content type**

application/json

Copy Expand all Collapse all

```
[
  - {
        "id": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
        "title": "Plot P-001",
        "block": "A",
        "facing": "East",
        "location": "315 PLOTS",
        "sizeSqFt": "1,200 sq ft",
        "pricePerSqFt": "₹4,167/sq ft",
        "roadWidth": "30 ft",
        "totalPriceFormatted": "₹50,00,000",
        "status": "AVAILABLE",
        "imageUrl": "https://images.unsplash.com/photo-1600585154340-be6161a56a0
        "latitude": 18.52,
        "longitude": 73.85,
        "mapOffsetX": 0.0333,
        "mapOffsetY": 0.0238
    }
]
```


## App: plot details

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | | |
|---|---|---|
| ⊣ id<br>required | string<br>Resource ID | |

### Responses

**— 200**

Plot

**> 401**

Not signed in or token expired: UNAUTHORIZED

> 404

Not found: NOT_FOUND

> 429

Too many requests: RATE_LIMITED

GET /api/v1/customer/plots/{id}

## Response samples

200 | 401 | 404 | 429

Content type
application/json

Copy


```
{
    "id": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
    "title": "Plot P-001",
    "block": "A",
    "facing": "East",
    "location": "315 PLOTS",
    "sizeSqFt": "1,200 sq ft",
    "pricePerSqFt": "₹4,167/sq ft",
    "roadWidth": "30 ft",
    "totalPriceFormatted": "₹50,00,000",
    "status": "AVAILABLE",
    "imageUrl": "https://images.unsplash.com/photo-1600585154340-be6161a56a0c",
    "latitude": 18.52,
    "longitude": 73.85,
    "mapOffsetX": 0.0333,
    "mapOffsetY": 0.0238
}
```

# App: booking plans

amount is in paise (for Razorpay); show amountFormatted.

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

BookingPlan[]

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/customer/booking-plans

### Response samples

200 401 429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
        "id": "b7a1c3e5-9d2f-4b6a-8e0c-1f3d5a7b9c22",
        "name": "Gold",
        "amount": 30000000,
        "amountFormatted": "₹3,00,000",
        "isPopular": true
    }
]
```


## App: book a plot

Holds the plot 15 minutes. Open Razorpay Checkout with checkout.razorpayKeyId / razorpayOrderId / amountPaise, then call POST /payments/verify.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- `plotId` string
  required
- `planId` string
  required

### Responses

**— 201**

Booking + checkout

**> 400**

Bad request: PROFILE_INCOMPLETE, VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

> **409**

Conflict (state changed): PLOT_UNAVAILABLE, PENDING_BOOKING_EXISTS

> **429**

Too many requests: RATE_LIMITED

> **502**

Payment/payout provider error: PROVIDER_ERROR

POST /api/v1/customer/bookings

## Request samples

Payload

Content type
application/json

Copy

```
{
   "plotId": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
   "planId": "b7a1c3e5-9d2f-4b6a-8e0c-1f3d5a7b9c22"
}
```

## Response samples

201 | 400 | 401 | 409 | 429 | 502

Content type
application/json

Copy Expand all Collapse all

```
{
   "plotId": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
   "plotTitle": "Plot P-001",
   "block": "A",
   "location": "315 PLOTS",
```

```
    "sizeSqFt": "1,200 sq ft",
    "planName": "Gold",
    "amountFormatted": "₹3,00,000",
    "orderId": "BK-2026-000123",
    "txnId": "pay_N8yR7mT2b",
    "stepText": "Step 3 of 4",
    "stepSummary": "Agreement: in progress",
  - "milestones": [
      + { … },
      + { … },
      + { … },
      + { … }
    ],
    "bookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
    "status": "PENDING_PAYMENT",
  - "checkout": {
        "bookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
        "bookingRef": "BK-2026-000123",
        "paymentId": "d1e2f3a4-b5c6-4d7e-8f9a-0b1c2d3e4f88",
        "paymentRef": "PAY-2026-000124",
        "amountPaise": 30000000,
        "currency": "INR",
        "razorpayOrderId": "order_N8xQ2LkP3a",
        "razorpayKeyId": "rzp_live_AbC123",
        "holdExpiresAt": "2026-10-22T09:45:00.000Z"
    }
}
```


## App: current booking

The latest booking that is pending payment, confirmed or being refunded. 204 No Content when there is none.

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

Booking

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 429**

Too many requests: RATE_LIMITED

GET /api/v1/customer/bookings/active

## Response samples

200 | 401 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
   "plotId": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
   "plotTitle": "Plot P-001",
   "block": "A",
   "location": "315 PLOTS",
   "sizeSqFt": "1,200 sq ft",
   "planName": "Gold",
   "amountFormatted": "₹3,00,000",
   "orderId": "BK-2026-000123",
   "txnId": "pay_N8yR7mT2b",
   "stepText": "Step 3 of 4",
   "stepSummary": "Agreement: in progress",
 - "milestones": [
    + { … },
    + { … },
    + { … },
    + { … }
   ],
```

```
    "bookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
    "status": "CONFIRMED"
}
```


# App: my payments

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

PaymentItem[]

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/customer/payments

**Response samples**

200 | 401 | 429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
        "id": "d1e2f3a4-b5c6-4d7e-8f9a-0b1c2d3e4f88",
        "amountFormatted": "₹3,00,000",
        "dateOrSubtitle": "22 Oct 2026 · PAY-2026-000124",
        "statusBadge": "Verified"
    }
]
```


# App: my documents

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

DocumentItem[]

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/customer/documents

### Response samples

200 | 401 | 429

**Content type**
application/json

Copy Expand all Collapse all


```
[
 - {
       "id": "f0e1d2c3-b4a5-4968-8776-655443322110",
       "title": "Sale Agreement",
       "subtitle": "Agreement · 22 Oct 2026",
       "statusBadge": "Action needed",
       "isActionNeeded": true
   }
]
```


# App: customer notifications

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

NotificationItem[]

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/customer/notifications

### Response samples

200 401 429

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c55",
      "title": "Booking confirmed",
      "timeAgo": "2h ago",
      "iconType": "booking"
   }
]
```


## App: customer profile

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

UserProfile

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/customer/profile

**Response samples**

200 401 429

**Content type**
application/json

Copy

```
{
    "fullName": "Asha Patil",
    "phone": "9876543210",
    "email": "asha@example.com",
    "nomineeName": "Rahul Patil",
    "roleTitle": "Customer"
}
```

## App: save customer profile

fullName is required before booking. phone is the login and cannot change.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

| | | |
|---|---|---|
| `fullName` required | string | <= 100 characters |
| `email` | string | <= 200 characters |
| `phone` | string | |
| `nomineeName` | string | <= 100 characters |

### Responses

**— 200**

UserProfile

**400**

Bad request: PHONE_CHANGE_NOT_ALLOWED, VALIDATION_FAILED

**401**

Not signed in or token expired: UNAUTHORIZED

**429**

Too many requests: RATE_LIMITED

PUT /api/v1/customer/profile

## Request samples

Payload

Content type
application/json

Copy

```
{
    "fullName": "Asha Patil",
    "email": "asha@example.com",
    "phone": "9876543210",
    "nomineeName": "Rahul Patil"
}
```

## Response samples

200 400 401 429

Content type
application/json

Copy

```
{
    "fullName": "Asha Patil",
    "phone": "9876543210",
```

```
    "email": "asha@example.com",
    "nomineeName": "Rahul Patil",
    "roleTitle": "Customer"
}
```

## App: who referred me

204 No Content when the customer has no referrer.

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

ReferrerInfo

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/customer/referrer

**Response samples**

200 | 401 | 429

Content type
application/json

Copy

```
{
    "agentCode": "P7KQ2XM",
    "agentName": "Vikram Shah",
    "agentRole": "Partner",
    "customerName": "Asha Patil",
    "customerStatus": "Booked"
}
```


## App: partner dashboard

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

DashboardStats

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: PARTNER_NOT_APPROVED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/agent/dashboard/stats

**Response samples**

200 | 401 | 403 | 429

Content type
application/json

Copy


```
{
    "leadsCount": "12",
    "activeLeadsCount": 8,
    "bookingsCount": "3",
    "netCommission": "₹90,000",
    "payoutDue": "₹45,000",
    "matchedVolume": "₹10,000"
}
```


## App: partner profile

Works before approval too (status shows Pending approval).

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

PartnerProfile

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/agent/profile

### Response samples

200 | 401 | 429

Content type
application/json

Copy


```
{
    "fullName": "Asha Patil",
    "phone": "9876543210",
    "email": "asha@example.com",
    "agentCode": "P7KQ2XM",
    "referralLink": "https://315plots.app/r/P7KQ2XM",
    "roleTitle": "Partner · 315 PLOTS",
    "status": "Approved",
    "panDocument": "******234F",
    "bankAccount": "HDFC0001234 · ****9012"
}
```


## App: update partner profile

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

| | | |
|---|---|---|
| `fullName` required | string | <= 100 characters |
| `email` | string | <= 200 characters |
| `phone` | string | |
| `address` | string | <= 500 characters |

## Responses

**— 200**

PartnerProfile

**> 400**

Bad request: PHONE_CHANGE_NOT_ALLOWED, VALIDATION_FAILED

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

PUT `/api/v1/agent/profile`

## Request samples

Payload

Content type
application/json

Copy

```
{
    "fullName": "Asha Patil",
    "email": "asha@example.com",
    "phone": "9876543210",
    "address": "Baner, Pune"
}
```

## Response samples

200 | 400 | 401 | 429

Content type
application/json

Copy

```
{
    "fullName": "Asha Patil",
    "phone": "9876543210",
    "email": "asha@example.com",
    "agentCode": "P7KQ2XM",
    "referralLink": "https://315plots.app/r/P7KQ2XM",
    "roleTitle": "Partner · 315 PLOTS",
    "status": "Approved",
    "panDocument": "******234F",
    "bankAccount": "HDFC0001234 · ****9012"
}
```


## App: apply as partner (PAN + bank)

Stores PAN and bank details encrypted and sets partner status to Pending approval. Bank details are registered for payouts when an admin approves.

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **pan** required — string^[A-Z]{5}[0-9]{4}[A-Z]$
- **accountNumber** required — string^\d{9,18}$
- **ifsc** required — string^[A-Z]{4}0[A-Z0-9]{6}$

### Responses

**— 201**

PartnerProfile

**> 400**

Bad request: PROFILE_INCOMPLETE, VALIDATION_FAILED

> **401**

Not signed in or token expired: UNAUTHORIZED

> **409**

Conflict (state changed): INVALID_STATE

> **429**

Too many requests: RATE_LIMITED

POST `/api/v1/agent/onboarding/kyc`

## Request samples

Payload

Content type
application/json

Copy

```
{
    "pan": "ABCDE1234F",
    "accountNumber": "123456789012",
    "ifsc": "HDFC0001234"
}
```

## Response samples

201 | 400 | 401 | 409 | 429

Content type
application/json

Copy

```
{
    "fullName": "Asha Patil",
    "phone": "9876543210",
    "email": "asha@example.com",
```

```
    "agentCode": "",
    "referralLink": "",
    "roleTitle": "Partner applicant",
    "status": "Pending approval",
    "panDocument": "******234F",
    "bankAccount": "HDFC0001234 · ****9012"
}
```


# App: my leads

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

Lead[]

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: PARTNER_NOT_APPROVED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/agent/leads

### Response samples

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c55",
      "name": "Neha Shah",
      "phone": "9822000000",
      "plotInterested": "Corner plot, Block A",
      "statusBadge": "Registered",
      "subtitle": "Added 22 Oct 2026"
   }
]
```


## App: register a lead

AUTHORIZATIONS: > *bearer*

REQUEST BODY SCHEMA: application/json
required

- **name** (required) — string <= 100 characters
- **phone** (required) — string^[6-9]\d{9}$
- **plotInterested** — string <= 200 characters

### Responses

**— 201**

Lead

**> 400**

Bad request: VALIDATION_FAILED

**401**

Not signed in or token expired: UNAUTHORIZED

**403**

Not allowed: PARTNER_NOT_APPROVED

**409**

Conflict (state changed): ALREADY_REGISTERED

**429**

Too many requests: RATE_LIMITED

POST /api/v1/agent/leads/register

## Request samples

Payload

Content type
application/json

Copy

```
{
   "name": "Neha Shah",
   "phone": "9822000000",
   "plotInterested": "Corner plot, Block A"
}
```

## Response samples

201 | 400 | 401 | 403 | 409 | 429

Content type
application/json

Copy

```
{
    "id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c55",
    "name": "Neha Shah",
    "phone": "9822000000",
    "plotInterested": "Corner plot, Block A",
    "statusBadge": "New",
    "subtitle": "Added 22 Oct 2026"
}
```


## App: team size per level

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

NetworkLevel[]

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: PARTNER_NOT_APPROVED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/agent/network/levels

**Response samples**

200 401 403 429

**Content type**
application/json

Copy Expand all Collapse all


```
[
 - {
       "level": 1,
       "membersCount": 6
   },
 - {
       "level": 2,
       "membersCount": 9
   },
 - {
       "level": 3,
       "membersCount": 4
   }
]
```


## App: referral tree (3 levels)

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

TreeNode

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: PARTNER_NOT_APPROVED

> 429

Too many requests: RATE_LIMITED

GET /api/v1/agent/network/tree

**Response samples**

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
   "id": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
   "name": "Asha Patil",
   "subtitle": "Code P7KQ2XM",
   "badgeText": "You",
   "level": 0,
 - "children": [
     + { … }
   ]
}
```


## App: commission list

Commission and matching entries, newest first; reversals show negative amounts.

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

CommissionItem[]

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 403**

Not allowed: PARTNER_NOT_APPROVED

**› 429**

Too many requests: RATE_LIMITED

GET /api/v1/agent/commissions

## Response samples

200 | 401 | 403 | 429

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
       "id": "e9f8a7b6-c5d4-4e3f-8a2b-1c0d9e8f7a66",
       "title": "Level 1 commission",
       "source": "BK-2026-000123 · Plot P-001 · Gold",
       "levelRate": "20%",
       "gross": "₹60,000",
       "adminDeduction": "₹12,000",
       "tdsDeduction": "₹3,000",
       "net": "₹45,000",
       "statusBadge": "Approved"
   }
]
```

# App: commission details

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | | |
|---|---|---|
| id<br>required | string | Resource ID |

## Responses

**— 200**

CommissionItem

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 404**

Not found: NOT_FOUND

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/agent/commissions/{id}

### Response samples

200 | 401 | 404 | 429

**Content type**

application/json

Copy


```
{
    "id": "e9f8a7b6-c5d4-4e3f-8a2b-1c0d9e8f7a66",
    "title": "Level 1 commission",
    "source": "BK-2026-000123 · Plot P-001 · Gold",
    "levelRate": "20%",
    "gross": "₹60,000",
    "adminDeduction": "₹12,000",
    "tdsDeduction": "₹3,000",
    "net": "₹45,000",
    "statusBadge": "Approved"
}
```


# App: 70:30 matching

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

MatchingSummary

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 403**

Not allowed: PARTNER_NOT_APPROVED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/agent/matching/summary

### Response samples

200 | 401 | 403 | 429

Content type
application/json

Copy


```
{
    "powerLeg": "₹3,00,000 (Left)",
    "weakerLeg": "₹71,000 (Right)",
    "matchedVolume": "₹10,000",
    "matchedVolShort": "₹10K",
    "gross50": "₹5,000",
    "admin20": "₹1,000",
    "net": "₹3,750"
}
```


## App: payout info

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

PayoutInfo

**> 401**

Not signed in or token expired: UNAUTHORIZED

> 403

Not allowed: PARTNER_NOT_APPROVED

> 429

Too many requests: RATE_LIMITED

GET /api/v1/agent/payouts/info

**Response samples**

200 | 401 | 403 | 429

Content type
application/json

Copy


```
{
    "bankName": "HDFC ****9012",
    "isVerified": true,
    "nextPayoutAmount": "₹45,000",
    "scheduledDate": "After admin approval"
}
```


## App: partner notifications

AUTHORIZATIONS: > *bearer*

### Responses

— 200

AgentNotification[]

> **401**

Not signed in or token expired: UNAUTHORIZED

> **429**

Too many requests: RATE_LIMITED

GET /api/v1/agent/notifications

### Response samples

200 | 401 | 429

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
       "id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c55",
       "title": "Commission earned",
       "timeAgo": "5m ago",
       "type": "COMMISSION"
   }
]
```


## App: admin overview

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

AdminOverviewStats

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/admin/dashboard/stats

### Response samples

200 | 401 | 429

Content type
application/json

Copy


```
{
    "totalPlots": 315,
    "plotsSold": 3,
    "plotsAvailable": 311,
    "activePartners": 14,
    "pendingApprovals": 2,
    "totalRevenue": "₹9,21,000",
    "pendingPayouts": "₹45,000"
}
```


## App: admin plot list

AUTHORIZATIONS: > *bearer*

## Responses

**— 200**

Plot[]

**› 401**

Not signed in or token expired: UNAUTHORIZED

**› 429**

Too many requests: RATE_LIMITED

GET /api/v1/admin/plots

### Response samples

200 401 429

**Content type**
application/json

Copy Expand all Collapse all

```
[
  - {
        "id": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
        "title": "Plot P-001",
        "block": "A",
        "facing": "East",
        "location": "315 PLOTS",
        "sizeSqFt": "1,200 sq ft",
        "pricePerSqFt": "₹4,167/sq ft",
        "roadWidth": "30 ft",
        "totalPriceFormatted": "₹50,00,000",
        "status": "AVAILABLE",
        "imageUrl": "https://images.unsplash.com/photo-1600585154340-be6161a56a0
        "latitude": 18.52,
        "longitude": 73.85,
        "mapOffsetX": 0.0333,
        "mapOffsetY": 0.0238
    }
]
```


## App: pending partner approvals

type PARTNER_KYC; id is the user ID.

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

AdminApprovalItem[]

**> 401**

Not signed in or token expired: UNAUTHORIZED

> 429

Too many requests: RATE_LIMITED

GET /api/v1/admin/approvals

### Response samples

200 401 429

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "id": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
      "type": "PARTNER_KYC",
      "title": "Asha Patil",
      "subtitle": "9876543210 · referred by Vikram",
      "status": "Pending",
      "submittedAt": "2h ago"
   }
]
```


## App: approve partner

Creates the referral code, registers submitted bank details for payouts, notifies the user.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | |
|---|---|
| id<br>required | string<br>Resource ID |

## Responses

**— 200**

Approved

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 404**

Not found: NOT_FOUND

**> 409**

Conflict (state changed): INVALID_STATE

**> 429**

Too many requests: RATE_LIMITED

POST /api/v1/admin/approvals/{id}/approve

### Response samples

200 | 401 | 404 | 409 | 429

Content type
application/json

Copy

```
{
  "success": true,
  "partnerStatus": "APPROVED",
  "referralCode": "P7KQ2XM"
}
```

# App: reject partner

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | | |
|---|---|---|
| id<br>required | string | Resource ID |

## Responses

**— 200**

Rejected

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 404**

Not found: NOT_FOUND

**> 409**

Conflict (state changed): INVALID_STATE

**> 429**

Too many requests: RATE_LIMITED

POST /api/v1/admin/approvals/{id}/reject

### Response samples

200 | 401 | 404 | 409 | 429

Content type
application/json

Copy


```
{
    "success": true,
    "partnerStatus": "REJECTED",
    "referralCode": null
}
```


## App: admin activity log

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

AdminActivityLog[]

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/admin/activity-logs

**Response samples**

200 401 429

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "id": "1042",
      "title": "Partner approve",
      "description": "Admin · user 6f1c2a8e",
      "timeAgo": "5m ago"
   }
]
```


## App: payout requests

id "pending:" = approved commission waiting to be paid (process it); other ids are payouts already sent.

AUTHORIZATIONS: > *bearer*

### Responses

**— 200**

AdminPayoutRequest[]

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 429**

Too many requests: RATE_LIMITED

GET /api/v1/admin/payouts

### Response samples

200 | 401 | 429

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "id": "pending:6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
      "agentName": "Asha Patil",
      "agentCode": "P7KQ2XM",
      "amount": "₹45,000",
      "bankDetails": "HDFC0001234 · ****9012",
      "period": "Due now",
      "status": "Pending"
    }
]
```


## App: send a payout

Pays a pending request through Cashfree.

AUTHORIZATIONS: > *bearer*

PATH PARAMETERS

| | |
|---|---|
| id<br>required | string<br>Resource ID |

## Responses

**— 200**

Batch result

**> 400**

Bad request: NOTHING_TO_PAY

**> 401**

Not signed in or token expired: UNAUTHORIZED

**> 409**

Conflict (state changed): ALREADY_PROCESSED

**> 429**

Too many requests: RATE_LIMITED

POST /api/v1/admin/payouts/{id}/process

## Response samples

200 | 400 | 401 | 409 | 429

Content type
application/json

Copy Expand all Collapse all


```
{
   "success": true,
   "created": 1,
 - "results": [
    + { … }
   ]
}
```