315 PLOTS — Mobile App API

Reference for the Kotlin app · 38 endpoints under `/api/v1`

Generated from the live OpenAPI spec · Interactive version: main.doi0il8u9q02x.amplifyapp.com/docs (section “App v1”)

Getting started

These are the endpoints the 315 PLOTS Android app calls. Each one matches a method in the app's `AuthApi`, `CustomerApi`, `AgentApi` or `AdminApi`, and returns the app's own Kotlin model, field for field.

Setting	Value
Base URL (staging)	`https://main.doi0il8u9q02x.amplifyapp.com/api/v1`
Set in the app	`ApiConfig.BASE_URL` = the base URL above, `USE_MOCK_API = false`
Format	JSON request and response bodies (`Content-Type: application/json`)
Auth header	`Authorization: Bearer <token>` on every call except `/auth/*`
Token lifetime	15 minutes; sign in again or use the returned `refreshToken`

Roles

`AuthResult.role`	Who	Can use
`CUSTOMER`	Any signed-in user	`/customer/*`, plus `/agent/profile`, `/agent/onboarding/kyc`, `/agent/notifications`
`AGENT`	Customer approved as partner	Everything under `/customer/*` and `/agent/*`
`ADMIN`	Operations staff	`/admin/*`

One account can be both customer and partner: a customer applies with `/agent/onboarding/kyc`, an admin approves, and the next login returns role `AGENT`.

Main flows

1. **Login:** with Firebase Phone Auth, verify the number in the app with Firebase, then `POST /auth/firebase-login` with the ID token. Or with our own OTP: `POST /auth/send-otp` → user enters code → `POST /auth/verify-otp` → save `token` (and `refreshToken`) → route by `role`. If `profileComplete` is false, show the profile screen and call `PUT /customer/profile`.
2. **Book a plot:** `GET /customer/plots` → `GET /customer/booking-plans` → `POST /customer/bookings` → open Razorpay Checkout with `checkout.razorpayKeyId`, `checkout.razorpayOrderId` and `checkout.amountPaise` → on success call `POST /payments/verify` (main API) → poll `GET /customer/bookings/active` until `status` is `CONFIRMED`. The plot is held for 15 minutes.

3. **Become a partner:** `PUT /agent/profile` → `POST /agent/onboarding/kyc` (PAN + bank) → admin approves in `/admin/approvals` → user logs in again as `AGENT` → share `agentCode` / `referralLink`.
4. **Earn and get paid:** a referred customer books → commission appears in `GET /agent/commissions` (Pending → Eligible after 7 days → Approved by admin) → admin sends it from `GET /admin/payouts` → `POST /admin/payouts/{id}/process`.

Conventions

- **Display-ready values.** Amounts (`"₹3,00,000"`), dates (`"22 Oct 2026"`), times (`"2h ago"`) and badges (`"Verified"`) come formatted; show them as they are. Raw values are in paise where present (`BookingPlan.amount`, `checkout.amountPaise`).
- **Lists** return a plain JSON array (newest first).
- **Fields marked "extra"** are additional to the app's current Kotlin model; ignore them or add them to the model (`bookingId`, `status`, `checkout`, `refreshToken`).
- **No content.** `GET /customer/bookings/active` and `GET /customer/referrer` return **204** with no body when there is nothing to show; map that to `null`.

Errors

Every error except on `/auth/*` returns this body:

```
{ "code": "PLOT_UNAVAILABLE", "message": "This plot is no longer available", "requestId": "3f0c9b2e-1a4d-4c8b-9e7f-2d1a6b5c4e30" }
```

Show `message` to the user and branch on `code`. Common errors any endpoint can return:

Status	Code	Meaning	App should
400	`VALIDATION_FAILED`	A field is missing or invalid; `message` lists them	Show the message
401	`UNAUTHORIZED` / `TOKEN_INVALID`	No token or it expired	Sign in again (or refresh)
403	`PARTNER_NOT_APPROVED` / `FORBIDDEN`	Wrong role	Hide the screen or show status
404	`NOT_FOUND`	Not found, or belongs to another user	Show not found
409	various	The state changed (plot taken, already done)	Refresh the screen
429	`RATE_LIMITED`	Too many requests	Wait and retry
502	`PROVIDER_ERROR`	Razorpay / Cashfree failed	Offer retry

All endpoints

Kotlin method	Endpoint	Purpose
`AuthApi.sendOtp()`	`POST /api/v1/auth/send-otp`	send OTP
`AuthApi.resendOtp()`	`POST /api/v1/auth/resend-otp`	resend OTP
`AuthApi.verifyOtp()`	`POST /api/v1/auth/verify-otp`	verify OTP and sign in
`AuthApi.googleLogin()`	`POST /api/v1/auth/google-login`	Google sign-in

Kotlin method	Endpoint	Purpose
`AuthApi.firebaseLogin()`	`POST /api/v1/auth/firebase-login`	Firebase phone sign-in
`AuthApi.logout()`	`POST /api/v1/auth/logout`	log out
`CustomerApi.getPlots()`	`GET /api/v1/customer/plots`	all plots
`CustomerApi.getPlotById()`	`GET /api/v1/customer/plots/{id}`	plot details
`CustomerApi.getPlans()`	`GET /api/v1/customer/booking-plans`	booking plans
`CustomerApi.createBooking()`	`POST /api/v1/customer/bookings`	book a plot
`CustomerApi.getActiveBooking()`	`GET /api/v1/customer/bookings/active`	current booking
`CustomerApi.getPayments()`	`GET /api/v1/customer/payments`	my payments
`CustomerApi.getDocuments()`	`GET /api/v1/customer/documents`	my documents
`CustomerApi.getNotifications()`	`GET /api/v1/customer/notifications`	customer notifications
`CustomerApi.getProfile()`	`GET /api/v1/customer/profile`	customer profile
`CustomerApi.saveProfile()`	`PUT /api/v1/customer/profile`	save customer profile
`CustomerApi.getReferrerInfo()`	`GET /api/v1/customer/referrer`	who referred me
`AgentApi.getDashboardStats()`	`GET /api/v1/agent/dashboard/stats`	partner dashboard
`AgentApi.getProfile()`	`GET /api/v1/agent/profile`	partner profile
`AgentApi.updateProfile()`	`PUT /api/v1/agent/profile`	update partner profile
`AgentApi.submitPartnerDetails()`	`POST /api/v1/agent/onboarding/kyc`	apply as partner (PAN + bank)
`AgentApi.getLeads()`	`GET /api/v1/agent/leads`	my leads
`AgentApi.registerLead()`	`POST /api/v1/agent/leads/register`	register a lead
`AgentApi.getNetworkLevels()`	`GET /api/v1/agent/network/levels`	team size per level
`AgentApi.getReferralTree()`	`GET /api/v1/agent/network/tree`	referral tree (3 levels)
`AgentApi.getCommissions()`	`GET /api/v1/agent/commissions`	commission list
`AgentApi.getCommissionById()`	`GET /api/v1/agent/commissions/{id}`	commission details
`AgentApi.getMatchingSummary()`	`GET /api/v1/agent/matching/summary`	70:30 matching
`AgentApi.getPayoutInfo()`	`GET /api/v1/agent/payouts/info`	payout info
`AgentApi.getNotifications()`	`GET /api/v1/agent/notifications`	partner notifications
`AdminApi.getOverviewStats()`	`GET /api/v1/admin/dashboard/stats`	admin overview
`Endpoints.ADMIN_PLOTS`	`GET /api/v1/admin/plots`	admin plot list
`AdminApi.getApprovals()`	`GET /api/v1/admin/approvals`	pending partner approvals
`AdminApi.approveItem()`	`POST /api/v1/admin/approvals/{id}/approve`	approve partner
`AdminApi.rejectItem()`	`POST /api/v1/admin/approvals/{id}/reject`	reject partner
`AdminApi.getActivityLogs()`	`GET /api/v1/admin/activity-logs`	admin activity log
`AdminApi.getPayoutRequests()`	`GET /api/v1/admin/payouts`	payout requests

Kotlin method	Endpoint	Purpose
`AdminApi.processPayout()`	`POST /api/v1/admin/payouts/{id}/process`	send a payout

Authentication

Sign in with mobile + OTP, Firebase Phone Auth or Google. With Firebase, the app verifies the number through Firebase and sends the ID token to `firebase-login`; send-otp and verify-otp are then not used. These endpoints always answer with `AuthResult`; a wrong or expired OTP returns HTTP 200 with `success: false` and `errorMessage`, so the app can show the message directly.

POST `/api/v1/auth/send-otp`

Send OTP. Sends a 6-digit login OTP. Returns AuthResult; on failure success=false with errorMessage (HTTP 429 when rate limited).

Item	Value
Kotlin	`AuthApi.sendOtp(phone)` → `AuthResult`
Auth	None (public)

Request body (JSON)

Field	Type	Required	Rules	Description
`phone`	string	yes	pattern `^[6-9]\d{9}$`	Login mobile, 10 digits starting 6–9, no +91

```
{
  "phone": "9876543210"
}
```

Response 200 — AuthResult

```
{
  "success": true,
  "token": null,
  "role": null,
  "errorMessage": null,
  "expiresInSec": 300,
  "resendAfterSec": 30
}
```

Response fields — `AuthResult`

Field	Kotlin type	Meaning
`success`	Boolean	true when the call worked
`token`	String?	Access token for `Authorization: Bearer` (15 min). Null for send/resend/logout
`role`	String?	`CUSTOMER`, `AGENT` (approved partner) or `ADMIN`
`errorMessage`	String?	Message to show when success is false
`refreshToken`	String (extra)	Use to get a new token; store securely
`expiresIn`	Int (extra)	Token lifetime in seconds

Errors (besides the common ones)

Status	Code	Message
429	`OTP_RATE_LIMITED`	Too many OTP requests, try again in 15 minutes

POST `/api/v1/auth/resend-otp`

Resend OTP. Same as send-otp.

Item	Value
Kotlin	`AuthApi.resendOtp(phone)` → `AuthResult`
Auth	None (public)

Request body (JSON)

Field	Type	Required	Rules	Description
`phone`	string	yes	pattern `^[6-9]\d{9}$`	Login mobile, 10 digits starting 6–9, no +91

```
{
  "phone": "9876543210"
}
```

Response 200 — AuthResult

```
{
  "success": true,
  "token": null,
  "role": null,
  "errorMessage": null
}
```

Response fields — `AuthResult`

Field	Kotlin type	Meaning
`success`	Boolean	true when the call worked
`token`	String?	Access token for `Authorization: Bearer` (15 min). Null for send/resend/logout
`role`	String?	`CUSTOMER`, `AGENT` (approved partner) or `ADMIN`
`errorMessage`	String?	Message to show when success is false
`refreshToken`	String (extra)	Use to get a new token; store securely
`expiresIn`	Int (extra)	Token lifetime in seconds

POST `/api/v1/auth/verify-otp`

Verify OTP and sign in. token is the access token for `Authorization: Bearer`. role is CUSTOMER, AGENT (approved partner) or ADMIN. Wrong/expired OTP → success=false with errorMessage.

Item	Value
Kotlin	`AuthApi.verifyOtp(phone, otp)` → `AuthResult`
Auth	None (public)

Request body (JSON)

Field	Type	Required	Rules	Description
`phone`	string	yes	pattern `^[6-9]\d{9}$`	Login mobile, 10 digits starting 6–9, no +91
`otp`	string	yes	pattern `^\d{6}$`	6-digit code from the SMS
`referralCode`	string	no	max 20 chars	Optional. Partner's referral code (new accounts only)

```
{
  "phone": "9876543210",
  "otp": "482913",
  "referralCode": "P7KQ2XM"
}
```

Response 200 — AuthResult

```
{
  "success": true,
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiI2ZjFj…",
  "role": "CUSTOMER",
  "errorMessage": null,
  "refreshToken": "q8V2c1sY9…",
  "expiresIn": 900,
  "isNewUser": true,
  "profileComplete": false
}
```

Response fields — `AuthResult`

Field	Kotlin type	Meaning
`success`	Boolean	true when the call worked
`token`	String?	Access token for `Authorization: Bearer` (15 min). Null for send/resend/logout
`role`	String?	`CUSTOMER`, `AGENT` (approved partner) or `ADMIN`
`errorMessage`	String?	Message to show when success is false
`refreshToken`	String (extra)	Use to get a new token; store securely
`expiresIn`	Int (extra)	Token lifetime in seconds

POST `/api/v1/auth/google-login`

Google sign-in.

Item	Value
Kotlin	`AuthApi.googleLogin(idToken)` → `AuthResult`
Auth	None (public)

Request body (JSON)

Field	Type	Required	Rules	Description
`idToken`	string	yes		ID token: from Google Sign-In (google-login) or FirebaseUser.getIdToken() (firebase-login)

```
{
  "idToken": "eyJhbGciOiJSUzI1NiIsImtpZCI6…"
}
```

Response 200 — AuthResult

```
{
  "success": true,
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiI2ZjFj…",
  "role": "CUSTOMER",
  "errorMessage": null,
  "refreshToken": "q8V2c1sY9…",
  "expiresIn": 900,
  "isNewUser": false,
  "profileComplete": false
}
```

Response fields — `AuthResult`

Field	Kotlin type	Meaning
`success`	Boolean	true when the call worked
`token`	String?	Access token for `Authorization: Bearer` (15 min). Null for send/resend/logout
`role`	String?	`CUSTOMER`, `AGENT` (approved partner) or `ADMIN`
`errorMessage`	String?	Message to show when success is false
`refreshToken`	String (extra)	Use to get a new token; store securely
`expiresIn`	Int (extra)	Token lifetime in seconds

POST `/api/v1/auth/firebase-login`

Firebase phone sign-in. Call after Firebase PhoneAuthProvider signs the user in: send FirebaseUser.getIdToken(). Firebase sends the SMS, so send-otp/verify-otp are not used. Failures → success=false with errorMessage.

Item	Value
Kotlin	`AuthApi.firebaseLogin(idToken, referralCode)` → `AuthResult`
Auth	None (public)

Request body (JSON)

Field	Type	Required	Rules	Description
`idToken`	string	yes		ID token: from Google Sign-In (google-login) or FirebaseUser.getIdToken() (firebase-login)
`referralCode`	string	no	max 20 chars	Optional. Partner's referral code (new accounts only)

```
{
  "idToken": "eyJhbGciOiJSUzI1NiIsImtpZCI6…",
  "referralCode": "P7KQ2XM"
}
```

Response 200 — AuthResult

```
{
  "success": true,
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiI2ZjFj…",
  "role": "CUSTOMER",
  "errorMessage": null,
  "refreshToken": "q8V2c1sY9…",
  "expiresIn": 900,
  "isNewUser": true,
  "profileComplete": false
}
```

Response fields — `AuthResult`

Field	Kotlin type	Meaning
`success`	Boolean	true when the call worked
`token`	String?	Access token for `Authorization: Bearer` (15 min). Null for send/resend/logout
`role`	String?	`CUSTOMER`, `AGENT` (approved partner) or `ADMIN`
`errorMessage`	String?	Message to show when success is false
`refreshToken`	String (extra)	Use to get a new token; store securely
`expiresIn`	Int (extra)	Token lifetime in seconds

POST `/api/v1/auth/logout`

Log out. Send the refresh token to revoke it.

Item	Value
Kotlin	`AuthApi.logout()` → `AuthResult`
Auth	None (public)

Request body (JSON)

Field	Type	Required	Rules	Description
`refreshToken`	string	no		Optional. Refresh token to revoke

```
{
  "refreshToken": "q8V2c1sY9…"
}
```

Response 200 — Logged out

```
{
  "success": true,
  "token": null,
  "role": null,
  "errorMessage": null
}
```

Response fields — `AuthResult`

Field	Kotlin type	Meaning
`success`	Boolean	true when the call worked
`token`	String?	Access token for `Authorization: Bearer` (15 min). Null for send/resend/logout
`role`	String?	`CUSTOMER`, `AGENT` (approved partner) or `ADMIN`
`errorMessage`	String?	Message to show when success is false
`refreshToken`	String (extra)	Use to get a new token; store securely
`expiresIn`	Int (extra)	Token lifetime in seconds

Customer

Every signed-in user. Browse plots, book and pay, track the booking, see payments, documents, notifications and profile.

GET `/api/v1/customer/plots`

All plots. Plot cards for list and map. status: AVAILABLE, BOOKED, ON_HOLD. mapOffsetX/Y are 0–1 positions on the site map.

Item	Value
Kotlin	`CustomerApi.getPlots()` → `List<Plot>`
Auth	Bearer token

Response 200 — Plot[]


```
[
  {
    "id": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
    "title": "Plot P-001",
    "block": "A",
    "facing": "East",
    "location": "315 PLOTS",
    "sizeSqFt": "1,200 sq ft",
    "pricePerSqFt": "₹4,167/sq ft",
    "roadWidth": "30 ft",
    "totalPriceFormatted": "₹50,00,000",
    "status": "AVAILABLE",
    "imageUrl": "https://images.unsplash.com/photo-1600585154340-be6161a56a0c",
    "latitude": 18.52,
    "longitude": 73.85,
    "mapOffsetX": 0.0333,
    "mapOffsetY": 0.0238
  }
]
```


Response fields — `Plot`

Field	Kotlin type	Meaning
`id`	String	Plot ID (UUID)
`title`	String	e.g. "Plot P-001"
`block`	String	Block / sector, may be empty
`facing`	String	Facing direction, may be empty
`location`	String	Project or plot location
`sizeSqFt`	String	e.g. "1,200 sq ft"
`pricePerSqFt`	String	e.g. "₹4,167/sq ft"
`roadWidth`	String	e.g. "30 ft"
`totalPriceFormatted`	String	e.g. "₹50,00,000"

Field	Kotlin type	Meaning
`status`	PlotStatus	`AVAILABLE` (bookable), `BOOKED`, `ON_HOLD` (someone is paying, or blocked)
`imageUrl`	String	Image to show
`latitude`	Double	Map latitude (0 if not set)
`longitude`	Double	Map longitude
`mapOffsetX`	Float	0–1 horizontal position on the site map
`mapOffsetY`	Float	0–1 vertical position on the site map

GET `/api/v1/customer/plots/{id}`

Plot details.

Item	Value
Kotlin	`CustomerApi.getPlotById(id)` → `Plot`
Auth	Bearer token

Path parameter	Description
`id`	ID from the list

Response 200 — Plot


```
{
  "id": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
  "title": "Plot P-001",
  "block": "A",
  "facing": "East",
  "location": "315 PLOTS",
  "sizeSqFt": "1,200 sq ft",
  "pricePerSqFt": "₹4,167/sq ft",
  "roadWidth": "30 ft",
  "totalPriceFormatted": "₹50,00,000",
  "status": "AVAILABLE",
  "imageUrl": "https://images.unsplash.com/photo-1600585154340-be6161a56a0c",
  "latitude": 18.52,
  "longitude": 73.85,
  "mapOffsetX": 0.0333,
  "mapOffsetY": 0.0238
}
```


Response fields — `Plot`

Field	Kotlin type	Meaning
`id`	String	Plot ID (UUID)
`title`	String	e.g. "Plot P-001"
`block`	String	Block / sector, may be empty
`facing`	String	Facing direction, may be empty

Field	Kotlin type	Meaning
`location`	String	Project or plot location
`sizeSqFt`	String	e.g. "1,200 sq ft"
`pricePerSqFt`	String	e.g. "₹4,167/sq ft"
`roadWidth`	String	e.g. "30 ft"
`totalPriceFormatted`	String	e.g. "₹50,00,000"
`status`	PlotStatus	`AVAILABLE` (bookable), `BOOKED`, `ON_HOLD` (someone is paying, or blocked)
`imageUrl`	String	Image to show
`latitude`	Double	Map latitude (0 if not set)
`longitude`	Double	Map longitude
`mapOffsetX`	Float	0–1 horizontal position on the site map
`mapOffsetY`	Float	0–1 vertical position on the site map

Errors (besides the common ones)

Status	Code	Message
404	`NOT_FOUND`	Plot not found

GET `/api/v1/customer/booking-plans`

Booking plans. amount is in paise (for Razorpay); show amountFormatted.

Item	Value
Kotlin	`CustomerApi.getPlans()` → `List<BookingPlan>`
Auth	Bearer token

Response 200 — BookingPlan[]

```
[
  {
    "id": "b7a1c3e5-9d2f-4b6a-8e0c-1f3d5a7b9c22",
    "name": "Gold",
    "amount": 30000000,
    "amountFormatted": "₹3,00,000",
    "isPopular": true
  }
]
```

Response fields — `BookingPlan`

Field	Kotlin type	Meaning
`id`	String	Plan ID; send as planId when booking
`name`	String	e.g. "Gold"
`amount`	Long	Amount in **paise** (for Razorpay)

Field	Kotlin type	Meaning
`amountFormatted`	String	e.g. "₹3,00,000"
`isPopular`	Boolean	Highlight this plan

POST `/api/v1/customer/bookings`

Book a plot. Holds the plot 15 minutes. Open Razorpay Checkout with checkout.razorpayKeyId / razorpayOrderId / amountPaise, then call POST /payments/verify.

Item	Value
Kotlin	`CustomerApi.createBooking(plotId, planId)` → `Booking`
Auth	Bearer token

Request body (JSON)

Field	Type	Required	Rules	Description
`plotId`	string	yes		Plot ID from the plot list (must be AVAILABLE)
`planId`	string	yes		Plan ID from booking plans

```
{
  "plotId": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
  "planId": "b7a1c3e5-9d2f-4b6a-8e0c-1f3d5a7b9c22"
}
```

Response 201 — Booking + checkout


```
{
  "plotId": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
  "plotTitle": "Plot P-001",
  "block": "A",
  "location": "315 PLOTS",
  "sizeSqFt": "1,200 sq ft",
  "planName": "Gold",
  "amountFormatted": "₹3,00,000",
  "orderId": "BK-2026-000123",
  "txnId": "pay_N8yR7mT2b",
  "stepText": "Step 3 of 4",
  "stepSummary": "Agreement: in progress",
  "milestones": [
    {
      "step": 1,
      "title": "Plot reserved",
      "subtitle": "Plot P-001 held for you",
      "status": "COMPLETED",
      "badgeLabel": "Done"
    },
    {
      "step": 2,
      "title": "Payment",
      "subtitle": "₹3,00,000 received",
      "status": "COMPLETED",
      "badgeLabel": "Done"
    },
    {
      "step": 3,
      "title": "Agreement",
      "subtitle": "Agreement sent",
      "status": "IN_PROGRESS",
      "badgeLabel": "In progress"
    },
    {
      "step": 4,
      "title": "Allotment",
      "subtitle": "After agreement",
      "status": "UPCOMING",
      "badgeLabel": "Upcoming"
    }
  ],
  "bookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
  "status": "PENDING_PAYMENT",
  "checkout": {
    "bookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
    "bookingRef": "BK-2026-000123",
    "paymentId": "d1e2f3a4-b5c6-4d7e-8f9a-0b1c2d3e4f88",
    "paymentRef": "PAY-2026-000124",
    "amountPaise": 30000000,
    "currency": "INR",
    "razorpayOrderId": "order_N8xQ2LkP3a",
    "razorpayKeyId": "rzp_live_AbC123",
    "holdExpiresAt": "2026-10-22T09:45:00.000Z"
  }
}
```

Response fields — `Booking`

Field	Kotlin type	Meaning
`plotId`	String	Booked plot
`plotTitle`	String	e.g. "Plot P-001"
`block`	String	Block
`location`	String	Location
`sizeSqFt`	String	Size
`planName`	String	Plan chosen
`amountFormatted`	String	Amount paid / due
`orderId`	String	Booking reference, e.g. BK-2026-000123
`txnId`	String	Razorpay payment ID once paid, else empty
`stepText`	String	e.g. "Step 3 of 4"
`stepSummary`	String	e.g. "Agreement: in progress"
`milestones`	List	4 steps: Plot reserved, Payment, Agreement, Allotment
`bookingId`	String (extra)	Booking ID
`status`	String (extra)	`PENDING_PAYMENT`, `CONFIRMED`, `REFUND_PENDING`…
`checkout`	object (extra, create only)	Razorpay data: razorpayKeyId, razorpayOrderId, amountPaise, holdExpiresAt

`Milestone`

Field	Kotlin type	Meaning
`step`	Int	1–4
`title`	String	Step name
`subtitle`	String	Detail
`status`	MilestoneStatus	`COMPLETED`, `IN_PROGRESS`, `UPCOMING`
`badgeLabel`	String	Done, In progress, Upcoming

Errors (besides the common ones)

Status	Code	Message
400	`PROFILE_INCOMPLETE`	Complete your profile before booking
409	`PLOT_UNAVAILABLE`	This plot is no longer available
409	`PENDING_BOOKING_EXISTS`	Finish or cancel your current checkout first
502	`PROVIDER_ERROR`	Could not start payment, please retry

GET `/api/v1/customer/bookings/active`

Current booking. The latest booking that is pending payment, confirmed or being refunded. 204 No Content when there is none.

Item	Value
Kotlin	`CustomerApi.getActiveBooking()` → `Booking?`
Auth	Bearer token

Response 200 — Booking


```
{
  "plotId": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
  "plotTitle": "Plot P-001",
  "block": "A",
  "location": "315 PLOTS",
  "sizeSqFt": "1,200 sq ft",
  "planName": "Gold",
  "amountFormatted": "₹3,00,000",
  "orderId": "BK-2026-000123",
  "txnId": "pay_N8yR7mT2b",
  "stepText": "Step 3 of 4",
  "stepSummary": "Agreement: in progress",
  "milestones": [
    {
      "step": 1,
      "title": "Plot reserved",
      "subtitle": "Plot P-001 held for you",
      "status": "COMPLETED",
      "badgeLabel": "Done"
    },
    {
      "step": 2,
      "title": "Payment",
      "subtitle": "₹3,00,000 received",
      "status": "COMPLETED",
      "badgeLabel": "Done"
    },
    {
      "step": 3,
      "title": "Agreement",
      "subtitle": "Agreement sent",
      "status": "IN_PROGRESS",
      "badgeLabel": "In progress"
    },
    {
      "step": 4,
      "title": "Allotment",
      "subtitle": "After agreement",
      "status": "UPCOMING",
      "badgeLabel": "Upcoming"
    }
  ],
  "bookingId": "c4d5e6f7-a8b9-4c0d-9e1f-2a3b4c5d6e77",
  "status": "CONFIRMED"
}
```

Response fields — `Booking`

Field	Kotlin type	Meaning
`plotId`	String	Booked plot
`plotTitle`	String	e.g. "Plot P-001"
`block`	String	Block
`location`	String	Location
`sizeSqFt`	String	Size
`planName`	String	Plan chosen
`amountFormatted`	String	Amount paid / due
`orderId`	String	Booking reference, e.g. BK-2026-000123
`txnId`	String	Razorpay payment ID once paid, else empty
`stepText`	String	e.g. "Step 3 of 4"
`stepSummary`	String	e.g. "Agreement: in progress"
`milestones`	List	4 steps: Plot reserved, Payment, Agreement, Allotment
`bookingId`	String (extra)	Booking ID
`status`	String (extra)	`PENDING_PAYMENT`, `CONFIRMED`, `REFUND_PENDING`…
`checkout`	object (extra, create only)	Razorpay data: razorpayKeyId, razorpayOrderId, amountPaise, holdExpiresAt

`Milestone`

Field	Kotlin type	Meaning
`step`	Int	1–4
`title`	String	Step name
`subtitle`	String	Detail
`status`	MilestoneStatus	`COMPLETED`, `IN_PROGRESS`, `UPCOMING`
`badgeLabel`	String	Done, In progress, Upcoming

GET `/api/v1/customer/payments`

My payments.

Item	Value
Kotlin	`CustomerApi.getPayments()` → `List<PaymentItem>`
Auth	Bearer token

Response 200 — PaymentItem[]

```
[
  {
    "id": "d1e2f3a4-b5c6-4d7e-8f9a-0b1c2d3e4f88",
    "amountFormatted": "₹3,00,000",
    "dateOrSubtitle": "22 Oct 2026 · PAY-2026-000124",
    "statusBadge": "Verified"
  }
]
```

Response fields — `PaymentItem`

Field	Kotlin type	Meaning
`id`	String	Payment ID
`amountFormatted`	String	e.g. "₹3,00,000"
`dateOrSubtitle`	String	e.g. "22 Oct 2026 · PAY-2026-000124"
`statusBadge`	String	Pending, Verified, Failed, Refund pending, Refunded

---

GET `/api/v1/customer/documents`

My documents.

Item	Value
Kotlin	`CustomerApi.getDocuments()` → `List<DocumentItem>`
Auth	Bearer token

Response 200 — DocumentItem[]

```
[
  {
    "id": "f0e1d2c3-b4a5-4968-8776-655443322110",
    "title": "Sale Agreement",
    "subtitle": "Agreement · 22 Oct 2026",
    "statusBadge": "Action needed",
    "isActionNeeded": true
  }
]
```

Response fields — `DocumentItem`

Field	Kotlin type	Meaning
`id`	String	Document ID
`title`	String	e.g. "Sale Agreement"
`subtitle`	String	Type and date
`statusBadge`	String	Action needed, Sent, Signed, Rejected, Expired
`isActionNeeded`	Boolean	true for an agreement waiting for the customer

GET /api/v1/customer/notifications

Customer notifications.

Item	Value
Kotlin	`CustomerApi.getNotifications()` → `List<NotificationItem>`
Auth	Bearer token

Response 200 — NotificationItem[]

```
[
  {
    "id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c55",
    "title": "Booking confirmed",
    "timeAgo": "2h ago",
    "iconType": "booking"
  }
]
```

Response fields — `NotificationItem`

Field	Kotlin type	Meaning
`id`	String	Notification ID
`title`	String	Text
`timeAgo`	String	e.g. "2h ago"
`iconType`	String	booking, payment, document, commission, payout, account, general

GET /api/v1/customer/profile

Customer profile.

Item	Value
Kotlin	`CustomerApi.getProfile()` → `UserProfile`
Auth	Bearer token

Response 200 — UserProfile

```
{
  "fullName": "Asha Patil",
  "phone": "9876543210",
  "email": "asha@example.com",
  "nomineeName": "Rahul Patil",
  "roleTitle": "Customer"
}
```

Response fields — `UserProfile`

Field	Kotlin type	Meaning
`fullName`	String	Name (required before booking)
`phone`	String	Login mobile
`email`	String	Email
`nomineeName`	String	Nominee
`roleTitle`	String	"Customer" or "Customer & Partner"

PUT `/api/v1/customer/profile`

Save customer profile. fullName is required before booking. phone is the login and cannot change.

Item	Value
Kotlin	`CustomerApi.saveProfile(fullName, email, phone, nomineeName)` → `UserProfile`
Auth	Bearer token

Request body (JSON)

Field	Type	Required	Rules	Description
`fullName`	string	yes	max 100 chars	Full name
`email`	string	no	max 200 chars	Optional. Email
`phone`	string	no		Login mobile, 10 digits starting 6–9, no +91
`nomineeName`	string	no	max 100 chars	Optional. Nominee name

```
{
  "fullName": "Asha Patil",
  "email": "asha@example.com",
  "phone": "9876543210",
  "nomineeName": "Rahul Patil"
}
```

Response 200 — UserProfile

```
{
  "fullName": "Asha Patil",
  "phone": "9876543210",
  "email": "asha@example.com",
  "nomineeName": "Rahul Patil",
  "roleTitle": "Customer"
}
```

Response fields — `UserProfile`

Field	Kotlin type	Meaning
`fullName`	String	Name (required before booking)

Field	Kotlin type	Meaning
`phone`	String	Login mobile
`email`	String	Email
`nomineeName`	String	Nominee
`roleTitle`	String	"Customer" or "Customer & Partner"

Errors (besides the common ones)

Status	Code	Message
400	`PHONE_CHANGE_NOT_ALLOWED`	Mobile number is your login and cannot be changed here

---

GET `/api/v1/customer/referrer`

Who referred me. 204 No Content when the customer has no referrer.

Item	Value
Kotlin	`CustomerApi.getReferrerInfo()` → `ReferrerInfo?`
Auth	Bearer token

Response 200 — ReferrerInfo

```
{
  "agentCode": "P7KQ2XM",
  "agentName": "Vikram Shah",
  "agentRole": "Partner",
  "customerName": "Asha Patil",
  "customerStatus": "Booked"
}
```

Response fields — `ReferrerInfo`

Field	Kotlin type	Meaning
`agentCode`	String	Referrer's referral code
`agentName`	String	Referrer's name
`agentRole`	String	"Partner"
`customerName`	String	This customer
`customerStatus`	String	"Registered" or "Booked"

Agent (partner)

Profile, onboarding and notifications work for any user; the rest needs an approved partner (`403 PARTNER_NOT_APPROVED` otherwise).

GET /api/v1/agent/dashboard/stats

Partner dashboard.

Item	Value
Kotlin	`AgentApi.getDashboardStats()` → `DashboardStats`
Auth	Bearer token of an **approved partner**

Response 200 — DashboardStats

```
{
  "leadsCount": "12",
  "activeLeadsCount": 8,
  "bookingsCount": "3",
  "netCommission": "₹90,000",
  "payoutDue": "₹45,000",
  "matchedVolume": "₹10,000"
}
```

Response fields — `DashboardStats`

Field	Kotlin type	Meaning
`leadsCount`	String	Total leads
`activeLeadsCount`	Int	Leads not yet booked
`bookingsCount`	String	Bookings that earned this partner commission
`netCommission`	String	Net earned (after 20% admin, 5% TDS)
`payoutDue`	String	Approved, waiting for payout
`matchedVolume`	String	Total 70:30 matched volume

Errors (besides the common ones)

Status	Code	Message
403	`PARTNER_NOT_APPROVED`	Partner approval is required

GET /api/v1/agent/profile

Partner profile. Works before approval too (status shows Pending approval).

Item	Value
Kotlin	`AgentApi.getProfile()` → `PartnerProfile`

Item	Value
Auth	Bearer token

Response 200 — PartnerProfile

```
{
  "fullName": "Asha Patil",
  "phone": "9876543210",
  "email": "asha@example.com",
  "agentCode": "P7KQ2XM",
  "referralLink": "https://315plots.app/r/P7KQ2XM",
  "roleTitle": "Partner · 315 PLOTS",
  "status": "Approved",
  "panDocument": "******234F",
  "bankAccount": "HDFC0001234 · ****9012"
}
```

Response fields — `PartnerProfile`

Field	Kotlin type	Meaning
`fullName`	String	Name
`phone`	String	Login mobile
`email`	String	Email
`agentCode`	String	Referral code (empty until approved)
`referralLink`	String	Share link (empty until approved)
`roleTitle`	String	e.g. "Partner · 315 PLOTS"
`status`	String	Not applied, Pending approval, Approved, Rejected, Suspended
`panDocument`	String	Masked PAN, e.g. "******234F"
`bankAccount`	String	Masked bank, e.g. "HDFC0001234 · ****9012"

PUT `/api/v1/agent/profile`

Update partner profile.

Item	Value
Kotlin	`AgentApi.updateProfile(fullName, email, phone, address)` → `PartnerProfile`
Auth	Bearer token

Request body (JSON)

Field	Type	Required	Rules	Description
`fullName`	string	yes	max 100 chars	Full name
`email`	string	no	max 200 chars	Optional. Email
`phone`	string	no		Login mobile, 10 digits starting 6–9, no +91

Field	Type	Required	Rules	Description
`address`	string	no	max 500 chars	Optional. Address

```
{
  "fullName": "Asha Patil",
  "email": "asha@example.com",
  "phone": "9876543210",
  "address": "Baner, Pune"
}
```

Response 200 — PartnerProfile

```
{
  "fullName": "Asha Patil",
  "phone": "9876543210",
  "email": "asha@example.com",
  "agentCode": "P7KQ2XM",
  "referralLink": "https://315plots.app/r/P7KQ2XM",
  "roleTitle": "Partner · 315 PLOTS",
  "status": "Approved",
  "panDocument": "******234F",
  "bankAccount": "HDFC0001234 · ****9012"
}
```

Response fields — `PartnerProfile`

Field	Kotlin type	Meaning
`fullName`	String	Name
`phone`	String	Login mobile
`email`	String	Email
`agentCode`	String	Referral code (empty until approved)
`referralLink`	String	Share link (empty until approved)
`roleTitle`	String	e.g. "Partner · 315 PLOTS"
`status`	String	Not applied, Pending approval, Approved, Rejected, Suspended
`panDocument`	String	Masked PAN, e.g. "******234F"
`bankAccount`	String	Masked bank, e.g. "HDFC0001234 · ****9012"

Errors (besides the common ones)

Status	Code	Message
400	`PHONE_CHANGE_NOT_ALLOWED`	Mobile number is your login and cannot be changed here

POST `/api/v1/agent/onboarding/kyc`

Apply as partner (PAN + bank). Stores PAN and bank details encrypted and sets partner status to Pending approval. Bank details are registered for payouts when an admin approves.

Item	Value
Kotlin	`AgentApi.submitPartnerDetails(pan, accountNumber, ifsc)` → `PartnerProfile`
Auth	Bearer token

Request body (JSON)

Field	Type	Required	Rules	Description
`pan`	string	yes	pattern `^[A-Z]{5}[0-9]{4}[A-Z]$`	PAN, e.g. ABCDE1234F (stored encrypted)
`accountNumber`	string	yes	pattern `^\d{9,18}$`	Bank account, 9–18 digits (stored encrypted)
`ifsc`	string	yes	pattern `^[A-Z]{4}0[A-Z0-9]{6}$`	IFSC, e.g. HDFC0001234

```
{
  "pan": "ABCDE1234F",
  "accountNumber": "123456789012",
  "ifsc": "HDFC0001234"
}
```

Response 201 — PartnerProfile

```
{
  "fullName": "Asha Patil",
  "phone": "9876543210",
  "email": "asha@example.com",
  "agentCode": "",
  "referralLink": "",
  "roleTitle": "Partner applicant",
  "status": "Pending approval",
  "panDocument": "******234F",
  "bankAccount": "HDFC0001234 · ****9012"
}
```

Response fields — `PartnerProfile`

Field	Kotlin type	Meaning
`fullName`	String	Name
`phone`	String	Login mobile
`email`	String	Email
`agentCode`	String	Referral code (empty until approved)
`referralLink`	String	Share link (empty until approved)
`roleTitle`	String	e.g. "Partner · 315 PLOTS"

Field	Kotlin type	Meaning
`status`	String	Not applied, Pending approval, Approved, Rejected, Suspended
`panDocument`	String	Masked PAN, e.g. "******234F"
`bankAccount`	String	Masked bank, e.g. "HDFC0001234 · ****9012"

Errors (besides the common ones)

Status	Code	Message
400	`PROFILE_INCOMPLETE`	Complete your profile first
409	`INVALID_STATE`	Partner status is APPROVED

GET `/api/v1/agent/leads`

My leads.

Item	Value
Kotlin	`AgentApi.getLeads()` → `List<Lead>`
Auth	Bearer token of an **approved partner**

Response 200 — Lead[]

```
[
  {
    "id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c55",
    "name": "Neha Shah",
    "phone": "9822000000",
    "plotInterested": "Corner plot, Block A",
    "statusBadge": "Registered",
    "subtitle": "Added 22 Oct 2026"
  }
]
```

Response fields — `Lead`

Field	Kotlin type	Meaning
`id`	String	Lead ID
`name`	String	Prospect name
`phone`	String	Prospect mobile
`plotInterested`	String	Note
`statusBadge`	String	New, Registered, Booked
`subtitle`	String	e.g. "Added 22 Oct 2026"

Errors (besides the common ones)

Status	Code	Message
403	`PARTNER_NOT_APPROVED`	Partner approval is required

POST `/api/v1/agent/leads/register`

Register a lead.

Item	Value
Kotlin	`AgentApi.registerLead(name, phone, plotInterested)` → `Lead`
Auth	Bearer token of an **approved partner**

Request body (JSON)

Field	Type	Required	Rules	Description
`name`	string	yes	max 100 chars	Prospect's name
`phone`	string	yes	pattern `^[6–9]\d{9}$`	Login mobile, 10 digits starting 6–9, no +91
`plotInterested`	string	no	max 200 chars	Optional. Note about interest

```
{
  "name": "Neha Shah",
  "phone": "9822000000",
  "plotInterested": "Corner plot, Block A"
}
```

Response 201 — Lead

```
{
  "id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c55",
  "name": "Neha Shah",
  "phone": "9822000000",
  "plotInterested": "Corner plot, Block A",
  "statusBadge": "New",
  "subtitle": "Added 22 Oct 2026"
}
```

Response fields — `Lead`

Field	Kotlin type	Meaning
`id`	String	Lead ID
`name`	String	Prospect name
`phone`	String	Prospect mobile
`plotInterested`	String	Note
`statusBadge`	String	New, Registered, Booked
`subtitle`	String	e.g. "Added 22 Oct 2026"

Errors (besides the common ones)

Status	Code	Message
403	`PARTNER_NOT_APPROVED`	Partner approval is required
409	`ALREADY_REGISTERED`	This mobile number already has an account

GET `/api/v1/agent/network/levels`

Team size per level.

Item	Value
Kotlin	`AgentApi.getNetworkLevels()` → `List<NetworkLevel>`
Auth	Bearer token of an **approved partner**

Response 200 — NetworkLevel[]

```
[
  {
    "level": 1,
    "membersCount": 6
  },
  {
    "level": 2,
    "membersCount": 9
  },
  {
    "level": 3,
    "membersCount": 4
  }
]
```

Response fields — `NetworkLevel`

Field	Kotlin type	Meaning
`level`	Int	1, 2 or 3
`membersCount`	Int	Members at that level

Errors (besides the common ones)

Status	Code	Message
403	`PARTNER_NOT_APPROVED`	Partner approval is required

`GET` `/api/v1/agent/network/tree`

Referral tree (3 levels).

Item	Value
Kotlin	`AgentApi.getReferralTree()` → `TreeNode`
Auth	Bearer token of an **approved partner**

Response 200 — TreeNode


```
{
  "id": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
  "name": "Asha Patil",
  "subtitle": "Code P7KQ2XM",
  "badgeText": "You",
  "level": 0,
  "children": [
    {
      "id": "9a2b3c4d-5e6f-4a7b-8c9d-0e1f2a3b4c5d",
      "name": "Vikram",
      "subtitle": "Left leg · Joined 22 Oct 2026",
      "badgeText": "Booked",
      "level": 1,
      "children": []
    }
  ]
}
```


Response fields — `TreeNode`

Field	Kotlin type	Meaning
`id`	String	User ID
`name`	String	Name
`subtitle`	String	Leg and join date
`badgeText`	String	You, Booked, Partner, Customer
`level`	Int	0 = you, 1–3 below
`children`	List	Next level down

Errors (besides the common ones)

Status	Code	Message
403	`PARTNER_NOT_APPROVED`	Partner approval is required

`GET` `/api/v1/agent/commissions`

Commission list. Commission and matching entries, newest first; reversals show negative amounts.

Item	Value
Kotlin	`AgentApi.getCommissions()` → `List<CommissionItem>`
Auth	Bearer token of an **approved partner**

Response 200 — CommissionItem[]


```
[
  {
    "id": "e9f8a7b6-c5d4-4e3f-8a2b-1c0d9e8f7a66",
    "title": "Level 1 commission",
    "source": "BK-2026-000123 · Plot P-001 · Gold",
    "levelRate": "20%",
    "gross": "₹60,000",
    "adminDeduction": "₹12,000",
    "tdsDeduction": "₹3,000",
    "net": "₹45,000",
    "statusBadge": "Approved"
  }
]
```


Response fields — `CommissionItem`

Field	Kotlin type	Meaning
`id`	String	Ledger entry ID
`title`	String	e.g. "Level 1 commission" or "Matching bonus"
`source`	String	Booking, plot and plan it came from
`levelRate`	String	e.g. "20%"
`gross`	String	Gross amount
`adminDeduction`	String	20% admin
`tdsDeduction`	String	5% TDS
`net`	String	Net payable (negative for reversals)
`statusBadge`	String	Pending, Eligible, Approved, Paid, On hold, Reversed

Errors (besides the common ones)

Status	Code	Message
403	`PARTNER_NOT_APPROVED`	Partner approval is required

`GET` `/api/v1/agent/commissions/{id}`

Commission details.

Item	Value
Kotlin	`AgentApi.getCommissionById(id)` → `CommissionItem`
Auth	Bearer token of an **approved partner**

Path parameter	Description
`id`	ID from the list

Response 200 — CommissionItem

```
{
  "id": "e9f8a7b6-c5d4-4e3f-8a2b-1c0d9e8f7a66",
  "title": "Level 1 commission",
  "source": "BK-2026-000123 · Plot P-001 · Gold",
  "levelRate": "20%",
  "gross": "₹60,000",
  "adminDeduction": "₹12,000",
  "tdsDeduction": "₹3,000",
  "net": "₹45,000",
  "statusBadge": "Approved"
}
```

Response fields — `CommissionItem`

Field	Kotlin type	Meaning
`id`	String	Ledger entry ID
`title`	String	e.g. "Level 1 commission" or "Matching bonus"
`source`	String	Booking, plot and plan it came from
`levelRate`	String	e.g. "20%"
`gross`	String	Gross amount
`adminDeduction`	String	20% admin
`tdsDeduction`	String	5% TDS
`net`	String	Net payable (negative for reversals)
`statusBadge`	String	Pending, Eligible, Approved, Paid, On hold, Reversed

Errors (besides the common ones)

Status	Code	Message
404	`NOT_FOUND`	Commission not found

GET `/api/v1/agent/matching/summary`

70:30 matching.

Item	Value
Kotlin	`AgentApi.getMatchingSummary()` → `MatchingSummary`
Auth	Bearer token of an **approved partner**

Response 200 — MatchingSummary

```
{
  "powerLeg": "₹3,00,000 (Left)",
  "weakerLeg": "₹71,000 (Right)",
  "matchedVolume": "₹10,000",
  "matchedVolShort": "₹10K",
  "gross50": "₹5,000",
  "admin20": "₹1,000",
  "net": "₹3,750"
}
```

Response fields — `MatchingSummary`

Field	Kotlin type	Meaning
`powerLeg`	String	Bigger leg volume, e.g. "₹3,00,000 (Left)"
`weakerLeg`	String	Smaller leg volume
`matchedVolume`	String	Total matched
`matchedVolShort`	String	Short form, e.g. "₹10K"
`gross50`	String	Bonus gross (50% of matched)
`admin20`	String	20% admin deduction
`net`	String	Net bonus

Errors (besides the common ones)

Status	Code	Message
403	`PARTNER_NOT_APPROVED`	Partner approval is required

GET `/api/v1/agent/payouts/info`

Payout info.

Item	Value
Kotlin	`AgentApi.getPayoutInfo()` → `PayoutInfo`
Auth	Bearer token of an **approved partner**

Response 200 — PayoutInfo

```
{
  "bankName": "HDFC ****9012",
  "isVerified": true,
  "nextPayoutAmount": "₹45,000",
  "scheduledDate": "After admin approval"
}
```

Response fields — `PayoutInfo`

Field	Kotlin type	Meaning
`bankName`	String	Masked bank, empty if none
`isVerified`	Boolean	Bank registered for payouts
`nextPayoutAmount`	String	Approved amount waiting
`scheduledDate`	String	When payouts run

Errors (besides the common ones)

Status	Code	Message
403	`PARTNER_NOT_APPROVED`	Partner approval is required

GET `/api/v1/agent/notifications`

Partner notifications.

Item	Value
Kotlin	`AgentApi.getNotifications()` → `List<AgentNotification>`
Auth	Bearer token

Response 200 — AgentNotification[]

```
[
  {
    "id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c55",
    "title": "Commission earned",
    "timeAgo": "5m ago",
    "type": "COMMISSION"
  }
]
```

Response fields — `AgentNotification`

Field	Kotlin type	Meaning
`id`	String	Notification ID
`title`	String	Text
`timeAgo`	String	e.g. "5m ago"

Field	Kotlin type	Meaning
`type`	String	BOOKING, COMMISSION, PAYOUT, ACCOUNT…

Admin

ADMIN accounts only (`403 FORBIDDEN` otherwise). Every action is written to the audit log.

GET `/api/v1/admin/dashboard/stats`

Admin overview.

Item	Value
Kotlin	`AdminApi.getOverviewStats()` → `AdminOverviewStats`
Auth	Bearer token of an **ADMIN** account

Response 200 — AdminOverviewStats

```
{
  "totalPlots": 315,
  "plotsSold": 3,
  "plotsAvailable": 311,
  "activePartners": 14,
  "pendingApprovals": 2,
  "totalRevenue": "₹9,21,000",
  "pendingPayouts": "₹45,000"
}
```

Response fields — `AdminOverviewStats`

Field	Kotlin type	Meaning
`totalPlots`	Int	All plots
`plotsSold`	Int	Booked
`plotsAvailable`	Int	Available
`activePartners`	Int	Approved partners
`pendingApprovals`	Int	Partner applications waiting
`totalRevenue`	String	Verified payments
`pendingPayouts`	String	Approved commission not yet paid

GET `/api/v1/admin/plots`

Admin plot list.

Item	Value
Kotlin	`Endpoints.ADMIN_PLOTS` → `List<Plot>`
Auth	Bearer token of an **ADMIN** account

Response 200 — Plot[]


```
[
  {
    "id": "3b8e6d1a-2c4f-4e9b-a1d7-5f0c8e2b9a33",
    "title": "Plot P-001",
    "block": "A",
    "facing": "East",
    "location": "315 PLOTS",
    "sizeSqFt": "1,200 sq ft",
    "pricePerSqFt": "₹4,167/sq ft",
    "roadWidth": "30 ft",
    "totalPriceFormatted": "₹50,00,000",
    "status": "AVAILABLE",
    "imageUrl": "https://images.unsplash.com/photo-1600585154340-be6161a56a0c",
    "latitude": 18.52,
    "longitude": 73.85,
    "mapOffsetX": 0.0333,
    "mapOffsetY": 0.0238
  }
]
```


Response fields — `Plot`

Field	Kotlin type	Meaning
`id`	String	Plot ID (UUID)
`title`	String	e.g. "Plot P-001"
`block`	String	Block / sector, may be empty
`facing`	String	Facing direction, may be empty
`location`	String	Project or plot location
`sizeSqFt`	String	e.g. "1,200 sq ft"
`pricePerSqFt`	String	e.g. "₹4,167/sq ft"
`roadWidth`	String	e.g. "30 ft"
`totalPriceFormatted`	String	e.g. "₹50,00,000"
`status`	PlotStatus	`AVAILABLE` (bookable), `BOOKED`, `ON_HOLD` (someone is paying, or blocked)
`imageUrl`	String	Image to show
`latitude`	Double	Map latitude (0 if not set)
`longitude`	Double	Map longitude
`mapOffsetX`	Float	0–1 horizontal position on the site map
`mapOffsetY`	Float	0–1 vertical position on the site map

GET `/api/v1/admin/approvals`

Pending partner approvals. type PARTNER_KYC; id is the user ID.

Item	Value
Kotlin	`AdminApi.getApprovals()` → `List<AdminApprovalItem>`
Auth	Bearer token of an **ADMIN** account

Response 200 — AdminApprovalItem[]

```
[
  {
    "id": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
    "type": "PARTNER_KYC",
    "title": "Asha Patil",
    "subtitle": "9876543210 · referred by Vikram",
    "status": "Pending",
    "submittedAt": "2h ago"
  }
]
```

Response fields — `AdminApprovalItem`

Field	Kotlin type	Meaning
`id`	String	Applicant's user ID (use for approve/reject)
`type`	ApprovalType	`PARTNER_KYC`
`title`	String	Applicant name
`subtitle`	String	Mobile and referrer
`status`	String	"Pending"
`submittedAt`	String	e.g. "2h ago"

POST `/api/v1/admin/approvals/{id}/approve`

Approve partner. Creates the referral code, registers submitted bank details for payouts, notifies the user.

Item	Value
Kotlin	`AdminApi.approveItem(id)` → `result`
Auth	Bearer token of an **ADMIN** account

Path parameter	Description
`id`	Applicant's user ID

Response 200 — Approved

```
{
  "success": true,
  "partnerStatus": "APPROVED",
  "referralCode": "P7KQ2XM"
}
```

Errors (besides the common ones)

Status	Code	Message
404	`NOT_FOUND`	User not found
409	`INVALID_STATE`	Cannot approve a APPROVED partner

POST `/api/v1/admin/approvals/{id}/reject`

Reject partner.

Item	Value
Kotlin	`AdminApi.rejectItem(id)` → `result`
Auth	Bearer token of an **ADMIN** account

Path parameter	Description
`id`	Applicant's user ID

Response 200 — Rejected

```
{
  "success": true,
  "partnerStatus": "REJECTED",
  "referralCode": null
}
```

Errors (besides the common ones)

Status	Code	Message
404	`NOT_FOUND`	User not found
409	`INVALID_STATE`	Cannot reject a APPROVED partner

GET `/api/v1/admin/activity-logs`

Admin activity log.

Item	Value
Kotlin	`AdminApi.getActivityLogs()` → `List<AdminActivityLog>`
Auth	Bearer token of an **ADMIN** account

Response 200 — AdminActivityLog[]

```
[
  {
    "id": "1042",
    "title": "Partner approve",
    "description": "Admin · user 6f1c2a8e",
    "timeAgo": "5m ago"
  }
]
```

Response fields — `AdminActivityLog`

Field	Kotlin type	Meaning
`id`	String	Log ID
`title`	String	Action, e.g. "Partner approve"
`description`	String	Who and what
`timeAgo`	String	When

GET `/api/v1/admin/payouts`

Payout requests. id "pending:" = approved commission waiting to be paid (process it); other ids are payouts already sent.

Item	Value
Kotlin	`AdminApi.getPayoutRequests()` → `List<AdminPayoutRequest>`
Auth	Bearer token of an **ADMIN** account

Response 200 — AdminPayoutRequest[]

```
[
  {
    "id": "pending:6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
    "agentName": "Asha Patil",
    "agentCode": "P7KQ2XM",
    "amount": "₹45,000",
    "bankDetails": "HDFC0001234 · ****9012",
    "period": "Due now",
    "status": "Pending"
  }
]
```

Response fields — `AdminPayoutRequest`

Field	Kotlin type	Meaning
`id`	String	"pending:" = due (process it); else a payout already sent
`agentName`	String	Partner
`agentCode`	String	Referral code

Field	Kotlin type	Meaning
`amount`	String	Amount
`bankDetails`	String	Masked bank or "Bank details missing"
`period`	String	"Due now" or the payout date
`status`	String	Pending, Requested, Processing, Paid, Failed

POST `/api/v1/admin/payouts/{id}/process`

Send a payout. Pays a pending request through Cashfree.

Item	Value
Kotlin	`AdminApi.processPayout(id)` → `result`
Auth	Bearer token of an **ADMIN** account

Path parameter	Description
`id`	Payout request ID from the list ("pending:")

Response 200 — Batch result

```
{
  "success": true,
  "created": 1,
  "results": [
    {
      "userId": "6f1c2a8e-4b7d-4f0a-9a3c-2d5e8b1f0a11",
      "payoutRef": "PO-2026-000210",
      "amountPaise": 4500000,
      "status": "PROCESSING"
    }
  ]
}
```

Errors (besides the common ones)

Status	Code	Message
400	`NOTHING_TO_PAY`	No approved amount above the minimum, or bank details are missing
409	`ALREADY_PROCESSED`	This payout was already sent