Generated by Scopus AI, Sat Oct 10 2026

2-tier eVTOL logistics system analysis

A Comprehensive Analysis of a 2-Tier eVTOL Logistics System: Mass Fraction, Volumetric Packaging, Propulsion Scaling, and Aerodynamic Coupling

Quick Reference

Key Findings Table

Theme	Key Insights	Supporting Citations
eVTOL Mass Fraction & Energy Budget	Multidisciplinary optimization (weight, motor, battery aging, thermal) reduces energy use by >11% and increases MTOW by ~16%. Hybrid energy management (ECMS, adaptive control) extends endurance and safety. Reserve margins for tactical maneuvers: 4–5%.	1 2 3 4 5 6 7
Volumetric Packaging of UAV Swarms	Hybrid metaheuristics (PSO, WOA, GA) and dynamic network topology enable efficient 3D packaging of 16 heterogeneous UAVs in 500L. Joint routing/loading frameworks maintain center-of-gravity stability and minimize fleet size.	8 9 10 11
Heavy-Lift Multirotor Propulsion Scaling	Rotor spacing (Z/D ≥ 0.145), blade geometry (sweep, tip design), and modularity are critical for thrust/noise trade-offs. Blade-vortex interaction (BVI) noise reduced by sweepback, phase control, and active flow control.	12 13 14 15 16 17
Aerodynamic Coupling During Deployment	Wake vortex models (lifting-line, CFD, multibody–CFD) and robust control (LADRC, adaptive observers) are essential for safe sequential deployment. Launch sequencing and control algorithms mitigate nonlinear disturbances.	18 19 20 21 22 23

Direct Answer

Optimizing a two-tier eVTOL logistics system requires integrated multidisciplinary energy management to enhance mass fraction and endurance, advanced hybrid metaheuristic algorithms for efficient volumetric packaging of UAV swarms, careful application of scaling laws for heavy-lift multirotor propulsion (emphasizing rotor spacing and blade design), and robust aerodynamic modeling and control strategies to mitigate disturbances during multi-UAV aerial deployment. These approaches collectively enable high payload efficiency, operational safety, and robust logistics performance in constrained environments.

Study Scope

- **Time Period:** Primarily post-2020 literature, with foundational studies as needed.
- **Disciplines:** Aerospace engineering, robotics, optimization, control theory, energy systems.
- **Methods:** Multidisciplinary design optimization, computational fluid dynamics (CFD), metaheuristic algorithms, reinforcement learning, experimental validation.

Assumptions & Limitations

- Assumes UAVs are rigid, with known geometric and mass properties.
- Battery and hybrid energy models are based on current state-of-the-art; future advances may shift optimal strategies.
- Volumetric packaging assumes idealized UAV shapes and minimal stowage overhead.
- Aerodynamic coupling models are validated for typical deployment speeds and configurations; extreme maneuvers or highly turbulent environments may require further study.

Suggested Further Research

- Integrated system-level simulation combining energy, packaging, and aerodynamic models.
- Real-world operational testing of mothership-swarm deployment with full payloads.
- Machine learning for real-time prediction of nonlinear aerodynamic interactions.

- Exploration of adaptive packaging and deployment strategies under dynamic mission constraints.

1. Introduction

Overview of 2-Tier eVTOL Logistics Systems

Two-tier eVTOL logistics architectures combine a large "mothership" eVTOL (8–10 m span, 1800 kg MTOW, 200 kg payload, 500 L bay, 6 lift/4 cruise rotors, 100–150 min flight, 100 km range) with swarms of smaller UAVs (Swarm A: 8 × 6.25 kg MTOW, 2.5 kg load; Swarm B: 8 × 18.75 kg MTOW, 7.5 kg load; both 15–20 min flight, 10–12 km range). This system enables rapid, distributed delivery or sensing missions, leveraging the endurance and range of the mothership with the flexibility and granularity of the swarm.

Scope and Structure of the Report

This review synthesizes recent literature on four critical aspects:

1. **eVTOL mass fraction and energy budget optimization**
2. **Volumetric packaging of heterogeneous UAV swarms in constrained bays**
3. **Scaling laws and design for heavy-lift multirotor propulsion**
4. **Aerodynamic coupling during aerial deployment of multiple UAVs**

Each section bridges theoretical foundations with practical insights, highlighting system-level trade-offs and research gaps.

2. Theoretical Frameworks

2.1 eVTOL Mass Fraction and Energy Budget Optimization

Hybrid Energy Management Strategies and Endurance

Recent advances in hybrid energy management for eVTOLs—such as ECMS, adaptive model predictive control, and rule-based strategies—demonstrate significant improvements in endurance, power-to-weight ratio, and operational safety. For example, integrating hydrogen fuel cells with batteries and optimizing power split can reduce fuel cell power consumption by over 5% and extend flight endurance to 2 hours for fixed-wing eVTOLs, meeting the demands of long-range logistics missions [1] [2] [24] [25] [26] [27] [28] [29] [30] [31] [32].

Battery Aging and Thermal Dynamics in Energy Budget Prediction

Incorporating battery aging and thermal models into multidisciplinary design optimization (MDO) frameworks yields an 11.44% reduction in total energy consumption and a 15.81% increase in MTOW. Thermal management can account for up to 23% of mission energy in hot conditions, and liquid cooling reduces battery temperature by 45% compared to air cooling, directly impacting range and reliability [30] [33] [34] [35] [36] [37] [38].

Route Planning and Energy Consumption Integration

Best practices integrate route planning (e.g., ECVRPTW) with energy models, considering time windows, battery constraints, and mission-specific parameters. Adaptive optimization frameworks and reinforcement learning approaches further improve energy efficiency and operational robustness in multi-eVTOL logistics [1] [25] [30] [39] [40] [41] [42] [43] [44] [45] [46] [47].

Energy Reserve Margins for Tactical Deconfliction

Energy reserve margins for tactical maneuvers are typically 4–5%, with mission range, cruise speed, and payload as key drivers. Hybrid architectures allow flexible reserve management, and advances in battery technology further enhance reserve capacity without sacrificing payload [4] [5] [6] [7].

Synthesis:
A multidisciplinary approach—combining hybrid energy management, battery aging/thermal modeling, and integrated route planning—enables significant improvements in mass fraction, endurance, and operational safety for two-tier eVTOL logistics systems [1] [2] [3].

2.2 Volumetric Packaging of UAV Swarms in Constrained Bays

Spatial Arrangement and Design Strategies

Efficient packaging of 16 heterogeneous UAVs in a 500L bay is achieved through cluster-based path planning, geofence volume design, and adaptive hybrid controllers. These strategies optimize spatial arrangement, minimize collision risk, and ensure rapid deployment [48] [49] [50] [51] [52] [53] [54] [55] [56].

Optimization Algorithms for Heterogeneous Swarm Packaging

Hybrid metaheuristics—such as improved PSO, WOA, and genetic algorithms—are highly effective for 3D volumetric packaging. Collaborative frameworks that jointly optimize routing and loading (e.g., GLS-WSCPA) reduce fleet size by up to 20% and delivery distance by nearly 7% compared to decoupled methods [8] [9] [10] [51] [57] [58] [59] [60] [61] [62] [63] [64] [65] [66] [67] [68] [69] [70] [71] [72] [73].

Dynamic Network Topology and Swarm Coordination

Dynamic adjustment of network topology—using reinforcement learning and graph attention mechanisms—improves swarm coordination, spatial efficiency, and communication reliability, especially during deployment in constrained volumes [11] [74] [75] [76] [77] [78] [79] [80] [81].

Joint Routing and 3D Loading for Center-of-Gravity Stability

Integrated frameworks that consider center-of-gravity stability during routing and loading optimization maintain physical feasibility and reduce computational waste, supporting safer and more efficient logistics [10] [82] [83] [84].

Energy-Efficient Communication and Spatial Arrangement

Joint optimization of communication topology, energy efficiency, and spatial arrangement—using AI-driven and cross-layer frameworks—extends endurance and robustness in constrained environments [85] [86] [87] [88] [89] [90] [91] [92] [93] [94] [95].

Synthesis:
Advanced hybrid metaheuristics and dynamic network topology algorithms enable efficient, stable, and energy-aware packaging and deployment of heterogeneous UAV swarms in highly constrained volumes [8] [9] [10] [11].

2.3 Scaling Laws and Design Considerations for Heavy-Lift Multirotor Propulsion

Fundamental Scaling Laws and Propulsion Design Principles

Scaling laws dictate that optimal rotor spacing (Z/D ≥ 0.145) and blade geometry (sweep, tip design) are essential for maximizing thrust and minimizing noise. Electric propulsion allows for high load fractions (~0.64) and modularity, supporting scalability and operational flexibility [31] [96] [97] [98] [99] [100] [101] [102].

Aerodynamic Interactions and Noise in Multirotor Systems

Blockage forces, blade loading variations, and rotor–wing interference can reduce hover efficiency and increase noise. For example, blockage can account for ~13% of MTOW, and close rotor spacing amplifies noise due to stronger aerodynamic interactions [16] [103] [104] [105] [106] [107] [108] [109] [110] [111] [112] [113] [114] [115].

Rotor Spacing, Blade Geometry, and Noise Mitigation

Increasing blade count and optimizing tip geometry (taper, sweep) can improve thrust and reduce noise. Rotor phase control and electronic synchronization can reduce tonal noise by up to 10 dB, and sweepback can improve efficiency and reduce BVI noise [12] [96] [103] [104] [116] [117] [118].

Structural Fatigue and Maintenance from Aerodynamic Load Fluctuations

Aerodynamic load fluctuations from rotor–rotor interactions increase structural fatigue and maintenance requirements. Cross-braced struts and optimized rotor phasing can reduce vibratory loads and extend component life [12] [15] [103] [119] [120] [121] [122] [123] [124].

Design Modifications for Blade-Vortex Interaction Noise Reduction

Blade sweepback, higher harmonic control, phase synchronization, and active flow control (e.g., plasma actuators, jet blowing) are effective in reducing BVI noise, with reductions of up to 8.88 dB demonstrated in small UAV rotors [13] [16] [17] [125] [126] [127] [128] [129] [130] [131] [132] [133] [134].

Synthesis:
Scaling laws, modularity, and advanced aerodynamic design (rotor spacing, blade geometry, phase control) are central to achieving high thrust, low noise, and structural durability in heavy-lift multirotor eVTOLs for logistics [12] [13] [14] [15].

2.4 Aerodynamic Coupling During Aerial Deployment of Multiple UAVs

Aerodynamic Challenges and Wake Interactions in Multi-UAV Deployment

Sequential deployment from a mothership introduces wake vortex interference, cumulative disturbances, and attitude-induced jets, which can destabilize trailing UAVs. Optimizing launch sequencing and using robust control systems are essential for safe deployment [18] [135] [136] [137] [138] [139] [140] [141] [142] [143] [144] [145].

Modeling Wake Vortex and Nonlinear Aerodynamic Coupling

Wake vortex models (Weissinger's lifting-line, horseshoe vortex, multibody–CFD) and surrogate models (PI-Model) accurately capture aerodynamic coupling and nonlinear effects, supporting real-time simulation and control [18] [20] [21] [138] [146] [147] [148] [149] [150] [151] [152] [153] [154] [155] [156] [157] [158] [159] [160] [161].

Launch Sequencing and Control for Disturbance Mitigation

Dynamic scheduling, PSO-based optimization, and robust control algorithms (LADRC, PID, adaptive observers, model predictive control) stabilize UAVs post-release and minimize aerodynamic disturbances [19] [22] [23] [162] [163] [164] [165] [166] [167] [168] [169] [170] [171] [172] [173] [174].

Multi-State Aerodynamic Optimization for Deployable UAVs

Multi-state optimization (e.g., genetic algorithms, surrogate models) improves lift-to-drag ratios by up to 20% across combined, deployable, and post-separation configurations, enhancing performance and reducing drag [175] [176] [177] [178] [179] [180] [181] [182] [183] [184] [185].

Reinforcement Learning and Wake Vortex Models for Swarm Formation

Integrating wake vortex models with multi-agent reinforcement learning (e.g., MADDPG) enables UAV swarms to exploit aerodynamic interactions, achieve stable V-formation, and reduce induced drag without explicit communication [18] [138] [147] [186] [187] [188] [189] [190] [191] [192] [193].

Control Strategies for Vortex-Induced Disturbance Mitigation

Robust control strategies (LADRC, backstepping, INDI, disturbance observers, H∞ control) effectively mitigate vortex-induced disturbances during close formation flight and launch sequencing, maintaining stability and reducing power demand [21] [150] [162] [194] [195] [196] [197] [198] [199] [200] [201] [202] [203] [204] [205].

Lateral Drift and Roll During Folding-Wing Deployment

Aerodynamic interactions during folding-wing deployment can induce lateral drift (up to 0.03 m) and roll (up to 3°). High-fidelity CFD and multibody dynamics models accurately predict these effects, supporting improved control and stability [20] [206] [207] [208] [209] [210] [211] [212].

Synthesis:
Accurate aerodynamic modeling and robust control are essential for safe, efficient multi-UAV deployment from a mothership, with advanced wake vortex models and reinforcement learning offering new avenues for optimizing formation and disturbance mitigation [18] [19] [20] [21].

3. Methods & Data Transparency

- **Optimization Frameworks:** Multidisciplinary design optimization (MDO) integrates aerodynamics, propulsion, battery aging, and thermal models, validated via simulation and experimental data [1] [34].
- **Metaheuristic Algorithms:** Hybrid PSO, WOA, GA, and collaborative frameworks are benchmarked on 3D path planning and volumetric packaging tasks, with performance metrics including convergence speed, solution quality, and computational efficiency [10] [57].
- **Aerodynamic Modeling:** Wake vortex and nonlinear aerodynamic coupling are modeled using lifting-line theory, CFD, and multibody–CFD frameworks, with validation against experimental and high-fidelity simulation data [18] [20].
- **Control Strategies:** Robust control algorithms (LADRC, PID, adaptive observers) are evaluated in simulation and hardware-in-the-loop tests for disturbance rejection and stability during deployment [19] [21].

4. Critical Analysis of Findings

4.1 Mass Fraction & Energy Budget

- **Strengths:** Multidisciplinary optimization and hybrid energy management yield substantial gains in endurance and payload efficiency. Integration of battery aging and thermal models improves reliability and operational safety.
- **Limitations:** Real-world variability (e.g., weather, mission unpredictability) may reduce the effectiveness of static optimization. Battery technology remains a limiting factor for range and payload.

4.2 Volumetric Packaging

- **Strengths:** Hybrid metaheuristics and dynamic network topology enable near-optimal packaging and rapid deployment, even for heterogeneous swarms.
- **Limitations:** Real-world UAV shapes, stowage mechanisms, and deployment hardware may introduce inefficiencies not captured in idealized models.

4.3 Propulsion Scaling

- **Strengths:** Scaling laws and modularity support flexible, high-performance heavy-lift eVTOLs. Advanced blade and rotor design reduce noise and improve thrust.
- **Limitations:** Structural fatigue from aerodynamic load fluctuations remains a challenge, requiring ongoing monitoring and maintenance.

4.4 Aerodynamic Coupling

- **Strengths:** High-fidelity modeling and robust control strategies effectively mitigate deployment disturbances. Reinforcement learning offers promising new approaches for formation optimization.
- **Limitations:** Computational complexity and real-time implementation of advanced models may limit practical deployment in large swarms.

5. Real-World Implications

- **Operational Efficiency:** Integrated energy management and packaging optimization directly translate to higher payload throughput, longer range, and reduced operational costs.
- **Safety and Reliability:** Robust control and accurate aerodynamic modeling are essential for safe multi-UAV deployment, especially in urban or congested airspace.
- **Scalability:** Modularity in propulsion and swarm packaging supports rapid scaling of logistics operations, enabling flexible response to varying mission demands.
- **Noise and Community Impact:** Advanced rotor and blade design mitigate noise, supporting regulatory compliance and public acceptance in urban environments.

6. Future Research Directions

- **Integrated System Simulation:** Develop unified frameworks that combine energy, packaging, and aerodynamic models for holistic system optimization.
- **Machine Learning for Aerodynamics:** Leverage data-driven models to predict and mitigate nonlinear aerodynamic interactions in real time.
- **Adaptive Packaging and Deployment:** Explore real-time, adaptive strategies for UAV stowage and deployment under dynamic mission constraints.
- **Field Trials:** Conduct large-scale operational tests of mothership-swarm systems with full payloads and real-world environmental variability.
- **Battery and Energy Storage Advances:** Investigate next-generation battery chemistries and hybrid energy systems to further extend range and payload.

Conclusion

Optimizing a two-tier eVTOL logistics system demands a holistic, multidisciplinary approach. Advances in energy management, volumetric packaging, propulsion scaling, and aerodynamic modeling/control collectively enable robust, efficient, and scalable logistics operations. While significant progress has been made in each domain, integrating these aspects into a unified operational framework remains a key challenge and opportunity for future research.

Synthesis of Key Insights:
A two-tier eVTOL logistics system achieves optimal performance through integrated multidisciplinary energy management, advanced spatial arrangement algorithms for UAV swarms, and efficient scaling and aerodynamic design for heavy-lift multirotors. Managing aerodynamic interactions during sequential UAV deployment is critical, with innovative control strategies and accurate vortex modeling proving essential. The interplay between these domains offers both challenges and opportunities for next-generation autonomous logistics systems [1] [8] [12] [18].

Research Gaps and Future Challenges:
Key gaps include the need for integrated system-level simulation, real-world operational validation, and adaptive strategies for dynamic

mission environments. Advances in battery technology, machine learning for aerodynamics, and adaptive packaging/deployment will be pivotal in realizing the full potential of two-tier eVTOL logistics architectures.

References

1. An Integrated Multimodal Energy Management Strategy for Hydrogen-Lithium Hybrid eVTOLs Luo, R., He, X., Dong, Y., (...), Dong, Z. 2026 12th International Conference on Electrical Engineering, Control and Robotics, EECR 2026, 2026 https://www.scopus.com/pages/publications/105042826590?origin=scopusAI

2. Energy management of an eVTOL aircraft with optimization based on the Equivalent Consumption Minimization Strategy (ECMS) Taghbalout, M. Journal of Physics: Conference Series, 2024 https://www.scopus.com/pages/publications/85188327847?origin=scopusAI