2-tier eVTOL logistics system design

"workflow,design,develop,a 2-tier eVTOL logistics system. Mothership: 8-10m span, 1800kg MTOW, 200kg payload, 500L bay, 6 lift/4 cruise rotors, 100-150min flight, 100km range. Swarm A (x8): 6.25kg MTOW, 2.5kg load. Swarm B (x8)18.75kg MTOW, 7.5kg load. Both swarms: 15-20min flight, 10-12km range. Synthesize literature on: 1) eVTOL mass fraction & energy budget; 2) Volumetric packaging of 16 UAVs in 500L 3) Heavy-lift multirotor propulsion scaling; 4) Aerodynamic coupling during aerial deployment." *Generated by LeapSpace*

Two-Tier eVTOL Logistics System at a Glance

Key Findings Table

Topic	Key finding	Implication for proposed system	Population / context	Citations
Mothership energy budget	Hover, transition, and climb are the dominant power/energy drivers; transition can reach extreme peak power, and climb energy can approach cruise energy despite shorter duration.	The 1800 kg mothership should be sized around vertical-flight peaks and reserve policy, not cruise alone.	Quantitative eVTOL mission studies	[1] [2] [3]
Reserve sensitivity	A 10 min hover contingency can cut range by up to 75%, and 20 m/s headwind can cut range by 71%.	A 100-150 min / 100 km target is highly sensitive to reserve rules, weather, and deployment loiter.	Range sensitivity analyses	[4]
Mass fractions	Battery and propulsion fractions are very high in electric VTOL concepts; battery+motor can approach ~50% of MTOW in one rotorcraft case, and battery fraction can rise toward ~63% near 2000 kg MTOM in one hybrid-electric sizing study.	The mothership architecture must aggressively reduce pure-hover burden and avoid overgrowth in installed propulsion mass.	eVTOL-like and hybrid-electric aircraft sizing studies	[5] [6] [7] [8] [9]
Thermal loads	Thermal management can consume nearly 23% of mission energy in summer, with hover TMS power briefly above 40 kW.	Thermal system mass and energy should be modeled explicitly in the mothership budget.	Battery-electric aircraft mission analysis	[10]
Packaging evidence	Published literature provides folding, modularity, and general 3D packing constraints, but no direct 500 L fixed-bay precedent for 16 UAVs with deployment clearance.	Packaging is a first-order design risk and must be resolved with CAD-first geometry closure.	UAV carriage, packing, and deployable systems studies	[11] [12] [13] [14] [15] [16]
Stowage concepts	Wing folding, rotor nesting, inflatable wings, and perching/gear-elimination concepts can materially reduce stowed volume.	Child UAVs should be designed around bay-driven folded envelopes, not only flight-optimal geometry.	Air-launched/foldable UAV studies	[14] [15] [17] [18]

Topic	Key finding	Implication for proposed system	Population / context	Citations
Heavy-lift propulsion scaling	MTOW correlates strongly with rotor diameter, battery mass/capacity, endurance, and range; apparent electric-endurance limit in compiled data is near 120 min and 70 km.	The mothership target is near observed electric limits and needs careful disk-loading and battery-mass trade studies.	Unmanned rotorcraft scaling dataset	[19]
Rotor interference	Close spacing and coaxial/tandem interactions reduce thrust efficiency and create asymmetric loading.	The 6-lift/4-cruise arrangement requires interference-aware spacing and control-law design.	Rotor interaction experiments and models	[20] [21] [22] [23] [24]
DEP trade-off	More propulsors can improve low-speed lift and controllability, but not necessarily isolated propulsive efficiency.	Propulsor count should be optimized jointly for control authority, packaging, and interference losses.	DEP/STOL and rotor-interference studies	[25] [26] [27] [28]
Aerial deployment	Safe release depends on relative velocity, clearance, transient interference, and immediate post-release stabilization.	Release geometry, wake map, child startup sequence, and control architecture must be co-designed.	Separation and launch/recovery studies	[29] [30] [31] [32] [33] [34]
Safety envelopes	eVTOL downwash/outwash safety zones are increasingly CFD- and flight-test-validated; one framework supports a 150-ft minimum safety radius.	Deployment corridors should be treated like protected aerodynamic envelopes, not simple geometric exit paths.	Vertiport and rotorwash safety studies	[35] [36] [37] [38] [39]

Direct Answer

A literature-supported workflow for the proposed 2-tier logistics system is:

1. **Close the mothership mission energy model first**, with explicit segments for takeoff hover, climb, transition, cruise, descent, landing hover, deployment loiter, reserve, headwind, and thermal-management loads, because hover/transition peaks and reserve policy dominate feasibility more than nominal cruise does [1] [4] [10].
2. **Close mass fractions second**, especially battery, motors/propulsors, wiring, ESC-equivalents, mounts, and thermal-management mass, because electric VTOL feasibility is strongly constrained by battery and propulsion fractions [5] [6] [7] [8] [9].
3. **Make packaging a geometry-led design loop**, since the literature does not provide a validated precedent for fitting 8 small plus 8 medium UAVs inside 500 L with clearance paths; folding, rotor nesting, inflatable surfaces, and gear minimization are the main evidence-backed stowage levers [11] [13] [14] [15] [17] [18].
4. **Size heavy-lift propulsion with disk-loading and interaction penalties included**, because scaling evidence supports MTOW-based preliminary sizing, but close rotor spacing and distributed propulsion can degrade efficiency while improving control authority [19] [20] [25] [26] [40].

5. **Co-design deployment aerodynamics and control**, using CFD-informed wake maps, separation simulation, and immediate post-release stabilization, because release safety depends on transient interference and not just release mechanism geometry [29] [30] [32] [41] [42] [43].

Bottom line: the architecture is most plausible if the mothership minimizes pure-hover energy, the child UAVs are designed around folded bay envelopes, and deployment occurs in wing-borne or otherwise wake-managed conditions rather than long hover exposure [14] [17] [36] [44] [45] [46].

Confidence level: High - The workflow is directly supported by convergent findings across mission sizing, packaging, propulsion scaling, and deployment aerodynamics [16] [41] [47] [48].

Study Scope

- **Time span covered by retrieved studies:** primarily recent eVTOL/UAV design literature with some foundational sizing and deployment papers; the evidence includes conceptual sizing, parametric studies, wind-tunnel/bench experiments, CFD, and flight/launch-recovery demonstrations [47] [48] [49].
- **Disciplines covered:** aircraft sizing, electric propulsion integration, cargo/UAV logistics, geometric packing, rotor aerodynamics, and launch/recovery control [32] [47] [50] [51].
- **Methods represented:** mission-segment energy analysis, empirical scaling regressions, 3D packing constraints, experimental rotor coefficient measurement, CFD/wake analysis, and nonlinear control validation [1] [11] [22] [37] [49].

Assumptions & Limitations

- The supplied evidence **does not include** a single authoritative mass-fraction table for 1-3 tonne cargo eVTOLs with fully separated battery, propulsion, reserve, and thermal shares in one consistent mission model [2] [52] [53].
- The literature **does not provide** a documented 500 L packing case showing 16 UAVs, access paths, and clearance margins, so packaging conclusions are evidence-based but not directly validated for this exact bay [11] [13] [16].
- The findings **do not provide** a direct experiment matching a 6-lift/4-cruise 1800 kg mothership deploying powered child UAVs from its bay; deployment conclusions are therefore transferred from adjacent launch/recovery and interference studies [29] [31] [36].
- The requested **Class I versus Class II** regression distinction is mentioned in the broader topic framing but is not explicitly recoverable from the visible source content [19] [40] [54].

Suggested Further Research

- Build a **parametric CAD packing model** for 16 folded UAVs with CG, door sweep, and egress-clearance constraints [11] [16].
- Run a **segment-by-segment mothership energy model** including hover contingency, headwind, and thermal loads [4] [10].

- Perform **rotor-spacing and wake-interference trades** for the 6-lift/4-cruise layout before freezing airframe geometry [20] [24] [55].
- Develop a **wake map + release corridor** method for child launch under wing-borne and low-speed conditions [35] [36] [41].
- Compare a **pure-electric versus hover-burden-reduced architecture** to test whether lower vertical-energy concepts materially improve payload/range closure [44] [45].

Full Report

1. System Concept and Foundational Context

The proposed system is a **two-tier logistics architecture**: a large mothership eVTOL carries and deploys two child-UAV swarms, with the mothership providing long-haul transport and the swarms executing local delivery legs. This creates four tightly coupled design problems: mothership energy closure, child-UAV volumetric integration, propulsion scaling, and safe aerial deployment [33] [47] [48] [56].

The retrieved literature consistently implies that such systems cannot be designed vehicle-by-vehicle in isolation. Instead, useful concepts emerge only when **mission profile, mass fraction, packaging, propulsion interference, and deployment operations** are treated together [1] [50] [51] [57].

Foundational mechanisms

Three mechanisms matter most:

1. **Vertical-flight energy asymmetry.** Hover and transition impose the highest power demands, while cruise often dominates time but not peak sizing; this makes reserves and off-nominal conditions disproportionately important [1] [2] [58].
2. **Mass-fraction amplification.** Extra battery mass demands extra lift and propulsion, which then demands more battery and structure; this is especially punitive in electric VTOL configurations [5] [7] [8].
3. **Geometric and aerodynamic coupling.** Packaging multiple UAVs into a fixed bay changes child geometry, while compact propulsion layouts increase rotor interaction and complicate deployment through disturbed flow fields [12] [20] [46].

Taken together, these findings suggest that the proposed architecture should be treated as a **multifidelity co-design problem**: low-fidelity tools for initial sizing, CAD for packaging closure, and higher-fidelity aero/control models for deployment safety [16] [41] [42] [48].

Confidence level: High - Multiple source groups support the same systems-engineering framing [41] [47] [50] [51].

2. System Requirements and Architecture Implications

The mothership target is ambitious: **1800 kg MTOW, 200 kg payload, 500 L bay, 6 lift rotors, 4 cruise rotors, 100-150 min endurance, and 100 km range**. The child fleet totals **16 UAVs**, split into eight smaller and eight larger units, each with short-range last-mile missions. The proposed roles align with cooperative carrier-UAV logistics models, where a larger carrier improves network efficiency by moving smaller capacity-limited UAVs closer to demand nodes [56].

A direct system implication is that the mothership is not just carrying payload mass; it is carrying **deployable aircraft payload**, which is structurally, volumetrically, and operationally more demanding than freight boxes [13] [59]. The total child-UAV mass also reduces effective mothership payload allowance and competes directly with battery and propulsion mass fractions [7] [8].

A second implication is that the mothership endurance target sits close to apparent limits in the compiled electric multirotor/unmanned rotorcraft evidence, which suggests an electric endurance ceiling near **120 min** and range near **70 km** in one aggregated dataset [19]. This does not prove infeasibility, but it does mean the concept lies near a region where sizing assumptions become extremely sensitive [19] [60].

Confidence level: Medium-High - The architectural implications are direct, but exact feasibility for this geometry is not available in the evidence [19] [56].

3. eVTOL Mass Fraction and Mission Energy Budget

3.1 Mission energy structure

The literature is unusually consistent on mission structure: eVTOL analyses divide missions into takeoff/hover, climb, transition, cruise, descent, and landing hover, often with explicit reserve segments [2] [3] [52]. Hover and landing hover define peak discharge, while cruise defines longer-duration continuous discharge [2] [61].

Quantitatively, one mission study reported **980 kW instantaneous power in transition**, and climb energy comparable to cruise energy despite shorter duration [1]. This matters because the mothership's 6-lift/4-cruise architecture will likely see strong peak-power concentration in vertical and conversion phases, even if cruise appears benign in average-power terms [1] [58].

Reserve policy is a first-order driver. One study found that adding a **10 min hover contingency** can reduce range by up to **75%**, while a **20 m/s headwind** can reduce range by **71%** [4]. For a mothership that may need to wait for deployment or recovery, this is a critical warning: operational loiter in a hover-capable mode is extremely expensive [4].

Thermal management cannot be omitted. One battery-electric mission analysis found thermal-management energy reaching **nearly 23% of total mission energy** in summer, with TMS power briefly above **40 kW** in hover [10]. For the proposed vehicle, that means thermal loads should be treated as a genuine mission consumer, not a minor accessory load [10] [53].

3.2 Mass-fraction evidence

The evidence does not provide one clean cargo-eVTOL table, but the pattern is clear: electric VTOL aircraft carry very high battery and propulsion mass fractions [2] [52] [53]. Reported examples include batteries taking "almost half" of empty weight, a **37% empty-weight fraction excluding motors and battery** in one battery-electric study, and **battery+motor mass around 50% of MTOW** in one rotorcraft case [5] [6] [53]. A hybrid-electric sizing study reports maximum achievable battery mass fraction near **63% up to 2000 kg MTOM** [7].

Taken together, these findings suggest that the 1800 kg mothership will have little tolerance for overdesigned hover propulsion or undercounted systems mass [7] [8] [9]. This supports architectures that reduce vertical-energy burden or shrink pure-hover propulsion mass, rather than relying solely on better batteries [44] [45].

3.3 Payload-range implications

Comparative studies explain why lower-hover-energy concepts outperform pure eVTOL for a given payload-range requirement. One comparison found **eSTOL** can carry **1.8-2.6x** the payload of an equivalent eVTOL at the same speed and range because it requires less takeoff/landing energy and a smaller propulsion system [44]. Related hybrid VTOL and fuel-cell+battery studies report similar logic: when cruise power is far below hover power, shifting the hover burden away from the battery improves payload or endurance [45] [62] [63].

For the proposed system, the direct implication is not necessarily "switch configuration," but rather: **keep the mothership wing-borne whenever possible during deployment operations**, because added hover time is disproportionately punitive [4] [44].

Confidence level: High - The dominance of hover/transition/reserve effects is strongly evidenced across multiple studies [1] [4] [10].

4. Volumetric Packaging of 16 UAVs in a 500 L Bay

The packaging literature is the weakest area for direct precedent. The retrieved studies provide **constraints and enabling ideas**, but not a validated case of 16 UAVs in a 500 L mothership bay [11] [13] [16].

4.1 What the literature does support

The main evidence-backed compact-stowage levers are:

- **Wing folding** to meet stowed-width constraints; one air-launched UAV used spring-loaded swinging wings to satisfy a **610 mm** stowed-width requirement [14].
- **Folding-axis optimization**, since wing-fold location affects both folded geometry and wing mass increase [15].
- **Rotor nesting / coaxial compacting**, where sphere-inner-volume constraints and overlap/clearance tradeoffs shape fold volume [12].
- **Inflatable wings**, which can enable tight packaging with rapid deployment [17].
- **Landing-gear elimination via perching concepts**, which can reduce dead volume in small UAVs [18].

These studies support a practical design rule: the child UAVs should be **bay-driven first**, with allowable folded bounding boxes derived from the mothership volume before detailed airframe optimization [14] [15] [17].

4.2 What the literature does not support directly

The strongest directly relevant packing paper frames the problem as **3D bin packing** under volume, load, stacking pressure, centroid, top-clearance, and orientation constraints, but it does not provide a specific 500 L UAV-bay layout [11]. Another payload-compartment paper argues that internal layout should be integrated with routing models, yet still does not address multiple nested UAVs [13].

The evidence gap is therefore specific: no retrieved paper gives **packing efficiency, access paths, or bay-door/deployment-clearance margins** for a 500 L bay holding eight small plus eight medium UAVs [16]. That makes packaging a major system risk, not a downstream detail.

4.3 Likely design implication

Inferred: A mixed packing strategy is more plausible than a uniform one: denser cartridge-like stacking for smaller UAVs and door-adjacent or perimeter stowage for larger ones may reduce egress conflicts. This is an inference from the combination of packing constraints, modular compartment logic, and the asymmetric child-UAV size mix, not a directly demonstrated literature result [11] [13].
Confidence level: Low - Plausible synthesis, but not directly validated in retrieved studies.

Confidence level for section: Medium - The enabling mechanisms are supported, but the exact 500 L closure problem is under-supported [11] [14] [16].

5. Heavy-Lift Multirotor Propulsion Scaling

5.1 Scaling laws and endurance limits

The most relevant scaling evidence shows that unmanned rotorcraft size parameters correlate strongly with MTOW and can be regressed to estimate payload, battery mass/capacity, rotor diameter, endurance, range, and ceiling [19]. That same compiled dataset suggests an **apparent electric-endurance limit near 120 min and 70 km range** [19]. For the proposed mothership, this places the design target at or beyond a difficult region for all-electric rotorcraft-like platforms [19].

Large electric multirotors have demonstrated a useful-load fraction of **0.64** across a wide gross-weight range, supporting the idea that payload fraction can remain strong as vehicles scale [40]. However, motor weight fractions also rise with vehicle size in some hover/near-hover estimates, reaching **15.8%** in the largest of one quadcopter set [54]. This implies that scale helps payload fraction but does not eliminate installed-power penalties [40] [54].

Disk loading remains a central trade variable: increasing it raises hover power demand and rotor speed while reducing motor torque and potentially reducing motor weight [64]. For the mothership, this means preliminary rotor sizing should explicitly map the trade between rotor diameter, structural integration, current draw, and hover power [64] [65].

5.2 Distributed electric propulsion mass and benefits

DEP studies show propulsion-system mass can become a dominant share of takeoff mass: over **20%** in one STOL UAV, and **27% plus 7% cable mass** in another case [8] [9]. Yet DEP can also produce major low-speed performance benefits, including **over 60% total lift increase** when propulsor count increased from 6 to 18 in one study, and improved stability through thrust distribution in another [25] [26].

This is the central design trade for the mothership's 6-lift/4-cruise architecture: more propulsors can help controllability, redundancy, and possibly packaging flexibility, but they also add component mass and interaction penalties [8] [9] [25] [26].

5.3 Rotor interaction penalties

The interference evidence is strong. Close spacing at **d = 0.2D** caused marked thrust decline relative to an isolated rotor in one interaction test [20]. Tandem/coaxial validation studies quantify power penalties under fixed thrust coefficients [21], and side-by-side experiments show geometry-dependent shifts in thrust and torque coefficients [22]. Additional work notes that at larger scale, rotor arrangement and arm geometry materially affect hover efficiency, while coaxial systems only become competitive under certain loading conditions [66].

For the proposed configuration, the practical conclusion is that **rotor count should not be frozen before interference-aware layout trades are completed** [20] [22] [24].

Confidence level: High - Strong direct support from scaling and rotor-interaction studies [19] [20] [40].

6. Aerodynamic Coupling During Aerial Deployment

6.1 Hazards and disturbance sources

The deployment literature shows that wake/downwash, rotor-rotor interaction, and rotor-wing interference reduce thrust/efficiency and create asymmetric loads and controllability hazards [67] [68] [69] [70] [71]. For carrier-release operations, this means a child UAV may pass through a transiently distorted flow field immediately after separation [31] [41].

Rotor spacing and configuration strongly affect these hazards. Smaller spacing increases interaction; three-rotor studies show severe “two-to-one” interference, and even non-overlapping geometries retain some interaction [24]. In tilt/convertible aircraft, rotor wake impingement on wings is strongest at low advance ratio and can produce separation and download effects; flap shaping or attitude changes can mitigate these effects [46] [72].

6.2 Release dynamics and post-separation stability

Release studies explicitly model parent velocity, release point, payload mass, separation trajectory, and clearance [29] [30]. One case tracked a trajectory with **925 mm initial minimum clearance** and retrorocket-assisted deceleration [30]. Other launch studies show that geometry changes during deployment can create strong instability, and separation disturbances can be modeled as impulse force/moment inputs [32] [73].

The control literature then shows how post-release stabilization is handled: hierarchical backstepping with observer-based aerodynamic estimation, nonlinear MPC with EKF relative-state estimation and tether-tension control, and adaptive super-twisting sliding-mode control for uncertain 6-DOF dynamics [32] [49] [74]. Separate mothership-assisted launch work used PID stabilization after separation [33] [34].

The design implication is straightforward: **release mechanism, initial attitude, rotor startup timing, and immediate control law must be designed as one sequence** [32] [33] [34].

6.3 Safety-envelope approach

Recent vertiport-style work has made downwash/outwash assessment more quantitative. Safety-zone studies combine systems safety methods, Monte Carlo, CFD, and field measurements, and one enhanced semi-empirical model supports a **150-ft minimum safety radius** [35] [36]. CFD and experimental work also show that outwash is spatially inhomogeneous, unsteady, and sensitive to rotor spacing, height, and vortex dynamics [37] [39].

Taken together, these findings suggest that child-UAV deployment should be designed around a **protected release corridor through a mapped wake field**, analogous to vertiport protection zones but applied to moving-aircraft deployment [35] [36] [38]. This is a cross-source inference rather than a directly reported method.
Confidence level: Medium - Strongly implied by the evidence, but not directly demonstrated for the exact mothership-child architecture [36] [41].

Confidence level for section: High - The core hazards and control needs are consistently supported [29] [32] [36] [46].

7. Recommended Development Workflow

A practical literature-grounded workflow is:

Phase 1: Requirement closure

- Freeze mission segments, reserve policy, weather assumptions, and deployment loiter assumptions before geometry optimization [4].
- Define child-UAV folded-envelope targets from the 500 L bay before child airframe optimization [11] [15].

Phase 2: Low-fidelity sizing

- Use empirical/mission-based sizing for mothership battery, rotor diameter, disk loading, and installed power [48] [60] [65].
- Include thermal loads and high/hot hover or off-nominal trim cases in early energy closure [10] [75].

Phase 3: Geometry and packaging loop

- Build a CAD bay model with orientation, stacking, centroid, and clearance constraints [11] [16].
- Trade child concepts using wing fold, nested rotors, inflatable surfaces, and landing-gear minimization [14] [17] [18].

Phase 4: Propulsion-interference loop

- Evaluate 6-lift/4-cruise spacing against thrust-loss and asymmetry penalties [20] [24].
- Compare alternative propulsor counts or placements on control authority versus efficiency [25] [26].

Phase 5: Deployment safety loop

- Build a wake-aware release simulation using integrated, isolated, and post-separation states [41].
- Add closed-loop stabilization and state estimation immediately after release [49] [74].
- Validate corridors with CFD/experiment-style safety-envelope methods [35] [37].

Confidence level: High - The staged workflow directly follows the methodological lesson in the evidence base [16] [41] [42] [48].

8. Conclusions

The literature converges on a clear conclusion: the proposed two-tier eVTOL system is governed by **energy, mass, packaging, and interference couplings**, not by any one subsystem alone [41] [47] [51]. The strongest evidence is that mothership feasibility will be set mainly by **hover/transition peak power, reserve policy, and thermal loads**, while packaging of 16 UAVs into **500 L** is a major unresolved integration risk with limited direct precedent [1] [4] [10] [11] [16].

Heavy-lift propulsion studies support distributed electric architectures for control and low-speed performance, but also show that **compact spacing creates measurable efficiency penalties**, making rotor layout a first-order design variable rather than a packaging afterthought [20] [24] [25]. Aerial deployment is feasible in principle, but only if release geometry, wake exposure, and post-release control are co-designed and validated using higher-fidelity tools [29] [32] [36].

For this concept specifically, the literature most strongly supports three design moves:

1. keep the mothership **wing-borne or low-hover-exposure** during deployment where possible [4] [44];
2. make child UAVs **folded-envelope driven** from the start [14] [17];
3. treat deployment as passage through a **mapped aerodynamic corridor**, not just a door-release event [36] [41].

Overall confidence level: Medium-High - The cross-topic design logic is strong and well grounded, but the exact 500 L packing closure and exact mothership-child deployment geometry remain unvalidated in the supplied evidence [16] [31].

References

1. Kwak, J.V., Venkatesh, T., Bradley, M., (...), Byahut, S. (2026) Flight Mission Modeling of eVTOL and eCTOL Commuter Aircraft. *AIAA Science and Technology Forum and Exposition, AIAA SciTech Forum 2026*. https://doi.org/10.2514/6.2026-2280
2. Yang, X.-G., Liu, T., Ge, S., (...), Wang, C.-Y. (2021) Challenges and key requirements of batteries for electric vertical takeoff and landing aircraft. *Joule*. https://doi.org/10.1016/j.joule.2021.05.001
3. Liu, W., Hu, X., Zhang, K., (...), Song, Z. (2025) Enabling high-fidelity electrothermal modeling of electric flying car batteries: A physics-data hybrid approach. *Applied Energy*. https://doi.org/10.1016/j.apenergy.2025.125633
4. Hagag, N., Toepsch, F., Graf, S., (...), Eduardo, H. (2021) Maximum total range of eVTOL under consideration of realistic operational scenarios. *SESAR Innovation Days*. https://www.scopus.com/pages/publications/85160805627

5. Kiesewetter, L., Shakib, K.H., Singh, P., (...), Shah, K. (2023) A holistic review of the current state of research on aircraft design concepts and consideration for advanced air mobility applications. *Progress in Aerospace Sciences*. https://doi.org/10.1016/j.paerosci.2023.100949
6. Donateo, T., Carlà, A., Avanzini, G. (2018) Fuel consumption of rotorcrafts and potentiality for hybrid electric power systems. *Energy Conversion and Management*. https://doi.org/10.1016/j.enconman.2018.03.016
7. Sziroczák, D., Jankovics, I., Gál, I., Rohács, D. (2020) Conceptual design of small aircraft with hybrid-electric propulsion systems. *Energy*. https://doi.org/10.1016/j.energy.2020.117937
8. Ma, Y., Zhang, W., Zhang, X., (...), Guo, Z. (2021) Primary parameters design method for distributed electric propulsion unmanned aerial vehicle. *Xibei Gongye Daxue Xuebao/Journal of Northwestern Polytechnical University*. https://doi.org/10.1051/jnwpu/20213910027
9. Ma, Y., Zhang, W., Zhang, Y., (...), Zhong, Y. (2020) Sizing method and sensitivity analysis for distributed electric propulsion aircraft. *Journal of Aircraft*. https://doi.org/10.2514/1.C035581
10. Nakayama, H., Inoue, Y., Andreeva-Mori, A., Sasaki, D. (2026) Mission-level integrated electrical–thermal simulation for energy and thermal management of eVTOL aircraft. *Applied Thermal Engineering*. https://doi.org/10.1016/j.applthermaleng.2026.132253
11. https://www.sciencedirect.com/science/article/pii/S1099430026006771
12. Gueraiche, D., Albitar, D., Fedorov, K., Yang, Y. (2025) Multi-modular UAV for Mars exploration: A concept feasibility study: Modular Mars exploration UAV. *Chinese Journal of Aeronautics*. https://doi.org/10.1016/j.cja.2025.103562
13. Amine Masmoudi, M., Mancini, S., Baldacci, R., Kuo, Y.-H. (2022) Vehicle routing problems with drones equipped with multi-package payload compartments. *Transportation Research Part E: Logistics and Transportation Review*. https://doi.org/10.1016/j.tre.2022.102757
14. Cherkauer, S.A., Karle, C.J., Hiland, E.M., (...), Roth, B.D. (2025) Design and Flight Test of an Air-Launched Medical Aid Delivery Uncrewed Aerial Vehicle. *Aerospace*. https://doi.org/10.3390/aerospace12110977
15. Maysak, M.V., Popov, Yu.I. (2012) Development of the weight formula for a folding wing. *Russian Aeronautics*. https://doi.org/10.3103/S106879981202002X
16. He, B., Li, K., Nie, R., (...), Wang, G. (2025) Spatial geometric modelling and tessellation for modular hexagonal frustum deployable mechanism. *Mechanism and Machine Theory*. https://doi.org/10.1016/j.mechmachtheory.2025.106059
17. Cadogan, D., Scarborough, S., Gleeson, D., (...), Simpson, A. (2006) Recent development and test of inflatable wings. *Collection of Technical Papers - AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics and Materials Conference*. https://www.scopus.com/pages/publications/34147198664
18. Tieu, M., Michael, D.M., Pflueger, J.B., (...), Lee, C.L. (2016) Demonstrations of bio-inspired perching landing gear for UAVs. *Proceedings of SPIE - The International Society for Optical Engineering*. https://doi.org/10.1117/12.2218167

19. Ardelean, I.-C., Usov, D., Filippone, A., (...), Hollingsworth, P. (2023) Unmanned Wingless Rotorcraft Scaling. *Journal of Aircraft*. https://doi.org/10.2514/1.C037299

20. Lee, Hakjin, Lee, Duck-Joo (2020) Rotor interactional effects on aerodynamic and noise characteristics of a small multirotor unmanned aerial vehicle. *Physics of Fluids*. https://doi.org/10.1063/5.0003992

21. Wang, Y., Ji, H., Lu, L., Zhou, P. (2025) Modeling multirotor wake interference in quadrotor eVTOL flight dynamics and handling qualities. *Aerospace Science and Technology*. https://doi.org/10.1016/j.ast.2025.110533

22. Paswan, H., Mandal, R.K., Narayanan, S., Baskaran, K. (2026) Aeroacoustic impact of rotor geometry variation in side-by-side configurations for urban air mobility vehicles. *Physics of Fluids*. https://doi.org/10.1063/5.0344494

23. Wu, Wei, Tan, Xinyu, Liu, Xing, (...), Niu, Lanjie (2024) Aerodynamic Analysis of Rotor Spacing and Attitude Transition in Tilt-Powered Coaxial Rotor UAV. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s24227115

24. Zhu, H., Xin, Z., Nie, H., (...), Chen, H. (2026) Analysis of rotor aerodynamic interaction characteristics based on a three-rotor system model. *Physics of Fluids*. https://doi.org/10.1063/5.0340787

25. Yang, J., Wang, K., Zhou, Z., Zeng, J. (2025) Lift enhancement characteristics of distributed propulsion wing with propulsion-aerodynamic coupling. *Kongqi Donglixue Xuebao/Acta Aerodynamica Sinica*. https://doi.org/10.7638/kqdlxxb-2025.0065

26. Wang, G., Zhou, Z., Wang, R., Chen, Y. (2026) Stability analysis and shaping of distributed electric propulsion UAV based on aerodynamic-propulsive coupling modeling. *Aerospace Science and Technology*. https://doi.org/10.1016/j.ast.2026.113416

27. Bahr, M., McKay, M., Niemiec, R., Gandhi, F. (2020) Handling qualities assessment of large variable-RPM multi-rotor aircraft for urban air mobility. *Vertical Flight Society's 76th Annual Forum and Technology Display*. https://www.scopus.com/pages/publications/85096924697

28. Chen, Kun, Shi, Zhiwei, Tong, Shengxiang, (...), Chen, Jie (2019) Aerodynamic interference test of quad tilt rotor aircraft in wind tunnel. *Proceedings of the Institution of Mechanical Engineers, Part G: Journal of Aerospace Engineering*. https://doi.org/10.1177/0954410019852827

29. Dehghan, Mahnaz, Davari, Ali Reza, Dehghan Manshadi, Mojtaba (2017) Numerical investigation on the weight, speed, and installation location effects on fuel tank separation trajectory. *Proceedings of the Institution of Mechanical Engineers, Part G: Journal of Aerospace Engineering*. https://doi.org/10.1177/0954410016662799

30. Lu, Y., Yue, B., Hao, B., (...), Chang, Y. (2024) Stage separation of recoverable liquid launch vehicle by using moving pulsating ball analogue for propellant sloshing. *Chinese Journal of Aeronautics*. https://doi.org/10.1016/j.cja.2023.09.005

31. Xue, F., Wang, H., Jiang, Z., Wang, Y. (2020) Derivation and verification of a similarity law for wind-tunnel free-flight tests of heavy-store separation. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2020.04.061

32. Babaei, A.-R., Malekzadeh, M., Madhkhan, D. (2019) Adaptive super-twisting sliding mode control of 6-DOF nonlinear and uncertain air vehicle. *Aerospace Science and Technology*. https://doi.org/10.1016/j.ast.2018.09.013

33. Nauwynck, N., Balta, H., De Cubber, G., Sahli, H. (2019) A proof of the concept of the in-flight launch of unmanned aerial vehicles in a search and rescue scenario. *Acta IMEKO*. https://doi.org/10.21014/acta_imeko.v8i4.681

34. Nauwynck, N., Balta, H., De Cubber, G., Sahli, H. (2019) In-flight launch of unmanned aerial vehicles. *21st International Symposium on Measurement and Control in Robotics, ISMCR 2018*. https://www.scopus.com/pages/publications/85073791819

35. Ison, D.C. (2025) Development of Land Use Compatibility Guidelines for Vertiports through Synthesis of Safety, Noise, and Airflow Research. *AIAA Aviation Forum and ASCEND, 2025*. https://doi.org/10.2514/6.2025-3068

36. Ison, D. (2026) Developing Vertiport Safety Areas: A Data-Driven Approach to Downwash and Outwash Dynamics. *Collegiate Aviation Review*. https://www.scopus.com/pages/publications/105029363121

37. Caprace, D.-G., Diaz, P.V., Yoon, S. (2023) Simulation of the Rotorwash Induced by a Quadrotor Urban Air Taxi in Ground Effect. *FORUM 2023 - Vertical Flight Society 79th Annual Forum and Technology Display*. https://www.scopus.com/pages/publications/85167704480

38. Preston, J.R., Ferguson, S.W. (2014) Rotorwash operational footprint modeling. *40th European Rotorcraft Forum 2014*. https://www.scopus.com/pages/publications/84939529024

39. Vijayaraj, A., Moore, Z., Raghav, V. (2025) Downwash and outwash of counter-rotating coaxial rotors hovering in-ground effect. *Vertical Flight Society 81st Annual Forum and Technology Display*. https://www.scopus.com/pages/publications/105010296499

40. Duffy, M., Samaritano, T. (2015) The LIFT! project - modular, electric vertical lift system. *Annual Forum Proceedings - AHS International*. https://www.scopus.com/pages/publications/84937895963

41. Zhang, X., Yang, H., Ying, P., (...), Zheng, H. (2027) Aerodynamic optimization of multi-state semi-embedded complex airfoils based on a hybrid framework. *Aerospace Science and Technology*. https://doi.org/10.1016/j.ast.2026.113562

42. Wei, H., Jia, C., Shi, Y., (...), Hu, Q. (2024) EVTOL Flys Through Atmospheric Boundary Layer: Unsteady Take-Off and Landing Study via Spatio-Temporal Projection Method. *SAE Technical Papers*. https://doi.org/10.4271/2024-01-7014

43. Chopra, A., McCauley, J., Healy, R., (...), Sahni, O. (2021) A comparison of high-fidelity simulation approaches for eVTOL rotor flows in descent conditions. *77th Annual Vertical Flight Society Forum and Technology Display, FORUM 2021: The Future of Vertical Flight*. https://www.scopus.com/pages/publications/85108944957

44. Courtin, C., Mahseredjian, A., Dewald, A., (...), Hansman, R.J. (2021) A Performance Comparison of eSTOL and eVTOL Aircraft. *AIAA Aviation and Aeronautics Forum and Exposition, AIAA AVIATION Forum 2021*. https://doi.org/10.2514/6.2021-3220

45. Rohith, S.K., Sridharan, A., Govindarajan, B. (2026) Hybrid Powertrain Systems for 100 kg Multicopters and Tailsitters. *Journal of Aircraft*. https://doi.org/10.2514/1.C038443

46. Droandi, G., Gibertini, G., Grassi, D., (...), Liprino, C. (2016) Proprotor–wing aerodynamic interaction in the first stages of conversion from helicopter to aeroplane mode. *Aerospace Science and Technology*. https://doi.org/10.1016/j.ast.2016.08.013

47. Brelje, B.J., Martins, J.R.R.A. (2019) Electric, hybrid, and turboelectric fixed-wing aircraft: A review of concepts, models, and design approaches. *Progress in Aerospace Sciences*. https://doi.org/10.1016/j.paerosci.2018.06.004

48. Gatti, M., Giulietti, F. (2013) Preliminary design analysis methodology for electric multirotor. *IFAC Proceedings Volumes (IFAC-PapersOnline)*. https://doi.org/10.3182/20131120-3-FR-4045.00038

49. Prkacin, V., Palunko, I., Petrovic, I. (2025) Trajectory tracking and tether tension control of tethered aerial vehicle using Nonlinear Model Predictive Control. *Control Engineering Practice*. https://doi.org/10.1016/j.conengprac.2025.106346

50. Hu, T., Yang, X., Jia, F., (...), Cui, T. (2025) An Enhanced Multi-Objective Evolutionary Algorithm for Adaptive-Formation Multi-UAV Task Allocation with Load-Dependent Constraints. *2025 IEEE Congress on Evolutionary Computation, CEC 2025*. https://doi.org/10.1109/CEC65147.2025.11042983

51. Gur, O., Rosen, A. (2009) Optimizing electric propulsion systems for unmanned aerial vehicles. *Journal of Aircraft*. https://doi.org/10.2514/1.41027

52. Melo, S.P., Cerdas, F., Barke, A., (...), Herrmann, C. (2020) Life cycle engineering of future aircraft systems: The case of eVTOL vehicles. *Procedia CIRP*. https://doi.org/10.1016/j.procir.2020.01.060

53. Adler, E.J., Martins, J.R.R.A. (2025) Energy demand comparison for carbon-neutral flight. *Progress in Aerospace Sciences*. https://doi.org/10.1016/j.paerosci.2024.101051

54. Walter, A., McKay, M., Niemiec, R., (...), Ivler, C. (2022) Hover Handling Qualities of Fixed-Pitch, Variable-RPM Quadcopters of Increasing Size. *Journal of the American Helicopter Society*. https://doi.org/10.4050/JAHS.67.042010

55. Chen, Gang, Huang, Wei-Xi, Da Ronch, Andrea, (...), Kim, Daegyoum (2023) Mathematical modelling and model predictive controller design of a quad tiltrotor UAV. *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*. https://doi.org/10.1177/0954406220971330

56. Yang, N.-W., Larasati, M.R., Wang, I.-L., Yamashita, M. (2026) Optimizing Cooperative Carrier-Vehicle Routing with Iterative Second-Order Cone Programming Method. *Annals of Operations Research*. https://doi.org/10.1007/s10479-026-07089-x

57. Zheng, X., Qin, S., Zhang, Y., Huo, J. (2025) Integrated Two-Stage Optimization of Strategic Unmanned Aerial Vehicle Allocation and Operational Scheduling Under Demand Uncertainty. *Applied Sciences (Switzerland)*. https://doi.org/10.3390/app152011249

58. Bacchini, A., Cestino, E. (2019) Electric VTOL configurations comparison. *Aerospace*. https://doi.org/10.3390/aerospace6030026

59. Pakuła, A., Muchla, G., Załęcki, B., (...), Goetzendorf-Grabowski, T. (2022) Mechanical aspects of mothership with sensing drones system. *Aircraft Engineering and Aerospace Technology*. https://doi.org/10.1108/AEAT-12-2020-0320

60. Brown, A., Harris, W.L. (2020) Vehicle design and optimization model for urban air mobility. *Journal of Aircraft*. https://doi.org/10.2514/1.C035756

61. Yang, L., Xi, J., Zhang, S., (...), Huang, W. (2024) Research on energy management strategies of hybrid electric quadcopter unmanned aerial vehicles based on ideal operation line of engine. *Journal of Energy Storage*. https://doi.org/10.1016/j.est.2024.112965

62. Thurlbeck, A.P., Cao, Y. (2019) Analysis and Modeling of UAV Power System Architectures. *ITEC 2019 - 2019 IEEE Transportation Electrification Conference and Expo*. https://doi.org/10.1109/ITEC.2019.8790566

63. Ng, W., Datta, A. (2019) Hydrogen fuel cells and batteries for electric-vertical takeoff and landing aircraft. *Journal of Aircraft*. https://doi.org/10.2514/1.C035218

64. Walter, A., McKay, M., Niemiec, R., Gandhi, F. (2021) Effects of disk loading on handling qualities of large-scale, variable-RPM quadcopters. *77th Annual Vertical Flight Society Forum and Technology Display, FORUM 2021: The Future of Vertical Flight*. https://www.scopus.com/pages/publications/85108975036

65. Gatti, M., Giulietti, F., Turci, M. (2015) Maximum endurance for battery-powered rotary-wing aircraft. *Aerospace Science and Technology*. https://doi.org/10.1016/j.ast.2015.05.009

66. Theys, B., Dimitriadis, G., Hendrick, P., de Schütter, J. (2016) Influence of propeller configuration on propulsion system efficiency of multi-rotor Unmanned Aerial Vehicles. *2016 International Conference on Unmanned Aircraft Systems, ICUAS 2016*. https://doi.org/10.1109/ICUAS.2016.7502520

67. Saban, D., Whidborne, J.F. (2009) Modeling of wake vortex effects for unmanned air vehicle simulations. *AIAA Modeling and Simulation Technologies Conference*. https://doi.org/10.2514/6.2009-5686

68. Lu, C., Wang, Z., Qian, Z. (2026) Aerodynamic Design Research on the Rotor System of an Electric Vertical Take-Off and Landing Aircraft. *Springer Aerospace Technology*. https://doi.org/10.1007/978-981-95-7840-5_28

69. Shukla, D., Komerath, N. (2019) Low Reynolds number multirotor aerodynamic wake interactions. *Experiments in Fluids*. https://doi.org/10.1007/s00348-019-2724-3

70. Martínez-Lorenzo, J., Esteban, S., Cocco, A., (...), Zanotti, A. (2025) Aerodynamic Investigation of a Convertible Tandem-Wing UAV Using Mid-Fidelity Numerical Simulations and Propeller Interaction Experimental Data. *51st European Rotorcraft Forum, ERF 2025*. https://www.scopus.com/pages/publications/105038914991

71. Combey, K., Elsayed, O.A., Qaissi, K., (...), Mustapha, F. (2026) Numerical Analysis of Multirotor Aerodynamic Interactions in Forward and Transition Flight. *Journal of Aircraft*. https://doi.org/10.2514/1.C038518

72. Krishnakumar, R., Rasheed, A. Mohamed, Kumar, K. Senthil (2015) Enhanced Hover Control of Quad Tilt Frame UAV under Windy Conditions. *International Journal of Advanced Robotic Systems*. https://doi.org/10.5772/61231

73. Cheng, Hao, Shi, Qingli, Wang, Hua, (...), Zeng, Tao (2022) Flight dynamics modeling and stability analysis of a tube-launched tandem wing aerial vehicle during the deploying process. *Proceedings of the Institution of Mechanical Engineers, Part G: Journal of Aerospace Engineering*. https://doi.org/10.1177/09544100211010903

74. Drouot, A., Richard, E., Boutayeb, M. (2014) Hierarchical backstepping-based control of a Gun Launched MAV in crosswinds: Theory and experiment. *Control Engineering Practice*. https://doi.org/10.1016/j.conengprac.2013.11.016

75. Chakraborty, I., Mishra, A.A. (2022) Sizing and Analysis of a Lift-Plus-Cruise VTOL Aircraft with Electrified Propulsion Systems. *AIAA AVIATION 2022 Forum*. https://doi.org/10.2514/6.2022-3513