Bridging the Digital Literacy Gap in Rural Agri-Logistics: A Trilingual, Context-Aware Intelligent Driver Assistance System

Lokesh Kumar, Student Member, IEEE (Member # 99402233)
Department of Software Engineering, Sindh Agriculture University, Tandojam, Sindh, Pakistan
IEEE Karachi Section
Email: 2K22-SE-42@student.sau.edu.pk

Under the Academic Supervision & Guidance of:
Prof. Dr. Bhawani Shankar Chowdhry, Sitara-e-Imtiaz, Izaz-e-Fazeelat, Life Senior Member, IEEE
HEC Distinguished National Professor / Professor Emeritus & Former Dean, MUET Jamshoro
Lead Advisor / Former Chair, IEEE Karachi Section

Abstract

Agricultural supply chains in developing economies suffer extensive post-harvest perishable crop losses due to severe infrastructure deficits, inaccurate transit modeling, and linguistic exclusion among rural transport drivers. In Lower Sindh, Pakistan, transit and safety updates are conventionally delivered in high-resource official languages (Urdu and English), marginalizing drivers whose native vernaculars are localized Indo-Aryan dialects (Sindhi and Dhatki). This paper presents the theoretical formulation, system architecture, and empirical validation of the **Agri-Logistics Intelligent Decision Advisory System (IDAS)**. The framework couples an Open Source Routing Machine (OSRM) true-road geospatial engine with an edge-compatible trilingual Natural Language Processing (NLP) pipeline delivering synthesized voice advisories. Using a purposive sampling strategy across eight major rural agricultural corridors, the study empirically tests five core hypotheses (H_1–H_5). Results reveal that conventional straight-line (Haversine) approximations underestimate actual transit distances by a mean of **17.07%** ($t(7) = 4.892$, $p = 0.0017$), causing unbudgeted fuel deficits of **8.84 Liters** (PKR 2,488.81) and delivery delays of up to 27.4 minutes per transit cycle. Furthermore, statistical benchmarking of the regional Dhatki NLP engine confirms an average semantic intent classification latency of **0.0034 ms** and an end-to-end audio delivery turnaround of **747.92 ms** (95th percentile: **766.12 ms**), rigorously satisfying automotive safety standards (< 1.0 s). Survey-based usability assessment confirmed strong construct reliability (Cronbach's $\alpha = 0.842$).

Index Terms—Intelligent Transportation Systems (ITS), Agri-Logistics, Dhatki Dialect, Open Source Routing Machine (OSRM), Low-Resource NLP, Cronbach's Alpha, Fuel Deficit Modeling, Post-Harvest Spoilage Mitigation.

I. INTRODUCTION

Perishable cash crops—most notably tomatoes (*Solanum lycopersicum*), chillies, and onions cultivated in Lower Sindh (Tharparkar, Badin, and Mirpurkhas)—undergo strenuous overland freight transit to wholesale terminal distribution hubs in Hyderabad and Karachi. Transport operations along these rural arteries are predominantly conducted by informal fleet drivers who face substantial digital and textual literacy barriers. Critical in-transit advisories regarding road washouts, culvert collapses, localized monsoon precipitation, and cargo thermal fluctuations are traditionally broadcast through text-heavy dashboards or mobile SMS. Because these dispatches are formulated in English or formal Urdu, drivers cannot readily comprehend them, triggering severe rerouting delays, elevated road accidents on slippery surfaces ($\mu < 0.40$), and post-harvest cargo decay rates exceeding 30%.


Simultaneously, conventional rural logistics management tools frequently deploy geometric straight-line formulations (e.g., the Haversine spherical equation) to estimate inter-depot distance and arrival schedules. In rural Sindh, where infrastructure meanders along irrigation canals, railway crossings, and unpaved farm bunds, naive geometric math systematically underestimates true road transit distance, leading to unbudgeted fuel shortages and cargo spoilage.

To address these interconnected engineering and societal challenges, and building upon the foundational paradigms of Wireless Sensor Networks (WSN) and Agritech IoT in developing regions established by Katyara, Chowdhry et al. [2], [3], [8], this research presents **Agri-Logistics IDAS**, an edge-responsive, voice-first logistics advisory framework.

II. THEORETICAL FRAMEWORK, CAUSAL ARCHITECTURE & RESEARCH OBJECTIVES

A. Conceptual Model & Variable Taxonomy

The theoretical model grounding this study evaluates the interaction between computational navigation, dialectal interfaces, driver behavior, and logistics efficiency:



- **Independent Variables (IV)**: Routing algorithm architecture (Straight-line Haversine vs. True-Road OSRM) and interaction modality (Standard English/Urdu text vs. Dhatki/Sindhi voice synthesis).
- **Mediating Variables (MV)**: Driver alert comprehension and route compliance rate.
- **Dependent Variables (DV)**: Distance projection error (ε_d), unbudgeted fuel consumption (Δ F), transit delay (Δ t), post-harvest decay risk, and in-cab processing latency (T_L).
- **Moderating Variables**: Environmental factors including surface friction coefficient (μ), precipitation intensity, and nocturnal driving constraints.

B. Dual-Theory Integration: Road Impedance & Frugal Acoustic-Phonetic HCI

Agri-Logistics IDAS bridges two previously siloed theoretical traditions:

1. **Theory A — Graph-Theoretic Road Impedance & ISO 26262 Real-Time Human Factors:** Transportation topology in Lower Sindh is modeled as a directed weighted graph G = (V, E) via OSRM Contraction Hierarchies [9], where edge traversal cost incorporates surface friction degradation:

$$W(e) = L(e) / (v_{max}(e) \cdot \mu_{surface})$$

   Concurrently, automotive functional safety (ISO 26262 human-machine interface timing constraints) dictates that eyes-free auditory warnings under degraded pavement friction ($\mu = 0.38$, corresponding to wet monsoon asphalt where braking distance expands sharply relative to dry asphalt $\mu = 0.82$) must complete synthesis and onset within $\leq$ 1,000 ms so cognitive reaction headroom is preserved during emergency maneuvers.
2. **Theory B — Frugal Acoustic-Phonetic NLP & ICT4D Zero-Literacy Adoption:** Under ICT4D zero-literacy voice interface theory [10], cognitive barriers drop when rural operators interact in native vernaculars rather than unfamiliar text menus. Agri-Logistics IDAS maps Dhatki speech deterministically to constrained domain intents via sub-millisecond phonetic token matching (`0.0034 ms`), reserving >99.99% of the 1,000 ms safety budget for speech synthesis (**747.92 ms** grand mean). Thus, computational frugality directly unlocks human-factors safety: minimizing parser overhead prevents auditory lag from compounding driver distraction on hazardous rural corridors.

C. Explicit Separation of Causal Mechanisms (Demonstrated vs. Proxy vs. Untested)

To guard against over-claiming causal inference from static benchmarks and simulation logs, Table I-A separates directly measured mechanisms from economic proxies and future in-cab field trials.

TABLE I-A: Causal Chain Verification Matrix (Demonstrated vs. Modeled vs. Untested)

Causal Stage	Verification Status	Operational Evidence / Exact Parameters	Methodological Caveat
1. Topological Divergence (dH → dR)	Directly Demonstrated	17.07% mean OSRM vs. Haversine divergence (t(7)=4.892, p=0.0017) across R01–R08.	Static OSM road snapshot; excludes temporary seasonal washouts.
2. Dialect Intent Parsing & Voice Timing	Directly Demonstrated	0.0034 ms Dhatki phonetic parse; 747.92 ms mean audio turnaround (766.12 ms P95; N=50 trials/intent).	Benchmarked in low-noise acoustic conditions using Web Speech API TTS.
3. Instrument Usability Construct	Directly Demonstrated	Driver pilot usability survey achieved Cronbach's α = 0.842 (N=25).	Measures perceived clarity, promptness, and trust rather than longitudinal retention.
4. Fuel & Cost Deficit (Δ F, Δ C)	Modeled / Proxy Step	+8.84 L diesel / Rs. 2,488.81 PKR modeled at constant η = 8.0 km/L and Rs. 282.00/L.	Linear efficiency proxy; ignores grade resistance, payload variance, and idling.

Causal Stage	Verification Status	Operational Evidence / Exact Parameters	Methodological Caveat
5. Perishable Thermal Spoilage Mitigation	Modeled / Proxy Step	Rerouting delay reduction coupled with 19.2°C cargo compartment threshold alerts.	Derived from horticultural decay bounds [4], [11], [14] rather than in-crate pulp thermometry.
6. Live In-Cab Compliance & Crop Decay	Untested (Phase 4 Target)	Continuous cab ASR under >85 dB diesel noise and live tomato enzymatic assay.	Targeted for the 2 × 2 Phase 4 field study under EPICS in IEEE instrumentation.

D. Research Objectives (RO) and Hypotheses (H)

This investigation tests five formal objectives:

- **RO1**: Quantify the geometric divergence between straight-line modeling and actual road networks in Lower Sindh.
  - *H_1: True-road GIS routing reveals statistically significant distance underestimation (> 15%) compared to Haversine straight-line approximations.*
- **RO2**: Develop and statistically benchmark a dialectal intent parsing engine tailored to rural Dhatki vernacular.
  - *H_2: Dhatki semantic intent classification executes in sub-millisecond computational time (< 0.05 ms) on edge hardware.*
- **RO3**: Evaluate end-to-end voice advisory synthesis turnaround against automotive safety thresholds.
  - *H_3: Total voice generation latency remains strictly below the 1.0-second ISO/IEEE automotive intervention limit.*
- **RO4**: Model the hidden economic and fuel deficits generated by naive spatial assumptions.
  - *H_4: Straight-line route modeling creates an unaccounted diesel deficit exceeding PKR 2,000 across a single multi-corridor transit cycle.*
- **RO5**: Evaluate driver usability and internal scale reliability of the multimodal voice interface.
  - *H_5: The driver perception survey achieves high internal construct reliability (Cronbach's $\alpha \geq 0.70$).*

III. LITERATURE REVIEW & RESEARCH GAP

A. Claim-to-Evidence Synthesis Matrix

Table III-A maps five foundational streams of prior literature against their empirical methods and the unresolved socio-technical deficits observed in Lower Sindh agricultural freight corridors.

TABLE III-A: Claim-to-Evidence Literature Synthesis Matrix

Reference	Domain & Core Claim	Empirical / Computational Method	Unresolved Gap in Lower Sindh
Katyara & Chowdhry et al. [2], [3], [8]	Agritech WSN & SCADA telemetry monitor irrigation and crop environments in developing regions.	Solar-powered field WSN nodes and remote SCADA control frameworks.	Scoped to stationary farm/canal monitoring; lacks mobile freight routing, wet-friction weighting, and driver voice HCI.
Luxen & Vetter [9]	Contraction Hierarchies on OpenStreetMap enable deterministic real-time routing at continent scale.	Bidirectional shortest-path graph contraction on OSM XML extracts.	Default OSRM travel weights exclude pavement surface friction (μ = 0.38), perishable shelf-life deadlines, and offline voice guidance.
Patel et al. [10]	Localized interactive voice forums (Avaaj Otalo) enable agricultural participation among low-literacy farmers.	Field deployment of cellular IVR audio boards with smallholder cohorts.	Relies on live cellular voice connectivity and server IVR; excludes off-grid navigation, real-time cab hazard warnings, and Dhatki phonetics.
Saeed et al. [11]	12-day tomato storage at ~20 °C shows corrugated cardboard cartons reduce decay and preserve quality better than wooden crates or nylon mesh bags.	Comparative 12-day packaging trial across wooden crates, cartons, and mesh bags.	Scoped to static container storage; omits corridor-level OSRM vs. Haversine route divergence and live transit driver alerts.
FAO [14] & Khaskheli et al. [15]	Horticultural commodities in Sindh and Pakistan face severe post-harvest losses from logistics, cold-chain, and processing deficits.	FAO HiH commodity-cluster analysis [14] and SAU tomato preservation & value-addition study [15].	Macro value-chain assessments bundle farm-gate handling with in-transit delays, masking micro-corridor routing bottlenecks.

B. Geospatial Discrepancy & Cross-Study Disagreement Analysis

In geographical information systems, great-circle distance d_H is formulated via the Haversine equation:

$$a = \sin^2(\Delta\varphi / 2) + \cos(\varphi_1) \cdot \cos(\varphi_2) \cdot \sin^2(\Delta\lambda / 2)$$

$$d_H = 2R \cdot \text{atan2}(\sqrt{a} , \sqrt{(1 - a)})$$

where R = 6371.0 km. While computationally instantaneous, d_H inherently assumes Euclidean flat space between coordinates. In rural developing regions, road network distance d_R is heavily constrained by topological impediments, bridge locations, and canal bypasses. The proportional underestimation error ε_d is expressed as:

$$\varepsilon_d = [(d_R - d_H) / d_R] \times 100\%$$

When ε_d exceeds 10%, route scheduling models under-project thermal exposure for perishable commodities, accelerating enzymatic tomato degradation.

Cross-Study Disagreement in Rural Sindh: Prior GIS routing validations evaluate predominantly gridded urban street networks where Euclidean approximations track closely with arterial grids, whereas field topology along Lower Sindh's agricultural feeder corridors (**R01–R08**) winds across irrigation canals (Nara, Rohri, and Kotri command embankments), producing feeder errors above **24%**. Similarly, while cloud-first ASR systems [5] and cellular IVR platforms [10] assume stable broadband or continuous GSM voice links, rural Badin–Mithi desert stretches experience intermittent 2G coverage and extended dead zones (qualitatively observed along field routes; quantitative RF signal-strength mapping is scheduled for Phase 4), rendering remote inference unreliable during acute cab hazard events.

C. Construct Taxonomy & Operationalization

Table III-B standardizes how core constructs vary between prior literature and the Agri-Logistics IDAS operationalization.

TABLE III-B: Cross-Study Construct Operationalization Taxonomy

Theoretical Construct	Prior Literature Operationalization	Agri-Logistics IDAS Operationalization
Context-Aware Routing	Shortest-time or shortest-distance static graph path [9] using dry-asphalt speed limits.	OSRM centerline traversal weighted by road friction (μ in [0.38, 0.82]), nocturnal visibility, and 19.2°C perishable alert ceiling.
Low-Resource Edge NLP	Cloud-hosted neural ASR or cellular telephony IVR requiring continuous network connectivity [5], [10].	Deterministic phonetic token parser (0.0034 ms) + localized romanized Dhatki/Sindhi/Urdu intent corpus (dhatki-agri-intents) on offline edge hardware.
Real-Time Safety Latency	End-to-end cloud round-trip API turnaround dependent on broadband availability.	End-to-end parser + acoustic onset measured with monotonic hardware timers (747.92 ms mean; 766.12 ms P95) against the <1,000 ms ISO 26262 safety ceiling.

D. Foundational Claim Verification & Dialectal Exclusion

An empirical audit of the widely cited **30–40% post-harvest tomato loss** benchmark across South Asia and Pakistan (FAO [14], Khaskheli et al. [15], alongside packaging decay trials by Saeed et al. [11]) indicates that aggregate losses combine two distinct physical stages: (1) **Farm-gate harvesting, rigid wooden-crate packaging compression, and pre-loading ambient holding**, which Saeed et al. [11] experimentally compared over 12-day ~20 °C storage trials across wooden crates, corrugated cardboard boxes, and nylon mesh bags prior to inter-city haulage; and (2) **In-transit thermal accumulation and routing-delay spoilage** during unrefrigerated transport [14], [15], where unbudgeted route extensions (+17.07%) prolong heat exposure past the 19.2°C cargo alert boundary and accelerate polygalacturonase softening [4]. Because existing macro statistics aggregate farm-gate curing losses with transit spoilage without separating their Lower Sindh sub-ratios, Agri-Logistics IDAS scopes its software intervention strictly to the **in-transit routing-delay and temperature-alert window** while deferring direct in-crate pulp spoilage attribution to Phase 4 field trials.

Simultaneously, while modern conversational agents and Speech-to-Text (STT) models achieve high accuracy in English and formal Urdu, they exhibit near-total failure when exposed to low-resource Indo-Aryan dialects such as **Dhatki** (spoken across Tharparkar and Mirpurkhas) and regional **Sindhi**. The absence of localized phonetic glossaries and speech corpuses creates a severe digital barrier for rural logistics operators.

Narrow Defensible Research Gap: Although general-purpose quantized acoustic models (e.g., Whisper-Tiny, Meta MMS) and offline map apps (e.g., OsmAnd, Valhalla) exist independently, no edge framework jointly achieves **sub-second (<1,000 ms) vernacular Dhatki intent classification and voice warning coupled with surface-friction-weighted perishable routing under >85 dB diesel cab noise and zero-cellular desert constraints.**

IV. EXPERIMENTAL METHODOLOGY

A. Sampling Strategy & Corridor Selection

A purposive, non-probability sampling methodology was implemented, selecting eight critical agricultural supply chain corridors connecting rural farmsteads to terminal hubs across Lower Sindh:

- **R01**: Mithi Farm A → Mithi Market (Local Feeder)
- **R02**: Mithi Depot → Naukot Junction (Arterial Connector)
- **R03**: Naukot Agricultural Belt → Digri Market (Secondary Feeder)
- **R04**: Digri Tomato Belt → Matli Hub (Perishable Tomato Corridor)
- **R05**: Matli Market → Hyderabad Processing Hub (Regional Wholesale)
- **R06**: Mithi → Hyderabad Full Corridor via NH-8 (Supply Trunk)
- **R07**: Diplo Pastoral Route → Mithi Market (Dairy / Livestock)
- **R08**: Tando Ghulam Ali → Tando Jam SAU Hub (Academic Research Corridor)

B. Fuel and Economic Modeling Parameters

Fleet fuel consumption was calculated based on standard medium-duty commercial diesel transport trucks:

- Baseline Fleet Efficiency: $\eta = 8.0$ km/L
- Diesel Price (National Baseline): P_{fuel} = PKR 282.00 per Liter
- Unbudgeted Fuel Consumption: $\Delta F = (d_R - d_H) / \eta$
- Hidden Economic Cost: $\Delta C = \Delta F \times P_{fuel}$

C. Dhatki NLP Latency Benchmarking Protocol

To test H_2 and H_3, an automated benchmarking suite executed 50 repeated trials across eight standardized operational queries in Dhatki vernacular. High-precision monotonic timers (`time.perf_counter()`) isolated semantic intent parsing latency (T_{NLP}) from text-to-speech synthesis latency (T_{TTS}).

V. EMPIRICAL RESULTS & QUANTITATIVE DISCUSSION

A. GIS Routing & Economic Discrepancy Analysis (H1, H4)

Table I displays the empirical spatial and fuel discrepancy data:

TABLE I: Routing Distance Discrepancies and Economic Impact in Sindh Corridors

Route ID	Agricultural Corridor	Cargo Classification	Haversine dH (km)	True-Road dR (km)	Distance Delta (km)	Error εd (%)	Travel Time tR (min)	Fuel Delta Δ F (L)	Cost Delta Δ C (PKR)
R01	Mithi Farm A → Mithi Market	Millet / Grain	1.49	1.99	+0.50	25.00%	3.5	+0.06	Rs. 18.00
R02	Mithi Depot → Naukot Junction	Mixed Produce	32.38	38.43	+6.05	15.74%	38.2	+0.76	Rs. 213.26
R03	Naukot Belt → Digri Market	Chili / Grain	56.24	75.04	+18.80	25.05%	83.7	+2.35	Rs. 662.70
R04	Digri Tomato Belt → Matli Hub	Perishable Tomato	10.63	14.07	+3.44	24.45%	23.1	+0.43	Rs. 121.26
R05	Matli Market → Hyderabad Hub	Vegetables / Onion	62.91	70.01	+7.10	10.14%	64.9	+0.89	Rs. 249.92
R06	Mithi → Hyderabad Corridor (NH-8)	Arterial Trunk Line	162.01	184.14	+22.13	12.02%	170.9	+2.77	Rs. 779.88
R07	Diplo Pastoral → Mithi Market	Dairy / Livestock	37.56	40.98	+3.42	8.35%	38.5	+0.43	Rs. 120.39
R08	Tando Ghulam Ali → Tando Jam Hub	Research Cargo	49.03	58.21	+9.18	15.77%	57.0	+1.15	Rs. 323.59
MEAN / TOTAL	**Aggregate Cross-Corridor Metrics**	**—**	**52.78**	**60.36**	**+7.58**	**17.07%**	**60.0**	**+8.84 L**	**Rs. 2,488.81**

- **Statistical Hypothesis Testing (H_1)**: A paired-samples t-test between d_R and d_H yielded $t(7) = 4.892$, $p = 0.0017$. Because $p < 0.01$, H_1 is strongly accepted: true-road routing corrects a statistically significant underestimation bias averaging **17.07%** across Lower Sindh.
- **Feeder vs. Trunk Corridor Variance (Secondary Spatial Outlier Analysis)**: Disaggregating Table I exposes a sharp architectural divergence between rural agricultural feeder routes and inter-district arterial highways. Feeder corridors—**R01 (25.00%)**, **R03 (25.05%)**, and **R04 (24.45%)**, averaging **24.83%** divergence—incur **2.44×** (~2.4×) the Haversine distance underestimation observed on arterial and straight pastoral routes (**R05: 10.14%**, **R07: 8.35%**, **R06: 12.02%**; trunk/pastoral mean **10.17%**). Consequently, short farm-to-mandi feeder hauls experience disproportionately severe schedule compression despite smaller absolute kilometer totals.
- **Economic Verification (H_4)**: Across one operational delivery cycle traversing these eight corridors, straight-line planning neglects **8.84 Liters of diesel**, incurring an unbudgeted loss of **Rs. 2,488.81 PKR**, confirming H_4.

B. Dhatki NLP Latency Benchmarks (H2, H3)

Table II outlines statistical execution metrics over 50 iterations per semantic intent:

TABLE II: Latency Benchmarks for Regional Dhatki NLP and Voice Synthesis

Test ID	Semantic Intent Class	Dhatki Input Utterance	Semantic Gloss	NLP Parse Mean (ms)	TTS Synthesis Mean (ms)	Total Mean Latency (ms)	95th Percentile Latency (ms)
DH_01	Route Guidance	taaro raah hyderabad hub te kenh ahe	Corridor destination request	0.0013	739.77	739.77	759.32
DH_02	Maneuver Turn	humai kayi side mura agte junction te	Junction turn inquiry	0.0021	658.57	658.58	672.64
DH_03	Speed Regulation	raftar ketri rakhani ahe raat mein	Night speed limitation check	0.0029	732.46	732.46	750.05
DH_04	Cargo Stabilization	tamatar nazuk maal ahe gadi mein dhyan rakh	Tomato load shock warning	0.0037	705.67	705.68	722.10
DH_05	Weather Hazard	sadak te barish ahe sadak chikani thia	Surface slip coefficient alert	0.0044	749.22	749.22	766.20
DH_06	Emergency Dispatch	gadi kharab thia ahe raste te madad mokh	Mechanical breakdown SOS	0.0051	908.63	908.64	930.55
DH_07	Fuel Station	aglo petrol pump kahan ahe diesel mukam	Fuel replenishment lookup	0.0060	682.55	682.55	700.23
DH_08	ETA Arrival	hyderabad mandi ketre waqt mein pohchan	Wholesale market ETA query	0.0015	806.47	806.47	827.91
OVERALL	**Statistical Grand Mean**	**—**	**—**	**0.0034 ms**	**747.92 ms**	**747.92 ms**	**766.12 ms**

- **Verification of H_2**: Semantic intent parsing executed with a grand mean of **0.0034 ms**, well within the < 0.05 ms threshold. A one-way ANOVA across language conditions (Dhatki vs. Sindhi vs. Urdu) confirmed no statistically significant processing penalty for dialectal inputs ($F(2, 21) = 0.421$, $p = 0.662$).
- **Verification of H_3**: Mean end-to-end voice turnaround was **747.92 ms**, with a 95th percentile peak of **766.12 ms**. Both metrics remain strictly below the 1.0-second real-time limit required for emergency vehicular alert delivery.
- **Outlier Recovery — `DH_06` Emergency Dispatch Latency Spike**: While aggregate latency meets safety targets, `DH_06` (*Mechanical Breakdown SOS*) exhibits a critical secondary outlier, reaching **908.64 ms mean** and **930.55 ms at the 95th percentile**—narrowing safety headroom to **<70 ms below the 1,000 ms ISO 26262 ceiling**. This +160.72 ms elevation over the grand mean stems from longer multi-clause emergency response phoneme synthesis chains rather than NLP parsing (`0.0051 ms`). Mitigating this tail latency via pre-cached PCM emergency earcons/WAV buffers is therefore mandated prior to bare-metal Raspberry Pi Zero 2W migration.

C. Instrument Usability & Construct Reliability (H5)

A structured 5-point Likert questionnaire administered to a pilot cohort of 25 commercial truck drivers evaluated three key constructs: *Auditory Clarity*, *Decision Promptness*, and *Operational Trust*. Scale reliability analysis demonstrated high internal consistency across survey items:

$$\alpha = [\, K / (K - 1) \,] \cdot [\, 1 - (\Sigma\sigma_i^2 / \sigma_X^2) \,] = 0.842$$

Because $\alpha > 0.80$, the instrument satisfies formal psychometric reliability criteria, confirming H_5.

VI. ASSUMPTION STRESS-TEST, OPERATIONAL BOUNDARIES & STUDY LIMITATIONS

A. Audit of Five Core Modeling Assumptions

Table VI-A audits and ranks the five primary assumptions underlying Phases 1–3 benchmarks by methodological sensitivity.

TABLE VI-A: Prioritized Core Assumption Audit Matrix

Priority	Underlying Assumption	Idealized Baseline Used	Real-World Failure Risk in Rural Sindh	Required Engineering Upgrade
A1 (Highest)	Cab Acoustic Signal-to-Noise Ratio (SNR)	Clean laboratory/quiet office acoustic inputs during intent trials.	Uninsulated medium-duty diesel truck cabs generate >85 dB engine + wind noise, degrading phoneme recognition accuracy.	Noise-augmented ASR ablation (0 dB, +5 dB, +10 dB) + close-talk lapel mic & WebRTC RNNoise/DSP frontend.
A2 (High)	Embedded TTS Synthesis Parity	Browser Web Speech API synthesis (747.92 ms mean; 930.55 ms DH_06 P95).	Bare-metal Raspberry Pi Zero 2W (512 MB RAM) running INT8 ONNX (<2.4 MB voice model) may suffer thermal throttling above 45°C.	Pre-compiled INT8 Piper/eSpeak-NG phonemic lookup + cached WAV emergency warnings (<150 ms ceiling).
A3 (Medium)	Constant Vehicle Fuel Efficiency	Fixed η = 8.0 km/L and diesel price Rs. 282.00/L.	Loaded/unloaded payload asymmetry, unpaved bund gear shifts, and wet mud rolling resistance (μ = 0.38) depress real η below static baselines.	OBD-II fuel-flow logging paired with grade-weighted speed-load regression.
A4 (Medium)	Static Road Network Topology	Cached OpenStreetMap road graph snapshot during simulation.	Acute Sindh monsoon flooding washes out single-lane feeder culverts on R01–R04 without immediate OSM updates.	Crowdsourced driver hazard flags relayed opportunistically over LoRaWAN P2P mesh.
A5 (Moderate)	Dialectal Uniformity Across Corridors	Standardized Tharparkar/Umerkot Dhatki lexicon (dhatki-agri-intents).	Phonetic and lexical drift across Mirpurkhas, Nagarparkar, and Badin Dhatki/Marwari sub-dialects.	Multi-tehsil phonetic synonym expansion and phoneme-edit-distance fuzzy matching.

B. Operational Boundary Conditions & Methodological Blind Spots

1. **Acoustic & Hardware Boundaries:** Current latency guarantees (`747.92 ms`) cease to hold when cab acoustic noise exceeds `85 dB` without active beamforming, or when hardware RAM falls below `256 MB` without an audio DAC.
2. **Temporal & Seasonal Scope:** Empirical field routing observations were restricted to the monsoon and immediate post-monsoon harvest window (July–September 2026); dry winter harvest freight dynamics remain outside the current sample.
3. **Geographical & Psychometric Scope:** Findings are delimited to Lower Sindh's provincial network (Tharparkar, Mirpurkhas, Badin, and Hyderabad districts). Moreover, pilot usability ($\alpha = 0.842$, $N = 25$) establishes self-reported interface trust rather than randomized controlled intervention compliance during live night-rain hauls.

VII. RESEARCH GAP RANKING, PHASE 4 EXPERIMENTAL PROTOCOL & CONCLUSION

A. Candidate Research Gap Ranking Matrix

Table VII-A scores four candidate Phase 4 follow-up directions across two realistic funding tiers: **$0 Self-Funded Software/Acoustic Benchmark** vs. **$9,175.00 USD EPICS in IEEE Solar/LoRa Grant Scope**.

TABLE VII-A: Candidate Research Gap Evaluation Matrix (1–5 Scale)

Candidate Follow-Up Gap	Evidential Support	Humanitarian / Scientific Value	Operational Clarity	Feasibility ($0 Self-Funded)	Feasibility ($9,175 EPICS Grant)	Priority Rank
G1: Sub-Second Dhatki ASR + Intent Robustness Under >85 dB Cab Noise	5	5	5	5 (Immediate)	5	#1 (Immediate Core)
G2: Surface-Friction (μ=0.38) & Thermal (19.2°C) Dynamic OSRM Weighting	5	5	5	4 (Sim + Logs)	5	#2 (Immediate Core)

Candidate Follow-Up Gap	Evidential Support	Humanitarian / Scientific Value	Operational Clarity	Feasibility ($0 Self-Funded)	Feasibility ($9,175 EPICS Grant)	Priority Rank
G3: Off-Grid Solar LoRaWAN Mesh Telemetry Across Thar Cellular Blackouts	4	5	4	2 (Needs Hardware)	5	#3 (EPICS Hardware)
G4: Multi-Corridor In-Crate Tomato Enzymatic Decay Pulp Assay	3	4	4	2	4	#4 (Agronomy Extension)

B. Adversarial Disproof Stress-Test & Gap Narrowing

To prevent trivial reinvention, **G1 + G2** was stress-tested against two strong off-the-shelf baselines: (a) **Quantized Whisper-Tiny / Meta MMS (`INT8/INT4`)** and (b) **Offline OsmAnd / Valhalla routing engines**. While Whisper-Tiny covers 99 languages, it omits Dhatki completely, suffers severe acoustic word-error spikes at `0 dB` to `+5 dB` diesel noise, and exceeds `<2.4 MB` ultra-frugal RAM footprints alongside audio synthesis on Raspberry Pi Zero 2W gateways. Similarly, while OsmAnd and Valhalla route offline via static speed hierarchies, neither ingests live wet-friction coefficients ($\mu = 0.38$) coupled with perishable tomato core-temperature limits (19.2°C) and sub-second `Dhatki` voice warnings. This yields our tightly scoped thesis gap: **sub-second joint acoustic-phonetic Dhatki intent classification and surface-friction-weighted perishable routing under high cab noise and zero-connectivity constraints.**

C. Publication-Grade Phase 4 Follow-Up Study Design (3–6 Month Protocol)

1. **Experimental Design (2 × 2 Factorial Ablation):** Evaluate **Routing Engine** (*Static OSRM* vs. *Friction- & Thermal-Weighted IDAS-OSRM*) crossed with **Acoustic Condition** (*Clean baseline* vs. *Real diesel truck cab noise injected at `0 dB`, `+5 dB`, and `+10 dB` SNR*) on both **Raspberry Pi Zero 2W** (`<2.4 MB` INT8 acoustic model + pre-cached emergency PCM alerts) and pilot cab hardware under SPO field partnership.
2. **Statistical Analysis Plan:**
   - Paired **Wilcoxon signed-rank tests** (non-parametric guard for skewed latency tails on `DH_06`) and **paired t-tests** ($\alpha = 0.05$, Bonferroni-adjusted) comparing end-to-end turnaround against the 1,000 ms ISO 26262 ceiling across all SNR levels.
   - **Precision / Macro-F_1 / Word-Intent Accuracy** degradation curves across `0 dB`, `+5 dB`, `+10 dB`, and clean conditions for Dhatki vs. Sindhi vs. Urdu.
3. **Literature Verification Search Queries (IEEE Xplore & ACL Anthology):**
   - *Query 1 (IEEE Xplore):* `("low-resource" OR "Dhatki" OR "Sindhi") AND ("voice assistant" OR "spoken intent") AND ("edge computing" OR "offline") AND ("automotive" OR "agriculture")`
   - *Query 2 (IEEE Xplore):* `("OSRM" OR "Contraction Hierarchies") AND ("surface friction" OR "perishable") AND ("post-harvest" OR "cold chain") AND ("rural" OR "developing")`
   - *Query 3 (ACL Anthology):* `("spoken language understanding" OR "intent classification") AND ("noisy" OR "SNR") AND ("Indo-Aryan" OR "zero-resource" OR "phonetic")`

D. Conclusion

This investigation formulated, audited, and validated the Agri-Logistics IDAS platform to bridge the digital and linguistic divide in rural agricultural transport. True-road OSRM modeling rectifies a statistically significant **17.07%** ($t(7)=4.892$, $p=0.0017$) straight-line underestimation—averaging **24.83%** on agricultural feeder corridors (R01, R03, R04)—eliminating modeled diesel deficits of **+8.84 L (Rs. 2,488.81 PKR)** per transit cycle. Dialectal NLP benchmarking confirms **0.0034 ms** intent parsing and **747.92 ms** grand mean audio turnaround ($\alpha = 0.842$), while explicitly bounding tail risks on emergency alerts (`DH_06`: `930.55 ms` P95) and high-decibel cab noise (`A1`) for Phase 4 EPICS in IEEE deployment.

ACKNOWLEDGMENT

The author expresses profound gratitude to **Prof. Dr. Bhawani Shankar Chowdhry** (*Sitara-e-Imtiaz*, *Izaz-e-Fazeelat*, Life Senior Member, IEEE) for his inspiring mentorship, rigorous methodological feedback, and continuous intellectual guidance throughout the design, algorithmic formulation, and empirical testing of this research. His pioneering contributions over four decades in Wireless Sensor Networks, Condition Monitoring, and IoT Applications in Agritech have directly grounded the architecture of this system. Sincere appreciation is also extended to the **IEEE Karachi Section** and the Faculty of Agricultural Engineering, Sindh Agriculture University, Tandojam, for providing experimental and computing facilities supporting this work.

REFERENCES

Foundational Books

[1] S. Ghosh and T. S. Lee, *Intelligent Transportation Systems: Smart and Green Infrastructure Design*, 2nd ed., Boca Raton, FL, USA: CRC Press, 2010.

[2] F. K. Shaikh, B. S. Chowdhry, H. M. Ammari, M. A. Uqaili, and A. Shah, Eds., *Wireless Sensor Networks for Developing Countries*, CCIS Vol. 366, Berlin, Heidelberg, Germany: Springer-Verlag, 2013, ISBN: 978-3-642-41053-6.

[3] B. S. Chowdhry, F. K. Shaikh, and N. A. Mahoto, Eds., *IoT Architectures, Models, and Platforms for Smart City Applications*, Hershey, PA, USA: IGI Global, 2019, ISBN: 978-1-79981-253-1.

[4] E. M. Yahia, Ed., *Postharvest Technology of Perishable Horticultural Commodities*, Cambridge, MA, USA: Woodhead Publishing / Elsevier, 2019.

[5] D. Jurafsky and J. H. Martin, *Speech and Language Processing: An Introduction to Natural Language Processing, Computational Linguistics, and Speech Recognition*, 3rd ed., Stanford, CA, USA: Prentice Hall / Stanford Univ., 2024.

[6] C. R. Kothari and G. Garg, *Research Methodology: Methods and Techniques*, 4th ed., New Delhi, India: New Age International Publishers, 2019.

[7] J. F. Hair, W. C. Black, B. J. Babin, and R. E. Anderson, *Multivariate Data Analysis*, 8th ed., Andover, UK: Cengage Learning, 2019.

Peer-Reviewed Research Papers

[8] S. Katyara, M. A. Shah, S. Zardari, B. S. Chowdhry, and W. Kumar, "WSN based smart control and remote field monitoring of Pakistan's irrigation system using SCADA applications," *Wireless Personal Communications*, vol. 95, no. 2, pp. 491–504, 2017.

[9] D. Luxen and C. Vetter, "Real-time routing with OpenStreetMap data," in *Proc. 19th ACM SIGSPATIAL Int. Conf. Adv. Geogr. Inf. Syst. (GIS)*, Chicago, IL, USA, 2011, pp. 513–516.

[10] N. Patel, D. Chittamuru, A. Jain, P. Dave, and T. S. Parikh, "Avaaj Otalo: A field study of an interactive voice forum for small farmers in rural India," in *Proc. ACM CHI Conf. Human Factors Comput. Syst.*, 2010, pp. 733–742, doi: 10.1145/1753326.1753434.

[11] A. F.-U.-H. Saeed, S. N. Khan, A. Sarwar, and J. J. Tahira, "Effect of packing materials on storage of tomato," *Mycopath*, vol. 8, no. 2, pp. 85–89, 2010.

[12] L. Kumar, "Agri-Logistics IDAS: Intelligent Decision Advisory System for Sindh Supply Chains," Research Prototype Technical Document, Sindh Agriculture University, Tandojam, 2026. [Online]. Available: https://agri-idas.tech/

Institutional & Industry Reports

[13] Ministry of Finance, Government of Pakistan, "Transport and Communications," in *Pakistan Economic Survey*, Islamabad, Pakistan, 2025/2026.

[14] Food and Agriculture Organization (FAO), *Hand-in-Hand (HiH) Initiative: Pakistan Tomato Commodity Cluster & Value-Chain Investment Briefs*, Rome, Italy: United Nations FAO, 2023–2025.

[15] S. G. Khaskheli, A. H. Soomro, and A. R. Junejo, "Physicochemical properties and antioxidant activity of tomato (*Solanum lycopersicum* L.) products: A comparative study of powder, juice, and ketchup," *Journal of Applied Research in Plant Sciences (JOARPS)*, vol. 7, no. 1, pp. 01–08, 2026, doi: 10.38211/joarps.2026.07.333.