Agri-Logistics IDAS: 13-Step Methodological Literature Audit & Graduate Research Proposal Dossier

Principal Investigator: Lokesh Kumar (Sonara), Student Member, IEEE (#99402233) · ORCID: 0009-0006-6510-6393
Undergraduate Institution: Department of Software Engineering, Sindh Agriculture University (SAU), Tandojam (Reg: 2K22-SE-42)
Faculty Mentor: Prof. Dr. Bhawani Shankar Chowdhry (Sitara-e-Imtiaz, Izaz-e-Fazeelat, Life Senior Member, IEEE), MUET Jamshoro
Field Implementation Partner: Strengthening Participatory Organisation (SPO), Pakistan
Open-Science Artifacts: Live Telemetry Portal (https://agri-idas.tech) · Corpus (lokeshsonara/dhatki-agri-intents)
Target Applications: Master's Research / Thesis Proposals for Erasmus Mundus (SE4GD / EDISS), DAAD, Italy DSU / MAECI, Stipendium Hungaricum, KAUST, and MBZUAI

EXECUTIVE SUMMARY

This dossier executes a **13-step foundational literature synthesis, assumption stress-test, outlier audit, and Phase 4 experimental design** on the *Agri-Logistics Intelligent Decision Advisory System (IDAS)* research program. While Phase 1–3 benchmarks establish a **17.07%** true-road OSRM vs. Haversine underestimation (t(7)=4.892, p=0.0017), **0.0034 ms** Dhatki semantic parsing, **747.92 ms** mean voice synthesis turnaround, and pilot psychometric reliability (α=0.842, N=25), rigorous self-audit identifies the exact causal boundaries, secondary outliers, `DH_06` P95 `930.55 ms`; `2.44×` feeder-to-trunk corridor divergence ratio), and `$0` vs. `$9,175.00 USD` (EPICS in IEEE) follow-up experiments required for publication-grade validation in an MS thesis.

STEP 1: CLAIM-TO-EVIDENCE LITERATURE SYNTHESIS MATRIX (PROMPT 1)

Reference	Empirical / Conceptual Claim	Underlying Method	Unresolved Gap in Lower Sindh Corridors
Katyara & Chowdhry et al. [2], [3], [8]	Agritech WSN and SCADA telemetry monitor irrigation and field conditions in developing regions.	Solar-powered field WSN telemetry & SCADA remote control.	Scoped to stationary farm/canal monitoring; lacks mobile haulage routing, wet-surface impedance (μ), and driver voice interfaces.
Luxen & Vetter [9]	Contraction Hierarchies enable deterministic sub-millisecond shortest-path queries over OSM road networks.	Bidirectional graph contraction on OpenStreetMap XML topology.	Default traversal weights ignore rainy road friction degradation (μ=0.38), thermal cargo alerts (19.2°C), and dialectal guidance.
Patel et al. [10]	Interactive vernacular voice forums (Avaaj Otalo) broaden agricultural adoption among low-literacy cohorts.	Field deployment of cellular IVR audio forums with rural farmers.	Assumes continuous GSM cellular connectivity and central IVR servers; omits off-grid navigation and Dhatki edge phonetics.
Saeed et al. [11]	12-day tomato storage at ~20 °C shows corrugated cardboard cartons reduce decay vs. wooden crates or nylon mesh bags.	Comparative 12-day packaging and storage stability trial.	Scoped to static container storage; omits OSRM vs. Haversine divergence and cab-side alerts.
FAO [14] & Khaskheli et al. [15]	Horticultural commodities in Sindh and Pakistan face high post-harvest losses from cold-chain and value-addition gaps.	FAO HiH commodity investment briefs [14] and SAU tomato preservation study [15].	Macro value-chain assessments bundle farm-gate curing losses with transit delays, hiding micro-corridor routing bottlenecks.

STEP 2: CROSS-STUDY DISAGREEMENT ANALYSIS (PROMPT 2)

Prior GIS validation studies evaluate predominantly gridded metropolitan road networks where Euclidean geometry tracks arterial grids closely. By contrast, empirical testing along Lower Sindh's agricultural supply corridors (**R01–R08**) shows **17.07%** mean divergence (t(7)=4.892, p=0.0017) because rural feeder roads wind continuously around irrigation barrages, Nara/Rohri canal embankments, and unpaved bunds. Likewise, cloud-first ASR systems [5] and cellular IVR platforms [10] assume continuous broadband or GSM voice links, whereas off-grid Thar desert stretches experience intermittent 2G/no-service blackouts (qualitatively observed along field routes; quantitative RF signal logging targeted for Phase 4).

STEP 3: CROSS-STUDY CONSTRUCT OPERATIONALIZATION TAXONOMY (PROMPT 3)

Construct	Conventional Literature Operationalization	Agri-Logistics IDAS Operationalization
Context-Aware Routing	Shortest-distance or dry-asphalt shortest-time OSM pathing [9].	OSRM centerline traversal dynamically weighted by wet/dry friction (μ in [0.38, 0.82]), nocturnal constraints, and 19.2°C cargo alert bounds.
Low-Resource Edge NLP	Cloud-hosted transformer ASR/NLU or telephony IVR requiring continuous network connectivity [5], [10].	Deterministic phonetic token parser (0.0034 ms) + localized romanized Dhatki/Sindhi/Urdu dataset (dhatki-agri-intents) executing 100% offline.
Real-Time Safety Latency	End-to-end cloud round-trip turnaround dependent on cellular broadband stability.	Monotonic timer measurement of parser + speech synthesis onset (747.92 ms mean; 766.12 ms P95) benchmarked against ISO 26262 <1,000 ms intervention limits.

STEP 4: PRIORITIZED CORE ASSUMPTION STRESS-TEST (PROMPT 4)

Rank	Underlying Assumption	Idealized Study Baseline	Real-World Failure Risk	Targeted Phase 4 Engineering Fix
A1 (Critical)	In-Cab Acoustic SNR	Quiet desktop microphone / clean synthetic token benchmark.	Diesel trucks in rural Sindh produce >85 dB cab wind and engine noise, risking speech recognition collapse.	Conduct controlled 0 dB, +5 dB, +10 dB diesel noise ablation + close-talk lapel mic & RNNoise filtering.
A2 (High)	Embedded TTS Hardware Parity	Browser Web Speech API engine (747.92 ms mean).	Bare-metal Raspberry Pi Zero 2W (512 MB RAM, <2.4 MB INT8 model) may throttle under 45°C cabin heat.	Migrate emergency advisories (DH_06) to pre-cached INT8 Piper/PCM WAV audio buffers (<150 ms).
A3 (Medium)	Constant Fuel Efficiency	Fixed η = 8.0 km/L at Rs. 282.00/L diesel baseline.	Heavy tomato payloads, idling, and wet mud rolling resistance (μ=0.38) depress real η below static baselines.	Log OBD-II fuel-injection telemetry paired with load-grade regression.
A4 (Medium)	Static OSM Topology	Pre-monsoon OpenStreetMap road graph snapshot.	Flash monsoon washouts sever rural feeder culverts along R01–R04 before OSM contributors update maps.	Peer-to-peer LoRaWAN driver hazard flagging triggered during route blackouts.
A5 (Moderate)	Dialectal Uniformity	Standardized Tharparkar/Umerkot romanized Dhatki lexicon.	Lexical drift toward Marwari/Sindhi idioms across Nagarparkar, Mirpurkhas, and Badin tehsils.	Multi-tehsil phonetic synonym clustering & fuzzy phoneme-edit matching.

STEP 5: CAUSAL CHAIN SEPARATION — DEMONSTRATED VS. MODELED VS. UNTESTED (PROMPT 5)

Stage in Causal Chain	Evidential Status	Exact Metrics & Provenance	Scoping Caveat
1. Road Network Divergence	Directly Demonstrated	17.07% mean OSRM vs. Haversine delta ($t(7)=4.892$, $p=0.0017$) over 8 corridors (1,313 centerline points).	Reflects static geometric OSM graph topology.
2. Dialect Parse & Voice Timing	Directly Demonstrated	0.0034 ms Dhatki parse; 747.92 ms mean TTS turnaround (766.12 ms P95; 50 trials/intent; ANOVA $p=0.662$).	Clean acoustic channel + browser TTS backend.
3. Pilot Driver Usability	Directly Demonstrated	5-point Likert pilot survey (N=25 drivers) yielded Cronbach's $\alpha = 0.842$ (>0.80 reliability).	Measures usability/clarity perception rather than live trip compliance.
4. Economic & Fuel Deficit	Modeled / Proxy	+8.84 L fuel / Rs. 2,488.81 PKR unbudgeted loss using constant η=8.0 km/L & Rs. 282/L.	Linear proxy; does not capture braking/idling variance.
5. Crop Spoilage Mitigation	Modeled / Proxy	Transit duration savings coupled with 19.2°C cargo thermal alerts.	Grounded in horticultural decay literature [4], [11], [14], not core pulp assay.
6. Live Cab Compliance & Decay	Untested (Phase 4 Target)	In-cab ASR under >85 dB noise + paired wet/dry trip spoilage measurement.	Scheduled for Phase 4 MS / EPICS instrumentation.

STEPS 6 & 7: METHODOLOGICAL BLIND SPOTS & BOUNDARY CONDITIONS (PROMPTS 6 & 7)

1. **Acoustic Envelope Ceiling:** Sub-second turnaround and accurate intent routing hold reliably up to laboratory/low-noise inputs; beyond **>85 dB cab noise** without acoustic denoising, ASR front-ends require calibrated SNR noise-injection training.
2. **Seasonal Harvest Boundary:** All field path audits occurred in **July–September 2026** (monsoon/post-monsoon window). Winter dry-season traffic density and thermal exposure bounds differ substantially.
3. **Device Hardware Floor:** Results assume a vehicular gateway or Raspberry Pi-class ARM processor with audio DAC; 8-bit/16-bit microcontrollers lacking floating-point DSP cannot host concurrent INT8 audio synthesis and Contraction Hierarchies routing.

STEP 8: TABLE II HYGIENE & RECOVERY OF UNREPORTED SECONDARY OUTLIERS (PROMPT 8)

1. **Vernacular Hygiene Fix (`DH_01`):** Replaced the residual English placeholder (`"give me my route to hyderabad hub"`) in `DH_01` with authentic romanized Dhatki (`"taaro raah hyderabad hub te kenh ahe"`), achieving 100% vernacular uniformity across `DH_01–DH_08`.
2. **Outlier #1 — `DH_06` Emergency Dispatch Tail Latency:** `DH_06` (*Mechanical Breakdown SOS*) recorded **908.64 ms mean** and **930.55 ms P95**—consuming 93.1% of the 1,000 ms ISO 26262 safety ceiling (`+160.72 ms` above grand mean). Longer emergency alerts trigger extended phoneme concatenation chains; switching SOS prompts to pre-cached WAV buffers removes TTS variance.
3. **Outlier #2 — 2.44× (~2.4×) Feeder vs. Trunk Error Variance in Table I:** Agricultural feeder routes (**R01: 25.00%**, **R03: 25.05%**, **R04: 24.45%**, mean **24.83%**) experience **2.44×** (~2.4×) the Euclidean divergence of arterial/pastoral routes (**R05: 10.14%**, **R07: 8.35%**, **R06: 12.02%**, mean **10.17%**). Short-haul feeder dispatchers suffer the steepest relative schedule error.

STEP 9: DUAL-THEORY INTEGRATION MECHANISM (PROMPT 9)

Agri-Logistics IDAS unifies **Theory A (Weighted Road-Graph Impedance $W(e)=L(e)/(v_{max}(e)\cdot\mu)$ + ISO 26262 Timing Bounds)** with **Theory B (Frugal Phonetic Edge NLP + ICT4D Zero-Literacy Voice HCI)**. When wet monsoon pavement reduces μ from 0.82 to 0.38, stopping distance expands sharply; sub-millisecond phonetic classification (`0.0034 ms`) consumes <0.0005% of the 1,000 ms safety budget, ensuring voice warnings begin within `747.92 ms` and minimizing eyes-off-road cognitive distraction on slick corridors.

STEP 10: DECONSTRUCTION OF THE >30% POST-HARVEST LOSS CLAIM (PROMPT 10)

Literature citations documenting 30–40% perishable tomato losses in Pakistan and South Asia (FAO [14], Khaskheli et al. [15]; alongside container stress evaluated by Saeed et al. [11]) aggregate two distinct physical failure stages:

- **Farm-Gate Staging, Packing Compression & Mechanical Bruising:** Non-cooled field sorting, rigid wooden-crate compression, and handling stress prior to dispatch (studied across 12-day ~20 °C wooden-crate, cardboard-carton, and nylon-mesh storage trials in Saeed et al. [11]).
- **In-Transit Thermal Accumulation & Routing-Delay Spoilage:** Unrefrigerated cargo heat buildup past the 19.2°C threshold compounded by unbudgeted +17.07% route distance/time over winding canal feeders [14], [15]. Because prior aggregate losses do not isolate Lower Sindh's exact sub-stage percentages, Agri-Logistics IDAS scopes its intervention qualitatively to the **in-transit routing-delay and thermal-alert mechanism** while reserving direct in-crate pulp spoilage attribution for Phase 4.

STEP 11: CANDIDATE FOLLOW-UP GAP RANKING ACROSS TWO BUDGET TIERS (PROMPT 11)

Candidate Research Gap	Evidential Support	Humanitarian Value	Operational Clarity	Feasibility ($0 Self-Funded)	Feasibility ($9,175 EPICS Grant)	Final Rank
G1: Noisy Cab (>85 dB) Dhatki ASR + Intent Robustness	5	5	5	5 (Immediate)	5	#1
G2: Surface-Friction (μ=0.38) & Thermal Dynamic OSRM	5	5	5	4 (Sim + Logs)	5	#2
G3: Solar LoRaWAN Mesh Telemetry Across Thar Blackouts	4	5	4	2	5	#3
G4: In-Crate Tomato Enzymatic Pulp Assay	3	4	4	2	4	#4

STEP 12: ADVERSARIAL DISPROOF & NARROW THESIS STATEMENT (PROMPT 12)

- **Against Quantized Whisper-Tiny / Meta MMS (`INT8/INT4`):** Whisper-Tiny omits Dhatki phonetics, loses accuracy sharply under `0 dB / +5 dB` diesel cab noise, and cannot fit inside `<2.4 MB` acoustic budgets alongside routing on Raspberry Pi Zero 2W (`512 MB` RAM).
- **Against Offline OsmAnd / Valhalla:** General offline routers compute static geometric/speed-limit paths and lack dynamic surface-friction (μ=0.38) crop-thermal (19.2°C) hazard edge weights paired with spoken Dhatki warnings.
- **Narrowed Research Thesis:** *"Engineering and validating a sub-second (<1,000 ms) joint acoustic-phonetic Dhatki intent classification and surface-friction-weighted perishable routing framework resilient to >85 dB diesel cab noise and zero-cellular desert constraints."*

STEP 13: PUBLICATION-GRADE PHASE 4 STUDY PROTOCOL (3–6 MONTH MS / EPICS PLAN) (PROMPT 13)

1. **Experimental Design (2 × 2 Factorial Ablation):** Cross **Routing Model** (*Static OSRM* vs. *Friction/Thermal-Weighted IDAS-OSRM*) with **Acoustic Condition** (*Clean speech* vs. *Recorded Lower Sindh truck cab noise injected at `0 dB`, `+5 dB`, and `+10 dB` SNR*) on bare-metal **Raspberry Pi Zero 2W** (`<2.4 MB` INT8 acoustic model + pre-cached emergency PCM buffers).
2. **Statistical Protocol:** Execute paired **Wilcoxon signed-rank tests** (guarding non-normal tail latency on `DH_06`) and **paired t-tests** ($\alpha = 0.05$, Bonferroni-corrected) against the 1,000 ms ISO 26262 ceiling, alongside Macro-F_1 / intent-error degradation curves across SNR strata.
3. **Reproducible Literature Verification Queries:**
   - **IEEE Xplore Query 1:** `("low-resource" OR "Dhatki" OR "Sindhi") AND ("voice assistant" OR "spoken intent") AND ("edge computing" OR "offline") AND ("automotive" OR "agriculture")`
   - **IEEE Xplore Query 2:** `("OSRM" OR "Contraction Hierarchies") AND ("surface friction" OR "perishable") AND ("post-harvest" OR "cold chain") AND ("rural" OR "developing")`
   - **ACL Anthology Query 3:** `("spoken language understanding" OR "intent classification") AND ("noisy" OR "SNR") AND ("Indo-Aryan" OR "zero-resource" OR "phonetic")`