

# Out of Distribution detection in 2D semantic segmentation

Lokesh Veeramacheneni

July 23, 2021

- ▶ Deep Uncertainty Quantification (DUQ) - Classification
- ▶ Adaptation idea to semantic segmentation
- ▶ Other OOD detection methods in semantic segmentation

# DUQ - Classification [1]

- ▶ Radial Basis Function (RBF) in final layer with score as uncertainty

$$K = \exp\left[-\frac{\frac{1}{n} \cdot \|W_c \cdot f(x) - e_c\|_2^2}{2 \cdot \sigma^2}\right]$$

- ▶ Update centroids ( $e_c$ ) with the exponential moving average
- ▶ Two sided gradient penalty to avoid *feature collapse*  
 $\lambda[\|\delta \sum_c K_c\|_2^2 - 1]^2$




Figure: DUQ architecture for classification [1]

$$n_{c,t} = \gamma * n_{c,t-1} + (1 - \gamma) * n_{c,t}$$

$$\mathbf{m}_{c,t} = \gamma * \mathbf{m}_{c,t-1} + (1 - \gamma) \sum_i \mathbf{W}_c f_\theta(\mathbf{x}_{c,t,i})$$

$$\mathbf{e}_{c,t} = \frac{\mathbf{m}_{c,t}}{n_{c,t}}$$

Figure: Update equations for the centroids [1]

# DUQ Adaptation - Semantic Segmentation




Figure: Semantic segmentation [2]

# DUQ Adaptation - Semantic Segmentation

- Classification RBF -  $K = \exp\left[-\frac{\frac{1}{n} \cdot \|W_c \cdot f(x) - e_c\|_2^2}{2 \cdot \sigma^2}\right]$




Figure: DUQ for semantic segmentation idea

- Same exponential moving average for centroids can be used

# Other OOD methods for semantic segmentation

- ▶ MetaSeg - Train a NN over the segmentation metrics for segmentation IoU [3].
- ▶ Pixel level OOD for semantic segmentation [4].
- ▶ GAN discriminator based OOD detection [5].
- ▶ More generative models as in [6], [7].

# References



J. van Amersfoort, L. Smith, Y. W. Teh, and Y. Gal, “Uncertainty estimation using a single deep deterministic neural network,”



J. Jordan, “An overview of semantic image segmentation.”



P. Oberdiek, M. Rottmann, and G. A. Fink, “Detection and retrieval of out-of-distribution objects in semantic segmentation,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, June 2020.



M. Angus, K. Czarnecki, and R. Salay, “Efficacy of pixel-level ood detection for semantic segmentation,”



P. Bevandic, I. Kreso, M. Orsic, and S. Segvic, “Discriminative out-of-distribution detection for semantic segmentation,”



E. Nalisnick, A. Matsukawa, Y. W. Teh, D. Gorur, and B. Lakshminarayanan, “Do deep generative models know what they don’t know?,” *arXiv preprint arXiv:1810.09136*, 2018.



D. Li, J. Yang, K. Kreis, A. Torralba, and S. Fidler, “Semantic segmentation with generative models: Semi-supervised learning and strong out-of-domain generalization,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 8300–8311, June 2021.