Exp: 11 Network Address Translation 01/01/2026

AIM:

To Configure & Examine Network Address translation with CISCO PACKET TRACER.

PROCEDURE:

1. Open & Start Cisco packet tracer
2. Add Network devices
   (1 Router, 1 switch, 1PC, 1 server)
3. Connect the devices with a copper straight through cable.
4. Open the Router CLI Tab & configure the interface.
5. Configure Static NAT & Save the configuration
6. Assign IP address & test for connectivity
7. Verify NAT translations & view NAT statistics

RESULT:

Thus, NAT with cisco packet tracer has been configured & verified successfully.

```
C:\> ping 200.1.1.2

Pinging 200.1.1.2 with 32 bytes of data:

Reply from 200.1.1.2: bytes=32 time<1ms TTL=127
Reply from 200.1.1.2: bytes=32 time<1ms TTL=127
Reply from 200.1.1.2: bytes=32 time<1ms TTL=127
Reply from 200.1.1.2: bytes=32 time<1ms TTL=127

Ping statistics for 200.1.1.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss)
```

```
Router# show ip nat statistics

Total active translations: 1 (1 static, 0 dynamic)
Outside interfaces:
  GigabitEthernet0/1
Inside interfaces:
  GigabitEthernet0/0
Hits: 4
Misses: 0
```

```
Router# show ip nat translations

Pro  Inside global   Inside local    Outside local   Outside global
---  200.1.1.100     192.168.1.2     ---             ---
```