# Non-Preemptive Priority Scheduling algorithm

Write a C program to implement the Non-Preemptive Priority Scheduling algorithm. The program should accept number of processes their Arrival Time (AT), Burst Time (BT), and Priority for each process. The process with the highest priority (lowest numerical value) must be executed first among those that have arrived. Calculate the Average Waiting Time and Average Turnaround Time.

**Input Format**

The first line contains an integer representing the number of processes.

The next lines contain three integers for each process, where

- The first integer denotes the Arrival Time (AT)
- The second integer denotes the Burst Time (BT)
- The third integer denotes the Priority of the process.

A lower numerical value indicates a higher priority.

**Output Format**

The output displays the Average Turnaround Time and the Average Waiting Time.

**Example 1**

**Sample Input 1**

3

0 5 2

1 3 1

2 2 3

**Sample Output 1**

Enter number of processes:

Enter AT, BT and Priority for P1:

Enter AT, BT and Priority for P2:
Enter AT, BT and Priority for P3:

Average Turnaround Time = 6.67

Average Waiting Time = 3.33

**Example 2**

**Sample Input 2**

4

0 4 3

0 3 1

2 2 4

5 1 2

**Sample Output 2**

Enter number of processes:

Enter AT, BT and Priority for P1:

Enter AT, BT and Priority for P2:

Enter AT, BT and Priority for P3: Enter

AT, BT and Priority for P4:

Average Turnaround Time = 5.25

Average Waiting Time = 2.75

# CODE:

```
#include <stdio.h>
int main(){
   int n, completed = 0, time = 0;

   printf("Enter number of processes: \n");
   scanf("%d", &n);

   int at[n], bt[n], priority[n], done[n];
   int ct[n], tat[n], wt[n]; float avgtat
   = 0, avgwt = 0;

   // Input
   for (int i = 0; i < n; i++)
   { printf("Enter AT, BT and Priority for P%d: \n", i + 1);
      scanf("%d %d %d", &at[i], &bt[i], &priority[i]);
      done[i] = 0;
   }

   // Scheduling while
   (completed < n)
   { int idx = -1; int
      highPriority = 9999;

      for (int i = 0; i < n; i++)
      { if (at[i] <= time && done[i] == 0)
         { if (priority[i] < highPriority)
            { highPriority = priority[i];
               idx = i;
            }
         }
      }

      if (idx != -1)
      { time += bt[idx];

         ct[idx] = time; tat[idx] =
         ct[idx] - at[idx]; wt[idx] =
         tat[idx] - bt[idx];

         done[idx] = 1;
         completed++; }else
```

```
        { time++; // CPU idle
        }
    }

    // Averages for (int i =
    0; i < n; i++)
    { avgtat += tat[i];
        avgwt += wt[i];
    }

    printf("\nAverage Turnaround Time: %.2f\n", avgtat / n); printf("Average
    Waiting Time: %.2f\n", avgwt / n);

    return 0;
}
```

**OUTPUT:**

Custom Test Success

Input :

```
3
0 5 2
1 3 1
2 2 3
```

Expected Output :

```
Enter number of processes:
Enter AT, BT and Priority for P1:
Enter AT, BT and Priority for P2:
Enter AT, BT and Priority for P3:

Average Turnaround Time = 6.67
Average Waiting Time = 3.33
```

Output :

```
Enter number of processes:
Enter AT, BT and Priority for P1:
Enter AT, BT and Priority for P2:
Enter AT, BT and Priority for P3:

Average Turnaround Time = 6.67
Average Waiting Time = 3.33
```