

SIMATS ENGINEERING (SAVEETHA SCHOOL OF ENGINEERING)

Department of Computer Science and Engineering

ASSESSMENT TOOL 1 – Coding Challenge Task

Course Code:	CSA06	Course Title:	Design and Analysis of Algorithms
CO Assessed:	CO4: Articulation (BL4, BL5)	Assessment:	Assessment Tool 1 – Coding Challenge Task
Weightage:	40% of CIA	Total Marks:	100
CO4 Statement:	Solve optimization problems using dynamic programming and greedy strategies.		
Student Name:	LOKESH S	Reg. No.:	192572151
Section / Batch:	CSE(AI) / 2 ND YEAR	Date:	11/08/2026

Instructions to Students

- Answer the following question. Total Marks: 100.
- Carefully analyze the given questions.
- Write clear code for the given problem.
- Analyze the Time complexity and Space complexity of your code using dynamic programming and greedy strategies

Question Type	Focus Area	Questions
Coding Challenge Task	Focus on Code and analyze optimization problems using dynamic programming and greedy strategies	Q1

SECTION A – Coding Challenge Task

Code of Conduct

I LOKESH S (192572151) (Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment. I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the Student: LOKESH S

RUBRICS FOR CALCULATION

Coding Challenge Task

Criteria	Weightage	Level 4 (Exemplary)	Level 3 (Proficient)	Level 2 (Developing)	Level 1 (Beginning)
Problem Understanding	20%	Clearly understands problem constraints, edge cases, and competitive requirements	Understands problem with minor gaps in constraints	Partial understanding; misses key constraints	Misinterprets problem or constraints
Algorithm	25%	Selects optimal algorithm with best time and space complexity for competitive constraints	Uses efficient algorithm with minor scope for improvement	Uses basic/inefficient approach	No clear algorithmic approach
Code Implementation	20%	Writes correct, efficient, and clean code that passes all constraints	Code works with minor errors or inefficiencies	Partially correct code; fails for some cases	Code does not execute or gives incorrect results
Competitive Performance	20%	Solves problem within time limits and handles large inputs effectively	Solves within acceptable time with minor delays	Struggles with time limits or larger inputs	Unable to solve within time constraints
Test Case Handling	15%	Handles all test cases including edge and hidden cases	Handles most test cases	Misses important edge cases	Fails on multiple test cases

Marks Evaluation:

Criteria	Wt.	Level 4 – Exemplary	Level 3 – Proficient	Level 2 – Developing	Level 1 – Beginning
Problem Understanding	20%				
Algorithm	25%				
Code Implementation	20%				
Competitive Performance	20%				
Test Case Handling	15%				
Total Marks (100):					

Faculty In-charge	Course Coordinator	Head of Department
Name: _____	Name: _____	Name: _____
Signature: _____	Signature: _____	Signature: _____
Date: _____	Date: _____	Date: _____

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz C++ Online Compiler

Programiz PRO >

main.cpp



Share

Run

Output

Clear

```
8   int values[] = {60, 100, 120};
9   int weights[] = {10, 20, 30};
10  int W = 50;
11
12  vector<vector<int>> dp(n + 1, vector<int>(W + 1, 0));
13
14  for (int i = 1; i <= n; i++) {
15      for (int w = 0; w <= W; w++) {
16          if (weights[i - 1] <= w) {
17              dp[i][w] = max(
18                  dp[i - 1][w],
19                  values[i - 1] + dp[i - 1][w - weights[i
20                      - 1]]
21              );
22          } else {
23              dp[i][w] = dp[i - 1][w];
24          }
25      }
26
27      cout << "Maximum Profit = " << dp[n][W] << endl;
28
29      return 0;
30 }
```

Maximum Profit = 220

=== Code Execution Successful ===

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz C++ Online Compiler

Programiz PRO >

main.cpp



Share

Run

Output

Clear

```
3 #include <algorithm>
4 using namespace std;
5
6 int main() {
7     int n = 3;
8     int values[] = {10, 30, 20};
9     int weights[] = {5, 10, 15};
10    int W = 100;
11
12    vector<int> dp(W + 1, 0);
13
14    for (int w = 0; w <= W; w++) {
15        for (int i = 0; i < n; i++) {
16            if (weights[i] <= w) {
17                dp[w] = max(dp[w],
18                    values[i] + dp[w - weights[i]]);
19            }
20        }
21    }
22
23    cout << "Maximum Profit = " << dp[W] << endl;
24
25    return 0;
26 }
```

Maximum Profit = 300

=== Code Execution Successful ===

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz PRO >

Programiz C++ Online Compiler

main.cpp



Share

Run

Output

Clear

```
1 #include <iostream>
2 #include <vector>
3 #include <algorithm>
4 using namespace std;
5
6 int main() {
7     int n = 4;
8
9     int cost[4][4] = {
10         {0, 10, 15, 20},
11         {10, 0, 35, 25},
12         {15, 35, 0, 30},
13         {20, 25, 30, 0}
14     };
15
16     int totalMasks = 1 << n;
17     const int INF = 1000000000;
18
19     vector<vector<int>> dp(totalMasks, vector<int>(n, INF));
20
21     // Start from city 0
22     dp[1][0] = 0;
23
24     for (int mask = 1; mask < totalMasks; mask++) {
```

Minimum Cost = 80

=== Code Execution Successful ===

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz C++ Online Compiler

Programiz PRO >

main.cpp



Share

Run

Output

Clear

```
1 #include <iostream>
2 using namespace std;
3
4 int main() {
5     const int INF = 999999;
6
7     int n = 3;
8
9     int graph[3][3] = {
10         {0, 5, INF},
11         {2, 0, 3},
12         {INF, INF, 0}
13     };
14
15     int dist[3][3];
16
17     // Copy graph
18     for (int i = 0; i < n; i++) {
19         for (int j = 0; j < n; j++) {
20             dist[i][j] = graph[i][j];
21         }
22     }
23
24     // Floyd-Warshall
25     for (int k = 0; k < n; k++) {
26         for (int i = 0; i < n; i++) {
27             for (int j = 0; j < n; j++) {
28                 if (dist[i][k] < INF && dist[k][j] < INF && dist[i][j] > dist[i][k] + dist[k][j])
29                     dist[i][j] = dist[i][k] + dist[k][j];
30             }
31         }
32     }
```

Shortest Distance Matrix:

```
0 5 8
2 0 3
INF INF 0
```

=== Code Execution Successful ===

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz C++ Online Compiler

Programiz PRO >

main.cpp



Share

Run

Output

Clear

```
1 #include <iostream>
2 #include <vector>
3 #include <climits>
4 using namespace std;
5
6 int main() {
7     int n = 3;
8
9     int keys[] = {10, 12, 20};
10    int freq[] = {34, 8, 50};
11
12    vector<vector<int>> dp(n, vector<int>(n, 0));
13
14    // Prefix sum for frequencies
15    vector<int> prefix(n + 1, 0);
16
17    for (int i = 0; i < n; i++) {
18        prefix[i + 1] = prefix[i] + freq[i];
19    }
20
21    auto sum = [&](int i, int j) {
22        return prefix[j + 1] - prefix[i];
23    };
24
25    // DP Table
```

Minimum Cost = 142

=== Code Execution Successful ===

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz C++ Online Compiler

Programiz PRO >

main.cpp



Share

Run

Output

Clear

```
1 #include <iostream>
2 #include <algorithm>
3 using namespace std;
4
5 struct Item {
6     int value;
7     int weight;
8     double ratio;
9 };
10
11 int main() {
12     int n = 3;
13
14     Item items[] = {
15         {60, 10, 0},
16         {100, 20, 0},
17         {120, 30, 0}
18     };
19
20     int W = 50;
21
22     // Calculate value/weight ratio
23     for (int i = 0; i < n; i++) {
24         items[i].ratio =
```

Maximum Profit = 240

=== Code Execution Successful ===

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz C++ Online Compiler

Programiz PRO >

main.cpp



Share

Run

Output

Clear

```
12  for (int i = 0; i < n; i++) {
13      pq.push(freq[i]);
14  }
15
16  int totalCost = 0;
17
18  while (pq.size() > 1) {
19      int a = pq.top();
20      pq.pop();
21
22      int b = pq.top();
23      pq.pop();
24
25      int combined = a + b;
26
27      totalCost += combined;
28
29      pq.push(combined);
30  }
31
32  cout << "Minimum Cost = " << totalCost << endl;
33
34  return 0;
35 }
```

Minimum Cost = 124

=== Code Execution Successful ===

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz C++ Online Compiler

Programiz PRO >

main.cpp



Run

Output

Clear

```
1 #include <iostream>
2 #include <queue>
3 #include <string>
4 using namespace std;
5
6 struct Node {
7     char ch;
8     int freq;
9     Node *left, *right;
10
11     Node(char c, int f) {
12         ch = c;
13         freq = f;
14         left = right = nullptr;
15     }
16 };
17
18 struct Compare {
19     bool operator()(Node* a, Node* b) {
20         return a->freq > b->freq;
21     }
22 };
23
24 void generateCodes(Node* root, string code) {
25
```

Huffman Codes:

A -> 00

B -> 01

C -> 10

D -> 11

=== Code Execution Successful ===

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz C++ Online Compiler

Programiz PRO >

main.cpp



Share

Run

Output

Clear

```
1 #include <iostream>
2 #include <vector>
3 #include <algorithm>
4 using namespace std;
5
6 struct Edge {
7     int u, v, weight;
8 };
9
10 class DSU {
11     vector<int> parent, rank;
12
13 public:
14     DSU(int n) {
15         parent.resize(n);
16         rank.resize(n, 0);
17
18         for (int i = 0; i < n; i++)
19             parent[i] = i;
20     }
21
22     int find(int x) {
23         if (parent[x] != x)
24             parent[x] = find(parent[x]);
25     }
```

```
0 - 1 : 2
1 - 3 : 2
0 - 2 : 3
MST Cost = 7
```

=== Code Execution Successful ===

Stop copy pasting code you don't actually understand

Build the coding confidence you need to become a developer companies will fight for

Become a PRO

Programiz C++ Online Compiler

Programiz PRO >

main.cpp



Run

Output

Clear

```
38         minKey = key[v];
39         u = v;
40     }
41 }
42
43 visited[u] = true;
44 mstCost += key[u];
45
46 // Update adjacent vertices
47 for (int v = 0; v < n; v++) {
48
49     if (graph[u][v] != 0 &&
50         !visited[v] &&
51         graph[u][v] < key[v]) {
52
53         key[v] = graph[u][v];
54     }
55 }
56 }
57
58 cout << "MST Cost = " << mstCost << endl;
59
60 return 0;
61 }
```

MST Cost = 6

=== Code Execution Successful ===