```
#include<stdio.h>
#include<stdlib.h>
int main()
{
   int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
   printf("Enter the number of Requests\n");
   scanf("%d",&n);
   printf("Enter the Requests sequence\n");
   for(i=0;i<n;i++)
    scanf("%d",&RQ[i]);
   printf("Enter initial head position\n");
   scanf("%d",&initial);
   printf("Enter total disk size\n");
   scanf("%d",&size);
   printf("Enter the head movement direction for high 1 and for low 0\n");
   scanf("%d",&move);

   // logic for C-look disk scheduling

      /*logic for sort the request array */
   for(i=0;i<n;i++)
   {
      for( j=0;j<n-i-1;j++)
      {
         if(RQ[j]>RQ[j+1])
         {
            int temp;
            temp=RQ[j];
            RQ[j]=RQ[j+1];
            RQ[j+1]=temp;
         }
```

```
    }
}

int index;
for(i=0;i<n;i++)
{
    if(initial<RQ[i])
    {
        index=i;
        break;
    }
}

// if movement is towards high value
if(move==1)
{
    for(i=index;i<n;i++)
    {
        TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
        initial=RQ[i];
    }

    for( i=0;i<index;i++)
    {
         TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
         initial=RQ[i];

    }
}
// if movement is towards low value
```

```
    else
    {
       for(i=index-1;i>=0;i--)
       {
          TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
          initial=RQ[i];
       }

       for(i=n-1;i>=index;i--)
       {
           TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
           initial=RQ[i];

       }
    }

    printf("Total head movement is %d",TotalHeadMoment);
    return 0;
}
```

