```c
#include<stdio.h>
#include<stdlib.h>
#include<unistd.h>
#include<string.h>
#include<sys/wait.h>

int main()
{
   int pipe1[2], pipe2[2];
   pid_t pid;
   char pathname[100];
   char buffer[1024];
   int n;

   // Create two pipes
   if (pipe(pipe1) == -1 || pipe(pipe2) == -1)
   {
      perror("pipe");
      exit(1);
   }

   // Create child process
   pid = fork();

   if (pid < 0)
   {
      perror("fork");
      exit(1);
   }

   // ---------- PARENT PROCESS ----------
```

```
if (pid > 0)
{
   // Close unused ends
   close(pipe1[0]);   // Parent writes to pipe1
   close(pipe2[1]);   // Parent reads from pipe2

   // Enter pathname
   printf("Enter the pathname of the file: ");
   scanf("%s", pathname);

   // Write pathname to first pipe
   write(pipe1[1], pathname, strlen(pathname) + 1);

   // Close writing end
   close(pipe1[1]);

   // Read file contents from second pipe
   printf("\nContents of the file:\n");

   while ((n = read(pipe2[0], buffer, sizeof(buffer) - 1)) > 0)
   {
      buffer[n] = '\0';
      printf("%s", buffer);
   }

   close(pipe2[0]);

   // Wait for child
   wait(NULL);
}
```

```
// ---------------- CHILD PROCESS ----------------
else
{
   FILE *fp;

   // Close unused ends
   close(pipe1[1]);   // Child reads from pipe1
   close(pipe2[0]);   // Child writes to pipe2

   // Read pathname from first pipe
   read(pipe1[0], pathname, sizeof(pathname));

   close(pipe1[0]);

   // Open the file
   fp = fopen(pathname, "r");

   if (fp == NULL)
   {
      char *msg = "Error: File cannot be opened.\n";
      write(pipe2[1], msg, strlen(msg));
      close(pipe2[1]);
      exit(1);
   }

   // Read file and send contents through second pipe
   while (fgets(buffer, sizeof(buffer), fp) != NULL)
   {
      write(pipe2[1], buffer, strlen(buffer));
   }
```

```
        fclose(fp);
        close(pipe2[1]);


        exit(0);
    }


    return 0;
}
```

OUTPUT -

