Address Book Management System

Bash Shell Scripting – Code Without Hash Comments

Source Code

```
FILE="addressbook.txt"

createAddressBook()
{
    if [ -e "$FILE" ]; then
        echo "Address book already exists."
    else
        touch "$FILE"
        echo "Address book created."
    fi
}

viewAddressBook()
{
    if [ ! -s "$FILE" ]; then
        echo "Address book is empty or does not exist."
    else
        echo "---- Address Book ----"
        cat "$FILE"
    fi
}

insertRecord()
{
    echo "Enter record in format: LastName,FirstName,Email,Phone"
    read record
    echo "$record" >> "$FILE"
    echo "Record inserted."
}

deleteRecord()
{
    echo "Enter a search string (e.g. name or email) to find the record to delete:"
    read search

    grep -n "$search" "$FILE"

    echo "Enter line number to delete:"
    read line

    sed -i "${line}d" "$FILE"

    echo "Record deleted."
}

modifyRecord()
{
    echo "Enter a search string (e.g. name or email) to find the record to modify:"
    read search

    grep -n "$search" "$FILE"

    echo "Enter line number to modify:"
    read line

    echo "Enter new record (LastName,FirstName,Email,Phone):"
    read newRecord

    sed -i "${line}s/.*/${newRecord}/" "$FILE"

    echo "Record modified."
}

exitProgram()
{
    echo "Exiting... Goodbye!"
    exit 0
}

while true; do
    echo
```

```
    echo "======= Address Book Menu ======="
    echo "1. Create Address Book"
    echo "2. View Address Book"
    echo "3. Insert a Record"
    echo "4. Delete a Record"
    echo "5. Modify a Record"
    echo "6. Exit"

    echo "Enter your choice:"
    read choice

    case $choice in
        1) createAddressBook ;;
        2) viewAddressBook ;;
        3) insertRecord ;;
        4) deleteRecord ;;
        5) modifyRecord ;;
        6) exitProgram ;;
        *) echo "Invalid choice. Please select 1-6." ;;
    esac

done
```