

Liivv — Architecture

For: IT / security review of the **application** (current stack)

From: Liivv — the people who built the app and who administer the BigCommerce store

App: Next.js 16 storefront (core/) + Liivv health and pharmacy extensions

Date: September 2026

Status: Current — Vercel + BigCommerce + Canadian Supabase + Stripe

PDF: [Liivv-Architecture.pdf](#)

This pack is **us talking to IT**. It describes **today's** app on **Vercel**. We do not claim Azure products we are not running. Where an Azure product has an equivalent in this app (API gateway layer, encrypted secrets, pharmacist login), that is what we show.

Gaps are labeled **We** (we change the app or a vendor setting) or **IT** (tell us if this is a requirement). There is no separate engineering / ops / legal team in this conversation.

Contents

The security story is **\$2** → **\$3** → **\$4** (map, still missing, already defended). **\$1** is the ask. **\$5–\$14** is how the app works.

§	Section	Job
1	What we are asking you to review	Why IT is scoring this app (leak, fake payment, key in the page)
2	Layers → Liivv today	Map — what pieces exist
3	Open gaps	What is still missing (G1 , G5)
4	Controls S1–S9	What is already defended , including vendor down
5	Systems of record	Who owns shop vs health vs cards
6	Trust boundary	Who is untrusted; /api gateway + action gateway
7	How the app talks to the database	Browser never opens Supabase; service role + RLS
8	Identity and pharmacist admin	Shopper login vs pharmacist admin
9	Health Canada DPD	Public drug catalog proxy — not PHI
10	Other systems (short)	Store engine; AI assistant is off
11	System context	Picture of callers and vendors
12	Data flows	Sequences: checkout, renewals, chat
13	Auth cookies and secrets	Cookies, webhook secrets, env vars
14	Evidence paths (code)	File paths if they want to look at the repo

1. What we are asking you to review

Liivv is a **Next.js 16** app (App Router) on **Vercel**. Shoppers see one site. The **browser is not the database client**. Next.js is the only process that holds service-role, admin, and payment secrets.

You are scoring whether **this application** would be a leak or jump-off point: can a shopper or random caller read PHI, fake a payment, or walk into a database with a key from the page?


IT often scores an Azure web app → API gateway → microservices → SQL **in the same estate**. Liivv is one Node runtime that calls **vendors** (BigCommerce, Supabase, Stripe) over TLS. Same **idea**: only the server talks to the database. Different **platform**. The **block diagram** is in §2.

Residual (true of that Azure pattern too): if someone steals the **server** secret (Supabase service role, BC admin token, Stripe secret), row rules on the database do not stop them. Mitigation is secret hygiene and never putting those keys in the browser — not “the database cannot be hacked.”

2. Layers → Liivv today

Map only. What the system is made of. What is still missing and what is already defended are §3 and §4.

IT's usual picture is **layers**: people → web app → gateway → services → SQL, plus identity, vault, CI/CD, and logging. Liivv uses the **same layers**. The picture below is that drawn for **this** app.



Liivv layers left to right: people, Next.js hosting with session wrapper and API gateway inside it, vendor data.

One picture, **five lanes**. The /api gateway arrows go to the **same vendor boxes** as shopping and health (they may cross). Identity (purple chips) is **BigCommerce** for shoppers and a **shared pharmacist login** for the Rx/chat admin. Both yellow boxes sit **inside** Hosting — they are Next.js code, the APIM-shaped layer in this app. Secrets are **Vercel encrypted env vars** (that is how this host injects keys; Azure Key Vault is not a Vercel setting).

Lane	What it says
Public shop → BigCommerce	No login needed. Cart is saved in BigCommerce . Cookie = cart id only.
Checkout → Stripe	BC login required , then Stripe (no PAN). Renewals: Stripe bills → BC order.
Account → action gateway → Supabase PHI	Health, insurance, Rx, chat. Page points in to the yellow action gateway (runCustomerAction); gateway points out to PHI. No session, no write. Not /api.
Pharmacist admin → action gateway → Supabase PHI	Approve prescriptions and answer care chat. Lives in a BigCommerce admin iframe (/pharmacy-admin). After BC opens the app, additional shared username/password at /pharmacy-admin/login.

Lane	What it says
Callers → Liivv API gateway	Azure APIM equivalent. Every <code>/api</code> hit first. Unknown = 404. One line then splits: Health Canada DPD , and around to BigCommerce , Stripe , and Supabase (chat count only). Gateway policies in \$6 .

How to read the layers: A typical Azure app splits **web app**, **API gateway**, and **backend services**. Liivv is **one** Next.js process. The **yellow** boxes are our two doors (**action gateway** for PHI form posts, **API gateway** for `/api`). Shop and checkout **skip** the action gateway. SQL sits at **vendors**, not next to the app.

Layer	Liivv today
Web app	Next.js 16 on Vercel (HTML, account dashboard, pharmacist admin)
API gateway	Liivv API gateway — Azure APIM equivalent. Every <code>/api/*</code> hits it first. Unknown = 404. Rate limit + per-route policy. PHI form posts use the action gateway , not <code>/api</code> .
Form posts (server actions)	Liivv action gateway (<code>core/lib/action-gateway/</code>): PHI / staff / account-kit writes <code>runCustomerAction</code> or <code>runStaffAction</code> first. Guest cart is not in this wrapper.
Backend microservices	One Node runtime, not a mesh of services
SQL in the estate	Canadian Supabase Postgres (PHI). Shop data in BigCommerce . Not Azure SQL next to the app
Identity / SSO / MFA	Shoppers: BigCommerce login. Pharmacists: BC control-panel iframe + shared Liivv login (password in Vercel encrypted env). Entra: see \$3 G1
Secrets / vault	Vercel encrypted env vars (required to host). Azure Key Vault is not how Vercel injects secrets
Rate limiting	Every <code>/api</code> : 120 / IP / min, one shared counter. DPD also 60 / IP / min
Webhook auth	Stripe signature; BC Bearer secret
CI/CD	GitHub → Vercel production . Preview is local (Cursor / <code>.env.local</code>), not Vercel Preview
Veracode, Sonar, CrowdStrike	Not in this pipeline — see \$3 G5
Logging	Vercel logs + Analytics + Speed Insights. No care-chat bodies in logs — see \$4
Backup / RPO	Supabase daily backups + restore — see \$4
Vendor down	Degraded UI per system (notice, not 500), not failover — see \$4
Email	BigCommerce transactional mail

3. Open gaps

Still missing. Everything already defended is in **\$4** next.

ID	Gap	Today	We / IT
G1	Entra SSO / MFA on Liivv	Shopper login is BigCommerce. Pharmacist admin is BC iframe + one shared login (password in Vercel encrypted env).	IT: Entra needs your approval. We cannot turn it on ourselves.
G5	Veracode / Sonar / CrowdStrike	Not in this repo's pipeline	IT: say if these scanners are required. Not in our pipeline today.

4. Controls S1–S9

Already defended.

ID	Topic	If left unchecked	Status	Control
S1	Who can query Supabase	High	In place	No DB key in the browser. RLS deny-by-default; no anon/authenticated policies. Service role only on the Next.js server. App uses HTTPS (PostgREST) — see notes below.
S2	Where health data lives	High	In place	PHI in Canadian Supabase. Transfer or fax only. Vendor DPAs/BAA's in place. Daily backups + restore steps below.
S3	Pharmacist access	Med	In place	BC iframe load session + shared username/password at /pharmacy-admin/login. Password in Vercel encrypted env. Rate-limited. Entra is still open (\$3 G1).
S4	AI chat assistant	Med	Off	VIRTUAL_CARE_BOT_ENABLED=false. Remains off. We can use IT resources later if we decide to implement it.
S5	Environment secrets	Med	In place	Vercel encrypted env + gitignored .env.local. Only production keys on Vercel; no Vercel Preview (local preview is Cursor).
S6	Pharmacist admin framing	Med	In place	Inside BigCommerce admin iframe (/pharmacy-admin). Cookies SameSite=None for the embed. Extra shared login after BC opens the app.
S7	Customer email	Low	In place	BigCommerce transactional mail.
S8	Medication search (DPD)	Low	In place	Gateway policy dpd-public + server proxy. All /api 120/IP/min; DPD also 60/IP/min; one shared counter.
S9	API gateway	Med	In place	Liivv API gateway on every /api/* (deny unknown; rate limit; per-route policy) plus action gateway on PHI / staff form posts.

Also in place: Stripe and BigCommerce webhooks verified; cart ID in a signed JWT; care-chat **message bodies are not** written to Vercel logs (core/lib/chat/logging-policy.ts).

S1 notes — Supabase network path

core/lib/supabase/client.ts uses supabase-js over HTTPS (PostgREST). There is no direct Postgres connection string in the app.

Supabase “Network Restrictions” cover only Postgres and the pooler — not HTTPS APIs. Locking Postgres to Vercel egress IPs would not gate the path this app uses. The real path is protected by: no browser key, RLS deny-by-default, and service role only on the server.

Optional (Postgres/pooler only, if IT still wants it): enable Vercel Static IPs, then allow those CIDRs under Supabase → Database → Network Restrictions. Without static egress, Vercel outbound IPs change and an allowlist will break production. Local Cursor/SQL tools would need their own allowlisted egress too.

S2 notes — Backup / RPO (restore after data loss)

Not the same as “vendor down” (degraded UI below). This is restore after data loss.

Mode	What it is	Typical RPO
Daily backups	Automatic on Pro / Team / Enterprise; retention depends on plan	Up to ~24 hours of loss
Point-in-Time Recovery (PITR)	Paid add-on	Worst case ~2 minutes (per Supabase docs)

Liivv target: accept daily-backup RPO (~24h) unless PITR is enabled. Owner: Liivv app admins (Supabase project access), not IT Azure ops.

Restore (daily backup): Supabase Dashboard → Database → Backups → pick timestamp → restore → verify shopper health/Rx/chat and /pharmacy-admin → note restore time for IT if reportable. PITR optional under project add-ons. BigCommerce / Stripe recovery is those vendors’ own backups.

Care-chat logging

Do not write care-chat message bodies, appointment free-text, or voice transcripts to stdout / Vercel logs. Enforcement: logChatOperationalError in core/lib/chat/logging-policy.ts. Messages live in Canadian Supabase; staff read them in /pharmacy-admin.

Vendor down (availability — not backup)

If a vendor is unreachable, the app does not fail over to a second copy. There is no replica shop, no second Stripe, no second BigCommerce. The Next.js app degrades: remaining vendors still work; the shopper sees a plain-language notice instead of a generic 500.

What we implemented (storefront): catch a vendor that is unreachable (network / 502–504), and return a notice. Env vars missing (“not configured”) is a different case from “configured but down.”

Down	Shop / cart	Checkout pay	Account health / pharmacist
BigCommerce	Friendly “store unavailable” (catalog, cart, and checkout all need BC)	No	Login / account chrome needs BC

Down	Shop / cart	Checkout pay	Account health / pharmacist
Supabase	Yes (subscribe + curated kit add UI hidden; existing sub cart lines cannot check out)	One-time pay still works; subscriptions and cart kits disabled site-wide	Health profile, pharmacy, care chat, pharmacist queues: unavailable — not a 500; Account → Subscriptions shows unavailable
Stripe	Yes (subscribe UI hidden)	Payment section: “payments unavailable”; cart is kept; subscriptions disabled	Health ok; subscription list unavailable
Vercel	Whole site down		

Where in the app: `core/lib/vendor-outage/` (detect + copy). BigCommerce GraphQL failures wrap to that error. Supabase HTTPS failures degrade `health/pharmacy/chat`. Checkout probes Stripe and disables pay if Stripe does not answer (`core/lib/stripe/availability.ts`). **Subscriptions** require Stripe reachable and (when configured) Supabase reachable (`core/lib/subscriptions/availability.ts`) — PDP / product cards hide Subscribe, add-to-cart refuses subscription, Account → Subscriptions and checkout with subscription lines degrade. **Cart kits** require Supabase reachable when configured (`core/lib/kit/availability.ts`) — curated kit PDP and add-kit-to-cart are disabled (`cart_kit_sessions`).

What the app does when each system is down

This is **not** G9 (restore after data loss). Shopper copy is the notice above. Background behavior is separate — especially **renewals**, which do **not** go through the checkout page.

If BigCommerce is down

- **This website:** catalog, cart, checkout, and account login cannot load. Shopper sees “The store is temporarily unavailable.”
- **Renewals:** Stripe still owns the card and still charges the due cycle. They POST `invoice.paid` to `/api/stripe/webhook`. We try to create the BigCommerce shop order. If BC is still down, we return **5xx** so Stripe retries for about **three days**. A retry of the same invoice does **not** skip just because we already queued it — we try the shop order again. We ack 200 only when the BC order already exists, or the rest of that day’s shipment batch is still unpaid. There is **no** extra sweeper. **Account** → **Subscriptions** can also retry a due batch. After Stripe stops retrying, a Dashboard resend of `invoice.paid` is the manual path.

If Stripe is down

- **This website:** browse and cart still work. **Subscribe is hidden** site-wide (PDP, product cards, account subscriptions, care bot). Checkout cannot take a **new** payment. Shopper sees “Payments are temporarily unavailable”; **the cart is kept**. Account health still loads.
- **Renewals:** Stripe Billing still owns the card on file. If Stripe’s billing was down and then returns, they still generate that cycle’s invoice and charge. Then they POST `invoice.paid` and we create the BC order. Storefront “payments unavailable” only means **this website** cannot start a **new** checkout with Stripe.

If Supabase is down

- **This website:** shop, cart, and **one-time** checkout still work. **Subscriptions are disabled** site-wide (same as Stripe down for subscribe UI / new sub checkout / Account → Subscriptions). **Curated cart kits are**

disabled (PDP customizer + add kit to cart — `cart_kit_sessions`). Health profile, pharmacy, care chat, and pharmacist queues show “Health tools are temporarily unavailable” — not a 500.

- **Renewals:** Stripe still charges. The shop order is still created in BigCommerce. If shipment-batch records cannot be written (they live in Supabase when it is configured), the webhook returns 5xx and Stripe retries the same way as BC-down, for about three days.

If Vercel is down

- **This website:** the whole app is unreachable (shop, account, pharmacist, `/api`).
- **Renewals:** Stripe still charges on their side. `invoice.paid` cannot reach us until Vercel is back; Stripe retries that webhook for about three days. Same retry/idempotent shop-order rules as above once we are up.

Not claimed: multi-region failover, a second vendor, or “the whole site stays up no matter which vendor is down.”

5. Systems of record

Shoppers see one site. **Commerce and health data use different systems of record.**

- **BigCommerce** — catalog, cart, checkout, orders, customer login, most customer email.
- **Supabase** — Canadian Postgres (`ca-central-1`): profile, insurance, prescriptions, CarePack, care chat.
- **Stripe** — card charges and subscriptions. PAN / CVC **never** stored in Liivv.

Orders are not stored in Supabase. Health records are not stored in BigCommerce.

Diagram: How a visit splits: customer shops on Liivv, then shopping goes to BigCommerce and health records go to Supabase

Function	System	Boundary
Catalog, cart, checkout, order of record	BigCommerce	Shop engine — not health records
Health profile, insurance, prescriptions, care chat	Supabase	Canadian Postgres — not the shop
Card charges and subscriptions	Stripe	Payment processor — PAN / CVC never stored

Domain	System of record	Notes
Storefront hosting	Vercel	Next.js 16 — not a data store of record
Products, categories, prices	BigCommerce	Synced to Stripe prices via BC webhooks
Customers (login identity)	BigCommerce	Linked in Supabase <code>profiles.bigcommerce_customer_id</code>
Cart / checkout cart	BigCommerce GraphQL	Cart ID in signed Auth.js / anonymous JWT

Domain	System of record	Notes
Orders	BigCommerce	Admin REST after Stripe success
Payment methods & subscriptions	Stripe	Renewals charge at Stripe; Liivv creates the BC order on <code>invoice.paid</code> (see \$4 — Stripe retries the shop order if BC or the webhook was down)
Health profile, insurance, Rx, CarePack, chat	Supabase	Not modeled in BC; pharmacist queue in <code>/pharmacy-admin</code> (BC admin iframe)


PII (personally identifiable information) is who they are: name, email, address, BC customer id — BigCommerce + Supabase profiles.

PHI is who they are **plus** health: insurance, Rx, CarePack, chat — Supabase only.

Canadian privacy frame is **PIPEDA** (and **PHIPA** in Ontario). HIPAA is a US statute; we do not claim HIPAA because we listed a Canadian region.

6. Trust boundary

The browser never receives service keys. Next.js on Vercel is the only secret holder.



Vercel is **hosting**, not a system of record. Secrets live in the Vercel project (encrypted) and gitignored `.env.local`.

There are **two** app-layer front doors (both **in place**, closed **G4**):

1. **Liivv API gateway** — every `/api/*` request (proxy).
2. **Liivv action gateway** — PHI / staff / account-kit **server actions** (form posts). They never hit the `/api` gateway.

Liivv API gateway

App-layer API gateway (Azure APIM equivalent). The Liivv API gateway in the Next.js proxy (`core/proxy.ts` → `core/lib/api-gateway/`) is that layer **in this app**. **Every** `/api/*` request hits it **before** the route. Unknown paths are **denied**. Allowlisted paths are **rate-limited** (120 / IP / min, shared counter), then get a policy:

Policy	Paths	What the gateway checks
customer-session	<code>/api/account/*</code> , <code>/api/live-chat/*</code>	Logged-in BigCommerce customer (session). No session → 401. Plus the all- <code>/api</code> rate limit (120 / IP / min).
webhook-stripe	POST <code>/api/stripe/webhook</code>	<code>stripe-signature</code> header present. Route still verifies the signature. Plus the all- <code>/api</code> rate limit (120 / IP / min).
webhook-bigcommerce	POST <code>/api/bigcommerce/webhook</code>	Authorization: Bearer matches the webhook secret. Plus the all- <code>/api</code> rate limit (120 / IP / min).
dpd-public	<code>/api/medications/*</code>	All- <code>/api</code> rate limit (120 / IP / min), then a tighter 60 / IP / min. Catalog only — no PHI.
bc-app-handshake	<code>/api/bigcommerce/app/*</code>	Allowlisted. Signed load token is verified in the route. Plus the all- <code>/api</code> rate limit (120 / IP / min).
auth-public	<code>/api/auth/*</code>	Login endpoints. Must stay reachable or nobody can sign in. Plus the all- <code>/api</code> rate limit (120 / IP / min).
storefront-public	<code>/api/products/*</code> , <code>/api/categories/*</code> , <code>/api/cart/*</code> , <code>/api/customer/*</code> , <code>/api/archive/*</code>	Public shop data. Server holds BC tokens. Plus the all- <code>/api</code> rate limit (120 / IP / min).
(none — denied)	Any other <code>/api/...</code>	404 . Not on the allowlist.

Each `/api` route and its policy

Route	Policy
POST <code>/api/stripe/webhook</code>	webhook-stripe
POST <code>/api/bigcommerce/webhook</code>	webhook-bigcommerce

Route	Policy
GET /api/bigcommerce/app/auth	bc-app-handshake
GET /api/bigcommerce/app/load	bc-app-handshake
GET /api/bigcommerce/app/uninstall	bc-app-handshake
GET /api/medications/search	dpd-public
GET /api/medications/[drugCode]/details	dpd-public
GET /api/live-chat/unread-count	customer-session
POST /api/account/notifications/mark-read	customer-session
/api/auth/* (NextAuth login)	auth-public
GET /api/products/[entityId]	storefront-public
GET /api/products/ids	storefront-public
GET /api/products/group/[group]	storefront-public
GET /api/categories/search	storefront-public
GET /api/categories/by-ids	storefront-public
GET /api/categories/products	storefront-public
GET /api/cart/line-item-count	storefront-public
GET /api/customer/group	storefront-public
GET /api/customer/groups	storefront-public
GET /api/archive/diabetes-care/[section]	storefront-public

Liivv action gateway

Second front door — not /api. Health and pharmacy **writes** are Next.js **server actions** (form posts) on /account/..., /liivv-health, and /pharmacy-admin. They **never** go through core/proxy.ts or the API gateway. Instead each sensitive action calls **runCustomerAction** or **runStaffAction** first (core/lib/action-gateway/session.ts). No session → no service-role write.

This is **session enforcement**, not rate limiting. Rate limits live on the API gateway. The action gateway answers: “Is this caller a signed-in shopper or staff before we touch Supabase PHI?”

Wrapper	Who	What the gateway checks	If there is no session
runCustomerAction	Shopper PHI and account kits	Auth.js / BigCommerce customer via getOnboardingCustomer()	Return an error result, or redirect to login

Wrapper	Who	What the gateway checks	If there is no session
<code>runStaffAction</code>	/pharmacy-admin queue and chat	BC iframe session and shared pharmacist session (<code>hasStaffAccess()</code>)	{ ok: false, error: 'Unauthorized.' }

withAuth still redirects **GET** /account/... to login (page load). The action gateway is what stops a **POST** (the actual write) if the session is missing or forged.

Each wrapped server action

Action (module)	Wrapper	Data touched
<code>saveHealthProfileStep</code>	<code>runCustomerAction</code>	Health profile (PHI)
<code>saveInsuranceStep</code>	<code>runCustomerAction</code>	Insurance (PHI)
<code>pharmacyAction</code>	<code>runCustomerAction</code>	Prescriptions / transfers (PHI)
<code>virtualCareChatAction</code> , <code>virtualCareAppointmentAction</code> , chat voice / unread helpers	<code>runCustomerAction</code>	Care chat + appointments (PHI)
<code>renameSavedKitAction</code> , <code>deleteSavedKitAction</code> , <code>addSavedKitToCartAction</code>	<code>runCustomerAction</code>	Saved kits (account)
<code>saveSignedInLandingQuiz</code> , <code>applyPendingGuestHealthProfile</code>	<code>runCustomerAction</code>	Onboarding answers → profile
<code>staffPortalAction</code> , <code>loadOlderStaffChatMessagesAction</code>	<code>runStaffAction</code>	Pharmacist queue + staff chat

Not in this wrapper (by design)

Kind	Examples	Why
Guest / shop commerce	Cart line updates, product wishlist, guest stash of quiz answers before login	Commerce or pre-auth; not a PHI write under the service role for a known customer
Checkout / Stripe	<code>initializePayment</code> , subscription portal actions	Payment path; session/cart checks live in those modules, not the PHI action gateway
Public contact / auth forms	Contact form, register, change password	Not Supabase PHI via service role

Guest cart / product buttons are **not** wrapped — those are commerce, not PHI.

Azure APIM as a named Azure SKU would need Azure hosting; we are on Vercel. The two gateways above are the APIM-shaped layer **in this app (in place)**.

7. How the app talks to the database

The browser **never** opens Supabase.

1. Customer or pharmacist hits Next.js (public shop, /account/... **dashboard**, or /pharmacy-admin inside BC admin).
2. Next.js checks the session through the **Liivv action gateway** (runCustomerAction / runStaffAction) — Auth.js / BigCommerce customer, or **BC iframe session + shared pharmacist session**.
3. **Only then** the server uses SUPABASE_URL + **service role** ([core/lib/supabase/client.ts](#) is server-only).
4. Table access is server modules (profiles, health, insurance, prescriptions, chat) — not a connection string in JavaScript shipped to the shopper.

Row Level Security (RLS) is **on**, with **no** anon/authenticated policies (deny by default). That stops a stolen **browser/anon** path from reading tables. The **service role bypasses RLS** — same class of risk as any API using a privileged SQL login. RLS is not “Supabase cannot be hacked.”

PHI forms are **not** on the homepage. Profile, health, insurance, pharmacy, and care chat are in the **logged-in account dashboard**. Those writes go through the action gateway before the service role.

8. Identity and pharmacist admin

Who	How they get in	What they see
Customer	BigCommerce login (Auth.js session)	Public shop; after login, account dashboard
Anonymous shopper	Signed cart cookie	Catalog and cart only
Pharmacist	BC admin iframe (/pharmacy-admin load) + shared username/password at /pharmacy-admin/login	Approve prescriptions, customers, care chat

Pharmacist admin lives **inside the BigCommerce control panel** as an iframe app (/pharmacy-admin). Opening it verifies BC’s signed load token and sets `liivv_pharmacy_admin`. Then pharmacists enter **one** shared username and password (`PHARMACIST_USERNAME` / `PHARMACIST_PASSWORD`) for `liivv_pharmacist`. **Both** are required for staff actions. /admin only redirects to the BigCommerce control panel.

Pharmacists read and update **Supabase** (prescription / refill / CarePack queues, customer pharmacy detail, care chat) — not BigCommerce orders.

Entra SSO is not wired. We cannot connect it unless **IT approves and provides an Entra connection**. Until then, **BC iframe + one shared pharmacist login** is the control. The username and password live in **Vercel encrypted env vars** (same as other server secrets). We cannot tell which person approved an Rx. Shopper MFA is also not in place.

9. Health Canada DPD

The **Drug Product Database** is Health Canada’s **free public API** (open government data — no key, no paid contract). Customers search by brand when adding a prescription in the account dashboard. Next.js **proxies** the call (browser never talks to Health Canada). The **prescription is stored in Supabase**. DPD is a catalog only.


Rate limit: **every** /api call is 120 / IP / min at the gateway; DPD search is also **60 / IP / min**. Counts are stored in **Vercel Runtime Cache**, so every instance shares the same counter.

10. Other systems (short)

BigCommerce is the only store engine: catalog, cart, checkout, official order, customer login, most email. Recurring: Stripe bills; Liivv still creates the order in BigCommerce.


AI chat assistant (Olivia) is **off** (VIRTUAL_CARE_BOT_ENABLED). Human care chat stays in Supabase via /pharmacy-admin. It **remains off** in production; we can use IT resources later if we decide to implement it.

11. System context




12. Data flows


Commerce



Account dashboard — onboarding and pharmacy



Care chat



13. Auth cookies and secrets

Plane	Mechanism	Cookie	Secret	Path / lifetime
Customer	NextAuth → BC GraphQL login	Auth.js session JWT	AUTH_SECRET	Site-wide

Plane	Mechanism	Cookie	Secret	Path / lifetime
	or Customer Login JWT			
Anonymous cart	Signed JWT containing cartId	authjs.anonymous-session-token	AUTH_SECRET	7 days
Pharmacist (BC load)	Signed load JWT verified	liivv_pharmacy_admin	BIGCOMMERCE_APP_CLIENT_SECRET	/pharmacy-admin, 12 hours, SameSite=None
Pharmacist (shared login)	Shared username + password	liivv_pharmacist	AUTH_SECRET (signs cookie); PHARMACIST_USERNAME / PHARMACIST_PASSWORD	/pharmacy-admin, 12 hours, SameSite=None

Webhooks: Stripe constructEvent + STRIPE_WEBHOOK_SECRET. BigCommerce Authorization: Bearer + BIGCOMMERCE_WEBHOOK_SECRET.

Secret	Purpose
AUTH_SECRET	Auth.js + anonymous cart JWT + pharmacist session cookie
PHARMACIST_USERNAME / PHARMACIST_PASSWORD	Shared pharmacist admin login
BIGCOMMERCE_STOREFRONT_TOKEN	Storefront GraphQL
BIGCOMMERCE_ACCESS_TOKEN	Admin REST (orders, customers)
BIGCOMMERCE_CLIENT_ID / CLIENT_SECRET	Customer Login API JWT
BIGCOMMERCE_WEBHOOK_SECRET	Product → Stripe sync
BIGCOMMERCE_APP_CLIENT_ID / SECRET	Embedded staff app
STRIPE_SECRET_KEY / STRIPE_WEBHOOK_SECRET	Payments
NEXT_PUBLIC_STRIPE_PUBLISHABLE_KEY	Public — Stripe.js only
SUPABASE_URL / SUPABASE_SERVICE_ROLE_KEY	DB (bypasses RLS)

14. Evidence paths (code)

```
core/proxy.ts
core/lib/api-gateway/
core/lib/action-gateway/
core/lib/kv/
core/package.json
.env.example
core/auth/index.ts
core/lib/supabase/client.ts
```

```
core/lib/supabase/onboarding-schema.sql
core/lib/supabase/pharmacy-schema.sql
core/lib/bc-app-session.ts
core/lib/pharmacist-session.ts
core/lib/staff-access.ts
core/lib/chat/logging-policy.ts
core/lib/vendor-outage/
core/lib/stripe/availability.ts
core/lib/content-security-policy.ts
core/lib/pharmacy/medication-rate-limit.ts
core/lib/stripe/webhook-handlers.ts
core/lib/virtual-care-bot/
core/app/api/medications/
core/app/api/stripe/webhook/route.ts
core/app/api/bigcommerce/webhook/route.ts
core/app/api/bigcommerce/app/{auth,load,uninstall}/route.ts
core/app/pharmacy-admin/
```