CERES EXPLORER - REV. 1.4 SUMMARY

December 31, 2025
Design & CAD: Robert Brownscombe | Analysis: AI Assistance

MISSION PROFILE

Destination:	Ceres (Main Asteroid Belt, 2.8 AU from Sun)
Crew:	13 personnel
Duration:	3.2 years (10 mo outbound, 18 mo operations, 10 mo return)
Propulsion:	Deuterium-Tritium (D-T) Fusion, magnetic nozzle steering
Specific Impulse:	15,000 seconds
Launch:	~2085-2100 (assumes fusion propulsion maturity)

MISSION OBJECTIVE:
First human expedition to the asteroid belt. Scientific investigation of Ceres' composition, water ice deposits, organic compounds, and potential subsurface ocean. Surface operations using two hypergolic landers visiting diverse landing sites. Crew includes flight operations, science team (geologists, planetologists, astrobiologists), and mission specialists for surface EVA.

SHIP SPECIFICATIONS

DIMENSIONS:

Total Length:	104.4 meters (STA 9.5 to 113.9)
Habitat Length:	20 meters (STA 10.5 to 30.5)
Habitat Diameter:	30 meters @ STA 20.5
Spine Length:	47.3 meters (structural truss)
Shield Diameter:	14 meters x 1 meter thick

MASS:

Dry (Without Gear):	3,249 tonnes
Loaded Mass (fueled):	4,888 tonnes
Propellant:	1,500 tonnes (water)
Mass Ratio:	1.5

PERFORMANCE:

Delta-V Available:	59.5 km/s
Mission Requirement:	~35.8 km/s (includes Earth capture)
Margin:	23.7 km/s (66% reserve)

VOLUME:

Total Enclosed:	7,068 m3 (inside outer pressure hull)
Water Jacket:	1,511 m3 (1m thick shielding)
Habitable Interior:	5,557 m3 (crew living/working space)
Per Crew:	427 m3/person (6x better than ISS: 71 m3/person)

SHIP LAYOUT (Major Components)

FORWARD UNIT (STA 9.5-31.5)	2095.0t @ STA 19.2
Whipple Shield (15.2):	Micrometeorite protection, truncated sphere
Habitat (20.5):	30m dia cylinder + 2:1 ellipsoidal heads pressure vessel
Outer Hull:	45.4t (7mm Al-Li cylinder/heads, 10mm transition bands)
Inner Hull:	22.0t (5mm Al-Li, water jacket containment)
Water Jacket:	1,511t (1m thick uniform, 100 g/cm2 shielding)
Habitable Volume:	5,557 m3 (comfortable for 13 crew, 3.2 years)
Integrated Hydronic:	Waste heat thermal management

```
  Rotating Ring (20.5):      90t, three-deck structure inside cylinder
                             1,319 m2, Variable gravity 0.1-0.6g (3-6 RPM)

  RCS Thrusters (20.5):      30t, 20 thrusters (4 clusters x 5 each)
                             Forward/aft/pitch/yaw/roll control
                             All accessible from habitat for EVA maintenance

  Storm Shelter (24.5):      85t, 9m ovoid, 0.4m polyethylene
                             Solar particle event protection, pressure vessel

  Batteries/Fuel Cells:      2.2t @ STA 31.5

MID SECTION (STA 30.5-93.3, 156.2t @ STA 45.0):
  RCS Propellant (38.0):     100t (2x 50t tanks)

  Utilities (47.0):          Hydronic recirculation

  Spine (54.1):              29.0t, structural truss 47.3m long

  Propellant Tanks (69.0):   27t dry 3x 10m diameter spheres,
                             Water (fusion reaction mass)
  Removable gear:

    Cargo Pallets (44.0):    7.8t, surface equipment (left on Ceres)

    Landers (55.0):          132t (on voyage from Earth)
        Landers (dry)        2 x 42.3t (left on Ceres)
        Propellant:          2 x 23.4t (used on Ceres)

AFT UNIT (STA 77.8-113.9)    979t @ STA 91.6
  Shadow Shield (78.3):      123t (14m dia x 1m thick)
                             Lithium Hydride + Boron

  Fusion Reactor (92.6):     800t, D-T fusion, Propulsion mode generates
                             gigawatt-scale plasma power at 15,000 ISP
                             Standby/electrical mode is capable of 30 MW
                               thermal output

  Radiators (92.6):          11t, He-Xe working fluid
                             4 panels extending to tail (125.8)

  Magnetic Nozzles (110.0):  45t, 6 nozzles, plasma exhaust
                             2-3° thrust vector control

================================================================================
KEY DESIGN FEATURES
================================================================================

1. CYLINDER + ELLIPSOIDAL HEAD HABITAT

 This change was driven by practical engineering considerations:

ADVANTAGES:
  * Uses standard 2:1 ellipsoidal heads, proven ASME design.
    (100+ years of pressure vessel heritage). Rotating ring fits naturally
    inside cylinder geometry.

  * Volume: 5,557 m3 habitable volume. 427 m3 per crew member
    (exceptionally spacious for 4.1-year mission)

STRUCTURAL DETAILS:
  Main Sections:     7mm Al-Li (SF = 2.08x, adequate for 1 atm pressure)
```

Transition Bands: 10mm Al-Li x 1m (knuckle reinforcement, SF = 3.0x)
Water Jacket: 1m uniform thickness (100 g/cm2 radiation shielding)

2. OPTIMIZED RADIATION SHIELDING

The 14-meter shadow shield provides adequate neutron attenuation. Shadow cone geometry graphically verified to be more than adequate to shadow habitat.

Radiation protection layers:
- 14m x 1m LiH+Boron shield: ~20,000x neutron attenuation
- 1m habitat water jacket: 100 g/cm2 permanent shielding
- 0.4m shelter polyethylene: 38 g/cm2 additional protection
- Distance advantage: 72m shield-to-habitat separation

Total: Adequate for 4.1-year deep space mission

4. DUAL-PURPOSE HYDRONIC THERMAL MANAGEMENT

The ship uses proven industrial hydronic (hot water) heating technology, adapted from commercial HVAC systems.

Primary loop: Reactor heats propellant tanks via recirculation circuit preventing freezing during the multi-year mission.

Secondary loop: Warm propellant water circulates through the habitat's 1,511t water jacket (the radiation shielding), providing 6 kW of heating with simple flow-regulated pumps.

5. FORWARD RCS CONFIGURATION (NEW IN REV 1.2c)

All 20 RCS thrusters positioned at habitat (STA 20.5, R=16m), eliminating the need for aft thrusters. This simplification provides:

* Maintenance Access: All thrusters reachable via EVA from habitat
* Simplified Plumbing: Short runs from tanks @ STA 38.0
* Eliminates long routing through 62m spine structure

Control Authority: 24m moment arm (STA 44.6 to 20.5) provides 6x better leverage than Apollo Service Module (4m arms). More than adequate for the minimal CG shifts throughout the mission.

Layout: 4 clusters x 5 thrusters each
- Forward/aft thrust (translation + pitch combinations)
- Radial thrust (pure pitch/yaw depending on cluster)
- Tangential CW/CCW (roll control)

6. MAGNETIC NOZZLE THRUST VECTORING

Six magnetic nozzles provide 2-3° thrust vector control, easily compensating for minimal CG shifts. The thrust line remains on the ship's central axis and passes through the CG, minimizes bending moments on the structure.

==

CENTER OF GRAVITY ANALYSIS

==

COMPONENT MASS BREAKDOWN:

FORWARD UNIT: 2095.0t @ STA 19.2:

Whipple shield:	3.6t	@ 15.2 =	55	moment
Outer hull:	45.4t	@ 20.5 =	931	
Inner hull:	22.0t	@ 20.5 =	451	
Water jacket:	1,511.0t	@ 20.5 =	30975	
Systems:	152.9t	@ 20.5 =	3135	

```
    Equipment (50.0t)
    Plumbing/bladders (15.0t)
    Hydronic heating (0.9t)
    Consumables/spares (87.0t)
  Rotating ring:           90.0t @ 20.5 =   1845
  RCS thrusters:           30.0t @ 20.5 =    615
  Storm shelter:           85.0t @ 24.5 =   2082
  Batteries/fuel cells:     2.2t @ 31.5 =     69

MID UNIT(DRY NO GEAR): 174.5t @ STA 47.2:
  RCS propellant tanks:   100.0t @ 38.0 =   3800
  Recirculation system:     0.2t @ 54.1 =     11
  Spine structure:         47.3t @ 54.1 =   2559
  Propellant tanks (dry):  27.0t @ 69.0 =   1863

AFT UNIT: 979t @ STA 91.6
  Shadow shield:          123.0t @  78.3 =  9631
  Fusion reactor:         800.0t @  92.6 = 74080
  Radiators:               11.0t @  92.6 =  1019
  Magnetic nozzles:        45.0t @ 110.0 =  4950

TOTAL (DRY NO GEAR): 3248.5t @ STA 42.5 = 138070

PROPELLANT:               1,500t @ 69.0 =  103500 (when loaded)
                          1,020t @ 69.0 =   70380 (Ceres arrival)
                            946t @ 69.0 =   65274 (Ceres departure)
                            266t @ 69.0 =   18354 (final Earth orbit)

GEAR LEFT ON SURFACE:
  Cargo pallets:            7.8t @ 44.0 =     343 (when loaded)
  Landers (2x) wet:       132.0t @ 55.0 =    7260 (when loaded)
```

CONFIGURATION SUMMARY:

Configuration	Mass (tonnes)	CG Location (STA)
Loaded (Earth departure)	4,888	51.0
Earth orbit (final)	3,515	44.5

CG shift from Earth departure to final orbit is 6.5m

PROPELLANT BUDGET (3.2-YEAR MISSION)

PHASE BREAKDOWN:

Phase	Duration	Delta-V	Propellant	Mass Start/End
Outbound Transit	0.85 years	13.0 km/s	480t	4,629t / 4,149t
Ceres Operations (orbit insertion, lowering, relay deployment, stationkeeping)	1.5 years	2.8 km/s	74t	4,149t / 4,075t
Gear left on surface (118t)				4,075t / 3,957t
Return Transit (Ceres departure, transfer, Earth approach)	0.85 years	16.0 km/s	520t	3,957t / 3,437t
Earth Capture (capture + circularization to stable orbit)	Variable	4.0 km/s	160t	3,437t / 3,277t

TOTAL MISSION 3.2 years ~35.8 km/s 1,234t used

FINAL IN STABLE EARTH ORBIT: 3,515 tonnes, 266t propellant remaining (18%)

MISSION FEASIBILITY ASSESSMENT

CERES (3.2 years): Achievable when fusion drive is feasible (2080-2100)

The Ceres Explorer represents an optimized design for crewed deep space missions using fusion propulsion and passive radiation shielding. The 3.2-year mission duration with 13 crew is feasible due to:

* Adequate radiation shielding (1m water jacket = 100 g/cm2, crew safe)
* Spacious habitat (5,557 m3 interior, 427 m3/person)
* Variable gravity 0.1-0.6g (3-6 RPM) (rotating ring inside cylinder)
* Exceptional delta-V margin (66% reserve, 59.5 km/s available)
* Reliable systems (proven industrial components, space-rated)
* Redundancy (two landers, forward RCS accessible, backup power)
* Fast transit (3.2 years, less crew health risks)

COMPARISON TO OTHER DEEP SPACE MISSIONS:

Mars (2 years):	Difficult but feasible with 2030s technology
Ceres (3.2 years):	THIS DESIGN - feasible with fusion drive
Jupiter (5+ years):	Not survivable without breakthrough technology
Saturn (6+ years):	Not survivable without breakthrough technology

Beyond Ceres requires: torch ships (constant high acceleration), active magnetic deflection shields (unproven), suspended animation (speculative), or fundamental breakthroughs in radiation protection.

HABITAT COMFORT:
With 5,557 m3 habitable volume for 13 crew over 3.2 years, the Ceres Explorer provides excellent living conditions:

- 427 m3 per crew (6x better than ISS: 71 m3/person)
- Geometry: optimizes space and mass
- Rotating ring: Artificial gravity essential for health, exercise, meals
- Modern amenities: Comfortable temperature, recreation, privacy
- Hydroponics provides fresh air, water and fresh vegetables
- THE VIEW: Asteroid belt, Ceres, the endless frontier

This is not a cramped submarine or Antarctic station - this is a comfortable home for 3.2 years of historic exploration.

TECHNICAL VALIDATION

CAD VERIFICATION (AutoCAD R14):
All geometry verified through detailed CAD work including cylinder + ellipsoidal head construction, shadow cone projection, component clearances, structural routing, and thermal plumbing runs, the 14m shield creating a adequate shadow at habitat specifically validated through geometric construction.

MASS BALANCE VERIFICATION:
Component-level summation method used throughout. Each component's mass and station location individually calculated, then summed for unit centroids and overall ship CG.

PERFORMANCE CALCULATION:
Delta-V = Isp x g■ x ln(mass ratio)
Delta-V = 15,000 s x 9.81 m/s2 x ln(4,608/3,077) = 59.5 km/s *

SHIELDING VALIDATION:
Water jacket effectiveness depends on thickness (g/cm2).
1m thickness = 100 g/cm2 shielding, adequate for 3.2-year mission.
The physics of radiation attenuation validates this approach.

CONCLUSION:
The optimization achieved 59.5 km/s delta-V, 3.2-year mission, a significant improvement over previous designs. This demonstrates that systematic engineering combined with practical judgment produces spacecraft that actually work.

The ship has a unique aesthetic because it is honest. Every component, every dimension is justified by engineering necessity and manufacturing reality.

Design by physics, not the appearance. Built by proven methods, not speculation.

==

Design and CAD Documentation: Robert Brownscombe
Analysis & Calculation: AI Assistance

Project Reference: Evolved from Europa, Enceladus, then Ceres missions with numerous iterations of the Expl

==