



Advanced Dynamic Workflow Import/Export Guide

Last Updated: March 30, 2026

Proprietary – © JAGGAER, LLC. The information contained in this document is **Proprietary**. External distribution is not permitted except under a non-disclosure agreement.

Table of Contents

Introduction	3
Supplier Validation	3
Advanced Dynamic Workflow Import - File Formats	4
XML File Format	4
Tab-Delimited Text File Format	8
Validate / Import Advanced Dynamic Workflow	10
Exporting Advanced Dynamic Workflow Configuration	11
Import Response Output	12
XML Response Output	12
Tab-Delimited Import Response Output	13
Appendix	14
DocumentTotal	14
CustomFieldValueAggSpendSingle	14
CustomFieldValueAggSpendMulti	15
Department	15
LineAmount	16
CustomFieldValueSingle	16
CustomFieldValueMulti	17
CommodityCodeSingle	17
CommodityCodeMulti	18
FormType	18
Country of Origin	19

Introduction

The JAGGAER suite of products offers the ability for organizations to manage the Advanced Dynamic Workflow configuration for various documents and actions through an XML file management process or via a Tab-Delimited Text file (i.e. import/export).

Specifically, the import/export process offers the ability to manage rule groups, rules, and associated approvers for Advanced Dynamic Workflow. This document explains how the import, validation and export functionality works as well as the required file format and validation rules.

Advanced Dynamic Workflow routing/management is available for the following, depending on your organization's licenses:

- Requisitions (PR)
- Purchase orders (PO)
- Fulfillment Sales Orders
- Invoices
- Receipts
- Supplier Registrations and Review Requests
- Contracts
- Requests
- Sourcing events and evaluations
- Savings initiatives
- Budget Manager
- Payments

Advanced Dynamic Workflow allows an organization to create rules based on various data elements depending on the document, including: custom field value, a supplier name, document or line total amount, commodity code, department, form type, spend associated with a custom field value, and many other criteria.

Note: In order to use Advanced Dynamic Workflow, JAGGAER must setup the workflow to appropriately reference the rules created in Advanced Dynamic Workflow.

For each type of workflow configuration, the Advanced Dynamic Workflow screens include Rule Group management, Rules Management, Rules Import/Export, and history logs for rule groups and rules.

Note: Some screens may look different. Available options on screens vary based on licenses and individual user permissions. Additionally, field management settings may be modified from by the organization or by JAGGAER from time-to-time based on usability needs.

Supplier Validation

JAGGAER's solution provides buyers with access to a network of suppliers and enables buyers to engage with and validate its supplier counterparties. Validating suppliers and their offerings and contracting with those suppliers remains the buyers' sole responsibility.

Advanced Dynamic Workflow Import - File Formats

XML File Format

The Advanced Dynamic Workflow import/export process utilizes an XML format designed to support the configuration options available. This guide presents the required and optional elements in the XML format. Please reference the link on the Advanced Dynamic Workflow Import/Export screen for a detailed example of a formatted import XML file. This file contains examples of the various elements available for the import process.

<DynamicWorkflowRuleMessage>

The **<DynamicWorkflowRuleMessage>** element is the top-most element in the XML. This element contains all of the Advanced Dynamic Workflow configuration information for a given document.

```
<DynamicWorkflowRuleMessage workflowType="requisition" operation="replace">
```

- **workflowType** – This attribute defines the specific document to which the rules are applied. The rules associated with a document must be imported in a single XML file. The application does not support importing rules for multiple documents in a single file. The valid values for workflowType are:
 - requisition - for Requisitions
 - po - for Purchase Orders
 - fulfillment - for internal fulfillment requests/sales orders
 - invoice - for Invoices
 - receipt - for Receipts
 - supplierregistration - for Supplier Registration
 - suppliermanagement - for Supplier Review
 - formrequest - for Form Requests
 - contract - for Contract Approval
 - sourcingeventprebid - For Sourcing Event approval
 - sourcingeventpostbid - For Sourcing Event evaluation (award approvals)
 - savingsinitiative - for Savings Initiative approval
- **operation** – The operation attribute defines how the included rules will be imported into the application. There are two types of import processes available to a user in the application. One of these operations must be declared at the top of every import XML file:
 - **insertUpdate** – this type of import is used to add new rule groups and rules as well as update existing rule groups and rules. The application will add any elements it cannot match (e.g. find an existing entry) and update any elements that it can match (e.g. there is an existing entry) in the application. NOTE: This is the operation included with all exports (see Export section for more information). The appropriate syntax for the operation is:
<DynamicWorkflowRuleMessage workflowType="requisition" operation="insertUpdate">.

- **replace** – this type of import is used to overwrite all of the rule groups and rules in the application. The application will remove **all** existing elements in Advanced Dynamic Workflow and replace them with the contents of the imported XML file. The appropriate syntax for the operation is: `<DynamicWorkflowRuleMessage workflowType="requisition" operation="replace">`.

<Header>

The **<Header>** element itself contains two elements:

- **<MessageID>** - a unique identifier for this particular import.
- **<Timestamp>** - a date/timestamp for the import file.

<RuleGroup>

The **<RuleGroup>** element contains information specific to the rule group. There is one RuleGroup element per Rule Group in the configuration. Each element contains Rule Group information as well as all of the rules associated with that Rule Group.

```
<RuleGroup internalName="Grants">
```

```
<DisplayName>
```

```
Grant Workflow
```

```
</DisplayName>
```

```
<Description>
```

```
Rule Group description text
```

```
</Description>
```

- **internalName** – The internalName attribute is used to define the Internal Name for a Rule Group. The Internal Name is the reference to the workflow step configuration. The Internal Name must be unique and is used to match a Rule Group in the XML file to one in the application when using an insertUpdate operation. The Internal Name is an alphanumeric field and can contain spaces.
- **<DisplayName>** - The DisplayName element defines the Rule Group's display name in the application. The display name is used for informational purposes only and is viewable in the Advanced Dynamic Workflow administrative screens. The display name is an alphanumeric field and can contain spaces. The Display Name must be a unique value across all Rule Groups.
- **<Description>** - The Description element supplies the Description for the Rule Group. Each Rule Group can have an optional Description to further explain the purpose of the Rule Group. The description is displayed only in the Advanced Dynamic Workflow administrative screens for informational purposes.

<Rule>

The **<Rule>** element is a sub-element to the RuleGroup element as all rules must be associated with a Rule Group. A Rule element contains the specific rule element(s) configuration for the rule as well as its associated approvers.

```
<Rule internalName="Grant">
  <DisplayName>
    Import testing
  </DisplayName>
  <Description>
    Rule description text
  </Description>
  <Active>
    True
  </Active>
  <Approvers>
    <UserRef username="marysmith"/>
  </Approvers>
  <ImplicitApprovers>
    <UserRef username="aadmin"/>
  </ImplicitApprovers>
  <AutoApprove>
    true
  </AutoApprove>
  <RuleElement type="DocumentTotal">
    <![CDATA[ greaterThanOrEqualTo|500.00|USD ]]>
  </RuleElement>
  <RuleElement type="Department">
```

<![CDATA[Biology]]>

</RuleElement>

</Rule>

- **internalName** – The internalName attribute is used to define the Internal Name for a Rule. The internal name is the application's reference to the rule in workflow. The Internal Name must be unique and is used to match a Rule in the XML file to one in the application when using an insertUpdate operation. The Internal Name is an alphanumeric field and can contain spaces.
- **<DisplayName>** - The DisplayName element defines the Rule's display name in the application. The display name is used for informational purposes only and is viewable in the Advanced Dynamic Workflow administrative screens. The display name is an alphanumeric field and can contain spaces. The Display Name must be a unique value across all Rules.
- **<Description>** - The Description element supplies the Description for the Rule. Each Rule can have an optional Description to further explain the purpose of the Rule. The description is displayed only in the Advanced Dynamic Workflow administrative screens for informational purposes.
- **<Active>** - The Active element defines whether the Rule is active in the application or not. Inactive Rules are not evaluated in the workflow process. The application sets the Rule to an active status if the value provided for this element equals "true". Any value other than "true" will set the Rule to an inactive status upon import.
- **<Approvers>** - The Approvers element provides a mechanism to import the approvers associated with a given rule. The approver's element is defined by the sub-element <UserRef>, which contains the specific reference to the approver's username. The <Approvers> element can contain one or more <UserRef> elements.
 - **<UserRef>** - A sub-element of Approvers, this element contains the specific reference to the approver's username. Each approver for a Rule must be referenced in a single <UserRef> element.
 - **username** – The username attribute contains the approver's username. If the username cannot be found, the approver is not added to the Rule.
- **<ImplicitApprovers>** - The ImplicitApprovers element provides a mechanism to import the implicit approvers associated with a given rule. whom the workflow rule is skipped if the document was submitted by that user. The rule must have **Enable Automatic Approvals** selected. The implicit approver's element is defined by the sub-element <UserRef>, which contains the specific reference to the implicit approver's username. The <ImplicitApprovers> element can contain one or more <UserRef> elements. When an implicit approver submits an order that is routed to a workflow rule for which they are listed as an implicit approver, AND Enable Automatic Approvals is selected for the rule, the order is implicitly approved for the workflow rule by the submitter. The document is routed to the next rule/step in the workflow process. .
- **<AutoApprove>** - The AutoApprove element defines whether or not the rule has Enable Automatic Approvals selected. If "true", the workflow step will be skipped for a document submitted by an implicit approver listed on the rule. If the value is "false", the document will route to the workflow step as defined by the rule criteria.

<RuleElement>

The **<RuleElement>** element contains the actual rule configuration information for the Rule. A <Rule> can contain one or more <RuleElement> tags.

- **type** – The type attribute defines the specific Rule Element being used within the Rule. There are several Rule Elements supported in the application and the configuration syntax varies based on the element being used. The Rule Element configuration is formatted as `<![CDATA[ ]]>`. The Appendix provides the syntax that should be used within the [] for each Rule Type Element.

Tab-Delimited Text File Format

The second method for bulk modification of Advanced Dynamic Workflow rules utilizes a tab-delimited text file for ease of use. This section presents the required and optional columns in the text file format. Please reference the link on the Advanced Dynamic Workflow Import/Export screen for a detailed example of a formatted text file. This file contains examples of the various column values available for the import process.

Note: It is best to edit tab-delimited Advanced Dynamic Workflow import/export files in a spreadsheet program such as Microsoft Excel.

Rule Group

The following column headers pertain to information specific to the rule group. For each line in the tab-delimited import file, the associated Rule Group columns will indicate the Rule Group the rule is within.

- **Rule Group Internal Name** is a unique name associated to an existing Rule Group within the application. This field is alphanumeric, and may contain spaces. The Internal Name is the reference to the workflow step configuration.
- **Rule Group Display Name** defines the Rule Group's display name in the application. The display name is used for informational purposes only and is viewable in the Advanced Dynamic Workflow administrative screens. The display name is an alphanumeric field and can contain spaces. The Display Name must be a unique value across all Rule Groups.
- **Rule Group Description** column supplies the description for the Rule Group. Each Rule Group can have an optional description to further explain the purpose of the Rule Group. The description is displayed only in the Advanced Dynamic Workflow administrative screens for informational purposes.

Rule

The next group of headers provides information regarding the rule itself which is contained within a Rule group. These columns contain the specific Rule configuration, status, type, and approvers.

- **Rule Internal Name** column is used to define the internal name for a Rule. The internal name is the application's reference to the rule in workflow. The internal name must be unique and is used to match existing Rules within the application. This field is alphanumeric and can contain spaces.
- **Rule Display Name** column defines the Rule's display name in the application. The display name is used for informational purposes only and is viewable in the Advanced Dynamic Workflow administrative screens. The display name is an alphanumeric field and can contain spaces. It must be a unique value across all Rules.
- **Rule Description** column supplies the description for the Rule. Each Rule can have an optional description to further explain the purpose of the Rule. The description is displayed only in the Advanced Dynamic Workflow administrative screens for informational purposes.

- **Rule Approvers** column is a pipe list of usernames who should be associated with the given rule. This list should be pipe "|" delineated and contain only existing usernames from within the application. If a username in this field cannot be found, the line will be in error.
- **Rule Approver Names** column contains the full name (first and last name) of the rule approver.
- **Implicit Approvers** column is a pipe list of usernames for whom the workflow rule is skipped if the document was submitted by that user. The rule must have **Enable Automatic Approvals** selected. When an implicit approver submits an order that is routed to a workflow rule for which they are listed as an implicit approver, AND Enable Automatic Approvals is selected for the rule, the order is implicitly approved for the workflow rule by the submitter. The document is routed to the next rule/step in the workflow process.
- **Implicit Approver Names** column contains the username of the rule approver.
- **Auto Approve** column defines whether the **Enable Automatic Approvals** setting is on or off. If the value is on (true), then the workflow step will be skipped for a document submitted by an implicit approver listed on the rule. If the value is off (false), the document will route to the workflow step as defined by the rule criteria.
- **Active** column defines whether the Rule is active in the application or not. Inactive Rules are not evaluated in the workflow process. The application sets the Rule to an active status if the value provided for this element equals "true". Any value other than "true" will set the Rule to an inactive status upon import.
- **Type and Value** - The **Type** column dictates what kind of calculation will be performed for the rule value. The **Value** column indicates the criteria that will be evaluated for the Type rule. Valid Types and Value column syntax for each Rule Type are defined in the Appendix.

Validate / Import Advanced Dynamic Workflow

Refer to the Template for the appropriate file format and columns. Use the template to populate the appropriate values. Or, you may use an Export file to modify current values and add new values. **Note: You must have Rule Groups in the application before you can import associated rules.**

You may choose to validate the file data without modifying the data within the application. After validation, you may choose to Import the data. Any errors or warnings will be written to the output file and available for review by the user on the right-hand side of the screen. You may also choose to Import directly without the validation step. Upon Import, the file is still checked for format and data content. **Best Practice** is to validate the file before importing.

1. Navigate to **Setup > Workflow Setup**. Select the appropriate document type for configuring workflow: Requisition, Purchase Order, Fulfillment, Invoice, Supplier Registration Workflow/Approval, Form Request, Sourcing Event Approval/Evaluation.
2. Select the **Advanced Dynamic Workflow** tab, and the **Rules Import/Export** sub-tab.
3. Choose the **File Format** – XML or Tab Delimited Text.
4. Choose the **Action**:
 - a. **Validate**: You may choose to Validate the file only. This will analyze the file for any errors and provide a file with errors and warnings. After validation is complete, you have the option of importing information that did not error. This is a recommended Best Practice!
 - b. **Import**: You may choose to Import the file without validation. If there are no errors or warnings associated with the import, no Errors/Warnings file is provided.
5. Enter a **Description**, up to 100 characters. Enter text that describes the type of import you are performing. For example, "adding new rules" or "Modifying department rules".
6. Browse and choose the **File Name**: Select the file name with the information you need to import.
7. Click the **Submit** button.
8. The page will refresh, and you will note that your requesting is "Pending" in the **Recent Activity** section of the **Rules Import/Export tab**. Choose the **Refresh this page** hyperlink to refresh the screen and view the status of your request.
9. Once the file completes processing, the **Recent Activity** section indicates details of the file including rows processed, as well as rows with warnings or errors.
10. If you chose to **Validate** the import file, you will note a Validation file is created noting any rows with errors, warnings or duplicates. Click the file to open and review any errors that you may want to correct and then re-validate the file. If you would like to import the file you validated (the information that did not error or generate a warning), choose the **Click to import...** link to import the file. The data that contained errors, warnings or duplicates will not be included in the import.
11. If you chose to **Import** the file without first validating, you will see the validation file link only if errors or warnings were identified during the import process. If no errors or warnings were detected, no validation file is generated.
12. Once you see that the **Import** has a status of **Completed**, the valid Advanced Dynamic Workflow Rule information is updated in the system.

Exporting Advanced Dynamic Workflow Configuration

The application supports the ability to export the Advanced Dynamic Workflow configuration for a given document type. To access this functionality, use the **Export** function in the **Action** dropdown.

By using the export functionality, the user may request an export of an XML or Tab-Delimited file for the document type based on the user's location in Advanced Dynamic Workflow. For instance, if the user is in the requisition portion of workflow setup, the file will contain all of the requisition rules. Either format of export output contains the full configuration as defined in Advanced Dynamic workflow at the time the export is performed.

1. Navigate to **Setup > Workflow Setup**. Select the appropriate document type for configuring workflow: Requisition, Purchase Order, Fulfillment, Invoice, Supplier Registration Workflow/Approval, Form Request, Sourcing Event Approval/Evaluation.
2. Select the **Advanced Dynamic Workflow** tab, and the **Rules Import/Export** sub-tab.
3. Choose the **File Format** for the Export – XML or Tab Delimited Text.
4. Choose the **Action** - Export
5. Enter a **Description**, up to 100 characters. Enter text that describes the type of import you are performing. For example, "text attribute file".
6. Click the **Submit** button.
7. The page will refresh, and you will note that your requesting is "Pending" in the **Recent Activity** section of the **Rules Import/Export** tab. Choose the **Refresh this Page** hyperlink to refresh the screen and view the status of your request.
8. Once the file completes processing, the **Recent Activity** page indicates the number of rows in the file.
9. Select the file name or **Click to download...** hyperlink to open or save the file.
10. **NOTE:** All XML exports include an operation attribute equal to **insertUpdate** for the **<DynamicWorkflowRuleMessage>** element.

Import Response Output

XML Response Output

For both the **Import** and **Validate** actions, all successes, errors, and warnings are logged within the output file. This section shows an example of an import response message. There are several validation rules for the import process that have been laid out in the individual sections above. If an error occurs, the import response XML contains details on the nature of the error. The import process stops at the first error it encounters, therefore it is possible that errors could occur on future imports once the stated error in the XML is corrected.

The **Recent Activity** section displays results of the validation/import once complete. If errors occurred, an error message will be displayed and a file is available for download.

Note the following regarding information in the response:

- Possible status codes
 - 200 (Success)
 - 400 (Bad Request)
 - 406 (Not accepted)
- Possible error types
 - Error
 - Warning

Example Import Response XML:

```
<?xml version="1.0" encoding="UTF-8" ?>

<!DOCTYPE DynamicWorkflowRuleResponse SYSTEM "DynamicWorkflowRule.dtd">

<DynamicWorkflowRuleResponse>

<Header>

<MessageId>

1172862612739

</MessageId>

<RelatedMessageId>

117260524315

</RelatedMessageId>

<Timestamp>
```

2013-03-02T14:10:12.739-05:00

</Timestamp>

</Header>

<Status>

<StatusCode>

400

</StatusCode>

<StatusText>

Bad Request

</StatusText>

<ObjectErrors>

<RuleError ruleInternalName="Grant2" ruleGroupInternalName="Grants">

<Error type="Error">

<ErrorMessage>

Multiple rule elements of this type are not permitted within a single rule: CommodityCodeMulti

</ErrorMessage>

</Error>

</RuleError>

</ObjectErrors>

</Status>

</DynamicWorkflowRuleResponse>

Tab-Delimited Import Response Output

When importing or validating a Tab-Delimited file that contains errors, the resulting output will contain the input provided, but with two additional columns on the left most side. These columns will have a heading of "Errors" and "Warnings" respectively. An error or warning will be placed in the row where the infraction occurred. The user may correct any errors and re-import the file, leaving the "Errors" and "Warning" columns in place.

Appendix

DocumentTotal

- Rule Element: Document Total Amount
- Syntax: [operator | amount | currency code]
- Available operators:
 - equalTo
 - notEqualTo
 - greaterThanOrEqualTo
 - lessThanOrEqualTo
 - Between – requires two amounts, add an addition | to separate the additional amount. For example, <![CDATA[Between|300.00|500.01|USD]]>
 - NotBetween – see "Between" operator for additional requirements
 - greaterThanReqTotalLimit (PR workflow only)
 - greaterThanPOTotalLimit (PO workflow only)
 - greaterThanPOTotalLimit
- Only one DocumentTotal reference per Rule is permitted
- XML Example:

```
<RuleElement type="DocumentTotal">  
  
<![CDATA[ greaterThanOrEqualTo|500.00|USD ]]>  
  
</RuleElement>
```

- Tab-Delimited Value Example:
greaterThanOrEqualTo|500.00|USD

CustomFieldValueAggSpendSingle

- Rule Element: spend total against a single custom field value
- Syntax: [operator | value | currency code | custom field name | custom field value]
- Available operators:
 - equalTo
 - notEqualTo
 - Between – requires two amounts, add an addition | to separate the additional amount. For example, <![CDATA[Between|300.00|500.01|USD|Organization|11005]]>
 - NotBetween – see "Between" operator for additional requirements
 - greaterThanOrEqualTo
 - lessThanOrEqualTo

- One or more permissible per Rule
- XML Example:

```
RuleElement type="CustomFieldValueAggSpendSingle">

<![CDATA[ greaterThanOrEqualTo|500.00|USD|Organization|11005 ]]>

</RuleElement>
```

- Tab-Delimited Value Example:

```
greaterThanOrEqualTo|500.00|USD|Organization|11005
```

CustomFieldValueAggSpendMulti

- Rule Element: spend total against a set of custom field values
- Syntax: [operator | value | currency code | custom field name | custom field value1 | custom field value2 | custom field value3]
- Available operators:
 - equalTo
 - notEqualTo
 - Between – requires two amounts, add an addition | to separate the additional amount. For example, <![CDATA[Between|300.00|500.01|USD|Organization|11005]]>
 - NotBetween – see "Between" operator for additional requirements
 - greaterThanOrEqualTo
 - lessThanOrEqualTo
- One or more permissible per Rule
- XML Example:

```
RuleElement type="CustomFieldValueAggSpendMulti">

<![CDATA[ greaterThanOrEqualTo|500.00|USD|Organization|11005
|11006|11007 ]]>

</RuleElement>
```

- Tab-Delimited Value Example:

```
greaterThanOrEqualTo|500.00|USD|Organization|11005|11006|11007
```

Department

- Rule Element: Department
- Syntax: [department name1 | department name2]
 - Blank departments can be added to the Rule Element by including a | in front of the first Department name. For example <![CDATA[| Biology]]>

- Only one Department reference per Rule is permitted.
- XML Example:

```
RuleElement type="Department">

<![CDATA[ Biology ]]>

</RuleElement>
```

- Tab-Delimited Value Example:

```
Biology
```

LineAmount

- Rule Element: Line Total Amount
- Syntax: [operator | amount | currency code]
- Available operators:
 - equalTo
 - notEqualTo
 - greaterThanOrEqualTo
 - lessThanOrEqualTo
 - Between – requires two amounts, add an addition | to separate the additional amount. For example, <![CDATA[Between|300.00|500.01|USD]]>
 - NotBetween – see "Between" operator for additional requirements
 - greaterThanReqLineLimit (PR workflow only)
 - greaterThanPOLineLimit (PO workflow only)
 - greaterThanPOLineLimit
- Only one LineTotal reference per Rule is permitted
- XML Example:

```
<RuleElement type="LineTotal">

<![CDATA[ greaterThanOrEqualTo|500.00|USD ]]>

</RuleElement>
```

- Tab-Delimited Value Example:

```
greaterThanOrEqualTo|500.00|USD
```

CustomFieldValueSingle

- Rule Element: a single custom field value or range
- Syntax: [custom field name | operator | value]

- Available operators:
 - equalTo
 - notEqualTo
 - Between – requires two amounts, add an addition | to separate the additional amount. For example, <![CDATA[Organization | Between|100|999|USD]]>
 - NotBetween – see "Between" operator for additional requirements
- One or more permissible per Rule
- XML Example:

```
<RuleElement type="CustomFieldValueSingle">

<![CDATA[ Organization|equalTo|11005 ]]>

</RuleElement>
```

- Tab-Delimited Value Example:

Organization | equalTo | 11005

CustomFieldValueMulti

- Rule Element: a set of custom field values
- Syntax: [custom field name | operator | custom field value1 | custom field value2]
- Available operators:
 - oneOf
 - notOneOf
 - Blank values can be added to the Rule Element by including | in front of the first custom field value. For example, <![CDATA[Organization|oneOf||11005|11006]]>
 - NotBetween – see "Between" operator for additional requirements
- One or more permissible per Rule
- XML Example:

```
<RuleElement type="CustomFieldValueMulti">

<![CDATA[ Organization|oneOf||11005|11006 ]]>

</RuleElement>
```

- Tab-Delimited Value Example:

Organization | oneOf | | 11005 | 11006

CommodityCodeSingle

- Rule Element: a single commodity code value or range
- Syntax: [operator | commodity code value]

- Available operators:
 - equalTo
 - notEqualTo
- Only one CommodityCodeSingle reference per Rule is permitted.
- XML Example:

```
<RuleElement type="CommodityCodeSingle">

<![CDATA[ equalTo|876543 ]]>

</RuleElement>
```

- Tab-Delimited Value Example:

```
equalTo | 876543
```

CommodityCodeMulti

- Rule Element: a set of commodity code values
- Syntax: [operator | commodity code value1 | commodity code value2]
- Available operators:
 - oneOf
 - notOneOf
 - Blank values can be added to the Rule Element by including | in front of the first commodity code value. For example, <![CDATA[oneOf||11005|11006]]>
- Only one CommodityCodeMulti reference per Rule is permitted.
- XML Example:

```
<RuleElement type="CommodityCodeMulti">

<![CDATA[ oneOf | 12345 | 45678 ]]>

</RuleElement>
```

- Tab-Delimited Value Example:

```
oneOf | 12345 | 45678
```

FormType

- Rule Element:Form Type
- Syntax: [Form Type1 | Form Type2]
- Only one Form Type reference per Rule is permitted.
- XML Example:

```
<RuleElement type="FormType">
```

```
<![CDATA[ Services ]]>
```

```
</RuleElement>
```

- Tab-Delimited Value Example:

Services

Country of Origin

- Rule Element: SupplierCountryOfOrigin
- Syntax: [operator|Country 1|Country 2]
- XML Example:

```
<RuleElement type="SupplierCountryOfOrigin">
```

```
<![CDATA[oneOf|US|GB|BQ|BA|RE|BL|GS|TT|VC|BO ]]>
```

```
</RuleElement>
```

- Tab-Delimited Value Example:

"SupplierCountryOfOrigin" "oneOf|AU|CR|JP|US"