

# Problem and Data

---

# Anomaly Detection on Taxi Calls

We are contacted by a Taxi company:



# Anomaly Detection on Taxi Calls

## We are contacted by a Taxi company:

- They have historical data about taxi calls in NYC
- They are interested in detecting "abnormal situations" (so called **anomalies**)

## Goals:

- Analyze anomalies (e.g. better size the fleet)
- Anticipate anomalies (so we can prepare)

## Typically referred to as **anomaly detection**:

- An important industrial problem
- Many context and possible applications

# Basic Setup

Let us start by setting up the notebook:

```
In [1]: %load_ext autoreload
        %autoreload 2
        <%matplotlib widget
```

Our module contains a pre-built function to load the data:

```
def load_series(file_name, data_folder):
    ...
```

- We will use data from the Numenta Anomaly Benchmark (NAB).
- NYC taxi data `nyc_taxi.csv` is in the `data/realKnownCause` folder

```
In [2]: from util import nab # Import our submodule
        data_folder = '../data/nab'
        file_name = 'realKnownCause/nyc_taxi.csv'
        data, labels, windows = nab.load_series(file_name, data_folder)
```

# A Look at the Data

Let's have a look at all the data we loaded

```
In [3]: data.head()
```

Out [3]:

	value
timestamp	
2014-07-01 00:00:00	10844
2014-07-01 00:30:00	8127
2014-07-01 01:00:00	6210
2014-07-01 01:30:00	4656
2014-07-01 02:00:00	3820

data is a pandas DataFrame object

- It is essentially a **table**, in this case representing a **time series**
- There are well defined **column names** (here "value")
- There is a well defined row **index** (here "timestamp")
- Jupyter displays DataFrame objects as HTML tables

# Time Series and Pandas

Our data is a **time series**

I.e. a sequence whose index represents time

- Specifically, we have a **univariate** time series...
- ...Since we are tracking only quantity (i.e. one variable)

**Times series have one difference w.r.t. classical table datasets**

- ...I.e. their row index is **meaningful**
- Since it represents the **position** of the example in the sequence

**That said, we do not care about **how** time is represented**

- Hence, time series are stored **just as usual!**
- Their peculiarities arise when we start to manipulate them

# Time Series and Pandas

## In pandas:

- Time series are stored as usual, via `DataFrame` or `Series` objects
- ...You just need to pay more attention to the index

## It **may** be convenient using a `datetime` index

- A `datetime` object in python allows to manipulate dates/hours directly
  - E.g. get year/month/day/hour/minute...
- In pandas they can be used as indices, so that for example:
  - Time stamps are easier to read
  - We can sort rows by time
  - We can represent arbitrarily long gaps between measurements
  - ...


That said, we still deal with normal `DataFrame` or `Series` objects

# A Look at the Data

Let's have a look at all the data we loaded

Our module contains a function to plot NAB series:

```
In [4]: nab.plot_series(data)
```



- If are curious, you can look up the function code in the module



# A Look at the Data

Let's have a look at all the data we loaded

We can now move to other data structures

```
In [5]: labels.head()
```

```
Out[5]: 0    2014-11-01 19:00:00  
        1    2014-11-27 15:30:00  
        2    2014-12-25 15:00:00  
        3    2015-01-01 01:00:00  
        4    2015-01-27 00:00:00  
        dtype: datetime64[ns]
```

**labels** is a pandas series object

- Similar to a 1D array
- ...But with a well defined row **index**

**This series contains the **timestamp of all anomalies****


- They are all hand-labeled

# A Look at the Data

Let's have a look at all the data we loaded

Let's plot both the series and the labels:

```
In [6]: nab.plot_series(data, labels)
```



- Anomalies occur rarely (which is typical for this kind of problem)

# A Look at the Data

Let's have a look at all the data we loaded

Now the "windows" data structure:

```
In [7]: windows.head()
```

```
Out[7]:
```

	begin	end
0	2014-10-30 15:30:00	2014-11-03 22:30:00
1	2014-11-25 12:00:00	2014-11-29 19:00:00
2	2014-12-23 11:30:00	2014-12-27 18:30:00
3	2014-12-29 21:30:00	2015-01-03 04:30:00
4	2015-01-24 20:30:00	2015-01-29 03:30:00

**windows is a pandas DataFrame object**


- Contains the start/end of windows containing anomalies
- They represent a suitable "resolution" for detecting anomalies
- Reporting the presence of anomalies at any point of the window...
- ...Has some value for the company

# A Look at the Data

## Let's have a look at all the data we loaded

Let's plot the series, the labels, and the windows all together:

```
In [8]: nab.plot_series(data, labels, windows)
```



- Detections that occur too early/late count as misses