

Route decision: Port of Shanghai → Port of Rotterdam


PORT-SHANGHAI → PORT-ROTTERDAM · mode sea (STRICT) · cargo general · priority normal · scenarios: SUEZ_BLOCK · planned 2026-09-29 13:47 UTC

Recommendation: BALANCED, SEA via Malacca, Capegood. Expected arrival in **742 h** (30.9 days); plan for 754 h (p85), worst case 771 h (p95). Cost: freight INR 369,830. Peak leg risk 8%.
Hold vs reroute: waiting at CHOKE-SUEZ for reopening would arrive at p50 945 h, 212 h later than the best reroute → **REROUTE**.

Options

Option	Mode	Via	Plan h	p50 h	p85 h	p95 h	Freight	Risk
FASTEST	SEA	Malacca, Capegood	659	733	758	776	INR 332,505	18%
SAFEST	SEA	Malacca, Capegood	677	742	753	770	INR 384,139	8%
BALANCED	SEA	Malacca, Capegood	678	742	754	771	INR 369,830	8%

ETA bands (bar p50–p95, tick p85, line plan → fully-correlated worst case)



Routes



Recommended route solid, alternatives dashed. Blue sea, amber air, green rail, orange road.

FASTEST: SEA via Malacca, Capegood

SEA via Malacca, Capegood; expected 733.4 h (p85 757.6 h, p95 775.6 h), INR 332,505 freight, 0 handoffs. 8.3 h faster than the next option. INR 37,371 cheaper (freight) than the lowest-cost alternative.

#	Mode	To	km	Hours	Delay p85	Cost	Risk	Signal
1	SEA	Strait of Malacca	3,810	108.9	+26.6	INR 54,907	0%	
2	SEA	Cape of Good Hope	9,573	273.5	+27.5	INR 137,956	0%	
3	SEA	Port of Rotterdam	9,690	276.9	+55.3	INR 139,642	18%	LIVE_NEWS: Temporary transformer in Europoort relieves grid congestion - Port of Rotterdam

Transit 659.3 h + transfers 0.0 h + announced scenario delay 0.0 h = plan 659.3 h. Model delay buffer p50/p85/p95: +74.1 / +109.4 / +141.9 h. Route band p50 733.4 h, p85 757.6 h, p95 775.6 h (independent legs); 801.2 h if all legs are late together. Costs: linehaul INR 332,505, transfers INR 0, disruption surcharge INR 0.

Why the slowest leg (CHOKE-CAPEGOOD → PORT-ROTTERDAM, p85 55.3 h) is slow: exact Shapley attribution of the p85 delay model, hours relative to a 28.9 h baseline



SAFEST: SEA via Malacca, Capegood

SEA via Malacca, Capegood; expected 741.7 h (p85 753.3 h, p95 770.0 h), INR 384,139 freight, 2 handoffs. 8.3 h slower than FASTEST. INR 51,590 more (freight) than FASTEST.

#	Mode	To	km	Hours	Delay p85	Cost	Risk	Signal
1	SEA	Strait of Malacca	3,810	108.9	+26.6	INR 54,907	0%	
2	SEA	Cape of Good Hope	9,573	273.5	+27.5	INR 137,956	0%	
3	SEA	Duisburg Logport	9,608	274.5	+27.5	INR 138,455	0%	
4	handoff	Duisburg Logport		4.0	+0.0	INR 9,607	3%	
5	ROAD	Port of Rotterdam	166	2.4	+3.6	INR 19,195	0%	
6	handoff	Port of Rotterdam		14.0	+0.0	INR 24,017	8%	

Transit 659.3 h + transfers 18.0 h + announced scenario delay 0.0 h = plan 677.3 h. Model delay buffer p50/p85/p95: +64.4 / +85.3 / +115.3 h. Route band p50 741.7 h, p85 753.3 h, p95 770.0 h (independent legs); 792.6 h if all legs are late together. Costs: linehaul INR 350,514, transfers INR 33,624, disruption surcharge INR 0.

Why the slowest leg (CHOKE-MALACCA → CHOKE-CAPEGOOD, p85 27.5 h) is slow: exact Shapley attribution of the p85 delay model, hours relative to a 28.9 h baseline



BALANCED: SEA via Malacca, Capegood

SEA via Malacca, Capegood; expected 742.4 h (p85 753.9 h, p95 770.6 h), INR 369,830 freight, 2 handoffs. 9.0 h slower than FASTEST. INR 37,371 more (freight) than FASTEST.

#	Mode	To	km	Hours	Delay p85	Cost	Risk	Signal
1	SEA	Strait of Malacca	3,810	108.9	+26.6	INR 54,907	0%	
2	SEA	Cape of Good Hope	9,573	273.5	+27.5	INR 137,956	0%	
3	SEA	Rotterdam Distripark	9,700	277.1	+27.5	INR 139,775	0%	
4	handoff	Rotterdam Distripark		4.0	+0.0	INR 9,607	3%	
5	ROAD	Port of Rotterdam	31	0.5	+3.6	INR 3,568	0%	
6	handoff	Port of Rotterdam		14.0	+0.0	INR 24,017	8%	

Transit 660.0 h + transfers 18.0 h + announced scenario delay 0.0 h = plan 678.0 h. Model delay buffer p50/p85/p95: +64.4 / +85.3 / +115.3 h. Route band p50 742.4 h, p85 753.9 h, p95 770.6 h (independent legs); 793.3 h if all legs are late together. Costs: linehaul INR 336,205, transfers INR 33,624, disruption surcharge INR 0.

Why the slowest leg (CHOKE-MALACCA → CHOKE-CAPEGOOD, p85 27.5 h) is slow: exact Shapley attribution of the p85 delay model, hours relative to a 28.9 h baseline



Method: legs are priced with gradient-boosted quantile models (p50/p85/p95) trained on synthetic delays fitted to published UNCTAD, World Bank and STB statistics; FASTEST plans on p50, BALANCED on p85 (plus cargo carrying cost when a value is given), SAFEST on p95 plus 240 risk-hours per unit of threat. Route bands assume independent legs. Sea distances are great-circle between chokepoint waypoints. Currency conversion: live (open.er-api.com) as of Tue, 29 Sep 2026 00:02:31 +0000.