

# Manage the Data from Indoor Spaces: Models, Indexes & Query Processing

Huan Li

Database Laboratory, Zhejiang University

*lihuancs@zju.edu.cn*

March 21, 2016

# Overview

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

# Aims

- To give a brief review introduction to *indoor data management techniques*.
- To review a series of works in this field, including their proposed *models, indexes* and *algorithms*.
- To discuss how to bring those advanced theoretical contents into practice.

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

## About This Work...

*Probabilistic Threshold  $k$  Nearest Neighbor Queries over Moving Objects in Symbolic Indoor Space.* [4]

B. Yang, H. Lu, and C. S. Jensen.

- Published in year 2010 at the *EDBT* conference.
- *Minimal Indoor Walking Distance*(MIWD) along with algorithms and data structures are proposed for distance computing and storage.
- Effective object indexing structures, also capture the uncertainty of object locations.
- On this foundation, Probabilistic threshold  $k$ NN (PT $k$ NN) query is studied.

# Motivation

- Indoor positioning makes it possible to support interesting queries over large populations of moving objects.
  - shopping mall, airports, office buildings
  - $k$ NN queries over indoor moving objects enables the detection of approaching potential threats at sensitive locations in a subway system
- Existing  $k$ NN techniques in spatial and spatialtemporal databases are inapplicable in indoor spaces.
  - complex entities and topologies
  - indoor positioning techniques differ fundamentally from outdoor GPS, low sampling frequency and accuracy

# Minimal Indoor Walking Distance

*Minimal Indoor Walking Distance*(MIWD) is used as the distance metric in indoor spaces.



## Minimal Indoor Walking Distance

*Minimal Indoor Walking Distance*(MIWD) is used as the distance metric in indoor spaces.

The mapping *Rooms* determines the room of an indoor position:

## Minimal Indoor Walking Distance

*Minimal Indoor Walking Distance*(MIWD) is used as the distance metric in indoor spaces.

The mapping *Rooms* determines the room of an indoor position:

$$Rooms : positions \rightarrow \Sigma_{rooms} \quad (1)$$

## Minimal Indoor Walking Distance

*Minimal Indoor Walking Distance*(MIWD) is used as the distance metric in indoor spaces.

The mapping *Rooms* determines the room of an indoor position:

$$Rooms : positions \rightarrow \Sigma_{rooms} \quad (1)$$

The mapping *Doors* maps a room to the doors that connect the room to an adjacent room:

# Minimal Indoor Walking Distance

*Minimal Indoor Walking Distance*(MIWD) is used as the distance metric in indoor spaces.

The mapping *Rooms* determines the room of an indoor position:


$$Rooms : positions \rightarrow \Sigma_{rooms} \quad (1)$$

The mapping *Doors* maps a room to the doors that connect the room to an adjacent room:

$$Doors : \Sigma_{rooms} \rightarrow 2^{\Sigma_{doors}} \quad (2)$$

## 2.3 Probabilistic Threshold k Nearest Neighbor Queries over Moving Objects in Symbolic Indoor Space

# Minimal Indoor Walking Distance



- intra-room obstructed distance, termed as  $d_o$ . E.g.,  
 $d_o(p_2, p_3) = |p_2 p_3|$  and  
 $d_o(p_4, p_5) = |p_4 c| + |c p_5|$ .
- if in different rooms, it should take into account the doors connecting the rooms. E.g.,  
 $d_{MIN}(p_1, p_2) = |p_1 d_{32}| + |d_{17} p_9|$ .
- if there exist several paths, the correct path should be the shortest one. E.g.,  
 $d_{MIN}(p_6, p_7) = |p_6 d_{12}| + |d_{12} p_7|$   
 $\neq |p_6 d_{15}| + |d_{15} d_{13}| + |d_{13} p_7|$ .



## Minimal Indoor Walking Distance

All door-to-door shortest path distances can be computed and recorded in a hash table D2D according to the Doors Graph.

# Minimal Indoor Walking Distance

All door-to-door shortest path distances can be computed and recorded in a hash table D2D according to the Doors Graph.

$$\text{D2D} : \{(d_p, d_j)\} \rightarrow R, \quad d_p, d_q \in \Sigma_{\text{doors}}. \quad (3)$$



# Minimal Indoor Walking Distance

All door-to-door shortest path distances can be computed and recorded in a hash table D2D according to the Doors Graph.

$$\text{D2D} : \{(d_p, d_j)\} \rightarrow R, \quad d_p, d_q \in \Sigma_{\text{doors}}. \quad (3)$$

Consequently, for two positions  $p$  and  $q$  in different rooms.

# Minimal Indoor Walking Distance

All door-to-door shortest path distances can be computed and recorded in a hash table D2D according to the Doors Graph.

$$\text{D2D} : \{(d_p, d_j)\} \rightarrow R, \quad d_p, d_q \in \Sigma_{\text{doors}}. \quad (3)$$

Consequently, for two positions  $p$  and  $q$  in different rooms.

$$d_{\text{MIN}}(d_p, d_q) = d_o(p, d_p) + \text{D2D}(d_p, d_q) + d_o(d_q, q) \quad (4)$$

where  $d_p(d_q)$  ranges over all doors of room  $p(q)$ .

---

**Algorithm 1**  $d_{\text{MIW}}(\text{Position } p, \text{Position } q)$ 


---

```

1: if Rooms(p)=Rooms(q) then
2:   minDist ← do(p, q);
3: else
4:   minDist ← +∞
5: for each door dp in Doors(Rooms(p)) do
6:   for each door dq ≠ dp in Doors(Rooms(q)) do
7:     l ← do(p, dp) + do(dq, q) + D2D(dp, dq)
8:     if l < minDist then
9:       minDist ← l;
10: return minDist;
```

---

it is possible to adapt this notion of distance to accommodate other semantics. For example, a person might prefer a longer indoor path that passes as few doors as possible.

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
- 4. Indoor Movement Analysis**
5. Appendix

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
- 5. Appendix**

## References



M. F. Worboys.  
Modeling indoor space.  
In *ISA*, pp. 1–6, 2011.



C. S. Jensen, H. Lu, and B. Yang.  
Graph model based indoor tracking.  
In *MDM*, pp. 122–131, 2009.



B. Yang, H. Lu, and C. S. Jensen.  
Scalable continuous range monitoring of moving objects in symbolic indoor space.  
In *CIKM*, pp. 671–680, 2009.



B. Yang, H. Lu, and C. S. Jensen.  
Probabilistic threshold k nearest neighbor queries over moving objects in symbolic indoor space.  
In *EDBT*, pp. 335–346, 2010.

## References



H. Lu, B. Yang, and C. S. Jensen.

Spatio-temporal Joins on Symbolic Indoor Tracking Data.

In *ICDE*, pp. 816–827, 2011.



H. Lu, X. Cao, and C. S. Jensen.

A foundation for efficient indoor distance-aware query processing.

In *ICDE*, pp. 438–449, 2012.



X. Xie, H. Lu, and T. B. Pedersen.

Efficient distance-aware query evaluation on indoor moving objects.

In *ICDE*, pp. 434–445, 2013.

The End. Thanks :)