

Manage the Data from Indoor Spaces: Models, Indexes & Query Processing

Huan Li

Database Laboratory, Zhejiang University

lihuancs@zju.edu.cn

March 15, 2016

Overview

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

Aims

- To give a brief review introduction to *indoor data management techniques*.
- To review a series of works in this field, including their proposed *models, indexes* and *algorithms*.
- To discuss how to bring those advanced theoretical contents into practice.

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

About This Work...

Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space. [3]

B. Yang, H. Lu, and C. S. Jensen.

- Published in *CIKM' 2009*.
- Application: continuously monitor indoor moving objects for space use analysis or security purposes.
- An incremental, query-aware continuous range query processing technique for objects moving in indoor space.
- Use maximum-speed constraint on object movement to refine the uncertain results.

Motivation

- People spend much time in indoor spaces.
- Indoor spaces are becoming increasingly larger and complex.
 - E.g., London Underground, 268 stations, 408 kilometers of network, +4 million daily passengers.
- Indoor monitoring of people can help support.
 - space use analysis
 - security purposes


Preliminaries: Indoors vs. Outdoors

- Modeling of indoor spaces do not assume
 - Euclidean space. (since obstacles render movement more constrained)
 - Spatial network. (since indoor movement is less constrained than movements in polylines)
- Instead indoor spaces are characterized by entities.
 - Doors, rooms, hallways, staircase, etc.
- **Symbolic models** are more suitable.
- *GPS* and *cellular tracking* do not work indoors.
- Sensing devices are used to detect objects within their activation range, e.g., RFID readers or Bluetooth hotspots.

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Positioning Devices Deployment Graph

- Two types of positioning devices
 - Partitioning Device – *undirected* (UP), e.g., d_{21} – *directed* (DP), e.g., d_{11} and $d_{11'}$
 - Presence Device – (PR)
- Note an indoor space is partitioned into *activation ranges* and *cells*




Deployment Graph

- $G = \{C, E, \Sigma_{devices}, l_E\}$
- C : the set of cells
- E : the set of edges, $\{c_i, c_j\}$ where $c_i, c_j \in C$
- $\Sigma_{devices}$: a mapping from *deviceID* to activation range and type
- l_E maps an edge to a set of positioning devices, i.e., $E \rightarrow 2^{\Sigma_{devices}}$

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space


Positioning Devices Deployment Graph

- Two types of positioning devices
 - Partitioning Device – *undirected* (UP), e.g., d_{21} – *directed* (DP), e.g., d_{11} and $d_{11'}$
 - Presence Device – (PR)
- Note an indoor space is partitioned into *activation ranges* and *cells*




Deployment Graph

- $G = \{C, E, \Sigma_{devices}, l_E\}$
- C : the set of cells
- E : the set of edges, $\{c_i, c_j\}$ where $c_i, c_j \in C$
- $\Sigma_{devices}$: a mapping from *deviceID* to activation range and type
- l_E maps an edge to a set of positioning devices, i.e., $E \rightarrow 2^{\Sigma_{devices}}$



2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

States of Indoor Moving Objects



- An object is in an **active state** when it is inside the activation range of a positioning device.
- Otherwise the object is in an **inactive state**
- When an object is in the inactive state it is
 - **nondeterministic** if it can be in more than one cell
 - **deterministic** if it is in one specific cell

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; \text{ deviceID} \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; \text{ deviceID} \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; deviceID \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; cellID \in C, O_D \subseteq O_{indoor}$$

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; deviceID \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; cellID \in C, O_D \subseteq O_{indoor}$$

Cell Nondeterministic Hash Table(CNHT) maps each cell to a set of nondeterministic objects:

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; deviceID \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; cellID \in C, O_D \subseteq O_{indoor}$$

Cell Nondeterministic Hash Table(CNHT) maps each cell to a set of nondeterministic objects:

$$CNHT[cellID] = O_N; cellID \in C, O_N \subseteq O_{indoor}$$

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; deviceID \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; cellID \in C, O_D \subseteq O_{indoor}$$

Cell Nondeterministic Hash Table(CNHT) maps each cell to a set of nondeterministic objects:

$$CNHT[cellID] = O_N; cellID \in C, O_N \subseteq O_{indoor}$$

Object Hash Table(OHT) maps objects to their current data(state, time, cell(s) the object can be in)

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; deviceID \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; cellID \in C, O_D \subseteq O_{indoor}$$

Cell Nondeterministic Hash Table(CNHT) maps each cell to a set of nondeterministic objects:

$$CNHT[cellID] = O_N; cellID \in C, O_N \subseteq O_{indoor}$$

Object Hash Table(OHT) maps objects to their current data(state, time, cell(s) the object can be in)

$$OHT[objectID] = (STATE, t, IDSet); objectID \in O_{indoor}$$

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; deviceID \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; cellID \in C, O_D \subseteq O_{indoor}$$

Cell Nondeterministic Hash Table(CNHT) maps each cell to a set of nondeterministic objects:

$$CNHT[cellID] = O_N; cellID \in C, O_N \subseteq O_{indoor}$$

Object Hash Table(OHT) maps objects to their current data(state, time, cell(s) the object can be in)

$$OHT[objectID] = (STATE, t, IDSet); objectID \in O_{indoor}$$

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

RFID Deployment Graph Construction

① Lines 1: reset $IDSet$

Algorithm 1 `updateHashTables`(Pre-processing output O , DeploymentGraph G)

```

1:  $IDSet\ sSet \leftarrow \emptyset$ ;
2: if  $O.flag = ENTER$  then
3:    $sSet \leftarrow OHT[O.objectID].IDSet$ ;
4:   if  $OHT[O.objectID].STATE = Active$  then
5:     for the single element  $c$  in  $sSet$  do
6:       Delete  $O.objectID$  from  $DHT[c]$ ;
7:   else if  $OHT[O.objectID].STATE = Deterministic$  then
8:     for the single element  $c$  in  $sSet$  do
9:       Delete  $O.objectID$  from  $CDHT[c]$ ;
10:  else
11:    for each element  $c$  in  $sSet$  do
12:      Delete  $O.objectID$  from  $CNHT[c]$ ;
13:  Add  $O.objectID$  to  $DHT[O.deviceID]$ ;
14:   $OHT[O.objectID] \leftarrow (Active, O.t, \{O.deviceID\})$ ;
15: else
16:  Delete  $O.objectID$  from  $DHT[O.deviceID]$ ;
17:   $sSet \leftarrow G.\ell_E^{-1}(O.deviceID)$ ;
18:  if  $Devices(O.deviceID).TYPE = UP$  then
19:     $OHT[O.objectID] \leftarrow (Nondeterministic, O.t, sSet)$ ;
20:    for each element  $c$  in  $sSet$  do
21:      Add  $O.objectID$  to  $CNHT[c]$ ;
22:  else
23:     $OHT[O.objectID] \leftarrow (Deterministic, O.t, sSet)$ ;
24:    for the single element  $c$  in  $sSet$  do
25:      Add  $O.objectID$  to  $CDHT[c]$ ;

```

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

RFID Deployment Graph Construction

Algorithm 1 `updateHashTables`(Pre-processing output O , DeploymentGraph G)

```

1:  $IDSet\ sSet \leftarrow \emptyset$ ;
2: if  $O.flag = ENTER$  then
3:    $sSet \leftarrow OHT[O.objectID].IDSet$ ;
4:   if  $OHT[O.objectID].STATE = Active$  then
5:     for the single element  $c$  in  $sSet$  do
6:       Delete  $O.objectID$  from  $DHT[c]$ ;
7:   else if  $OHT[O.objectID].STATE = Deterministic$  then
8:     for the single element  $c$  in  $sSet$  do
9:       Delete  $O.objectID$  from  $CDHT[c]$ ;
10:  else
11:    for each element  $c$  in  $sSet$  do
12:      Delete  $O.objectID$  from  $CNHT[c]$ ;
13:  Add  $O.objectID$  to  $DHT[O.deviceID]$ ;
14:   $OHT[O.objectID] \leftarrow (Active, O.t, \{O.deviceID\})$ ;
15: else
16:  Delete  $O.objectID$  from  $DHT[O.deviceID]$ ;
17:   $sSet \leftarrow G.\ell_E^{-1}(O.deviceID)$ ;
18:  if  $Devices(O.deviceID).TYPE = UP$  then
19:     $OHT[O.objectID] \leftarrow (Nondeterministic, O.t, sSet)$ ;
20:    for each element  $c$  in  $sSet$  do
21:      Add  $O.objectID$  to  $CNHT[c]$ ;
22:  else
23:     $OHT[O.objectID] \leftarrow (Deterministic, O.t, sSet)$ ;
24:    for the single element  $c$  in  $sSet$  do
25:      Add  $O.objectID$  to  $CDHT[c]$ ;

```

① Lines 1: reset $IDSet$

② Lines 2–12: $O.flag$ is ENTER so check the object's previous state. Remove O from the corresponding table according to its previous state

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

RFID Deployment Graph Construction

Algorithm 1 updateHashTables(Pre-processing output O , DeploymentGraph G)

```

1: IDSet  $sSet \leftarrow \emptyset$ ;
2: if  $O.flag = ENTER$  then
3:    $sSet \leftarrow OHT[O.objectID].IDSet$ ;
4:   if  $OHT[O.objectID].STATE = Active$  then
5:     for the single element  $c$  in  $sSet$  do
6:       Delete  $O.objectID$  from  $DHT[c]$ ;
7:   else if  $OHT[O.objectID].STATE = Deterministic$  then
8:     for the single element  $c$  in  $sSet$  do
9:       Delete  $O.objectID$  from  $CDHT[c]$ ;
10:  else
11:    for each element  $c$  in  $sSet$  do
12:      Delete  $O.objectID$  from  $CNHT[c]$ ;
13:  Add  $O.objectID$  to  $DHT[O.deviceID]$ ;
14:   $OHT[O.objectID] \leftarrow (Active, O.t, \{O.deviceID\})$ ;
15: else
16:  Delete  $O.objectID$  from  $DHT[O.deviceID]$ ;
17:   $sSet \leftarrow G.\ell_E^{-1}(O.deviceID)$ ;
18:  if  $Devices(O.deviceID).TYPE = UP$  then
19:     $OHT[O.objectID] \leftarrow (Nondeterministic, O.t, sSet)$ ;
20:    for each element  $c$  in  $sSet$  do
21:      Add  $O.objectID$  to  $CNHT[c]$ ;
22:  else
23:     $OHT[O.objectID] \leftarrow (Deterministic, O.t, sSet)$ ;
24:    for the single element  $c$  in  $sSet$  do
25:      Add  $O.objectID$  to  $CDHT[c]$ ;

```

- ① Lines 1: reset $IDSet$
- ② Lines 2–12: $O.flag$ is ENTER so check the object's previous state. Remove O from the corresponding table according its previous state
- ③ Lines 13–14: add O to table of active objects (DHT), and update O 's in the objects' table (OHT)

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

RFID Deployment Graph Construction

Algorithm 1 updateHashTables(Pre-processing output O , DeploymentGraph G)

```

1: IDSet  $sSet \leftarrow \emptyset$ ;
2: if  $O.flag = ENTER$  then
3:    $sSet \leftarrow OHT[O.objectID].IDSet$ ;
4:   if  $OHT[O.objectID].STATE = Active$  then
5:     for the single element  $c$  in  $sSet$  do
6:       Delete  $O.objectID$  from  $DHT[c]$ ;
7:   else if  $OHT[O.objectID].STATE = Deterministic$  then
8:     for the single element  $c$  in  $sSet$  do
9:       Delete  $O.objectID$  from  $CDHT[c]$ ;
10:  else
11:    for each element  $c$  in  $sSet$  do
12:      Delete  $O.objectID$  from  $CNHT[c]$ ;
13:  Add  $O.objectID$  to  $DHT[O.deviceID]$ ;
14:   $OHT[O.objectID] \leftarrow (Active, O.t, \{O.deviceID\})$ ;
15: else
16:   Delete  $O.objectID$  from  $DHT[O.deviceID]$ ;
17:    $sSet \leftarrow G.\ell_E^{-1}(O.deviceID)$ ;
18:   if  $Devices(O.deviceID).TYPE = UP$  then
19:      $OHT[O.objectID] \leftarrow (Nondeterministic, O.t, sSet)$ ;
20:     for each element  $c$  in  $sSet$  do
21:       Add  $O.objectID$  to  $CNHT[c]$ ;
22:   else
23:      $OHT[O.objectID] \leftarrow (Deterministic, O.t, sSet)$ ;
24:     for the single element  $c$  in  $sSet$  do
25:       Add  $O.objectID$  to  $CDHT[c]$ ;

```

- ① Lines 1: reset $IDSet$
- ② Lines 2–12: $O.flag$ is ENTER so check the object's previous state. Remove O from the corresponding table according its previous state
- ③ Lines 13–14: add O to table of active objects (DHT), and update O 's in the objects' table (OHT)
- ④ Lines 16–17: $O.flag$ is LEAVE so remove the object from DHT. Get the possible cells that O can move to

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

RFID Deployment Graph Construction

Algorithm 1 `updateHashTables`(Pre-processing output O , DeploymentGraph G)

```

1:  $IDSet\ sSet \leftarrow \emptyset$ ;
2: if  $O.flag = ENTER$  then
3:    $sSet \leftarrow OHT[O.objectID].IDSet$ ;
4:   if  $OHT[O.objectID].STATE = Active$  then
5:     for the single element  $c$  in  $sSet$  do
6:       Delete  $O.objectID$  from  $DHT[c]$ ;
7:   else if  $OHT[O.objectID].STATE = Deterministic$  then
8:     for the single element  $c$  in  $sSet$  do
9:       Delete  $O.objectID$  from  $CDHT[c]$ ;
10:  else
11:    for each element  $c$  in  $sSet$  do
12:      Delete  $O.objectID$  from  $CNHT[c]$ ;
13:  Add  $O.objectID$  to  $DHT[O.deviceID]$ ;
14:   $OHT[O.objectID] \leftarrow (Active, O.t, \{O.deviceID\})$ ;
15: else
16:  Delete  $O.objectID$  from  $DHT[O.deviceID]$ ;
17:   $sSet \leftarrow G.\ell_E^{-1}(O.deviceID)$ ;
18:  if  $Devices(O.deviceID).TYPE = UP$  then
19:     $OHT[O.objectID] \leftarrow (Nondeterministic, O.t, sSet)$ ;
20:    for each element  $c$  in  $sSet$  do
21:      Add  $O.objectID$  to  $CNHT[c]$ ;
22:  else
23:     $OHT[O.objectID] \leftarrow (Deterministic, O.t, sSet)$ ;
24:    for the single element  $c$  in  $sSet$  do
25:      Add  $O.objectID$  to  $CDHT[c]$ ;

```

- ① Lines 1: reset $IDSet$
- ② Lines 2–12: $O.flag$ is ENTER so check the object's previous state. Remove O from the corresponding table according its previous state
- ③ Lines 13–14: add O to table of active objects (DHT), and update O 's in the objects' table (OHT)
- ④ Lines 16–17: $O.flag$ is LEAVE so remove the object from DHT. Get the possible cells that O can move to
- ⑤ Lines 18–25: if the device is undirected, set O in OHT and add O to CNHT for the cells in $sSet$, else apply the same to CDHT

Continuous Range Monitoring: Query Definition

- A *Continuous Range Monitoring Query* (CRMQ)
 - takes an **indoor spatial range** R as parameter
 - keeps reporting the objects when it is registered for a certain time frame $[t_s, t_e]$
- The **query result** \mathcal{M} – the set of moving objects in R – is maintained as follows:

$$\forall t \in [t_s, t_e] : o \in CRMQ[R](\mathcal{M}) \Leftrightarrow o \in \mathcal{M} \wedge pos_{\mathcal{M}}(o, t) \in R$$

where $pos_{\mathcal{M}}$ is a function that can determine the position of object o at time t

- Multiple monitoring queries may coexist

For a CRMQ query, a *critical device* is one from which a new observation can potentially change the query result (either certain or uncertain)




- ◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ↺ 🔍 ↻

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Critical Devices

- To handle concurrent CRMQs, a *Query Hash Table* is created hold the results
 - $QHT[queryID] = (CR, UR); CR \subseteq O_{indoor}, UR \subseteq O_{indoor}$
 - where CR is the certain result and UR is the uncertain result
- Overview



1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
- 4. Indoor Movement Analysis**
5. Appendix

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
- 5. Appendix**

References



M. F. Worboys.

Modeling indoor space.

In *ISA*, pp. 1–6, 2011.



X. Xie, H. Lu, and T. B. Pedersen.

Efficient distance-aware query evaluation on indoor moving objects.

In *ICDE*, pp. 434–445, 2013.



B. Yang, H. Lu, and C. S. Jensen.

Scalable continuous range monitoring of moving objects in symbolic indoor space.

In *CIKM*, pp. 671–680, 2009.



B. Yang, H. Lu, and C. S. Jensen.

Probabilistic threshold k nearest neighbor queries over moving objects in symbolic indoor space.

In *EDBT*, pp. 335–346, 2010.

References



H. Lu, X. Cao, and C. S. Jensen.

A foundation for efficient indoor distance-aware query processing.

In *ICDE*, pp. 438–449, 2012.



C. S. Jensen, H. Lu, and B. Yang.

Graph model based indoor tracking.

In *MDM*, pp. 122–131, 2009.



H. Lu, B. Yang, and C. S. Jensen.

Spatio-temporal Joins on Symbolic Indoor Tracking Data.

In *ICDE*, pp. 816–827, 2011.

The End. Thanks :)