

Manage the Data from Indoor Spaces: Models, Indexes & Query Processing

Huan Li

Database Laboratory, Zhejiang University

lihuancs@zju.edu.cn

March 24, 2016

Overview

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

1. **Outlines**
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

About This Work...

Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space. [2]

B. Yang, H. Lu, and C. S. Jensen.

- Published in *CIKM' 2009*.
- Application: continuously monitor indoor moving objects for space use analysis or security purposes.
- An incremental, query-aware continuous range query processing technique for objects moving in indoor space.
- Use maximum speed constraint on object movement to refine the uncertain results.

Motivation

- People spend much time in indoor spaces.
- Indoor spaces are becoming increasingly larger and complex.
 - E.g., London Underground, 268 stations, 408 kilometers of network, +4 million daily passengers.
- Indoor monitoring of people can help support.
 - space use analysis
 - security purposes


Preliminaries: Indoors vs. Outdoors

- Modeling of indoor spaces do not assume [4]
 - Euclidean space. (since obstacles render movement more constrained)
 - Spatial network. (since indoor movement is less constrained than movements in polylines)
- Instead indoor spaces are characterized by entities [1].
 - Doors, rooms, hallways, staircase, etc.
- **Symbolic models** are more suitable [3].
- *GPS* and *cellular tracking* do not work indoors.
- Sensing devices are used to detect objects within their activation range, e.g., RFID readers or Bluetooth hotspots.

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Positioning Devices Deployment Graph

- Two types of positioning devices
 - Partitioning Device – *undirected* (**UP**), e.g., d_{21} – *directed* (**DP**), e.g., d_{11} and $d_{11'}$
 - Presence Device – (**PR**)
- Note an indoor space is partitioned into *activation ranges* and *cells*




Deployment Graph

- $G = \{C, E, \Sigma_{devices}, l_E\}$
- C : the set of cells
- E : the set of edges, $\{c_i, c_j\}$ where $c_i, c_j \in C$
- $\Sigma_{devices}$: a mapping from *deviceID* to activation range and type
- l_E maps an edge to a set of positioning devices, i.e., $E \rightarrow 2^{\Sigma_{devices}}$

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space


Positioning Devices Deployment Graph

- Two types of positioning devices
 - Partitioning Device – *undirected* (**UP**), e.g., d_{21} – *directed* (**DP**), e.g., d_{11} and $d_{11'}$
 - Presence Device – (**PR**)
- Note an indoor space is partitioned into *activation ranges* and *cells*




Deployment Graph

- $G = \{C, E, \Sigma_{devices}, l_E\}$
- C : the set of cells
- E : the set of edges, $\{c_i, c_j\}$ where $c_i, c_j \in C$
- $\Sigma_{devices}$: a mapping from *deviceID* to activation range and type
- l_E maps an edge to a set of positioning devices, i.e., $E \rightarrow 2^{\Sigma_{devices}}$



2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

States of Indoor Moving Objects



- An object is in an **active state** when it is inside the activation range of a positioning device.
- Otherwise the object is in an **inactive state**
- When an object is in the inactive state it is
 - **nondeterministic** if it can be in more than one cell
 - **deterministic** if it is in one specific cell

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; \text{ deviceID} \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; \text{ deviceID} \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; \text{ deviceID} \in \Sigma_{\text{devices}}, O_A \subseteq O_{\text{indoor}}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; \text{ cellID} \in C, O_D \subseteq O_{\text{indoor}}$$

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; deviceID \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; cellID \in C, O_D \subseteq O_{indoor}$$

Cell Nondeterministic Hash Table(CNHT) maps each cell to a set of nondeterministic objects:

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; deviceID \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; cellID \in C, O_D \subseteq O_{indoor}$$

Cell Nondeterministic Hash Table(CNHT) maps each cell to a set of nondeterministic objects:

$$CNHT[cellID] = O_N; cellID \in C, O_N \subseteq O_{indoor}$$

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; deviceID \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; cellID \in C, O_D \subseteq O_{indoor}$$

Cell Nondeterministic Hash Table(CNHT) maps each cell to a set of nondeterministic objects:

$$CNHT[cellID] = O_N; cellID \in C, O_N \subseteq O_{indoor}$$

Object Hash Table(OHT) maps objects to their current data(state, time, cell(s) the object can be in)

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; deviceID \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; cellID \in C, O_D \subseteq O_{indoor}$$

Cell Nondeterministic Hash Table(CNHT) maps each cell to a set of nondeterministic objects:

$$CNHT[cellID] = O_N; cellID \in C, O_N \subseteq O_{indoor}$$

Object Hash Table(OHT) maps objects to their current data(state, time, cell(s) the object can be in)

$$OHT[objectID] = (STATE, t, IDSet); objectID \in O_{indoor}$$

Indexing Indoor Moving Objects

The proposed indexing scheme uses 4 hash tables

Device Hash Table(DHT) maps each device to a set of active objects:

$$DHT[deviceID] = O_A; deviceID \in \Sigma_{devices}, O_A \subseteq O_{indoor}$$

Cell Deterministic Hash Table(CDHT) maps each cell to a set of deterministic objects:

$$CDHT[cellID] = O_D; cellID \in C, O_D \subseteq O_{indoor}$$

Cell Nondeterministic Hash Table(CNHT) maps each cell to a set of nondeterministic objects:

$$CNHT[cellID] = O_N; cellID \in C, O_N \subseteq O_{indoor}$$

Object Hash Table(OHT) maps objects to their current data(state, time, cell(s) the object can be in)

$$OHT[objectID] = (STATE, t, IDSet); objectID \in O_{indoor}$$

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

RFID Deployment Graph Construction

Algorithm 1 updateHashTables(Pre-processing output O , DeploymentGraph G)

```

1: IDSet  $sSet \leftarrow \emptyset$ ;
2: if  $O.flag = ENTER$  then
3:    $sSet \leftarrow OHT[O.objectID].IDSet$ ;
4:   if  $OHT[O.objectID].STATE = Active$  then
5:     for the single element  $c$  in  $sSet$  do
6:       Delete  $O.objectID$  from  $DHT[c]$ ;
7:   else if  $OHT[O.objectID].STATE = Deterministic$  then
8:     for the single element  $c$  in  $sSet$  do
9:       Delete  $O.objectID$  from  $CDHT[c]$ ;
10:  else
11:    for each element  $c$  in  $sSet$  do
12:      Delete  $O.objectID$  from  $CNHT[c]$ ;
13:  Add  $O.objectID$  to  $DHT[O.deviceID]$ ;
14:   $OHT[O.objectID] \leftarrow (Active, O.t, \{O.deviceID\})$ ;
15: else
16:  Delete  $O.objectID$  from  $DHT[O.deviceID]$ ;
17:   $sSet \leftarrow G.\ell_E^{-1}(O.deviceID)$ ;
18:  if  $Devices(O.deviceID).TYPE = UP$  then
19:     $OHT[O.objectID] \leftarrow (Nondeterministic, O.t, sSet)$ ;
20:    for each element  $c$  in  $sSet$  do
21:      Add  $O.objectID$  to  $CNHT[c]$ ;
22:  else
23:     $OHT[O.objectID] \leftarrow (Deterministic, O.t, sSet)$ ;
24:    for the single element  $c$  in  $sSet$  do
25:      Add  $O.objectID$  to  $CDHT[c]$ ;

```

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

RFID Deployment Graph Construction

Algorithm 1 `updateHashTables`(Pre-processing output O , DeploymentGraph G)

```

1:  $IDSet\ sSet \leftarrow \emptyset$ ;
2: if  $O.flag = ENTER$  then
3:    $sSet \leftarrow OHT[O.objectID].IDSet$ ;
4:   if  $OHT[O.objectID].STATE = Active$  then
5:     for the single element  $c$  in  $sSet$  do
6:       Delete  $O.objectID$  from  $DHT[c]$ ;
7:   else if  $OHT[O.objectID].STATE = Deterministic$  then
8:     for the single element  $c$  in  $sSet$  do
9:       Delete  $O.objectID$  from  $CDHT[c]$ ;
10:  else
11:    for each element  $c$  in  $sSet$  do
12:      Delete  $O.objectID$  from  $CNHT[c]$ ;
13:  Add  $O.objectID$  to  $DHT[O.deviceID]$ ;
14:   $OHT[O.objectID] \leftarrow (Active, O.t, \{O.deviceID\})$ ;
15: else
16:  Delete  $O.objectID$  from  $DHT[O.deviceID]$ ;
17:   $sSet \leftarrow G.\ell_E^{-1}(O.deviceID)$ ;
18:  if  $Devices(O.deviceID).TYPE = UP$  then
19:     $OHT[O.objectID] \leftarrow (Nondeterministic, O.t, sSet)$ ;
20:    for each element  $c$  in  $sSet$  do
21:      Add  $O.objectID$  to  $CNHT[c]$ ;
22:  else
23:     $OHT[O.objectID] \leftarrow (Deterministic, O.t, sSet)$ ;
24:    for the single element  $c$  in  $sSet$  do
25:      Add  $O.objectID$  to  $CDHT[c]$ ;

```

① Line 1: reset $IDSet$

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

RFID Deployment Graph Construction

Algorithm 1 `updateHashTables`(Pre-processing output O , DeploymentGraph G)

```

1:  $IDSet\ sSet \leftarrow \emptyset$ ;
2: if  $O.flag = ENTER$  then
3:    $sSet \leftarrow OHT[O.objectID].IDSet$ ;
4:   if  $OHT[O.objectID].STATE = Active$  then
5:     for the single element  $c$  in  $sSet$  do
6:       Delete  $O.objectID$  from  $DHT[c]$ ;
7:   else if  $OHT[O.objectID].STATE = Deterministic$  then
8:     for the single element  $c$  in  $sSet$  do
9:       Delete  $O.objectID$  from  $CDHT[c]$ ;
10:  else
11:    for each element  $c$  in  $sSet$  do
12:      Delete  $O.objectID$  from  $CNHT[c]$ ;
13:  Add  $O.objectID$  to  $DHT[O.deviceID]$ ;
14:   $OHT[O.objectID] \leftarrow (Active, O.t, \{O.deviceID\})$ ;
15: else
16:  Delete  $O.objectID$  from  $DHT[O.deviceID]$ ;
17:   $sSet \leftarrow G.\ell_E^{-1}(O.deviceID)$ ;
18:  if  $Devices(O.deviceID).TYPE = UP$  then
19:     $OHT[O.objectID] \leftarrow (Nondeterministic, O.t, sSet)$ ;
20:    for each element  $c$  in  $sSet$  do
21:      Add  $O.objectID$  to  $CNHT[c]$ ;
22:  else
23:     $OHT[O.objectID] \leftarrow (Deterministic, O.t, sSet)$ ;
24:    for the single element  $c$  in  $sSet$  do
25:      Add  $O.objectID$  to  $CDHT[c]$ ;

```

① Line 1: reset $IDSet$

② Lines 2–12: $O.flag$ is ENTER so check the object's previous state. Remove O from the corresponding table according to its previous state

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

RFID Deployment Graph Construction

Algorithm 1 updateHashTables(Pre-processing output O , DeploymentGraph G)

```

1: IDSet  $sSet \leftarrow \emptyset$ ;
2: if  $O.flag = ENTER$  then
3:    $sSet \leftarrow OHT[O.objectID].IDSet$ ;
4:   if  $OHT[O.objectID].STATE = Active$  then
5:     for the single element  $c$  in  $sSet$  do
6:       Delete  $O.objectID$  from  $DHT[c]$ ;
7:   else if  $OHT[O.objectID].STATE = Deterministic$  then
8:     for the single element  $c$  in  $sSet$  do
9:       Delete  $O.objectID$  from  $CDHT[c]$ ;
10:  else
11:    for each element  $c$  in  $sSet$  do
12:      Delete  $O.objectID$  from  $CNHT[c]$ ;
13:  Add  $O.objectID$  to  $DHT[O.deviceID]$ ;
14:   $OHT[O.objectID] \leftarrow (Active, O.t, \{O.deviceID\})$ ;
15: else
16:  Delete  $O.objectID$  from  $DHT[O.deviceID]$ ;
17:   $sSet \leftarrow G.\ell_E^{-1}(O.deviceID)$ ;
18:  if  $Devices(O.deviceID).TYPE = UP$  then
19:     $OHT[O.objectID] \leftarrow (Nondeterministic, O.t, sSet)$ ;
20:    for each element  $c$  in  $sSet$  do
21:      Add  $O.objectID$  to  $CNHT[c]$ ;
22:  else
23:     $OHT[O.objectID] \leftarrow (Deterministic, O.t, sSet)$ ;
24:    for the single element  $c$  in  $sSet$  do
25:      Add  $O.objectID$  to  $CDHT[c]$ ;

```

- ① Line 1: reset $IDSet$
- ② Lines 2–12: $O.flag$ is ENTER so check the object's previous state. Remove O from the corresponding table according its previous state
- ③ Lines 13–14: add O to table of active objects (DHT), and update O 's in the objects' table (OHT)

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

RFID Deployment Graph Construction

Algorithm 1 updateHashTables(Pre-processing output O , DeploymentGraph G)

```

1: IDSet  $sSet \leftarrow \emptyset$ ;
2: if  $O.flag = ENTER$  then
3:    $sSet \leftarrow OHT[O.objectID].IDSet$ ;
4:   if  $OHT[O.objectID].STATE = Active$  then
5:     for the single element  $c$  in  $sSet$  do
6:       Delete  $O.objectID$  from  $DHT[c]$ ;
7:   else if  $OHT[O.objectID].STATE = Deterministic$  then
8:     for the single element  $c$  in  $sSet$  do
9:       Delete  $O.objectID$  from  $CDHT[c]$ ;
10:  else
11:    for each element  $c$  in  $sSet$  do
12:      Delete  $O.objectID$  from  $CNHT[c]$ ;
13:  Add  $O.objectID$  to  $DHT[O.deviceID]$ ;
14:   $OHT[O.objectID] \leftarrow (Active, O.t, \{O.deviceID\})$ ;
15: else
16:   Delete  $O.objectID$  from  $DHT[O.deviceID]$ ;
17:    $sSet \leftarrow G.\ell_E^{-1}(O.deviceID)$ ;
18:   if  $Devices(O.deviceID).TYPE = UP$  then
19:      $OHT[O.objectID] \leftarrow (Nondeterministic, O.t, sSet)$ ;
20:     for each element  $c$  in  $sSet$  do
21:       Add  $O.objectID$  to  $CNHT[c]$ ;
22:   else
23:      $OHT[O.objectID] \leftarrow (Deterministic, O.t, sSet)$ ;
24:     for the single element  $c$  in  $sSet$  do
25:       Add  $O.objectID$  to  $CDHT[c]$ ;

```

- ① Line 1: reset $IDSet$
- ② Lines 2–12: $O.flag$ is ENTER so check the object's previous state. Remove O from the corresponding table according its previous state
- ③ Lines 13–14: add O to table of active objects (DHT), and update O 's in the objects' table (OHT)
- ④ Lines 16–17: $O.flag$ is LEAVE so remove the object from DHT. Get the possible cells that O can move to

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

RFID Deployment Graph Construction

Algorithm 1 updateHashTables(Pre-processing output O , DeploymentGraph G)

```

1: IDSet  $sSet \leftarrow \emptyset$ ;
2: if  $O.flag = ENTER$  then
3:    $sSet \leftarrow OHT[O.objectID].IDSet$ ;
4:   if  $OHT[O.objectID].STATE = Active$  then
5:     for the single element  $c$  in  $sSet$  do
6:       Delete  $O.objectID$  from  $DHT[c]$ ;
7:   else if  $OHT[O.objectID].STATE = Deterministic$  then
8:     for the single element  $c$  in  $sSet$  do
9:       Delete  $O.objectID$  from  $CDHT[c]$ ;
10:  else
11:    for each element  $c$  in  $sSet$  do
12:      Delete  $O.objectID$  from  $CNHT[c]$ ;
13:  Add  $O.objectID$  to  $DHT[O.deviceID]$ ;
14:   $OHT[O.objectID] \leftarrow (Active, O.t, \{O.deviceID\})$ ;
15: else
16:   Delete  $O.objectID$  from  $DHT[O.deviceID]$ ;
17:    $sSet \leftarrow G.\ell_E^{-1}(O.deviceID)$ ;
18:   if  $Devices(O.deviceID).TYPE = UP$  then
19:      $OHT[O.objectID] \leftarrow (Nondeterministic, O.t, sSet)$ ;
20:     for each element  $c$  in  $sSet$  do
21:       Add  $O.objectID$  to  $CNHT[c]$ ;
22:   else
23:      $OHT[O.objectID] \leftarrow (Deterministic, O.t, sSet)$ ;
24:     for the single element  $c$  in  $sSet$  do
25:       Add  $O.objectID$  to  $CDHT[c]$ ;

```

- ① Line 1: reset $IDSet$
- ② Lines 2–12: $O.flag$ is ENTER so check the object's previous state. Remove O from the corresponding table according to its previous state
- ③ Lines 13–14: add O to table of active objects (DHT), and update O 's in the objects' table (OHT)
- ④ Lines 16–17: $O.flag$ is LEAVE so remove the object from DHT. Get the possible cells that O can move to
- ⑤ Lines 18–25: if the device is undirected, set O in OHT and add O to CNHT for the cells in $sSet$, else apply the same to CDHT

Continuous Range Monitoring: Query Definition

- A *Continuous Range Monitoring Query* (CRMQ)
 - takes an **indoor spatial range** \mathbf{R} as parameter
 - keeps reporting the objects when it is registered for a certain time frame $[t_s, t_e]$
- The **query result** \mathcal{M} – the set of moving objects in \mathbf{R} – is maintained as follows:

$$\forall t \in [t_s, t_e] : o \in CRMQ[R](\mathcal{M}) \Leftrightarrow o \in \mathcal{M} \wedge pos_{\mathcal{M}}(o, t) \in R$$

where $pos_{\mathcal{M}}$ is a function that can determine the position of object o at time t


- Multiple monitoring queries may coexist

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Critical Devices

For a CRMQ query, a *critical device* is one from which a new observation can potentially change the query result (either certain or uncertain). Use a *Device Query Hash Table* (DQHT) to record the relationships:

$$DQHT[deviceID] = \{(queryID, CLASS)\}$$




2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Critical Devices

For a CRMQ query, a *critical device* is one from which a new observation can potentially change the query result (either certain or uncertain). Use a *Device Query Hash Table* (DQHT) to record the relationships:

$$DQHT[deviceID] = \{(queryID, CLASS)\}$$

- CLASS1 – Device is fully covered in R along with cells, e.g., $(device_{16}, query_2)$




2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Critical Devices

For a CRMQ query, a *critical device* is one from which a new observation can potentially change the query result (either certain or uncertain). Use a *Device Query Hash Table* (DQHT) to record the relationships:

$$DQHT[deviceID] = \{(queryID, CLASS)\}$$


- CLASS1 – Device is fully covered in R along with cells, e.g., $(device_{16}, query_2)$
- CLASS2 – Device is fully covered but corresponding cells are not, e.g., $(device_{13}, query_1)$



Critical Devices

For a CRMQ query, a *critical device* is one from which a new observation can potentially change the query result (either certain or uncertain). Use a *Device Query Hash Table* (DQHT) to record the relationships:

$$DQHT[deviceID] = \{(queryID, CLASS)\}$$



- CLASS1 – Device is fully covered in R along with cells, e.g., $(device_{16}, query_2)$
- CLASS2 – Device is fully covered but corresponding cells are not, e.g., $(device_{13}, query_1)$
- CLASS3 – Device intersects with the query range R , e.g., $(device_{16}, query_1)$


2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Critical Devices

For a CRMQ query, a *critical device* is one from which a new observation can potentially change the query result (either certain or uncertain). Use a *Device Query Hash Table* (DQHT) to record the relationships:

$$DQHT[deviceID] = \{(queryID, CLASS)\}$$

- CLASS1 – Device is fully covered in R along with cells, e.g., ($device_{16}, query_2$)
- CLASS2 – Device is fully covered but corresponding cells are not, e.g., ($device_{13}, query_1$)
- CLASS3 – Device intersects with the query range R , e.g., ($device_{16}, query_1$)
- CLASS4 – Device is disjoint from R and at least one of its corresponding cells in $C_{ic} = \{c | c \cap R \neq \emptyset\}$, e.g., ($device_1, query_1$)




2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Critical Devices

For a CRMQ query, a *critical device* is one from which a new observation can potentially change the query result (either certain or uncertain). Use a *Device Query Hash Table* (DQHT) to record the relationships:

$$DQHT[deviceID] = \{(queryID, CLASS)\}$$




- CLASS1 – Device is fully covered in R along with cells, e.g., ($device_{16}, query_2$)
- CLASS2 – Device is fully covered but corresponding cells are not, e.g., ($device_{13}, query_1$)
- CLASS3 – Device intersects with the query range R , e.g., ($device_{16}, query_1$)
- CLASS4 – Device is disjoint from R and at least one of its corresponding cells in $C_{ic} = \{c | c \cap R \neq \emptyset\}$, e.g., ($device_1, query_1$)
- CLASS5 – Device is disjoint from R and at least one of its corresponding cells in $C_{ex} = \{c | \{c, c'\} \in G.E, c' \in C_{ic}\}$, but none of them are in C_{ic} , e.g., ($device_{10}, query_2$)

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration

- To handle concurrent CRMQs, a *Query Hash Table* is created hold the results
 - $QHT[queryID] = (CR, UR); CR \subseteq O_{indoor}, UR \subseteq O_{indoor}$
 - where CR is the certain result and UR is the uncertain result
- Overview



2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (I)

Algorithm 2 register (Range R , DeploymentGraph G)

```

1: deviceSet  $D_c \leftarrow \emptyset$ ,  $D_{uc} \leftarrow \emptyset$ ;
2: cellSet  $C_c \leftarrow \emptyset$ ,  $C_{uc} \leftarrow \emptyset$ ,  $C_{ex} \leftarrow \emptyset$ ;
3: objectSet  $R_c \leftarrow \emptyset$ ,  $R_{uc} \leftarrow \emptyset$ ;
4: CriticalDeviceList(deviceID, CLASS)  $cd \leftarrow \emptyset$ ;
5: Generate a new identifier queryID for the query;
6:  $D_c \leftarrow$  Devices that are covered by  $R$ ;
7:  $D_{uc} \leftarrow$  Devices that intersect with  $R$ ;
8:  $C_c \leftarrow$  Cells which are covered by  $R$ ;
9:  $C_{uc} \leftarrow$  Cells that intersect with  $R$ ;
10: for each device  $d$  in  $D_c$  do
11:   if all the cells in  $G.\ell_E^{-1}(d)$  are in  $C_c$  then
12:     Add  $(d, CLASS1)$  to  $cd$ ;
13:   else if one of the cells in  $G.\ell_E^{-1}(d)$  is in  $C_{uc}$  then
14:     Add  $(d, CLASS2)$  to  $cd$ ;
15: for each device  $d$  in  $D_{uc}$  do
16:   Add  $(d, CLASS3)$  to  $cd$ ;
17: for each edge  $e$  in  $G$  do
18:   if  $(C_c \cup C_{uc}) \cap e \neq \emptyset$  AND  $(C_c \cup C_{uc}) \cap e \neq (C_c \cup C_{uc})$  then
19:     if  $G.\ell_E(e) \notin cd.deviceID$  then
20:       Add  $(G.\ell_E(e), CLASS4)$  to  $cd$ ;
21:      $C_{ex} \leftarrow C_{ex} \cup e \setminus (C_c \cup C_{uc})$ ;
22: for each edge  $e$  in  $G$  do
23:   if  $C_{ex} \cap e \neq \emptyset$  then
24:     if  $G.\ell_E(e) \notin cd.deviceID$  then
25:       Add  $(G.\ell_E(e), CLASS5)$  to  $cd$ ;

```

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (I)

Algorithm 2 register (Range R , DeploymentGraph G)

```

1: deviceSet  $D_c \leftarrow \emptyset$ ,  $D_{uc} \leftarrow \emptyset$ ;
2: cellSet  $C_c \leftarrow \emptyset$ ,  $C_{uc} \leftarrow \emptyset$ ,  $C_{ex} \leftarrow \emptyset$ ;
3: objectSet  $R_c \leftarrow \emptyset$ ,  $R_{uc} \leftarrow \emptyset$ ;
4: CriticalDeviceList(deviceID, CLASS)  $cd \leftarrow \emptyset$ ;
5: Generate a new identifier  $queryID$  for the query;
6:  $D_c \leftarrow$  Devices that are covered by  $R$ ;
7:  $D_{uc} \leftarrow$  Devices that intersect with  $R$ ;
8:  $C_c \leftarrow$  Cells which are covered by  $R$ ;
9:  $C_{uc} \leftarrow$  Cells that intersect with  $R$ ;
10: for each device  $d$  in  $D_c$  do
11:   if all the cells in  $G.\ell_E^{-1}(d)$  are in  $C_c$  then
12:     Add  $(d, CLASS1)$  to  $cd$ ;
13:   else if one of the cells in  $G.\ell_E^{-1}(d)$  is in  $C_{uc}$  then
14:     Add  $(d, CLASS2)$  to  $cd$ ;
15: for each device  $d$  in  $D_{uc}$  do
16:   Add  $(d, CLASS3)$  to  $cd$ ;
17: for each edge  $e$  in  $G$  do
18:   if  $(C_c \cup C_{uc}) \cap e \neq \emptyset$  AND  $(C_c \cup C_{uc}) \cap e \neq (C_c \cup C_{uc})$  then
19:     if  $G.\ell_E(e) \notin cd.deviceID$  then
20:       Add  $(G.\ell_E(e), CLASS4)$  to  $cd$ ;
21:      $C_{ex} \leftarrow C_{ex} \cup e \setminus (C_c \cup C_{uc})$ ;
22: for each edge  $e$  in  $G$  do
23:   if  $C_{ex} \cap e \neq \emptyset$  then
24:     if  $G.\ell_E(e) \notin cd.deviceID$  then
25:       Add  $(G.\ell_E(e), CLASS5)$  to  $cd$ ;

```

① Lines 1–9: Initialization

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (I)

Algorithm 2 register (Range R , DeploymentGraph G)

```

1: deviceSet  $D_c \leftarrow \emptyset$ ,  $D_{uc} \leftarrow \emptyset$ ;
2: cellSet  $C_c \leftarrow \emptyset$ ,  $C_{uc} \leftarrow \emptyset$ ,  $C_{ex} \leftarrow \emptyset$ ;
3: objectSet  $R_c \leftarrow \emptyset$ ,  $R_{uc} \leftarrow \emptyset$ ;
4: CriticalDeviceList(deviceID, CLASS)  $cd \leftarrow \emptyset$ ;
5: Generate a new identifier  $queryID$  for the query;
6:  $D_c \leftarrow$  Devices that are covered by  $R$ ;
7:  $D_{uc} \leftarrow$  Devices that intersect with  $R$ ;
8:  $C_c \leftarrow$  Cells which are covered by  $R$ ;
9:  $C_{uc} \leftarrow$  Cells that intersect with  $R$ ;
10: for each device  $d$  in  $D_c$  do
11:   if all the cells in  $G.\ell_E^{-1}(d)$  are in  $C_c$  then
12:     Add  $(d, CLASS1)$  to  $cd$ ;
13:   else if one of the cells in  $G.\ell_E^{-1}(d)$  is in  $C_{uc}$  then
14:     Add  $(d, CLASS2)$  to  $cd$ ;
15: for each device  $d$  in  $D_{uc}$  do
16:   Add  $(d, CLASS3)$  to  $cd$ ;
17: for each edge  $e$  in  $G$  do
18:   if  $(C_c \cup C_{uc}) \cap e \neq \emptyset$  AND  $(C_c \cup C_{uc}) \cap e \neq (C_c \cup C_{uc})$  then
19:     if  $G.\ell_E(e) \notin cd.deviceID$  then
20:       Add  $(G.\ell_E(e), CLASS4)$  to  $cd$ ;
21:      $C_{ex} \leftarrow C_{ex} \cup e \setminus (C_c \cup C_{uc})$ ;
22: for each edge  $e$  in  $G$  do
23:   if  $C_{ex} \cap e \neq \emptyset$  then
24:     if  $G.\ell_E(e) \notin cd.deviceID$  then
25:       Add  $(G.\ell_E(e), CLASS5)$  to  $cd$ ;

```

① Lines 1–9: Initialization

② Lines 10–14: Add possible devices to CriticalDeviceList cd (CLASS1 and CLASS2)

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (I)

Algorithm 2 register (Range R , DeploymentGraph G)

```

1: deviceSet  $D_c \leftarrow \emptyset$ ,  $D_{uc} \leftarrow \emptyset$ ;
2: cellSet  $C_c \leftarrow \emptyset$ ,  $C_{uc} \leftarrow \emptyset$ ,  $C_{ex} \leftarrow \emptyset$ ;
3: objectSet  $R_c \leftarrow \emptyset$ ,  $R_{uc} \leftarrow \emptyset$ ;
4: CriticalDeviceList(deviceID, CLASS)  $cd \leftarrow \emptyset$ ;
5: Generate a new identifier queryID for the query;
6:  $D_c \leftarrow$  Devices that are covered by  $R$ ;
7:  $D_{uc} \leftarrow$  Devices that intersect with  $R$ ;
8:  $C_c \leftarrow$  Cells which are covered by  $R$ ;
9:  $C_{uc} \leftarrow$  Cells that intersect with  $R$ ;
10: for each device  $d$  in  $D_c$  do
11:   if all the cells in  $G.\ell_E^{-1}(d)$  are in  $C_c$  then
12:     Add  $(d, CLASS1)$  to  $cd$ ;
13:   else if one of the cells in  $G.\ell_E^{-1}(d)$  is in  $C_{uc}$  then
14:     Add  $(d, CLASS2)$  to  $cd$ ;
15: for each device  $d$  in  $D_{uc}$  do
16:   Add  $(d, CLASS3)$  to  $cd$ ;
17: for each edge  $e$  in  $G$  do
18:   if  $(C_c \cup C_{uc}) \cap e \neq \emptyset$  AND  $(C_c \cup C_{uc}) \cap e \neq (C_c \cup C_{uc})$  then
19:     if  $G.\ell_E(e) \notin cd.deviceID$  then
20:       Add  $(G.\ell_E(e), CLASS4)$  to  $cd$ ;
21:      $C_{ex} \leftarrow C_{ex} \cup e \setminus (C_c \cup C_{uc})$ ;
22: for each edge  $e$  in  $G$  do
23:   if  $C_{ex} \cap e \neq \emptyset$  then
24:     if  $G.\ell_E(e) \notin cd.deviceID$  then
25:       Add  $(G.\ell_E(e), CLASS5)$  to  $cd$ ;

```

① Lines 1–9: Initialization

② Lines 10–14: Add possible devices to CriticalDeviceList cd (CLASS1 and CLASS2)

③ Lines 15–16: Add possible CLASS3 devices

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (I)

Algorithm 2 register (Range R , DeploymentGraph G)

```

1: deviceSet  $D_c \leftarrow \emptyset$ ,  $D_{uc} \leftarrow \emptyset$ ;
2: cellSet  $C_c \leftarrow \emptyset$ ,  $C_{uc} \leftarrow \emptyset$ ,  $C_{ex} \leftarrow \emptyset$ ;
3: objectSet  $R_c \leftarrow \emptyset$ ,  $R_{uc} \leftarrow \emptyset$ ;
4: CriticalDeviceList(deviceID, CLASS)  $cd \leftarrow \emptyset$ ;
5: Generate a new identifier  $queryID$  for the query;
6:  $D_c \leftarrow$  Devices that are covered by  $R$ ;
7:  $D_{uc} \leftarrow$  Devices that intersect with  $R$ ;
8:  $C_c \leftarrow$  Cells which are covered by  $R$ ;
9:  $C_{uc} \leftarrow$  Cells that intersect with  $R$ ;
10: for each device  $d$  in  $D_c$  do
11:   if all the cells in  $G.\ell_E^{-1}(d)$  are in  $C_c$  then
12:     Add  $(d, CLASS1)$  to  $cd$ ;
13:   else if one of the cells in  $G.\ell_E^{-1}(d)$  is in  $C_{uc}$  then
14:     Add  $(d, CLASS2)$  to  $cd$ ;
15: for each device  $d$  in  $D_{uc}$  do
16:   Add  $(d, CLASS3)$  to  $cd$ ;
17: for each edge  $e$  in  $G$  do
18:   if  $(C_c \cup C_{uc}) \cap e \neq \emptyset$  AND  $(C_c \cup C_{uc}) \cap e \neq (C_c \cup C_{uc})$  then
19:     if  $G.\ell_E(e) \notin cd.deviceID$  then
20:       Add  $(G.\ell_E(e), CLASS4)$  to  $cd$ ;
21:      $C_{ex} \leftarrow C_{ex} \cup e \setminus (C_c \cup C_{uc})$ ;
22: for each edge  $e$  in  $G$  do
23:   if  $C_{ex} \cap e \neq \emptyset$  then
24:     if  $G.\ell_E(e) \notin cd.deviceID$  then
25:       Add  $(G.\ell_E(e), CLASS5)$  to  $cd$ ;

```

① Lines 1–9: Initialization

② Lines 10–14: Add possible devices to CriticalDeviceList cd (CLASS1 and CLASS2)

③ Lines 15–16: Add possible CLASS3 devices

④ Lines 17–20: Add possible CLASS4 devices

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (I)

Algorithm 2 register (Range R , DeploymentGraph G)

```

1: deviceSet  $D_c \leftarrow \emptyset$ ,  $D_{uc} \leftarrow \emptyset$ ;
2: cellSet  $C_c \leftarrow \emptyset$ ,  $C_{uc} \leftarrow \emptyset$ ,  $C_{ex} \leftarrow \emptyset$ ;
3: objectSet  $R_c \leftarrow \emptyset$ ,  $R_{uc} \leftarrow \emptyset$ ;
4: CriticalDeviceList(deviceID, CLASS)  $cd \leftarrow \emptyset$ ;
5: Generate a new identifier queryID for the query;
6:  $D_c \leftarrow$  Devices that are covered by  $R$ ;
7:  $D_{uc} \leftarrow$  Devices that intersect with  $R$ ;
8:  $C_c \leftarrow$  Cells which are covered by  $R$ ;
9:  $C_{uc} \leftarrow$  Cells that intersect with  $R$ ;
10: for each device  $d$  in  $D_c$  do
11:   if all the cells in  $G.\ell_E^{-1}(d)$  are in  $C_c$  then
12:     Add  $(d, CLASS1)$  to  $cd$ ;
13:   else if one of the cells in  $G.\ell_E^{-1}(d)$  is in  $C_{uc}$  then
14:     Add  $(d, CLASS2)$  to  $cd$ ;
15: for each device  $d$  in  $D_{uc}$  do
16:   Add  $(d, CLASS3)$  to  $cd$ ;
17: for each edge  $e$  in  $G$  do
18:   if  $(C_c \cup C_{uc}) \cap e \neq \emptyset$  AND  $(C_c \cup C_{uc}) \cap e \neq (C_c \cup C_{uc})$  then
19:     if  $G.\ell_E(e) \notin cd.deviceID$  then
20:       Add  $(G.\ell_E(e), CLASS4)$  to  $cd$ ;
21:    $C_{ex} \leftarrow C_{ex} \cup e \setminus (C_c \cup C_{uc})$ ;
22: for each edge  $e$  in  $G$  do
23:   if  $C_{ex} \cap e \neq \emptyset$  then
24:     if  $G.\ell_E(e) \notin cd.deviceID$  then
25:       Add  $(G.\ell_E(e), CLASS5)$  to  $cd$ ;

```

① Lines 1–9: Initialization

② Lines 10–14: Add possible devices to CriticalDeviceList cd (CLASS1 and CLASS2)

③ Lines 15–16: Add possible CLASS3 devices

④ Lines 17–20: Add possible CLASS4 devices

⑤ Line 21: Determine extended cell set C_{ex}

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (I)

Algorithm 2 register (Range R , DeploymentGraph G)

```

1: deviceSet  $D_c \leftarrow \emptyset$ ,  $D_{uc} \leftarrow \emptyset$ ;
2: cellSet  $C_c \leftarrow \emptyset$ ,  $C_{uc} \leftarrow \emptyset$ ,  $C_{ex} \leftarrow \emptyset$ ;
3: objectSet  $R_c \leftarrow \emptyset$ ,  $R_{uc} \leftarrow \emptyset$ ;
4: CriticalDeviceList(deviceID, CLASS)  $cd \leftarrow \emptyset$ ;
5: Generate a new identifier queryID for the query;
6:  $D_c \leftarrow$  Devices that are covered by  $R$ ;
7:  $D_{uc} \leftarrow$  Devices that intersect with  $R$ ;
8:  $C_c \leftarrow$  Cells which are covered by  $R$ ;
9:  $C_{uc} \leftarrow$  Cells that intersect with  $R$ ;
10: for each device  $d$  in  $D_c$  do
11:   if all the cells in  $G.\ell_E^{-1}(d)$  are in  $C_c$  then
12:     Add  $(d, CLASS1)$  to  $cd$ ;
13:   else if one of the cells in  $G.\ell_E^{-1}(d)$  is in  $C_{uc}$  then
14:     Add  $(d, CLASS2)$  to  $cd$ ;
15: for each device  $d$  in  $D_{uc}$  do
16:   Add  $(d, CLASS3)$  to  $cd$ ;
17: for each edge  $e$  in  $G$  do
18:   if  $(C_c \cup C_{uc}) \cap e \neq \emptyset$  AND  $(C_c \cup C_{uc}) \cap e \neq (C_c \cup C_{uc})$  then
19:     if  $G.\ell_E(e) \notin cd.deviceID$  then
20:       Add  $(G.\ell_E(e), CLASS4)$  to  $cd$ ;
21:      $C_{ex} \leftarrow C_{ex} \cup e \setminus (C_c \cup C_{uc})$ ;
22: for each edge  $e$  in  $G$  do
23:   if  $C_{ex} \cap e \neq \emptyset$  then
24:     if  $G.\ell_E(e) \notin cd.deviceID$  then
25:       Add  $(G.\ell_E(e), CLASS5)$  to  $cd$ ;

```

① Lines 1–9: Initialization

② Lines 10–14: Add possible devices to CriticalDeviceList cd (CLASS1 and CLASS2)

③ Lines 15–16: Add possible CLASS3 devices

④ Lines 17–20: Add possible CLASS4 devices

⑤ Line 21: Determine extended cell set C_{ex}

⑥ Lines 22–25: Add possible CLASS5 devices

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (II)

```

26: for each device  $d$  in  $\bar{D}_c$  do
27:    $R_c \leftarrow R_c \cup DHT[d]$ ;
28: for each device  $d$  in  $D_{uc}$  do
29:    $R_{uc} \leftarrow R_{uc} \cup DHT[d]$ ;
30: for each cell  $c$  in  $C_c$  do
31:    $R_c \leftarrow R_c \cup CDHT[c]$ ;
32: if  $|C_c| > 1$  then
33:   for each nondeterministic object  $o$  in  $C_c$  do
34:     if  $OHT[o].IDSet \subset C_c$  then
35:       Add  $o$  into  $R_c$ ;
36:     else
37:       Add  $o$  into  $R_{uc}$ 
38: else
39:    $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
40: for each cell  $c$  in  $C_{uc}$  do
41:    $R_c \leftarrow R_c \cup CDHT[c]$ ;  $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
42:  $QHT[queryID] \leftarrow (R_c, R_{uc})$ ;
43: for each item  $a$  in  $cd$  do
44:   Add  $(queryID, a.CLASS)$  into  $DQHT[a.deviceID]$ ;

```

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (II)

- ① Lines 26–27: Add active objects from DHT to the certain result

```

26: for each device  $d$  in  $\bar{D}_c$  do
27:    $R_c \leftarrow R_c \cup DHT[d]$ ;
28: for each device  $d$  in  $D_{uc}$  do
29:    $R_{uc} \leftarrow R_{uc} \cup DHT[d]$ ;
30: for each cell  $c$  in  $C_c$  do
31:    $R_c \leftarrow R_c \cup CDHT[c]$ ;
32: if  $|C_c| > 1$  then
33:   for each nondeterministic object  $o$  in  $C_c$  do
34:     if  $OHT[o].IDSet \subset C_c$  then
35:       Add  $o$  into  $R_c$ ;
36:     else
37:       Add  $o$  into  $R_{uc}$ 
38: else
39:    $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
40: for each cell  $c$  in  $C_{uc}$  do
41:    $R_c \leftarrow R_c \cup CDHT[c]$ ;  $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
42:  $QHT[queryID] \leftarrow (R_c, R_{uc})$ ;
43: for each item  $a$  in  $cd$  do
44:   Add  $(queryID, a.CLASS)$  into  $DQHT[a.deviceID]$ ;

```

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (II)

- 1 Lines 26–27: Add active objects from DHT to the certain result
- 2 Lines 28–29: Intersected device set, add active objects from DHT to the uncertain result

```

26: for each device  $d$  in  $\bar{D}_c$  do
27:    $R_c \leftarrow R_c \cup DHT[d]$ ;
28: for each device  $d$  in  $D_{uc}$  do
29:    $R_{uc} \leftarrow R_{uc} \cup DHT[d]$ ;
30: for each cell  $c$  in  $C_c$  do
31:    $R_c \leftarrow R_c \cup CDHT[c]$ ;
32:   if  $|C_c| > 1$  then
33:     for each nondeterministic object  $o$  in  $C_c$  do
34:       if  $OHT[o].IDSet \subset C_c$  then
35:         Add  $o$  into  $R_c$ ;
36:       else
37:         Add  $o$  into  $R_{uc}$ 
38:   else
39:      $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
40: for each cell  $c$  in  $C_{uc}$  do
41:    $R_c \leftarrow R_c \cup CDHT[c]$ ;  $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
42:  $QHT[queryID] \leftarrow (R_c, R_{uc})$ ;
43: for each item  $a$  in  $cd$  do
44:   Add ( $queryID, a.CLASS$ ) into  $DQHT[a.deviceID]$ ;

```

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (II)

```

26: for each device  $d$  in  $\bar{D}_c$  do
27:    $R_c \leftarrow R_c \cup DHT[d]$ ;
28: for each device  $d$  in  $D_{uc}$  do
29:    $R_{uc} \leftarrow R_{uc} \cup DHT[d]$ ;
30: for each cell  $c$  in  $C_c$  do
31:    $R_c \leftarrow R_c \cup CDHT[c]$ ;
32: if  $|C_c| > 1$  then
33:   for each nondeterministic object  $o$  in  $C_c$  do
34:     if  $OHT[o].IDSet \subset C_c$  then
35:       Add  $o$  into  $R_c$ ;
36:     else
37:       Add  $o$  into  $R_{uc}$ 
38: else
39:    $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
40: for each cell  $c$  in  $C_{uc}$  do
41:    $R_c \leftarrow R_c \cup CDHT[c]$ ;  $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
42:  $QHT[queryID] \leftarrow (R_c, R_{uc})$ ;
43: for each item  $a$  in  $cd$  do
44:   Add  $(queryID, a.CLASS)$  into  $DQHT[a.deviceID]$ ;

```

- ① Lines 26–27: Add active objects from DHT to the certain result
- ② Lines 28–29: Intersected device set, add active objects from DHT to the uncertain result
- ③ Lines 30–31: From covered cells, add deterministic objects to the certain result

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (II)

```

26: for each device  $d$  in  $\bar{D}_c$  do
27:    $R_c \leftarrow R_c \cup DHT[d]$ ;
28: for each device  $d$  in  $D_{uc}$  do
29:    $R_{uc} \leftarrow R_{uc} \cup DHT[d]$ ;
30: for each cell  $c$  in  $C_c$  do
31:    $R_c \leftarrow R_c \cup CDHT[c]$ ;
32: if  $|C_c| > 1$  then
33:   for each nondeterministic object  $o$  in  $C_c$  do
34:     if  $OHT[o].IDSet \subset C_c$  then
35:       Add  $o$  into  $R_c$ ;
36:     else
37:       Add  $o$  into  $R_{uc}$ 
38: else
39:    $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
40: for each cell  $c$  in  $C_{uc}$  do
41:    $R_c \leftarrow R_c \cup CDHT[c]$ ;  $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
42:  $QHT[queryID] \leftarrow (R_c, R_{uc})$ ;
43: for each item  $a$  in  $cd$  do
44:   Add  $(queryID, a.CLASS)$  into  $DQHT[a.deviceID]$ ;

```

- ① Lines 26–27: Add active objects from DHT to the certain result
- ② Lines 28–29: Intersected device set, add active objects from DHT to the uncertain result
- ③ Lines 30–31: From covered cells, add deterministic objects to the certain result
- ④ Lines 32–37: If more than one cell, check nondeterministic objects. If all its possible cells are in C_c add the object to the certain result, else uncertain result

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (II)

```

26: for each device  $d$  in  $\bar{D}_c$  do
27:    $R_c \leftarrow R_c \cup DHT[d]$ ;
28: for each device  $d$  in  $D_{uc}$  do
29:    $R_{uc} \leftarrow R_{uc} \cup DHT[d]$ ;
30: for each cell  $c$  in  $C_c$  do
31:    $R_c \leftarrow R_c \cup CDHT[c]$ ;
32:   if  $|C_c| > 1$  then
33:     for each nondeterministic object  $o$  in  $C_c$  do
34:       if  $OHT[o].IDSet \subset C_c$  then
35:         Add  $o$  into  $R_c$ ;
36:       else
37:         Add  $o$  into  $R_{uc}$ 
38:   else
39:      $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
40:   for each cell  $c$  in  $C_{uc}$  do
41:      $R_c \leftarrow R_c \cup CDHT[c]$ ;  $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
42:    $QHT[queryID] \leftarrow (R_c, R_{uc})$ ;
43:   for each item  $a$  in  $cd$  do
44:     Add  $(queryID, a.CLASS)$  into  $DQHT[a.deviceID]$ ;

```

- ① Lines 26–27: Add active objects from DHT to the certain result
- ② Lines 28–29: Intersected device set, add active objects from DHT to the uncertain result
- ③ Lines 30–31: From covered cells, add deterministic objects to the certain result
- ④ Lines 32–37: If more than one cell, check nondeterministic objects. If all its possible cells are in C_c add the object to the certain result, else uncertain result
- ⑤ Lines 38–39: Only one cell. Nondeterministic objects are added to the uncertain result

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (II)

```

26: for each device  $d$  in  $\bar{D}_c$  do
27:    $R_c \leftarrow R_c \cup DHT[d]$ ;
28: for each device  $d$  in  $D_{uc}$  do
29:    $R_{uc} \leftarrow R_{uc} \cup DHT[d]$ ;
30: for each cell  $c$  in  $C_c$  do
31:    $R_c \leftarrow R_c \cup CDHT[c]$ ;
32: if  $|C_c| > 1$  then
33:   for each nondeterministic object  $o$  in  $C_c$  do
34:     if  $OHT[o].IDSet \subset C_c$  then
35:       Add  $o$  into  $R_c$ ;
36:     else
37:       Add  $o$  into  $R_{uc}$ 
38: else
39:    $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
40: for each cell  $c$  in  $C_{uc}$  do
41:    $R_c \leftarrow R_c \cup CDHT[c]$ ;  $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
42:  $QHT[queryID] \leftarrow (R_c, R_{uc})$ ;
43: for each item  $a$  in  $cd$  do
44:   Add  $(queryID, a.CLASS)$  into  $DQHT[a.deviceID]$ ;

```

- ① Lines 26–27: Add active objects from DHT to the certain result
- ② Lines 28–29: Intersected device set, add active objects from DHT to the uncertain result
- ③ Lines 30–31: From covered cells, add deterministic objects to the certain result
- ④ Lines 32–37: If more than one cell, check nondeterministic objects. If all its possible cells are in C_c add the object to the certain result, else uncertain result
- ⑤ Lines 38–39: Only one cell. Nondeterministic objects are added to the uncertain result
- ⑥ Lines 40–41: Intersected set. Add all objects to the uncertain result

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (II)

```

26: for each device  $d$  in  $\bar{D}_c$  do
27:    $R_c \leftarrow R_c \cup DHT[d]$ ;
28: for each device  $d$  in  $D_{uc}$  do
29:    $R_{uc} \leftarrow R_{uc} \cup DHT[d]$ ;
30: for each cell  $c$  in  $C_c$  do
31:    $R_c \leftarrow R_c \cup CDHT[c]$ ;
32: if  $|C_c| > 1$  then
33:   for each nondeterministic object  $o$  in  $C_c$  do
34:     if  $OHT[o].IDSet \subset C_c$  then
35:       Add  $o$  into  $R_c$ ;
36:   else
37:     Add  $o$  into  $R_{uc}$ 
38: else
39:    $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
40: for each cell  $c$  in  $C_{uc}$  do
41:    $R_c \leftarrow R_c \cup CDHT[c]$ ;  $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
42:  $QHT[queryID] \leftarrow (R_c, R_{uc})$ ;
43: for each item  $a$  in  $cd$  do
44:   Add  $(queryID, a.CLASS)$  into  $DQHT[a.deviceID]$ ;

```

- ① Lines 26–27: Add active objects from DHT to the certain result
- ② Lines 28–29: Intersected device set, add active objects from DHT to the uncertain result
- ③ Lines 30–31: From covered cells, add deterministic objects to the certain result
- ④ Lines 32–37: If more than one cell, check nondeterministic objects. If all its possible cells are in C_c add the object to the certain result, else uncertain result
- ⑤ Lines 38–39: Only one cell. Nondeterministic objects are added to the uncertain result
- ⑥ Lines 40–41: Intersected set. Add all objects to the uncertain result
- ⑦ Line 42: Results added to QHT

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Query Registration Algorithm (II)

```

26: for each device  $d$  in  $\bar{D}_c$  do
27:    $R_c \leftarrow R_c \cup DHT[d]$ ;
28: for each device  $d$  in  $D_{uc}$  do
29:    $R_{uc} \leftarrow R_{uc} \cup DHT[d]$ ;
30: for each cell  $c$  in  $C_c$  do
31:    $R_c \leftarrow R_c \cup CDHT[c]$ ;
32: if  $|C_c| > 1$  then
33:   for each nondeterministic object  $o$  in  $C_c$  do
34:     if  $OHT[o].IDSet \subset C_c$  then
35:       Add  $o$  into  $R_c$ ;
36:     else
37:       Add  $o$  into  $R_{uc}$ 
38: else
39:    $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
40: for each cell  $c$  in  $C_{uc}$  do
41:    $R_c \leftarrow R_c \cup CDHT[c]$ ;  $R_{uc} \leftarrow R_{uc} \cup CNHT[c]$ ;
42:  $QHT[queryID] \leftarrow (R_c, R_{uc})$ ;
43: for each item  $a$  in  $cd$  do
44:   Add  $(queryID, a.CLASS)$  into  $DQHT[a.deviceID]$ ;

```

- ① Lines 26–27: Add active objects from DHT to the certain result
- ② Lines 28–29: Intersected device set, add active objects from DHT to the uncertain result
- ③ Lines 30–31: From covered cells, add deterministic objects to the certain result
- ④ Lines 32–37: If more than one cell, check nondeterministic objects. If all its possible cells are in C_c add the object to the certain result, else uncertain result
- ⑤ Lines 38–39: Only one cell. Nondeterministic objects are added to the uncertain result
- ⑥ Lines 40–41: Intersected set. Add all objects to the uncertain result
- ⑦ Line 42: Results added to QHT
- ⑧ Lines 43–44: DQHT entry is created for each critical device

Query Result Updates

- When an object enters the activation range of a critical device:
 - For CLASS1 or CLASS2 devices the object is the certain result
 - For CLASS3 devices the object is possibly in the query range
 - For CLASS4 or CLASS5 devices the object is not in the query range
- When an object leaves:
 - For CLASS1, 3, 5 devices there are no changes
 - For CLASS2 devices the object may still be in the query range, thus it is moved to the uncertain result
 - For CLASS4 devices the object may be in a cell that intersects with the query range and it added to the uncertain result


Table 1: Query Updates w.r.t. Critical Devices

	ENTER	LEAVE
CLASS1	$CR \cup \{o\}, UR \setminus \{o\}$	CR, UR
CLASS2	$CR \cup \{o\}, UR \setminus \{o\}$	$CR \setminus \{o\}, UR \cup \{o\}$
CLASS3	$CR \setminus \{o\}, UR \cup \{o\}$	CR, UR
CLASS4	$CR \setminus \{o\}, UR \setminus \{o\}$	$CR, UR \cup \{o\}$
CLASS5	$CR \setminus \{o\}, UR \setminus \{o\}$	CR, UR

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Deferred Query Updates

- Deferred query updates is the concept of postponing updates where we already know the result
- The time a query result is still valid is calculated from *minimum indoor walking distance* divided by the *maximum speed* an object can travel




Consider $query_1$, after the object o leaves a CLASS2 critical device $device_{13}$, it should be moved from certain to uncertain result.

Let V_{max} be the maximum speed, if $R_1 = V_{max} * \Delta t$, the certain result can be maintained without updating for an extra period of time Δt .

2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Deferred Query Updates

- Deferred query updates is the concept of postponing updates where we already know the result
- The time a query result is still valid is calculated from *minimum indoor walking distance* divided by the *maximum speed* an object can travel



Consider $query_1$, after the object o leaves a CLASS2 critical device $device_{13}$, it should be moved from certain to uncertain result.

Let V_{max} be the maximum speed, if $R_1 = V_{max} * \Delta t$, the certain result can be maintained without updating for an extra period of time Δt .


2.2 Scalable Continuous Range Monitoring of Moving Objects in Symbolic Indoor Space

Probabilistic Analysis of Uncertain Results

2. Probabilities for Inactive Objects

For the case that after leaving CLASS2, 3, 4 devices, the probabilities for inactive objects can be defined based on the maximum speed constraint.

An example for an inactive object that just leaves *device*₁₂...



Conclusion

- A solution with a symbolic model of the floor plan, device locations, and activation ranges
- Data is stored in several hash tables which make it possible to efficiently locate a specific object (result is a single room/cell, or a set of rooms/cells)
- Future work
 - sharing of query processing among concurrent queries
 - common critical devices exploitation
 - other types of queries: range and k NN
 - further investigate the probability analysis

References I

- [1] C. S. Jensen, H. Lu, and B. Yang.
Graph model based indoor tracking.
In *MDM*, pp. 122–131, 2009.
- [2] B. Yang, H. Lu, and C. S. Jensen.
Scalable continuous range monitoring of moving objects in symbolic indoor space.
In *CIKM*, pp. 671–680, 2009.
- [3] C. Becker and F. Dür.
On location models for ubiquitous computing.
In *Personal and Ubiquitous Computing*, pp. 20–31, 2005.
- [4] C. S. Jensen, H. Lu, B. Yang.
Indoor-A New Data Management Frontier.
In *IEEE Data Eng. Bull.*, pp. 12–17, 2010.

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
- 4. Indoor Movement Analysis**
5. Appendix

1. Outlines
2. Indoor Space Models & Applications
3. Indoor Data Cleansing
4. Indoor Movement Analysis
5. Appendix

The End. Thanks :)