

Mục lục

1	Java Fast Input
2	Simple Max Matching
3	Konig
4	Hopcroft Karp Max Matching algorithm
5	Max matching min cost
6	Ganeral Matching
7	Dinic MaxFlow
8	Mincost MaxFlow SPFA
9	Upper Lower
10	Two sat
11	Alternative Tree
12	Max Clique
13	Euler Path
14	Interection of two paths
15	Tree ISO
16	Aho Corasick
17	Suffix Array
18	Suffix Array O(n)
19	Manacher
20	DP knuth
21	DP divide conquer
22	Convex Hull
23	Geometry's tricks
24	Geometry 2D

25	Geometry 3D	18
26	FFT	19
27	NTT	20
28	Gauss	21
29	Simplex	21
30	Primitive Root	22
31	Range Prime Counting	22
32	Knight's shortest path	23
33	Extended Euclid	23
34	Factorial Mod	23
35	Sqrt Mod	23
36	Interval line	23
37	BIT 2D	25
38	Heavy-Light Decomposition	25

1 Java Fast Input

```

class InputReader {
    private final BufferedReader reader;
    private StringTokenizer tokenizer;

    public InputReader(InputStream stream) {
        reader = new BufferedReader(new InputStreamReader(stream));
        tokenizer = null;
    }

    public String nextLine() {
        try {
            return reader.readLine();
        } catch (IOException e) {
            throw new RuntimeException(e);
        }
    }
}

```

```

public String next() {
    while (tokenizer == null || !tokenizer.hasMoreTokens()) {
        tokenizer = new StringTokenizer(nextLine());
    }
    return tokenizer.nextToken();
}

public int nextInt() {
    return Integer.parseInt(next());
}
}

```

2 Simple Max Matching

```

bool dfs(int u) {
    if (mx[u] == T) return false;
    mx[u] = T;
    for(int v : ke[u]) {
        if (!my[v] || dfs(my[v])) {
            my[v] = u;
            return true;
        }
    }
    return false;
}

int main() {
    For(i,1,n) {
        T++;
        res += dfs(i);
    }
    // choose my & i
}

```

3 Konig

```

void konig(){
    queue<int> qu;

    f1(i,m) if (!Assigned[i]) qu.push(i);
    f1(i,n) if (!Assigned[N-i]) qu.push(N-i);
}

```

```

while (qu.size()){
    int u=qu.front(); qu.pop();
    for (int i=0; int v=a[u][i]; i++)
        if (!(Choosed[v]++)) qu.push(Assigned[v]);
}

f1(i,m) if (Assigned[i] && !Choosed[i] && !Choosed[Assigned[i]])
    Choosed[i]=true;
}

```

4 Hopcroft Karp Max Matching algorithm

```

// Worse Case: E * sqrt(v)
const int MAXN = 50005, MAXM = 50005;
vector<int> gph[MAXN];
int dis[MAXN], l[MAXN], r[MAXM], vis[MAXN];
void clear() {
    for (int i = 0; i < MAXN; i++)
        gph[i].clear();
}

void add_edge(int l, int r) {
    gph[l].push_back(r);
}

bool bfs(int n) {
    queue<int> que;
    bool ok = 0;
    memset(dis, 0, sizeof(dis));
    for (int i = 0; i < n; i++) {
        if (l[i] == -1 && !dis[i]) {
            que.push(i);
            dis[i] = 1;
        }
    }

    while (!que.empty()) {
        int x = que.front();
        que.pop();
        for (auto &i : gph[x]) {
            if (r[i] == -1)
                ok = 1;
            else if (!dis[r[i]]) {
                dis[r[i]] = dis[x] + 1;
                que.push(r[i]);
            }
        }
    }
}

```

```

    }
}
return ok;
}
bool dfs(int x) {
    for (auto &i : gph[x]) {
        if (r[i] == -1 || (!vis[r[i]] && dis[r[i]] == dis[x] + 1 &&
            dfs(r[i]))) {
            vis[r[i]] = 1;
            l[x] = i;
            r[i] = x;
            return 1;
        }
    }
    return 0;
}
int match(int n) {
    memset(l, -1, sizeof(l));
    memset(r, -1, sizeof(r));
    int ret = 0;
    while (bfs(n)) {
        memset(vis, 0, sizeof(vis));
        for (int i = 0; i < n; i++)
            if (l[i] == -1 && dfs(i))
                ret++;
    }
    return ret;
}
bool chk[MAXN + MAXM];
void rdfs(int x, int n) {
    if (chk[x])
        return;
    chk[x] = 1;
    for (auto &i : gph[x]) {
        chk[i + n] = 1;
        rdfs(r[i], n);
    }
}
vector<int> getcover(int n, int m) {
    // solve min. vertex cover
    match(n);
    memset(chk, 0, sizeof(chk));
    for (int i = 0; i < n; i++)
        if (l[i] == -1)

```

```

        rdfs(i, n);
    vector<int> v;
    for (int i = 0; i < n; i++)
        if (!chk[i])
            v.push_back(i);
    for (int i = n; i < n + m; i++)
        if (chk[i])
            v.push_back(i);
    return v;
}

```

5 Max matching min cost

```

// numbered from 0. i -> mx[i]
const int V = 1000, INF = 1e9;
int g[V][V], mx[V], my[V], fx[V], fy[V], d[V], ar[V], tr[V], p;
int slack(int u, int v) {
    return g[u][v] - fx[u] - fy[v];
}
int augment(int s) {
    queue<int> q;
    q.push(s);
    fill_n(tr, p, -1);
    for(int i = 0; i < p; ++i) d[i] = slack(s, i), ar[i] = s;
    while(true) {
        while(!q.empty()) {
            int u = q.front();
            q.pop();
            for(int v = 0; v < p; ++v) if(tr[v] == -1) {
                int w = slack(u, v);
                if(w == 0) {
                    tr[v] = u;
                    if(my[v] == -1) return v;
                    q.push(my[v]);
                }
                if(d[v] > w) d[v] = w, ar[v] = u;
            }
        }
        int delta = INF;
        for(int v = 0; v < p; ++v) if(tr[v] == -1) delta =
            min(delta, d[v]);
        fx[s] += delta;
        for(int v = 0; v < p; ++v)

```

```

        if(tr[v] == -1) d[v] -= delta;
        else fx[my[v]] += delta, fy[v] -= delta;
        for(int v = 0; v < p; ++v) if(tr[v] == -1 && d[v] == 0) {
            tr[v] = ar[v];
            if(my[v] == -1) return v;
            q.push(my[v]);
        }
    }
}

void maxMatchMinCost() {
    fill_n(mx, p, -1);
    fill_n(my, p, -1);
    for(int i = 0; i < p; ++i) fx[i] = *min_element(g[i], g[i]+p);
    for(int s = 0; s < p; ++s) {
        int f = augment(s);
        while(f != -1) {
            int x = tr[f], nx = mx[x];
            mx[x] = f;
            my[f] = x;
            f = nx;
        }
    }
}

```

6 Ganeral Matching

```

class MatchingGraph {
public:
    vector <vector<int> > adj;
    vector <bool> blossom;
    vector <int> parent;
    vector <int> base;
    vector <int> match;
    int n;
    MatchingGraph() {
        n = 0;
    }
    void addEdge(int x, int y) {
        adj[x].push_back(y);
        adj[y].push_back(x);
    }
    void clearGraph() {
        int i;

```

```

        for (i=0; i<SZ(adj); ++i)
            adj[i].clear();
        fill(blossom.begin(),blossom.end(),false);
        fill(parent.begin(),parent.end(),-1);
        for (i=0; i<n; ++i)
            base[i] = i;
        for (i=0; i<n; ++i)
            match[i] = -1;
    }

    void setN(int newn) {
        n = newn;
        adj.resize(n);
        blossom.resize(n);
        base.resize(n);
        match.resize(n);
        parent.resize(n);
        clearGraph();
    }

    int lca(int x, int y) {
        vector <bool> fy;
        fy.resize(n);
        fill(fy.begin(),fy.end(),false);
        while (true) {
            x = base[x];
            fy[x] = true;
            if (match[x] == -1)
                break;
            x = parent[match[x]];
        }
        while (true) {
            y = base[y];
            if (fy[y])
                return y;
            y = parent[match[y]];
        }
        return -1;
    }

    void path(int now, int child, int curbase) {
        while (base[now] != curbase) {
            blossom[base[now]] = blossom[base[match[now]]] = true;
            parent[now] = child;
            child = match[now];
            now = parent[match[now]];
        }
    }
}

```

```

}
int augmentPath(int x) {
    int i,j;
    for (i=0; i<n; ++i)
        base[i] = i;
    for (i=0; i<n; ++i)
        parent[i] = -1;
    queue<int> bfs;
    vector<bool> sudah;
    sudah.resize(n);
    fill(sudah.begin(), sudah.end(), false);
    sudah[x] = true;
    bfs.push(x);
    while (!bfs.empty()) {
        int now = bfs.front();
        bfs.pop();
        for (i=0; i<SZ(adj[now]); ++i) {
            int next = adj[now][i];
            if (base[next]==base[now] || match[next] == now);
            else if (next == x || (match[next]!=-1 &&
                                parent[match[next]]!=-1)) {
                int curbase = lca(now,next);
                fill(blossom.begin(), blossom.end(), false);
                path(now,next,curbase);
                path(next,now,curbase);
                for (j = 0; j < n; ++j)
                    if (blossom[j]) {
                        base[j] = curbase;
                        if (!sudah[j]) {
                            sudah[j] = true;
                            bfs.push(j);
                        }
                    }
            } else if (parent[next]==-1) {
                parent[next] = now;
                if (match[next] == -1)
                    return next;
                sudah[match[next]] = true;
                bfs.push(match[next]);
            }
        }
    }
    return -1;
}

```

```

int edmondsMatch() {
    int i;
    int res = 0;
    for (i=0; i<n; ++i) {
        if (match[i]==-1) {
            int x = augmentPath(i);
            while (x>=0) {
                int p = parent[x];
                int pp = match[p];
                match[x] = p;
                match[p] = x;
                x = pp;
            }
        }
    }
    for (i=0; i<n; ++i)
        if (match[i]!=-1)
            ++res;
    return res >> 1;
}
};

```

7 Dinic MaxFlow

```

class DinicFlow {
private:
    vector<int> dist, head, work;
    vector<int> point, flow, capa, next;
    int n, m;

    bool bfs(int s, int t) {
        For(i, 1, n) dist[i] = -1;
        queue<int> q;
        dist[s] = 0;
        q.push(s);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (int i = head[u]; i >= 0; i = next[i])
                if (flow[i] < capa[i] && dist[point[i]] < 0) {
                    dist[point[i]] = dist[u] + 1;
                    q.push(point[i]);
                }
        }
    }
}

```

```

    }
    return dist[t] >= 0;
}

int dfs(int s, int t, int f) {
    if (s == t) return f;
    for (int &i = work[s]; i >= 0; i = next[i])
        if (flow[i] < capa[i] && dist[point[i]] == dist[s] + 1) {
            int d = dfs(point[i], t, min(f, capa[i] - flow[i]));
            if (d > 0) {
                flow[i] += d;
                flow[i ^ 1] -= d;
                return d;
            }
        }
    return 0;
}

public:
    DinicFlow(int n = 0) {
        this->n = n;
        this->m = 0;
        dist.assign(n + 7, 0);
        head.assign(n + 7, -1);
        work.assign(n + 7, 0);
    }

    void addEdge(int u, int v, int c1, int c2 = 0) {
        point.push_back(v);
        capa.push_back(c1);
        flow.push_back(0);
        next.push_back(head[u]);
        head[u] = m++;
        point.push_back(u);
        capa.push_back(c2);
        flow.push_back(0);
        next.push_back(head[v]);
        head[v] = m++;
    }

    int maxFlow(int s, int t) {
        int totFlow = 0;
        while (bfs(s, t)) {
            For(i, 1, n) work[i] = head[i];

```

```

        while (true) {
            int d = dfs(s, t, cmax);
            if (d == 0) break;
            totFlow += d;
        }
    }
    return totFlow;
}

```

8 Mincost MaxFlow SPFA

Min Cost Max Flow - SPFA
 Index from 0
 edges cap changed during find flow
 Lots of double comparison --> likely to fail for double
 Example:
 MinCostFlow mcf(n);
 mcf.addEdge(u, v, cap, cost);
 cout << mcf.minCostFlow() << endl;

```

template<class Flow=int, class Cost=int>
struct MinCostFlow {
    const Flow INF_FLOW = 1000111000;
    const Cost INF_COST = 1000111000111000LL;

    int n, t, S, T;
    Flow totalFlow;
    Cost totalCost;
    vector<int> last, visited;
    vector<Cost> dis;
    struct Edge {
        int to;
        Flow cap;
        Cost cost;
        int next;
        Edge(int to, Flow cap, Cost cost, int next) :
            to(to), cap(cap), cost(cost), next(next) {}
    };
    vector<Edge> edges;

    MinCostFlow(int n) : n(n), t(0), totalFlow(0), totalCost(0), last(n,
        -1), visited(n, 0), dis(n, 0) {}

```

```

        edges.clear();
    }

    int addEdge(int from, int to, Flow cap, Cost cost) {
        edges.push_back(Edge(to, cap, cost, last[from]));
        last[from] = t++;
        edges.push_back(Edge(from, 0, -cost, last[to]));
        last[to] = t++;
        return t - 2;
    }

    pair<Flow, Cost> minCostFlow(int _S, int _T) {
        S = _S; T = _T;
        SPFA();
        while (1) {
            while (1) {
                REP(i,n) visited[i] = 0;
                if (!findFlow(S, INF_FLOW)) break;
            }
            if (!modifyLabel()) break;
        }
        return make_pair(totalFlow, totalCost);
    }

private:
    void SPFA() {
        REP(i,n) dis[i] = INF_COST;
        priority_queue< pair<Cost,int> > Q;
        Q.push(make_pair(dis[S]=0, S));
        while (!Q.empty()) {
            int x = Q.top().second;
            Cost d = -Q.top().first;
            Q.pop();
            // For double: dis[x] > d + EPS
            if (dis[x] != d) continue;
            for(int it = last[x]; it >= 0; it = edges[it].next)
                if (edges[it].cap > 0 && dis[edges[it].to] > d + edges[it].cost)
                    Q.push(make_pair(-(dis[edges[it].to] = d + edges[it].cost), edges[it].to));
        }
        Cost disT = dis[T]; REP(i,n) dis[i] = disT - dis[i];
    }
}

```

```

Flow findFlow(int x, Flow flow) {
    if (x == T) {
        totalCost += dis[S] * flow;
        totalFlow += flow;
        return flow;
    }
    visited[x] = 1;
    Flow now = flow;
    for(int it = last[x]; it >= 0; it = edges[it].next)
        // For double: fabs(dis[edges[it].to] + edges[it].cost - dis[x]) < EPS
        if (edges[it].cap && !visited[edges[it].to] && dis[edges[it].to] + edges[it].cost == dis[x]) {
            Flow tmp = findFlow(edges[it].to, min(now, edges[it].cap));
            ;
            edges[it].cap -= tmp;
            edges[it ^ 1].cap += tmp;
            now -= tmp;
            if (!now) break;
        }
    return flow - now;
}

bool modifyLabel() {
    Cost d = INF_COST;
    REP(i,n) if (visited[i])
        for(int it = last[i]; it >= 0; it = edges[it].next)
            if (edges[it].cap && !visited[edges[it].to])
                d = min(d, dis[edges[it].to] + edges[it].cost - dis[i]);

    // For double: if (d > INF_COST / 10)    INF_COST = 1e20
    if (d == INF_COST) return false;
    REP(i,n) if (visited[i])
        dis[i] += d;
    return true;
}
};

```

9 Upper Lower

- For each edge in original flow:
- Add edge with cap = upper bound - lower bound.

- Add source s, sink t.
- Let $M[v] = (\text{sum of lower bounds of ingoing edges to } v) - (\text{sum of lower bounds of outgoing edges from } v)$.
- For all v, if $M[v] > 0$, add (s, v, M), else add (v, t, -M).
- If all outgoing edges from S are full --> feasible flow exists, it is flow + lower bounds.

Feasible flow in network with upper + lower constraint, with source & sink :

- Add edge (t, s) with capacity [0, INF].
- Check feasible in network without source & sink.

Max flow with both upper + lower constraints, source s, sink t: add edge (t, s, +INF).

- Binary search lower bound, check whether feasible flow exists WITHOUT source / sink

10 Two sat

```
int n, m, g[maxn];
bool cx[maxn];
vector<int> listV, ke[maxn], K[maxn];
```

```
int cal(int x) {
    if (x%2 == 0) return x - 1;
    else return x + 1;
}
```

```
void add(int u, int v) {
    ke[u].pb(v);
    K[v].pb(u);
}
```

```
void dfs(int u) {
    cx[u] = true;
    for(int v : ke[u])
        if (!cx[v]) dfs(v);
    listV.pb(u);
}
```

```
void dfs(int u, int x) {
    g[u] = x;
    for(int v : K[u])
```

```
        if (g[v] == 0) dfs(v,x);
    }

int main() {
    cin >> m >> n;
    n += n;
    For(i,1,m) {
        int u, v;
        cin >> u >> v;
        u *= 2;
        v *= 2;
        if (u < 0) u = cal(abs(u));
        if (v < 0) v = cal(abs(v));
        add(cal(u),v);
        add(cal(v),u);
    }
    listV.pb(0);
    For(i,1,n)
        if (!cx[i]) dfs(i);
    int ng = 0;
    Ford(i,n,1) {
        int u = listV[i];
        if (g[u] == 0) dfs(u,++ng);
    }
    for(int i = 2; i <= n; i += 2)
        if (g[i] == g[i-1]) NO;
    YES;
    vector<int> result;
    for(int i = 2; i <= n; i += 2)
        if (g[i] > g[i-1]) result.pb(i>>1);
}
```

11 Alternative Tree

```
int n, m, l, q, t, res, test,
    a[maxn], tin[maxn], tout[maxn], mark[maxn], terror[maxn], f[maxn][20];
vector<int> adj[maxn], _adj[maxn];
stack<int> stk;

void visit(const int &u) {
    tin[u] = ++t;
    for(int i = 1; i <= l; ++i) f[u][i] = f[f[u][i-1]][i-1];
    for(auto v : adj[u])
```



```

        if (v != f[u][0]) {
            f[v][0] = u;
            visit(v);
        }
        tout[u] = ++t;
    }

bool anc(const int &u, const int &v) {
    return tin[u] <= tin[v] && tout[u] >= tout[v];
}

int lca(int u, int v) {
    if (anc(u,v)) return u;
    if (anc(v,u)) return v;
    for(int i = 1; i >= 0; --i)
        if (!anc(f[u][i],v)) u = f[u][i];
    return f[u][0];
}

void query() {
    cin >> m;
    for(int i = 1; i <= m; ++i) {
        cin >> a[i];
        _adj[a[i]].clear();
        mark[a[i]] = test;
        terror[a[i]] = test;
    }
    sort(a+1,a+m+1,cmp);
    for(int i = 1; i < m; ++i) {
        int tmp = lca(a[i],a[i+1]);
        if (mark[tmp] < test) {
            mark[tmp] = test;
            a[++m] = tmp;
            _adj[tmp].clear();
        }
    }
    // sort theo tin
    sort(a+1,a+m+1,cmp);
    while (!stk.empty()) stk.pop();
    stk.push(a[1]);
    for(int i = 2; i <= m; ++i) {
        while (tout[stk.top()] < tout[a[i]]) stk.pop();
        _adj[stk.top()].push_back(a[i]);
        stk.push(a[i]);
    }
}

```

```

    }
    res = 0;
    check(a[1]);
    cout << res << "\n";
}

int main() {
    l = log2(n);
    cin >> q;
    f[1][0] = 1;
    visit(1);
    for(test = 1; test <= q; ++test) query();
}

```

12 Max Clique

```

class MaxClique {
public:
    static const int MV = 210;

    int V;
    int el[MV][MV/30+1];
    int dp[MV];
    int ans;
    int s[MV][MV/30+1];
    vector<int> sol;

    void init(int v) {
        V = v; ans = 0;
        FZ(el); FZ(dp);
    }

    /* Zero Base */
    void addEdge(int u, int v) {
        if(u > v) swap(u, v);
        if(u == v) return;
        el[u][v/32] |= (1<<(v%32));
    }

    bool dfs(int v, int k) {
        int c = 0, d = 0;
        for(int i=0; i<(V+31)/32; i++) {
            s[k][i] = el[v][i];
        }
    }
}

```

```

        if(k != 1) s[k][i] &= s[k-1][i];
        c += __builtin_popcount(s[k][i]);
    }
    if(c == 0) {
        if(k > ans) {
            ans = k;
            sol.clear();
            sol.push_back(v);
            return 1;
        }
        return 0;
    }
    for(int i=0; i<(V+31)/32; i++) {
        for(int a = s[k][i]; a ; d++) {
            if(k + (c-d) <= ans) return 0;
            int lb = a&(-a), lg = 0;
            a ^= lb;
            while(lb!=1) {
                lb = (unsigned int)(lb) >> 1;
                lg ++;
            }
            int u = i*32 + lg;
            if(k + dp[u] <= ans) return 0;
            if(dfs(u, k+1)) {
                sol.push_back(v);
                return 1;
            }
        }
    }
    return 0;
}

int solve() {
    for(int i=V-1; i>=0; i--) {
        dfs(i, 1);
        dp[i] = ans;
    }
    return ans;
}
};

```

13 Euler Path

NOTES:

- When choosing starting vertex (for calling find_path), make sure $\deg[\text{start}] > 0$.
- If find Euler path, starting vertex must have odd degree.
- Check no solution: $\text{SZ}(\text{path}) == \text{nEdge} + 1$.

If directed:

- Edge $-->$ int
- add_edge(int a, int b) { adj[a].push_back(b); }
- Check for no solution:
 - - for all u, $|\text{in_deg}[u] - \text{out_deg}[u]| \leq 1$
 - - At most 1 vertex with $\text{in_deg}[u] - \text{out_deg}[u] = 1$
 - - At most 1 vertex with $\text{out_deg}[u] - \text{in_deg}[u] = 1$ (start vertex)
 - - BFS from start vertex, all vertices u with $\text{out_deg}[u] > 0$ must be visited

```

struct Edge {
    int to;
    list<Edge>::iterator rev;

    Edge(int to) :to(to) {}
};

```

```

const int MN = 100111;
list<Edge> adj[MN];
vector<int> path; // our result

```

```

void find_path(int v) {
    while(adj[v].size() > 0) {
        int vn = adj[v].front().to;
        adj[vn].erase(adj[v].front().rev);
        adj[v].pop_front();
        find_path(vn);
    }
    path.push_back(v);
}

```

```

void add_edge(int a, int b) {
    adj[a].push_front(Edge(b));
    auto ita = adj[a].begin();
    adj[b].push_front(Edge(a));
    auto itb = adj[b].begin();
    ita->rev = itb;
    itb->rev = ita;
}

```

14 Interesection of two paths

```
int intersect(int a, int b, int c, int d){
    if(lca(b,c)!=c) return 0;
    int z = lca(b,d);
    if(lv[c]<lv[a]){
        if(lca(a,z)==a) return dist(z,a);
        }else{
        if(lca(c,z)==c) return dist(c,z);}
    return 0;
}
```

15 Tree ISO

```
namespace TreeISO {
typedef vector<vector<int>> vvi;
typedef vector<int> vi;
typedef pair<vi, int> pvii;
const int MAXN = 4010;
#define ii pair<int, int>
int N;
vvi edges[2], levels[2];
int ts[MAXN], label[2][MAXN], parent[2][MAXN];
vi centroid[2];
int findCentroid(const int tID, const int u, const int p) {
    int children = 0, curr;
    for (auto &e : edges[tID][u]) {
        if (e != p) {
            curr = findCentroid(tID, e, u);
            if (curr > (N >> 1))
                break;
            children += curr;
        }//if
    }//for
    if (N - children - 1 <= (N >> 1))
        centroid[tID].push_back(u);
    return ts[u] = children + 1;
}//findCentroid

int setLevels(const int tID, const int u, const int p, const int d) {
    parent[tID][u] = p;
    levels[tID][d].push_back(u);
    int mx = d;
    for (auto &e : edges[tID][u])
```

```
        if (e != p)
            mx = max(mx, setLevels(tID, e, u, d + 1));
    return mx;
}//setLevels

bool isoCheck(const int lvl) {
    for (int it = lvl; it >= 0; it--) {
        vector<pvii> order[2];
        for (int i = 0; i < 2; i++) {
            for (auto &u : levels[i][it]) {
                order[i].push_back(pvii(vi(), u));
                for (auto &e : edges[i][u])
                    if (e != parent[i][u])
                        order[i].back().first.push_back(label[i][e]);
            }//for
        }//for
        if ((int) order[0].size() != ((int) order[1].size()))
            return 0;
        for (int i = 0; i < 2; i++) {
            for (int j = 0; j < (int) order[0].size(); j++)
                sort(order[i][j].first.begin(), order[i][j].first.end());
            sort(order[i].begin(), order[i].end());
        }//for
        int labelID = 0;
        for (int i = 0; i < (int) order[0].size(); i++) {
            if (order[0][i].first != order[1][i].first)
                return 0;
            if (i && order[0][i].first == order[0][i - 1].first) {
                label[0][order[0][i].second] = label[1][order[1][i].second] =
                    labelID;
                continue;
            }//if
            label[0][order[0][i].second] = label[1][order[1][i].second] = ++
                labelID;
        }//for
    }//for
    return 1;
}//isoCheck

int checkISO(int _N, vector<ii> _edges) {
    N = _N;
    int u, v;
    int T = 1;
    while (T--) {
        int cur = 0;
        memset(ts, 0, sizeof(int) * (N + 2));
```

```

for (int i = 0; i < 2; i++) {
    edges[i].assign(N + 5, vi());
    levels[i].assign(N + 5, vi());
    memset(label[i], 0, sizeof(int) * (N + 2));
    memset(parent[i], 0, sizeof(int) * (N + 2));
    centroid[i].clear();
    for (int j = 0; j < N - 1; j++) {
        int u = _edges[cur].first;
        int v = _edges[cur].second;
        cur++;
        edges[i][u].push_back(v);
        edges[i][v].push_back(u);
    } //for
    findCentroid(i, edges[i][0].empty() ? 1 : 0, -1);
} //for
if (edges[0][0].empty())
    N++;
if ((int) centroid[0].size() != (int) centroid[1].size()) {
    return 0;
} //if
if ((int) centroid[0].size() == 2) {
    for (int i = 0; i < 2; i++) {
        for (int j = 0; j < 2; j++) {
            edges[i][centroid[i][j]].erase(std::remove(edges[i][centroid[i][j]].begin(),
                edges[i][centroid[i][j]].end(),
                centroid[i][!j]),
                edges[i][centroid[i][j]].end());

            edges[i][centroid[i][j]].push_back(N);
            edges[i][N].push_back(centroid[i][j]);
        } //for
        centroid[i][0] = N;
    } //for
} //if
int d[2];
for (int i = 0; i < 2; i++)
    d[i] = setLevels(i, centroid[i][0], -1, 0);
if (d[0] != d[1]) {
    return 0;
} //if
if (d[0] >= 0)
    return isoCheck(d[0] - 1) ? 1 : 0;

```

```

} //while
return 0;
} //main
}

```

16 Centroid

```

void findCentroid(int u, int par, int Size) {
    nChild[u] = 1;
    bool pre = true;
    for (int i = 0; i < a[u].size(); i++) {
        int v = a[u][i];
        if (v != par && ok[v]) {
            findCentroid(v, u, Size);
            if (nChild[v] > Size / 2) pre = false;
            nChild[u] += nChild[v];
        }
    }
    if (pre && nChild[u] >= Size / 2)
        centroid = u;
}

```

17 Aho Corasick

```

const int NODE = (int) 1e6 + 1;
const int NC = 26;

int nextNode[NODE][NC];
int chr[NODE];
int parent[NODE];
int prefix[NODE];
int numNodes;
set<int> match[NODE];

int getPrefix(int);

int go(int u, int c) {
    if (nextNode[u][c] != -1) return nextNode[u][c];
    if (u == 0) return 0;
    return nextNode[u][c] = go(getPrefix(u), c);
}

```

```

int getPrefix(int u) {
    if (prefix[u] != -1) return prefix[u];
    if (u == 0 || parent[u] == 0) return prefix[u] = 0;
    return prefix[u] = go(getPrefix(parent[u]), chr[u]);
}

void add(const string &s, int id) {
    int u = 0;
    for (int i = 0; i < (int) s.size(); ++i) {
        int c = s[i] - 'A';
        if (nextNode[u][c] == -1) {
            nextNode[u][c] = numNodes;
            fill(nextNode[numNodes], nextNode[numNodes] + NC, -1);
            chr[numNodes] = c;
            parent[numNodes] = u;
            prefix[numNodes] = -1;
            match[numNodes].clear();
            match[numNodes].insert(-1);
            ++numNodes;
        }
        u = nextNode[u][c];
    }
    match[u].insert(id);
}

set<int>& getMatch(int u) {
    if (match[u].count(-1) == 0) return match[u];
    const set<int> &foo = getMatch(getPrefix(u));
    match[u].insert(foo.begin(), foo.end());
    match[u].erase(-1);
    return match[u];
}

void init() {
    fill(nextNode[0], nextNode[0] + NC, -1);
    numNodes = 1;
}

```

18 Suffix Array

```

struct SuffixArray {
    const int L;
    string s;

```

```

    vector<vector<int>> > P;
    vector<pair<pair<int,int>,int>> > M;
    SuffixArray(const string &s) : L(s.length()), s(s), P(1,
        vector<int>(L, 0)), M(L) {
        for (int i = 0; i < L; i++) P[0][i] = int(s[i]);
        for (int skip = 1, lv = 1; skip < L; skip *= 2, lv++) {
            P.push_back(vector<int>(L, 0));
            for (int i = 0; i < L; i++)
                M[i] = make_pair(make_pair(P[lv-1][i], i + skip < L
                    ? P[lv-1][i + skip] : -1000), i);

            sort(M.begin(), M.end());
            for (int i = 0; i < L; i++)
                P[lv][M[i].se] = (i > 0 && M[i].fi == M[i-1].fi) ?
                    P[lv][M[i-1].se] : i;
        }
    }

    vector<int> GetSuffixArray() {
        return P.back();
    }

    // returns the length of the longest common prefix of s[i...L-1]
    and s[j...L-1]
    int LongestCommonPrefix(int i, int j) {
        int len = 0;
        if (i == j) return L - i;
        for (int k = P.size() - 1; k >= 0 && i < L && j < L; k--) {
            if (P[k][i] == P[k][j]) {
                i += 1 << k;
                j += 1 << k;
                len += 1 << k;
            }
        }
        return len;
    }
};

```

19 Suffix Array O(n)

```

#include <bits/stdc++.h>
#define FOR(i,a,b) for (int i=(a),_b=(b);i<=_b;i=i+1)
#define REP(i,n) for (int i=0,_n=(n);i<_n;i=i+1)
#define MASK(i) (1LL<<(i))
#define BIT(x,i) (((x)>>(i))&1)

```

```

#define tget(i) BIT(t[(i) >> 3], (i) & 7)
#define tset(i, b) { if (b) t[(i) >> 3] |= MASK((i) & 7); else t[(i) >> 3]
    &= ~MASK((i) & 7); }
#define chr(i) (cs == sizeof(int) ? ((int *)s)[i] : ((unc *)s)[i])
#define isLMS(i) ((i) > 0 && tget(i) && !tget((i) - 1))

typedef unsigned char unc;
class SuffixArray {
public:
    int *sa, *lcp, *rank, n;
    unc *s;
    void getbuckets(unc s[], vector<int> &bkt, int n, int k, int cs, bool
        end) {
        FOR(i, 0, k) bkt[i] = 0;
        REP(i, n) bkt[chr(i)]++;
        int sum = 0;
        FOR(i, 0, k) {
            sum += bkt[i];
            bkt[i] = end ? sum : sum - bkt[i];
        }
    }
    void inducesal(vector<unc> &t, int sa[], unc s[], vector<int> &bkt,
        int n, int k, int cs, bool end) {
        getbuckets(s, bkt, n, k, cs, end);
        REP(i, n) {
            int j = sa[i] - 1;
            if (j >= 0 && !tget(j)) sa[bkt[chr(j)]++] = j;
        }
    }
    void inducesas(vector<unc> &t, int sa[], unc s[], vector<int> &bkt,
        int n, int k, int cs, bool end) {
        getbuckets(s, bkt, n, k, cs, end);
        FORD(i, n - 1, 0) {
            int j = sa[i] - 1;
            if (j >= 0 && tget(j)) sa[--bkt[chr(j)]] = j;
        }
    }
    void build(unc s[], int sa[], int n, int k, int cs) {
        int j;
        vector<unc> t = vector<unc>(n / 8 + 1, 0);
        tset(n - 2, 0);
        tset(n - 1, 1);
        FORD(i, n - 3, 0) tset(i, chr(i) < chr(i+1) || (chr(i) == chr(i+1)
            && tget(i+1)));
    }
};

```

```

vector<int> bkt = vector<int> (k + 1, 0);
getbuckets(s, bkt, n, k, cs, true);
REP(i, n) sa[i] = -1;
REP(i, n) if (isLMS(i)) sa[--bkt[chr(i)]] = i;
inducesal(t, sa, s, bkt, n, k, cs, false);
inducesas(t, sa, s, bkt, n, k, cs, true);
bkt.clear();
int n1 = 0;
REP(i, n) if (isLMS(sa[i])) sa[n1++] = sa[i];
FOR(i, n1, n - 1) sa[i] = -1;
int name = 0;
int prev = -1;
REP(i, n1) {
    int pos = sa[i];
    bool diff = false;
    REP(d, n) {
        if (prev < 0 || chr(prev + d) != chr(pos + d) || tget(prev
            + d) != tget(pos + d)) {
            diff = true;
            break;
        }
        else if (d > 0 && (isLMS(prev + d) || isLMS(pos + d)))
            break;
    }
    if (diff) {
        name++;
        prev = pos;
    }
    sa[n1 + pos / 2] = name - 1;
}
j = n - 1;
FORD(i, n - 1, n1) if (sa[i] >= 0) sa[j--] = sa[i];
int *sa1 = sa;
int *s1 = sa + n - n1;
if (name < n1) build((unc *)s1, sa1, n1, name-1, sizeof(int));
else REP(i, n1) sa1[s1[i]] = i;
bkt.assign(k + 1, 0);
getbuckets(s, bkt, n, k, cs, true);
j = 0;
REP(i, n) if (isLMS(i)) s1[j++] = i;
REP(i, n1) sa1[i] = s1[sa1[i]];
FOR(i, n1, n - 1) sa[i] = -1;
FORD(i, n1 - 1, 0) {
    j = sa[i];
}

```

```

        sa[i] = -1;
        sa[--bkt[chr(j)]] = j;
    }
    inducesal(t, sa, s, bkt, n, k, cs, false);
    inducesas(t, sa, s, bkt, n, k, cs, true);
    bkt.clear();
    t.clear();
}

void calc_lcp(void) {
    FOR(i,1,n) rank[sa[i]] = i;
    int h = 0;
    REP(i, n) if (rank[i] < n) {
        int j = sa[rank[i] + 1];
        while (s[i + h] == s[j + h]) h++;
        lcp[rank[i]] = h;
        if (h > 0) h--;
    }
}

SuffixArray() {
    n = 0;
    sa = lcp = rank = NULL;
    s=NULL;
}

SuffixArray(string ss) {
    n = ss.size();
    sa = new int[n + 7];
    lcp = new int [n + 7];
    rank = new int [n + 7];
    s = (unc *)ss.c_str();
    build(s, sa, n + 1, 256, sizeof(char));
    calc_lcp();
}
};

//Sorted suffices are SA[1] to SA[N]. The values of SA[1], SA[2], ..., SA[
N] are 0, 1, ..., N - 1
//The longest common prefix of SA[i] and SA[i + 1] is LCP[i]

int main(void) {
    string s = "mississippi";
    SuffixArray suffixArray(s);
    FOR(i, 1, 11) printf("%d %s %d\n", suffixArray.sa[i], s.substr(
        suffixArray.sa[i]).c_str(), suffixArray.lcp[i]);
}

```

20 Manacher

```

void manacher() {
    memset(p,0,sizeof p);
    int center = 0, right = 0,mi;
    for (int i = 1; i < n; i++) {
        mi = 2 * center - i;
        if (right > i) p[i] = min(right - i, p[mi]);
        while (a[i+(1+p[i])] == a[i-(1+p[i])]) p[i]++;
        //printf("%d:%d\n",i,p[i]);
        if (i + p[i] > right) {
            right = i+p[i];
            center = i;
        }
    }
}

```

21 DP knuth

<http://codeforces.com/blog/entry/8219>

Original Recurrence:

$$dp[i][j] = \min(dp[i][k] + dp[k][j]) + C[i][j] \quad \text{for } k = i+1..j-1$$

Necessary & Sufficient Conditions:

$$A[i][j-1] \leq A[i][j] \leq A[i+1][j]$$

with $A[i][j]$ = smallest k that gives optimal answer

Also applicable if the following conditions are met:

1. $C[a][c] + C[b][d] \leq C[a][d] + C[b][c]$ (quadrangle inequality)
2. $C[b][c] \leq C[a][d]$ (monotonicity)

for all $a \leq b \leq c \leq d$

To use:

Calculate $dp[i][i]$ and $A[i][i]$

```

FOR(len = 1..n-1)
    FOR(i = 1..n-len) {
        j = i + len
        FOR(k = A[i][j-1]..A[i+1][j])
            update(dp[i][j])
    }

```

// OPTCUT

#include "../template.h"

const int MN = 2011;

```

int a[MN], dp[MN][MN], C[MN][MN], A[MN][MN];
int n;

void solve() {
    cin >> n; FOR(i,1,n) { cin >> a[i]; a[i] += a[i-1]; }
    FOR(i,1,n) FOR(j,i,n) C[i][j] = a[j] - a[i-1];

    FOR(i,1,n) dp[i][i] = 0, A[i][i] = i;

    FOR(len,1,n-1)
        FOR(i,1,n-len) {
            int j = i + len;
            dp[i][j] = 2000111000;
            FOR(k,A[i][j-1],A[i+1][j]) {
                int cur = dp[i][k-1] + dp[k][j] + C[i][j];
                if (cur < dp[i][j]) {
                    dp[i][j] = cur;
                    A[i][j] = k;
                }
            }
        }
    cout << dp[1][n] << endl;
}

```

22 DP divide conquer

```

// http://codeforces.com/blog/entry/8219
// Divide and conquer optimization:
// Original Recurrence
//  $dp[i][j] = \min(dp[i-1][k] + C[k][j])$  for  $k < j$ 
// Sufficient condition:
//  $A[i][j] \leq A[i][j+1]$ 
// where  $A[i][j]$  = smallest  $k$  that gives optimal answer
// How to use:
// // compute  $i$ -th row of  $dp$  from  $L$  to  $R$ .  $optL \leq A[i][L] \leq A[i][R] \leq optR$ 
// compute( $i, L, R, optL, optR$ )
// 1. special case  $L == R$ 
// 2. let  $M = (L + R) / 2$ . Calculate  $dp[i][M]$  and  $opt[i][M]$  using 0
// ( $optR - optL + 1$ )
// 3. compute( $i, L, M-1, optL, opt[i][M]$ )
// 4. compute( $i, M+1, R, opt[i][M], optR$ )
const int MN = 4011;

```

```

const int inf = 1000111000;
int n, k, cost[MN][MN], dp[811][MN];
inline int getCost(int i, int j) {
    return cost[j][j] - cost[j][i-1] - cost[i-1][j] + cost[i-1][i-1];
}
void compute(int i, int L, int R, int optL, int optR) {
    if (L > R) return ;
    int mid = (L + R) >> 1, savek = optL;
    dp[i][mid] = inf;
    FOR(k,optL,min(mid-1, optR)) {
        int cur = dp[i-1][k] + getCost(k+1, mid);
        if (cur < dp[i][mid]) {
            dp[i][mid] = cur;
            savek = k;
        }
    }
    compute(i, L, mid-1, optL, savek);
    compute(i, mid+1, R, savek, optR);
}
void solve() {
    cin >> n >> k;
    FOR(i,1,n) FOR(j,1,n) {
        cin >> cost[i][j];
        cost[i][j] = cost[i-1][j] + cost[i][j-1] - cost[i-1][j-1] + cost[i][j];
    }
    dp[0][0] = 0;
    FOR(i,1,n) dp[0][i] = inf;

    FOR(i,1,k) {
        compute(i, 1, n, 0, n);
    }
    cout << dp[k][n] / 2 << endl;
}

```

23 Convex Hull

```

struct Point {
    long long x, y;
    bool operator < (const Point &v) const {
        return x == v.x ? y < v.y : x < v.x;
    }
    long long cross(const Point &p, const Point &q) const {

```



```

        return (p.x - x) * (q.y - y) - (p.y - y) * (q.x - x);
    }
};

vector<Point> convexHull(vector<Point> p) {
    sort(p.begin(), p.end());
    int k = 0, n = p.size();
    vector<Point> poly (2 * n);
    for(int i = 0; i < n; ++i) {
        while(k >= 2 && poly[k-2].cross(poly[k-1], p[i]) < 0) --k;
        poly[k++] = p[i];
    }
    for(int i = n-2, t = k+1; i >= 0; --i) {
        while(k >= t && poly[k-2].cross(poly[k-1], p[i]) < 0) --k;
        poly[k++] = p[i];
    }
    poly.resize(min(n, max(0, k - 1)));
    return poly;
}

```

24 Geometry's tricks

```

int __builtin_clz(int x); //number of leading zero
int __builtin_ctz(int x); //number of trailing zero
int __builtin_clzll(long long x); //number of leading zero
int __builtin_ctzll(long long x); //number of trailing zero
int __builtin_popcount(int x); // number of 1-bits in x
int __builtin_popcountll(long long x); //number of 1-bits i
// hash func overload
struct point{
    int x, y;
    bool operator==(const point &p)const{ return x == p.x && y == p.y; }
};
struct hasher {
    size_t operator()(const point &p)const{ return p.x * 2 + p.y * 3; }
};
unordered_map<point, int, hasher> hsh;
const double eps = 1e-9;
bool equal(const double &x, const double &y) {
    return fabs(x - y) <
        eps;
}
struct Point {
    double x, y;

```

```

    Point(double x = 0, double y = 0): x(x), y(y) {}
    Point operator + (const Point &p) const {
        return {x + p.x, y +
            p.y
        };
    }
    Point operator - (const Point &p) const {
        return {x - p.x, y -
            p.y
        };
    }
    Point operator * (double t) const {
        return {x * t, y * t};
    }
    double operator * (const Point &p) const {
        return x * p.x + y *
            p.y;
    }
    double operator % (const Point &p) const {
        return x * p.y - y *
            p.x;
    }
    bool operator == (const Point &p) const {
        return equal(x, p.x)
            && equal(y, p.y);
    }
    double operator ~ () const {
        return sqrt(*this **this);
    }
};

struct Comparator {
    Point a, b;
    Comparator(Point a, Point b): a(a), b(b) {}
    bool operator () (const Point &p, const Point &q) {
        return (p-a) * (b-a) < (q-a) * (b-a);
    }
};

bool between(double x, double l, double r) {
    if (l > r) swap(l, r);
    return x + eps > l && x - eps < r;
}

bool inside(Point q, const vector<Point> &p) {
    int n = p.size();
    for (int i = 0; i < n; i++) {

```

```

    int j = i + 1 < n ? i + 1 : 0;
    if (fabs((q - p[i]) % (p[j] - p[i])) > eps) continue;
    if ((q - p[i]) * (p[j] - p[i]) < -eps) continue;
    if ((q - p[j]) * (p[i] - p[j]) < -eps) continue;
    return true;
}

int fl = 0;
for (int i = 0; i < n; i++) {
    int j = i + 1 < n ? i + 1 : 0;
    Point a = p[i], b = p[j];
    if (equal(a.x, b.x)) continue;
    if (a.x > b.x) swap(a, b);
    if (q.x < a.x - eps) continue;
    if (q.x > b.x - eps) continue;
    if ((q - a) % (b - a) > 0) fl ^= 1;
}

return fl;
}

void intersect(Point p, Point q, Point a, Point b, vector<Point>
               &ints) {
    double na = (a - p) % (q - p), nb = (b - p) % (q - p);
    if (na * nb > eps) return;
    if (equal(na, nb)) return;
    ints.push_back(a + (b - a) * (na / (na - nb)));
}

void intersectCircleLine() {
    double r, a, b, c;
    double x0 = -a*c/(a*a+b*b), y0 = -b*c/(a*a+b*b);
    if (c*c > r*r*(a*a+b*b)+EPS) puts ("no points");
    else if (abs (c*c - r*r*(a*a+b*b)) < EPS) {
        puts ("1 point");
        cout << x0 << ' ' << y0 << '\n';
    } else {
        double d = r*r - c*c/(a*a+b*b);
        double mult = sqrt (d / (a*a+b*b));
        double ax,ay,bx,by;
        ax = x0 + b * mult;
        bx = x0 - b * mult;
        ay = y0 - a * mult;
        by = y0 + a * mult;
        puts ("2 points");
        cout << ax << ' ' << ay << '\n' << bx << ' ' << by << '\n';
    }
}
}

```

25 Geometry 2D

```

// Circle Circle Intersection
// zz: pairs of points
zz circleLine(double r, double a, double b, double c){
    zz res = zz(ii(-1e9 - 1, -1e9 - 1), ii(-1e9 - 1, -1e9 - 1));
    double x0 = -a*c/(a*a+b*b), y0 = -b*c/(a*a+b*b);
    if (c*c > r*r*(a*a+b*b) + eps)
        return res;
    else if (abs (c*c - r*r*(a*a+b*b)) < eps) {
        res.first = ii(x0, y0);
        return res; }
    else {
        double d = r*r - c*c/(a*a+b*b);
        double mult = sqrt (d / (a*a+b*b));
        double ax, ay, bx, by;
        ax = x0 + b * mult; bx = x0 - b * mult;
        ay = y0 - a * mult; by = y0 + a * mult;
        res.first = ii(ax, ay); res.second = ii(bx, by);
        return res; } }

zz circleCircleIntersection(Circle c1, Circle c2) {
    zz res = zz(ii(-1e9 - 1, -1e9 - 1), ii(-1e9 - 1, -1e9 - 1));
    if (dist(ii(c1.x, c1.y), ii(c2.x, c2.y)) < eps) {
        if (abs(c1.r - c2.r) < eps)
            return res;
        return res; }
    double dx = c2.x - c1.x; double dy = c2.y - c1.y;
    double A = -2 * dx; double B = -2 * dy;
    double C = dx * dx + dy * dy + c1.r * c1.r - c2.r * c2.r;
    res = circleLine(c1.r, A, B, C);
    res.first = ii(res.first.first + c1.x, res.first.second + c1.y);
    res.second = ii(res.second.first + c1.x, res.second.second + c1.y);
    return res;
}

///// 2 segments intersection
bool onSegment(Point p, Point q, Point r) // q lies on (p, r)
int orientation(Point p, Point q, Point r){
    int val = (q.y - p.y) * (r.x - q.x) - (q.x - p.x) * (r.y - q.y);
    if (val == 0) return 0; // colinear
    return (val > 0)? 1: 2;}

bool doIntersect(Point p1, Point q1, Point p2, Point q2){
    int o1 = orientation(p1, q1, p2); int o2 = orientation(p1, q1, q2)
    ;
    int o3 = orientation(p2, q2, p1); int o4 = orientation(p2, q2, q1);
}

```

```

    if (o1 != o2 && o3 != o4) return true;
    if (o1 == 0 && onSegment(p1, p2, q1)) return true;
    if (o2 == 0 && onSegment(p1, q2, q1)) return true;
    if (o3 == 0 && onSegment(p2, p1, q2)) return true;
    if (o4 == 0 && onSegment(p2, q1, q2)) return true;
    return false;}
////

```

26 Geometry 3D

```

typedef double T;
struct p3 {
    T x,y,z;
    p3 operator+(p3 p) {return {x+p.x, y+p.y, z+p.z};}
    p3 operator-(p3 p) {return {x-p.x, y-p.y, z-p.z};}
    p3 operator*(T d) {return {x*d, y*d, z*d};}
    p3 operator/(T d) {return {x/d, y/d, z/d};} //only for floating-point
    bool operator==(p3 p) {return tie(x,y,z) == tie(p.x,p.y,p.z);}
    bool operator!=(p3 p) {return !operator==(p);}
    T operator|(p3 v, p3 w) {return v.x*w.x + v.y*w.y + v.z*w.z;} //dot
        product
    p3 operator*(p3 v, p3 w) { //cross product
        return {v.y*w.z - v.z*w.y, v.z*w.x - v.x*w.z, v.x*w.y - v.y*w.x};
    }
    T sq(p3 v) {return v|v;}
    double abs(p3 v) {return sqrt(sq(v));}
    p3 unit(p3 v) {return v/abs(v);}
    double angle(p3 v, p3 w) {
        double cosTheta = (v|w) / abs(v) / abs(w);
        return acos(max(-1.0, min(1.0, cosTheta)));}
    T orient(p3 p, p3 q, p3 r, p3 s) {return (q-p)*(r-p)|(s-p);} // S vs plane
        PQR
    struct plane {
        p3 n; T d; // From normal n and offset d
        plane(p3 n, T d) : n(n), d(d) {} // From normal n and point P
        plane(p3 n, p3 p) : n(n), d(n|p) {} // From three non-collinear points
            P,Q,R
        plane(p3 p, p3 q, p3 r) : plane((q-p)*(r-p), p) {}
        // - these work with T = int
        T side(p3 p) {return (n|p)-d;}
        double dist(p3 p) {return abs(side(p))/abs(n);}
        plane translate(p3 t) {return {n, d+(n|t)};}
        // - these require T = double

```

```

        plane shiftUp(double dist) {return {n, d + dist*abs(n)};}
        p3 proj(p3 p) {return p - n*side(p)/sq(n);}
        p3 refl(p3 p) {return p - n*2*side(p)/sq(n)};}
    struct line3d {
        p3 d, o;
        // From two points P, Q
        line3d(p3 p, p3 q) : d(q-p), o(p) {}
        // From two planes p1, p2 (requires T = double)
        line3d(plane p1, plane p2) {
            d = p1.n*p2.n;
            o = (p2.n*p1.d - p1.n*p2.d)*d/sq(d);
        }
        // - these work with T = int
        double sqDist(p3 p) {return sq(d*(p-o))/sq(d);}
        double dist(p3 p) {return sqrt(sqDist(p));}
        bool cmpProj(p3 p, p3 q) {return (d|p) < (d|q);}
        // - these require T = double
        p3 proj(p3 p) {return o + d*(d|(a-o))/sq(d);}
        p3 refl(p3 p) {return proj(p)*2 - p;}
        p3 inter(plane p) {return o - d*p.side(o)/(p.n|d)};}
    double dist(line l1, line l2) {
        p3 n = l1.d*l2.d;
        if (n == zero) return l1.dist(l2.o);
        return abs((l2.o-l1.o)|n)/abs(n);}
    p3 closestOnL1(line l1, line l2) {
        p3 n2 = l2.d*(l1.d*l2.d);
        return l1.o + l1.d*((l2.o-l1.o)|n2)/(l1.d|n2);}
    double smallAngle(p3 v, p3 w) {
        return acos(min(abs(v|w)/abs(v)/abs(w), 1.0));}
    double angle(plane p1, plane p2) {
        return smallAngle(p1.n, p2.n);}
    bool isParallel(plane p1, plane p2) {
        return p1.n*p2.n == zero;}
    bool isPerpendicular(plane p1, plane p2) {
        return (p1.n|p2.n) == 0;}
    double angle(line3d l1, line3d l2) {
        return smallAngle(l1.p, l2.d);}
    bool isParallel(line3d l1, line3d l2) {
        return l1.d*l2.d == zero;}
    bool isPerpendicular(line3d l1, line3d l2) {
        return (l1.d|l2.d) == 0;}
    double angle(plane p, line3d l) {
        return M_PI/2 - smallAngle(p.n, l.d);}
    bool isParallel(plane p, line3d l) {

```

```

    return (p.n|l.d) == 0;}
bool isPerpendicular(plane p, line3d l) {
    return p.n*l.d == zero;}
line3d perpThrough(plane p, p3 o) {return line(o, o+p.n);}
plane perpThrough(line3d l, p3 o) {return plane(l.d, o);}

```

27 FFT

```

const double PI = acos(-1.0);
typedef complex<double> Complex;
#define MASK(i) (1LL<<(i))
#define BIT(x,i) (((x) >> (i)) & 1)
#define LOG 17
Complex fftRoot[MASK(LOG)], invRoot[MASK(LOG)];
#define REP(i, n) for (int i = 0, _n = (n); i < _n; i = i + 1)
void initFFT(void) {
    REP(i, MASK(LOG)) {
        double alpha = 2 * PI / MASK(LOG) * i;
        fftRoot[i] = Complex(cos(alpha), sin(alpha));
        invRoot[i] = Complex(cos(-alpha), sin(-alpha));
    }
}
unsigned roundUp(unsigned v) {
    --v;
    REP(i, 5) v |= v >> MASK(i);
    return v + 1;
}
int reverse(int num, int lg) {
    int res = 0;
    REP(i, lg) if (BIT(num, i)) res |= MASK(lg - i - 1);
    return res;
}
vector<Complex> fft(vector<Complex> a, bool invert) {
    int n = a.size(), lg = 0;
    while (MASK(lg) < n) lg++;
    vector<Complex> roots(n);
    REP(i, n) roots[i] = invert ? invRoot[MASK(LOG) / n * i] :
        fftRoot[MASK(LOG) / n * i];

    REP(i, n) {
        int rev = reverse(i, lg);
        if (i < rev) swap(a[i], a[rev]);
    }
    for (int len = 2; len <= n; len <= 1)

```

```

        for (int i = 0; i < n; i += len)
            for (int j = 0; j < (len >> 1); j++) {
                Complex u = a[ i + j], v = a[ i + j + (len >> 1)] *
                    roots[n / len * j];

                a[ i + j] = u + v;
                a[ i + j + (len >> 1)] = u - v;
            }
    if (invert) REP(i, n) a[i] /= n;
    return a;
}
vector<long long> multiply(const vector<int> &a, const vector<int>
    &b) {
    int n = roundUp(size(a) + size(b) - 1);
    vector<Complex> pa (n), pb (n);
    for(int i = 0; i < size(a); ++i) pa[i] = a[i];
    for(int i = 0; i < size(b); ++i) pb[i] = b[i];
    pa = fft(pa, false);
    pb = fft(pb, false);
    for(int i = 0; i < n; ++i) pa[i] *= pb[i];
    pa = fft(pa, true);
    vector<long long> res (n);
    for(int i = 0; i < n; ++i) res[i] = round(real(pa[i]));
    return res;
}

```

28 NTT

```

const int MODULO = 998244353;
const int ROOT = 3; // Primitive root
void fft(vector<int> &a, bool invert) {
    int n = a.size();
    assert((n & (n - 1)) == 0);
    int lg = __builtin_ctz(n);
    for (int i = 0; i < n; ++i) {
        int j = 0;
        for (int k = 0; k < lg; ++k) if ((i&1<<k)!=0) j |= 1 <<
            (lg-k-1);
        if (i < j) swap(a[i], a[j]);
    }
    for (int len = 2; len <= n; len *= 2) {
        int wlen = power(ROOT, (MODULO - 1) / len);
        if (invert) wlen = inverse(wlen);
        for (int i = 0; i < n; i += len) {

```

```

    int w = 1;
    for (int j = 0; j < len / 2; ++j) {
        int u = a[i + j];
        int v = 1LL * a[i + j + len / 2] * w % MODULO;
        a[i + j] = (u + v) % MODULO;
        a[i + j + len / 2] = (u - v + MODULO) % MODULO;
        w = 1LL * w * wlen % MODULO;
    }
}

if (invert) {
    int mul = inverse(n);
    for (auto &x : a) x = 1LL * x * mul % MODULO;
}

998244353 = 119 * 223 + 1. Primitive root: 3.
985661441 = 235 * 222 + 1. Primitive root: 3.
1012924417 = 483 * 221 + 1. Primitive root: 5

```

29 Gauss

```

// INPUT:      a[][] = an n×n matrix
//             b[][] = an n×m matrix
// OUTPUT:     X      = an n×m matrix (stored in b[][])
//             A-1 = an n×n matrix (stored in a[][])
//             returns determinant of a[][]

const double EPS = 1e-10;
typedef vector<int> VI;
typedef double T;
typedef vector<T> VT;
typedef vector<VT> VVT;
T GaussJordan(VVT &a, VVT &b) {
    const int n = a.size();
    const int m = b[0].size();
    VI irow(n), icol(n), ipiv(n);
    T det = 1;
    for (int i = 0; i < n; i++) {
        int pj = -1, pk = -1;
        for (int j = 0; j < n; j++) if (!ipiv[j])
            for (int k = 0; k < n; k++) if (!ipiv[k])
                if (pj == -1 || fabs(a[j][k]) > fabs(a[pj][pk])) { pj = j;
                    pk = k; }
        if (fabs(a[pj][pk]) < EPS) { cerr << "Matrix is singular." << endl

```

```

        ; exit(0); }
        ipiv[pk]++;
        swap(a[pj], a[pk]);
        swap(b[pj], b[pk]);
        if (pj != pk) det *= -1;
        irow[i] = pj;
        icol[i] = pk;
        T c = 1.0 / a[pk][pk];
        det *= a[pk][pk];
        a[pk][pk] = 1.0;
        for (int p = 0; p < n; p++) a[pk][p] *= c;
        for (int p = 0; p < m; p++) b[pk][p] *= c;
        for (int p = 0; p < n; p++) if (p != pk) {
            c = a[p][pk];
            a[p][pk] = 0;
            for (int q = 0; q < n; q++) a[p][q] -= a[pk][q] * c;
            for (int q = 0; q < m; q++) b[p][q] -= b[pk][q] * c;
        }
    }
    for (int p = n-1; p >= 0; p--) if (irow[p] != icol[p]) {
        for (int k = 0; k < n; k++) swap(a[k][irow[p]], a[k][icol[p]]);
    }
    return det;
}

```

30 Simplex

```

struct LPSolver {
    static vector<ld> simplex(vector<vector<ld>> a) {
        int n = (int) a.size() - 1;
        int m = (int) a[0].size() - 1;
        vector<int> left(n + 1);
        vector<int> up(m + 1);
        iota(left.begin(), left.end(), m);
        iota(up.begin(), up.end(), 0);
        auto pivot = [&](int x, int y) {
            swap(left[x], up[y]);
            ld k = a[x][y];
            a[x][y] = 1;
            vector<int> pos;
            for (int j = 0; j <= m; j++) {
                a[x][j] /= k;
                if (fabs(a[x][j]) > EPS) pos.push_back(j);
            }

```

```

    }
    for (int i = 0; i <= n; i++) {
        if (fabs(a[i][y]) < EPS || i == x) continue;
        k = a[i][y];
        a[i][y] = 0;
        for (int j : pos) a[i][j] -= k * a[x][j];
    }
};
while (1) {
    int x = -1;
    for (int i = 1; i <= n; i++) {
        if (a[i][0] < -EPS && (x == -1 || a[i][0] < a[x][0])) {
            x = i;
        }
    }
    if (x == -1) break;
    int y = -1;
    for (int j = 1; j <= m; j++) {
        if (a[x][j] < -EPS && (y == -1 || a[x][j] < a[x][y])) {
            {
                y = j;
            }
        }
    }
    if (y == -1) return vector<ld>(); // infeasible
    pivot(x, y);
}
while (1) {
    int y = -1;
    for (int j = 1; j <= m; j++) {
        if (a[0][j] > EPS && (y == -1 || a[0][j] > a[0][y])) {
            y = j;
        }
    }
    if (y == -1) break;
    int x = -1;
    for (int i = 1; i <= n; i++) {
        if (a[i][y] > EPS && (x == -1 || a[i][0] / a[i][y] < a[x][0] / a[x][y])) {
            x = i;
        }
    }
    if (x == -1) return vector<ld>(); // unbounded
    pivot(x, y);
}

```

```

    vector<ld> ans(m + 1);
    for (int i = 1; i <= n; i++) {
        if (left[i] <= m) ans[left[i]] = a[i][0];
    }
    ans[0] = -a[0][0];
    return ans;
}
};

```

31 Primitive Root

```

int generator(int p) {
    vector<int> fact;
    int phi = p-1, n = phi;
    for (int i=2; i*i<=n; ++i) if (n % i == 0) {
        fact.push_back(i);
        while (n % i == 0) n /= i;
    }
    if (n > 1) fact.push_back(n);
    for (int res=2; res<=p; ++res) {
        bool ok = true;
        for (size_t i=0; i<fact.size() && ok; ++i)
            ok &= powmod(res, phi / fact[i], p) != 1;
        if (ok) return res;
    }
    return -1;
}

```

32 Range Prime Counting

```

// Primes up to 10^12 can be counted in ~1 second.
const int MAXN = 1000005; // MAXN is the maximum value of sqrt(N) + 2
bool prime[MAXN];
int prec[MAXN];
vector<int> P;
void init() {
    prime[2] = true;
    for (int i = 3; i < MAXN; i += 2) prime[i] = true;
    for (int i = 3; i*i < MAXN; i += 2) {
        if (prime[i]) {
            for (int j = i*i; j < MAXN; j += i*i) prime[j] = false;

```

```

    }
}
for(int i=1; i<MAXN; i++) {
    if (prime[i]) P.push_back(i);
    prec[i] = prec[i-1] + prime[i];
}
}

lint rec(lint N, int K) {
    if (N <= 1 || K < 0) return 0;
    if (N <= P[K]) return N-1;
    if (N < MAXN && 1ll * P[K]*P[K] > N) return N-1 - prec[N] +
        prec[P[K]];
    const int LIM = 250;
    static int memo[LIM*LIM][LIM];
    bool ok = N < LIM*LIM;
    if (ok && memo[N][K]) return memo[N][K];
    lint ret = N/P[K] - rec(N/P[K], K-1) + rec(N, K-1);
    if (ok) memo[N][K] = ret;
    return ret;
}

lint count_primes(lint N) { //less than or equal to
    if (N < MAXN) return prec[N];
    int K = prec[(int)sqrt(N) + 1];
    return N-1 - rec(N, K) + prec[P[K]];
}

```

33 Knight's shortest path

```

int KSP(int x,int y) {
    if (x < y) swap(x, y);
    if (x == 1 && y == 0) return 3;
    if (x == 2 && y == 2) return 4;
    int d = x - y;
    if (y > d) return 2*((y-d+2)/3)+d;
    return d-2*((d-y)/4);
}

```

34 Extended Euclid

Gia su ket qua la (x_0, y_0) , ho nghiem la $(x_0 + k * b / d, y_0 - k * a / d)$

Phuong trinh $ax + by = d$ co nghiem khi va chi khi d chia het cho $\gcd(a, b)$

```

)
a x + b y = gcd(a, b)
int extgcd(int a, int b, int &x, int &y) {
    int g = a; x = 1; y = 0;
    if (b != 0) g = extgcd(b, a % b, y, x), y -= (a / b) * x;
    return g;
}

```

35 Factorial Mod

```

int factmod (int n, int p) { // n!, excluding p^k of course
    int res = 1;
    while (n > 1) {
        res = (res * ((n/p) % 2 ? p-1 : 1)) % p;
        for (int i=2; i<=n%p; ++i)
            res = (res * i) % p;
        n /= p;
    }
    return res % p;
}

```

36 Sqrt Mod

```

// Jacobi Symbol (m/n), m,n >= 0 and n is odd
#define NEGPOW(e) ((e) % 2 ? -1 : 1)
int jacobi(int a, int m) {
    if (a == 0) return m == 1 ? 1 : 0;
    if (a % 2) return NEGPOW((a-1)*(m-1)/4)*jacobi(m%a, a);
    else return NEGPOW((m*m-1)/8)*jacobi(a/2, m);
}

int invMod(int a, int m) {
    int x, y;
    if (extgcd(a, m, x, y) == 1) return (x + m) % m;
    else return 0; // unsolvable
}

// No solution when:  $n(p-1)/2 = -1 \pmod p$ 
int sqrtMod(int n, int p) { //find x:  $x^2 = n \pmod p$  p is prime
    int S, Q, W, i, m = invMod(n, p);
    for (Q = p - 1, S = 0; Q % 2 == 0; Q /= 2, ++S);
    do { W = rand() % p; } while (W == 0 || jacobi(W, p) != -1);
    for (int R = powMod(n, (Q+1)/2, p), V = powMod(W, Q, p); ;) {

```

```

        int z = R * R * m % p;
        for (i = 0; i < S && z % p != 1; z *= z, ++i);
        if (i == 0) return R;
        R = (R * powMod(V, 1 << (S-i-1), p)) % p;
    }
}

int powMod (int a, int b, int p) {
    int res = 1;
    while (b)
        if (b & 1)
            res = int (res * 1ll * a % p), --b;
        else
            a = int (a * 1ll * a % p), b >>= 1;
    return res;
}

```

37 Interval line

```

class Line {
public:
    long long a, b;
    Line(int _a, int _b) {
        a = _a;
        b = _b;
    }

    Line() {
        a = 0;
        b = 0;
    }

    long long getY(int y) { return a * y + b; }
};

class Node {
public:
    Line line;
    Node *leftNode, *rightNode;

    Node(Line _line) {
        line = _line;
        leftNode = NULL;
        rightNode = NULL;
    }
}

```

```

Node() {
    leftNode = NULL;
    rightNode = NULL;
}

};

class IntervallLineTree {
private:
    int n;
    Node *root;

    void update(Node *node, int lo, int hi, Line &line) {
        int mid = (lo + hi) >> 1;
        if (line.getY(lo) <= line.getY(hi) && line.getY(hi) <= node->line.getY(hi))
            return;

        if (line.getY(lo) >= node->line.getY(lo) &&
            line.getY(hi) >= node->line.getY(hi)) {
            node->line = line;
            return;
        }

        if (node->leftNode == NULL) {
            node->leftNode = new Node();
        }

        if (node->rightNode == NULL) {
            node->rightNode = new Node();
        }

        if (line.getY(lo) <= node->line.getY(lo) &&
            line.getY(mid) <= node->line.getY(mid)) {
            update(node->rightNode, mid + 1, hi, line);
            return;
        }

        if (line.getY(lo) >= node->line.getY(lo) &&
            line.getY(mid) >= node->line.getY(mid)) {
            update(node->rightNode, mid + 1, hi, node->line);
            node->line = line;
            return;
        }
    }
}

```



```

    if (line.getY(mid+1) <= node->line.getY(mid+1) &&
        line.getY(hi) <= node->line.getY(hi)) {
        update(node->leftNode, lo, mid, line);
    }

    if (line.getY(mid + 1) >= node->line.getY(mid + 1) &&
        line.getY(hi) >= node->line.getY(hi)) {
        update(node->leftNode, lo, mid, node->line);
        node->line = line;
    }
}

long long get(Node *node, int lo, int hi, int pos) {
    if (lo > pos || hi < pos) return 0;
    long long res = node->line.getY(pos);
    if (lo == hi) return res;
    int mid = (lo + hi) >> 1;
    if (node->leftNode != NULL)
        res = max(res, get(node->leftNode, lo, mid, pos));
    if (node->rightNode != NULL) {
        res = max(res, get(node->rightNode, mid + 1, hi, pos));
    }
    return res;
}

public:
    IntervalLineTree(int _n) {
        n = _n;
        root = new Node();
    }

    void update(Line &line) { update(root, 1, n, line); }

    long long get(int pos) { return get(root, 1, n, pos); }
};

```

38 BIT 2D

```

class BIT2D {
public:
    vector<int> nodes[maxn];
    vector<int> f[maxn];

```

```

    void fakeUpdate(int u, int v) {
        for (int x = u; x <= n; x += x & -x)
            nodes[x].push_back(v);
    }

    void fakeGet(int u, int v) {
        for (int x = u; x > 0; x -= x & -x)
            nodes[x].push_back(v);
    }

    void update(int u, int v) {
        for (int x = u; x <= n; x += x & -x)
            for (int y = lower_bound(nodes[x].begin(), nodes[x].end(), v) -
                nodes[x].begin() + 1; y <= nodes[x].size();
                y += y & -y)
                f[x][y]++;
    }

    int get(int u, int v) {
        int res = 0;
        for (int x = u; x > 0; x -= x & -x)
            for (int y = upper_bound(nodes[x].begin(), nodes[x].end(), v) -
                nodes[x].begin(); y > 0; y -= y & -y)
                res += f[x][y];
        return res;
    }

    void prepare(vector<pair<int, int>> queries) {
        reverse(queries.begin(), queries.end());
        for (auto query : queries) {
            fakeUpdate(query.first, query.second);
        }
        reverse(queries.begin(), queries.end());
        for (int i = 1; i <= n; i++) {
            nodes[i].push_back(0);
            sort(nodes[i].begin(), nodes[i].end());
            f[i].resize(((int) nodes[i].size()) + 3);
        }
    }
} bit2D;

```

39 Heavy-Light Decomposition

```

chainHead [c] dinh dau cua chuoi c
chainInd [u] chuoi ma dinh u nam trong

void hld(int u) {

    //Neu chuoi hien tai chua co dinh dau dinh gan goc nhut thi dat u lam
    dinh dau cua no
    if (chainHead[nChain] == 0) chainHead[nChain] = u;

    //Gan chuoi hien tai cho u
    chainInd[u] = nChain;

    //Giai thich ben duoi
    posInBase[u] = ++nBase;

    // Bien luu dinh con dac biet
    int mxVtx = -1;

    // Tim dinh con dac biet trong so nhung dinh con cua u
    for (int i = 0; i < adj[u].size(); i++) {
        int v = adj[u][i];
        if (v != parent[u]) {
            if (mxVtx == -1 || nChild[v] > nChild[mxVtx]) {
                mxVtx = v;
            }
        }
    }

    //Neu tim ra dinh con dac biet (u khong phai la dinh la) thi di chuyen
    den dinh do
    if (mxVtx > -1)
        hld(mxVtx);

    // Sau khi di het mot chuoi thi tang nChain len va bat dau mot chuoi
    moi
    for (int i = 0; i < adj[u].size(); i++) {
        int v = adj[u][i];
        if (v != parent[u] && v != mxVtx) {
            nChain++;
            hld(v);
        }
    }
}
}

```

```

void update(int u, int a) {
    // uchain chuoi hien tai cua u
    // achain chuoi hien tai cua a
    int uchain = chainInd[u], achain = chainInd[a];

    while (1) {
        // Neu u va a cung nam tren mot chuoi thi update doan tu u den a
        va ket thuc
        if (uchain == achain) {
            updateIntervalTree(..., posInBase[a], posInBase[u], ...);
            break;
        }
        // Neu u va a khong nam tren cung mot chuoi thi update doan tu u
        den dinh dau cua chuoi hien tai
        updateIntervalTree(..., posInBase[chainHead[uchain]], posInBase[
            u], ...);

        // Nhay len dinh cha cua dinh dau hien tai
        u = parent[chainHead[uchain]];
        uchain = chainInd[u];
    }
}

/**
    Geometry - Tungluu18
    */

    Duong tron di qua 3 diem cho truoc Let A = (0, 0) centers are  $Cy(Bx^2 + By^2) - By(Cx^2 + Cy^2)/D$ 
    and  $(Bx(Cx^2 + Cy^2) - Cx(Bx^2 + By^2))/D$  where  $D = 2(BxCy - ByCx)$ .

    Diem trong tam giac
    bool isInside(const Vector &P) {
        Vector a = C - A, b = B - A, c = P - A;
        T under = a.x*b.y - b.x*a.y;
        T u = (c.x*b.y - c.y*b.x);
        T v = (a.x*c.y - a.y*c.x);
        return u >= 0 && v >= 0 && u+v <= under || u<=0
            && v<=0 && u+v >= under;
    } //remove equalities if not want the boundary

    Pick's theorem (So diem trong da giac co dinh nguyen)
    I = A - B/2 + 1

```

A is the area of a lattice polygon,
I is number of lattice points inside it,
B is number of lattice points on the boundary.
Number of lattice points minus one on a line segment
from (0, 0) and (x, y) is gcd(x, y).

Distance from line AB to P (for any dimension) : $| (A - P)x(B - P) | / (A - B)$

Hình chiếu: Hình chiếu của C trên đường thẳng AB [$\text{dot}(\text{AB}, \text{AC}) / \text{dot}(\text{AB}, \text{AB})$]

$$C_n = \frac{1}{n+1} * \binom{2n}{n} = \frac{(2n)!}{(n+1)!(n!)} = \frac{n+k}{k} (k=2- > n)$$

Prime: 999999999999999989(18) – 999999937(9)