

Week 6 - HMI Research Group

10 Jul 2017 - 14 Jul 2017

Long Phi Nguyen (넌피롱), 한국전자통신연구원

July 13, 2017

Summary

The previous plan for generating new motions has been ruled out—the method of data collection and analysis was very brute-force-based, inaccurate, and did not take sequential data into account. As such, NAO fell down almost 100% of the time when trying to generate new gestures aside from the **BodyTalk** category. Time series analysis is in progress.

Points

- `README.md` has been created on Github repository for documentation purposes.
- Reparsed NAO's sensor data to collect sensor data chronologically as he moves while performing **BodyTalk** gestures.
- Wrote a function that calculates and plots the time series data for each of the **BodyTalk** gestures.
- Noticed some general trends between certain groups of joints related to the **BodyTalk** category, such as joint symmetry during interpolation, etc.
- Read through the USC paper regarding low-dimensional manifolds.

Plans

- Come up with a preliminary method to work with the time series data and generate better gestures from it.
- Link data from gestures in a way that doesn't rely on brute-forcing them by skewed frequency (be smart about analysis).
- Set constraints on generated gestures so that transitions between successive gestures are smooth, not abrupt as they currently are.
- Refactor code for ease of understanding.

Addendum

The repository can be found [here](#) with its updated `README.md`. Time series plots for gestures from the **BodyTalk** category can be found [here](#).