




# Unit 5

## Scanner

# Task of a scanner

## ■ Delivers tokens



## ■ Skip meaningless characters

- ☐ blanks
- ☐ Tabulator characters
- ☐ End-of-line characters (CR,LF)
- ☐ Comments



# Tokens have a syntactic structure

```
ident =    letter {letter | digit}.  
number =  digit {digit}.  
if =      "i" "f".  
eq =      "=" "=".  
...
```

- Why is scanning not a part of parsing?



# Why is scanning not a part of parsing?


- It would make parsing more complicated, e.g.
  - Difficult distinction between identifiers and keywords
  - The scanner must have complicated rules for eliminating blanks, tabs, comments, etc.
  - => would lead to very complicated grammars



# Token classes of KPL

- Unsigned integer
- Identifier
- Key word: begin,end, if,then, while, do, call, const, var, procedure, program,type, function,of,integer,char,else,for, to,array
- Character constant
- Operators:
  - Arithmetic  
+ - \*/
  - Relational  
= != < > <= >=
  - Assign :=
- Separators  
( ) . : ; ( . .)

# The scanner as Finite Automaton



After every recognized token, the scanner starts in state 0 again

If an illegal character is met, the scanner would change to the states 30 or 38 which tell the scanner to stop scanning and return error messages.

Notice the yellow states



# Scanner implementation based on DFA

```
state = 0;
currentChar = getCurrentChar;
token = getToken();
while ( token!=EOF)
{
    state =0;
    token = getToken();
}
```



# Token recognizer

```
switch (state)
{
case 0 : currentChar =
    getCurrentChar();
    switch (currentChar)
    {
        case space
            state = 1;
        case lpar
            state = 2;
        case letter
            state = 8;
        case digit
            state = 10;
        case plus
            state = 12;
        .....
    }
}
```



# Token recognizer (cont'd)

case 1:

```
while (current Char== space) // skip blanks
    currentChar = getCurrentChar();
```

```
state =0;
```

case 2:

```
currentChar = getCurrentChar();
```

```
switch (currentChar)
```

```
{
```

```
case period
```

```
    state = 6; // token lsel
```


```
case times
```

```
    state =3; //skip comment
```

```
else
```

```
    state =7; // token lpar
```

```
}
```



# Token recognizer (cont'd)


case 3: // skip comment

```
currentChar = getCurrentChar();  
while (currentChar != times)  
{  
    state = 3;  
    currentChar = getCurrentChar();  
}  
state = 4;
```

case 4:

```
currentChar = getCurrentChar();  
while (currentChar == times)  
{  
    state = 4;  
    currentChar = getCurrentChar();  
}
```

If (currentChar == lpar) state = 5; else state = 3;





# Token recognizer (cont'd)

case 9:

```
if (checkKeyword (token) == TK_NONE)
```

```
install_ident();// save to symbol table
```

```
else
```

```
return checkKeyword(token);
```

```
.....
```



# Initialize a symbol table

- The following information about identifiers is saved
  - ☐ Name:string
  - ☐ Attribute : type name, variable name, constant name.
  - ☐ ..
  - ☐ Data type
  - ☐ Scope
  - ☐ Address and size of the memory where the lexeme is located
  - ☐ . . .



# Distinction between identifiers and keywords

- Variable `ch` is assigned with the first character of the lexeme.
- Read all digits and letters into string `t`
- Use binary search algorithm to find if there is an entry for that string in table of keyword
- If found `t.kind = order of the keyword`
- Otherwise, `t.kind = ident`
- At last, variable `ch` contains the first character of the next lexeme



# Data structure for tokens

```
enum {  
    TK_NONE, TK_IDENT, TK_NUMBER, TK_CHAR, TK_EOF,  
  
    KW_PROGRAM, KW_CONST, KW_TYPE, KW_VAR,  
    KW_INTEGER, KW_CHAR, KW_ARRAY, KW_OF,  
    KW_FUNCTION, KW_PROCEDURE,  
    KW_BEGIN, KW_END, KW_CALL,  
    KW_IF, KW_THEN, KW_ELSE,  
    KW_WHILE, KW_DO, KW_FOR, KW_TO,  
  
    SB_SEMICOLON, SB_COLON, SB_PERIOD, SB_COMMA,  
    SB_ASSIGN, SB_EQ, SB_NEQ, SB_LT, SB_LE, SB_GT, SB_GE,  
    SB_PLUS, SB_MINUS, SB_TIMES, SB_SLASH,  
    SB_LPAR, SB_RPAR, SB_LSEL, SB_RSEL  
};
```