How PreAutheri Annotaion work

1-Put the annotation in the configuration

Gemini Code Assist: Use Alt+F to finish changes to this file

```java
import org.springframework.context.annotation.Configuration;
import org.springframework.http.HttpMethod;
import org.springframework.security.config.annotation.method.configuration.EnableMethodSecurity;
import org.springframework.security.config.annotation.web.builders.HttpSecurity;
import org.springframework.security.config.annotation.web.configuration.EnableWebSecurity;
import org.springframework.security.oauth2.server.resource.authentication.JwtAuthenticationConverter;
import org.springframework.security.web.SecurityFilterChain;

import java.util.Collection;
import java.util.Collections;
import java.util.HashSet;


@EnableMethodSecurity(prePostEnabled = true)
@Configuration
@EnableWebSecurity
// Use to enable spring security
public class WebSecurity{

    @Bean
    SecurityFilterChain configure(HttpSecurity http) throws Exception{

        JwtAuthenticationConverter jwtAuthenticationConverter = new JwtAuthenticationConverter();
        jwtAuthenticationConverter.setJwtGrantedAuthoritiesConverter(new KeyCloakConverter());

        // Create object with filter chain
        http.authorizeHttpRequests(authz ->
                        authz
                                .requestMatchers(HttpMethod.GET, "/users/status/check")
//                                .hasAuthority("SCOPE_profile")
                                .hasRole("developer")
//                                .hasAnyRole("USER","ADMIN")
                                .anyRequest().authenticated())
                .oauth2ResourceServer(oauth2 ->
                        oauth2.jwt(jwt ->
                                jwt.jwtAuthenticationConverter(jwtAuthenticationConverter)));
        return http.build();
```

@EnableMethodSecurity(prePostEnabled = true)

2-In the controller
@PreAuthorize("hasRole('developer')")

```
controllers
    TokenController
    UsersController
security
    KeyCloakConverter
    WebSecurity
ResourceServerApplication
resources
t
ributes
ore
.cmd
ml
Libraries
s and Consoles
```

```
12
13      @GetMapping("/status/check")
14      public String status(){
15          log.info("Request From scope profile");
16          return "Working...";
17      }
18
19      @PreAuthorize("hasRole('developer')")
20  //    @Secured("ROLE_developer")
21      @DeleteMapping(path="/{id}")  Alt+F Finish changes to file | Escape Dismiss
22      public String deletedUser(@PathVariable String id){
23          return "Deleted user with id: " + id;
24      }
25  }
26
27
```

Or we can put

@PreAuthorize("hasAuthority('ROLE_developer')")

```
17      }
18
19      @PreAuthorize("hasAuthority('ROLE_developer')")
20  //    @PreAuthorize("hasRole('developer')")
21  //    @Secured("ROLE_developer")
22      @DeleteMapping(path="/{id}")  Alt+F Finish changes to file | Escape Dismiss
23      public String deletedUser(@PathVariable String id){
24          return "Deleted user with id: " + id;
25      }
26  }
27
28
```