

Create Multiple Service

1- Create Service

>> ng g s services/helloService

>> ng g s services/customerService

```
hello-service.service.ts U X
src > app > services > hello-service.service.ts > HelloServiceService
1  import { Injectable } from '@angular/core';
2  import { HttpClient } from '@angular/common/http';
3
4  @Injectable({
5    providedIn: 'root'
6  })
7  export class HelloServiceService {
8
9    constructor(private _httpClient: HttpClient) { }
10
11    public helloService():any{
12      return this._httpClient.get("http://localhost:8080/api/uppercase/hello",{
13        responseType: 'text'
14      });
15    }
16
17
18    public helloService1():any{
19      return this._httpClient.get("http://localhost:8080/api/uppercase/hello1");
20    }
21
22  }
23
```

```
customer-service.service.ts U X
src > app > services > customer-service.service.ts > ...
1  import { Injectable } from '@angular/core';
2  import { HttpClient } from '@angular/common/http';
3
4  @Injectable({
5    providedIn: 'root'
6  })
7  export class CustomerServiceService {
8
9    constructor(private _httpClient: HttpClient) { }
10
11    public getAllCountry():any{
12      return this._httpClient.get("http://localhost:8080/api/countries");
13    }
14
15  }
16
```

```
import { Injectable } from '@angular/core';
import { HttpClient } from '@angular/common/http';
```

```
@Injectable({
  providedIn: 'root'
})
export class HelloServiceService {

  constructor(private _httpClient: HttpClient) { }

  public helloService():any {
    return this._httpClient.get("http://localhost:8080/api/uppercase/hello",{
      responseType: 'text'
    });
  }

  public helloService1():any {
    return this._httpClient.get("http://localhost:8080/api/uppercase/hello1");
  }

}
```

```
import { Component, OnInit } from '@angular/core';
import { CustomerServiceService } from 'src/app/services/customer-service.service';
import { HelloServiceService } from 'src/app/services/hello-service.service';
```

```
@Component({
  selector: 'app-multiple-services',
  templateUrl: './multiple-services.component.html',
  styleUrls: ['./multiple-services.component.css']
})
export class MultipleServicesComponent implements OnInit {

  public helloResponse:any;
  public helloResponse1:any;
  public countryResponse:any;
  public testshow:any = "Hello You";

  constructor(private _helloService: HelloServiceService, private _customerService: CustomerServiceService) { }

  ngOnInit(): void {
    this._helloService.helloService().subscribe((res:any)=>this.helloResponse=res);
    this._helloService.helloService1().subscribe((res:any)=>this.helloResponse1=res);
    this._customerService.getAllCountry().subscribe((res:any)=>this.countryResponse=res);
  }

}
```

2. Create component

>> ng g c components/multipleServices

```
multiple-services.component.ts U X
src > app > components > multiple-services > multiple-services.component.ts > MultipleServicesComponent > helloResponse
1  import { Component, OnInit } from '@angular/core';
2  import { CustomerServiceService } from 'src/app/services/customer-service.service';
3  import { HelloServiceService } from 'src/app/services/hello-service.service';
4
5  @Component({
6    selector: 'app-multiple-services',
7    templateUrl: './multiple-services.component.html',
8    styleUrls: ['./multiple-services.component.css']
9  })
10 export class MultipleServicesComponent implements OnInit {
11
12    public helloResponse:any;
13    public helloResponse1:any;
14    public countryResponse:any;
15    public testshow:any = "Hello You";
16
17    constructor(private _helloService: HelloServiceService, private _customerService: CustomerServiceService) { }
18
19    ngOnInit(): void {
20        this._helloService.helloService().subscribe((res:any)=>this.helloResponse=res);
21        this._helloService.helloService1().subscribe((res:any)=>this.helloResponse1=res);
22        this._customerService.getAllCountry().subscribe((res:any)=>this.countryResponse=res);
23    }
24
25 }
```

```
import { Component, OnInit } from '@angular/core';
import { CustomerServiceService } from 'src/app/services/customer-service.service';
import { HelloServiceService } from 'src/app/services/hello-service.service';
```

```
@Component({
  selector: 'app-multiple-services',
  templateUrl: './multiple-services.component.html',
  styleUrls: ['./multiple-services.component.css']
})
export class MultipleServicesComponent implements OnInit {
```

```
  public helloResponse:any;
  public helloResponse1:any;
  public countryResponse:any;
  public testshow:any = "Hello You";
```

```
  constructor(private _helloService: HelloServiceService, private _customerService:
CustomerServiceService) { }
```

```
  ngOnInit(): void {
    this._helloService.helloService().subscribe((res:any)=>this.helloResponse=res);
    this._helloService.helloService1().subscribe((res:any)=>this.helloResponse1=res);
    this._customerService.getAllCountry().subscribe((res:any)=>this.countryResponse=res);
  }
}
```

2-Html

```
multiple-services.component.html U X
src > app > components > multiple-services > multiple-services.component.html > h1
1 <h1>Hello Response Text</h1>
2 <h2 style="color: rgb(255, 0, 55);">{{helloResponse}}</h2>
3
4 <h1>Hello Response Json</h1>
5 <h2 style="color: blue;">{{helloResponse1 | json}}</h2>
6
7 <h1>Country Response</h1>
8 <h2 style="color: green;">{{countryResponse | json}}</h2>>
9
10 <h1>{{testshow}}</h1>
```

<h1>Hello Response Text</h1>

<h2 style="color: rgb(255, 0, 55);">{{helloResponse}}</h2>

<h1>Hello Response Json</h1>

<h2 style="color: blue;">{{helloResponse1 | json}}</h2>

<h1>Country Response</h1>

<h2 style="color: green;">{{countryResponse | json}}</h2>>

<h1>{{testshow}}</h1>

3- App.module.ts

- First : add provider : កន្លែង ដែលយើងដាក់ service (providers: [HelloServiceService, CustomerServiceService])
- import { HttpClientModule } from '@angular/common/http' : យើងត្រូវធ្វើការ import HttpClientModule ដើម្បីប្រើប្រាស់ httpClient
- bootstrap: [MultipleServicesComponent] : កន្លែង starter app

```
app.module.ts M X
src > app > app.module.ts > AppModule
1  import { NgModule } from '@angular/core';
2  import { BrowserModule } from '@angular/platform-browser';
3
4  import { AppComponent } from './app.component';
5  import { MultipleServicesComponent } from './components/multiple-services/multiple-services.component';
6  import { HelloServiceService } from './services/hello-service.service';
7  import { CustomerServiceService } from './services/customer-service.service';
8  import { HttpClientModule } from '@angular/common/http';
9
10 @NgModule({
11   declarations: [
12     AppComponent,
13     MultipleServicesComponent
14   ],
15   imports: [
16     BrowserModule,
17     HttpClientModule
18   ],
19   providers: [HelloServiceService, CustomerServiceService],
20
21   ],
22   bootstrap: [MultipleServicesComponent]
23 })
24 export class AppModule { }
```

4- index.html

```
module.ts M index.html M X
index.html > ...
<!doctype html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title>CleanServiceApp</title>
  <base href="/">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <link rel="icon" type="image/x-icon" href="favicon.ico">
</head>
<body>
  <!-- <app-root></app-root> -->
  <app-multiple-services></app-multiple-services>
</body>
</body>
</html>
```

យើងត្រូវដាក់ <app-multiple-services></app-multiple-services>

Improving

ដោយសារតែនៅក្នុង life cycle : ngOnInit(): void {} វាធ្វើការ ហៅ service ម្តងមួយមកប្រើចឹង ធ្វើអោយ service នឹងមាន delay យើងអាចធ្វើការ Improve វាបានដោយ ប្រើ forkJoin

```
multiple-services.component.ts U X
src > app > components > multiple-services > multiple-services.component.ts > MultipleServicesComponent
1 import { Component, OnInit } from '@angular/core';
2 import { CustomerServiceService } from 'src/app/services/customer-service.service';
3 import { HelloServiceService } from 'src/app/services/hello-service.service';
4 import { forkJoin } from 'rxjs';
5
6 @Component({
7   selector: 'app-multiple-services',
8   templateUrl: './multiple-services.component.html',
9   styleUrls: ['./multiple-services.component.css']
10 })
11 export class MultipleServicesComponent implements OnInit {
12
13   public helloResponse:any;
14   public countryResponse:any;
15
16   constructor(private _helloService: HelloServiceService, private _customerService: CustomerServiceService) { }
17
18   ngOnInit(): void {
19     forkJoin([this._helloService.helloService(), this._customerService.getAllCountry()])
20       .subscribe(responses => {
21         this.helloResponse = responses[0];
22         this.countryResponse = responses[1];
23       });
24   }
25 }
```

```
ngOnInit(): void {
  forkJoin([this._helloService.helloService(), this._customerService.getAllCountry()])
    .subscribe(responses => {
      this.helloResponse = responses[0];
      this.countryResponse = responses[1];
    });
}
```

Error Angular Version in VS code:

The screenshot shows the Visual Studio Code interface with the Angular Language Service extension details. The extension is 'angular.ng-template' with version 11.1.2. A red circle highlights the version information in the 'Installation' section. A red number '1' is placed over the 'Update to v22.0.0' button.

Identifier	Version	Last Updated	Size
angular.ng-template	11.1.2	2 hours ago	62.11MB

```
src > app > app.module.ts > AppModule
1 import { NgModule } from '@angular/core';
2 import { BrowserModule } from '@angular/platform-browser';
3
4 import { AppComponent } from './app.component';
5 import { MultipleServicesComponent } from './components/multiple-services/multiple-services.component';
6 import { HelloServiceService } from './services/hello-service.service';
7 import { CustomerServiceService } from './services/customer-service.service';
8 import { HttpClientModule } from '@angular/common/http';
9
10 @NgModule({
11   declarations: [
12     AppComponent,
13     MultipleServicesComponent
14   ],
15   imports: [
16     BrowserModule,
17     HttpClientModule
18   ],
19   providers: [HelloServiceService, CustomerServiceService],
20   bootstrap: [MultipleServicesComponent]
21 },
22 {
23 })
24 export class AppModule { }
```

កំនែងដែលវា Error